IgGM: A Generative Model for Functional Antibody and Nanobody Design

Rubo Wang[1, 2, 3]*, **Fandi Wu**[3]*, **Xingyu Gao**[1]†, **Jiaxiang Wu**[3], **Peilin Zhao**[3], **Jianhua Yao**[3]†

[1]Institute of Microelectronics of the Chinese Academy of Sciences, Beijing, China
[2]University of Chinese Academy of Sciences, Beijing, China
[3]Tencent AI Lab, Shenzhen, China

wangrubo@hotmail.com, {fandiwu, masonzhao, jianhuayao}@tencent.com, xingyugao@ime.ac.cn

Abstract

Immunoglobulins are crucial proteins produced by the immune system to identify and bind to foreign substances, playing an essential role in shielding organisms from infections and diseases. Designing specific antibodies opens new pathways for disease treatment. With the rise of deep learning, AI-driven drug design has become possible, leading to several methods for antibody design. However, many of these approaches require additional conditions that differ from real-world scenarios, making it challenging to incorporate them into existing antibody design processes. Here, we introduce IgGM, generative model that combines a diffusion model and the consistency model for generating antibodies with functional specificity. IgGM produces antibody sequences and structures simultaneously for a given antigen, consisting of three core components: a pre-trained language model for extracting sequence features, a feature learning module for identifying pertinent features, and a prediction module that outputs designed antibody sequences and the predicted complete antibody-antigen complex structure. IgGM has shown effectiveness in both predicting structures and designing novel antibodies and nanobodies, making it relevant in various practical scenarios of antibody and nanobody design. [3]

1 Introduction

Antibodies, also known as immunoglobulins (Ig), are Y-shaped proteins secreted by B lymphocytes, primarily found in blood and lymphatic fluid [Silverthorn, 2015, Akkaya et al., 2020]. They consist of two heavy chains and two light chains, each containing a variable region (VR) and a framework region (FR). The variable regions include three complementarity-determining regions (CDRs), which are crucial for antigen binding and determine the antibody's specificity. The FR provides structural support for the VR and exhibits relatively low variability. Antibodies play a critical role in the immune system by recognizing and binding to specific foreign substances such as bacteria, viruses, fungi, and parasites, tagging them for clearance [Schroeder Jr and Cavacini, 2010, Litman et al., 1993]. Their importance extends to medicine, scientific research, and biotechnology, where they are used in disease treatment, personalized medicine, vaccine development, diagnostics, and new drug development [Nelson et al., 2010, Weiner, 2015, Sliwkowski and Mellman, 2013].

Despite their significance, traditional methods for antibody production face challenges such as long production cycles [Georgiou et al., 2014], batch-to-batch variations [Bradbury et al., 2018], and the need for humanization [Safdari et al., 2013] to reduce immunogenicity. These challenges limit the

---

*Equal contribution.

†Corresponding author.

[3]Code is available at: `https://github.com/TencentAI4S/IgGM`

Figure 1: The existing methods for antibody design differ from actual design scenarios. The solid box represents the conditions required for the design process of existing methods, which necessitate known sequences and known structures or template structures of antibody constructed from datasets as inputs. The the dotted line indicate the de novo antibody design process, where specific framework region sequences are utilized to design the final antibody targeting a known antigen.

widespread application and therapeutic efficacy of antibodies. To address these issues, researchers have turned to artificial intelligence for antibody design. Early approaches, such as energy-based computational methods [Li et al., 2014, Adolf-Bryfogle et al., 2018], were limited by the expressive capability of statistical energy functions. Language models trained on sequences [Liu et al., 2020, Saka et al., 2021, Akbar et al., 2022, Shin et al., 2021, Jing et al., 2020, Cao et al., 2021] also showed suboptimal performance due to a lack of structural knowledge. Recently, co-design methods that simultaneously design protein sequences and structures [Anishchenko et al., 2021, Wang et al., 2022, Anand and Achim, 2022, Shi et al., 2023] have demonstrated the feasibility of using AI for antibody design [Jin et al., 2021, 2022, Luo et al., 2022, Kong et al., 2023a,b]. Many current methods rely on known experimental structures of antibody-antigen complexes and the modification of existing antibodies. These structures and antibodies, however, are not always available for designing novel antibodies targeting a specific antigen. As shown in Figure 1, most approaches depend on actual framework region structures or templates derived from datasets. Unfortunately, such information is often missing when targeting a new antigen.

To overcome these limitations, we proposed IgGM, a deep learning method that performs simultaneous co-design of antibody sequence and structure using a diffusion model. IgGM employs a multi-level network architecture. It first utilizes a pre-trained protein language model to extract evolutionary features of sequences. Then, a feature learning module studies the interactions between antigens and antibodies. Finally, a prediction module outputs the structures and sequences of the antibodies. IgGM leverages the interplay between sequence and structure to generate accurate antibody designs, even when only partial sequences of the framework region are available. This capability aligns with practical application scenarios, offering new possibilities for antibody design. IgGM excels at generating the CDR regions and their structures and can dock the generated structure to the corresponding epitope. It supports multiple design scenarios and can adapt to various conditions without the need for retraining, such as predicting antigen-antibody complexes, designing the CDR H3 region of antibodies, and designing multiple CDR regions. Furthermore, it can be extended to nanobodies, which are small, single-domain antibodies that exhibit strong binding affinity to antigens and high stability [Cai et al., 2020]. Experimental results indicate that IgGM achieves superior performance across multiple design tasks, demonstrating accuracy in structure prediction tasks that is comparable to existing structure prediction methods.

2 Related Work

Protein design. Protein design aims to create new protein molecules with multiple functions [Dahiyat and Mayo, 1997]. Traditional methods utilize energy functions, such as molecular dynamics simulations, for protein design; however, these energy function-based approaches are time-consuming and not suitable for practical protein design. In recent years, various machine learning methods have

been applied to protein design, focusing on either sequences [Madani et al., 2023, Ferruz et al., 2022, Munsamy et al., 2022, Alamdari et al., 2023] or structures [Watson et al., 2023, Ingraham et al., 2023, Lutz et al., 2023]. ProGEN [Madani et al., 2023] uses Transformer [Vaswani et al., 2017] for protein sequence design. ProtGPT2 [Ferruz et al., 2022] deploys a GPT model [Radford et al., 2018] to generate protein sequences. Evodiff [Alamdari et al., 2023] implements protein sequence design through an autoregressive diffusion model. Lutz et al. [2023] utilizes reinforcement learning to design the structure of proteins. RFDiffusion [Watson et al., 2023] uses a diffusion model to generate the structure of proteins and then obtains the corresponding sequences through ProteinMPNN [Dauparas et al., 2022]. AlphaProteo [Zambaldi et al., 2024] employs a generator to design high-affinity binders, achieving a high success rate. We focus on the design of antibodies, which are important proteins for disease treatment.

Antibody design. Early antibody design methods relied on Monte Carlo iterations to update and generate antibody sequences and structures through handcrafted functions [Pantazes and Maranas, 2010, Lapidoth et al., 2015, Adolf-Bryfogle et al., 2018, Warszawski et al., 2019, Ruffolo et al., 2021]. However, this approach is resource-intensive and typically produces antibodies that conform strictly to the energy function, heavily relying on the design of the energy function itself. Sequence models [Alley et al., 2019, Saka et al., 2021, Shin et al., 2021, Akbar et al., 2022] were widely used in the early stages of deep learning for antibody design. RefineGNN [Jin et al., 2022] was the first to propose the co-design of antibody CDRs and structures, utilizing an autoregressive approach to generate the CDR regions of antibodies. DiffAb [Luo et al., 2022] employs diffusion models to design the sequences and structures of CDR regions for specific antigens. MEAN [Kong et al., 2023a] utilizes graph neural networks to iteratively generate the sequences and structures of antibody CDR regions. dyMEAN [Kong et al., 2023b] further expands the capabilities of MEAN, enabling end-to-end antibody design. However, these methods are limited to the design of CDR regions, specifically the CDR H3 region, while the other regions of the antibody must be predefined, rendering them unsuitable for practical antibody design.

Generative models. Generative models are becoming increasingly popular in the field of biomolecular generation [You et al., 2018, Liu et al., 2018], particularly due to the high quality of samples produced by diffusion models [Song and Ermon, 2019, Ho et al., 2020, Leach et al., 2022, Austin et al., 2021]. Consequently, a growing number of studies have introduced diffusion models into biomolecular generation. Many works have successfully utilized diffusion models to design multi-functional proteins [Wu et al., 2022, Trippe et al., 2022, Gao et al., 2023]. To address the limitations of inference steps in diffusion models, Song et al. [2023] proposed the consistency model. This model can map any point back to the initial point at a given time step while maintaining high quality. Several studies [Luo et al., 2023, Sauer et al., 2023, Xiao et al., 2023, Wang et al., 2023] have demonstrated the effectiveness of the consistency model. In this work, we utilize the consistency model to accelerate sampling.

3 Methods

3.1 Preliminaries

Proteins are composed of 20 different amino acids. For a given protein of length N, the protein sequence can be represented as $\mathcal{S} = \{s_i\}_{i=1}^{N}$, where each s_i denotes a residue. The three-dimensional structure of the protein can be represented by the three-dimensional coordinates of the backbone atoms, denoted as $\mathcal{X} = \{\boldsymbol{x}_{i,\omega}\}_{i=1}^{N}$, where each $\boldsymbol{x}_{i,\omega} \in \mathbb{R}^3$ and $\omega \in \{C\alpha, N, C, O\}$. Antibodies are specialized proteins that consist of two distinct chains, while nanobodies contain only a single heavy chain. Each chain comprises a constant region and a variable region, with the variable region referred to as the complementarity-determining region (CDR). The CDR regions of each chain can be further divided into three segments: CDR H1, CDR H2, and CDR H3 for the heavy chain, and CDR L1, CDR L2, and CDR L3 for the light chain. An antigen-antibody complex can be represented as

$$\mathcal{H} : \mathcal{L} - \mathcal{A} = \{(\mathcal{S}_i, \boldsymbol{x}_{i,\omega}) | i \in \{0, ..., l_{\mathcal{H}}, ..., l_{\mathcal{H}} + l_{\mathcal{L}}, ..., l_{\mathcal{H}} + l_{\mathcal{L}} + l_{\mathcal{A}}\}\}, \quad (1)$$

where l represents the length of the amino acid sequence for each chain. In the case of a nanobody-antigen complex, the light chain is not included.

Previous studies have defined the antibody design problem as selecting a framework region [Shin et al., 2021, Akbar et al., 2022] to design the CDRs to create antibodies that can bind to specific antigens. Since the influence of the framework region on the antigen-antibody interaction is relatively

Figure 2: Diffusion Model Process for Co-Design of Antibody Sequences and Structures: The figure illustrates an example trajectory in the design of antibodies, incorporating specific antigen and antibody framework region sequences. It depicts the input data (s_T, x_T) to the model, along with the corresponding predicted outcomes (s_0, x_0). Utilizing consistency models, the diffusion model is capable of generating antibody sequences and structures across diverse noise levels, demonstrating the gradual refinement from noisy inputs to a well-defined antibody structure.

minor, earlier research has primarily focused on designing the CDRs, often assuming that the structure of the framework region is fixed and unchanging. However, when faced with a completely new antigen, the structure of the resulting antibody, including the framework region, is unknown and cannot be predetermined.

3.2 Problem formulation

In practical antibody design, existing work has utilized the sequences of known framework regions to guide antibody design [Bennett et al., 2024]. However, in the absence of the complementarity-determining region (CDR), the structure of the antibody is not fixed. Therefore, we investigate the problem in real-world application scenarios, specifically designing antibody structures and sequences that can bind to specific locations (epitopes) on the antigen, given the framework region. We separate the residues of CDRs and the framework regions for easier identification. The set of residues contained in the CDRs and framework regions is given by:

$$\mathcal{R}_C := \left\{(\mathcal{S}_C, \mathcal{X}_{C,\omega}) | (\mathcal{S}_C, \mathcal{X}_{C,\omega}) \in \{\mathcal{S}_{\text{CDRs}}, \mathcal{X}_{\text{CDRs}}\}\right\}, \tag{2}$$

The set of residues representing the framework regions is denoted as

$$\mathcal{R}_F := \left\{(\mathcal{S}_F, \mathcal{X}_{F,\omega}) | (\mathcal{S}_F, \mathcal{X}_{F,\omega}) \in \{\mathcal{S}_{\text{FRs}}, \mathcal{X}_{\text{FRs}}\}\right\}. \tag{3}$$

The entire design problem can be simplified to the task of designing the sequences of CDRs s_C and the overall structure $(\mathcal{X}_{C,\omega}, \mathcal{X}_{F,\omega})$ of the antibody, given the sequence and structure of the antigen $\mathcal{R}_A(\mathcal{S}_A, \mathcal{X}_{A,\omega})$ as well as the sequences of the antibody's framework regions $\mathcal{S}_F$.

3.3 Diffusion models and consistency models

Diffusion models [Sohl-Dickstein et al., 2015, Song and Ermon, 2019, Ho et al., 2020] are a type of generative model that have been successfully applied in various fields, including image generation [Dhariwal and Nichol, 2021, Nichol and Dhariwal, 2021, Rombach et al., 2022], protein design [Anand and Achim, 2022, Trippe et al., 2023, Komorowska et al., 2024], among others. Diffusion models gradually add noise to the data through a forward process until it becomes random noise, and then learn a reversible backward process to progressively recover the original data from the noise. More detail can be found in Appendix A.

Consistency Models (CMs) [Song et al., 2023, Song and Dhariwal, 2024] leverage the PF-ODE framework to create a direct relationship between data and noise distributions. The primary objective of CMs is to develop a consistency function $f(\mathbf{x}_t, t)$ that effectively transforms a noisy image $\mathbf{x}_t$

Figure 3: IgGM Model Framework Diagram: Before being input into the model, the antibody sequence and structure are pre-noised. The model includes a pre-trained ESM-PPI module, a Inter-chain Feature Embedding Module, a Structure Encoder, the Feature Embedding Module, 16 layers of Sgformer, and an 8 layers of Prediction Module.

back into its clean counterpart $\mathbf{x}_0$, adhering to a boundary condition at $t = 0$. This is accomplished through a specific parameterization:

$$f_\theta(\mathbf{x}_t, t) = c_{\text{skip}}(t)\,\mathbf{x}_t + c_{\text{out}}(t)\,F_\theta(\mathbf{x}_t, t), \tag{4}$$

where the conditions $c_{\text{skip}}(0) = 1$ and $c_{\text{out}}(0) = 0$ ensure compliance with the boundary requirement. During training, the PF-ODE is discretized into $N - 1$ segments, and a loss function is minimized to quantify the difference between adjacent points along the sampling path:

$$\arg\min_\theta \mathbb{E}\left[\lambda(t_i)d(f_\theta(\mathbf{x}_{t_{n+1}}, t_{n+1}), f_{\theta^-}(\tilde{\mathbf{x}}_{t_n}, t_n))\right]. \tag{5}$$

In this equation, $d(\cdot, \cdot)$ represents a chosen metric, f_{θ^-} denotes an exponential moving average of previous outputs, and $\tilde{\mathbf{x}}_{t_n}$ is calculated based on the noise gradient. The selection of the metric and the sampling strategy is vital for effective model training.

3.4 Denoising network architecture

The overall network architecture is illustrated in Figure 3, which includes a pre-trained protein language model, a multi-level feature encoder, and a sequence and structure design module.

Feature extraction from protein language models. Inspired by the success of pre-trained language models in natural language processing, we employed protein pre-trained large models Lin et al. [2022], Chen et al. [2023], Hayes et al. [2024] as a feature extractor. We select ESM-PPI [Wu et al., 2024] as our sequence feature extractor due to its ability to handle inter-chain relationships. ESM-PPI is an extension of the ESM2 model [Lin et al., 2022], which has been further refined to improve its proficiency in capturing the structural and functional characteristics of multi-chain protein complexes. The antigen and perturbed antibody data are processed by the PLM, with the features from the final layer being meticulously extracted to serve as input to feature encoder. To preserve the integrity of the learned features and to conserve computational resources, we maintain the PLM's parameters in a frozen state throughout this process. The enhanced capabilities of ESM-PPI for multi-chain protein structure prediction are detailed in [Wu et al., 2024], where readers can find a more in-depth discussion of the model's architecture, training procedure, and its application.

Multi-level feature encoder. To fully leverage the interactions between different features, we utilize a multi-level feature encoder for feature encoding, as illustrated in Figure 3. This approach allows the model to develop an understanding of the distinct chains that comprise the antibody structure. We incorporate chain-specific representations into the output features of the pre-trained language model (PLM). Furthermore, to address the critical aspect of antigen epitopes, we augment the antigen feature set with specialized representations that emphasize the interactions between the antibody and the antigen. We employ a structural encoder to provide the model with a means to identify the precise

positions of individual amino acids. Subsequently, these extracted features are input into Sgformer consisting of 16 blocks for further feature fusion and encoding. The sequence features extracted at this stage are pivotal for the subsequent recovery of the original sequence from the perturbed input, while the pair-wise representations encode the relational information essential for understanding the complex folding of the antibody-antigen complex.

Sequence and structure design module. IgGM employs 8 layers of Predict modules, as illustrated in Figure 6. The Predict modules utilize invariant point attention to optimize the structure while simultaneously outputting the designed sequences. Due to the invariance of the Predict modules, this ensures that the model's predictions remain consistent regardless of the orientation or position of the antibody in space. The Predict modules fully leverage the sequence features and pair-wise representations learned by the Sgformer modules, while also incorporating the structures obtained from the initial sampling as input. By integrating these features with the invariant point attention mechanism, the Predict modules are able to iteratively refine the coordinates of the amino acids, ultimately revealing the precise spatial arrangement of the antibody's three-dimensional structure.

3.5 Training and sampling

Loss function. In the context of diffusion models, the objective can either be to predict the added noise or to recover the original target [Ho et al., 2020]. For our hybrid diffusion model, we have opted to design our functions to focus on recovering the original target. Drawing inspiration from previous work, we have developed a suite of loss functions to train our model for the desired recovery. The overall training objective is presented below, with more details available in Appendix C.

$$\mathcal{L} = \mathcal{L}_{srcv} + \mathcal{L}_{geo} + \mathcal{L}_{Frame} + \mathcal{L}_{iFrame} + 0.02\mathcal{L}_{viol} \tag{6}$$

Training details. The process of training the diffusion model is divided into two phases. In the first phase, we focus on training the structural component while preserving the information of the original sequences. In the second phase, we utilize the weights initialized from the first phase to perform joint training of sequences and structures. At each training step t, we sample a sample$(s_0, x_0)$from the training set, along with noise variables (s_t, x_t). The model weights are updated based on the loss. If sequence design is not involved, the original sequences are retained. During the training process, we employ a self-conditioning approach to compensate for the relatively small amount of data. Upon completion of the training, we distill the trained diffusion model into a consistency model to accelerate sampling, following the methodology proposed by Song et al. [2023]. For further details, please refer to the Appendix B.2.

Sampling. During the sampling process, we consider different design scenarios, taking the collaborative design of sequence and structure as an example. Initially, we sample (s_t, x_t), where s_t represents the initial sequence, x_t denotes the coordinates of C_α, and the orientation of the amino acids. Subsequently, the distilled consistency model is employed to perform denoising, enabling either single-step or multi-step generation. We compared the performance differences between multistep generation and singlestep generation in the Appendix B.3.

4 Experiments

We constructed our training, validation, and test sets from the SAbDab database, employing the widely used method of dividing the dataset based on time, as previously established in other works [Jumper et al., 2021, Ruffolo et al., 2023, Wu et al., 2024, Abramson et al., 2024]. We removed antibodies from the second half of 2023 that exhibited high sequence similarity to those in the training set to construct the test set, resulting in a test set comprising 60 antibodies (SAb-23H2-Ab) and a test set of 27 nanobodies (SAb-23H2-Nano). More details can be found in the appendix B.1. Due to the limitations of AlphaFold 3, we generate five samples for each example to ensure a fair comparison. The details of the evaluation metrics can be found in Appendix B.4. Moreover, an ablation study of IgGM is in Appendix D.

4.1 complex structure prediction

Complex structure prediction involves predicting the structure of the complex based on a given antibody sequence and antigen. IgGM can achieve structure prediction without the need for sequence design. Following the evaluation criteria of tFold-Ag [Wu et al., 2024], we assess the results

Table 1: Complex Structure Prediction. Methods with superscript [†] use the antigen structure as input, while those with superscript [*] utilize epitope information as input; [‡] utilize MSA. (AF3) indicates that the structure predicted by AlphaFold 3 is used as the initial input. RMSD in different CDR H3 are reported. **Bold** indicates the best performance, while <u>underline</u> represents the second best.

Method	Antibody Structure			Docking			
	TM-Score↑	lDDT↑	RMSD↓	DockQ↑	iRMS↓	LRMS↓	SR↑
IgFold[†]→HDock	0.9577	0.9019	2.1715	0.0218	16.6519	48.1571	0.0000
tFold-Ag[*‡]	<u>0.9634</u>	<u>0.9142</u>	<u>1.9489</u>	0.2522	6.7957	21.0346	0.4068
AlphaFold 3[‡]	**0.9729**	**0.9305**	**1.5063**	0.2951	10.9645	32.4080	0.3684
dyMEAN[†*]	0.9572	0.8882	2.2521	0.1005	8.9227	27.4234	0.0667
IgGM[†*]	0.9591	0.8956	2.1997	<u>0.2986</u>	<u>6.2195</u>	<u>19.4888</u>	<u>0.4667</u>
IgGM[†*](AF3)	0.9580	0.8941	2.1422	**0.3630**	**3.8635**	**11.2647**	**0.6667**

using the TM-Score [Zhang and Skolnick, 2004], DockQ [Basu and Wallner, 2016], and success rate(DockQ> 0.23) of the predicted overall structure of the complex. We evaluated the structural prediction performance on the SAb23H2 test set, comparing three methods: the antibody structure prediction methods IgFold [Ruffolo et al., 2023] and tFold-Ag [Wu et al., 2024], as well as the latest protein structure prediction method AlphaFold 3 [Abramson et al., 2024], alongside the antibody design method dyMEAN [Kong et al., 2023b]. Since IgFold only supports the prediction of antibody structures, we utilized HDock [Yan et al., 2020] to dock the predicted antibody structures with the original antigen. For tFold-Ag and AlphaFold 3, which can directly predict the structure of antigen-antibody complexes, we used the antigen-antibody sequences as input. In the case of dyMEAN and IgGM, we predicted the structure of the antigen-antibody complex given the antigen, using the antibody sequence as input.

As shown in Table 1, for the predicted antibody structures, IgGM outperformed dyMEAN, which uses templates for initialization, in terms of antibody structure prediction. Although there is still a gap compared to specialized structure prediction methods, the results are overall quite close, indicating that our method has learned the distribution of antibody structures. In terms of docking performance, our method surpassed both structure prediction methods and antibody design methods on DockQ, demonstrating that IgGM can achieve high docking performance. Additionally, it showed improved accuracy on iRMS and LRMS, with a success rate of 0.4667, significantly higher than dyMEAN's 0.067. This indicates that IgGM is capable of capturing the interactions between antigens and antibodies effectively. When using the structures predicted by AlphaFold 3 as the initial input for IgGM instead of randomly initialized structures, IgGM demonstrated improved performance across all metrics, particularly in docking-related indicators. Specifically, utilizing AlphaFold 3 structures increased the success rate by 20% compared to using randomly initialized structures.

Figure 4: (A) Structures of the designed antibodies (PDB: 8hpu), designed by IgGM (left, DockQ = 0.824) and dyMEAN (right, DockQ = 0.029). (B) Structures of the designed nanobodies (PDB: 8q93), designed by IgGM (left, DockQ = 0.766) and DiffAb (right, DockQ = 0.495).

4.2 De novo design of antibodies for specific antigen

Due to the limitations of previous methods in achieving end-to-end antibody design, we employed two pipelines to evaluate these approaches. Specifically, the first pipeline follows the dyMEAN

Table 2: Results of the novel antibody design on SAb-2023H2-Ab. (IgFold) or (AF3) indicates that the antibody structure predicted by IgFold or AlphaFold 3 is used as the initial input. Backbone RMSD in different CDR regions are reported. H1-H3 indicate the CDRs of heavy chain while L1-L3 indicate the CDRs of light chain. **Bold** indicates the best performance, while <u>underline</u> represents the second best.

Model		DiffAb (IgFold)	DiffAb (AF3)	MEAN (IgFold)	MEAN (AF3)	dyMEAN	IgGM	IgGM (AF3)
AAR↑	L1	0.597	0.608	-	-	0.633	**0.750**	<u>0.737</u>
	L2	0.598	0.599	-	-	0.634	**0.743**	<u>0.735</u>
	L3	0.421	0.424	-	-	0.570	**0.635**	<u>0.602</u>
	H1	0.642	0.637	-	-	**0.742**	<u>0.740</u>	0.739
	H2	0.363	0.394	-	-	0.627	**0.644**	<u>0.639</u>
	H3	0.214	0.226	0.248	0.246	0.294	**0.360**	<u>0.330</u>
RMSD↓	L1	0.783	0.749	-	-	0.864	**0.589**	<u>0.659</u>
	L2	0.471	0.466	-	-	0.481	**0.378**	<u>0.395</u>
	L3	1.002	1.017	-	-	0.941	**0.847**	<u>0.903</u>
	H1	0.650	0.623	-	-	0.633	**0.555**	<u>0.590</u>
	H2	0.641	0.586	-	-	0.705	**0.486**	<u>0.566</u>
	H3	2.741	2.646	2.357	2.300	2.454	**2.131**	<u>2.155</u>
Docking	DockQ↑	0.022	0.208	0.022	0.207	0.079	<u>0.246</u>	**0.326**
	iRMS↓	17.034	9.731	16.838	8.968	9.698	<u>6.579</u>	**4.030**
	LRMS↓	48.163	27.559	48.104	27.557	28.764	<u>19.678</u>	**11.229**
	SR↑	0.000	0.368	0.000	0.354	0.049	<u>0.433</u>	**0.627**

process (structure prediction⇒docking⇒CDR generation⇒side-chain packing). For a given antibody sequence, we use IgFold [Ruffolo et al., 2023] to predict the antibody structure, followed by docking with the antigen using HDock [Yan et al., 2020], and then apply design methods for CDR generation. The second pipeline utilizes AlphaFold 3 [Abramson et al., 2024] for complex structure prediction (replacing IgFold⇒HDock), after which the antigen structure is aligned, and the native antigen structure is replaced for the predicted antigen structure to ensure that the antigen structure does not influence subsequent evaluations. In terms of antibody design, we evaluated several methods, including MEAN [Kong et al., 2023a], which employs graph neural networks to simultaneously generate sequences and structures for CDR H3; DiffAb [Luo et al., 2022], which uses diffusion models to generate sequences and structures for the CDR regions of antibodies; and dyMEAN [Kong et al., 2023b], which utilizes an end-to-end model for antibody design, allowing for novel structural designs through template utilization.

We tested various methods for the collaborative design of antibody sequence structures, with results presented in Table 2. It is noteworthy that MEAN [Kong et al., 2023a] is limited to designing the CDR H3 region. Therefore, we only tracked the performance of these two methods in this specific region. In contrast, DiffAb [Luo et al., 2022], dyMEAN [Kong et al., 2023b], and IgGM are capable of simultaneously designing all six CDR regions in both the light and heavy chains of antibodies. IgGM outperformed all other methods across nearly all metrics, such as sequence recovery rate and accuracy of generated docking positions, demonstrating the effectiveness of our approach. In comparison to DiffAb and MEAN, which do not support the design of overall structures, their performance varied when using different structures for initialization. The structures predicted by AlphaFold 3 were more accurate, leading to better docking position accuracy than dyMEAN as shown in Figure 4(A), although still lower than that of IgGM. Notably, IgGM was the only method with an iRMS below 8 and an LRMS below 20, while achieving a docking success rate of 43.3%, highlighting its generalizability. In terms of sequence and structural fidelity in the CDR regions, IgGM achieved a higher sequence recovery rate, with a 36% recovery rate in the highly flexible CDR-H3 region, representing a 22.4% improvement over the previous state-of-the-art method, dyMEAN. Additionally, the generated structures exhibited smaller deviations from the true structures. We also implemented a method using structures predicted by AlphaFold 3 as the initial input. The generated results demonstrate a significant improvement in docking-related metrics, with an increase in success rate of nearly 20%. Although there was a slight decline in performance regarding the CDR sequences

Table 3: Results of structure prediction and novel nanobody design on SAb-2023H2-Nano. (AF3) signifies that the structure predicted by AlphaFold 3 is utilized as the initial input. Backbone RMSD in different CDR3. CDR1-CDR3 indicate AAR of the rigons. **Bold** indicates the best performance.

Structure prediction of Nanobody							
Method	TM-Score↑	lDDT↑	RMSD↓	DockQ↑	iRMS↓	LRMS↓	SR↑
tFold-Ag	0.9344	**0.9303**	1.6722	0.2881	**6.3490**	**15.0810**	0.4296
AlphaFold 3	**0.9519**	0.9286	**1.1885**	0.2867	11.2194	32.6760	0.3885
IgGM	0.9318	0.8931	1.9925	**0.2907**	7.9879	22.0168	**0.4400**

Design of Nanobody							
Method	CDR1↑	CDR2↑	CDR3↑	RMSD↓	DockQ↑	iRMS↓	LRMS↓	SR↑
DiffAb(AF3)	0.533	0.291	0.156	2.274	0.211	13.265	35.805	0.346
IgGM	**0.565**	**0.330**	**0.183**	**1.980**	**0.267**	**6.927**	**14.966**	**0.415**

and structures of the antibodies, the decrease was minimal. This indicates that utilizing powerful structural prediction methods to pre-estimate structures can effectively enhance the quality of the designed structures.

4.3 Structure prediction and de novo design of nanobodies

Nanobody sources are a type of single-domain antibody known as VHH fragments [Harmsen and De Haard, 2007]. Nanobodies offer several significant advantages over traditional antibodies. Their structure is simpler, yet they possess a longer CDR3 region, making them particularly suitable for modifications and fusions with other proteins or biomolecules, thereby enabling the creation of multifunctional therapeutic and diagnostic agents based on nanobodies. Thanks to the extensibility of IgGM, it can also be used to design nanobodies. We evaluated the performance of IgGM in predicting nanobody structures using the SAb-2023H2-Nano dataset, comparing it with DiffAb and using structures predicted by AlphaFold 3 as the initialization.

As shown in Table 3, we assessed IgGM in terms of structural prediction and novel design for nanobodies. In the structural prediction of nanobody complexes, the relevant metrics for nanobody structures show an overall improvement compared to traditional antibodies. This enhancement is due to the fact that nanobodies consist of a single chain, making them relatively easier to analyze than the two-chain structure of conventional antibodies. However, for docking-related metrics, the performance of nanobodies is somewhat inferior to that of antibodies. This decline is attributed to the more flexible binding modes of nanobodies, which complicate the accurate prediction of the correct binding positions. IgGM achieved the best performance in terms of success rate and DockQ metrics, demonstrating a success rate of 44%. For nanobody design, IgGM outperformed DiffAb (AF3) across various metrics; however, there was a noticeable decline in the sequence recovery rate of the CDR regions compared to Antibody. This decline can be attributed to the longer CDR regions of nanobodies, which complicate the design process. In terms of structure, IgGM surpassed DiffAb (AF3), benefiting from the robust structural prediction capabilities of AlphaFold 3 as shown in Figure 4(B). While DiffAb (AF3) achieved a success rate of 0.346, the structures predicted by IgGM were more accurate, resulting in a success rate of 0.415.

5 Conclusion

In this study, we introduce IgGM, an innovative model for antibody design that leverages diffusion models to jointly design CDR sequences and the entire antibody structure. Unlike conventional approaches that target specific regions such as the CDR H3, IgGM considers the whole antibody, requiring only the target antigen and an antibody framework sequence. By integrating structural data, IgGM enhances specificity and quality, resulting in higher success rates for predicting binding positions. Our experimental results demonstrate that IgGM outperforms traditional methods in terms of accuracy and efficiency. Additionally, IgGM shows potential in nanobody design, expanding its applicability. As more experimental data becomes available and structural prediction methods improve, IgGM's capabilities are expected to be significantly enhanced, making it a powerful tool for practical antibody design and accelerating the development and application of antibodies.

References

Josh Abramson, Jonas Adler, Jack Dunger, Richard Evans, Tim Green, Alexander Pritzel, Olaf Ronneberger, Lindsay Willmore, Andrew J. Ballard, Joshua Bambrick, Sebastian W. Bodenstein, David A. Evans, Chia-Chun Hung, Michael O'Neill, David Reiman, Kathryn Tunyasuvunakool, Zachary Wu, Akvilė Žemgulytė, Eirini Arvaniti, Charles Beattie, Ottavia Bertolli, Alex Bridgland, Alexey Cherepanov, Miles Congreve, Alexander I. Cowen-Rivers, Andrew Cowie, Michael Figurnov, Fabian B. Fuchs, Hannah Gladman, Rishub Jain, Yousuf A. Khan, Caroline M. R. Low, Kuba Perlin, Anna Potapenko, Pascal Savy, Sukhdeep Singh, Adrian Stecula, Ashok Thillaisundaram, Catherine Tong, Sergei Yakneen, Ellen D. Zhong, Michal Zielinski, Augustin Žídek, Victor Bapst, Pushmeet Kohli, Max Jaderberg, Demis Hassabis, and John M. Jumper. Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature*, 630(8016):493–500, June 2024. ISSN 1476-4687. doi: 10.1038/s41586-024-07487-w. URL https://www.nature.com/articles/s41586-024-07487-w.

Jared Adolf-Bryfogle, Oleks Kalyuzhniy, Michael Kubitz, Brian D Weitzner, Xiaozhen Hu, Yumiko Adachi, William R Schief, and Roland L Dunbrack Jr. Rosettaantibodydesign (rabd): A general framework for computational antibody design. *PLoS computational biology*, 14(4):e1006112, 2018.

Rahmad Akbar, Philippe A Robert, Cédric R Weber, Michael Widrich, Robert Frank, Milena Pavlović, Lonneke Scheffer, Maria Chernigovskaya, Igor Snapkov, Andrei Slabodkin, et al. In silico proof of principle of machine learning-based antibody design at unconstrained scale. In *MAbs*, volume 14, page 2031482. Taylor & Francis, 2022.

Munir Akkaya, Kihyuck Kwak, and Susan K Pierce. B cell memory: building two walls of protection against pathogens. *Nature Reviews Immunology*, 20(4):229–238, 2020.

Sarah Alamdari, Nitya Thakkar, Rianne van den Berg, Alex Xijie Lu, Nicolo Fusi, Ava Pardis Amini, and Kevin K Yang. Protein generation with evolutionary diffusion: sequence is all you need. *bioRxiv*, pages 2023–09, 2023.

Ethan C Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M Church. Unified rational protein engineering with sequence-based deep representation learning. *Nature methods*, 16(12):1315–1322, 2019.

Namrata Anand and Tudor Achim. Protein structure and sequence generation with equivariant denoising diffusion probabilistic models. *arXiv preprint arXiv:2205.15019*, 2022.

Ivan Anishchenko, Samuel J Pellock, Tamuka M Chidyausiku, Theresa A Ramelot, Sergey Ovchinnikov, Jingzhou Hao, Khushboo Bafna, Christoffer Norn, Alex Kang, Asim K Bera, et al. De novo protein design by deep network hallucination. *Nature*, 600(7889):547–552, 2021.

Jacob Austin, Daniel D Johnson, Jonathan Ho, Daniel Tarlow, and Rianne Van Den Berg. Structured denoising diffusion models in discrete state-spaces. *Advances in Neural Information Processing Systems*, 34:17981–17993, 2021.

Sankar Basu and Björn Wallner. Dockq: A quality measure for protein-protein docking models. *PLOS ONE*, 11(8):1–9, 08 2016. doi: 10.1371/journal.pone.0161879. URL https://doi.org/10.1371/journal.pone.0161879.

Nathaniel R Bennett, Joseph L Watson, Robert J Ragotte, Andrew J Borst, Déjenaé L See, Connor Weidle, Riti Biswas, Ellen L Shrock, Philip JY Leung, Buwei Huang, et al. Atomically accurate de novo design of single-domain antibodies. *bioRxiv*, pages 2024–03, 2024.

Andrew RM Bradbury, Nathan D Trinklein, Holger Thie, Ian C Wilkinson, Atul K Tandon, Stephen Anderson, Catherine L Bladen, Brittany Jones, Shelley Force Aldred, Marco Bestagno, et al. When monoclonal antibodies are not monospecific: Hybridomas frequently express additional functional variable regions. In *MAbs*, volume 10, pages 539–546. Taylor & Francis, 2018.

Hongmin Cai, Hebang Yao, Tingting Li, Cedric AJ Hutter, Yanfang Li, Yannan Tang, Markus A Seeger, and Dianfan Li. An improved fluorescent tag and its nanobodies for membrane protein expression, stability assay, and purification. *Communications biology*, 3(1):753, 2020.

Yue Cao, Payel Das, Vijil Chenthamarakshan, Pin-Yu Chen, Igor Melnyk, and Yang Shen. Fold2seq: A joint sequence (1d)-fold (3d) embedding-based generative model for protein design. In *International Conference on Machine Learning*, pages 1261–1271. PMLR, 2021.

Bo Chen, Xingyi Cheng, Yangli-ao Geng, Shen Li, Xin Zeng, Boyan Wang, Jing Gong, Chiming Liu, Aohan Zeng, Yuxiao Dong, Jie Tang, and Le Song. xtrimopglm: Unified 100b-scale pre-trained transformer for deciphering the language of protein. 2023. doi: 10.1101/2023.07.05.547496.

Ting Chen, Ruixiang ZHANG, and Geoffrey Hinton. Analog bits: Generating discrete data using diffusion models with self-conditioning. In *The Eleventh International Conference on Learning Representations*.

Bassil I Dahiyat and Stephen L Mayo. De novo protein design: fully automated sequence selection. *Science*, 278(5335):82–87, 1997.

Justas Dauparas, Ivan Anishchenko, Nathaniel Bennett, Hua Bai, Robert J Ragotte, Lukas F Milles, Basile IM Wicky, Alexis Courbet, Rob J de Haas, Neville Bethel, et al. Robust deep learning–based protein sequence design using proteinmpnn. *Science*, 378(6615):49–56, 2022.

Prafulla Dhariwal and Alexander Nichol. Diffusion models beat gans on image synthesis. *Advances in neural information processing systems*, 34:8780–8794, 2021.

Richard Evans, Michael O'Neill, Alexander Pritzel, Natasha Antropova, Andrew W Senior, Timothy Green, Augustin Žídek, Russell Bates, Sam Blackwell, Jason Yim, et al. Protein complex prediction with alphafold-multimer. *BioRxiv*, 2021.

Noelia Ferruz, Steffen Schmidt, and Birte Höcker. Protgpt2 is a deep unsupervised language model for protein design. *Nature communications*, 13(1):4348, 2022.

Zhangyang Gao, Cheng Tan, and Stan Z Li. Diffsds: A language diffusion model for protein backbone inpainting under geometric conditions and constraints. *arXiv preprint arXiv:2301.09642*, 2023.

George Georgiou, Gregory C Ippolito, John Beausang, Christian E Busse, Hedda Wardemann, and Stephen R Quake. The promise and challenge of high-throughput sequencing of the antibody repertoire. *Nature biotechnology*, 32(2):158–168, 2014.

Michiel M Harmsen and Hans J De Haard. Properties, production, and applications of camelid single-domain antibody fragments. *Applied microbiology and biotechnology*, 77:13–22, 2007.

Tomas Hayes, Roshan Rao, Halil Akin, Nicholas J Sofroniew, Deniz Oktay, Zeming Lin, Robert Verkuil, Vincent Q Tran, Jonathan Deaton, Marius Wiggert, et al. Simulating 500 million years of evolution with a language model. *bioRxiv*, pages 2024–07, 2024.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851, 2020.

John B Ingraham, Max Baranov, Zak Costello, Karl W Barber, Wujie Wang, Ahmed Ismail, Vincent Frappier, Dana M Lord, Christopher Ng-Thow-Hing, Erik R Van Vlack, et al. Illuminating protein space with a programmable generative model. *Nature*, 623(7989):1070–1078, 2023.

Wengong Jin, Jeremy Wohlwend, Regina Barzilay, and Tommi Jaakkola. Iterative refinement graph neural network for antibody sequence-structure co-design. *arXiv preprint arXiv:2110.04624*, 2021.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Antibody-antigen docking and design via hierarchical structure refinement. In *International Conference on Machine Learning*, pages 10217–10227. PMLR, 2022.

Bowen Jing, Stephan Eismann, Patricia Suriana, Raphael John Lamarre Townshend, and Ron Dror. Learning from protein structure with geometric vector perceptrons. In *International Conference on Learning Representations*, 2020.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, Alex Bridgland, Clemens Meyer, Simon A. A. Kohl, Andrew J. Ballard, Andrew Cowie, Bernardino Romera-Paredes, Stanislav Nikolov, Rishub Jain, Jonas Adler, Trevor Back, Stig Petersen, David Reiman, Ellen Clancy, Michal Zielinski, Martin Steinegger, Michalina Pacholska, Tamas Berghammer, Sebastian Bodenstein, David Silver, Oriol Vinyals, Andrew W. Senior, Koray Kavukcuoglu, Pushmeet Kohli, and Demis Hassabis. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, Aug 2021. ISSN 1476-4687. doi: 10.1038/s41586-021-03819-2. URL `https://doi.org/10.1038/s41586-021-03819-2`.

Urszula Julia Komorowska, Simon V Mathis, Kieran Didi, Francisco Vargas, Pietro Lio, and Mateja Jamnik. Dynamics-informed protein design with structure conditioning. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=jZPqf2G9Sw`.

Xiangzhe Kong, Wenbing Huang, and Yang Liu. Conditional antibody design as 3d equivariant graph translation. In *ICLR*, 2023a. URL `https://openreview.net/forum?id=LFHFQbjxIiP`.

Xiangzhe Kong, Wenbing Huang, and Yang Liu. End-to-end full-atom antibody design. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett, editors, *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 17409–17429. PMLR, 23–29 Jul 2023b.

Gideon D Lapidoth, Dror Baran, Gabriele M Pszolla, Christoffer Norn, Assaf Alon, Michael D Tyka, and Sarel J Fleishman. Abdesign: A n algorithm for combinatorial backbone design guided by natural conformations and sequences. *Proteins: Structure, Function, and Bioinformatics*, 83(8): 1385–1406, 2015.

Adam Leach, Sebastian M Schmon, Matteo T. Degiacomi, and Chris G. Willcocks. Denoising diffusion probabilistic models on SO(3) for rotational alignment. In *ICLR 2022 Workshop on Geometrical and Topological Representation Learning*, 2022. URL `https://openreview.net/forum?id=BY88eBbkpe5`.

Tong Li, Robert J Pantazes, and Costas D Maranas. Optmaven–a new framework for the de novo design of antibody variable region models targeting specific antigen epitopes. *PloS one*, 9(8): e105954, 2014.

Weizhong Li and Adam Godzik. Cd-hit: a fast program for clustering and comparing large sets of protein or nucleotide sequences. *Bioinformatics*, 22(13):1658–1659, 2006.

Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Allan dos Santos Costa, Maryam Fazel-Zarandi, Tom Sercu, Sal Candido, et al. Language models of protein sequences at the scale of evolution enable accurate structure prediction. *bioRxiv*, 2022.

Gary W Litman, Jonathan P Rast, Michael J Shamblott, Robert N Haire, Michele Hulst, William Roess, Ronda T Litman, Kristin R Hinds-Frey, Anna Zilch, and Chris T Amemiya. Phylogenetic diversification of immunoglobulin genes and the antibody repertoire. *Molecular biology and evolution*, 10(1):60–72, 1993.

Ge Liu, Haoyang Zeng, Jonas Mueller, Brandon Carter, Ziheng Wang, Jonas Schilz, Geraldine Horny, Michael E Birnbaum, Stefan Ewert, and David K Gifford. Antibody complementarity determining region design using high-capacity machine learning. *Bioinformatics*, 36(7):2126–2133, 2020.

Qi Liu, Miltiadis Allamanis, Marc Brockschmidt, and Alexander Gaunt. Constrained graph variational autoencoders for molecule design. *NeurIPS*, 31, 2018.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Shitong Luo, Yufeng Su, Xingang Peng, Sheng Wang, Jian Peng, and Jianzhu Ma. Antigen-specific antibody design and optimization with diffusion-based generative models for protein structures. *Advances in Neural Information Processing Systems*, 35:9754–9767, 2022.

Simian Luo, Yiqin Tan, Suraj Patil, Daniel Gu, Patrick von Platen, Apolinário Passos, Longbo Huang, Jian Li, and Hang Zhao. Lcm-lora: A universal stable-diffusion acceleration module. *arXiv preprint arXiv:2311.05556*, 2023.

Isaac D Lutz, Shunzhi Wang, Christoffer Norn, Alexis Courbet, Andrew J Borst, Yan Ting Zhao, Annie Dosey, Longxing Cao, Jinwei Xu, Elizabeth M Leaf, et al. Top-down design of protein architectures with reinforcement learning. *Science*, 380(6642):266–273, 2023.

Ali Madani, Ben Krause, Eric R Greene, Subu Subramanian, Benjamin P Mohr, James M Holton, Jose Luis Olmos, Caiming Xiong, Zachary Z Sun, Richard Socher, et al. Large language models generate functional protein sequences across diverse families. *Nature Biotechnology*, 41(8): 1099–1106, 2023.

Geraldene Munsamy, Sebastian Lindner, Philipp Lorenz, and Noelia Ferruz. Zymctrl: a conditional language model for the controllable generation of artificial enzymes. In *NeurIPS Machine Learning in Structural Biology Workshop*, 2022.

Aaron L Nelson, Eugen Dhimolea, and Janice M Reichert. Development trends for human monoclonal antibody therapeutics. *Nature reviews drug discovery*, 9(10):767–774, 2010.

Alexander Quinn Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. In *International conference on machine learning*, pages 8162–8171. PMLR, 2021.

RJ Pantazes and Costas D Maranas. Optcdr: a general computational method for the design of antibody complementarity determining regions for targeted epitope binding. *Protein Engineering, Design & Selection*, 23(11):849–858, 2010.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding with unsupervised learning. 2018.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10684–10695, 2022.

Jeffrey A Ruffolo, Jeffrey J Gray, and Jeremias Sulam. Deciphering antibody affinity maturation with language models and weakly supervised learning. *arXiv preprint arXiv:2112.07782*, 2021.

Jeffrey A Ruffolo, Lee-Shin Chu, Sai Pooja Mahajan, and Jeffrey J Gray. Fast, accurate antibody structure prediction from deep learning on massive set of natural antibodies. *Nature communications*, 14(1):2389, 2023.

Yaghoub Safdari, Safar Farajnia, Mohammad Asgharzadeh, and Masoumeh Khalili. Antibody humanization methods–a review and update. *Biotechnology and Genetic Engineering Reviews*, 29 (2):175–186, 2013.

Koichiro Saka, Taro Kakuzaki, Shoichi Metsugi, Daiki Kashiwagi, Kenji Yoshida, Manabu Wada, Hiroyuki Tsunoda, and Reiji Teramoto. Antibody design using lstm based deep generative model from phage display library for affinity maturation. *Scientific reports*, 11(1):5852, 2021.

Axel Sauer, Dominik Lorenz, Andreas Blattmann, and Robin Rombach. Adversarial diffusion distillation. *arXiv preprint arXiv:2311.17042*, 2023.

Harry W Schroeder Jr and Lisa Cavacini. Structure and function of immunoglobulins. *Journal of allergy and clinical immunology*, 125(2):S41–S52, 2010.

Chence Shi, Chuanrui Wang, Jiarui Lu, Bozitao Zhong, and Jian Tang. Protein sequence and structure co-design with equivariant translation. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=pRCMXcfdihq.

Jung-Eun Shin, Adam J Riesselman, Aaron W Kollasch, Conor McMahon, Elana Simon, Chris Sander, Aashish Manglik, Andrew C Kruse, and Debora S Marks. Protein design and variant prediction using autoregressive generative models. *Nature communications*, 12(1):2403, 2021.

Dee Unglaub Silverthorn. *Human physiology*. Jones & Bartlett Publishers, 2015.

Mark X Sliwkowski and Ira Mellman. Antibody therapeutics in cancer. *Science*, 341(6151):1192–1198, 2013.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International conference on machine learning*, pages 2256–2265. PMLR, 2015.

Yang Song and Prafulla Dhariwal. Improved techniques for training consistency models. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=WNzy9bRDvG`.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *NeurIPS*, 32, 2019.

Yang Song, Prafulla Dhariwal, Mark Chen, and Ilya Sutskever. Consistency models. In *International Conference on Machine Learning*, pages 32211–32252. PMLR, 2023.

Brian L Trippe, Jason Yim, Doug Tischer, Tamara Broderick, David Baker, Regina Barzilay, and Tommi Jaakkola. Diffusion probabilistic modeling of protein backbones in 3d for the motif-scaffolding problem. *arXiv preprint arXiv:2206.04119*, 2022.

Brian L. Trippe, Jason Yim, Doug Tischer, David Baker, Tamara Broderick, Regina Barzilay, and Tommi S. Jaakkola. Diffusion probabilistic modeling of protein backbones in 3d for the motif-scaffolding problem. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=6TxBxqNME1Y`.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Jue Wang, Sidney Lisanza, David Juergens, Doug Tischer, Joseph L Watson, Karla M Castro, Robert Ragotte, Amijai Saragovi, Lukas F Milles, Minkyung Baek, et al. Scaffolding protein functional sites using deep learning. *Science*, 377(6604):387–394, 2022.

Xiang Wang, Shiwei Zhang, Han Zhang, Yu Liu, Yingya Zhang, Changxin Gao, and Nong Sang. Videolcm: Video latent consistency model. *arXiv preprint arXiv:2312.09109*, 2023.

Shira Warszawski, Aliza Borenstein Katz, Rosalie Lipsh, Lev Khmelnitsky, Gili Ben Nissan, Gabriel Javitt, Orly Dym, Tamar Unger, Orli Knop, Shira Albeck, et al. Optimizing antibody affinity and stability by the automated design of the variable light-heavy chain interfaces. *PLoS computational biology*, 15(8):e1007207, 2019.

Joseph L Watson, David Juergens, Nathaniel R Bennett, Brian L Trippe, Jason Yim, Helen E Eisenach, Woody Ahern, Andrew J Borst, Robert J Ragotte, Lukas F Milles, et al. De novo design of protein structure and function with rfdiffusion. *Nature*, 620(7976):1089–1100, 2023.

George J Weiner. Building better monoclonal antibody-based therapeutics. *Nature Reviews Cancer*, 15(6):361–370, 2015.

Fandi Wu, Yu Zhao, Jiaxiang Wu, Biaobin Jiang, Bing He, Longkai Huang, Chenchen Qin, Fan Yang, Ningqiao Huang, Yang Xiao, et al. Fast and accurate modeling and design of antibody-antigen complex using tfold. *bioRxiv*, pages 2024–02, 2024.

Kevin E Wu, Kevin K Yang, Rianne van den Berg, James Y Zou, Alex X Lu, and Ava P Amini. Protein structure generation via folding diffusion. *arXiv preprint arXiv:2209.15611*, 2022.

Jie Xiao, Kai Zhu, Han Zhang, Zhiheng Liu, Yujun Shen, Yu Liu, Xueyang Fu, and Zheng-Jun Zha. Ccm: Adding conditional controls to text-to-image consistency models. *arXiv preprint arXiv:2312.06971*, 2023.

Yumeng Yan, Huanyu Tao, Jiahua He, and Sheng-You Huang. The hdock server for integrated protein–protein docking. *Nature protocols*, 15(5):1829–1852, 2020.

Jianyi Yang, Ivan Anishchenko, Hahnbeom Park, Zhenling Peng, Sergey Ovchinnikov, and David Baker. Improved protein structure prediction using predicted interresidue orientations. *Proceedings of the National Academy of Sciences*, 117(3):1496–1503, 2020.

Jiaxuan You, Rex Ying, Xiang Ren, William Hamilton, and Jure Leskovec. Graphrnn: Generating realistic graphs with deep auto-regressive models. In *ICML*, pages 5708–5717. PMLR, 2018.

Vinicius Zambaldi, David La, Alexander E. Chu, Harshnira Patani, Amy E. Danson, Tristan O. C. Kwan, Thomas Frerix, Rosalia G. Schneider, David Saxton, Ashok Thillaisundaram, Zachary Wu, Isabel Moraes, Oskar Lange, Eliseo Papa, Gabriella Stanton, Victor Martin, Sukhdeep Singh, Lai H. Wong, Russ Bates, Simon A. Kohl, Josh Abramson, Andrew W. Senior, Yilmaz Alguel, Mary Y. Wu, Irene M. Aspalter, Katie Bentley, David L.V. Bauer, Peter Cherepanov, Demis Hassabis, Pushmeet Kohli, Rob Fergus, and Jue Wang. De novo design of high-affinity protein binders with alphaproteo. *Google DeepMind*, 2024.

Adam Zemla. Lga: a method for finding 3d similarities in protein structures. *Nucleic acids research*, 31(13):3370–3374, 2003.

Yang Zhang and Jeffrey Skolnick. Scoring function for automated assessment of protein structure template quality. *Proteins: Structure, Function, and Bioinformatics*, 57(4):702–710, 2004.

A   Diffusion models

Continuous Diffusion   To model a distribution $p(w)$, an effective method involves first embedding w into a continuous variable x_0 using an embedding matrix U_θ and then adding Gaussian noise. The prior distribution is set as $\pi(x) = \mathcal{N}(0, I)$, and the forward process is defined by:

$$p(x_t|x_0) = \mathcal{N}(x_t; \sqrt{\bar{\alpha_t}}x_0, (1 - \bar{\alpha}_t)I) \tag{7}$$

where $\bar{\alpha}_t$ ranges from 0 to 1. The values of $\bar{\alpha}_t$ are determined by a predefined noise schedule.

The reverse process aims to learn a function $p_\theta(\hat{w}|x_t, t)$ that can reconstruct the sequence from the noisy data points x_t. This is achieved by minimizing the following loss function with respect to θ:

$$L(\theta) = \mathbb{E}_{w_0,t}\left[-\log p_\theta(w_0|x_t)\right], \quad x_t \sim p(x_t|x_0 = U_\theta w_0).$$

Using $p_\theta(\hat{w}|x_t, t)$, we can define the reverse process distribution as follows:

$$p_\theta(x_{t-1}|x_t) = \sum_{\hat{w}} p\left(x_{t-1}|x_t, \hat{x}_0 = U_\theta\hat{w}\right)p(\hat{w}|x_t, t), \tag{8}$$

where $p(x_{t-1}|x_t, x_0)$ is also a Gaussian distribution. During inference, the learned reverse process can be used to transform samples from $\pi(x)$ into samples from the learned distribution $p_\theta(x_0)$. This is done by iteratively sampling from $p_\theta(x_{t-1}|x_t)$ and then sampling $w \sim p_\theta(\hat{w}|x_0, 0)$.

Discrete Diffusion   As proposed by Austin et al. [2021], for scalar discrete random variables with K categories, denoted as s_t and s_{t-1} where $s_t, s_{t-1} \in \{1, \ldots, K\}$, the forward transition probabilities can be represented using matrices: $[Q_t]_{ij} = q(s_t = j|s_{t-1} = i)$. Representing s in its one-hot form as a row vector $\mathbf{s}$, the forward transition can be expressed as:

$$q(\mathbf{s}_t|\mathbf{s}_{t-1}) = \mathrm{Cat}(\mathbf{s}_t; \mathbf{p} = \mathbf{s}_{t-1}Q_t), \tag{9}$$

where $\mathrm{Cat}(\mathbf{s}; \mathbf{p})$ denotes a categorical distribution over the one-hot vector $\mathbf{s}$ with probabilities from $\mathbf{p}$. The term $\mathbf{s}_{t-1}Q_t$ represents a row vector-matrix product, with Q_t applied independently to each pixel or token.

Starting from $\mathbf{s}_0$, the t-step marginal and posterior at time $t-1$ are given by:

$$q(\mathbf{s}_t|\mathbf{s}_0) = \mathrm{Cat}(\mathbf{s}_t; p = \mathbf{s}_0\overline{Q}_t), \quad \text{with} \quad \overline{Q}_t = Q_1Q_2\cdots Q_t,$$

$$q(\mathbf{s}_{t-1}|\mathbf{s}_t, \mathbf{s}_0) = \frac{q(\mathbf{s}_t|\mathbf{s}_{t-1}, \mathbf{s}_0)q(\mathbf{s}_{t-1}|\mathbf{s}_0)}{q(\mathbf{s}_t|\mathbf{s}_0)} = \mathrm{Cat}(\mathbf{s}_{t-1}; \mathbf{p} = \frac{\mathbf{s}_t Q_t^\top \odot \mathbf{s}_0\overline{Q}_{t-1}}{\mathbf{s}_0\overline{Q}_t\mathbf{s}_t^\top}). \tag{10}$$

SO(3) Diffusion   For each amino acid direction, the orientation within the local coordinate system of each amino acid can be considered as a continuous value in the SO(3) space, analogous to a uniform distribution on polar coordinates [Leach et al., 2022]. Consequently, we can construct both forward and backward diffusion processes on the three-dimensional rotation group SO(3). The forward process diffusing the direction data o_0 into pure noise, following the specific formula:

$$q(o_t|o_0) = \mathrm{IGSO}(3)(\lambda(\sqrt{\alpha_t}, o_0), (1 - \alpha_t)) \tag{11}$$

where $\mathrm{IGSO}(3)$ denotes the isotropic Gaussian distribution on SO(3), and λ represents the scalar product along the geodesic from the identity rotation matrix to o_0. Conversely, the backward process is designed to transform noise back into data, guided by the following probability distribution:

$$p(o_{t-1}|o_t, o_0) = \mathrm{IGSO}(3)(\widetilde{\mu}(o_t, o_0), \widetilde{\beta}_t) \tag{12}$$

where $\widetilde{\mu}(o_t, o_0)$ denotes the mean of the backward process, which is calculated as the product of two rotation matrices.

B Experiment details

B.1 Dataset

We selected all experimentally determined antibody structures published in the database up to December 31, 2022, as our training set. The final training set consisted of 6,448 antibody-antigen complexes with both heavy and light chains and 1,907 single-chain antibody-antigen complexes. During the training process, we used CD-Hit [Li and Godzik, 2006] to cluster the training set, with each cluster containing antibodies with sequence similarities above 95%, resulting in a total of 2,436 clusters. To ensure the utilization of available data, we randomly sampled one sample from each cluster for training in each epoch. The validation and test sets included antigen-antibody complexes determined experimentally and published between January 1, 2023, and June 30, 2023, and between June 30, 2023, and December 30, 2023, respectively. More details can be found at B.2. We removed sequences that were similar to those in the training set to eliminate redundancy in the data, ensuring a fair evaluation. This process resulted in 101 validation samples and 60 test samples, both of which were completely unrelated to the training set. The validation set was used for hyperparameter tuning and model selection, while the test set, named SAb-23H2-Ab, was utilized for subsequent performance evaluation. We also utilized a nanobody dataset released in the second half of 2023 to construct a test set for nanobodies, referred to as SAb-23H2-Nano.

B.2 training details

The training process of IgGM is divided into two stages, following the concept of curriculum learning. Initially, we train the model for structural design, we use the Adam [Loshchilov and Hutter, 2017] optimizer and set the batch size of the training process to 32. We also maintain an EMA (Exponential Moving Average) decay of 0.999 for the model parameters and evaluate the model, selecting the best TM-Score on the validation subset as the optimal model. Given an antigen-antibody complex, we perturb the antibody structure to introduce noise, and then have the model reconstruct the perturbed antibody structure. This process lasted for 5 days on 8 A100 GPUs. Once the first-stage model has converged, we use the parameters from the first-stage training to proceed with the second stage. In the second stage, we perturb the sequence and structure of the antibody's CDR regions and have the model reconstruct the perturbed antibody. This perturbation is aimed at introducing greater complexity and variability into the training data, thereby challenging the model to generalize better to unseen data. This process also lasted for 5 days on 8 A100 GPUs. Throughout both stages, we use self-conditioning [Chen et al.] to enhance the stability of the training. This self-conditioning technique involves feeding the model with additional information derived from the original unperturbed structure, which helps the model to better learn the underlying patterns and regularities in the data. Ensuring that the model learns robustly and can generalize well to new and challenging data. The two-stage training process allows the model to first learn basic patterns and then progressively build on that knowledge to handle more complex scenarios. After training the generative model, we distill the consistency model using the method proposed by Song et al. [2023]. For specific details, please refer to Song et al. [2023].

B.3 sampling

Table 4: Different sample steps for IgGM.

Method	AAR↑ CDR3	DockQ↑	iRMS↓	LRMS↓	SR↑
Step=1	0.362	0.240	6.474	19.694	0.383
Step=2	0.363	0.244	6.570	19.616	0.383
Step=5	0.363	0.242	6.610	19.932	0.400
Step=10	0.360	0.246	6.579	19.678	0.433
Step=20	0.361	0.232	6.840	20.980	0.400
Step=50	0.348	0.225	6.809	20.905	0.383

As shown in Algorithm 1, during the generation process, we adopted the consistency model [Song et al., 2023] to accelerate the sampling speed for antibody sequences and structures, as traditional

---
Algorithm 1: IgGM Sampling
---
1 **Input:** Model $f_{\theta}(\cdot, \cdot)$, sequence of time points $\tau_1 > \tau_2 > \cdots > \tau_{N-1}$, initial noise $(\hat{s}_T, \hat{x}_T)$, antigen $s_A, x_A)$ $(s, x) \leftarrow f_{\theta}((\hat{s}_T, \hat{x}_T), T, (s_A, x_A))$ $n = 1$ **to** $N-1$ Sample $\bar{Q}_z = Q_1 Q_2 ... Q_T \sim q(x_t = j | x_{t-1} = i), \quad x_z \sim (N(\mathbf{0}, \mathbf{I}), \text{Uniform}(SO(3)))$ $\hat{s}_{\tau_n} \leftarrow s\bar{Q}_z$, $\hat{x}_{\tau_n} \leftarrow x + \sqrt{\tau_n^2 - \epsilon^2} x_z$ $x \leftarrow f_{\theta}((\hat{s}_{\tau_n}, \hat{x}_{\tau_n}), \tau_n, (s_A, x_A))$ **Output:** (s, x)
---

diffusion models often exhibit sluggish performance. IgGM allows for both single-step and multi-step sampling during the generation process. Alternatively, the model can be optimized through multiple iterations to enhance the stability of the generated results. During single-step sampling, once the initial sequences and structures are obtained from the noise, the model can generate the final sequences and structures in one step. In contrast, multi-step sampling allows for the generation of relatively more stable structures and sequences. The sampling results for different step counts are shown in Table 4. We selected 10 steps to achieve a balance between quality and speed.

B.4 evaluation metrics

For the sequence portion, we employ metrics that have been widely used in previous work [Luo et al., 2022, Jin et al., 2021, 2022, Kong et al., 2023a,b]: AAR, the amino acid recovery rate represents the proportion of similarity between the designed antibody sequence and the actual antibody sequence. A higher value indicates that the model has a greater ability to generate a specific antibody.

For the evaluation of antibody structure design, we employ several established protein structure assessment metrics, including the RMSD, TM-Score [Zhang and Skolnick, 2004], GDT-TS [Zemla, 2003], DockQ [Basu and Wallner, 2016], and SR.

- Root Mean Square Deviation (RMSD): This metric obtained by calculating the mean of the squared differences between the coordinates of aligned CDR H3 backbone atoms and then taking the square root. The CDR H3 region is the most flexible, making it more challenging to predict.

- TM-Score (Template Modeling Score): This metric measures the structural similarity between the predicted antibody structure and a reference structure. A TM-Score of 1 indicates an exact match between the two structures, while a score closer to 0 indicates a poor match, a high TM-Score suggests that the predicted structure closely resembles the native structure.

- GDT-TS (Global Distance Test-Total Score): This metric provides an overall assessment of the model's accuracy by comparing the predicted structure to the native structure based on the global distance test. It takes into account both the accuracy of the model's predictions and the conformational similarity to the native structure. A higher GDT-TS score indicates a better match between the predicted structure and the native structure, suggesting a higher quality design.

- DockQ: This metric is specifically designed for evaluating the quality of protein-protein docking predictions. It assesses the interface complementarity and the conformational accuracy of the predicted complex structure. A high DockQ value indicates that the predicted interface is likely to be functional and stable, suggesting a well-designed multi-chain interface.

$$\text{DockQ} = \frac{\text{Fnat} + \text{RMS}_{\text{scaled}}(\text{LRMS}, d_1) + \text{RMS}_{\text{scaled}}(\text{iRMS}, d_2)}{3}, \tag{13}$$

where $\text{RMS}_{\text{scaled}}$ represents the scaled RMS deviation corresponding to either LRMS or iRMS, d_i is a scaling factor, d_1 is used for LRMS, and d_2 is used for iRMS. Fnat is defined as the fraction of native contacts retained in the predicted complex interface.

- SR (Success Rate): Indicates that the quality of the designed multi-chain interface positioning is within an acceptable range when DockQ is greater than 0.23. High SR indicates that more structure of antibodies is good.

Figure 5: The SgFormer blocks update the single and pair representations through sequence attention and triangle update module.

Figure 6: Antibody Sequence-Structure Prediction Module: The features input into a prediction module that includes an IPA module and a Sequence head to predict the sequence and structure of the antibody.

C The objective of IgGM

For amino acid sequences, given that there are only 20 types of amino acids, different amino acids exhibit similar backbone atoms. We treat sequence recovery as a classification problem. We employ cross-entropy loss to guide the model in learning the correct sequence.

When it comes to the structure of antibodies, as previously mentioned in section A, our objective is to recover the spatial coordinates of alpha carbons and the orientations of backbone atoms. To this end, we utilize the residue Frame Mean Squared Error (FMSE) loss, which has been demonstrated to be effective in [Watson et al., 2023]. This loss function is specifically designed to measure the discrepancy between the predicted and actual frames of protein residues, which are essential for accurately modeling the three-dimensional structure of antibodies. We have further developed an enhanced loss function termed inter-chain Frame Mean Squared Error (iFMSE) loss. This loss function is specifically tailored to impose constraints on the differences between different chains within the antibody structure. The iFMSE loss is designed to ensure that the model accurately captures the relative orientations and positions of the various chains that make up the antibody, which is crucial for maintaining the integrity of the quaternary structure. Additionally, we employ the inter-residue

distance and angle metrics to reconstruct the orientations of backbone atoms. By incorporating these loss functions, our model is trained to not only accurately predict the amino acid sequences but also to reconstruct the intricate three-dimensional structures of antibodies, thereby enhancing the potential of our approach in the fields of structural biology and antibody modeling.

The overall objective of the model is to recover the correct sequence and structure from the denoised antibody data. The overall loss function can be represented as follows:

$$\mathcal{L} = \mathcal{L}_{srcv} + \mathcal{L}_{geo} + \mathcal{L}_{Frame} + \mathcal{L}_{iFrame} + 0.02\mathcal{L}_{viol} \tag{14}$$

- **Amino-acid Sequence Recovery Loss** $\mathcal{L}_{sr}$ is designed to supervise the model to recover the amino-acid sequence s_i at the position i. A total 20 classes for common amino acid types are considered. sequence embedding $\{s_i\}$ are linearly projected into the output classes and scored with the cross-entropy loss:

$$\mathcal{L}_{srcv} = -\frac{1}{\sum_{i \in design}} \sum_{c=1}^{20} p_i^c \log p_i^c \tag{15}$$

  where p_i^c are predicted class probabilities, y_i^c are one-hot encoded ground-truth values, and averaging across the masked positions.

- **Inter-residue Geometric Loss** $\mathcal{L}_{geo}$ is designed to provide more direct supervision in the following stack. Four auxiliary heads, implemented as feed-forward layers, are added to the top of the final pair features for predicting inter-residue distances and angles, as described in trRosetta [Yang et al., 2020]. These include:

    - D_{ij}: Distance between C_β and C'_β
    - Ω_{ij}: Dihedral angle formed by C_α, C_β, C'_β, and C'_α
    - Θ_{ij}: Dihedral angle formed by N, C_α, C_β, and C'_β
    - Φ_{ij}: Planar angle formed by C_α, C_β, and C'_β

  Each prediction head outputs a probabilistic estimation of the aforementioned distance and angles, denoted as logits_{ij}^d, $\text{logits}_{ij}^\omega$, $\text{logits}_{ij}^\theta$, and $\text{logits}_{ij}^\varphi$. The cross-entropy loss is calculated for each term and summed up to form the final inter-residue geometric loss:

$$\mathcal{L}_{geo} = \sum_{ij} \text{CE}\left(\text{logits}_{ij}^d; D_{ij}\right) + \text{CE}\left(\text{logits}_{ij}^\omega; \Omega_{ij}\right) + \text{CE}\left(\text{logits}_{ij}^\Theta; \theta_{ij}\right) + \text{CE}\left(\text{logits}_{ij}^\Phi; \varphi_{ij}\right) \tag{16}$$

- **Residue Frame MSE Loss** is designed to provide more direct supervision in the predict module to recover the structure of antibody. The formula can be expressed as follows:

$$L_{\text{Frame}} = \frac{1}{\sum_{i=0}^{I-1} \gamma^i} \sum_{i=1}^{I} \gamma^{I-i} d(x^{(0)}, \hat{x}^{(0),i})^2 \tag{17}$$

  where $d(x^{(0)}, \hat{x}^{(0)})$ represents the distance about both rotation and translation, and it can be expressed in the following form:

$$d(x^{(0)}, \hat{x}^{(0)}) = \sqrt{\frac{1}{L} \sum_{l=1}^{L} \left(w_t \min\left(\left\|z_l^{(0)} - \hat{z}_l^{(0)}\right\|^2, d_{\text{clamp}}\right)^2 + w_r \left\|I_3 - \hat{r}_l^{(0)\top} r_l^{(0)}\right\|_F^2 \right)} \tag{18}$$

  where w_t and w_r are weights on the translation and rotation distances, and d_{clamp} is a maximum distance to avoid the numerical overflow.

- **Interface Residue Frame MSE Loss** is designed to provide more direct supervision in the predict module to recover the structure of antibody between interchain.

- **Structure violation loss** $\mathcal{L}_{viol}$: Similar to AlphaFold2 [Jumper et al., 2021], we introduce penalty terms for incorrect peptide bond length and angles, as well as steric clashes between non-bonded atoms. For multimer structure prediction, we do not penalize the bond length and angle between the last residue in the heavy chain and the first residue in the light chain, since there is no peptide bond between them. Besides, we normalize the steric clash loss by the number of non-bonded atom pairs in clash to stabilize the model optimization, as suggested in AlphaFold-Multimer [Evans et al., 2021].

$$\mathcal{L}_{viol} = \mathcal{L}_{bond-length} + \mathcal{L}_{bond-angle} + \mathcal{L}_{clash} \tag{19}$$

D   Ablation Study

We conducted ablation experiments on parts of the model and evaluated it on the test set, as shown in Table 5. The removal of the two-stage training resulted in a significant decline in all metrics, particularly with the SR dropping to 0, indicating that the two-stage training is crucial for model performance. The absence of epitope information led to a marked deterioration in the DockQ, iRMS, and LRMS metrics, highlighting the importance of epitope information on the docking quality and bias of the model. After removing ESM-PPI, there was a slight decrease in AAR and DockQ, while iRMS and LRMS increased, suggesting that ESM-PPI has a certain impact on the bias of the interface and ligand. The removal of mixed training also resulted in a slight decline in AAR and DockQ, with increases in iRMS and LRMS, indicating that mixed training has a notable effect on the overall performance of the model. Overall, the various components and training strategies of the IgGM model significantly influence its performance, with the two-stage training and epitope information being particularly critical for the docking quality and success rate of the model.

Table 5: Ablations performance for IgGM.

Method	AAR↑ CDR3	DockQ↑	iRMS↓	LRMS↓	SR↑
IgGM	0.360	0.246	6.579	19.678	0.433
w/o two stage training	0.160	0.072	10.260	30.961	0.000
w/o epotipe	0.326	0.069	14.609	36.967	0.050
w/o ESM-PPI	0.322	0.233	7.444	20.996	0.426
w/o mixed training	0.334	0.231	7.524	22.713	0.350

E   examples

We present additional examples of the de novo designs generated by our IgGM in Figure 7.

Figure 7: Samples of generated antibodies and nanobodies by IgGM.