RanBALL: An Ensemble Random Projection Model for Identifying Subtypes of B-Cell Acute Lymphoblastic Leukemia

Lusheng Li[1], Hanyu Xiao[1], Xinchao Wu[1], Zhenya Tang[2], Joseph D. Khoury[2], Jieqiong Wang[3], and Shibiao Wan[1]*

[1]Department of Genetics, Cell Biology and Anatomy, University of Nebraska Medical Center, Omaha, NE, USA

[2]Department of Pathology, Microbiology and Immunology, University of Nebraska Medical Center, Omaha, NE, USA

[3]Department of Neurological Sciences, University of Nebraska Medical Center, Omaha, NE, USA

*Correspondence: Shibiao Wan, swan@unmc.edu

ORCID: https://orcid.org/0000-0003-0661-2684

Abstract

As the most common pediatric malignancy, B-cell acute lymphoblastic leukemia (B-ALL) has multiple distinct subtypes characterized by recurrent and sporadic somatic and germline genetic alterations. Identifying B-ALL subtypes can facilitate risk stratification and enable tailored therapeutic design. Existing methods for B-ALL subtyping primarily depend on immunophenotyping, cytogenetic tests and genomic profiling, which would be costly, complicated, and laborious. To overcome these challenges, we present **RanBALL** (an ensemble **Ran**dom projection-based model for identifying **B-ALL** subtypes), an accurate and cost-effective model for B-ALL subtype identification. By leveraging random projection (RP) and ensemble learning, RanBALL can preserve patient-to-patient distances after dimension reduction and yield robustly accurate classification performance for B-ALL subtyping. Benchmarking results based on >1700 B-ALL patients demonstrated that RanBALL achieved remarkable performance (accuracy: 0.93, F1-score: 0.93, and Matthews correlation coefficient: 0.93), significantly outperforming state-of-the-art methods like ALLSorts in terms of all performance metrics. In addition,

29 RanBALL performs better than tSNE in terms of visualizing B-ALL subtype information.

30 We believe RanBALL will facilitate the discovery of B-ALL subtype-specific marker genes

31 and therapeutic targets to have consequential positive impacts on downstream risk

32 stratification and tailored treatment design. To extend its applicability and impacts, a

33 Python-based RanBALL package is available at https://github.com/wan-mlab/RanBALL.

Background

B-cell acute lymphoblastic leukemia (B-ALL) is a hematological malignancy that

originates from the precursor B-cells of the bone marrow. As the most common type of

acute lymphoblastic leukemia (ALL), B-ALL accounts for approximately 5,000 cases in

the United States each year, especially affecting children under the age of five (1,2). The

clinic diagnostic and biologic heterogeneity of B-ALL present a significant challenge in

terms of subtype classification and risk stratification (3,4). Previous studies have

highlighted the necessity of precise subtype identification for highly diverse therapeutic

approaches for each patient (5–8). So far, multiple distinct B-ALL subtypes have been

characterized through recurrent and sporadic somatic and germline genetic alterations,

e.g., BCR-ABL1 (Philadelphia (Ph) chromosome), TCF3-PBX1 (9), hypodiploid (10), etc.

Based on integrated genomic analysis of 1,988 childhood and adult cases, Gu et al. (11)

identified 23 B-ALL subtypes by chromosomal rearrangements, sequence mutations and

heterogeneous genomic alterations. In addition, another study (12) comprehensively

reviewed the etiologic heterogeneity of childhood acute lymphoblastic leukemia (ALL)

across different subtypes, highlighting the critical need for further investigations into risk

factors that are specific to each subtype.

Conventional methods for B-ALL subtype identification primarily depend on a

combination of morphological, immunophenotypic, cytogenetic, and molecular

characteristics (13,14). With advancements in the next-generation sequencing (NGS)

(15,16), RNA-seq has become an effective tool to unveil chromosomal rearrangements in

individual tumors for genetic or clinical marker discovery (11,17). It has been increasingly

investigated as an advanced diagnostic method for ALL clinical trials, underscoring its capability to accurately diagnose specific molecular subtypes (18,19). In addition, large cohort studies for new subtype detection and rapid classification with large-scale datasets raise more interest in the progress of the precision medicine (20–22). Categorizing new B-ALL subtypes typically involves integrating different types of NGS techniques such as whole-genome sequencing (WGS) (23), whole-exome sequencing (WES) (24), cytogenetic assays (25), etc. However, these methods for subtype identification would be costly, complicated, and time-consuming in clinical applications. In addition, extensive manual review of the results from these analyses like fusion detection and mutation calling is required, which is a laborious process.

Recognizing these challenges, the application of machine learning (ML) models to B-ALL subtype identification has emerged as a promising approach to revolutionize our understanding of this disease and improve patient outcomes (26). In recent years, multiple subtype classification tools based on different ML algorithms have been introduced based on well-defined B-ALL subtypes from WHO-HAEM5 (27), and ICC (28) classification system. For instance, Allspice (17) was developed to predict the B-ALL subtypes and driver genes based on a centroid model. However, centroid methods in Allspice may not fit in scenarios involving overlapping classes or imbalanced datasets. In addition, ALLSorts (29) was introduced to classify 18 B-ALL subtypes with logistic regression, which nevertheless could perform poorly as the relationships between features and subtypes were more complicated than a simple logistic model. Furthermore, ALLCatchR (30) was proposed based on integrating linear support vector machine (SVM) and gene set-based nearest-neighbor models. However, nearest-neighbor models in ALLCatchR relied heavily on calculating distances between data points, which could be computationally expensive for large datasets, especially as the number of samples or features increased. Recently, MD-ALL (31) was developed to predict B-ALL subtypes using SVM and PhenoGraph algorithms. Nevertheless, PhenoGraph's clustering relied on the number of nearest neighbors to construct a graph, which might significantly affect classification results.

To address these concerns, we presented **RanBALL** (an Ensemble **Ran**dom Projection-Based Model for Identifying **B**-Cell **A**cute **L**ymphoblastic **L**eukemia Subtypes), an accurate and cost-effective model for B-ALL subtype identification based on transcriptomic profiling only. By leveraging the RP, RanBALL transformed the high-dimensional feature of gene expression data to lower-dimensional representations, effectively minimizing redundant and irrelevant information. To obtain robust performance of RanBALL model, multiple RPs were applied to the original gene expression matrix. The resulting dimension-reduced matrices were then used for an ensemble of SVM classifiers to generate the final subtype predictions. Benchmarking results based on a comprehensive B-ALL dataset demonstrated that RanBALL achieved significantly and consistently better performance than state-of-the-art B-ALL subtyping methods in term of accuracy, F1-score and Matthews correlation coefficient. We anticipate that RanBALL will bring substantially positive and direct impacts on clinical diagnosis improvement, risk stratification, and the development of personalized treatment strategies for B-ALL patients.

Methods

B-ALL datasets

The RNA-seq data and clinical information of B-ALL samples were obtained from St. Jude Cloud (https://pecan.stjude.cloud/static/hg19/pan-all/BALL-1988S-HTSeq.zip). The dataset included 1988 samples that were classified as 23 B-ALL subtypes from the study (11). In data processing, samples with two subtypes and those identified as "other" categories were filtered out. Additionally, the samples were processed by referring to the classification architecture outlined in the ALLSorts classifier (29). Due to the limited number of samples in subtypes "ZNF384-like" and "KMT2A-like", "ZNF384-like" samples were merged with "ZNF384" samples to form a broader category labeled the "ZNF384 Group", and "KMT2A-like" samples were merged with "KMT2A" samples to form a broader category labeled the "KMT2A Group". Samples classified as the "CRLF2(non-

Ph-like)" subtype were excluded due to limited sample size. After filtering, the B-ALL

dataset contained a total of 1,743 samples across 20 distinct categories (Fig. 1A). The

breakdown of the B-ALL dataset among the various subtypes was depicted in the pie

chart (Fig. 1A). This B-ALL dataset was very imbalanced, with a few categories (such as

Ph-like, High hyperdiploid and ETV6-RUNX1) taking up a significantly larger proportion

(i.e., 18.6%, 15.4% and 10.8%) of the total compared to others. As illustrated in the Fig.

1B, the majority (about 81.0%) of patients for the B-ALL dataset belonged to the

childhood and AYA groups. The distribution showed a higher concentration of B-ALL

cases in younger age groups, with notable peaks in childhood and young adulthood.

Figure 1. Overview of B-ALL subtype identification study using RanBALL

framework. (A) The breakdown of the B-ALL dataset. The pie chart showed the

distribution of 1,743 B-ALL samples across 20 molecular subtypes, each represented by

a distinct color. Percentages reflected the relative prevalence of each subtype within the

dataset. **(B)** The age distribution of the B-ALL dataset. The histogram illustrated the number of patients within each age group across three categories: childhood (red), adolescent and young adult (AYA, green), and adult (blue). **(C)** The framework of RanBALL. The feature dimension of preprocessed data was reduced by RP, and an ensemble of SVM classifier was trained on multiple dimensionally reduced matrices. In this framework, the dimensionality to be reduced to was predefined as 1200. The symbol m represents the m-th reduced-dimensional data matrix, while n denotes the predicted subtype. The RanBALL framework was designed to classify distinct subtypes, with the final prediction obtained through an aggregated output from the ensemble. Beyond subtype prediction, RanBALL also facilitated enhanced visualization of subtype clusters and the identification of subtype-specific markers, providing additional insights into the biological characteristics of each subtype. **(D)** Data preprocessing pipeline. The flowchart outlines the multi-step preprocessing applied to the RNA-seq data, starting with raw read counts and ending with log-transformed TPM values for 21,365 genes from 1,743 selected samples.

RanBALL framework

RanBALL is an ensemble random projection-based multi-class classification model specifically designed for B-ALL subtyping using gene expression profiling. Leveraging the RP and SVM techniques, our model accurately and efficiently identifies distinct B-ALL subtypes, offering reliable diagnostic insights that can significantly support clinical decision-making. With the gene expression data of B-ALL patients as input, RanBALL is versatile and accepts various types of gene expression data as input, including raw counts, Fragments Per Kilobase of transcript per Million mapped reads (FPKM), and Transcripts Per Million (TPM). Different data types would be transformed into $\log_2$(TPM +1) for predicting the B-ALL subtypes. The processing pipeline encompassed four main steps: (1) data preprocessing and normalization, (2) RP-based dimension reduction, and (3) ensemble learning for multi-class classification, as depicted in Fig. 1C. This framework is particularly suited for the high-dimensional nature of gene expression data and the complex task of B-ALL subtyping, offering both accurate classification and improved visualization capabilities.

Data preprocessing

The data preprocessing pipeline was illustrated as Fig. 1D. For the raw gene expression counts of 1988 B-ALL samples, only the gene expressed in at least 75% of the samples

were retained, resulting in and finally 21,635 of the 52,007 original genes were kept. This

filtering step eliminated rarely expressed genes that could introduce noise into the

analysis. Subsequently, the raw read counts were then normalized to Transcripts Per

Million (TPM), which allows for biological meaningful comparisons between different

samples by adjusting for variations in the sequencing depth between samples (32). To

prevent the inherent skewness of gene expression data, TPM values were transformed

using the formula $\log_2(\text{TPM}+1)$. Ultimately, the log-transformed TPM for subsequent

model training and B-ALL subtype identification.

Random projection

RP is a dimensionality reduction technique that aims to reduce the dimensionality of high-

dimensional data while approximately preserving pairwise distances between data points.

It is based on the Johnson–Lindenstrauss lemma (33) which provides a theoretical

justification that a high-dimensional dataset can be approximately projected into a low-

dimensional space while approximately preserving pairwise distances between data

points. Specifically, the original D-dimensional data are projected onto a d-dimensional

subspace through multiplying the original D-dimensional data matrix by the $d \times N$ random

projection matrix. Namely,

$$\mathbf{A} = \frac{1}{\sqrt{d}}\mathbf{R}\mathbf{T} \in \mathbb{R}^{d \times N}, \quad \mathbf{T} \in \mathbb{R}^{d \times N}, \quad \mathbf{R} \in \mathbb{R}^{d \times D}, \tag{1}$$

where $\mathbf{R}$ is random projection matrix, $\mathbf{T}$ is the original transcriptomic dataset, with D

corresponding to the number of gene features and N denoting the number of B-ALL

samples. The random projection matrix $\mathbf{R}$ should conform to any distributions with zero

mean and unit variance, so that the random projection matrix $\mathbf{R}$ will give a mapping that

satisfies the Johnson–Lindenstrauss lemma. For computational efficiency and the

requirement of sparseness, we implemented a highly sparse RP method (34) This

method determines the elements of $\mathbf{R}$ (i.e., $r_{i,j}$) as follows:

$$r_{i,j} = \sqrt{p} \begin{cases} 1, & \text{with probability } \dfrac{1}{2p}, \\[2mm] 0, & \text{with probability } 1 - \dfrac{1}{p}, \\[2mm] -1, & \text{with probability } \dfrac{1}{2p}, \end{cases} \quad \begin{aligned} &\text{where } i = \{1, \dots, d\}, \\ &\qquad j = \{1, \dots, D\} \end{aligned} \tag{2}$$

In accordance with the recommendation (34), we selected $p = \sqrt{D}$.

Ensemble learning model

To obtain reliable and robust performance, multiple RPs were applied into the original data matrix. The transformed low dimensional data matrix obtained from Eq. 1 was used for training an ensemble of SVM classifiers. To develop a robust model, we ensembled the predicted probability scores of each B-ALL subtype for low-dimensional data matrix and obtained an ensemble model. The ensemble score S_m^{en} for each subtype was calculated by averaging all the prediction probability scores from each m-th SVM model in the ensemble:

$$S_m^{en} = \frac{1}{M} \sum_{m=1}^{M} \sum_{\gamma \in S_m} \sum_{n=1}^{N} \alpha_{m,\gamma} y_{m,\gamma} K(\mathbf{A}_{train}, \mathbf{A}_{test}), \tag{3}$$

where S_m is the set of support vector indexes corresponding to the m-th SVM, M is the ensemble size, $\alpha_{m,\gamma}$ are the Lagrange multipliers, N is the number of predicted subtypes, $y_{m,\gamma}$ is the class label for each subtype, $K(\cdot, \cdot)$ is the kernel function. Here, we used linear kernel for SVM after evaluating different kernel options. The $\mathbf{A}_{train}$ represents the projected RNA-seq data for training B-ALL samples, and the $\mathbf{A}_{test}$ corresponds to the test samples. To achieve optimal performance, we tried to optimize multiple hyperparameters including ensemble size (i.e., number of RPs to be used for ensemble), reduced dimensions, etc. Details can be found in the Results section below.

RanBALL visualization

To capture both the global structure of the data and the specificity of subtype predictions, we developed a new visualization method for RanBALL (for ease of convenience, we

refer to this as RanBALL visualization). Specifically, we utilized a weighted combination of

two key matrices: a dimension-reduced feature matrix and a sample-to-subtype matrix

derived from prediction results. The dimension-reduced feature matrix was obtained

through RP techniques. This matrix was then normalized using Z-Score, centering and

scaling the data along each dimension across samples. The prediction subtype for each

sample was encoded by one-hot encoding to create a sample-to-subtype matrix, where

each row corresponds to a sample, and each column represents a subtype. This matrix

was then normalized using a Z-Score transformation across all samples to ensure that

the data is centered and scaled, making the features comparable with the dimension-

reduced matrix. These two matrices were then combined with different weights to

formulate the final visualization matrix, combining the predicted subtype information with

the dimensional features. We defined w as the weight ratio of the dimension-reduced

feature matrix over the sample-to-subtype matrix. This weight can be adjusted to

emphasize either the reduced feature space ($w > 1$) or the predicted subtype information

($0 < w < 1$) in the final visualization. This combined matrix served as the input for t-SNE

visualization (35), allowing for a more informative and potentially more biologically

relevant representation of the data. The predicted subtypes can provide additional

information with the original gene expression profiling data for clustering data points in

visualizations. Furthermore, the adjustable weight parameter provides flexibility for

researchers to emphasize either global patterns or subtype-specific characteristics. By

combining the global patterns from dimension-reduced feature matrix with the subtype-

specific information from RanBALL predictions, the visualization provides a more faithful

and informative representation of the data.

Subtype-specific differential gene expression analysis

For subtype-specific differentially gene expression (DGE) analysis, the expected raw

counts from B-ALL samples were used. Genes with low read counts were filtered out

using a CPM cutoff threshold equivalent to a count of 10 reads. Normalization factors

were then calculated using the TMM method (36), and the counts was further processed

using the *voom* transformation. The normalized counts were analyzed with the *lmFit* and

eBayes functions from the *limma* R package v3.54.2 (37). The cutoffs of FDR < 0.05, and

$|\log_2 FC| > 1$ were applied to define significantly differentially expressed genes. Heatmap

plots were generated by Pheatmap package (1.0.12) (38).

Performance evaluation

248   To evaluate model performance, we measured accuracy (Acc), F1-score ($F1$), and

249   Matthews correlation coefficient (MCC) (39) as follows:

$$Acc = \frac{TP + TN}{TP + FP + FN + TN} \tag{4}$$

$$F1 = \frac{2TP}{2TP + FP + FN} \tag{5}$$

$$MCC = \frac{TP \times TN - FP \times FN}{\sqrt{(TP + FP)(TP + FN)(TN + FP)(TN + FN)}} \tag{6}$$

True positives (TP) denote the count of samples predicted to possess the specific

subtype, which aligns with clinical documentation. False positives (FP) represent the

count of samples incorrectly classified into different categories. True negatives (TN)

indicate the count of samples predicted as 'other' that genuinely do not belong to the

specified subtype category, while false negatives (FN) refer to the count of samples

predicted as 'other' but are indeed found within the specified subtype category. The F1-

score is a statistical measure used to evaluate the accuracy of a classification model,

which is a way to balance the trade-off between precision and recall. A high precision

might indicate a low tolerance for false positives, while a high recall might indicate a low

tolerance for false negatives. The F1-score helps to find a balance between these two

factors, making it a useful metric for evaluating the overall quality of a classification

model. It is particularly useful in situations where the class distribution is imbalanced. In

addition, MCC is a balanced measure that takes into account true and false positives and

negatives. This makes it particularly helpful in imbalanced datasets where the number of

positive instances may be very different from the number of negative instances.

Results

RanBALL preserves sample-to-sample distance

To explain the contributions of RP for dimension reduction in RanBALL, we investigated the degree of distortion caused by dimension reduction and compared the correlation of sample-to-sample distances after shrink with PCA (40), t-SNE (35) and UMAP (41), respectively, in different levels. We conducted Pearson correlation analysis to assess the similarities in sample-to-sample distances between the original and dimension-reduced data. As depicted in Fig. 2, RP achieved very high similarities in sample-to-sample distance, with the Pearson correlation coefficients exceeding 0.93. For example, when reducing the data to 1200 dimensions (from 21,635 to 1200), the correlation remained high at 0.94, indicating the preservation of almost all embedded information after dimension reduction. The remarkable performance of RP can be attributed to several key factors. One critical factor is RP's ability to preserve pairwise distances (42), which plays a central role in maintaining high correlation coefficients between the original and projected data. This property is theoretically supported by the Johnson-Lindenstrauss lemma (34), which guarantees that a set of points in high-dimensional space can be projected onto a lower-dimensional space while approximately maintaining relative distances with high probability. Furthermore, RP's linear transformation ensures that the overall structure of the data (43), including relative distances between samples, is preserved without introducing complex non-linear distortions. This simplicity not only enhances computational efficiency but also minimizes the risk of overfitting to specific data patterns. In contrast, correlations observed with PCA, t-SNE, and UMAP were notably lower (overall below 0.67, with a minimum of 0.32). This disparity in performance can be explained by the inherent characteristics of these methods. While effective for linear dimensionality reduction, PCA focuses on preserving directions of maximum variance, potentially losing information crucial for maintaining sample-to-sample distances but not significantly contributing to overall variance. As non-linear techniques designed for dimension reduction and low-dimensional visualization, t-SNE and UMAP focus on preserving local structure and often distort global structure. These could be the

reasons to explain their poor performance in preserving overall sample-to-sample

distances in this context. RP's exceptional performance in preserving sample-to-sample

distances while significantly reducing dimensionality makes it particularly well-suited for

the high-dimensional, complex nature of gene expression data in B-ALL subtyping.

Figure 2. RP preserves sample-to-sample information better than state-of-the-art
dimension reduction methods including PCA, t-SNE, and UMAP for RanBALL
subtype identification. We compared RP with other state-of-the-art dimensionality
reduction methods across different dimensions (400, 600,…, 2000). The upper triangular
section of each matrix displayed the PCC between the sample-to-sample distances in the
original high-dimensional space (Ori.) and the corresponding reduced-dimensional space
for each method. Higher PCC values indicated better preservation of the original data
structure. RP consistently achieved higher PCC (highlighted in red) that outperformed

PCA, t-SNE, and UMAP. The lower triangular section provided scatter plots of pairwise
distances between samples before and after dimensionality reduction, illustrating how
well each method preserved the relative distances between points.
312

The ensemble RP model performs better than individual RP models

To ensure the robust and stable performance of RanBALL, we applied ensemble learning

to the predicted results obtained after dimensionality reduction with multi-class SVM. By

aggregating predictions from multiple models, ensemble methods typically lead to better

performance than relying on individual models. Additionally, ensemble methods help to

reduce overfitting by averaging the biases of different models, thus providing a more

generalizable solution. The original dimension (21,365) was reduced to a low dimension

(we tried from 400 to 2000, with an interval of 200), to test the performances of different

dimensions. Fig. 3A showed the performance of comparing ensemble models and

individual models based on 100 runs of RPs. Focusing on overall accuracy metrics (Fig.

3A), the results revealed that the ensemble method's prediction exhibited greater

performance and stability with statistical significance compared to individual tests across

all dimensions, indicating ensemble method's superiority in generating stable and

trustworthy prediction outcomes. To find the optimal reduced dimensionality, multiple

dimensions of RP were applied in the model. The results showed that there was no

significant difference for different dimensions when the number of dimensions is no less

than 600 (Fig. 3B). The performance was stabilized when the dimensionality is no less

than 1200. In addition, the performance variations of individual RP models with 100 times

of running RP were limited when the dimensionality reached 1200 (Fig. 3B). Based on

these results, 1200 was chosen for the subsequent model training. Next, we compared

the performance with different ensemble sizes. Fig. 3C demonstrated that the ensemble

size of 30 had more stable and robust performance in term of accuracy. Based on this

finding, we selected the ensemble size of 30 for the model training. The empirical

approach to determining these parameters ensures that the final model configuration is

well-suited to the B-ALL subtyping with complex gene expression data.

Figure 3. The performance of RanBALL in different RP models. (A) The ensemble
RP model outperformed individual RP models across different reduced dimensions. Red
boxes represented the accuracy distribution of the ensemble method aggregating 30 RPs,
while green boxes denoted the accuracy distribution of individual classifiers on single RP.
Statistical significance was assessed using the Wilcoxon signed-rank test, with p-values
displayed above each comparison. **(B)** The model performance across different reduced
dimensions. The violin plot illustrated the distribution of accuracy scores for dimensions
ranging from 100 to 2000, with an interval of 200. **(C)** The model performance across
different ensemble sizes. Violin plots depicted the distribution of accuracy scores for
ensemble sizes ranging from 5 to 50. Black dots represented individual data points, while
the violin shape showed the probability density of the data.

RanBALL outperforms state-of-the-art methods for B-ALL subtyping

To assess the performance of the RanBALL model and its potential generalizability to

unseen data, we employed a rigorous 100 times 5-fold cross-validation (CV) tests on an

RNA-seq dataset comprising 1743 B-ALL samples with 20 subtypes as described in Fig.

1A. Our RanBALL model yielded impressive results exhibiting an accuracy of 93.35%, an

F1-score of 93.10% and an MCC of 0.93 (Fig. 4A). These metrics collectively offered a

comprehensive evaluation of the model's efficacy. Given its exceptional performance

across these metrics, the RanBALL model demonstrated significant promise for B-ALL

subtyping. Additionally, we conducted a comparative analysis of the performance

between RanBALL and ALLSorts (29), a well-established logistic regression classifier for

B-ALL subtyping with the same data. As illustrated in Fig. 4A, RanBALL exhibited

superior performance compared to ALLSorts in terms of Accuracy, F1-score and MCC.

Notably, the superior F1-score of RanBALL suggested a more balanced trade-off

between precision and recall relative to ALLSorts. The MCC performance matrix offered a

balanced assessment even in scenarios where classes exhibit disparate sizes, indicating

that RanBALL demonstrated superior performance particularly in multiclass classification

settings with imbalanced class distributions compared to ALLSorts.

Subsequently, we applied the RanBALL model to hold-out tests to further demonstrate

the superiority of RanBALL over state-of-the-art methods. Specifically, we selected one of

the hold-out test sets, which was comprised of 521 samples, generated by randomly

sampling 30% of the entire B-ALL dataset. The RanBALL model demonstrated a

remarkable accuracy of 94.24% on this held-out test subset. The prediction probabilities

of each test sample were shown in Fig. 4B, demonstrating the model's consistent ability

to maintain high confidence levels for accurate predictions. The robust performance of

the model, evidenced by high-probability predictions, indicated its proficiency in

distinguishing intrinsic data patterns, thereby yielding confident and reliable outcomes.

Notably, it exhibited the capability to deliver accurate predictions even for subtypes

characterized by limited sample sizes. However, it's important to acknowledge that

prediction probabilities for such subtypes may not attain exceptionally high levels. The 30%

held-out test was also performed for ALLSorts, which achieved an accuracy of 89.64% on

the same test dataset. The confusion matrices were illustrated in Fig. 4C-D, providing a

detailed breakdown of the model's prediction ability for each subtype in test data. Most

significantly, RanBALL achieved superior classification accuracy for the Ph-like subtype,

correctly identifying 91 out of 97 patients, surpassing ALLSorts' performance of 84 correct

classifications. Additionally, RanBALL showed improved performance in distinguishing

Low hyperdiploid, accurately classifying 13 out of 15 cases, compared to ALLSorts' 8

correct classifications. For some subtypes with similar characteristics and features, it is

likely for the model to incorrectly predict the sample of one subtype to be another group.

For example, 2 samples with Ph subtype were wrongly predicted in the Ph-like by

RanBALL, while 3 were wrongly classified as the Ph subtype in the Ph-like by ALLSorts.

This situation also occurred in the subtypes related to chromosome rearrangement (Near

haploid, Low hyperdiploid, and High hyperdiploid), suggesting that B-ALL patients in

these subtypes with similar characteristics and features were difficult to distinguish.

Figure 4. Comparing RanBALL with state-of-the-art methods like ALLSorts for B-
ALL subtyping. (A) Comparing RanBALL and ALLSorts for identifying B-ALL subtypes in
terms of various performance metrics. Accuracy, F1-score and MCC were used for
evaluating model performance. Box plots illustrated the distribution of Accuracy, F1-
score, and MCC across 100 times 5-fold cross validation. **(B)** Prediction probability
distribution for the 30% held-out test set using RanBALL. Each point represents the
probability of a sample (out of 521) being classified into a specific B-ALL subtype.
Specifically, the blue dots indicate the specific subtype that the RanBALL model predicts
to align with the categories on the horizontal axis. **(C, D)** Confusion matrices for the 30%
held-out test set, comparing RanBALL (**C**) and ALLSorts (**D**) performance. Each element
of the matrices shows the number of samples classified, with the diagonal representing
correct classifications (True Positives). Color intensity correlates with the number of
samples.

RanBALL provides better data visualization compared to tSNE

RanBALL demonstrated superior visualization capabilities compared to traditional methods by incorporating predicted subtype information. We selected the t-SNE, one of the powerful and representative methods for visualizing high-dimensional data, to compare the performance of visualization. Fig. 5A illustrated the effectiveness of RanBALL in visualizing B-ALL samples, where the majority of subtypes were well-clustered, reflecting the model's capability to maintain and highlight the inherent structure in the data. This visualization allowed for easy identification and interpretation of the 20 different subtypes, ranging from common subtypes like BCL2/MYC and DUX4 to rarer subtypes such as ZNF384 Group and iAMP21. Each subtype, represented by different colors and labels, formed tight, distinct clusters. In contrast, Fig. 5B presented a conventional t-SNE visualization without the integration of predicted subtype information, where subtype boundaries were less distinct and overlap more significantly. Subtypes such as High hyperdiploid, KMT2A Group, PH and Ph-like did not cluster as clearly, indicating that conventional tSNE was unable to distinguish subtypes of B-ALL patients with similar gene expression patterns. The difference between the visualization results by RanBALL and tSNE underscored the value of RanBALL's approach in enhancing the interpretability and informative visual representations of complex transcriptomic data. By leveraging predicted subtype information, RanBALL not only improved visual clarity but also potentially revealed biologically meaningful relationships between subtypes. This enhanced visualization technique could provide valuable information for researchers in identifying patterns, outliers, and potential new subgroups within B-ALL samples, ultimately leading to better understanding and classification of this complex disease.

Figure 5. Comparing B-ALL and state-of-the-art visualization methods like tSNE for visualizing B-ALL subtype groups. (A) RanBALL visualization of the reduced dimension matrix incorporating predicted subtype information. **(B)** t-SNE visualization of the reduced dimension matrix with conventional gene expression profiling information only. The same color scheme was used in the two plots.

Subtype-specific differential gene expression analysis of B-ALL patients

To identify and investigate the subtype-specific biomarkers for each B-ALL subtype, we performed subtype-specific differential gene expression analysis. Fig. 6A illustrated the differential expressed genes (DEGs) between Ph-like B-ALL and the rest subtypes. The expression plots of the upregulated DEG ENAM across all B-ALL samples were shown in Fig. 6C, highlighting its specific overexpression in the Ph-like subtype. The ENAM gene was specifically expressed at the samples with Ph-like subtype. The heatmap displayed the expression profiles of top 20 DEGs (Fig. 6B). It indicated the potential differences among subtypes within the biological functions and processes. Among the most upregulated genes, CRLF2, one of the most important genes in Ph-like ALL, was consistent with its known role in activating JAK-STAT signaling in a subset of Ph-like cases (44,45). Other significantly overexpressed genes, including GPR110, ENAM, LDB3, and IGJ, suggesting alterations in cell adhesion, signaling, and immunoglobulin production (44,46,47). Notably, SPATS2L overexpression has been associated with poor prognosis (48,49). We also conducted differential gene expression analysis on the PAX5alt subtype (Fig. 6D-F). These upregulated genes may play crucial roles in promoting cell proliferation, survival, and signaling pathways in PAX5alt B-ALL. For instance, TPBG was upregulated in high-risk cytogenetic subgroups and overexpressed

on the plasma membrane of lymphoblasts collected at relapse in patients with B-cell

precursor ALL (50). Similarly, KSR2, a kinase suppressor of Ras 2, has been implicated

in dysregulation of multiple signaling (51), suggesting a similar altered signaling pathway

in PAX5alt B-ALL. Additionally, TIFAB has been shown to regulate USP15-mediated p53

signaling in stressed and malignant hematopoiesis (52). Interestingly, NFATC4 significant

upregulation in PAX5alt B-ALL contrasts with its significant downregulation in Ph-like B-

ALL, highlighting distinct transcriptional programs between these subtypes. For

differential gene expression analysis between High hyperdiploid and other subtypes (Fig.

6G~I), the upregulated gene DDIT4L has been identified as therapeutic targets in PDX

ALL carrying the recently described DUX4-IGH translocation (53). Notably, the

upregulated gene OVCH2 was observed that it was downregulated in ALL (54,55).

Additionally, S100A16 has been implicated in suppressing the growth and survival of

leukemia cells in adults with Ph-negative B-ALL (56). The subtype-specific differential

gene expression analysis for the remaining B-ALL subtypes were presented in Fig. S1-S6.

These subtype-specific differential gene expression analyses revealed distinct molecular

signatures and characteristics across B-ALL subtypes, which could expand our

understanding of molecular mechanisms underlying different subtypes.

Figure 6. Subtype-specific differential gene expression analysis within B-ALL subtypes. (A, D, G) Volcano plots illustrated differential expression genes between specific B-ALL subtypes and all other subtypes. The x-axis represented log2 fold change, while the y-axis showed -log10(p-value). Red dots indicated 20 significantly up-regulated genes, blue dots represented 20 significantly down-regulated genes. Top 20 DEGs were labeled, with the most significant gene circled in red. **(A)** Ph-like vs. rest; **(D)** PAX5alt vs. rest; **(G)** High hyperdiploid vs. rest. **(B, E, H)** Heatmaps displayed expression patterns of the top 20 DEGs for each subtype comparison. Rows represented genes, columns represented samples. Color scale ranges from blue (low expression) to red (high expression). Hierarchical clustering dendrograms were shown for both genes and samples. Sidebar annotations indicated sample subtypes and relative level of gene expression. **(B)** Ph-like vs. rest; **(E)** PAX5alt vs. rest; **(H)** High hyperdiploid vs. rest. **(C, F, I)** The expression plot of the up-regulated DEG for Ph-like subtype. RanBALL plots visualized the expression levels of the significantly up-regulated gene for each subtype across all B-ALL samples. Each point represented a sample, colored by expression intensity (red: high, grey: low). Numbers indicated different B-ALL subtypes. **(C)** DEG for Ph-like (ENAM); **(F)** DEG for PAX5alt (TPBG); **(I)** DEG for High hyperdiploid (LOXHD1).

Discussion

In this study, we introduced an ensemble-based model, RanBALL, which integrated ensemble RP and SVM techniques to accurately identify B-ALL subtypes using solely RNA-seq data. One of the key strengths of RanBALL lies in its ability to preserve sample-to-sample distances after dimensionality reduction, as evidenced by the high Pearson correlation coefficients (PCC) compared to PCA, t-SNE, and UMAP (Fig. 2). This preservation of data structure is crucial for accurate subtype classification and represents a significant advantage over traditional dimensionality reduction methods. Moreover, the integration of ensemble learning with RP enhanced the stability and reliability of predictions, mitigating the risks associated with imbalanced datasets and reducing overfitting. The experiments indicated that the ensemble learning method achieved superior stability and better performance than the individual RP models (Fig. 3A). In addition, RanBALL achieved remarkable performance metrics (accuracy: 93.35%, F1-score: 93.10%, MCC: 0.93) that significantly surpassed those of ALLSorts (Fig. 4A), one of the current state-of-the-art methods. This is particularly important given the heterogeneous nature of B-ALL, where accurate classification can directly influence risk stratification and treatment decisions. The high Moreover, MCC (92.62%) specifically indicated RanBALL's effectiveness in handling the inherent class imbalance present in B-ALL subtypes, which is a common challenge in clinical datasets. The application of ML models in B-ALL subtype identification demonstrated the feasibility of leveraging complex datasets to discover subtle differences among patients. This approach overcame the limitations of traditional subtyping methods, which often rely on a limited set of markers and may not capture the full spectrum of disease heterogeneity.

Beyond classification, our enhanced visualization approach, which incorporates predicted subtype information, demonstrated better visualization capabilities compared to traditional methods. The incorporation of predicted subtype information into visualizations resulted in more distinct clusters, facilitating the discovery of novel subtype-specific markers. The subtype-specific differential gene expression analysis revealed distinct

gene signatures that could serve as therapeutic targets or prognostic indicators across B-

ALL subtypes, providing valuable insights into the translational research.

However, there is still room for improvement in certain B-ALL subtypes, necessitating

further enhancement of prediction capabilities. First, future studies should aim to validate

our models in more diverse and independent cohorts to ensure their broad applicability.

Second, the predictive performance of our models could be influenced by technical and

biological confounders (57), such as batch effects and sample quality. Rigorous data

preprocessing and quality control measures will be essential to mitigate these factors in

future work. Some common batch-effect correction methods, like ComBat (58), can be

applied to mitigate the batch effects to better address real-world challenges and facilitate

clinical applications (59). Additionally, the imbalance among B-ALL subtypes within the

dataset may also potentially impede model performance. To address this issue, data

augmentation techniques (60) can be applied to augment the representation of minority

subtypes.

Furthermore, the integration of additional multi-omics and multi-modal data types, such

as genetic (61,62), epigenetic (63,64) and imaging data (65,66), may potentially enhance

the accuracy and reliability of ML models in B-ALL subtype identification. The advent of

single cell sequencing technologies has revolutionized our ability to dissect heterogeneity

of B-ALL, enabling the characterization of cellular subpopulations and their functional

states at an unprecedented resolution. The integration of multi-scale multi-omics and

multi-modality can provide valuable insights into the molecular landscape of B-ALL

subtypes and inform personalized therapeutic approaches.

We anticipate that the deployment of RanBALL will yield direct positive impacts on clinical

diagnosis, personalized treatment strategies, and risk stratification within the realm of

biomedical research and clinical settings. This is particularly essential as distinct B-ALL

subtypes may respond differentially to various treatments and are associated with

diverse outcomes and survival rates. Moreover, precise subtype identification can aid

clinicians in selecting the most effective treatment strategies for each patient. To facilitate further extending and accessibility of RanBALL, we have developed an open-source Python package, available at https://github.com/wan-mlab/RanBALL.

Acknowledgements

The authors would like to express our gratitude to St. Jude Cloud platform (https://www.stjude.cloud), which provided publicly accessible genomic data. Special thanks to all members of Dr. Wan's lab for insightful discussions. The abstract of this work was published at AACR Annual Meeting 2024 (67).

Authors' contributions

L.L.: data preprocessing, machine learning model development, data analysis and interpretation, manuscript preparation, editing, and review. H.X.: data analysis and interpretation, manuscript preparation, editing, and review. X.W.: manuscript preparation, editing, and review. Z.T.: manuscript editing and review. J.D.K.: manuscript editing and review. J.W.: manuscript editing and review. S.W.: study concept and design, manuscript editing and review.

Data availability

The RNA-seq data of B-ALL samples can be publicly accessed from St. Jude Cloud (https://pecan.stjude.cloud/static/hg19/pan-all/BALL-1988S-HTSeq.zip).

Code availability

The RanBALL package can be accessed at https://github.com/wan-mlab/RanBALL.

Competing Interests

The authors declare no conflict of interest.

Funding information

Research reported in this publication was supported by the National Cancer Institute of the National Institutes of Health under Award Number P30CA036727, and by the Office Of The Director, National Institutes Of Health of the National Institutes of Health under Award Number R03OD038391. This work was supported by the American Cancer Society under award number IRG-22-146-07-IRG, and by the Buffett Cancer Center, which is supported by the National Cancer Institute under award number CA036727. This work was supported by the Buffet Cancer Center, which is supported by the National Cancer Institute under award number CA036727, in collaboration with the UNMC/Children's Hospital & Medical Center Child Health Research Institute Pediatric Cancer Research Group. This study was supported, in part, by the National Institute on Alcohol Abuse and Alcoholism (P50AA030407-5126, Pilot Core grant). This study was also supported by the Nebraska EPSCoR FIRST Award (OIA-2044049). This work was also partially supported by the National Institute of General Medical Sciences under Award Numbers P20GM103427 and P20GM130447. This study was in part financially supported by the Child Health Research Institute at UNMC/Children's Nebraska. This work was also partially supported by the University of Nebraska Collaboration Initiative Grant from the Nebraska Research Initiative (NRI). The content is solely the responsibility of the authors and does not necessarily represent the official views from the funding organizations.

Reference:

1. Hunger Stephen P., Mullighan Charles G. Acute Lymphoblastic Leukemia in Children. N Engl J Med. 373(16):1541–52.

2. Chouvarine P, Antić Ž, Lentes J, Schröder C, Alten J, Brüggemann M, et al. Transcriptional and Mutational Profiling of B-Other Acute Lymphoblastic Leukemia for Improved Diagnostics. Cancers. 2021 Nov 12;13(22):5653.

3. Avraham Frisch, Yishai Ofran. How I diagnose and manage Philadelphia chromosome-like acute lymphoblastic leukemia. Haematologica. 2019 Oct

30;104(11):2135-43.

4. Meyers S, Alberti-Servera L, Gielen O, Erard M, Swings T, De Bie J, et al.
Monitoring of Leukemia Clones in B-cell Acute Lymphoblastic Leukemia at
Diagnosis and During Treatment by Single-cell DNA Amplicon Sequencing.
HemaSphere   [Internet].   2022;6(4).   Available   from:
https://journals.lww.com/hemasphere/fulltext/2022/04000/monitoring_of_leuke
mia_clones_in_b_cell_acute.2.aspx

5. Bassan R, Hoelzer D. Modern Therapy of Acute Lymphoblastic Leukemia. J Clin
Oncol. 2011 Feb 10;29(5):532-43.

6. Mullighan CG. How advanced are we in targeting novel subtypes of ALL? Acute
Leuk Myelodysplasia Adv Controv. 2019 Dec 1;32(4):101095.

7. Jeha S, Choi J, Roberts KG, Pei D, Coustan-Smith E, Inaba H, et al.
Clinical Significance of Novel Subtypes of Acute Lymphoblastic Leukemia in
the Context of Minimal Residual Disease-Directed Therapy. Blood Cancer
Discov. 2021 Jul 1;2(4):326-37.

8. Lee SHR, Yang W, Gocho Y, John A, Rowland L, Smart B, et al. Pharmacotypes
across the genomic landscape of pediatric acute lymphoblastic leukemia and
impact on treatment response. Nat Med. 2023 Jan 1;29(1):170-9.

9. Shirai R, Osumi T, Sato‑Otsubo A, Nakabayashi K, Mori T, Yoshida M, et al.
Genetic features of B‑cell lymphoblastic lymphoma with *TCF3‑PBX1*.
Cancer Rep. 2022 Sep;5(9):e1559.

10. Holmfeldt L, Wei L, Diaz-Flores E, Walsh M, Zhang J, Ding L, et al. The
genomic landscape of hypodiploid acute lymphoblastic leukemia. Nat Genet.
2013 Mar;45(3):242-52.

11. Gu Z, Churchman ML, Roberts KG, Moore I, Zhou X, Nakitandwe J, et al. PAX5-
driven subtypes of B-progenitor acute lymphoblastic leukemia. Nat Genet.
2019 Feb;51(2):296-307.

12. Williams LA, Yang JJ, Hirsch BA, Marcotte EL, Spector LG. Is There
Etiologic Heterogeneity between Subtypes of Childhood Acute Lymphoblastic
Leukemia? A Review of Variation in Risk by Subtype. Cancer Epidemiol
Biomarkers Prev. 2019 May 3;28(5):846-56.

13. Chiaretti S, Zini G, Bassan R. DIAGNOSIS AND SUBCLASSIFICATION OF ACUTE
LYMPHOBLASTIC LEUKEMIA. Mediterr J Hematol Infect Dis. 2014 Oct
24;6(1):e2014073.

14. Mrózek K, Harper DP, Aplan PD. Cytogenetics and Molecular Genetics of Acute
Lymphoblastic Leukemia. Recent Prog Treat Acute Lymphoblastic Leuk. 2009

649  Oct 1;23(5):991–1010.

650 15. Behjati S, Tarpey PS. What is next generation sequencing? Arch Dis Child-
651   Educ Pract. 2013;

652 16. Dahui Qin. Next-generation sequencing and its clinical application. Cancer
653   Biol Med. 2019 Feb 1;16(1):4.

654 17. Mäkinen VP, Rehn J, Breen J, Yeung D, White DL. Multi-Cohort Transcriptomic
655   Subtyping of B-Cell Acute Lymphoblastic Leukemia. Int J Mol Sci. 2022 Apr
656   20;23(9):4574.

657 18. Tran TH, Loh ML. Ph-like acute lymphoblastic leukemia. Hematology. 2016 Dec
658   2;2016(1):561–6.

659 19. Inaba H, Azzato EM, Mullighan CG. Integration of Next-Generation Sequencing
660   to Treat Acute Lymphoblastic Leukemia with Targetable Lesions: The St. Jude
661   Children's Research Hospital Approach. Front Pediatr [Internet]. 2017;5.
662   Available               from:
663   https://www.frontiersin.org/journals/pediatrics/articles/10.3389/fped.2017.
664   00258

665 20. Brown LM, Lonsdale A, Zhu A, Davidson NM, Schmidt B, Hawkins A, et al. The
666   application of RNA sequencing for the diagnosis and genomic classification
667   of pediatric acute lymphoblastic leukemia. Blood Adv. 2020 Mar 10;4(5):930–
668   42.

669 21. Li JF, Dai YT, Lilljebjörn H, Shen SH, Cui BW, Bai L, et al.
670   Transcriptional landscape of B cell precursor acute lymphoblastic leukemia
671   based on an international study of 1,223 cases. Proc Natl Acad Sci. 2018
672   Dec 11;115(50):E11711–20.

673 22. Coccaro N, Anelli L, Zagaria A, Specchia G, Albano F. Next-Generation
674   Sequencing in Acute Lymphoblastic Leukemia. Int J Mol Sci. 2019;20(12).

675 23. Ng PC, Kirkness EF. Whole Genome Sequencing. In: Barnes MR, Breen G,
676   editors. Genetic Variation: Methods and Protocols [Internet]. Totowa, NJ:
677   Humana Press; 2010. p. 215–26. Available from: https://doi.org/10.1007/978-
678   1-60327-367-1_12

679 24. Rabbani B, Tekin M, Mahdieh N. The promise of whole-exome sequencing in
680   medical genetics. J Hum Genet. 2014;59(1):5–15.

681 25. Antonio Agraz-Doblas, Clara Bueno, Rachael Bashford-Rogers, Anindita Roy,
682   Pauline Schneider, Michela Bardini, et al. Unraveling the cellular origin
683   and clinical prognostic markers of infant B-cell acute lymphoblastic
684   leukemia using genome-wide analysis. Haematologica. 2019 May

31;104(6):1176-88.

26. Gu Z, Hu Z, Jia Z, Liu J, Mao A, Han H. MD-ALL: an Integrative Platform for
Molecular Diagnosis of B-cell Acute Lymphoblastic Leukemia [Internet]. 2023
[cited   2024   May   6].   Available   from:
https://www.researchsquare.com/article/rs-2798895/v1

27. Alaggio R, Amador C, Anagnostopoulos I, Attygalle AD, Araujo IBDO, Berti E,
et al. The 5th edition of the World Health Organization Classification of
Haematolymphoid Tumours: Lymphoid Neoplasms. Leukemia. 2022 Jul;36(7):1720-
48.

28. Arber DA, Orazi A, Hasserjian RP, Borowitz MJ, Calvo KR, Kvasnicka HM, et
al. International Consensus Classification of Myeloid Neoplasms and Acute
Leukemias: integrating morphologic, clinical, and genomic data. Blood. 2022
Sep 15;140(11):1200-28.

29. Schmidt B, Brown LM, Ryland GL, Lonsdale A, Kosasih HJ, Ludlow LE, et al.
ALLSorts: an RNA-Seq subtype classifier for B-cell acute lymphoblastic
leukemia. Blood Adv. 2022 Jul 26;6(14):4093-7.

30. Beder T, Hansen BT, Hartmann AM, Zimmermann J, Amelunxen E, Wolgast N, et
al. The Gene Expression Classifier ALLCatchR Identifies B-cell Precursor
ALL   Subtypes   and   Underlying   Developmental   Trajectories   Across   Age.
HemaSphere. 2023 Sep;7(9):e939.

31. Hu Z, Jia Z, Liu J, Mao A, Han H, Gu Z. MD-ALL: an integrative platform for
molecular diagnosis of B-acute lymphoblastic leukemia. Haematologica. 2024
Jun 1;109(6):1741-54.

32. Zhao Y, Li MC, Konaté MM, Chen L, Das B, Karlovich C, et al. TPM, FPKM, or
Normalized Counts? A Comparative Study of Quantification Measures for the
Analysis of RNA-seq Data from the NCI Patient-Derived Models Repository. J
Transl Med. 2021 Jun 22;19(1):269.

33. Johnson   WB,   Lindenstrauss   J.   Extensions   of   Lipschitz   mappings   into   a
Hilbert   space.   In: Beals   R,   Beck   A,   Bellow   A,   Hajian   A,   editors.
Contemporary   Mathematics   [Internet].   Providence,   Rhode   Island: American
Mathematical Society; 1984 [cited 2023 Dec 1]. p. 189-206. Available from:
http://www.ams.org/conm/026/

34. Li P, Hastie TJ, Church KW. Very sparse random projections. In: Proceedings
of the 12th ACM SIGKDD international conference on Knowledge discovery and
data mining [Internet]. Philadelphia PA USA: ACM; 2006 [cited 2023 Dec 1].
p. 287-96. Available from: https://dl.acm.org/doi/10.1145/1150402.1150436

35. van der Maaten L, Hinton G. Visualizing Data using t-SNE. J Mach Learn Res.

2008 11/1/2008;9(11):2579-605.

36. Robinson MD, Oshlack A. A scaling normalization method for differential
expression analysis of RNA-seq data. Genome Biol. 2010 Mar 2;11(3):R25.

37. Law CW, Chen Y, Shi W, Smyth GK. voom: precision weights unlock linear
model analysis tools for RNA-seq read counts. Genome Biol. 2014 Feb
3;15(2):R29.

38. Kolde R. Pheatmap: pretty heatmaps. R Package Version. 2019;1(2):726.

39. Baldi P, Brunak S, Chauvin Y, Andersen CAF, Nielsen H. Assessing the
accuracy of prediction algorithms for classification: an overview.
Bioinformatics. 2000 May 1;16(5):412-24.

40. Reisfeld B, Mayeno AN, editors. Computational Toxicology: Volume II
[Internet]. Totowa, NJ: Humana Press; 2013 [cited 2024 Mar 19]. (Methods in
Molecular Biology; vol. 930). Available from:
https://link.springer.com/10.1007/978-1-62703-059-5

41. McInnes L, Healy J, Melville J. UMAP: Uniform Manifold Approximation and
Projection for Dimension Reduction [Internet]. arXiv; 2020 [cited 2024 Mar
19]. Available from: http://arxiv.org/abs/1802.03426

42. Bingham E, Mannila H. Random projection in dimensionality reduction:
applications to image and text data. In 2001. p. 245-50.

43. Vu K, Poirion PL, Liberti L. Random projections for linear programming.
Math Oper Res. 2018;43(4):1051-71.

44. Sadras T, Heatley SL, Kok CH, Dang P, Galbraith KM, McClure BJ, et al.
Differential expression of MUC4, GPR110 and IL2RA defines two groups of
CRLF2-rearranged acute lymphoblastic leukemia patients with distinct
secondary lesions. Cancer Lett. 2017 Nov 1;408:92-101.

45. Pui CH, Roberts KG, Yang JJ, Mullighan CG. Philadelphia Chromosome-like
Acute Lymphoblastic Leukemia. Clin Lymphoma Myeloma Leuk. 2017 Aug
1;17(8):464-70.

46. Sánchez R, Ribera J, Morgades M, Ayala R, Onecha E, Ruiz-Heredia Y, et al.
A novel targeted RNA-Seq panel identifies a subset of adult patients with
acute lymphoblastic leukemia with BCR-ABL1-like characteristics. Blood
Cancer J. 2020 Apr 24;10(4):43.

47. Gestrich CK, Oduro KA. Restricted Immunoglobulin Joining Chain (IgJ)
Protein Expression in B Lymphoblastic Leukemia (B-ALL) Based on B-ALL
Subtype. Blood. 2020 Nov 5;136:7.

48. Li F, Ye W, Yao Y, Wei W, Lin X, Zhuang H, et al. Spermatogenesis
associated serine rich 2 like plays a prognostic factor and therapeutic
target in acute myeloid leukemia by regulating the JAK2/STAT3/STAT5 axis. J
Transl Med. 2023 Feb 11;21(1):115.

49. Lin J, Yan J, Deng X ling, Wang C shan, Wang H sheng. SPATS2 is correlated
with cell cycle progression and immune cells infiltration in hepatocellular
carcinoma. BMC Gastroenterol. 2023 Jan 11;23(1):8.

50. McGinn OJ, Krishnan S, Bourquin JP, Sapra P, Dempsey C, Saha V, et al.
Targeting the 5T4 oncofetal glycoprotein with an antibody drug conjugate
(A1mcMMAF) improves survival in patient-derived xenograft models of acute
lymphoblastic leukemia. Haematologica. 2017 Jun;102(6):1075-84.

51. Pearce LR, Atanassova N, Banton MC, Bottomley B, van der Klaauw AA, Revelli
JP, et al. KSR2 Mutations Are Associated with Obesity, Insulin Resistance,
and Impaired Cellular Fuel Oxidation. Cell. 2013 Nov 7;155(4):765-77.

52. Niederkorn M, Hueneman K, Choi K, Varney ME, Romano L, Pujato MA, et al.
TIFAB Regulates USP15-Mediated p53 Signaling during Stressed and Malignant
Hematopoiesis. Cell Rep. 2020 Feb 25;30(8):2776-2790.e6.

53. Carlet M, Völse K, Vergalli J, Becker M, Herold T, Arner A, et al. In vivo
inducible reverse genetics in patients' tumors to identify individual
therapeutic targets. Nat Commun. 2021 Sep 27;12(1):5655.

54. McClure BJ, Heatley SL, Kok CH, Sadras T, An J, Hughes TP, et al. Pre-B
acute lymphoblastic leukaemia recurrent fusion, EP300-ZNF384, is associated
with a distinct gene expression. Br J Cancer. 2018 Apr 1;118(7):1000-4.

55. Zhu L, Bai W, Cheng Q, Fang J. ZNF384-Related Fusion Genes in Acute
Lymphoblastic Leukemia. Cancer Control. 2023 Jan 1;30:10732748231182787.

56. Zhang J, Lu WY, Zhang JM, Lu RQ, Wu LX, Qin YZ, et al. S100A16 suppresses
the growth and survival of leukaemia cells and correlates with relapse and
relapse free survival in adults with Philadelphia chromosome-negative B-
cell acute lymphoblastic leukaemia. Br J Haematol. 2019 Jun 1;185(5):836-51.

57. McIntyre LM, Lopiano KK, Morse AM, Amin V, Oberg AL, Young LJ, et al. RNA-
seq: technical variability and sampling. BMC Genomics. 2011 Jun 6;12(1):293.

58. Leek JT, Johnson WE, Parker HS, Jaffe AE, Storey JD. The sva package for
removing batch effects and other unwanted variation in high-throughput
experiments. Bioinformatics. 2012 Mar 15;28(6):882-3.

59. Leek JT, Scharpf RB, Bravo HC, Simcha D, Langmead B, Johnson WE, et al.
Tackling the widespread and critical impact of batch effects in high-

throughput data. Nat Rev Genet. 2010 Oct 1;11(10):733-9.

60. Mumuni A, Mumuni F. Data augmentation: A comprehensive survey of modern
approaches. Array. 2022 Dec 1;16:100258.

61. Marketa Zaliova, Jan Stuchly, Lucie Winkowska, Alena Musilova, Karel Fiser,
Martina Slamova, et al. Genomic landscape of pediatric B-other acute
lymphoblastic leukemia in a consecutive European cohort. Haematologica.
2019 Jun 30;104(7):1396-406.

62. Ryan SL, Peden JF, Kingsbury Z, Schwab CJ, James T, Polonen P, et al. Whole
genome sequencing provides comprehensive genetic testing in childhood B-
cell acute lymphoblastic leukaemia. Leukemia. 2023 Mar 1;37(3):518-28.

63. Diedrich JD, Dong Q, Ferguson DC, Bergeron BP, Autry RJ, Qian M, et al.
Profiling chromatin accessibility in pediatric acute lymphoblastic leukemia
identifies subtype-specific chromatin landscapes and gene regulatory
networks. Leukemia. 2021 Nov 1;35(11):3078-91.

64. Wang H, Sun H, Liang B, Zhang F, Yang F, Cui B, et al. Chromatin
accessibility landscape of relapsed pediatric B-lineage acute lymphoblastic
leukemia. Nat Commun. 2023 Oct 25;14(1):6792.

65. Anilkumar KK, Manoj VJ, Sagi TM. A review on computer aided detection and
classification of leukemia. Multimed Tools Appl. 2024 Feb 1;83(6):17961-81.

66. Leszczenko P, Nowakowska AM, Jakubowska J, Pastorczak A, Zabczynska M,
Mlynarski W, et al. Raman spectroscopy can recognize the KMT2A
rearrangement as a distinct subtype of leukemia. Spectrochim Acta A Mol
Biomol Spectrosc. 2024 Jun 5;314:124173.

67. Li L, Xiao H, Khoury JD, Wang J, Wan S. Abstract 4907: RanBALL: Identifying
B-cell acute lymphoblastic leukemia subtypes based on an ensemble random
projection model. Cancer Res. 2024 Mar 22;84(6_Supplement):4907-4907.

819