Retinotopic coding organizes the interaction between internally and externally oriented brain networks

Adam Steel[1,2,3,4,*,+], Peter A. Angeli[3,4+], Caroline E. Robertson[3*]

[1] Beckman Institute, University of Illinois Urbana-Champaign, Urbana, Illinois, USA

[2] Department of Psychology, University of Illinois Urbana-Champaign, Urbana, Illinois, USA

[3] Department of Psychology, Dartmouth College, Hanover, NH, USA

[4] These authors contributed equally to this work.

*To whom correspondence may be addressed: adamdanielsteel@gmail.com and caroline.e.robertson@dartmouth.edu

Competing interests: The authors declare no competing interests.

Preprint: Steel*, Angeli*, Robertson. Retinotopic coding organizes the opponent dynamic between internally and externally oriented brain networks. DOI: 10.1101/2024.09.25.615084.

Data availability: All data is made publicly available via the Natural Scenes Dataset (https://naturalscenesdataset.org/). All code required to reproduce the results of this paper will be made available in Open Science Framework repository upon publication.

Acknowledgements: The authors would like to thank the authors of the Natural Scenes Dataset for making these data publicly available. This work was supported by an award from the National Institutes of Mental Health (R01MH130529) to CER. AS was supported by the Neukom Institute for Computational Sciences.

Author contributions: A.S., P.A., and C.E.R. designed the study, analyzed the data, and interpreted the experiments. A.S. and C.E.R. wrote and edited the manuscript; P.A. edited the manuscript. C.E.R. secured funding.

Abstract

The human brain seamlessly integrates internally generated thoughts with incoming sensory information, yet the large-scale networks that support these functions -- the (Default Network, DN) and external (Dorsal Attention Network, dATN) -- are traditionally viewed as functionally antagonistic. This raises a crucial question: how does the brain integrate information across these seemingly opposed systems? Here, using densely sampled 7T fMRI, individualized resting-state parcellations, and voxel-wise population-receptive-field mapping, we show that these internal/external networks are more interlocked than previously thought. Although spontaneous DN and dATN activity during rest is uncorrelated at the network level, functional coupling across networks is shaped by the latent visual field preferences of individual voxels in each network, as measured during independent retinotopic mapping. Voxels that share visual field preferences exhibit stronger spontaneous coupling than those with divergent preferences. These retinotopically-specific interactions are bivalent: DN voxels with negative (suppressive) visual response amplitudes are anticorrelated with matched (positive) dATN voxels, while those with positive response amplitudes are positively correlated. Thus, distinct subpopulations of visually-tuned DN voxels participate in spatially-specific interactions with the dATN. Further, retinotopic coding is intrinsic to the DN, persisting even during periods of elevated top-down drive from the DN to the dATN. These findings challenge the prevailing view of global DN-dATN antagonism, revealing a latent, voxel-level architecture of retinotopically-grounded interactions. Taken together, our results suggest that retinotopic coding underpins the dynamic coordination of perception and thought in the human brain.

Main Text

A fundamental goal of neuroscience is to understand how the coordinated activity of distributed brain networks gives rise to cognition (1–9). Central to this aim is understanding principles that govern interactions among networks with distinct computational roles. In particular, it is unclear how networks involved in externally-oriented attention (e.g., processing sensory input) interact with those that support internally-oriented attention (e.g., introspection and memory) (10–14). Understanding this interplay is crucial, because the dynamic exchange between internal and external representations underlies how we perceive, remember, and navigate our world -- yet the 'common language' that enables communication between these systems remains unclear.

Historically, the Default Network (DN) and Dorsal Attention Network (dATN)—prototypical networks for internal and external attention, respectively—have been viewed as functionally competitive (10–12, 14, 15). Classic neuroimaging studies show that externally oriented tasks activate the dATN and deactivate the DN (10, 13, 14, 16–18), while internally oriented tasks produce the opposite pattern (6, 19–23). This dissociation is also observed at rest, where DN and dATN activity is typically independent or anti-correlated (11, 12, 24, 25), depending on the application of global signal regression (11, 26). Such findings have led to the prevailing view that DN/dATN antagonism supports selective attention to either internal or external information, minimizing interference between perception and memory (10, 12, 27, 28). Yet, this framework leaves open a fundamental question: if these networks are functionally dissociated, how does the brain integrate perceptual and mnemonic information when both are required – for example during anticipatory saccades or memory-guided attention?

Recent studies of the voxel-level coding properties within these large-scale networks offer insight into this question. Although the DN is traditionally associated with abstract or semantic coding (2, 28–30), emerging evidence suggests that it also exhibits a neural code typically associated with externally-oriented visual processing: coding of retinotopic stimulus position (31–34). Notably, retinotopic coding in the DN differs from that observed in traditional visually responsive areas, including the dATN. While visual stimulation elicits position-dependent *increases* in neural activity in traditional visual areas, many DN voxels often show position-dependent *decreases* in activity(31, 33, 34). This voxel-level pattern suggests that the DN's global deactivation during externally-oriented tasks may not reflect a simple disengagement from external input, but rather a structured, spatially-tuned response to visual stimulation.

What purpose might the DN's voxel-level retinotopic code serve? We and others have proposed that the visual code in the DN might play a functional role in structuring mnemonic-perceptual interactions (31, 32, 34, 35). Recent work provides critical support for this theory, revealing that scene-selective memory regions near the DN (36) exhibit voxel-level retinotopic opponency with scene-selective visual areas (34). Specifically, the inverted retinotopic code in mnemonic regions is functionally tethered to the positive code in perceptual regions: during perception, visual stimuli at specific field locations activate perceptual voxels while suppressing memory voxels tuned to the same location, a pattern that reverses during memory retrieval (34). These results indicate that visual field location can coordinate dynamic interactions between specialized perceptual and mnemonic areas at the cortical apex, raising the intriguing hypothesis that retinotopic grounding

might support perceptual-mnemonic interactions more broadly across the brain. Yet, whether
retinotopic coding serves as a more general organizing principle for interactions across large-
scale networks remains unknown.

Here, we tested the hypothesis that global interactions across large-scale internally- and
externally-oriented brain networks are structured at the voxel level by a shared retinotopic code[35].
This framework challenges the traditional view of internally- and externally-oriented brain
networks as globally antagonistic, proposing instead that voxel-level retinotopic tuning enables
functional coupling and shared information processing between them. To evaluate this
hypothesis, we leveraged a high-resolution 7T fMRI dataset(37), individualized network
identification(3, 4, 8), and voxel-wise modeling(38) to test three core predictions. First, voxel-wise
retinotopic coding should be robustly present within individuals' DN and dATN networks, but with
divergent tuning polarities: positive retinotopic responses should dominate the dATN, while DN
should contains a significant proportion of retinotopic voxels with negative response amplitudes
to visual stimulation. Second, we predicted that spontaneous DN–dATN interactions during
resting-state fMRI would be structured by the retinotopic properties of individual voxels.
Specifically, functional coupling should be stronger between voxels that share visual field
preferences across networks, revealing that retinotopic position-specific responses form a latent
architecture to scaffold cross-network interactions even in the absence of overt task demands.
Third, we predicted that these retinotopically grounded interactions would support both top-down
and bottom-up coupling between the DN and dATN, suggesting that shared spatial tuning enables
dynamic, bidirectional interactions. Together, these findings would position retinotopy as a
unifying framework for brain-wide information processing and for the coordination of internal and
external attentional dynamics.

Retinotopic coding in internally and externally oriented networks

To investigate the role of retinotopic coding in structuring interactions between internally- and
externally-oriented brain networks, we analyzed 7T fMRI data from the Natural Scenes
Dataset(37), acquired from the same densely-sampled participants during both resting-state and
retinotopic mapping sessions (Fig. 1A-B).

We first identified individualized large-scale networks for each participant using their resting-state
fMRI data (8, 39) (Fig. 1B, S1). Resting-state data were preprocessed using independent
components analysis (ICA) with manual noise component selection(40, 41), and no global signal
regression was performed(26). Networks were identified using a multi-session hierarchical
Bayesian modeling approach(8, 39, 42), which leverages repeated data runs to estimate within
participant variation and derive stable parcellations for 15 cortical networks, including the Default
Networks A-B and the Dorsal Attention Networks A-B (Fig. 1B). Unless otherwise noted, we
combined the Default Networks A-B and the Dorsal Attention Networks A-B to constitute our
internal and externally oriented networks, respectively (hereafter, DN and dATN).

Next, we determined the visual field preferences of all voxels within these individualized networks
using a voxel-wise population receptive field (pRF) modeling approach(38, 43) to fit each
participant's BOLD activity during retinotopic mapping(38) (Fig 1A, S2). We considered any voxel

with >14% variance explained by our pRF model to be exhibiting a retinotopic code, and hereafter
we refer to these voxels as "pRFs". This threshold was determined by defining the noise floor of
our retinotopic model in the DN and dATN by comparing task-derived model fits to a control null
distribution derived from resting-state fMRI data (Fig. 1C; distribution of voxel-wise variance
explained by task versus null, K-S tests: D^-s>0.124, ps<0.001). Two pRF features were of primary
interest: 1) center position, which estimates the preferred location in visual space that drives a
given voxel's response (x,y), and 2) amplitude of the voxel's response (positive or negative)
(Fig. 1A). Importantly, both features were highly reproducible across runs of pRF data in the dATN
and DN in all subjects (Fig. 1D).

Next, we compared the retinotopic properties of voxels within the DN and dATN(11, 12, 18).
Across participants, we observed a larger proportion of retinotopic voxels in the dATN as
compared to the DN (43.36% of dATN voxels, 9.42% of DN voxels) consistent with their role as
externally- and internally-oriented networks, respectively. Further, the amplitude of retinotopic
responses (i.e. whether a stimulus in their preferred visual field location evoked a positive or a
negative BOLD response) differed significantly between these two networks (Fig 1E). Consistent
with prior reports, negative voxel-wise response amplitudes were clustered within the DN and in
similar locations across participants (31, 34), evidenced by a consensus map of pRF sign (Fig.
S3). On average, more than half (58.77%) of all pRFs in the DNs were inverted (i.e., had a
negative BOLD response to visual stimulation in their population receptive field, -pRFs). In
contrast, just 7.57% of the pRFs in the dATN were -pRFs (i.e., the vast majority of the voxels had
positive BOLD responses to visual stimulation in their receptive field, +pRFs). The difference in
negative pRF proportion between the dATNs and DNs was significant (t(6)=7.94, p<0.001; Fig.
1E, inset), and there was no difference among the sub-networks of each system (dATNs:
t(6)=0.24, p=0.82; DNs: t(6)=0.89, p=0.41). This distinction is particularly remarkable given the
proximity of dATN and DN clusters in posterior cerebral cortex. Like visual areas, both DN and
dATN pRFs exhibited a contralateral visual field bias, as we would predict from prior literature (31,
33, 34) (positive dATN pRFs: t(6)=26.0, p<0.001; negative DN pRFs: t(6)=4.86, p=0.003; positive
DN pRFs: t(6)=5.20, p=0.002) (Fig. 1F; see Fig. S4 for additional retinotopic properties). Together,
these results show that individualized DNs have voxel-wise responses that exhibit visual coding
-- the necessary foundation for assessing whether the voxel-wise retinotopic code structures
global interactions between the internally- and externally-oriented networks.

Figure 1. Inversion of retinotopic coding between externally- and internally- oriented brain networks. A. Population receptive field (pRF) modeling with fMRI. We established visual field preferences for each voxel using pRF modelling(38). Voxels with positive BOLD responses to the visual stimulus are classified as positive pRFs (+pRFs), and those with negative BOLD responses are classified as negative pRFs (-pRFs). B. Individualized resting-state network parcellation. Resting-state fMRI was collected in all participants (N=7; 34-102 minutes per participant) and used to derive individualized cortical network parcellations. Parcellations were generated using the multi-session hierarchical Bayesian modelling approach with the Yeo 15 HCP atlas as a prior(8, 42). C. PRF model variance explained is greater when fit to the pRF mapping task versus resting-state fMRI data for negative and positive pRFs in the DN and dATN. Histograms show voxel-wise variance explained for all pRFs fit to rest (dark) and the pRF modeling task fMRI data (light). All distributions were significantly shifted rightward for data fit to the pRF modeling task (dATN pRFs: K-S test: D⁻=0.655, p<0.001; Negative DN pRFs: D⁻=0.232, p<0.001; Positive DN pRFs: D⁻=0.124, p<0.001). Dashed lines indicate the 95th percentile of R² within the null distribution used; we chose the threshold for visually-defined voxels for subsequent analyses (R² > 0.14) to exceed these values. D. DN and dATN pRF amplitude and center location estimates are reliable. To assess reliability of pRF amplitude estimates, we compared voxel-wise signed amplitude by computing the dice coefficients of binarized pRF amplitude maps (i.e., positive or negative pRFs) between pairs of pRF modelling runs. To estimate center position, we calculated the distance between pairs of pRF centers iteratively between pRF modeling runs. For both metrics, chance was estimated by performing the same computation on a random sampling of voxels drawn from both pRFs and non-pRFs (5000 iterations for each metric). In all subjects, for dATN positive and DN positive and negative pRFs, pRF amplitude and center position exceeded what would be expected by chance (z-scored Dice/distance values > 2.9). Although only dATN positive pRFs were included in subsequent analyses, the dATN pRF amplitude was not reliable above chance in two participants; this suggests that negative amplitude pRFs are not stable in all cortical networks. E. The internally-oriented DN contains a larger proportion of negative pRFs than the externally-oriented dATN. Proportion of negative pRFs (of total pRFs that survive thresholding in that network) in all cortical networks are shown. Inset. DN-A and DN-B contain more negative pRFs than the dATN (t(6)=7.94, p<0.001), and there is no difference in the proportion of negative pRFs among sub-networks. F. DN and dATN pRFs networks show contralateral bias. Coverage plots across participants for positive dATN pRFs and positive and negative DN pRFs. Bar plots show the difference in coverage between contra- versus ipsi-lateral visual fields for each pRF type. Bar plots show mean across participants, connected points represent individual participant data.

Visual responsiveness stratifies DN-dATN resting-state interactions

Next, we examined whether the retinotopic response properties of individual voxels (estimated during the retinotopic mapping sessions) predict their functional coupling across DN-dATN during task-absent, spontaneous activity (during the resting state scans). Specifically, we tested whether voxel-level visual response classes—non-retinotopic voxels, positively tuned pRFs (+pRFs), and negatively tuned pRFs (–pRFs)—predict the strength and direction of coupling between the DN and dATN. Such a finding would reveal a stable, voxel-level organizational principle underlying the global dissociation that is hypothesized to exist between the DN and dATN(11–13, 15, 24, 25).

Across resting state runs, global activity of the DN and dATN was independent (i.e., not correlated) after accounting for variance across all cortical networks using partial correlation(44) (mean correlation = 0. 0.031±0.13 s.d., t(6) = 0.6287, p=0.55; Fig. 2A). Crucially, however, this global relationship masked a striking stratification based on DN voxel responsiveness (Fig. 2B). Non-retinotopic DN voxels (i.e., pRF model R^2<0.14) were not significantly correlated with the dATN (mean correlation = 0.014±0.135, t(6) = 0.26, p = 0.79). In contrast, DN voxels that responded positively to visual stimulation (DN positive pRFs, +pRFs) had a positive correlation with the dATN (mean correlation = 0.284±0.152, t(6) = 4.96, p = 0.0025), while DN voxels with systematic negative responses to visual stimulation (DN negative pRFs, -pRFs) were anti-correlated with the dATN (mean correlation = -0.21±0.149, t(6) = -3.75, p = 0.0094). Thus, voxel-level visual response profiles shape DN-dATN coupling during spontaneous resting-state activity. Specifically, opponency at rest between the DN and dATN appears to be driven by the subset of DN voxels with negative retinotopic tuning.

Shared visual field preferences structure functional coupling among visually-responsive DN and dATN voxels

We next asked whether functional coupling between DN and dATN voxels is modulated by the visual field preferences of retinotopic voxels — that is, whether their pRFs are centered on similar versus different visual field locations (i.e., their retinotopic alignment). We hypothesized that DN–dATN interactions would be stronger for voxel pairs with shared visual field preferences. To test this, we quantified the retinotopic alignment of voxel-wise pRFs across the DN and dATN. Because we only considered positive pRFs in the dATN, hereafter we refer to these as "dATN pRFs."

For each pRF in the DN (+pRFs and –pRFs), we computed the Euclidean distance between its receptive-field center (x, y) and those of all dATN pRFs (Fig. 2C). We then identified the 10 closest dATN pRFs ("Matched" set) and averaged their resting-state time series. As a comparison group, we repeated this procedure using 10 randomly selected, poorly matched dATN pRFs ("Random" set; see Methods). This procedure was repeated 1000 times for each DN voxel across resting-state runs.

Matched dATN pRFs were distributed throughout the network, spanning posterior retinotopic
cortex to anterior regions, including prefrontal cortex (Fig. S5). Crucially, the spatial dispersion
(i.e., the distance between the pRFs across the cortex) of matched and randomly-matched pRFs
did not significantly differ (matched versus random – DN -pRFs x dATN pRFs: t(6)=0.38, p=0.71;
DN +pRFs x dATN pRFs: t(6)=0.67, p=0.52), ruling out spatial proximity as a confounding factor
-- any difference in correlation with DN voxels should therefore be attributable to shared visual
field preferences.

If DN-dATN interactions are scaffolded by a retinotopic code, spatially matched pRFs should
exhibit stronger functional coupling than randomly-matched pRFs. Consistent with this prediction,
after partialling out variance from DN +pRFs to isolate the specific co-fluctuation between DN -
pRFs with dATN pRFs (34, 44), DN -pRFs remained anticorrelated with dATN pRFs in nearly
every resting-state run (Fig. 2D). Critically, matched pRFs were significantly more anticorrelated
compared with randomly-matched pRFs (linear mixed-effects model with random intercepts for
subject and run: F(1,194) = 105.7, p < 0.001; coefficient = –0.023 ± 0.002 s.d.). This effect was
evident when run-level correlations were averaged within each participant (7/7 participants $r_{matched}$
< r_{random}; t(6)=6.9, p<0.001, Fig.2E) and could not be explained by signal quality differences, as
matched and random pRF sets did not differ in tSNR (t(6) = 1.01, p = 0.353). This is strong
evidence that the retinotopic code underpins the opponent interaction between negative DN and
positive dATN pRFs.

Voxel-wise retinotopic alignment scaffolded the interaction between positive DN and dATN pRFs
as well. After controlling for DN -pRFs, DN +pRFs were positively correlated with dATN pRFs
(Fig. 2D). Retinotopic alignment again strengthened the interaction: matched correlations
exceeded random correlations in a mixed-effects model (F(1,194)= 406.5, p < 0.001; coefficient
= +0.050 ± 0.003 s.d.) and for every individual participant (7 / 7; t(6) = 5.7, p = 0.001) (Fig. 2E).

Together, these results demonstrate that shared retinotopic alignment enhances functional
coupling between DN and dATN voxels. Voxels tuned to the same region of visual space show
stronger spontaneous co-fluctuation—whether positively or negatively coupled—than those with
non-overlapping spatial preferences. This suggests that a shared spatial code helps organize
spontaneous interactions between large-scale internal and external attention networks during
rest.

Subnetwork Specificity within the DN

Recent work has suggested that the subnetworks of the DN, DN-A and DN-B, support different
cognitive processes: episodic projection and theory of mind, respectively (8, 45–47). Indeed, DN-
A is particularly sensitive to the process of scene construction(47), closely linked to visual
imagery, suggesting that dATN pRFs would show greater interaction with visually-responsive
voxels in DN-A compared with DN-B. Consistent with this hypothesis, spontaneous correlations
with dATN pRFs were significantly stronger for DN-A than DN-B voxels (collapsed across positive
and negative pRFs: t(6) = 4.80, p = 0.003). Crucially, however, voxel-scale retinotopic alignment
structured interactions between the DN and the dATN for both DN sub-networks (Fig. 2F-G; DN-
A: -pRFs t(6) = –4.56, p = 0.004; +pRFs t(6) = 5.65, p = 0.0013; DN-B: -pRFs t(6) = –7.49, p <

0.001; +pRFs t(6) = 2.92, p = 0.027). The strength of this effect did significantly differ between
DN-A and DN-B (t(6) = 1.51, p = 0.182). Thus, although DN-A is more strongly globally coupled
with dATN, retinotopic preferences of individual voxels structure functional interactions across
both DN subnetworks equally.

In addition, using the same matched-vs-random pRF procedure, we found that resting activity
between the lateral place-memory area (LPMA) and the adjacent occipital place area (OPA) was
significantly more correlated for retinotopically matched than random voxel pairs (t(6)=3.01,
p=0.024; SI). This shows that retinotopic scaffolding within domain-specific systems extends
beyond perceptual and memory tasks (34), organizing spontaneous activity within these systems
as well. These findings build on and extend our previous work (34) and others(48).

Figure 2. Retinotopic coding organizes spontaneous interaction between internally and externally oriented brain
networks. A. Overall activity of the dorsal attention networks (dATN-A/B) and default networks (DN-A/B) were
independent at rest. One individual's dATN and DN are shown. Time series from all voxels in the DN and dATN
subnetworks were averaged together, and we calculated the partial correlation(44) of these networks while
accounting for variance of the other 11 networks within the group-prior parcellation(1, 8). The dATN and DN network
correlation was not significantly different from zero, suggesting the activity of these networks is largely independent.
Bar plot shows the average partial correlation across participants, each data point is the average of all runs for a
single participant. B. Interaction between the DN and dATN differs by visual field preference of DN voxels. Splitting
the DN voxels by visual responsiveness revealed distinct patterns of resting-state correlation. DN +pRFs had a
positive correlation with the dATN (mean correlation = 0.22±0.144, t(6) = 3.99, p = 0.0072), while non-retinotopic DN
voxels (i.e., pRF model R2 < 0.08) were not significantly correlated with the dATN (mean correlation = 0.02±0.115,
t(6) = 0.37, p = 0.72). On the other hand, DN -pRFs were anti-correlated with the dATN (mean correlation = -
0.20±0.12, t(6) = 4.22, p = 0.0055). C. Determining spatially-matched pRFs in dATNs and DNs. We assessed the
influence of retinotopic coding on the interaction between internally- and externally-oriented brain areas' spontaneous
activity during resting-state fMRI, by comparing the correlation in activation between pRFs in these networks that

represent similar (vs. different) regions of visual space. For each DN -pRF, we established the top 10 closest *positive*
dATN pRFs' centers based on their x and y position ("matched"), and correlated *the DN pRF* time series with the
average *timeseries of these* matched *dATN* pRFs. We *compared these correlation values with the correlation of the*
DN pRF timeseries paired with 10 randomly selected pRFs from the 33% furthest (1000 iterations per pRF). We
computed this for all *DN pRFs for each* all *runs in each subject. Inset* shows *the pairwise distances between all pRFs*
in all participants, dotted line shows the *66%ile. D. Negative (upper) and positive (lower) DN pRFs show retinotopic*
specific interaction with the dATN. Each set of bars depicts the average correlation of the matched and randomly
paired pRFs between the DN and dATN for each participant, with each run shown as connected points. All
participants showed greater correlation (either positive or negative) for matched compared with randomly paired
pRFs. E. Data shown averaging runs within each participant. For both positive and negative pRFs, the correlation
between matched compared with randomly matched pRFs was significantly greater (consistent with their amplitude,
ps<0.01). F, G. show the correlation between positive and negative pRFs in the DN with the dATN, split across the
sub-networks of the DN-A and B. Both DN-A and B show a significant impact of matching, indicating that both
*subnetworks interact with the dATN via a retinotopic code (ps<0.05). *: p<0.05, **: p<0.01, ***:p<0.001*

Retinotopic coding is intrinsic to internally-oriented areas

Our findings thus far highlight a role for retinotopic coding in structuring spontaneous interactions
between voxels across large-scale internally- and externally-oriented brain networks. However, a
key mechanistic question remains: is retinotopic coding an intrinsic property of the DN, or does it
only emerge in response to bottom-up perceptual input? For instance, one possibility is that top-
down DN-driven modulation of dATN activity reflects a global, non-selective suppression, with
retinotopic coding in the DN arising only through bottom-up input from the dATN. Alternatively,
retinotopic coding may be intrinsic to the DN itself – such that top-down signals from the DN to
the dATN are retinotopically-specific, allowing the DN to shape fine-grained spatial
representations within the dATN. Disambiguating these possibilities is essential for determining
whether the retinotopic scaffold constitutes a general mechanism for cross-network
communication, independent of task demands or cognitive domain (e.g., memory versus
perception).

To address this, we again turned to participants' resting-state fMRI data. Because participants
are not engaged in any task, resting-state provides a neutral testbed for assessing spontaneous
DN–dATN interactions. Moreover, experience sampling during rest has shown that attention
naturally alternates between internal and external focus during rest (49, 50), making it possible to
assess whether retinotopic coding emerges primarily during bottom-up (dATN-driven) or top-
down (DN-driven) events.

We developed an event-triggered analytical approach to dissociate bottom-up perceptual from
top-down mnemonic events. Specifically, we identified timepoints where spontaneous activity of
individual DN or dATN pRFs exceeded the 99th percentile of their resting-state distribution. These
high-activation time points were treated as neural "events" (Fig. 3A-C), with DN pRFs events
interpreted as top-down events, and dATN pRF events as bottom-up. To test whether these
events produced retinotopically-specific responses in the target network, we compared peri-event
activation in the target network's most 10 closely matched pRFs (i.e., those with similar visual
field preferences) to that in the 10 worst-matched (anti-matched) pRFs (Fig. 3A). We used the
worst matched pRFs for this analysis because the large number of pRFs made the random
matching procedure impractical. All analyses were conducted separately for positive and negative
pRF populations within the DN. This design enabled us to test two competing predictions: if

retinotopy in the DN only reflects bottom-up input, we should only see retinotopically specific coupling during bottom-up (dATN-driven) events. If, however, the DN possesses an intrinsic retinotopic scaffold used for top-down communication, we should observe retinotopic specificity during both bottom-up and top-down events. A windowed correlation analysis produced similar results (Fig. S6).

Across all participants, we detected 78,978 top-down events in DN -pRFs, 52,595 top-down events in DN +pRFs, and 541,546 bottom-up events in dATN pRFs. Bottom-up events were more frequent than either top-down type (dATN vs. negative DN: t(6)=15.19, p<0.001; dATN vs. positive DN: t(6)=25.63, p<0.001), but there was no difference between top-down event types (t(6)=2.03, p=0.18). On average, participants exhibited 2082±535 (mean±SD) negative DN, 1799±400 positive DN, and 3102±602 dATN events per run. Each pRF showed 0–4 events per run (Fig. S7). More than 90% of timepoints involved <10 simultaneous events, suggesting that individual pRF-level correlation could be isolated from global fluctuations in regional activity, making this approach suitable for evaluating distinct interactions at the individual voxel level.

We found a robust effect of retinotopic alignment (i.e., matched versus anti-matched) on pRF activation during both bottom-up and top-down interactions (Fig. 3D-I). For DN -pRFs, a linear mixed-effects model (factors: top-down/bottom-up and retinotopic alignment; subject as random effect) revealed a main effect of match status (F(1,24)=15.3, p=0.0006) and no interaction between match status and direction (F(1,24)=0.0748, p=0.40). During top-down events in DN -pRFs, matched dATN pRFs showed lower activity than anti-matched (t(6)=5.46, p=0.001) and were significantly deactivated relative to the pre-event baseline. The same was true of DN -pRFs during bottom-up events in dATN +pRFs: we observed lower activation for matched vs. anti-matched pRFs (t(6)=3.80, p=0.009). These results are consistent with a retinotopically-specific interaction between dATN +pRFs and DN -pRFs during both top-down and bottom-up events detected in spontaneous activity during resting-state fMRI.

The interaction between DN +pRFs and dATN pRFs also showed evidence of retinotopic coding during both bottom-up and top-down events, but these effects were modulated by a direction × match interaction (F(1,24)=12.84, p=0.002). Both top-down (t(6) = 8.76, p < 0.001) and bottom-up (t(6) = 9.14, p < 0.001) events evoked strong activation in the target network (dATN or DN, respectively). However, anti-matched pRFs were more active during top-down compared to bottom-up events (t(6) = 4.92, p = 0.0026), suggesting that top-down signals from positive DN pRFs to dATN may be less retinotopically specific than bottom-up signals. These results align with prior findings showing decreased spatial precision in visual representations during memory recall compared to perception(51, 52).

Taken together, these results support the view that retinotopic coding serves as a general scaffold for DN-dATN interactions. This alignment shapes spontaneous coupling during both periods of DN-driven (top-down) and dATN-driven (bottom-up) activity, even in the absence of external tasks. Because the effect persists without sensory input, it likely reflects an intrinsic feature of the DN activity rather than a transient result of bottom-up drive.

Figure 3. Top-down vs. bottom-up neural events detected in spontaneous resting-state dynamics show evidence for retinotopically-specific suppression. A. Event detection and analysis procedure and example events from a single resting-state run. To detect events, we extracted the time series from each pRF in the source regions (top-down: positive or negative pRFs in the DN; bottom-up: positive pRFs in the dATN) and isolated time points where the z-scored time series exceeded 2.4 s.d. (99th percentile). We then examined the activity of 10 best matched and 10 worst matched (anti-matched) pRFs from the target region in this peri-event time frame (6 TRs (8 s) before and after the event). B. Example top-down event in the representative time series shows elevated source pRF activity (DN -pRF) and corresponding target area activity (dATN +pRF). C. Same as B, but for bottom-up activity with the event detected in a dATN +pRF. D, E. Evidence for retinotopically-specific suppression of ongoing activity during events top-down events detected in DN -pRFs (D) and bottom-up events detected in dATN +pRFs (E). D. Time series show the peri-event activity of matched and anti-matched dATN +pRFs averaged across all participants for events detected in DN -pRFs (N=78,978 events). E. Time series shows the peri-event activity in DN -pRFs during events detected in dATN +pRFs

Discussion

Despite extensive evidence that internally- and externally-oriented brain networks – including the default network (DN) and dorsal attention network (dATN) – are critical for human cognition(1–8, 11–13), the coding principles that enable these distributed systems to interact have remained unclear(30, 53–57). Here, we show that DN–dATN coupling is retinotopically grounded at the voxel scale: the visual field biases of individual voxels scaffold bidirectional interactions between these networks, even during spontaneous dynamics in the absence of visual task demands. Analyses of transient elevated activity in either the DN or dATN confirm that this retinotopic opponency shapes both bottom-up signals (from the dATN to the DN) and top-down signals (from the DN to the dATN), indicating that the retinotopic code is intrinsic to both internal and external networks. These findings offer a multi-scale account of network communication in which macro-scale dynamics are underpinned by latent, fine-grained voxel-scale biases. Rather than functionally dissociated, our data show that the DN and dATN are dynamically coordinated systems that are poised to integrate internal and external information through a shared spatial scaffold.

Resolving the coding principles of the DN is critical given its central roles in spatial and episodic memory, social cognition, and executive function(13, 58–63). Classic views of systems-level brain organization posit regions at the apex of the cortical hierarchy, like the DN, likely have abstract, amodal neural codes, in contrast to sensory codes–like retinotopy–that manifest in earlier areas of the cortical hierarchy (2, 29, 30). Our findings and others challenge this view. Instead of shedding the retinotopic code at the cortical apex, the DN retains a retinotopic code(31, 33) and functionally deploys this code to structure interactions with the externally-oriented dATN. Thus, a code once thought to be exclusive to early visual cortex and visually-oriented tasks plays a widespread role in shaping brain activity across the cortical hierarchy—even at rest.

Establishing this voxel-level structure within the DN and dATN reframes a long-standing debate that has cast these networks as globally competitive or functionally independent(11, 23, 27, 28). These views have stemmed from macro-scale observations of reciprocal activation patterns during external versus internal task demands(6, 10, 13, 14, 16–23), and resting-state analyses that reveal zero or negative correlations between their mean time series(11, 12, 24, 25). However,

by focusing on global, network-level activity across voxels, these approaches have obscured a
latent, voxel-level structure to DN-dATN functional coupling. Specifically, we find that DN–dATN
coupling is not globally antagonistic. Instead, two subpopulations of voxels within the DN
contribute to a retinotopically-grounded cross-network interaction that is stratified by their voxel-
level visual selectivity. One population of DN voxels is positively tuned to visual stimulation, and
positively covaries with dATN voxels that share their visual field preference. In contrast, DN voxels
that are negatively tuned to visual stimulation negatively covary with retinotopically matched dATN
voxels as a function visual field preference. When these voxel-level tuning preferences are not
taken into account, cross-network activity "averages out" into a global opponency or
independence(11, 12), reinforcing the misconception that the networks support mutually exclusive
cognitive modes. By revealing a shared retinotopic scaffold, our findings reconcile why DN and
dATN can appear oppositional in coarse analyses yet remain functionally integrated, offering a
new framework for understanding how internal and external attention are coordinated in the
human brain.

Importantly, there are key differences in the nature of retinotopic coding between the DN and
visual areas, including the dATN. First, retinotopy in the DN is predominantly negative in
valence—DN voxels more often show spatially-specific suppression in response to visual
stimulation(31, 33, 34), unlike the positive spatially-specific response that is typically observed
in visual areas. Second, although many DN voxels exhibit reliable retinotopic coding, the DN lacks
the map-like retinotopic organization seen in early visual cortex. In visual areas, retinotopic coding
is not only the foundational code, but also the dominant topographic organizing principle across
the cortical surface, where voxels that are proximal on the cortical surface tend to share visual
selectivity for nearby regions of visual space(64). However, the presence of a coding scheme
does not necessarily require a map-like organization on the cortical surface. For example, rodent
and bat head direction cells are not laid out in a literal ring, but the population code of these
neurons forms a ring manifold(65, 66). Similarly, in humans, retrosplenial cortex shows head-
direction coding during navigation tasks despite lacking topographic organization of head-
direction responses(67). Analogously, the DN may implement a retinotopic code that is distributed
across the network in a format that does not spatially mirror the retina. That is, the DN may use a
retinotopic code without a retinotopic map – the representational structure can be preserved even
in the absence of spatially ordered cortical layouts.

What function might the bivalent (positive and negative) voxel-scale retinotopic alignment across
these large-scale networks serve? Our previous work has identified a role for retinotopic-
alignment in structuring the functional coupling of scene-selective mnemonic and perceptual brain
areas(34, 48) located near the dATN and DN, respectively (36, 68). Near to the DN, scene-
selective memory areas exhibit a negative retinotopic code, while functionally-paired scene-
selective perceptual regions exhibit a positive retinotopic code(34). This bivalent retinotopic code
structures the mutual activity of these mnemonic and perceptual areas: scene-recall activates
scene-memory voxels, it but suppresses voxels in scene-perception areas that are tuned to
matched visual locations, a pattern that reverses during scene perception(34). The current work
significantly extends this observation beyond perceptual and mnemonic task-states -- identifying
widespread retinotopic alignment across large-scale networks with presumed different

orientations (internal vs. external) even during spontaneous activity at rest, in the absence of
tasks.

As to the functional role of the bivalent retinotopic alignment across internal and externally-
oriented large-scale networks, we propose two complementary possibilities. One possibility is that
the bivalent (positive and negative) subpopulations of DN pRFs may serve as a neural mechanism
for maintaining separate channels for perceptual and mnemonic information(54), preventing
mnemonic signals from being interpreted as or interfering with sensory signals. A second
possibility is that bivalent coding across the DN and dATN could be a mechanism for signaling
mnemonic predictions via top-down inhibitory processes(34, 69). Specifically, when the DN
generates predictions about incoming sensory information based on memory, the inverted
retinotopic code could act as a suppressive signal that sharpens tuning in perceptual areas and
enhances signal-to-noise for expected stimuli(70, 71). These mechanisms may work in concert:
the inverted code simultaneously maintains separate channels for memory/perception within the
DN, while enabling precise top-down predictive signaling across DN-dATN. Future work that
combines high-resolution recordings with behavior will be essential for testing how these
mechanisms jointly support constructive operations such as memory-based prediction during
visually guided navigation.

Retinotopic alignment between the DN and dATN was clear in both subnetworks of the DN, DN-
A and DN-B(3, 8, 20). This is surprising given their distinct functional profiles: DN-A has been
more directly linked to visually grounded memory processes, such as episodic projection and
scene construction(8, 20, 47), and spatially overlaps with regions previously shown to exhibit
retinotopy and engage in scene memory and perception(68). In contrast, DN-B is more often
associated with processes that are not obviously tied to vision: theory of mind and affective tasks,
such as interpreting false beliefs or representing physical and emotional pain (8, 20). Why might
the DN-B show retinotopically-grounded coupling with perceptual networks? Retinotopic coding
might still be a useful format for transforming abstract social representations into sensory-
grounded signals to inform perceptual predictions (e.g., anticipating changes in facial expression)
or behavioral decisions (e.g., making eye movements). Future work might consider direct
manipulation of social perceptual processes to assess the impact of social tasks on retinotopic
coding between DN-B and dATN.

Moments of high spontaneous activity originating in the DN co-occurred with suppression of
retinotopically-matched dATN pRFs, suggesting that retinotopy functions as a native coding
format in the DN for targeted modulation of perceptual cortex. This result aligns with other recent
studies suggesting an important role of the DN in shaping visual processing. For example,
ongoing pre-stimulus DN activity has been shown to influence sensitivity during near-threshold
visual object recognition(72). Other work has shown that subareas of the DN encode kinematic
of spatial exploration in rodents(73), and represent the visuospatial context that is associated in
memory with a perceived scene(34, 36, 68, 74, 75). Relatedly, DN activity reflects semantic-level
attentional priorities during visual search(76). Taken together, these findings show that, rather
than being disengaged during visual tasks, the DN actively shapes responses in perceptually-
oriented cortex in a spatially-precise manner. In this sense, retinotopic coding is part of the DN's
"native language". Taken together, these findings prompt a reevaluation of the DN's role in

perceptual processing, and the extent to which roles in "internally- and externally-oriented
attention" adequately captures the DN and dATN's role in cognition.

Is the DN a "visual" network? One possible interpretation of retinotopic coding in the DN is that
the DN directly and obligatorily represents retinal position in addition to more abstract features(38,
64). Under this hypothesis, the retinotopic code may indicate that the information represented in
the DN is, in part, sensory. Alternatively, the apparent visual coding may simply represent an
underlying connectivity structure(77) , which enables associative and semantic information that
the DN directly represents(30, 78, 79) to be effectively transferred to sensory areas of the brain.
Under this alternative hypothesis, the information represented in the DN is not itself sensory in
nature; the retinotopic code in the DN simply serves as a "highway" between the abstract
representations in the DN and sensory representations in the dATN. Notably, in either case the
retinotopic scaffolding represents a latent structure linking high-level and low-level areas through
consistent, spatially-organized interactions(77). This provides more evidence that low-level
sensory codes are distributed across the brain, joining recent work showing latent somatotopic
codes in regions of the brain that are not typically associated with somatosensation, including
visual cortex(80). The wide and overlapping distribution of sensory codes across the brain may
allow for multiplexing of complex information to structure cross-network interactions(35, 80).
Further studies investigating this framework with diverse tasks and stimuli could reshape our
understanding of how the brain processes and integrates information across different levels of
cognitive complexity.

In summary, our results show that a voxel-level retinotopic code organizes the spontaneous
interactions between large-scale internally- and externally-oriented networks in the human brain
– the DN and dATN. Even when global activity appears uncorrelated across DN-dATN, voxel-
level visual-field tuning reveals a tightly interlocked, bidirectional functional dynamic that persists
in the absence of external stimulation. This latent scaffold reconciles the apparent macroscale
independence of internally- and externally- oriented systems with their evident functional need to
cooperate, revealing that the DN is not divorced from perceptual networks, but modulates
perceptual voxels through a common visuospatial reference frame. Taken together, by grounding
large-scale network interactions in a shared, bivalent spatial code, retinotopy may offer a simple
organizing principle for the brain's coordination of thought and perception.

553 Materials and Methods

554 Dataset and Participants

The data analyzed here are part of the Natural Scenes Dataset (NSD), a large-scale precision 7T
fMRI dataset consisting of high-resolution anatomical scans, retinotopic mapping, functional
localizers for visual areas, and both task and resting-state fMRI data for eight adult participants.
A full description of the dataset can be found in the original manuscript (37). Here, we detail the
data, processing, and analysis steps relevant to the present work.

Participants (N = 8; 2 male, 6 female; ages 19–32) were scanned at the University of Minnesota
over the course of 33-43 sessions. All participants had normal or correct to normal vision and no
known neurological impairments. Informed consent was collected from all participants, and the
study was approved by the University of Minnesota institutional review board. One subject
(subj03) was excluded from resting-state analyses for having insufficient resting-state runs that
passed our quality metrics (see below).

For the present study, we focused on two components of the NSD protocol: retinotopic mapping
and resting-state fMRI. All participants completed three runs of a sweeping bar retinotopic
mapping task (5 mins each). Retinotopic mapping was conducted during Session 1, along with
the functional localizer scans. This task is referred to as "RETBAR" in NSD documentation.

All participants completed at least 14 runs of a resting-state fixation task (range: 14-34 runs; 5
mins each). Resting-state data runs were included in all NSD scan sessions after session 20 (i.e.,
session 21, 22, etc.). Each of these sessions included two 5-minute resting-state runs -- one at
the start and one at the end of the session -- yielding 14 to 34 total resting-state runs per
participant. During the second resting-state run, participants performed a deep breath in the first
5 seconds of scanning. To account for this, and to ensure the two resting-state runs were equated
in length, we excluded the first 30 seconds of the resting-state data from all runs. One participant
(subj03) was excluded from resting-state analyses due to having an insufficient number of usable
runs after quality control. All remaining participants had at least 8 high-quality resting-state runs
(mean: 14 ± 6.13 runs).

MRI acquisition and processing

For this study we made use of the following data from the NSD: anatomical (T1 and FreeSurfer
segmentation/reconstruction(81, 82)), functional regions of interest (ROIs), and minimally
preprocessed retinotopy and resting-state time series. All analyses except network identification
were conducted in original subject volume space, and data were projected on the surface for
visualization purposes only. Network identification was performed on the fsaverage6 surface, then
projected into subject specific volume space for quantification.

Anatomical data

588 Anatomical data was collected using a 3T Siemens Prisma scanner and a 32-channel head coil.
589 We used the anatomical data provided at 0.8mm resolution as well as the registered output from
590 FreeSurfer recon-all, aligned to the 1.8mm functional data. For visualization purposes, we
591 projected statistical and retinotopy data to the cortical surface using SUMA (83) from the AFNI
592 software package(84).

Functional MRI data acquisition and processing

594 All analyses were conducted on 1.8mm isotropic resolution minimally processed runs of a
595 sweeping-bar retinotopy task and resting-state fixation provided in the NSD.

Quality assessment

To ensure only high-quality resting-state data were included, we trimmed the first 25 TRs (40s) from each run (74), which left 4.25 min of resting-state data per run. We then used AFNI's quality control assessment tool (APQC(85)) on the raw trimmed resting-state time series to assess the degree of motion in the resting-state scans. We excluded runs with greater than 1.8mm maximum displacement per run or 0.12mm framewise displacement from analysis, and assessed runs with greater than 1mm displacement or 0.10mm framewise displacement on a case-by-case basis(8). After exclusions, one participant (subj03) had only a single run that survived our criteria (4.25 minutes of data)), so we excluded them from our analyses. The remaining 7 participants had at least 8 resting-state runs (> 34 minutes of data; mean number of runs: 14±6.13 (sd), range: 8-24 runs).

ICA denoising

To further denoise the retinotopy and remaining resting-state data, we used manual ICA classification of signal and noise on the minimally-preprocessed time series(36, 40, 41). We used manual classification because automated tools perform poorly on the high spatial and temporal resolution data of the NSD(86). For each retinotopy and resting state run, we decomposed the data into independent spatial components and their associated temporal signals using ICA (FSL's melodic(87, 88)). We then manually classified each component as signal or noise using the criteria established in(41). Noise signals were projected out of the data using fsl_regfilt(40).

We did not perform global signal regression(26). Data were normalized to percent signal change. A 2.5mm FWHM smooth was applied on the surface to resting-state fixation data used in functional connectivity network identification. The analysis of voxel-scale interactions performed on unsmoothed data.

Data analysis – Identifying Resting-State Networks

Individual-specific cerebral network estimation

In each participant, we identified a set of 15 distributed networks on the cerebral cortical surface using a multi-session hierarchical Bayesian model (MS-HBM) functional connectivity approach (8, 39). Briefly, the MS-HBM approach calculates a connectivity profile for every vertex on the cortical surface derived from the top 10% of correlations from that vertex to 1,175 ROIs uniformly disturbed across the cortical surface(1). We applied an expectation-maximization algorithm, initialized with a 15-network group-level spatial prior created by applying previous methods of network identification(1) on a portion of the HCP S900 data, to all the connectivity profiles from all participants. This algorithm then estimated each network's group-level connectivity profile, along with parameters for subject-, session/run-, and region-level variability, which together were used to generate individual-specific, labeled parcellations.

The MS-HBM approach is well-suited to derive parcellations for the participants in the NSD, where resting-state data was collected across multiple days, because this method uses repeated resting-state runs for each participant to estimate within-participant variance. This leverages a strength

of the NSD (the relatively large number of resting-state runs for each individual) and can account
for differences in connectivity both within an individual (likely the result of confounding variables
such as scanner variability, time of day, etc.), and between participants (reflecting potentially
meaningful individual differences). Moreover, the MS-HBS incorporates a group spatial prior,
further stabilizing the resulting network parcellations for each participant. This also ensures that
all networks will be identified in all participants, while allowing for idiosyncratic topographic
differences.

Data analysis – Retinotopic Mapping

Population receptive field (pRF) Modelling

The NSD retinotopy stimuli consist of a mosaic of faces, houses, and objects superimposed on
pink noise that are revealed through a continuously drifting aperture. For our analysis, we
considered only the bar stimulus time series, which is consistent with other studies investigating
negative pRFs in high-level cortical areas (31, 33, 34). We did not consider the wedge/ring
stimulus for any analyses.

After denoising the retinotopy data, we averaged the three retinotopy runs with the bar aperture
together to form the final retinotopy time series. We performed population receptive field modeling
using AFNI following the procedure described in (43). First, because the pRF stimulus in the NSD
is continuous, we resampled the stimulus time series to the fMRI temporal resolution (TR =
1.333s). Next, we implemented AFNI's pRF mapping procedure (3dNLfim). Given the position of
the stimulus in the visual field at every time point, the model estimates the pRF parameters that
yield the best fit to the data: pRF amplitude (positive, negative), pRF center location (x, y) and
size (diameter of the pRF). Both Simplex and Powell optimization algorithms are used
simultaneously to find the best time series/parameter sets (amplitude, x, y, size) by minimizing
the least-squares error of the predicted time series with the acquired time series for each voxel.
Relevant to the present work, the amplitude measure refers to the signed (positive or negative)
degree of linear scaling applied to the pRF model, which reflects the sign of the neural response
to visual stimulation of its receptive field.

Identifying Retinotopic Voxels – Empirically-derived R^2 thresholds

We developed a rigorous, data-driven approach to determine whether our pRF model fits truly
reflect visual coding rather than physiological noise. To do this, we leveraged the resting-state
fMRI data – where there is no dynamic visual stimulation -- to create a control (null) distribution
for retinotopic model fits and establish a "noise floor" for each network (i.e., the DN and dATN).
Then, we compared task-derived model fits to this rest-based null distribution to establish an
empirical R^2 threshold for pRFs in each network.

Specifically, we fit the pRF model to the average timeseries across all resting-state runs for each
participant. We then compared the resulting voxel-level R^2 distribution to that from the pRF
mapping task data, pooled across participants. To test whether the model fits were significantly
higher for the task vs. null distribution, we performed a one-tailed Kolmogorov-Smirnov test for
each network on the respective cumulative distribution functions (H_0: $CDF_{rest}(R^2) \leq CDF_{task}(R^2)$,

H_a: $CDF_{rest}(R^2)$ > $CDF_{task}(R^2)$). These analyses were performed separately for the dATN and
positive and negatively responsive voxels within the DN.

We defined a voxel as exhibiting a retinotopic code (hereafter referred to as a "pRF") if its model
fit exceeded 14% variance explained. This threshold was based on the 95th percentile of the null
R^2 distributions, which yielded noise floors of R^2 = 0.124 (dATN), R^2 = 0.132 (DN-positive), and
R^2 = 0.137 (DN-negative). We therefore set our global threshold for visually responsive voxels
across all networks at R^2 > 0.14, as this value exceeded the noise floor calculated in each network
separately.

Quantifying visual field coverage

Visual-field coverage (VFC) plots represent the sensitivity of an ROI across the visual field. We
followed the procedure in Steel et al., 2024(34), which we have reproduced here. Individual
participant VFC plots were first derived based pRF center, as well as pRF size and R^2. These
plots combine the best Gaussian receptive field model for each suprathreshold voxel within each
ROI by calculating the max operator at each point in the visual field, defined as the maximum
value from all pRFs within the ROI. The resulting coverage plot thus represents the maximum
envelope of sensitivity across the visual field. Individual participant VFC plots were averaged
across participants to create group-level coverage plots.

To compute the elevation biases, we calculated the mean pRF value (defined as the mean of the
average max operator values in a specific portion of the visual-field coverage plot) in the
contralateral upper visual field (UVF) and contralateral lower visual field (LVF) and computed the
difference (UVF–LVF) for each participant, ROI and amplitude (+/−) separately. A positive value
thus represents an upper visual-field bias, whereas a negative value represents a lower visual-
field bias.

Reliability of pRF amplitude and center position estimates

We tested whether key pRF features of interest – amplitude (i.e., positive vs. negative) and center
position (i.e., x,y) – were reliable across retinotopy runs. To assess the reliability of pRF amplitude,
we iteratively compared the amplitude of significant pRFs from individual runs of pRF data.
Specifically, for each retinotopy run, we fit the pRF model and then binarized any significant voxels
(R^2 > 0.14) by amplitude. When testing positive-pRF reliability (in dATN and DN), positive voxels
= 1; all others = 0. For negative-pRF reliability (in DN), significant negative voxels = 1. We then
computed a three-run Dice coefficient: (dice $coefficient = \frac{3|run1 \cap run2 \cap run3|}{|run1|+|run2|+|run3|}$). We compared this
value against 5000 bootstrapped Dice scores derived from the same number of voxels randomly
sampled from all voxels, both significant and non-significant, in the ROI. For each participant, this
resulted in 1 "observed" dice coefficient along with 5000 bootstrapped values representing the
distribution of dice coefficients expected by chance. The observed coefficient was z-scored
against this null distribution for each participant.

We also evaluated center position (x,y) reliability. For every significant voxel, we calculated the
Euclidean distance between its center estimates across the three run pairs (i.e 1-2, 2-3, 1-3). As
with amplitude, we generated a null distribution by repeating this computation on 5,000 random

voxel sets (significant + non-significant). To establish significance of the true estimate, the
observed estimate was z-scored against this null distribution for each participant.

Data Analysis – Retinotopically-Grounded Resting-state Analyses

Evaluating global functional coupling between cortical networks at rest

716   To assess global functional coupling between the default network (DN) and the dorsal attention
717   network (dATN) at rest, we used a partial correlation analysis that accounted for variation
718   associated with other cortical networks (44). For this and all subsequent analyses, each individual
719   resting state run was z-scored in time. Prior to calculating the partial correlation between them,
720   we first averaged the time series within each DN and dATN subnetwork.

Evaluating the Contributions of Voxel-Level Visual Response Valence to Cross-Network Coupling

724   To test whether DN–dATN coupling is modulated by the visual responsiveness (i.e., response
725   valence) of DN voxels, we repeated this analysis separately using only: (i) sub-threshold/non-
726   retinotopic voxels, (ii) positive pRFs, or (iii) negative pRFs from the DN -- while still partialing out
727   the remaining networks. This allowed us to assess whether specific classes of visually responsive
728   voxels in the DN differentially contribute to functional coupling with positive pRFs in the dATN.

Evaluating Voxel-Level Retinotopic Alignment in Cross-Network Coupling

To test whether functional coupling is shaped by the shared visual field preferences of DN-dATN
voxels (i.e., retinotopic alignment), we compared resting-state correlations between pRF pairs
across the DN and dATN that had matched (vs. unmatched) pRF centers.

To do this, for each pRF in the DN (positive or negative), we computed the Euclidean distance
between its receptive-field center (x, y) and those of all dATN +pRFs. We focused on center
position instead of pRF size because 1) size estimates are relatively unstable compared with
center position(89), and 2) we lacked a clear prediction about how pRF size would be related
between the two networks. For each DN voxel, we identified the 10 nearest dATN +pRFs based
on center position—the "matched" set—and averaged their resting-state time series. As a null
comparison, we defined a "random" set by sampling with replacement 10 dATN +pRFs from the
most distant third of the match distribution (i.e., (the 1/3 furthest pRF pairs). We considered the
bottom 33% because the overwhelming majority of pRFs constituted relatively equal "good"
matches. This random sampling was repeated 1,000 times per DN voxel, generating a distribution
of 1,000 random correlation values, which we then averaged to yield a single "random" correlation
for each DN source pRF.

We calculated the correlation between each DN pRF's resting-state time series and that of its 10
best-matched dATN pRFs ("matched" correlation). We averaged across the 10 best matches to
(1) reflect the likely distributed input from multiple dATN sources and (2) improve signal-to-noise.
To isolate pRF-specific effects, we partialed out the mean time series of the complementary DN

pRF population from the signals of interest. For example, when analyzing correlations between –
DN and +dATN, we treated +DN activity as a nuisance regressor (and vice versa)(34, 44). This
provided a network-level analog to the whole-brain partial correlation described above (see
Section: Correlation among cortical networks), allowing us to isolate the unique contribution of
the pRFs of interest from overall activity in the region as well as to control for global fluctuations
that cause widespread positive correlations like motion and attentional state(34, 44). All
correlation values were Fisher-transformed, and we took the median value across voxels within
each network to yield a single value per run. This procedure was repeated for all runs and all
participants.

We then statistically compared Fisher-transformed correlations for matched vs. random pRF pairs
using a linear mixed effects model, with match status (matched vs. random) as a fixed effect and
subject and run as random effects. This model accounted for both between- and within-subject
variation across session. For follow-up tests, we compared the average matched and random
values across participants using a paired t-test.

Resting-state event detection analyses

To dissociate the influence of top-down versus bottom-up drive on spontaneous interactions
between the DN and dATN, we developed an event-triggered analysis of resting-state fMRI data.
Because participants were not engaged in any task, resting-state data provide a neutral testbed
for evaluating the directionality and spatial specificity of DN–dATN interactions. Building on prior
findings that attention during rest naturally alternates between internally and externally oriented
states(23, 49, 50) we reasoned that transient "neural events" in these networks could reveal
spontaneous top-down and bottom-up communication.

We defined top-down events as transient high-activation periods in DN pRFs, and bottom-up
events as high-activation periods in positive-polarity dATN pRFs(90, 91). Event detection was
performed independently for each source pRF by taking each pRF's z-scored resting-state time
series and identifying TRs with unusually high activity. Specifically, we considered any time point
with a z-value greater than 2.4 (i.e., 99.18 percentile) as a neural event. Results were comparable
with a range of thresholds ($2.1 < z < 2.9$).

At each detected event, we extracted the resting-state time series of the 10 most retinotopically
aligned pRFs in the target network—i.e., the 10 with the smallest Euclidean distance in receptive-
field center (x, y)—over a 13-TR peri-event window (–6 to +6 TRs). These time series were
normalized to the mean of the first four pre-event TRs to allow comparisons across events and
conditions. To evaluate the spatial specificity of these interactions, we compared responses in
the matched pRFs to those in an "anti-matched" pRFs set: the 10 most distant pRFs in the target
network in terms of visual field preference (i.e., pRF center positions). Unlike prior analyses that
used random sampling to define unmatched control pRFs, here we used a deterministic anti-
match procedure to avoid the computational burden of repeated resampling, given the large
number of events.

This procedure was repeated across all relevant source–target network pairs: top-down (DN as
source, dATN as target), bottom-up (dATN as source, DN as target), and for both positive and

negative DN pRFs. For each event type and match status, we computed the average response
in the target pRFs at time zero (event peak). These values were entered into a linear mixed effects
model with fixed effects of match status (matched vs. anti-matched) and event direction (top-down
vs. bottom-up), and with subject as a random effect. This allowed us to test whether retinotopic
alignment modulates DN-dATN interactions during spontaneous events and whether such
modulation differs for top-down vs. bottom-up events.

Statistical tests

796 Statistical analyses were implemented in MATLAB (Mathworks, Inc). Given the relatively small
797 number of participants and large number of runs per subject, we used linear mixed effects models
798 to account for both within- and between-subject variability, as described in the relevant sections
799 above. For follow-up tests, we used paired-sample t-tests and corrected for multiple comparisons
800 where appropriate. Corrected p-values are reported where appropriate.

References

1. B. T. Thomas Yeo, *et al.*, The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *J Neurophysiol* **106**, 1125–1165 (2011).

2. D. S. Margulies, *et al.*, Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proc Natl Acad Sci U S A* **113**, 12574–12579 (2016).

3. R. M. Braga, R. L. Buckner, Parallel Interdigitated Distributed Networks within the Individual Estimated by Intrinsic Functional Connectivity. *Neuron* **95**, 457-471.e5 (2017).

4. E. M. Gordon, *et al.*, Precision Functional Mapping of Individual Human Brains. *Neuron* **95**, 791-807.e7 (2017).

5. C. Ranganath, M. Ritchey, Two cortical systems for memory-guided behaviour. *Nat Rev Neurosci* [Preprint] (2012). [Accessed 11 March 2020].

6. J. R. Andrews-Hanna, J. S. Reidler, J. Sepulcre, R. Poulin, R. L. Buckner, Functional-Anatomic Fractionation of the Brain's Default Network. *Neuron* **65**, 550–562 (2010).

7. A. J. Barnett, *et al.*, Intrinsic connectivity reveals functionally distinct cortico-hippocampal networks in the human brain. *PLoS Biol* **19**, e3001275 (2021).

8. J. Du, *et al.*, Organization of the human cerebral cortex estimated within individuals: networks, global topography, and function. *J Neurophysiol* **131**, 1014–1082 (2024).

9. T. O. Laumann, *et al.*, Functional System and Areal Organization of a Highly Sampled Individual Human Brain. *Neuron* **87**, 657–670 (2015).

10. M. M. Chun, J. D. Golomb, N. B. Turk-Browne, A Taxonomy of External and Internal Attention. *Annu Rev Psychol* **62**, 73–101 (2011).

11. M. L. Dixon, *et al.*, Interactions between the default network and dorsal attention network vary across default subsystems, time, and cognitive states. *Neuroimage* **147**, 632–649 (2017).

12. M. D. Fox, *et al.*, The human brain is intrinsically organized into dynamic, anticorrelated functional networks. *Proc Natl Acad Sci U S A* **102**, 9673–9678 (2005).

13. M. E. Raichle, The Brain's Default Mode Network. *Annu Rev Neurosci* **38**, 433–447 (2015).

14. M. D. Fox, M. Corbetta, A. Z. Snyder, J. L. Vincent, M. E. Raichle, Spontaneous neuronal activity distinguishes human dorsal and ventral attention systems. *Proceedings of the National Academy of Sciences* **103**, 10046–10051 (2006).

15. M. E. Raichle, *et al.*, A default mode of brain function. *Proceedings of the National Academy of Sciences* **98**, 676–682 (2001).

16.   E. Fedorenko, J. Duncan, N. Kanwisher, Broad domain generality in focal regions of frontal
and parietal cortex. *Proceedings of the National Academy of Sciences* **110**, 16616–16621
(2013).

17.   S. Vossel, J. J. Geng, G. R. Fink, Dorsal and Ventral Attention Systems: Distinct Neural
Circuits but Collaborative Roles. *The Neuroscientist* **20**, 150–159 (2013).

18.   G. L. Shulman, *et al.*, Common Blood Flow Changes across Visual Tasks: II. Decreases in
Cerebral Cortex. *J Cogn Neurosci* **9**, 648–663 (1997).

19.   E. H. Silson, A. Steel, A. Kidder, A. W. Gilmore, C. I. Baker, Distinct subdivisions of human
medial parietal cortex support recollection of people and places. *Elife* **8** (2019).

20.   L. M. DiNicola, R. M. Braga, R. L. Buckner, Parallel distributed networks dissociate episodic
and social functions within the individual. *J Neurophysiol* **123**, 1144–1179 (2020).

21.   P. P. Thakral, K. P. Madore, D. L. Schacter, A Role for the Left Angular Gyrus in Episodic
Simulation and Memory. *J Neurosci* **37**, 8142–8149 (2017).

22.   A. W. Gilmore, *et al.*, Dynamic Content Reactivation Supports Naturalistic Autobiographical
Recall in Humans. *Journal of Neuroscience* **41**, 153–166 (2021).

23.   K. Christoff, A. M. Gordon, J. Smallwood, R. Smith, J. W. Schooler, Experience sampling
during fMRI reveals default network and executive system contributions to mind wandering.
Proc Natl Acad Sci U S A **106**, 8719–8724 (2009).

24.   M. D. Greicius, B. Krasnow, A. L. Reiss, V. Menon, Functional connectivity in the resting
brain: A network analysis of the default mode hypothesis. *Proceedings of the National
Academy of Sciences* **100**, 253–258 (2003).

25.   V. Menon, 20 years of the default mode network: A review and synthesis. *Neuron* **111**,
2469–2487 (2023).

26.   Z. S. Saad, *et al.*, Trouble at Rest: How Correlation Patterns and Group Differences
Become Distorted After Global Signal Regression. *Brain Connect* **2**, 25–32 (2012).

27.   C. Murphy, *et al.*, Modes of operation: A topographic neural gradient supporting stimulus
dependent and independent cognition. *Neuroimage* **186**, 487–496 (2019).

28.   C. Murphy, *et al.*, Distant from input: Evidence of regions within the default mode network
supporting perceptually-decoupled and conceptually-guided cognition. *Neuroimage* **171**,
393–401 (2018).

29.   J. L. S. Bellmund, P. Gärdenfors, E. I. Moser, C. F. Doeller, Navigating cognition: Spatial
codes for human thinking. *Science (1979)* **362**, eaat6766 (2018).

30.   S. F. Popham, *et al.*, Visual and linguistic semantic representations are aligned at the
border of human visual cortex. *Nature Neuroscience 2021 24:11* **24**, 1628–1636 (2021).

31.   M. Szinte, T. Knapen, Visual Organization of the Default Network. *Cerebral Cortex* **30**,
3518–3527 (2020).

32.   T. Knapen, Topographic connectivity reveals task-dependent retinotopic processing
throughout the human brain. *Proc Natl Acad Sci U S A* **118** (2021).

33.   P. Christiaan Klink, X. Chen, W. Vanduffel, P. R. Roelfsema, Population receptive fields in
non-human primates from whole-brain fmri and large-scale neurophysiology in visual
cortex. *Elife* **10** (2021).

34.   A. Steel, E. H. Silson, B. D. Garcia, C. E. Robertson, A retinotopic code structures the
interaction between perception and memory systems. *Nat Neurosci* **27**, 339–347 (2024).

35.   I. I. A. Groen, T. M. Dekker, T. Knapen, E. H. Silson, Visuospatial coding as ubiquitous
scaffolding for human cognition. *Trends Cogn Sci* **26**, 81–96 (2022).

36.   A. Steel, M. M. Billings, E. H. Silson, C. E. Robertson, A network linking scene perception
and spatial memory systems in posterior cerebral cortex. *Nature Communications 2021
12:1* **12**, 1–13 (2021).

37.   E. J. Allen, *et al.*, A massive 7T fMRI dataset to bridge cognitive neuroscience and artificial
intelligence. *Nature Neuroscience 2021 25:1* **25**, 116–126 (2021).

38.   S. O. Dumoulin, B. A. Wandell, Population receptive field estimates in human visual cortex.
Neuroimage **39**, 647 (2008).

39.   R. Kong, *et al.*, Individual-Specific Areal-Level Parcellations Improve Functional
Connectivity Prediction of Behavior. *Cerebral Cortex* **31**, 4477–4500 (2021).

40.   L. Griffanti, *et al.*, ICA-based artefact removal and accelerated fMRI acquisition for
improved resting state network imaging. *Neuroimage* **95**, 232–247 (2014).

41.   L. Griffanti, *et al.*, Hand classification of fMRI ICA noise components. *Neuroimage* **154**,
188–205 (2017).

42.   R. Kong, *et al.*, Spatial Topography of Individual-Specific Cortical Networks Predicts
Human Cognition, Personality, and Emotion. *Cerebral Cortex* **29**, 2533–2551 (2019).

43.   E. H. Silson, A. W. Y. Chan, R. C. Reynolds, D. J. Kravitz, C. I. Baker, A retinotopic basis
for the division of high-level scene processing between lateral and ventral human
occipitotemporal cortex. *Journal of Neuroscience* **35**, 11921–11935 (2015).

44.   S. M. Smith, *et al.*, Functional connectomics from resting-state fMRI. *Trends Cogn Sci* **17**,
666–682 (2013).

45.   L. M. DiNicola, R. L. Buckner, Precision estimates of parallel distributed association
networks: evidence for domain specialization and implications for evolution and
development. *Curr Opin Behav Sci* **40**, 120–129 (2021).

46.   L. M. DiNicola, R. M. Braga, R. L. Buckner, Parallel Distributed Networks Dissociate
902   Episodic and Social Functions Within the Individual. *bioRxiv* 733048 (2019).
903   https://doi.org/10.1101/733048.

904   47.   L. M. DiNicola, O. I. Ariyo, R. L. Buckner, Functional specialization of parallel distributed
905   networks revealed by analysis of trial-to-trial variation in processing demands. *J
906   Neurophysiol* **129**, 17–40 (2023).

907   48.   C. L. Scrivener, E. H. Silson, Opponent visuospatial coding structures responses during
908   memory recall and visual perception in medial parietal cortex. *Imaging Neuroscience* **3**
909   (2025).

910   49.   J. Gonzalez-Castillo, J. W. Y. Kam, C. W. Hoy, P. A. Bandettini, How to Interpret Resting-
911   State fMRI: Ask Your Participants. *The Journal of Neuroscience* **41**, 1130–1141 (2021).

912   50.   L. Van Calster, A. D'Argembeau, E. Salmon, F. Peters, S. Majerus, Fluctuations of
913   Attentional Networks and Default Mode Network during the Resting State Reflect
914   Variations in Cognitive States: Evidence from a Novel Resting-state Experience Sampling
915   Method. *J Cogn Neurosci* **29**, 95–113 (2017).

916   51.   S. E. Favila, B. A. Kuhl, J. Winawer, Perception and memory have distinct spatial tuning
917   properties in human visual cortex. *Nature Communications 2022 13:1* **13**, 1–21 (2022).

918   52.   J. L. Breedlove, G. St-Yves, C. A. Olman, T. Naselaris, Generative Feedback Explains
919   Distinct Brain Activity Codes for Seen and Mental Images. *Current Biology* 1–14 (2020).
920   https://doi.org/10.1016/j.cub.2020.04.014.

921   53.   T. J. Buschman, M. Siegel, J. E. Roy, E. K. Miller, Neural substrates of cognitive capacity
922   limitations. *Proc Natl Acad Sci U S A* **108**, 11252–11255 (2011).

923   54.   A. Libby, T. J. Buschman, Rotational dynamics reduce interference between sensory and
924   memory representations. *Nature Neuroscience 2021 24:5* **24**, 715–726 (2021).

925   55.   J. D. Semedo, A. Zandvakili, C. K. Machens, B. M. Yu, A. Kohn, Cortical areas interact
926   through a communication subspace. *Neuron* **102**, 249 (2019).

927   56.   G. G. Gregoriou, S. J. Gotts, H. Zhou, R. Desimone, High-frequency, long-range coupling
928   between prefrontal and visual cortex during attention. *Science* **324**, 1207–1210 (2009).

929   57.   C. A. Bosman, *et al.*, Attentional stimulus selection through selective synchronization
930   between monkey visual areas. *Neuron* **75**, 875–888 (2012).

931   58.   D. S. Margulies, *et al.*, Situating the default-mode network along a principal gradient of
932   macroscale cortical organization. *Proc Natl Acad Sci U S A* **113**, 12574–12579 (2016).

933   59.   R. L. Buckner, L. M. DiNicola, The brain's default network: updated anatomy, physiology
934   and evolving insights. *Nat Rev Neurosci* (2019). https://doi.org/10.1038/s41583-019-0212-
935   7.

60. Y. Yeshurun, M. Nguyen, U. Hasson, The default mode network: where the idiosyncratic
self meets the shared social world. *Nature Reviews Neuroscience 2021 22:3* **22**, 181–192
(2021).

61. R. N. Spreng, W. D. Stevens, J. P. Chamberlain, A. W. Gilmore, D. L. Schacter, Default
network activity, coupled with the frontoparietal control network, supports goal-directed
cognition. *Neuroimage* **53**, 303–317 (2010).

62. R. N. Spreng, R. A. Mar, A. S. N. Kim, The common neural basis of autobiographical
memory, prospection, navigation, theory of mind, and the default mode: A quantitative
meta-analysis. *J Cogn Neurosci* **21**, 489–510 (2009).

63. B. L. Foster, *et al.*, A tripartite view of the posterior cingulate cortex. *Nat Rev Neurosci* **24**,
173–189 (2023).

64. B. A. Wandell, S. O. Dumoulin, A. A. Brewer, Visual field maps in human cortex. *Neuron*
56, 366–383 (2007).

65. J. S. Taube, The Head Direction Signal: Origins and Sensory-Motor Integration. *Annu Rev*
Neurosci **30**, 181–207 (2007).

66. A. Finkelstein, *et al.*, Three-dimensional head-direction coding in the bat brain. *Nature* **517**,
159–164 (2015).

67. M. Nau, T. Navarro Schröder, M. Frey, C. F. Doeller, Behavior-dependent directional tuning
in the human visual-navigation network. *Nat Commun* **11**, 3247 (2020).

68. A. Steel, D. Prasad, B. D. Garcia, C. E. Robertson, Relating scene memory and perception
activity to functional properties, networks, and landmarks of posterior cerebral cortex - a
probabilistic atlas. *The Journal of Neuroscience* e0028252025 (2025).
https://doi.org/10.1523/JNEUROSCI.0028-25.2025.

69. A. M. Bastos, *et al.*, Canonical Microcircuits for Predictive Coding. *Neuron* **76**, 695–711
(2012).

70. T. D. Albright, On the perception of probable things: neural substrates of associative
memory, imagery, and perception. *Neuron* **74**, 227–245 (2012).

71. H. C. Barron, T. P. Vogels, T. E. Behrens, M. Ramaswami, E. D. by Thomas Albright,
Inhibitory engrams in perception and memory. **114**, 6666–6674 (2017).

72. Y. Wu, E. Podvalny, M. Levinson, B. J. He, Network mechanisms of ongoing brain activity's
influence on conscious visual perception. *Nat Commun* **15**, 5720 (2024).

73. T.-A. E. Nghiem, *et al.*, Space wandering in the rodent default mode network. *Proceedings*
of the National Academy of Sciences **121** (2024).

74.   A. Steel, C. Thomas, A. Trefler, G. Chen, C. I. Baker, Finding the baby in the bath water –
evidence for task-specific changes in resting state functional connectivity evoked by
training. *Neuroimage* **188**, 524–538 (2019).

75.   A. Steel, B. D. Garcia, K. Goyal, A. Mynick, C. E. Robertson, Scene Perception and
Visuospatial Memory Converge at the Anterior Edge of Visually Responsive Cortex. *The*
Journal of Neuroscience **43**, 5723 (2023).

76.   T. Çukur, S. Nishimoto, A. G. Huth, J. L. Gallant, Attention during natural vision warps
semantic representation across the human brain. *Nat Neurosci* **16**, 763–770 (2013).

77.   M. Arcaro, M. Livingstone, A Whole-Brain Topographic Ontology. *Annu Rev Neurosci* **47**,
21–40 (2024).

78.   M. Peer, I. K. Brunec, N. S. Newcombe, R. A. Epstein, Structuring Knowledge with
Cognitive Maps and Cognitive Graphs. *Trends Cogn Sci* (2020).
https://doi.org/10.1016/j.tics.2020.10.004.

79.   A. G. Huth, W. A. De Heer, T. L. Griffiths, F. E. Theunissen, J. L. Gallant, Natural speech
reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453–458 (2016).

80.   N. Hedger, T. Naselaris, K. Kay, T. Knapen, Vicarious Somatotopic Maps Tile Visual
Cortex. *bioRxiv* 2024.10.21.619382 (2024). https://doi.org/10.1101/2024.10.21.619382.

81.   A. M. Dale, B. Fischl, M. I. Sereno, Cortical surface-based analysis: I. Segmentation and
surface reconstruction. *Neuroimage* **9**, 179–194 (1999).

82.   B. Fischl, *et al.*, Whole brain segmentation: Automated labeling of neuroanatomical
structures in the human brain. *Neuron* **33**, 341–355 (2002).

83.   Z. S. Saad, R. C. Reynolds, SUMA. *Neuroimage* **62**, 768–773 (2012).

84.   R. W. Cox, AFNI: Software for analysis and visualization of functional magnetic resonance
neuroimages. *Computers and Biomedical Research* **29**, 162–173 (1996).

85.   P. A. Taylor, *et al.*, A Set of FMRI Quality Control Tools in AFNI: Systematic, in-depth and
interactive QC with afni_proc.py and more. *bioRxiv* 2024.03.27.586976 (2024).
https://doi.org/10.1101/2024.03.27.586976.

86.   A. B. Beckers, *et al.*, Comparing the efficacy of data-driven denoising methods for a multi-
echo fMRI acquisition at 7T. *Neuroimage* **280**, 120361 (2023).

87.   M. Jenkinson, C. F. Beckmann, T. E. J. Behrens, M. W. Woolrich, S. M. Smith, FSL.
Neuroimage **62**, 782–790 (2012).

88.   S. M. Smith, *et al.*, Advances in functional and structural MR image analysis and
implementation as FSL in *NeuroImage*, (Academic Press, 2004), pp. S208–S219.

89. I. Alvarez, B. de Haas, C. A. Clark, G. Rees, D. Samuel Schwarzkopf, Comparing different
stimulus configurations for population receptive field mapping in human fMRI. *Front Hum*
Neurosci **9**, 121251 (2015).

90. E. M. Gordon, *et al.*, A somato-cognitive action network alternates with effector regions in
motor cortex. *Nature* **617**, 351–359 (2023).

91. A. Mitra, A. Z. Snyder, T. Blazey, M. E. Raichle, Lag threads organize the brain's intrinsic
activity. *Proceedings of the National Academy of Sciences* **112**, E2235–E2244 (2015).

92. E. H. Silson, I. I. A. Groen, D. J. Kravitz, C. I. Baker, Evaluating the correspondence
between face-, scene-, and object-selectivity and retinotopic organization within lateral
occipitotemporal cortex. *J Vis* **16**, 14–14 (2016).

93. R. M. Hutchison, J. C. Culham, S. Everling, J. R. Flanagan, J. P. Gallivan, Distinct and
distributed functional connectivity patterns across cortex reflect the domain-specific
constraints of object, face, scene, body, and tool category-selective modules in the ventral
visual pathway. *Neuroimage* **96**, 216–236 (2014).

94. W. D. Stevens, M. H. Tessler, C. S. Peng, A. Martin, Functional connectivity constrains the
category-related organization of human ventral occipitotemporal cortex. *Hum Brain Mapp*
36, 2187–2206 (2015).

95. E. H. Silson, A. D. Steel, C. I. Baker, Scene-Selectivity and Retinotopy in Medial Parietal
Cortex. *Front Hum Neurosci* **10**, 412 (2016).

96. C. Baldassano, A. Esteva, L. Fei-Fei, D. M. Beck, Two Distinct Scene-Processing Networks
Connecting Vision and Memory. *eNeuro* **3** (2016).

97. D. D. Dilks, J. B. Julian, A. M. Paunov, N. Kanwisher, The occipital place area is causally
and selectively involved in scene perception. *Journal of Neuroscience* **33**, 1331–1336
(2013).

98. U. Hasson, M. Harel, I. Levy, R. Malach, Large-scale mirror-symmetry organization of
human occipito-temporal object areas. *Neuron* **37**, 1027–1041 (2003).

99. N. Kanwisher, J. McDermott, M. M. Chun, The fusiform face area: A module in human
extrastriate cortex specialized for face perception. *Journal of Neuroscience* **17**, 4302–4311
(1997).

100. E. Halgren, *et al.*, Location of human face-selective cortex with respect to retinotopic areas.
Hum Brain Mapp **7**, 29 (1999).

101. M. Rosenke, R. van Hoof, J. van den Hurk, K. Grill-Spector, R. Goebel, A Probabilistic
Functional Atlas of Human Occipito-Temporal Visual Cortex. *Cerebral Cortex* **31**, 603–619
(2021).

1036

Supporting Information

 Fig S1. Cortical network parcellations for individual participants. Networks were parcellated based
 on a 15-network group prior(1, 8) using the multi-session hierarchical Bayesian model (MS-HBM)
 method(42).

1048

1049   Fig S2. PRF amplitude maps from all participants. Only voxels with greater than 8% variance
1050   explained by the pRF model are shown for visualization only.

1051

1052

Fig. *S3.* Negative pRFs are clustered in DN-A and DN-B. Brain shows the consensus signed pRF
amplitude map, which is the sum of the signed pRF amplitude across participants. Consensus
was calculated by binarizing each vertex based on the sign of the visual response: participants
with a positive response at a vertex were assigned a +1, participants with a negative response at
a vertex were assigned a -1, and participants that did not respond (i.e., had variance explained
below our 0.14 threshold) were assigned a 0. We then summed these maps across participants.
Vertices with positive values were positive in the majority of participants, vertices with negative
values were negative in the majority of participants, and vertices with 0 value showed no
consensus. Outlines show DN-A (purple), DN-B (pink), dATN A (light green), and dATN-B (dark
green).

1063
1064

1065

1066

Fig. S4. Eccentricity and pRF size differs between DN and dATNs. A. Both positive and negative
DN pRFs tend to be more eccentric than dATN pRFs (positive dATN v negative DN pRFs:
t(6)=2.27, p=0.06; positive dATN v positive DN pRFs: t(6)=3.04, p=0.023; negative DN v positive
DN pRFs: t(6)=0.41, p=0.69). B. Both positive and negative DN pRFs tend to be smaller than
dATN pRFs (positive dATN v negative DN pRFs: t(6)=2.36, p=0.056; positive dATN v positive DN
pRFs: t(6)=2.46, p=0.049; negative DN v positive DN pRFs: t(6)=0.16, p=0.87) (Fig. S4A).

Importantly, these results are averaged across the whole network. Results may differ when
individual regions of each network are considered.

*=p<0.05, +=p<0.1, n.s. = non-significant

1076

Fig. S5. Spatial distribution of positive dATN pRFs matched with negative DN pRFs in cortex across all participants. Vertices are colored based on number of matched pRFs. Only vertices with greater than 7 matched pRFs (i.e., at least one for each subject) are shown. Group prior maps*(1, 8)* dATN A-B and DN A-B are shown for reference. Note that pRFs were matched in individualized dATN of each participant and are not expected to correspond precisely with the group network maps.

1086

Fig. S6. A. Time series show the peri-event cross-covariance of matched and *anti-match*ed dATN
pRFs averaged across all participants for events detected in negative DN pRFs (N=78,978
events). B. Time series shows the peri-event cross-covariance in negative DN pRFs during events
detected in dATN pRFs (N=541,546). C. Bars show the average cross-covariance at event time
of the target areas' matched and *anti-match*ed pRFs for each participant. Although this difference
did not reach significance (F(1,24)=3.94, p=0.058), the results qualitatively support our conclusion
– that matched pRFs in the target region have a stronger interaction with the source pRFs. D, E.
Evidence for retinotopically-specific excitation of ongoing activity during events top-down events
detected in positive DN pRFs (D) and bottom-up events detected in dATN pRFs (E). D. Grand
average cross-covariance for matched and *anti-match*ed dATN pRFs during events detected in
positive pRFs for all participants. E. Grand average cross-covariance for matched and
anitmatched positive DN pRFs during events detected in dATN pRFs. I. For positive DN pRFs
paired with dATN pRFs, target area shows retinotopically-specific positive covariance for both
top-down and bottom-up events. Bars show the average activation at event time of the target
areas' matched and *anti-match*ed pRFs for each participant. We observed a strong influence of
match status on covariance (F(1,25)=25.324, p<0.001; t(6)=7.73, p<0.001). Similar to our findings
when examining activation at event time, bottom-up events had a greater influence from
retinotopic coding compared with top-down events, evidenced by a greater difference between
matched versus *anti-match*ed pRF covariation at event time (F(1,24)=6.22, p=0.02, t(6)=3.99,
p=0.007). For time series plots, solid bars along the x-axis indicate periods with a significant
difference between matched and *anti-match*ed pRF activity within the target area.

1108

1109

Fig S7. Events are widely distributed in time and across voxels. A,C,E. Number of events per time
point combined for top down and bottom up events for dATN, positive DN, and negative DN pRFs.
Bars indicate the number of voxel events detected at a given time point within a resting-state run,
aggregated across runs. Events were sparsely distributed: most time points contained no events
(Proportion = 0.66, bar not shown), with the number of events decreasing approximately
exponentially. This is further evidence for a wide temporal distribution of events. B,D,F. Proportion
of voxels with events in each run for dATN, positive DN, and negative DN pRFs. No voxel had
more than 4 events per run. Data are combined between top down and bottom-up events.

1118

Fig. S8. Retinotopic coding structures the spontaneous interaction between functionally-coupled mnemonic and perceptual areas during resting-state fMRI. A. Isolating functionally coupled internally- and externally-oriented brain areas within the DNs and dATNs. We identified brain areas that were specialized in two domains: scenes and faces processing. Specifically, we focused on the lateral place memory area (LPMA; from (36)), white), a memory area in the domain of scene perception at the posterior edge of the DN-A (purple; from (8)). We examined LPMA's relationship to three different of category-selective visual areas in the dATN (green; from (8)), 1) the occipital place area (OPA; from (36)), an area within the domain of scene perception, along with 2) the occipital face area (OFA) and 3) the fusiform face area (FFA), two areas involved in the domain of face perception (white; from (101)). B-C. We localized LPMA in all participants by contrasting the correlation in resting-state activity between anterior and posterior parahippocampal place area (PPA) (B). This yielded a region in lateral occipital-parietal cortex that overlapped with the LPMA defined in an independent group of participants (C). D-E. Consistent with prior work, the connectivity-defined LPMA had greater concentration of negative pRFs compared to OPA (D), and exhibited a lower visual field bias to OPA (E), consistent with an opponent interaction between these areas during perception. F. We assessed the influence of retinotopic coding on the interaction between negative pRFs in mnemonic and positive pRFs in perceptual areas using the same pRF matching and correlation procedure described above. We compared pRFs within functional domain (scene memory x perception – LPMA to OPA) as well as across domains (scene memory x face perception – LPMA to the occipital face area (OFA) and fusiform face area (FFA)). G. We found that LPMA and OPA were interlocked in a retinotopically-grounded opponent interaction. Resting-state activity of -LPMA and +OPA pRFs was reliably negatively correlated after accounting for variance associated with +LPMA pRFs, and, critically, this negative correlation was stronger for matched compared with randomly

matched pRFs (t(6)=3.012, p=0.024). We next tested whether this opponent dynamic was modified by functional domain (i.e., the scene memory area LPMA paired with the face perception areas FFA and OFA), and we observed no significant difference between the distribution of correlation values for matched and randomly-matched pRFs between -LPMA and OFA (t(6)=0.59, p=0.57) and -LPMA and FFA (t(6)=2.01, p=0.09). However, when we compared the difference of matched and randomly-matched pRFs across domains, we found no significant interaction (F(1,19)=0.99,p=0.33).

Figure S8 Results:

Our main results establish that retinotopic coding structures spontaneous interactions between internally- and externally-oriented neural systems in the absence of task demands. However, high-level cortical areas generally associate into networks based on their functional domain. For example, within the visual system, brain areas with differing retinotopic preferences (e.g., the scene-selective areas on the lateral and ventral surfaces of the brain) (43, 92) nevertheless form functional networks based on their apparent preference for specific visual categories (e.g., faces, objects, or scenes)(93, 94). This raises a question: do retinotopic and domain-specific organizational principles interact to facilitate or constrain information flow across internally- and externally-oriented networks? Addressing this question would shed light on mechanisms that enable the brain to integrate information while maintaining functional specialization.

To address this question, we focused on the functional interplay between a set of areas in posterior cerebral cortex that are established models for mnemonic and visual processing in the domains of scene and face perception. Specifically, we considered the mnemonic lateral place memory area (LPMA(36, 75)), an area on the brain's lateral surface that is implicated in processing mnemonic information relevant to visual scenes at the border between DN-A and the dATNs (Fig 2A). We examined OPA and LPMA because these regions are maximally spatially dissociable (36, 68, 75) and can be localized independently using resting-state data(95, 96). We examined how LPMA activation co-fluctuates with the adjacent, scene-perception area "occipital place area" on the brain's lateral surface (OPA(97, 98)) compared to two face-perception regions on the lateral and ventral surfaces, the occipital and fusiform face areas (OFA and FFA (99, 100)). At a group level, these perceptual regions are situated within the dATNs and are at the same level of the visual hierarchy (Fig. S8A), but they are differentially associated with the domains of scene (OPA) and face (OFA, FFA) processing, making them ideal model systems to examine the impact of domain-specificity and retinotopic coding in organizing neural activity.

We first defined the mnemonic area LPMA in the NSD participants. To do this, we contrasted functional connectivity between the anterior and posterior halves of the parahippocampal place area using each participant's resting state data(95, 96) (Fig. S8B), which revealed a cluster in lateral parietal cortex with a similar topographic profile as LPMA based on a group analysis from our prior work (36) (Fig.S8C). Replicating our previous findings(34), this connectivity-defined LPMA had a higher concentration of robust negative pRFs compared to OPA (t(7)=5.26, p=0.002) (Fig. S8D) and exhibited a similar lower visual field bias as OPA (OPA: 8/8 t(7)=3.13, p=0.016; LPMA: 7/8 participants, t(7)=2.11, p=0.07; OPA v LPMA: t(7)=0.441, p=0.67) (Fig. S8E).

We considered whether the retinotopic opponent dynamic we have previously shown in the
domain of scenes (i.e., between -LPMA and +OPA pRFs) during perceptual and mnemonic
tasks(34) was also present at rest (Fig. S8F). As we observed for the overall negative DN and
positive dATN pRFs, we found that -LPMA and +OPA pRFs are interlocked in a retinotopically-
grounded opponent interaction. We used the same matching and randomization procedure as we
used for the DN.

Remarkably, we found that LPMA and OPA were interlocked in a retinotopically-grounded
opponent interaction (Fig. S8G). Resting-state activity of -LPMA and +OPA pRFs was reliably
negatively correlated after accounting for variance associated with +LPMA pRFs, and, critically,
this negative correlation was stronger for matched compared with randomly matched pRFs
(t(6)=3.012, p=0.024). We next tested whether this opponent dynamic was modified by functional
domain (i.e., the scene memory area LPMA paired with the face perception areas FFA and OFA),
and we observed no significant difference between the distribution of correlation values for
matched and randomly-matched pRFs between -LPMA and OFA (t(6)=0.59, p=0.57) and -LPMA
and FFA (t(6)=2.01, p=0.09). However, when we compared the difference of matched and
randomly-matched pRFs across domains, we found no significant interaction
(F(1,19)=0.99,p=0.33).

One possibility is that the quality of the retinotopic matching between pRFs in different areas might
contribute to the within versus across domain distinction in retinotopic coding. We checked
whether there was a difference in the match quality between the top 10 best matched pRFs
between connectivity-defined LPMA and OPA compared with the face perception areas FFA and
OFA. For this analysis, we computed the euclidean distance between all pRFs centers between
regions, and we took the median of the best pRF center matches. For example, if a participant
had 162 negative pRFs LPMA and 90 pRFs in OPA, we found the top 10 best matched OPA pRFs
for each LPMA pRF, and then took the median distance of these 1620 matches. This gave us the
most representative distance for matched pRFs for each participant.

Overall, we found that the quality of pRF matching was better for within domain (LPMA to OPA)
compared with across domains (LPMA to OFA and FFA) (Negative pRFs: t(6)=5.86, p=0.001;
positive pRFs: t(6)=6.79, p<0.001). This suggests that the quality of the matches does depend on
the stimulus domain. This fits with the notion that visual response properties are inherited by
upstream areas, and that these response properties depend in part on the nature of the stimuli
within a domain.

These results suggest that retinotopic coding structures the interaction between brain areas if
they share a functional domain, but more studies are needed to confirm whether this is specific
to within-domain matching.

Figure S8 Methods:

Defining functional regions of interest (PPA, OPA, OFA, FFA)

We used the volumetric functional regions of interest provided with the NSD at 1.8mm resolution. Specifically, we used the parahippocampal place area (PPA), occipital place area (OPA), iog-faces (referred to here as occipital face area (OFA)), and pfus-faces (fusiform face area, FFA1) regions of interest. In brief, these regions were defined in the NSD using within-subject data collected from 6 runs of a multi-category visual localizer paradigm (37).

Defining functional region LPMA

Because the NSD did not include mnemonic localizers (36), we used the resting-state data to define the lateral place memory area (LPMA). Briefly, the LPMA is a region anterior to OPA and near caudal inferior parietal lobule(95, 96) that selectively responds during recall of personally familiar places compared to other stimulus types. We have previous shown that OPA and LPMA are functionally-linked and work jointly to process knowledge of visuospatial context out of view during scene perception.

Prior work has suggested that a mnemonic area linked to scenes on the lateral surface can be localized by comparing resting-state co-fluctuations of anterior versus posterior PPA (aPPA and pPPA, respectively)(19, 95, 96), and we adopted that approach here. We preprocessed the resting-state fixation fMRI data, runs 1 and 14 from NSD sessions 22 and 23, in all participants (prior to data exclusion) and extracted the average time series of aPPA, pPPA, aFFA, and pFFA. We used these time series as regressors in a general linear model, and we compared the beta-values from the aPPA and pPPA. We considered any voxels with a t-statistic > 5 within posterior parietal-occipital cortex on the lateral surface as an LPMA ROI (Individual ROIs can be found in Supplemental Fig.4). Across subjects, there was considerable overlap between this connectivity-defined area and a group-level LPMA defined based on our prior work (Fig. 2).