Retinotopic coding organizes the interaction between internally and externally oriented brain networks

Adam Steel[1,2,3,5,*,+], Peter A. Angeli[3,+], Caroline E. Robertson[3,4,**]

[1] Beckman Institute, University of Illinois Urbana-Champaign, Urbana, Illinois, USA

[2] Department of Psychology, University of Illinois Urbana-Champaign, Urbana, Illinois, USA

[3] Department of Psychology, Dartmouth College, Hanover, NH, USA

[4] Senior author

[5] Lead contact

+ These authors contributed equally to this work.

*Correspondence: adamdanielsteel@gmail.com

**Correspondence: caroline.e.robertson@dartmouth.edu

Competing interests: The authors declare no competing interests.

Data availability: All data is made publicly available via the Natural Scenes Dataset (https://naturalscenesdataset.org/)

Code availability: This data does not use any original code. Any additional information required to reanalyze the data reported in this paper is available from the lead contact upon request.

Acknowledgements: The authors would like to thank the authors of the Natural Scenes Dataset for making these data publicly available. This work was supported by an award from the National Institutes of Mental Health (R01MH130529) to CER. AS was supported by the Neukom Institute for Computational Sciences.

Number of Figures: 3

Number of Tables: 0

Number of Supplemental Figures: 8

Abstract word count: 236

Main text word count: 4865

During the preparation of this work, the author(s) used Claude (Anthropic) to assist in revising the manuscript. After using this tool/service, the author(s) reviewed and edited the content as needed and take(s) full responsibility for the content of the publication.

Abstract

The human brain seamlessly integrates internally generated thoughts with incoming sensory information, yet the large-scale networks that support these functions -- the (Default Network, DN) and external (Dorsal Attention Network, dATN) -- are traditionally viewed as functionally antagonistic. This raises a crucial question: how does the brain integrate information across these seemingly opposed systems? Here, using densely sampled 7 T fMRI, individualized resting-state parcellations, and voxel-wise population-receptive-field mapping, we show that these internal/external networks are more interlocked than previously thought. Although spontaneous DN and dATN activity during rest is uncorrelated at the network level, functional coupling across networks is shaped by the latent visual field preferences of individual voxels in each network, as measured during independent retinotopic mapping. Voxels that share visual field preferences exhibit stronger spontaneous coupling than those with divergent preferences. These retinotopically-specific interactions are bivalent: DN voxels with negative (suppressive) visual response amplitudes are anticorrelated with matched (positive) dATN voxels, while those with positive response amplitudes are positively correlated. Thus, distinct subpopulations of visually-tuned DN voxels participate in spatially-specific interactions with the dATN. Further, retinotopic coding is intrinsic to the DN, persisting even during periods of elevated top-down drive from the DN to the dATN. These findings challenge the prevailing view of global DN-dATN antagonism, revealing a latent, voxel-level architecture of retinotopically-grounded interactions. Taken together, our results suggest that retinotopic coding underpins the dynamic coordination of perception and thought in the human brain.

Main text

A fundamental goal of neuroscience is to understand how distributed activity across the brain's functional networks gives rise to cognition [1–9]. Central to this aim is understanding principles that govern interactions between different brain networks, particularly networks involved in externally-oriented attention (e.g., processing sensory input) and internally-oriented attention (e.g., introspection and memory) [10–14]. This knowledge gap confounds our understanding of human cognition: the interaction between internally- and externally-oriented representations is foundational to how we perceive, remember, and navigate our world, yet the 'common language' facilitating the communication between neural systems that process this information remains unclear.

Historically, the Default Network (DN) and Dorsal Attention Network (dATN)—prototypical networks for internal and external attention, respectively—have been viewed as functionally competitive [10–12,14,15]. Classic neuroimaging studies show that externally oriented tasks activate the dATN and deactivate the DN [10,13,14,16–18] while internally oriented tasks produce the opposite pattern [6,19–23]. This dissociation is also observed at rest, where DN and dATN activity is typically independent or anti-correlated [11,12,24,25], depending on the application of global signal regression [11,26]. Such findings have led to the prevailing view that DN/dATN antagonism supports selective attention to either internal or external information, minimizing interference between

perception and memory [10,12,27,28]. Yet, this framework leaves open a fundamental question: if these
networks are functionally dissociated, how does the brain integrate perceptual and mnemonic
information when both are required (e.g., anticipatory saccades, memory-based attention tasks,
and mental imagery)?

Recent studies of the voxel-level coding properties within these large-scale networks offer insight
into this question. Although the DN is traditionally associated with abstract or semantic coding[2,28–
30], emerging evidence suggests that it also exhibits a neural code typically associated with
externally-oriented visual processing: coding of retinotopic stimulus position[31–34]. Notably,
retinotopic coding in the DN differs from that observed in traditional visually responsive areas,
including the dATN. While visual stimulation elicits position-dependent *increases* in neural activity
in traditional visual areas, many DN voxels often show position-dependent *decreases* in
activity[31,33,34]. This voxel-level pattern suggests that the DN's global deactivation during externally-
oriented tasks may not reflect a simple disengagement from external input, but rather a structured,
spatially-tuned response to visual stimulation.
87
What purpose might the DN's voxel-level retinotopic code serve? We and others have proposed
that the visual code in the DN might play a functional role in structuring mnemonic-perceptual
interactions[31,32,34,35]. Recent work provides critical support for this theory, revealing that scene-
selective memory regions near the DN exhibit voxel-level retinotopic opponency with scene-
selective visual areas. Specifically, the inverted retinotopic code in mnemonic regions is
functionally tethered to the positive code in perceptual regions: during perception, visual stimuli
at specific field locations activate perceptual voxels while suppressing memory voxels tuned to
the same location, a pattern that reverses during memory retrieval[34]. These results indicate that
visual field location can coordinate dynamic interactions between specialized perceptual and
mnemonic areas at the cortical apex, raising the intriguing hypothesis that retinotopic grounding
might support perceptual-mnemonic interactions more broadly across the brain. However,
whether retinotopic coding serves a more general function in structuring interactions across large-
scale networks remains unknown.
101
Here, we tested the hypothesis that global interactions across large-scale internally- and
externally-oriented brain networks are structured at the voxel level by a retinotopic code[35]. This
framework challenges the traditional view of internally- and externally-oriented brain networks as
globally antagonistic, proposing instead that voxel-level retinotopic tuning enables functional
coupling and shared information processing between these networks. We leveraged a high-
resolution 7T fMRI dataset[36], individualized network identification[3,4,8], and voxel-wise modeling[37]
to evaluate three core predictions. First, voxel-wise retinotopic coding is robustly present within
individuals' DN and dATN networks, but their tuning polarities diverge: positive retinotopic
responses dominate the dATN, while DN contains a significant proportion of retinotopic voxels
with negative response amplitudes to visual stimulation. Second, we predicted that spontaneous
DN–dATN interactions during resting-state fMRI would be structured by the retinotopic properties
of individual voxels. Specifically, functional coupling should be stronger between voxels that share
visual field preferences across networks, revealing that retinotopic position-specific responses
form a latent architecture to scaffold cross-network interactions even in the absence of overt task

demands. Third, we hypothesized that these retinotopically grounded interactions would support
both top-down and bottom-up coupling between the DN and dATN, suggesting that shared spatial
tuning enables dynamic, bidirectional interactions. Together, these findings would position
retinotopy as a unifying framework for brain-wide information processing and the coordination of
internal and external attentional dynamics.

Retinotopic coding in internally and externally oriented networks

To investigate the role of retinotopic coding in structuring interactions between internally- and
externally-oriented brain networks, we analyzed 7T fMRI data from the Natural Scenes Dataset[36],
acquired from the same densely-sampled participants during both resting-state and retinotopic
mapping sessions (Fig. 1A-B).

We first identified individualized large-scale networks for each participant using their resting-state
fMRI data [8,38] (Fig. 1B, S1). Resting-state data were preprocessed using independent components
analysis (ICA) with manual noise component selection[39,40], and no global signal regression was
performed[26]. Networks were identified using a multi-session hierarchical Bayesian modeling
approach[8,38,41], which leverages repeated data runs to estimate within participant variation and
derive stable parcellations for 15 cortical networks, including the Default Networks A-B and the
Dorsal Attention Networks A-B (Fig. 1B). Unless otherwise noted, we combined the Default
Networks A-B and the Dorsal Attention Networks A-B to constitute our internal and externally
oriented networks, respectively (hereafter, DN and dATN).

Next, we determined the visual field preferences of all voxels within these individualized networks
using a voxel-wise population receptive field (pRF) modeling approach[37,42] to fit each participant's
BOLD activity during retinotopic mapping[37] (Fig 1A, S2). We considered any voxel with >14%
variance explained by our pRF model to be exhibiting a retinotopic code, and hereafter we refer
to these voxels as "pRFs". This threshold was determined by defining the noise floor of our
retinotopic model in the DN and dATN by comparing task-derived model fits to a control null
distribution derived from resting-state fMRI data (Fig. 1C; distribution of voxel-wise variance
explained by task versus null, K-S tests: $D^-s>0.124$, ps<0.001). Two pRF features were of
particular interest: center position, which estimates the preferred location in visual space that
drives a given voxel's response (x,y), and amplitude of the voxel's response (positive or negative)
(Fig. 1A). Importantly, both features were highly reproducible across runs of pRF data in both
subnetworks of the dATN and DN in all subjects (Fig. 1D).

Next, we compared the retinotopic properties of voxels within the DN and dATN[11,12,18]. Across
participants, we observed a larger proportion of retinotopic voxels in the dATN as compared to
the DN (43.36% of dATN voxels, 9.42% of DN voxels) consistent with their role as externally- and
internally-oriented networks, respectively. Further, the amplitude of retinotopic responses (i.e.
whether a stimulus in their preferred visual field location evoked a positive or a negative BOLD
response) differed significantly between these two networks (Fig 1E). Consistent with prior
reports, negative voxel-wise response amplitudes were clustered within the DN and in similar
locations across participants [31,34], evidenced by a consensus map of pRF sign (Fig. S3). On
average, more than half (58.77%) of all pRFs in the DNs were inverted (i.e., had a negative BOLD

response to visual stimulation in their population receptive field, -pRFs). In contrast, just 7.57% of
the pRFs in the dATN were -pRFs (i.e., the vast majority of the voxels had positive BOLD
responses to visual stimulation in their receptive field, +pRFs). The difference in negative pRF
proportion between the dATNs and DNs was significant (t(6)=7.94, p<0.001; Fig. 1E, inset), and
there was no difference among the sub-networks of each system (dATNs: t(6)=0.24, p=0.82; DNs:
t(6)=0.89, p=0.41). This distinction is particularly remarkable given the proximity of dATN and DN
clusters in posterior cerebral cortex. Like visual areas, both DN and dATN pRFs exhibited a
contralateral visual field bias, as we would predict from prior literature [31,33,34] (positive dATN pRFs:
t(6)=26.0, p<0.001; negative DN pRFs: t(6)=4.86, p=0.003; positive DN pRFs: t(6)=5.20, p=0.002)
(Fig. 1F; see Fig. S4 for additional retinotopic properties). Together, these results show that
individualized DNs have voxel-wise responses that exhibit visual coding -- the necessary
foundation for assessing whether the voxel-wise retinotopic code structures global interactions
between the internally- and externally-oriented networks.

Figure 1. Inversion of retinotopic coding between externally- and internally- oriented networks in the human brain. A.
Population receptive field (pRF) modeling with fMRI. We established visual field preferences for each voxel using pRF
modelling[37]. Voxels with positive BOLD responses to the visual stimulus are referred to as positive pRFs (+pRFs), and
those with negative BOLD responses are referred to as negative pRFs (-pRFs). B. Individualized resting-state network
parcellation. Resting-state fMRI was collected in all participants (N=7; 34-102 minutes per participant) and used to
derive individualized cortical network parcellations. Parcellations were generated using the multi-session hierarchical
Bayesian modelling approach with the Yeo 15 HCP atlas as a prior[8,41]. C. PRF model variance explained is greater
when fit to the pRF mapping task versus resting-state fMRI data for negative and positive pRFs in the DN and dATN.
Histograms show voxel-wise variance explained for all pRFs fit to rest (dark) and the pRF modeling task fMRI data

Visual responsiveness stratifies DN-dATN resting-state interactions

Next, we examined whether the retinotopic response properties of individual voxels (estimated
during the retinotopic mapping sessions) predict their functional coupling across DN-dATN during
task-absent, spontaneous activity (during the resting state scans). Specifically, we tested whether
voxel-level visual response classes—non-retinotopic voxels, positively tuned pRFs (+pRFs), and
negatively tuned pRFs (–pRFs)—predict the strength and direction of coupling between the DN
and dATN. Such a finding would reveal a stable, voxel-level organizational principle underlying
the global dissociation that is hypothesized to exist between the DN and dATN[11–13,15,24,25].

Across resting state runs, global activity of the DN and dATN was independent (i.e., not
correlated) after accounting for variance across all cortical networks using partial correlation[43]
(mean correlation = 0. 0.031±0.13 s.d., t(6) = 0.6287, p=0.55; Fig. 2A). Crucially, however, this
global relationship masked a striking stratification based on DN voxel responsiveness (Fig. 2B).
Non-retinotopic DN voxels (i.e., pRF model R^2<0.14) were not significantly correlated with the
dATN (mean correlation = 0.014±0.135, t(6) = 0.26, p = 0.79). In contrast, DN voxels that
responded positively to visual stimulation (DN positive pRFs, +pRFs) had a positive correlation
with the dATN (mean correlation = 0.284±0.152, t(6) = 4.96, p = 0.0025), while DN voxels with
systematic negative responses to visual stimulation (DN negative pRFs, -pRFs) were anti-
correlated with the dATN (mean correlation = -0.21±0.149, t(6) = -3.75, p = 0.0094). Thus, voxel-
level visual response profiles shape DN-dATN coupling during spontaneous resting-state activity.
Specifically, opponency at rest between the DN and dATN appears to be driven by the subset of
DN voxels with negative retinotopic tuning.

Shared visual field preferences structure functional coupling among visually-responsive DN and dATN voxels

220 We next asked whether functional coupling between DN and dATN voxels is modulated by the
221 visual field preferences of retinotopic voxels — that is, whether their pRFs are centered on similar

versus different visual field locations (i.e., their retinotopic alignment). We hypothesized that DN–dATN interactions would be stronger for voxel pairs with shared visual field preferences. To test this, we quantified the retinotopic alignment of voxel-wise pRFs across the DN and dATN. Because we only considered positive pRFs in the dATN, hereafter we refer to these as "dATN pRFs."

For each pRF in the DN (+pRFs and –pRFs), we computed the Euclidean distance between its receptive-field center (x, y) and those of all dATN pRFs (Fig. 2C). We then identified the 10 closest dATN pRFs ("Matched" set) and averaged their resting-state time series. As a comparison group, we repeated this procedure using 10 randomly selected, poorly matched dATN pRFs ("Random" set; see Methods). This procedure was repeated 1000 times for each DN voxel across resting-state runs.

Matched dATN pRFs were distributed throughout the network, spanning posterior retinotopic cortex to anterior regions, including prefrontal cortex (Fig. S5). Crucially, the spatial dispersion (i.e., the distance between the pRFs across the cortex) of matched and randomly-matched pRFs did not significantly differ (matched versus random – DN -pRFs x dATN pRFs: $t(6)=0.38$, $p=0.71$; DN +pRFs x dATN pRFs: $t(6)=0.67$, $p=0.52$), ruling out spatial proximity as a confounding factor -- any difference in correlation with DN voxels should therefore be attributable to shared visual field preferences.

If DN-dATN interactions are scaffolded by a retinotopic code, spatially matched pRFs should exhibit stronger functional coupling than randomly-matched pRFs. Consistent with this prediction, after partialling out variance from DN +pRFs to isolate the specific co-fluctuation between DN -pRFs with dATN pRFs [34,43], DN -pRFs remained anticorrelated with dATN pRFs in nearly every resting-state run (Fig. 2D). Critically, matched pRFs were significantly more anticorrelated compared with randomly-matched pRFs (linear mixed-effects model with random intercepts for subject and run: $F(1,194) = 105.7$, $p < 0.001$; coefficient = -0.023 ± 0.002 s.d.). This effect was evident when run-level correlations were averaged within each participant (7/7 participants $r_{matched} < r_{random}$; $t(6)=6.9$, $p<0.001$, Fig.2E) and could not be explained by signal quality differences, as matched and random pRF sets did not differ in tSNR ($t(6) = 1.01$, $p = 0.353$). This is strong evidence that the retinotopic code underpins the opponent interaction between negative DN and positive dATN pRFs.

Voxel-wise retinotopic alignment scaffolded the interaction between positive DN and dATN pRFs as well. After controlling for DN -pRFs, DN +pRFs were positively correlated with dATN pRFs (Fig. 2D). Retinotopic alignment again strengthened the interaction: matched correlations exceeded random correlations in a mixed-effects model ($F(1,194)= 406.5$, $p < 0.001$; coefficient = $+0.050 \pm 0.003$ s.d.) and for every individual participant (7 / 7; $t(6) = 5.7$, $p = 0.001$) (Fig. 2E).

Together, these results demonstrate that shared retinotopic alignment enhances functional coupling between DN and dATN voxels. Voxels tuned to the same region of visual space show stronger spontaneous co-fluctuation—whether positively or negatively coupled—than those with non-overlapping spatial preferences. This suggests that a shared spatial code helps organize spontaneous interactions between large-scale internal and external attention networks during rest.

Subnetwork Specificity within the DN

Recent work has suggested that the subnetworks of the DN, DN-A and DN-B, support different cognitive processes: episodic projection and theory of mind, respectively [8,44–46]. Indeed, DN-A is particularly sensitive to the process of scene construction[46], closely linked to visual imagery, suggesting that dATN pRFs would show greater interaction with visually-responsive voxels in DN-A compared with DN-B. Consistent with this hypothesis, spontaneous correlations with dATN pRFs were significantly stronger for DN-A than DN-B voxels (collapsed across positive and negative pRFs: $t(6) = 4.80$, $p = 0.003$). Crucially, however, voxel-scale retinotopic alignment structured interactions between the DN and the dATN for both DN sub-networks (Fig. 2F-G; DN-A: -pRFs $t(6) = -4.56$, $p = 0.004$; +pRFs $t(6) = 5.65$, $p = 0.0013$; DN-B: -pRFs $t(6) = -7.49$, $p < 0.001$; +pRFs $t(6) = 2.92$, $p = 0.027$). The strength of this effect did significantly differ between DN-A and DN-B ($t(6) = 1.51$, $p = 0.182$). Thus, although DN-A is more strongly globally coupled with dATN, retinotopic preferences of individual voxels structure functional interactions across both DN subnetworks equally.

In addition, using the same matched-vs-random pRF procedure, we found that resting activity between the lateral place-memory area (LPMA) and the adjacent occipital place area (OPA) was significantly more correlated for retinotopically matched than random voxel pairs ($t(6)=3.01$, $p=0.024$; Supplementary Results). This shows that retinotopic scaffolding within domain-specific systems extends beyond perceptual and memory tasks [34], organizing spontaneous activity within these systems as well. These findings build on and extend our previous work [34] and others[47].

Figure 2. Retinotopic coding organizes spontaneous interaction between internally and externally oriented brain networks. A. Overall activity of the dorsal attention networks (dATN-A/B) and default networks (DN-A/B) were independent at rest. One individual's dATN and DN are shown. Time series from all voxels in the DN and dATN subnetworks were averaged together, and we calculated the partial correlation[43] of these networks while accounting for variance of the other 11 networks within the group-prior parcellation[1,8]. The dATN and DN network correlation was not significantly different from zero, suggesting the activity of these networks is largely independent. Bar plot shows the average partial correlation across participants, each data point is the average of all runs for a single participant. B. Interaction between the DN and dATN differs by visual field preference of DN voxels. *Splitting the DN voxels by visual responsiveness revealed distinct patterns of resting-state correlation. DN* +pRFs had a positive correlation with the dATN (mean correlation = 0.22±0.144, t(6) = 3.99, p = 0.0072), while non-retinotopic DN voxels (i.e., pRF model R2 < 0.08) were not significantly correlated with the dATN (mean correlation = 0.02±0.115, t(6) = 0.37, p = 0.72). On the other hand, DN -pRFs were anti-correlated with the dATN (mean correlation = -0.20±0.12, t(6) = 4.22, p = 0.0055). *C.* Determining spatially-matched pRFs in dATNs and DNs. We assessed the influence of retinotopic coding on the

interaction between internally- and externally-oriented brain areas' spontaneous activity during resting-state fMRI, by
comparing the correlation in activation between pRFs in these networks that represent similar (vs. different) regions
of visual space. For each DN -pRF, we established the top 10 closest *positive dATN pRFs' centers based on their x*
and y position ("matched"), and correlated *the DN pRF* time series with the average *timeseries of these* matched
dATN pRFs. We *compared these correlation values with the correlation of the DN pRF timeseries paired with 10*
randomly selected pRFs from the 33% furthest (1000 iterations per pRF). We computed this for all *DN pRFs for each*
all *runs in each subject. Inset* shows *the pairwise distances between all pRFs in all participants, dotted line* shows the
66%ile. D. Negative (upper) and positive (lower) DN pRFs show retinotopic specific interaction with the dATN. Each
set of bars depicts the average correlation of the matched and randomly paired pRFs between the DN and dATN for
each participant, with each run shown as connected points. All participants showed greater correlation (either positive
or negative) for matched compared with randomly paired pRFs. E. Data shown averaging runs within each
participant. For both positive and negative pRFs, the correlation between matched compared with randomly matched
pRFs was significantly greater (consistent with their amplitude, ps<0.01). F, G. show the correlation between positive
and negative pRFs in the DN with the dATN, split across the sub-networks of the DN-A and B. Both DN-A and B
show a significant impact of matching, indicating that both subnetworks interact with the dATN via a retinotopic code
*(ps<0.05). *: p<0.05, **: p<0.01, ***:p<0.001*

Retinotopic coding is inherent to internally-oriented areas

Our findings thus far highlight a role for retinotopic coding in structuring spontaneous interactions
between voxels across large-scale internally- and externally-oriented brain networks. However, a
key mechanistic question remains unresolved. Is retinotopy an intrinsic property of the DN, or
does their retinotopic code only emerge in response to bottom-up perceptual input? For instance,
top-down DN-driven modulation of dATN activity might manifest as a global, non-selective
suppression, and retinotopic coding in the DN might only emerge in response to bottom-up signals
from the dATN. Alternatively, retinotopic coding may be intrinsic to the DN. In this case, top-down
signals from the DN to the dATN would be retinotopically-specific, allowing the DN to shape fine-
grained spatial representations within the dATN. Disambiguating these possibilities is essential
for determining whether the retinotopic scaffold constitutes a general mechanism for cross-
network communication, independent of task demands or cognitive domain (e.g., memory versus
perception).

To address this, we again turned to participants' resting-state fMRI data. Because participants
are not engaged in any task, resting-state provides a neutral testbed for assessing spontaneous
DN–dATN interactions. Moreover, experience sampling during rest has shown that attention
naturally alternates between internal and external focus during rest[48,49] , making it possible to
assess whether retinotopic coding emerges primarily during bottom-up (dATN-driven) or top-
down (DN-driven) events. We developed an event-triggered analytical approach to dissociate
bottom-up perceptual from top-down mnemonic events. Specifically, we identified timepoints
where spontaneous activity of individual DN or dATN pRFs exceeded the 99th percentile of their
resting-state distribution. These high-activation time points were treated as neural "events" (Fig.
3A-C). Events in DN pRFs were interpreted as top-down events, while events in dATN pRFs were
interpreted as bottom-up events.

To test whether these events produced retinotopically-specific responses in the target network,
we compared peri-event activation in the target network's most 10 closely matched pRFs (i.e.,
those with similar visual field preferences) to that in the 10 worst-matched (anti-matched) pRFs
(Fig. 3A). We used the worst matched pRFs for this analysis because the large number of pRFs
made the random matching procedure impractical. All analyses were conducted separately for

positive and negative pRF populations within the DN. This design enabled us to test two
competing predictions: if retinotopy in the DN only reflects bottom-up input, we should only see
retinotopically specific coupling during bottom-up (dATN-driven) events. If, however, the DN
possesses an intrinsic retinotopic scaffold used for top-down communication, we should observe
retinotopic specificity during both bottom-up and top-down events. A windowed correlation
analysis produced similar results (Fig. S6).

We detected 78,978 top-down events in DN -pRFs, 52,595 top-down events in DN +pRFs, and
541,546 bottom-up events in dATN pRFs. Bottom-up events were more frequent than either top-
down type (dATN vs. negative DN: t(6)=15.19, p<0.001; dATN vs. positive DN: t(6)=25.63,
p<0.001), but there was no difference between top-down event types (t(6)=2.03, p=0.18). On
average, participants had 2082±535 (mean±SD) negative DN, 1799±400 positive DN, and
3102±602 dATN events per run. Each pRF showed 0–4 events per run (Fig. S7). More than 90%
of timepoints involved <10 simultaneous events. The wide distribution of events in time suggested
that individual pRF-level correlation could be isolated from global fluctuations in regional activity,
making this approach suitable for evaluating distinct interactions at the individual voxel level.

We found a robust effect of retinotopic alignment (i.e., matched versus anti-matched) on pRF
activation during both bottom-up and top-down interactions (Fig. 3D-I). For DN -pRFs, a linear
mixed-effects model (factors: top-down/bottom-up and retinotopic alignment; subject as random
effect) revealed a main effect of match status (F(1,24)=9.73, p=0.004) and no interaction
(F(1,24)=0.084, p=0.77). During top-down events in DN -pRFs, matched dATN pRFs showed
lower activity than anti-matched (t(6)=5.46, p=0.001) and were significantly deactivated relative
to the pre-event baseline. During bottom-up events, DN -pRFs showed elevated activity compared
to pre-event baseline, but again with lower activation for matched vs. anti-matched pRFs
(t(6)=3.60, p=0.011), consistent with a retinotopically-specific interaction.

The interaction between DN +pRFs and dATN pRFs also showed evidence of retinotopic coding
during both bottom-up and top-down events, but these effects were modulated by a direction ×
match interaction (F(1,24)=12.84, p=0.002). Both top-down (t(6) = 8.76, p < 0.001) and bottom-
up (t(6) = 9.14, p < 0.001) events evoked strong activation in the target network (dATN or DN,
respectively). However, anti-matched pRFs were more active during top-down compared to
bottom-up events (t(6) = 4.92, p = 0.0026), suggesting that top-down signals from positive DN
pRFs to dATN may be less retinotopically specific than bottom-up signals. These results align
with prior findings showing decreased spatial precision in visual representations during memory
recall compared to perception[50,51].

Taken together, these results support the view that retinotopic coding serves as a general scaffold
for DN-dATN interactions. This alignment shapes spontaneous coupling during both periods of
DN-driven (top-down) and dATN-driven (bottom-up) activity, even in the absence of external
tasks. Because the effect persists without sensory input, it likely reflects an intrinsic feature of the
DN activity rather than a transient result of bottom-up drive.

Figure 3. Top-down vs. bottom-up neural events detected in spontaneous resting-state dynamics show evidence for retinotopically-specific suppression. A. Event detection and analysis procedure and example events from a single resting-state run. To detect events, we extracted the time series from each pRF in the source regions (top-down: positive or negative pRFs in the DN; bottom-up: positive pRFs in the dATN) and isolated time points where the z-scored time series exceeded 2.4 s.d. (99th percentile). We then examined the activity of 10 best matched and 10 worst matched (anti-matched) pRFs from the target region in this peri-event time frame (6 TRs (8 s) before and after the event). B. Example top-down event in the representative time series shows elevated source pRF activity (DN -pRF) and corresponding target area activity (dATN +pRF). C. Same as B, but for bottom-up activity with the event detected in a dATN +pRF. D, E. Evidence for retinotopically-specific suppression of ongoing activity during events top-down events detected in DN -pRFs (D) and bottom-up events detected in dATN +pRFs (E). D. Time series show the peri-event activity of matched and anti-matched dATN +pRFs averaged across all participants for events detected in DN -pRFs (N=78,978 events). E. Time series shows the peri-event activity in DN -pRFs during events detected in dATN +pRFs

(N=541,546). F. For DN -pRFs paired with dATN +pRFs, target area shows retinotopically-specific suppression of
activity for both top-down and bottom-up events. Bars show the average activation at event time of the target areas'
matched and anti-matched pRFs for each participant. Activity was lower in matched compared with anti-matched pRFs
for top-down and bottom-up events (ts>3.6, ps<0.011). G, H. Evidence for retinotopically-specific excitation of ongoing
activity during events top-down events detected in DN +pRFs (G) and bottom-up events detected in dATN +pRFs (H).
G. Grand average time series for matched and anti-matched dATN +pRFs during events detected in DN +pRFs for all
participants. H. Grand average time series for matched and anti-matched DN +pRFs during events detected in dATN
+pRFs. I. For DN +pRFs paired with dATN +pRFs, target area shows retinotopically-specific excitation for both top-
down and bottom-up events. Bars show the average activation at event time of the target areas' matched and anti-
matched pRFs for each participant. Activity was higher in matched compared with anti-matched pRFs for top-down and
bottom-up events (ts>8.75, ps<0.001). Interestingly, the activity of anti-matched pRFs was greater during top-down
compared with bottom-up events (t(6)=4.92, p=0.0026), suggesting that top-down input from DN +pRFs to the dATN
+pRFs may be more global and less retinotopically-targeted compared with bottom-up signaling between these
networks. For time series plots, solid bars along the x-axis indicate periods with a significant difference between
*matched and anti-matched pRF activity within the target area. *: p<0.05, **: p<0.01, ***:p<0.001. -DN: Negative DN*
pRFs; +DN: positive DN pRFs; +dATN: Positive dATN pRFs

Discussion

Despite extensive evidence that internally- and externally-oriented brain networks – including the
default network (DN) and dorsal attention network (dATN) – are critical for human cognition[1–8,11–
13], the coding principles that enable these distributed systems to interact have remained
unclear[30,52–56]. Here, we show that DN–dATN coupling is retinotopically grounded at the voxel
scale: the visual field biases of individual voxels scaffold bidirectional interactions between these
networks, even during spontaneous dynamics in the absence of visual task demands. Analyses
of transient neural events confirm that this retinotopic opponency shapes both bottom-up signals
from the dATN to the DN and top-down signals from the DN to the dATN, indicating that the
retinotopic code is intrinsic to both internal and external networks. These findings offer a multi-
scale account of network communication in which macro-scale dynamics emerge from latent, fine-
grained voxel biases. Rather than purely dissociated, our data suggest that the DN and dATN are
dynamically coordinated systems that integrate perception, attention, and thought through a
shared spatial scaffold.

Resolving the coding principles of the DN is critical given its central roles in spatial and episodic
memory, social cognition, and executive function[13,57–62]. Classic views of systems-level neural
coding posit that sensory codes like retinotopy are gradually replaced by abstract, amodal codes
moving up the cortical hierarchy towards the DN[2,29,30]. Our findings and others challenge this view.
Instead of shedding the retinotopic code at the cortical apex, the DN retains a retinotopic code[31,33]
and functionally deploys this code to structure interactions with the externally-oriented dATN. The
present work, which shows that retinotopy structures communication across large-scale networks
even at rest, significantly extends prior work showing that voxel-scale retinotopic-alignment
coordinates interactions between specialized mnemonic and perceptual areas near the DN during
visuo-mnemonic tasks[34,47]. Thus, a code once thought to be exclusive to early visual cortex and
visually-oriented tasks plays a widespread role in shaping brain activity across the cortical
hierarchy—even at rest.

Establishing this voxel-level structure within the DN and dATN reframes a long-standing debate
that has cast these networks as globally competitive or functionally independent[11,23,27,28]. These
views have stemmed from macro-scale observations of reciprocal activation patterns during

external versus internal task demands[6,10,13,14,16–23], and resting-state analyses that reveal zero or
negative correlations between their mean time series[11,12,24,25]. By focusing on global, network-
level activity across voxels, however, these approaches obscure a latent, voxel-level structure.
Our voxel-level analysis shows that DN–dATN coupling is not globally antagonistic, but instead is
selectively coordinated. Two subpopulations of voxels within the DN contribute to a retinotopically-
grounded cross-network interaction that is stratified by voxel-level visual selectivity. One
population of DN voxels is positively tuned to visual stimulation, and positive covaries with dATN
voxels that share their visual field preference. On the other hand, DN voxels that are negatively
tuned to visual stimulation show an opponent dynamic with retinotopically matched dATN voxels.
When these voxel-wise tuning preferences are not taken into account, cross-network activity
"averages out" into a global opponency or independence[11,12], reinforcing the misconception that
the networks support mutually exclusive cognitive modes. By revealing a shared retinotopic
scaffold, our findings reconcile why DN and dATN can appear oppositional in coarse analyses yet
remain functionally integrated, offering a new framework for understanding how internal and
external attention are coordinated in the human brain.

Importantly, there are key differences in the nature of retinotopic coding between the DN and
visual areas, including the dATN. First, retinotopy in the DN is predominantly negative in
valence—DN voxels more often show spatially-specific suppression, rather than activation, in
response to visual stimulation[31,33,34]. Second, although many DN voxels exhibit reliable retinotopic
coding, the DN lacks the map-like retinotopic organization seen in early visual cortex. In visual
areas, retinotopic coding is not only the foundational code, but also the dominant topographic
organizing principle[63]. However, the presence of a coding scheme does not necessarily entail a
map-like organization on the cortical surface. In high-level regions like the DN, it is important to
distinguish between the presence of a code and its cortical layout. For example, rodent and bat
head direction cells are not laid out in a literal ring, but the population code of these neurons forms
a ring manifold[64,65]. Similarly, in humans, retrosplenial cortex shows head-direction coding during
navigation tasks despite lacking topographic organization of head-direction responses[66].
Analogously, the DN may implement a retinotopic code that is distributed across the network in a
format that does not spatially mirror the retina. That is, the DN may use a retinotopic code without
a retinotopic map – the representational structure can be preserved even in the absence of
spatially ordered cortical layouts.

What function might the bivalent (positive and negative) visual coding within these large-scale
networks serve? We propose two complementary possibilities. One possibility is that joint coding
of positive and negative DN pRFs may serve as a neural mechanism for maintaining separate
channels for perceptual and mnemonic information[53], preventing mnemonic signals from being
interpreted as external or interfering with one another – analogous to broadcasting on different
radio frequencies to carry different signals without interference. A second possibility is that
oppositional coding could be a mechanism for signaling mnemonic predictions via top-down
inhibitory processes[67]. Specifically, when the DN generates predictions about incoming sensory
information based on memory, the inverted retinotopic code could act as a suppressive signal
that sharpens tuning in perceptual areas and enhances signal-to-noise for expected stimuli[68,69].
These mechanisms may work in concert: the inverted code simultaneously maintains separate
channels for memory/perception while enabling precise top-down predictive signaling. Future

work that combines high-resolution recordings with behavior will be essential for testing how these
mechanisms jointly support constructive operations such as memory-based prediction during
visually guided navigation.

Retinotopic alignment between the DN and dATN was clear in both subnetworks of the DN, DN-
A and DN-B[3,8,20]. This is surprising given their distinct functional profiles: DN-A has been more
directly linked to visually grounded memory processes, such as episodic projection and scene
construction[8,20,46], and spatially overlaps with regions previously shown to exhibit retinotopy and
engage in scene memory and perception [70]. In contrast, DN-B is more often associated with
processes that are not obviously tied to vision: theory of mind and affective tasks, such as
interpreting false beliefs or representing physical and emotional pain [8,20]. Why might the DN-B
show retinotopically-grounded coupling with perceptual networks? Retinotopic coding might still
be a useful format for transforming abstract social representations into sensory-grounded signals
to inform perceptual predictions (e.g., anticipating changes in facial expression) or behavioral
decisions (e.g., making eye movements). Future work might consider direct manipulation of social
perceptual processes to assess the impact of social tasks on retinotopic coding between DN-B
and dATN.

Moments of high spontaneous activity originating in the DN co-occurred with suppression of
retinotopically-matched dATN pRFs, suggesting that retinotopy functions as a native coding
format in the DN for targeted modulation of perceptual cortex. This result aligns with other recent
studies suggesting an important role of the DN in shaping visual processing. For example,
ongoing pre-stimulus DN activity has been shown to influence sensitivity during near-threshold
visual object recognition[71]. Other work has shown that subareas of the DN encode kinematic of
spatial exploration in rodents[72], and represent the visuospatial context that is associated in
memory with a perceived scene[34,70,73–75]. Relatedly, DN activity reflects semantic-level attentional
priorities during visual search[76]. Taken together, these findings show that, rather than being
disengaged during visual tasks, the DN actively shapes responses in perceptually-oriented cortex
in a spatially-precise manner. In this sense, retinotopic coding is part of the DN's "native
language". Taken together, these findings prompt a reevaluation of the DN's role in perceptual
processing, and the extent to which roles in "internally- and externally-oriented attention"
adequately captures the DN and dATN's role in cognition.

Is the DN a "visual" network? One possible interpretation of retinotopic coding in the DN is that
the DN directly and obligatorily represents retinal position in addition to more abstract features[37,63].
Under this hypothesis, the retinotopic code indicates that the information represented in the DN
is, in part, sensory. Alternatively, the apparent visual coding may simply represent an underlying
connectivity structure[77], which enables associative and semantic information that the DN directly
represents[30,78,79] to be effectively transferred to sensory areas of the brain. Under this alternative
hypothesis, the information represented in the DN is not itself sensory in nature; the retinotopic
code in the DN simply serves as a "highway" between the abstract representations in the DN and
sensory representations in the dATN. Notably, in either case the retinotopic scaffolding represents
a latent structure linking high-level and low-level areas through consistent, spatially-organized
interactions[77]. This provides more evidence that low-level sensory codes are distributed across
the brain, joining recent work showing latent somatotopic codes in regions of the brain that are

not typically associated with somatosensation, including visual cortex[80]. The wide and overlapping distribution of sensory codes across the brain may allow for multiplexing of complex information to structure cross-network interactions[35,80]. Further studies investigating this framework with diverse tasks and stimuli could reshape our understanding of how the brain processes and integrates information across different levels of cognitive complexity.

In summary, our results show that a voxel-level retinotopic code organizes the spontaneous interactions between large-scale internally- and externally-oriented networks in the human brain – the DN and dATN. Even when global activity appears uncorrelated across DN-dATN, voxel-level visual-field tuning reveals a tightly interlocked, bidirectional functional dynamic that persists in the absence of external stimulation. This latent scaffold reconciles the apparent macroscale independence of internally- and externally- oriented systems with their evident functional need to cooperate, revealing that the DN is not divorced from perceptual networks, but modulates perceptual voxels through a common visuospatial reference frame. Taken together, these results indicate that retinotopic coding serves a brain-wide "common currency" or subspace for information exchange[35,80] across distributed large-scale brain networks.

Methods

Dataset and Participants

The data analyzed here are part of the Natural Scenes Dataset (NSD), a large-scale precision 7T fMRI dataset consisting of high-resolution anatomical scans, retinotopic mapping, functional localizers for visual areas, and both task and resting-state fMRI data for eight adult participants. A full description of the dataset can be found in the original manuscript [36]. Here, we detail the data, processing, and analysis steps relevant to the present work.

Participants (N = 8; 2 male, 6 female; ages 19–32) were scanned at the University of Minnesota over the course of 33-43 sessions. All participants had normal or correct to normal vision and no known neurological impairments. Informed consent was collected from all participants, and the study was approved by the University of Minnesota institutional review board. One subject (subj03) was excluded from resting-state analyses for having insufficient resting-state runs that passed our quality metrics (see below).

For the present study, we focused on two components of the NSD protocol: retinotopic mapping and resting-state fMRI. All participants completed three runs of a sweeping bar retinotopic mapping task during (5 mins each). Retinotopic mapping was conducted during Session 1, along with the functional localizer scans. This task is referred to as "RETBAR" in NSD documentation.

All participants completed at least 14 runs of a resting-state fixation task (range: 14-34 runs; 5 mins each). Resting-state data runs were included in all NSD scan sessions after session 20-40 (i.e., session 21, 22, etc.). Each of these sessions included two 5-minute resting-state runs -- one at the start and one at the end of the session -- yielding 14 to 34 total resting-state runs per participant. During the second resting-state run, participants performed a deep breath in the first

561 5 seconds of scanning. To account for this, and to ensure the two resting-state runs were equated
562 in length, we excluded the first 30 seconds of the resting-state data from all runs. One participant
563 (subj03) was excluded from resting-state analyses due to having an insufficient number of usable
564 runs after quality control. All remaining participants had at least 8 high-quality resting-state runs
565 (mean: 14 ± 6.13 runs).

MRI acquisition and processing

567 For this study we made use of the following data from the NSD: anatomical (T1 and FreeSurfer
568 segmentation/reconstruction[81,82]), functional regions of interest (ROIs), and minimally
569 preprocessed retinotopy and resting-state time series. All analyses were conducted in original
570 subject volume space, and data were projected on the surface for visualization purposes only.

Anatomical data

572 Anatomical data was collected using a 3T Siemens Prisma scanner and a 32-channel head coil.
573 We used the anatomical data provided at 0.8mm resolution as well as the registered output from
574 FreeSurfer recon-all, aligned to the 1.8mm functional data. For visualization purposes, we
575 projected statistical and retinotopy data to the cortical surface using SUMA [83] from the AFNI
576 software package[84].

Functional MRI data acquisition and processing

578 All analyses were conducted on 1.8mm isotropic resolution minimally processed runs of a
579 sweeping-bar retinotopy task and resting-state fixation provided in the NSD.

Quality assessment

To ensure only high-quality resting-state data were included, we trimmed the first 25 TRs (40s)
from each run [73], which left 4.25 min of resting-state data per run. We then used AFNI's quality
control assessment tool (APQC[85]) on the raw trimmed resting-state time series to assess the
degree of motion in the resting-state scans. We excluded runs with greater than 1.8mm maximum
displacement per run or 0.12mm framewise displacement from analysis and assessed runs with
greater than 1mm displacement or 0.10mm framewise displacement on a case-by-case basis[8].
After exclusions, one participant (subj03) had only a single run that survived our criteria (4.25
minutes of data)), so we excluded them from resting-state analyses. The remaining 7 participants
had at least 8 resting-state runs (> 34 minutes of data; mean number of runs: 14±6.13 (sd), range:
8-24 runs).

ICA denoising

To further denoise the retinotopy and remaining resting-state data, we used manual ICA
classification of signal and noise on the minimally-preprocessed time series[39,40,74]. We used
manual classification because automated tools perform poorly on the high spatial and temporal
resolution data of the NSD[86]. For each retinotopy and resting state run, we decomposed the data
into independent spatial components and their associated temporal signals using ICA (FSL's

melodic[87,88]). We then manually classified each component as signal or noise using the criteria
established in[40]. Noise signals were projected out of the data using fsl_regfilt[39].

We did not perform global signal regression[26]. Data were normalized to percent signal change. A
2.5mm FWHM smooth was applied to resting-state fixation data used in functional connectivity
network identification. The analysis of voxel-scale interactions performed on unsmoothed data.

Data analysis – Identifying Resting-State Networks

Individual-specific cerebral network estimation

In each participant, we identified a set of 15 distributed networks on the cerebral cortical surface
using a multi-session hierarchical Bayesian model (MS-HBM) functional connectivity approach
[8,38]. Briefly, the MS-HBM approach calculates a connectivity profile for every vertex on the cortical
surface derived from the top 10% of correlations from that vertex to 1,175 ROIs uniformly
disturbed across the cortical surface[1]. We applied an expectation-maximization algorithm,
initialized with a 15-network group-level spatial prior created by applying previous methods of
network identification[1] to a portion of the HCP S900 data, to all the connectivity profiles from all
participants. This algorithm then estimated each network's group-level connectivity profile, along
with parameters for subject-, session/run-, and region-level variability, which together were used
to generate individual-specific, labeled parcellations.

The MS-HBM approach is well-suited to derive parcellations for the participants in the NSD, where
resting-state data was collected across multiple days, because this method uses repeated resting-
state runs for each participant to estimate within-participant variance. This leverages a strength
of the NSD (the relatively large number of resting-state runs for each individual) and can account
for differences in connectivity both within an individual (likely the result of confounding variables
such as scanner variability, time of day, etc.), and between participants (reflecting potentially
meaningful individual differences). Moreover, the MS-HBS incorporates a group spatial prior,
further stabilizing the resulting network parcellations for each participant. This also ensures that
all networks will be identified in all participants, while allowing for idiosyncratic topographic
differences.

Data analysis – Retinotopic Mapping

Population receptive field (pRF) Modelling

The NSD retinotopy stimuli consist of a mosaic of faces, houses, and objects superimposed on
pink noise that are revealed through a continuously drifting aperture. For our analysis, we
considered only the bar stimulus time series, which is consistent with other studies investigating
negative pRFs in high-level cortical areas [31,33,34]. We did not consider the wedge/ring stimulus for
any analyses.

After denoising the retinotopy data, we averaged the three retinotopy runs with the bar aperture
together to form the final retinotopy time series. We performed population receptive field modeling
using AFNI following the procedure described in [42]. First, because the pRF stimulus in the NSD

is continuous, we resampled the stimulus time series to the fMRI temporal resolution (TR =
1.333s). Next, we implemented AFNI's pRF mapping procedure (3dNLfim). Given the position of
the stimulus in the visual field at every time point, the model estimates the pRF parameters that
yield the best fit to the data: pRF amplitude (positive, negative), pRF center location (x, y) and
size (diameter of the pRF). Both Simplex and Powell optimization algorithms are used
simultaneously to find the best time series/parameter sets (amplitude, x, y, size) by minimizing
the least-squares error of the predicted time series with the acquired time series for each voxel.
Relevant to the present work, the amplitude measure refers to the signed (positive or negative)
degree of linear scaling applied to the pRF model, which reflects the sign of the neural response
to visual stimulation of its receptive field.

Identifying Retinotopic Voxels – Empirically-derived R² thresholds

We developed a rigorous, data-driven approach to determine whether our pRF model fits truly
reflect visual coding rather than physiological noise. To do this, we leveraged the resting-state
fMRI data – where there is no visual stimulation -- to create a control (null) distribution for
retinotopic model fits and establish a "noise floor" for each network (i.e., the DN and dATN). Then,
we compared task-derived model fits to this rest-based null distribution to establish an empirical
R² threshold for pRFs in each network.

Specifically, we fit the pRF model to the average timeseries across all resting-state runs for each
participant. We then compared the resulting voxel-level R² distribution to that from the pRF
mapping task data, pooled across participants. To test whether the model fits were significantly
higher for the task vs. null distribution, we performed a one-tailed Kolmogorov-Smirnov test for
each network on the respective cumulative distribution functions (H_0: $CDF_{rest}(R^2) \leq CDF_{task}(R^2)$,
H_a: $CDF_{rest}(R^2) > CDF_{task}(R^2)$). These analyses were performed separately for the dATN and
positive and negatively responsive voxels within the DN.

We defined a voxel as exhibiting a retinotopic code (hereafter referred to as a "pRF") if its model
fit exceeded 14% variance explained. This threshold was based on the 95th percentile of the null
R² distributions, which yielded noise floors of R² = 0.124 (dATN), R² = 0.132 (DN-positive), and
R² = 0.137 (DN-negative). We therefore set our global threshold for visually responsive voxels
across all networks at R² > 0.14, as this value exceeded the noise floor calculated in each network
separately.

Quantifying visual field coverage

Visual-field coverage (VFC) plots represent the sensitivity of an ROI across the visual field. We
followed the procedure in Steel et al., 2024[34], which we have reproduced here. Individual
participant VFC plots were first derived based pRF center, as well as pRF size and R^2. These
plots combine the best Gaussian receptive field model for each suprathreshold voxel within each
ROI by calculating the max operator at each point in the visual field, defined as the maximum
value from all pRFs within the ROI. The resulting coverage plot thus represents the maximum
envelope of sensitivity across the visual field. Individual participant VFC plots were averaged
across participants to create group-level coverage plots.

To compute the elevation biases, we calculated the mean pRF value (defined as the mean of the
average max operator values in a specific portion of the visual-field coverage plot) in the
contralateral upper visual field (UVF) and contralateral lower visual field (LVF) and computed the
difference (UVF–LVF) for each participant, ROI and amplitude (+/−) separately. A positive value
thus represents an upper visual-field bias, whereas a negative value represents a lower visual-
field bias.

Reliability of pRF amplitude and center position estimates

We tested whether key pRF features of interest – amplitude (i.e., positive vs. negative) and center
position (i.e., x,y) – were reliable across retinotopy runs. To assess the reliability of pRF amplitude,
we iteratively compared the amplitude of significant pRFs from individual runs of pRF data.
Specifically, for each retinotopy run, we fit the pRF model and then binarized any significant voxels
($R^2 > 0.14$) by amplitude. When testing positive-pRF reliability (in dATN and DN), positive voxels
= 1; all others = 0. For negative-pRF reliability (in DN), significant negative voxels = 1. We then
computed a three-run Dice coefficient: (dice $coefficient = \frac{3|run1 \cap run2 \cap run3|}{|run1|+|run2|+|run3|}$). We compared this
value against 5000 bootstrapped Dice scores derived from the same number of voxels randomly
sampled from all voxels, both significant and non-significant, in the ROI. For each participant, this
resulted in 1 "observed" dice coefficient along with 5000 bootstrapped values representing the
distribution of dice coefficients expected by chance. The observed coefficient was z-scored
against this null distribution for each participant.

We also evaluated center position (x,y) reliability. For every significant voxel, we calculated the
Euclidean distance between its center estimates across the three run pairs (i.e. 1-2, 2-3, 1-3). As
with amplitude, we generated a null distribution by repeating this computation on 5,000 random
voxel sets (significant + non-significant). To establish significance of the true estimate, the
observed estimate was z-scored against this null distribution for each participant.

Data Analysis – Retinotopically-Grounded Resting-state Analyses

Evaluating global functional coupling between cortical networks at rest

To assess global functional coupling between the default network (DN) and the dorsal attention
network (dATN) at rest, we used a partial correlation analysis that accounted for variation
associated with other cortical networks [43] . We first averaged the time series within each DN and
dATN subnetwork prior to calculating the partial correlation between them.

Evaluating the Contributions of Voxel-Level Visual Response Valence to Cross-Network
Coupling

To test whether DN–dATN coupling is modulated by the visual responsiveness (i.e., response
valence) of DN voxels, we repeated this analysis separately using only: (i) sub-threshold/non-
retinotopic voxels, (ii) positive pRFs, or (iii) negative pRFs from the DN -- while still partialling out

the remaining networks. This allowed us to assess whether specific classes of visually responsive
voxels in the DN differentially contribute to functional coupling with the dATN.

Evaluating Voxel-Level Retinotopic Alignment in Cross-Network Coupling

To test whether functional coupling is shaped by the shared visual field preferences of DN-dATN
voxels (i.e., retinotopic alignment), we compared resting-state correlations between pRF pairs
across the DN and dATN that had matched (vs. unmatched) pRF centers.

To do this, for each pRF in the DN (positive or negative), we computed the Euclidean distance
between its receptive-field center (x, y) and those of all dATN pRFs. We focused on center
position instead of pRF size because 1) size estimates are relatively unstable compared with
center position[89], and 2) we lacked a clear prediction about how pRF size would be related
between the two networks. For each DN voxel, we identified the 10 nearest dATN pRFs based
on center position—the "matched" set—and averaged their resting-state time series. As a null
comparison, we defined a "random" set by sampling 10 dATN pRFs from the most distant third of
the match distribution (i.e., (the 1/3 furthest pRF pairs). We considered the bottom 33% because
the overwhelming majority of pRFs constituted relatively equal "good" matches. This random
sampling was repeated 1,000 times per DN voxel, generating a distribution of 1,000 random
correlation values, which we then averaged to yield a single "random" correlation for each DN
source pRF.

We calculated the correlation between each DN pRF's resting-state time series and that of its 10
best-matched dATN pRFs ("matched" correlation). We averaged across the 10 best matches to
(1) reflect the likely distributed input from multiple dATN sources and (2) improve signal-to-noise.
To isolate pRF-specific effects, we partialled out the mean time series of the complementary DN
pRF population from the signals of interest. For example, when analyzing correlations between –
DN and +dATN, we treated +DN activity as a nuisance regressor (and vice versa)[34,43]. This
provided a network-level analog to the whole-brain partial correlation described above (see
Section: Correlation among cortical networks), allowing us to isolate the unique contribution of
the pRFs of interest from overall activity in the region as well as to control for global fluctuations
that cause widespread positive correlations like motion and attentional state[34,43]. All correlation
values were Fisher-transformed, and we took the median value across voxels within each network
to yield a single value per run. This procedure was repeated for all runs and all participants.

We then statistically compared Fisher-transformed correlations for matched vs. random pRF pairs
using a linear mixed effects model, with match status (matched vs. random) as a fixed effect and
subject and run as random effects. This model accounted for both between- and within-subject
variation across session. For follow-up tests, we compared the average matched and random
values across participants using a paired t-test.

Resting-state event detection analyses

To dissociate the influence of top-down versus bottom-up drive on spontaneous interactions
between the DN and dATN, we developed an event-triggered analysis of resting-state fMRI data.
Because participants were not engaged in any task, resting-state data provide a neutral testbed

for evaluating the directionality and spatial specificity of DN–dATN interactions. Building on prior
findings that attention during rest naturally alternates between internally and externally oriented
states[23,48,49] we reasoned that transient "neural events" in these networks could reveal
spontaneous top-down and bottom-up communication.

We defined top-down events as transient high-activation periods in DN pRFs, and bottom-up
events as high-activation periods in positive-polarity dATN pRFs[90,91]. Event detection was
performed independently for each pRF. We first z-scored each pRF's resting-state time series
and identified TRs with unusually high activity in source network pRFs. Specifically, we
considered any time point with a z-value greater than 2.4 (i.e., 99.18 percentile) as a neural event.
Results were comparable with a range of thresholds (2.1 < z < 2.9).

At each detected event, we extracted the resting-state time series of the 10 most retinotopically
aligned pRFs in the target network—i.e., the 10 with the smallest Euclidean distance in receptive-
field center (x, y)—over a 13-TR peri-event window (–6 to +6 TRs). These time series were
normalized to the mean of the first four pre-event TRs to allow comparisons across events and
conditions. To evaluate the spatial specificity of these interactions, we compared responses in
the matched pRFs to those in an "anti-matched" pRFs set: the 10 most distant pRFs in the target
network in terms of visual field preference (i.e., pRF center positions). Unlike prior analyses that
used random sampling to define unmatched control pRFs, here we used a deterministic anti-
match procedure to avoid the computational burden of repeated resampling, given the large
number of events.

This procedure was repeated across all relevant source–target network pairs: top-down (DN as
source, dATN as target), bottom-up (dATN as source, DN as target), and for both positive and
negative DN pRFs. For each event type and match status, we computed the average response
in the target pRFs at time zero (event peak). These values were entered into a linear mixed effects
model with fixed effects of match status (matched vs. anti-matched) and event direction (top-down
vs. bottom-up), and with subject as a random effect. This allowed us to test whether retinotopic
alignment modulates DN-dATN interactions during spontaneous events and whether such
modulation differs for top-down vs. bottom-up events.

Statistical tests

777 Statistical analyses were implemented in MATLAB (Mathworks, Inc). Given the relatively small
778 number of participants and large number of runs per subject, we used linear mixed effects models
779 to account for both within- and between-subject variability, as described in the relevant sections
780 above. For follow-up tests, we used paired-sample t-tests and corrected for multiple comparisons
781 where appropriate. Corrected p-values are reported where appropriate.

References

1. Thomas Yeo, B.T., Krienen, F.M., Sepulcre, J., Sabuncu, M.R., Lashkari, D., Hollinshead, M., Roffman, J.L., Smoller, J.W., Zöllei, L., Polimeni, J.R., et al. (2011). The organization of the human cerebral cortex estimated by intrinsic functional connectivity. J Neurophysiol *106*, 1125–1165. https://doi.org/10.1152/JN.00338.2011.

2. Margulies, D.S., Ghosh, S.S., Goulas, A., Falkiewicz, M., Huntenburg, J.M., Langs, G., Bezgin, G., Eickhoff, S.B., Castellanos, F.X., Petrides, M., et al. (2016). Situating the default-mode network along a principal gradient of macroscale cortical organization. Proc Natl Acad Sci U S A *113*, 12574–12579. https://doi.org/10.1073/PNAS.1608282113/SUPPL_FILE/PNAS.201608282SI.PDF.

3. Braga, R.M., and Buckner, R.L. (2017). Parallel Interdigitated Distributed Networks within the Individual Estimated by Intrinsic Functional Connectivity. Neuron *95*, 457-471.e5. https://doi.org/10.1016/j.neuron.2017.06.038.

4. Gordon, E.M., Laumann, T.O., Gilmore, A.W., Newbold, D.J., Greene, D.J., Berg, J.J., Ortega, M., Hoyt-Drazen, C., Gratton, C., Sun, H., et al. (2017). Precision Functional Mapping of Individual Human Brains. Neuron *95*, 791-807.e7. https://doi.org/10.1016/J.NEURON.2017.07.011.

5. Ranganath, C., and Ritchey, M. (2012). Two cortical systems for memory-guided behaviour. Preprint at Nature Publishing Group, https://doi.org/10.1038/nrn3338 https://doi.org/10.1038/nrn3338.

6. Andrews-Hanna, J.R., Reidler, J.S., Sepulcre, J., Poulin, R., and Buckner, R.L. (2010). Functional-Anatomic Fractionation of the Brain's Default Network. Neuron *65*, 550–562. https://doi.org/10.1016/j.neuron.2010.02.005.

7. Barnett, A.J., Reilly, W., Dimsdale-Zucker, H.R., Mizrak, E., Reagh, Z., and Ranganath, C. (2021). Intrinsic connectivity reveals functionally distinct cortico-hippocampal networks in the human brain. PLoS Biol *19*, e3001275. https://doi.org/10.1371/JOURNAL.PBIO.3001275.

8. Du, J., DiNicola, L.M., Angeli, P.A., Saadon-Grosman, N., Sun, W., Kaiser, S., Ladopoulou, J., Xue, A., Yeo, B.T.T., Eldaief, M.C., et al. (2024). Organization of the human cerebral cortex estimated within individuals: networks, global topography, and function. J Neurophysiol *131*, 1014–1082. https://doi.org/10.1152/jn.00308.2023.

9. Laumann, T.O., Gordon, E.M., Adeyemo, B., Snyder, A.Z., Joo, S.J., Chen, M.Y., Gilmore, A.W., McDermott, K.B., Nelson, S.M., Dosenbach, N.U.F., et al. (2015). Functional System and Areal Organization of a Highly Sampled Individual Human Brain. Neuron *87*, 657–670. https://doi.org/10.1016/J.NEURON.2015.06.037.

10.   Chun, M.M., Golomb, J.D., and Turk-Browne, N.B. (2011). A Taxonomy of External and
Internal Attention. Annu Rev Psychol *62*, 73–101.
https://doi.org/https://doi.org/10.1146/annurev.psych.093008.100427.

11.   Dixon, M.L., Andrews-Hanna, J.R., Spreng, R.N., Irving, Z.C., Mills, C., Girn, M., and
Christoff, K. (2017). Interactions between the default network and dorsal attention network
vary across default subsystems, time, and cognitive states. Neuroimage *147*, 632–649.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2016.12.073.

12.   Fox, M.D., Snyder, A.Z., Vincent, J.L., Corbetta, M., Van Essen, D.C., and Raichle, M.E.
(2005). The human brain is intrinsically organized into dynamic, anticorrelated functional
networks. Proc Natl Acad Sci U S A *102*, 9673–9678.
https://doi.org/10.1073/PNAS.0504136102.

13.   Raichle, M.E. (2015). The Brain's Default Mode Network. Annu Rev Neurosci *38*, 433–447.
https://doi.org/10.1146/annurev-neuro-071013-014030.

14.   Fox, M.D., Corbetta, M., Snyder, A.Z., Vincent, J.L., and Raichle, M.E. (2006).
Spontaneous neuronal activity distinguishes human dorsal and ventral attention systems.
Proceedings of the National Academy of Sciences *103*, 10046–10051.
https://doi.org/10.1073/pnas.0604187103.

15.   Raichle, M.E., MacLeod, A.M., Snyder, A.Z., Powers, W.J., Gusnard, D.A., and Shulman,
G.L. (2001). A default mode of brain function. Proceedings of the National Academy of
Sciences *98*, 676–682. https://doi.org/10.1073/pnas.98.2.676.

16.   Fedorenko, E., Duncan, J., and Kanwisher, N. (2013). Broad domain generality in focal
regions of frontal and parietal cortex. Proceedings of the National Academy of Sciences
110, 16616–16621. https://doi.org/10.1073/pnas.1315235110.

17.   Vossel, S., Geng, J.J., and Fink, G.R. (2013). Dorsal and Ventral Attention Systems:
Distinct Neural Circuits but Collaborative Roles. The Neuroscientist *20*, 150–159.
https://doi.org/10.1177/1073858413494269.

18.   Shulman, G.L., Fiez, J.A., Corbetta, M., Buckner, R.L., Miezin, F.M., Raichle, M.E., and
Petersen, S.E. (1997). Common Blood Flow Changes across Visual Tasks: II. Decreases
in Cerebral Cortex. J Cogn Neurosci *9*, 648–663.
https://doi.org/10.1162/JOCN.1997.9.5.648.

19.   Silson, E.H., Steel, A., Kidder, A., Gilmore, A.W., and Baker, C.I. (2019). Distinct
subdivisions of human medial parietal cortex support recollection of people and places.
Elife *8*. https://doi.org/10.7554/eLife.47391.

20.   DiNicola, L.M., Braga, R.M., and Buckner, R.L. (2020). Parallel distributed networks
dissociate episodic and social functions within the individual. J Neurophysiol *123*, 1144–
1179. https://doi.org/10.1152/jn.00529.2019.

21.   Thakral, P.P., Madore, K.P., and Schacter, D.L. (2017). A Role for the Left Angular Gyrus
854   in Episodic Simulation and Memory. J Neurosci *37*, 8142–8149.
855   https://doi.org/10.1523/JNEUROSCI.1319-17.2017.

856   22.   Gilmore, A.W., Quach, A., Kalinowski, S.E., Gotts, S.J., Schacter, D.L., and Martin, A.
857   (2021). Dynamic Content Reactivation Supports Naturalistic Autobiographical Recall in
858   Humans. Journal of Neuroscience *41*, 153–166.
859   https://doi.org/10.1523/JNEUROSCI.1490-20.2020.

860   23.   Christoff, K., Gordon, A.M., Smallwood, J., Smith, R., and Schooler, J.W. (2009).
861   Experience sampling during fMRI reveals default network and executive system
862   contributions to mind wandering. Proc Natl Acad Sci U S A *106*, 8719–8724.
863   https://doi.org/10.1073/PNAS.0900234106/SUPPL_FILE/0900234106SI.PDF.

864   24.   Greicius, M.D., Krasnow, B., Reiss, A.L., and Menon, V. (2003). Functional connectivity in
865   the resting brain: A network analysis of the default mode hypothesis. Proceedings of the
866   National Academy of Sciences *100*, 253–258. https://doi.org/10.1073/pnas.0135058100.

867   25.   Menon, V. (2023). 20 years of the default mode network: A review and synthesis. Neuron
868   *111*, 2469–2487. https://doi.org/10.1016/j.neuron.2023.04.023.

869   26.   Saad, Z.S., Gotts, S.J., Murphy, K., Chen, G., Jo, H.J., Martin, A., and Cox, R.W. (2012).
870   Trouble at Rest: How Correlation Patterns and Group Differences Become Distorted After
871   Global Signal Regression. Brain Connect *2*, 25–32.
872   https://doi.org/10.1089/brain.2012.0080.

873   27.   Murphy, C., Wang, H.-T., Konu, D., Lowndes, R., Margulies, D.S., Jefferies, E., and
874   Smallwood, J. (2019). Modes of operation: A topographic neural gradient supporting
875   stimulus dependent and independent cognition. Neuroimage *186*, 487–496.
876   https://doi.org/10.1016/j.neuroimage.2018.11.009.

877   28.   Murphy, C., Jefferies, E., Rueschemeyer, S.A., Sormaz, M., Wang, H. ting, Margulies, D.S.,
878   and Smallwood, J. (2018). Distant from input: Evidence of regions within the default mode
879   network supporting perceptually-decoupled and conceptually-guided cognition.
880   Neuroimage *171*, 393–401. https://doi.org/10.1016/J.NEUROIMAGE.2018.01.017.

881   29.   Bellmund, J.L.S., Gärdenfors, P., Moser, E.I., and Doeller, C.F. (2018). Navigating
882   cognition: Spatial codes for human thinking. Science (1979) *362*, eaat6766.
883   https://doi.org/10.1126/SCIENCE.AAT6766.

884   30.   Popham, S.F., Huth, A.G., Bilenko, N.Y., Deniz, F., Gao, J.S., Nunez-Elizalde, A.O., and
885   Gallant, J.L. (2021). Visual and linguistic semantic representations are aligned at the border
886   of human visual cortex. Nature Neuroscience 2021 24:11 *24*, 1628–1636.
887   https://doi.org/10.1038/s41593-021-00921-6.

888   31.   Szinte, M., and Knapen, T. (2020). Visual Organization of the Default Network. Cerebral
889   Cortex *30*, 3518–3527. https://doi.org/10.1093/CERCOR/BHZ323.

890   32.   Knapen, T. (2021). Topographic connectivity reveals task-dependent retinotopic
891   processing throughout the human brain. Proc Natl Acad Sci U S A *118*.
892   https://doi.org/10.1073/PNAS.2017032118.

893   33.   Christiaan Klink, P., Chen, X., Vanduffel, W., and Roelfsema, P.R. (2021). Population
894   receptive fields in non-human primates from whole-brain fmri and large-scale
895   neurophysiology in visual cortex. Elife *10*. https://doi.org/10.7554/ELIFE.67304.

896   34.   Steel, A., Silson, E.H., Garcia, B.D., and Robertson, C.E. (2024). A retinotopic code
897   structures the interaction between perception and memory systems. Nat Neurosci *27*, 339–
898   347. https://doi.org/10.1038/s41593-023-01512-3.

899   35.   Groen, I.I.A., Dekker, T.M., Knapen, T., and Silson, E.H. (2022). Visuospatial coding as
900   ubiquitous scaffolding for human cognition. Trends Cogn Sci *26*, 81–96.
901   https://doi.org/10.1016/J.TICS.2021.10.011.

902   36.   Allen, E.J., St-Yves, G., Wu, Y., Breedlove, J.L., Prince, J.S., Dowdle, L.T., Nau, M., Caron,
903   B., Pestilli, F., Charest, I., et al. (2021). A massive 7T fMRI dataset to bridge cognitive
904   neuroscience and artificial intelligence. Nature Neuroscience 2021 25:1 *25*, 116–126.
905   https://doi.org/10.1038/s41593-021-00962-x.

906   37.   Dumoulin, S.O., and Wandell, B.A. (2008). Population receptive field estimates in human
907   visual cortex. Neuroimage *39*, 647. https://doi.org/10.1016/J.NEUROIMAGE.2007.09.034.

908   38.   Kong, R., Yang, Q., Gordon, E., Xue, A., Yan, X., Orban, C., Zuo, X.-N., Spreng, N., Ge,
909   T., Holmes, A., et al. (2021). Individual-Specific Areal-Level Parcellations Improve
910   Functional Connectivity Prediction of Behavior. Cerebral Cortex *31*, 4477–4500.
911   https://doi.org/10.1093/cercor/bhab101.

912   39.   Griffanti, L., Salimi-Khorshidi, G., Beckmann, C.F., Auerbach, E.J., Douaud, G., Sexton,
913   C.E., Zsoldos, E., Ebmeier, K.P., Filippini, N., Mackay, C.E., et al. (2014). ICA-based
914   artefact removal and accelerated fMRI acquisition for improved resting state network
915   imaging. Neuroimage *95*, 232–247. https://doi.org/10.1016/j.neuroimage.2014.03.034.

916   40.   Griffanti, L., Douaud, G., Bijsterbosch, J., Evangelisti, S., Alfaro-Almagro, F., Glasser, M.F.,
917   Duff, E.P., Fitzgibbon, S., Westphal, R., Carone, D., et al. (2017). Hand classification of
918   fMRI ICA noise components. Neuroimage *154*, 188–205.
919   https://doi.org/10.1016/J.NEUROIMAGE.2016.12.036.

920   41.   Kong, R., Li, J., Orban, C., Sabuncu, M.R., Liu, H., Schaefer, A., Sun, N., Zuo, X.-N.,
921   Holmes, A.J., Eickhoff, S.B., et al. (2019). Spatial Topography of Individual-Specific
922   Cortical Networks Predicts Human Cognition, Personality, and Emotion. Cerebral Cortex
923   *29*, 2533–2551. https://doi.org/10.1093/cercor/bhy123.

924   42.   Silson, E.H., Chan, A.W.Y., Reynolds, R.C., Kravitz, D.J., and Baker, C.I. (2015). A
925   retinotopic basis for the division of high-level scene processing between lateral and ventral

human occipitotemporal cortex. Journal of Neuroscience *35*, 11921–11935.
https://doi.org/10.1523/JNEUROSCI.0137-15.2015.

43. Smith, S.M., Vidaurre, D., Beckmann, C.F., Glasser, M.F., Jenkinson, M., Miller, K.L.,
Nichols, T.E., Robinson, E.C., Salimi-Khorshidi, G., Woolrich, M.W., et al. (2013).
Functional connectomics from resting-state fMRI. Trends Cogn Sci *17*, 666–682.
https://doi.org/10.1016/j.tics.2013.09.016.

44. DiNicola, L.M., and Buckner, R.L. (2021). Precision estimates of parallel distributed
association networks: evidence for domain specialization and implications for evolution and
development.   Curr   Opin   Behav   Sci   *40*,   120–129.
https://doi.org/10.1016/j.cobeha.2021.03.029.

45. DiNicola, L.M., Braga, R.M., and Buckner, R.L. (2019). Parallel Distributed Networks
Dissociate Episodic and Social Functions Within the Individual. bioRxiv, 733048.
https://doi.org/10.1101/733048.

46. DiNicola, L.M., Ariyo, O.I., and Buckner, R.L. (2023). Functional specialization of parallel
distributed networks revealed by analysis of trial-to-trial variation in processing demands.
J Neurophysiol *129*, 17–40. https://doi.org/10.1152/jn.00211.2022.

47. Scrivener, C.L., and Silson, E.H. (2025). Opponent visuospatial coding structures
responses during memory recall and visual perception in medial parietal cortex. Imaging
Neuroscience *3*. https://doi.org/10.1162/imag_a_00507.

48. Gonzalez-Castillo, J., Kam, J.W.Y., Hoy, C.W., and Bandettini, P.A. (2021). How to
Interpret Resting-State fMRI: Ask Your Participants. The Journal of Neuroscience *41*,
1130–1141. https://doi.org/10.1523/JNEUROSCI.1786-20.2020.

49. Van Calster, L., D'Argembeau, A., Salmon, E., Peters, F., and Majerus, S. (2017).
Fluctuations of Attentional Networks and Default Mode Network during the Resting State
Reflect Variations in Cognitive States: Evidence from a Novel Resting-state Experience
Sampling Method. J Cogn Neurosci *29*, 95–113. https://doi.org/10.1162/jocn_a_01025.

50. Favila, S.E., Kuhl, B.A., and Winawer, J. (2022). Perception and memory have distinct
spatial tuning properties in human visual cortex. Nature Communications 2022 13:1 *13*, 1–
21. https://doi.org/10.1038/s41467-022-33161-8.

51. Breedlove, J.L., St-Yves, G., Olman, C.A., and Naselaris, T. (2020). Generative Feedback
Explains Distinct Brain Activity Codes for Seen and Mental Images. Current Biology, 1–14.
https://doi.org/10.1016/j.cub.2020.04.014.

52. Buschman, T.J., Siegel, M., Roy, J.E., and Miller, E.K. (2011). Neural substrates of
cognitive capacity limitations. Proc Natl Acad Sci U S A *108*, 11252–11255.
https://doi.org/10.1073/PNAS.1104666108/-
/DCSUPPLEMENTAL/PNAS.201104666SI.PDF.

53.   Libby, A., and Buschman, T.J. (2021). Rotational dynamics reduce interference between
sensory and memory representations. Nature Neuroscience 2021 24:5 *24*, 715–726.
https://doi.org/10.1038/s41593-021-00821-9.

54.   Semedo, J.D., Zandvakili, A., Machens, C.K., Yu, B.M., and Kohn, A. (2019). Cortical areas
interact through a communication subspace. Neuron *102*, 249.
https://doi.org/10.1016/J.NEURON.2019.01.026.

55.   Gregoriou, G.G., Gotts, S.J., Zhou, H., and Desimone, R. (2009). High-frequency, long-
range coupling between prefrontal and visual cortex during attention. Science *324*, 1207–
1210. https://doi.org/10.1126/SCIENCE.1171402.

56.   Bosman, C.A., Schoffelen, J.M., Brunet, N., Oostenveld, R., Bastos, A.M., Womelsdorf, T.,
Rubehn, B., Stieglitz, T., De Weerd, P., and Fries, P. (2012). Attentional stimulus selection
through selective synchronization between monkey visual areas. Neuron *75*, 875–888.
https://doi.org/10.1016/J.NEURON.2012.06.037.

57.   Margulies, D.S., Ghosh, S.S., Goulas, A., Falkiewicz, M., Huntenburg, J.M., Langs, G.,
Bezgin, G., Eickhoff, S.B., Castellanos, F.X., Petrides, M., et al. (2016). Situating the
default-mode network along a principal gradient of macroscale cortical organization. Proc
Natl Acad Sci U S A *113*, 12574–12579. https://doi.org/10.1073/pnas.1608282113.

58.   Buckner, R.L., and DiNicola, L.M. (2019). The brain's default network: updated anatomy,
physiology and evolving insights. Nat Rev Neurosci. https://doi.org/10.1038/s41583-019-
0212-7.

59.   Yeshurun, Y., Nguyen, M., and Hasson, U. (2021). The default mode network: where the
idiosyncratic self meets the shared social world. Nature Reviews Neuroscience 2021 22:3
22, 181–192. https://doi.org/10.1038/s41583-020-00420-w.

60.   Spreng, R.N., Stevens, W.D., Chamberlain, J.P., Gilmore, A.W., and Schacter, D.L. (2010).
Default network activity, coupled with the frontoparietal control network, supports goal-
directed cognition. Neuroimage *53*, 303–317.
https://doi.org/10.1016/j.neuroimage.2010.06.016.

61.   Spreng, R.N., Mar, R.A., and Kim, A.S.N. (2009). The common neural basis of
autobiographical memory, prospection, navigation, theory of mind, and the default mode:
A quantitative meta-analysis. J Cogn Neurosci *21*, 489–510.
https://doi.org/10.1162/jocn.2008.21029.

62.   Foster, B.L., Koslov, S.R., Aponik-Gremillion, L., Monko, M.E., Hayden, B.Y., and
Heilbronner, S.R. (2023). A tripartite view of the posterior cingulate cortex. Nat Rev
Neurosci *24*, 173–189. https://doi.org/10.1038/s41583-022-00661-x.

63.   Wandell, B.A., Dumoulin, S.O., and Brewer, A.A. (2007). Visual field maps in human cortex.
Neuron *56*, 366–383. https://doi.org/10.1016/J.NEURON.2007.10.012.

64.   Taube, J.S. (2007). The Head Direction Signal: Origins and Sensory-Motor Integration.
Annu   Rev   Neurosci   *30*,   181–207.
https://doi.org/10.1146/annurev.neuro.29.051605.112854.

65.   Finkelstein, A., Derdikman, D., Rubin, A., Foerster, J.N., Las, L., and Ulanovsky, N. (2015).
Three-dimensional head-direction coding in the bat brain. Nature *517*, 159–164.
https://doi.org/10.1038/nature14031.

66.   Nau, M., Navarro Schröder, T., Frey, M., and Doeller, C.F. (2020). Behavior-dependent
directional tuning in the human visual-navigation network. Nat Commun *11*, 3247.
https://doi.org/10.1038/s41467-020-17000-2.

67.   Bastos, A.M., Usrey, W.M., Adams, R.A., Mangun, G.R., Fries, P., and Friston, K.J. (2012).
Canonical   Microcircuits   for   Predictive   Coding.   Neuron   *76*,   695–711.
https://doi.org/10.1016/J.NEURON.2012.10.038.

68.   Albright, T.D. (2012). On the perception of probable things: neural substrates of associative
memory,   imagery,   and   perception.   Neuron   *74*,   227–245.
https://doi.org/10.1016/J.NEURON.2012.04.001.

69.   Barron, H.C., Vogels, T.P., Behrens, T.E., Ramaswami, M., and by Thomas Albright, E.D.
(2017).   Inhibitory   engrams   in   perception   and   memory.   *114*,   6666–6674.
https://doi.org/10.1073/pnas.1701812114.

70.   Steel, A., Prasad, D., Garcia, B.D., and Robertson, C.E. (2025). Relating scene memory
and perception activity to functional properties, networks, and landmarks of posterior
cerebral cortex - a probabilistic atlas. The Journal of Neuroscience, e0028252025.
https://doi.org/10.1523/JNEUROSCI.0028-25.2025.

71.   Wu, Y., Podvalny, E., Levinson, M., and He, B.J. (2024). Network mechanisms of ongoing
brain activity's influence on conscious visual perception. Nat Commun *15*, 5720.
https://doi.org/10.1038/s41467-024-50102-9.

72.   Nghiem, T.-A.E., Lee, B., Chao, T.-H.H., Branigan, N.K., Mistry, P.K., Shih, Y.-Y.I., and
Menon, V. (2024). Space wandering in the rodent default mode network. Proceedings of
the National Academy of Sciences *121*. https://doi.org/10.1073/pnas.2315167121.

73.   Steel, A., Thomas, C., Trefler, A., Chen, G., and Baker, C.I. (2019). Finding the baby in the
bath water – evidence for task-specific changes in resting state functional connectivity
evoked   by   training.   Neuroimage   *188*,   524–538.
https://doi.org/10.1016/J.NEUROIMAGE.2018.12.038.

74.   Steel, A., Billings, M.M., Silson, E.H., and Robertson, C.E. (2021). A network linking scene
perception   and   spatial   memory   systems   in   posterior   cerebral   cortex.   Nature
Communications 2021 12:1 *12*, 1–13. https://doi.org/10.1038/s41467-021-22848-z.

75.   Steel, A., Garcia, B.D., Goyal, K., Mynick, A., and Robertson, C.E. (2023). Scene
Perception and Visuospatial Memory Converge at the Anterior Edge of Visually

Responsive Cortex. The Journal of Neuroscience *43*, 5723.
https://doi.org/10.1523/JNEUROSCI.2043-22.2023.

76. Çukur, T., Nishimoto, S., Huth, A.G., and Gallant, J.L. (2013). Attention during natural
vision warps semantic representation across the human brain. Nat Neurosci *16*, 763–770.
https://doi.org/10.1038/nn.3381.

77. Arcaro, M., and Livingstone, M. (2024). A Whole-Brain Topographic Ontology. Annu Rev
Neurosci *47*, 21–40. https://doi.org/https://doi.org/10.1146/annurev-neuro-082823-
073701.

78. Peer, M., Brunec, I.K., Newcombe, N.S., and Epstein, R.A. (2020). Structuring Knowledge
with Cognitive Maps and Cognitive Graphs. Trends Cogn Sci.
https://doi.org/10.1016/j.tics.2020.10.004.

79. Huth, A.G., De Heer, W.A., Griffiths, T.L., Theunissen, F.E., and Gallant, J.L. (2016).
Natural speech reveals the semantic maps that tile human cerebral cortex. Nature *532*,
453–458. https://doi.org/10.1038/NATURE17637.

80. Hedger, N., Naselaris, T., Kay, K., and Knapen, T. (2024). Vicarious Somatotopic Maps
Tile Visual Cortex. bioRxiv, 2024.10.21.619382.
https://doi.org/10.1101/2024.10.21.619382.

81. Dale, A.M., Fischl, B., and Sereno, M.I. (1999). Cortical surface-based analysis: I.
Segmentation and surface reconstruction. Neuroimage *9*, 179–194.
https://doi.org/10.1006/nimg.1998.0395.

82. Fischl, B., Salat, D.H., Busa, E., Albert, M., Dieterich, M., Haselgrove, C., Van Der Kouwe,
A., Killiany, R., Kennedy, D., Klaveness, S., et al. (2002). Whole brain segmentation:
Automated labeling of neuroanatomical structures in the human brain. Neuron *33*, 341–
355. https://doi.org/10.1016/S0896-6273(02)00569-X.

83. Saad, Z.S., and Reynolds, R.C. (2012). SUMA. Neuroimage *62*, 768–773.
https://doi.org/10.1016/J.NEUROIMAGE.2011.09.016.

84. Cox, R.W. (1996). AFNI: Software for analysis and visualization of functional magnetic
resonance neuroimages. Computers and Biomedical Research *29*, 162–173.
https://doi.org/10.1006/cbmr.1996.0014.

85. Taylor, P.A., Glen, D.R., Chen, G., Cox, R.W., Hanayik, T., Rorden, C., Nielson, D.M.,
Rajendra, J.K., and Reynolds, R.C. (2024). A Set of FMRI Quality Control Tools in AFNI:
Systematic, in-depth and interactive QC with afni_proc.py and more. bioRxiv,
2024.03.27.586976. https://doi.org/10.1101/2024.03.27.586976.

86. Beckers, A.B., Drenthen, G.S., Jansen, J.F.A., Backes, W.H., Poser, B.A., and Keszthelyi,
D. (2023). Comparing the efficacy of data-driven denoising methods for a multi-echo fMRI
acquisition at 7T. Neuroimage *280*, 120361.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2023.120361.

87.   Jenkinson, M., Beckmann, C.F., Behrens, T.E.J., Woolrich, M.W., and Smith, S.M. (2012).
1073   FSL. Neuroimage *62*, 782–790. https://doi.org/10.1016/j.neuroimage.2011.09.015.

1074   88.   Smith, S.M., Jenkinson, M., Woolrich, M.W., Beckmann, C.F., Behrens, T.E.J., Johansen-
1075   Berg, H., Bannister, P.R., De Luca, M., Drobnjak, I., Flitney, D.E., et al. (2004). Advances
1076   in functional and structural MR image analysis and implementation as FSL. In NeuroImage
1077   (Academic Press), pp. S208–S219. https://doi.org/10.1016/j.neuroimage.2004.07.051.

1078   89.   Alvarez, I., de Haas, B., Clark, C.A., Rees, G., and Samuel Schwarzkopf, D. (2015).
1079   Comparing different stimulus configurations for population receptive field mapping in
1080   human   fMRI.   Front   Hum   Neurosci   *9*,   121251.
1081   https://doi.org/10.3389/FNHUM.2015.00096/ABSTRACT.

1082   90.   Gordon, E.M., Chauvin, R.J., Van, A.N., Rajesh, A., Nielsen, A., Newbold, D.J., Lynch,
1083   C.J., Seider, N.A., Krimmel, S.R., Scheidter, K.M., et al. (2023). A somato-cognitive action
1084   network alternates with effector regions in motor cortex. Nature *617*, 351–359.
1085   https://doi.org/10.1038/s41586-023-05964-2.

1086   91.   Mitra, A., Snyder, A.Z., Blazey, T., and Raichle, M.E. (2015). Lag threads organize the
1087   brain's intrinsic activity. Proceedings of the National Academy of Sciences *112*, E2235–
1088   E2244. https://doi.org/10.1073/pnas.1503960112.

1089   92.   Silson, E.H., Groen, I.I.A., Kravitz, D.J., and Baker, C.I. (2016). Evaluating the
1090   correspondence between face-, scene-, and object-selectivity and retinotopic organization
1091   within lateral occipitotemporal cortex. J Vis *16*, 14–14. https://doi.org/10.1167/16.6.14.

1092   93.   Hutchison, R.M., Culham, J.C., Everling, S., Flanagan, J.R., and Gallivan, J.P. (2014).
1093   Distinct and distributed functional connectivity patterns across cortex reflect the domain-
1094   specific constraints of object, face, scene, body, and tool category-selective modules in the
1095   ventral   visual   pathway.   Neuroimage   *96*,   216–236.
1096   https://doi.org/https://doi.org/10.1016/j.neuroimage.2014.03.068.

1097   94.   Stevens, W.D., Tessler, M.H., Peng, C.S., and Martin, A. (2015). Functional connectivity
1098   constrains the category-related organization of human ventral occipitotemporal cortex.
1099   Hum Brain Mapp *36*, 2187–2206. https://doi.org/https://doi.org/10.1002/hbm.22764.

1100   95.   Silson, E.H., Steel, A.D., and Baker, C.I. (2016). Scene-Selectivity and Retinotopy in Medial
1101   Parietal Cortex. Front Hum Neurosci *10*, 412. https://doi.org/10.3389/fnhum.2016.00412.

1102   96.   Baldassano, C., Esteva, A., Fei-Fei, L., and Beck, D.M. (2016). Two Distinct Scene-
1103   Processing   Networks   Connecting   Vision   and   Memory.   eNeuro   *3*.
1104   https://doi.org/10.1523/ENEURO.0178-16.2016.

1105   97.   Dilks, D.D., Julian, J.B., Paunov, A.M., and Kanwisher, N. (2013). The occipital place area
1106   is causally and selectively involved in scene perception. Journal of Neuroscience *33*, 1331–
1107   1336. https://doi.org/10.1523/JNEUROSCI.4081-12.2013.

1108   98.   Hasson, U., Harel, M., Levy, I., and Malach, R. (2003). Large-scale mirror-symmetry
1109   organization of human occipito-temporal object areas. Neuron *37*, 1027–1041.
1110   https://doi.org/10.1016/S0896-6273(03)00144-2.

1111   99.   Kanwisher, N., McDermott, J., and Chun, M.M. (1997). The fusiform face area: A module
1112   in human extrastriate cortex specialized for face perception. Journal of Neuroscience *17*,
1113   4302–4311. https://doi.org/10.1523/jneurosci.17-11-04302.1997.

1114   100.   Halgren, E., Dale, A.M., Sereno, M.I., Tootell, R.B.H., Marinkovic, K., and Rosen, B.R.
1115   (1999). Location of human face-selective cortex with respect to retinotopic areas. Hum
1116   Brain   Mapp   *7*,   29.   https://doi.org/10.1002/(sici)1097-0193(1999)7:1<29::aid-
1117   hbm3>3.0.co;2-r.

1118   101.   Rosenke, M., van Hoof, R., van den Hurk, J., Grill-Spector, K., and Goebel, R. (2021). A
1119   Probabilistic Functional Atlas of Human Occipito-Temporal Visual Cortex. Cerebral Cortex
1120   *31*, 603–619. https://doi.org/10.1093/cercor/bhaa246.

1121

1122

1123

Supplemental material

1124

1125

1126

1127

1128 Fig S1. Cortical network parcellations for individual participants. Networks were parcellated based
1129 on a 15-network group prior[1,8] using the multi-session hierarchical Bayesian model (MS-HBM)
1130 method[41].

1131

1132

1133

1134 Fig S2. PRF amplitude maps from all participants. Only voxels with greater than 8% variance
1135 explained by the pRF model are shown for visualization only.

1136

1137

Fig. *S3.* Negative pRFs are clustered in DN-A and DN-B. Brain shows the consensus signed pRF amplitude map, which is the sum of the signed pRF amplitude across participants. Consensus was calculated by binarizing each vertex based on the sign of the visual response: participants with a positive response at a vertex were assigned a +1, participants with a negative response at a vertex were assigned a -1, and participants that did not respond (i.e., had variance explained below our 0.14 threshold) were assigned a 0. We then summed these maps across participants. Vertices with positive values were positive in the majority of participants, vertices with negative values were negative in the majority of participants, and vertices with 0 value showed no consensus. Outlines show DN-A (purple), DN-B (pink), dATN A (light green), and dATN-B (dark green).

1151

Fig. S4. Eccentricity and pRF size differs between DN and dATNs. A. Both positive and negative
DN pRFs tend to be more eccentric than dATN pRFs (positive dATN v negative DN pRFs:
t(6)=2.27, p=0.06; positive dATN v positive DN pRFs: t(6)=3.04, p=0.023; negative DN v positive
DN pRFs: t(6)=0.41, p=0.69). B. Both positive and negative DN pRFs tend to be smaller than
dATN pRFs (positive dATN v negative DN pRFs: t(6)=2.36, p=0.056; positive dATN v positive DN
pRFs: t(6)=2.46, p=0.049; negative DN v positive DN pRFs: t(6)=0.16, p=0.87) (Fig. S4A).

Importantly, these results are averaged across the whole network. Results may differ when
individual regions of each network are considered.

*=p<0.05, +=p<0.1, n.s. = non-significant

1161

1162

dATN-A   DN-A
dATN-B   DN-B

<7   Number of matched pRFs   >70

Vertices containing at least 7 matched pRFs
across participants

1163

Fig. S5. Spatial distribution of positive dATN pRFs matched with negative DN pRFs in cortex
across all participants. Vertices are colored based on number of matched pRFs. Only vertices
with greater than 7 matched pRFs (i.e., at least one for each subject) are shown. Group prior
maps[1,8] dATN A-B and DN A-B are shown for reference. Note that pRFs were matched in
individualized dATN of each participant and are not expected to correspond precisely with the
group network maps.

1170

1171

Fig. S6. A. Time series show the peri-event cross-covariance of matched and *anti-match*ed dATN pRFs averaged across all participants for events detected in negative DN pRFs (N=78,978 events). B. Time series shows the peri-event cross-covariance in negative DN pRFs during events detected in dATN pRFs (N=541,546). C. Bars show the average cross-covariance at event time of the target areas' matched and *anti-match*ed pRFs for each participant. Although this difference did not reach significance (F(1,24)=3.94, p=0.058), the results qualitatively support our conclusion – that matched pRFs in the target region have a stronger interaction with the source pRFs. D, E. Evidence for retinotopically-specific excitation of ongoing activity during events top-down events detected in positive DN pRFs (D) and bottom-up events detected in dATN pRFs (E). D. Grand average cross-covariance for matched and *anti-match*ed dATN pRFs during events detected in positive pRFs for all participants. E. Grand average cross-covariance for matched and anitmatched positive DN pRFs during events detected in dATN pRFs. I. For positive DN pRFs paired with dATN pRFs, target area shows retinotopically-specific positive covariance for both top-down and bottom-up events. Bars show the average activation at event time of the target areas' matched and *anti-match*ed pRFs for each participant. We observed a strong influence of match status on covariance (F(1,25)=25.324, p<0.001; t(6)=7.73, p<0.001). Similar to our findings when examining activation at event time, bottom-up events had a greater influence from retinotopic coding compared with top-down events, evidenced by a greater difference between matched versus *anti-match*ed pRF covariation at event time (F(1,24)=6.22, p=0.02, t(6)=3.99, p=0.007). For time series plots, solid bars along the x-axis indicate periods with a significant difference between matched and *anti-match*ed pRF activity within the target area.

1193

1194

Fig S7. Events are widely distributed in time and across voxels. A,C,E. Number of events per time point combined for top down and bottom up events for dATN, positive DN, and negative DN pRFs. Bars indicate the number of voxel events detected at a given time point within a resting-state run, aggregated across runs. Events were sparsely distributed: most time points contained no events (Proportion = 0.66, bar not shown), with the number of events decreasing approximately exponentially. This is further evidence for a wide temporal distribution of events. B,D,F. Proportion of voxels with events in each run for dATN, positive DN, and negative DN pRFs. No voxel had more than 4 events per run. Data are combined between top down and bottom-up events.

1203

Supplemental results

Our results establish that retinotopic coding structures spontaneous interactions between internally- and externally-oriented neural systems in the absence of task demands. However, high-level cortical areas generally associate into networks based on their functional domain. For example, within the visual system, brain areas with differing retinotopic preferences (e.g., the scene-selective areas on the lateral and ventral surfaces of the brain) [42,92] nevertheless form functional networks based on their apparent preference for specific visual categories (e.g., faces, objects, or scenes)[93,94]. This raises a question: do retinotopic and domain-specific organizational principles interact to facilitate or constrain information flow across internally- and externally-oriented networks? Addressing this question would shed light on mechanisms that enable the brain to integrate information while maintaining functional specialization.

To address this question, we focused on the functional interplay between a set of areas in posterior cerebral cortex that are established models for mnemonic and visual processing in the domains of scene and face perception. Specifically, we considered the mnemonic lateral place memory area (LPMA[74,75]), an area on the brain's lateral surface that is implicated in processing mnemonic information relevant to visual scenes at the border between DN-A and the dATNs (Fig 2A). We examined OPA and LPMA because these regions are maximally spatially dissociable [70,74,75] and can be localized independently using resting-state data[95,96]. We examined how LPMA activation co-fluctuates with the adjacent, scene-perception area "occipital place area" on the brain's lateral surface (OPA[97,98]) compared to two face-perception regions on the lateral and ventral surfaces, the occipital and fusiform face areas (OFA and FFA [99,100]). At a group level, these perceptual regions are situated within the dATNs and are at the same level of the visual hierarchy (Fig. S8A), but they are differentially associated with the domains of scene (OPA) and face (OFA, FFA) processing, making them ideal model systems to examine the impact of domain-specificity and retinotopic coding in organizing neural activity.

We first defined the mnemonic area LPMA in the NSD participants. To do this, we contrasted functional connectivity between the anterior and posterior halves of the parahippocampal place area using each participant's resting state data[95,96] (Fig. S8B), which revealed a cluster in lateral parietal cortex with a similar topographic profile as LPMA based on a group analysis from our prior work [74] (Fig.S8C). Replicating our previous findings[34], this connectivity-defined LPMA had a higher concentration of robust negative pRFs compared to OPA ($t(7)=5.26$, $p=0.002$) (Fig. S8D) and exhibited a similar lower visual field bias as OPA (OPA: 8/8 $t(7)=3.13$, $p=0.016$; LPMA: 7/8 participants, $t(7)=2.11$, $p=0.07$; OPA v LPMA: $t(7)=0.441$, $p=0.67$) (Fig. S8E).

We considered whether the retinotopic opponent dynamic we have previously shown in the domain of scenes (i.e., between -LPMA and +OPA pRFs) during perceptual and mnemonic tasks[34] was also present at rest (Fig. S8F). As we observed for the overall negative DN and positive dATN pRFs, we found that -LPMA and +OPA pRFs are interlocked in a retinotopically-grounded opponent interaction. We used the same matching and randomization procedure as we used for the DN.

Remarkably, we found that LPMA and OPA were interlocked in a retinotopically-grounded
opponent interaction (Fig. S8G). Resting-state activity of -LPMA and +OPA pRFs was reliably
negatively correlated after accounting for variance associated with +LPMA pRFs, and, critically,
this negative correlation was stronger for matched compared with randomly matched pRFs
(t(6)=3.012, p=0.024). We next tested whether this opponent dynamic was modified by functional
domain (i.e., the scene memory area LPMA paired with the face perception areas FFA and OFA),
and we observed no significant difference between the distribution of correlation values for
matched and randomly-matched pRFs between -LPMA and OFA (t(6)=0.59, p=0.57) and -LPMA
and FFA (t(6)=2.01, p=0.09). However, when we compared the difference of matched and
randomly-matched pRFs across domains, we found no significant interaction
(F(1,19)=0.99,p=0.33).

One possibility is that the quality of the retinotopic matching between pRFs in different areas might
contribute to the within versus across domain distinction in retinotopic coding. We checked
whether there was a difference in the match quality between the top 10 best matched pRFs
between connectivity-defined LPMA and OPA compared with the face perception areas FFA and
OFA. For this analysis, we computed the euclidean distance between all pRFs centers between
regions, and we took the median of the best pRF center matches. For example, if a participant
had 162 negative pRFs LPMA and 90 pRFs in OPA, we found the top 10 best matched OPA pRFs
for each LPMA pRF, and then took the median distance of these 1620 matches. This gave us the
most representative distance for matched pRFs for each participant.

Overall, we found that the quality of pRF matching was better for within domain (LPMA to OPA)
compared with across domains (LPMA to OFA and FFA) (Negative pRFs: t(6)=5.86, p=0.001;
positive pRFs: t(6)=6.79, p<0.001). This suggests that the quality of the matches does depend on
the stimulus domain. This fits with the notion that visual response properties are inherited by
upstream areas, and that these response properties depend in part on the nature of the stimuli
within a domain.

These results suggest that retinotopic coding structures the interaction between brain areas if
they share a functional domain, but more studies are needed to confirm whether this is specific
to within-domain matching.

1272

Fig. S8. Retinotopic coding structures the spontaneous interaction between functionally-coupled mnemonic and perceptual areas during resting-state fMRI. A. Isolating functionally coupled internally- and externally-oriented brain areas within the DNs and dATNs. We identified brain areas that were specialized in two domains: scenes and faces processing. Specifically, we focused on the lateral place memory area (LPMA; from [74]), white), a memory area in the domain of scene perception at the posterior edge of the DN-A (purple; from [8]). We examined LPMA's relationship to three different of category-selective visual areas in the dATN (green; from [8]), 1) the occipital place area (OPA; from [74]), an area within the domain of scene perception, along with 2) the occipital face area (OFA) and 3) the fusiform face area (FFA), two areas involved in the domain of face perception (white; from [101]). B-C. We localized LPMA in all participants by contrasting the correlation in resting-state activity between anterior and posterior parahippocampal place area (PPA) (B). This yielded a region in lateral occipital-parietal cortex that overlapped with the LPMA defined in an independent group of participants (C). D-E. Consistent with prior work, the connectivity-defined LPMA had greater concentration of negative pRFs compared to OPA (D), and exhibited a lower visual field bias to OPA (E), consistent with an opponent interaction between these areas during perception. F. We assessed the influence of retinotopic coding on the interaction between negative pRFs in mnemonic and positive pRFs in perceptual areas using the same pRF matching and correlation procedure described above. We compared pRFs within functional domain (scene memory x perception – LPMA to OPA) as well as across domains (scene memory x face perception – LPMA to the occipital face area (OFA) and fusiform face area (FFA)). G. We found that LPMA and OPA were interlocked in a retinotopically-grounded opponent interaction. Resting-state activity of -LPMA and +OPA pRFs was reliably negatively correlated after accounting for variance associated with +LPMA pRFs, and, critically, this negative correlation was stronger for matched compared with randomly

matched pRFs (t(6)=3.012, p=0.024). We next tested whether this opponent dynamic was
modified by functional domain (i.e., the scene memory area LPMA paired with the face perception
areas FFA and OFA), and we observed no significant difference between the distribution of
correlation values for matched and randomly-matched pRFs between -LPMA and OFA (t(6)=0.59,
p=0.57) and -LPMA and FFA (t(6)=2.01, p=0.09). However, when we compared the difference of
matched and randomly-matched pRFs across domains, we found no significant interaction
(F(1,19)=0.99,p=0.33).

1304 Methods for defining these regions of interest are below:

Defining functional regions of interest (PPA, OPA, OFA, FFA)

We used the volumetric functional regions of interest provided with the NSD at 1.8mm resolution.
Specifically, we used the parahippocampal place area (PPA), occipital place area (OPA), iog-
faces (referred to here as occipital face area (OFA)), and pfus-faces (fusiform face area, FFA1)
regions of interest. In brief, these regions were defined in the NSD using within-subject data
collected from 6 runs of a multi-category visual localizer paradigm [36].

Defining functional region LPMA

Because the NSD did not include mnemonic localizers [74], we used the resting-state data to define
the lateral place memory area (LPMA). Briefly, the LPMA is a region anterior to OPA and near
caudal inferior parietal lobule[95,96] that selectively responds during recall of personally familiar
places compared to other stimulus types. We have previous shown that OPA and LPMA are
functionally-linked and work jointly to process knowledge of visuospatial context out of view during
scene perception.

Prior work has suggested that a mnemonic area linked to scenes on the lateral surface can be
localized by comparing resting-state co-fluctuations of anterior versus posterior PPA (aPPA and
pPPA, respectively)[19,95,96], and we adopted that approach here. We preprocessed the resting-
state fixation fMRI data, runs 1 and 14 from NSD sessions 22 and 23, in all participants (prior to
data exclusion) and extracted the average time series of aPPA, pPPA, aFFA, and pFFA. We used
these time series as regressors in a general linear model, and we compared the beta-values from
the aPPA and pPPA. We considered any voxels with a t-statistic > 5 within posterior parietal-
occipital cortex on the lateral surface as an LPMA ROI (Individual ROIs can be found in
Supplemental Fig.4). Across subjects, there was considerable overlap between this connectivity-
defined area and a group-level LPMA defined based on our prior work (Fig. 2).

1328