Novel AI-powered computational method using tensor decomposition for identification of common optimal bin sizes when integrating multiple Hi-C datasets

Y-H Taguchi[1*] and Turki Turki[2]

[1*]Department of Physics, Chuo University, 1-13-27 Kasuga, Bunkyo-ku, Tokyo, 112-8551, Japan.
[2]Department of Computer Science, King Abdulaziz University, Jeddah, 21589, Saudi Arabia.

*Corresponding author(s). E-mail(s): tag@granular.com;
Contributing authors: tturki@kau.edu.sa;

Abstract

Identifying the optimal bin sizes (or resolutions) for the integration of multiple Hi-C datasets is a challenge due to the fact that bin sizes must be common over multiple datasets. By contrast, the dependence of quality upon bin sizes can vary from dataset to dataset. Moreover, common structures should not be sought in bin sizes smaller than the optimal bin sizes, below which common structure cannot be the primary structure any more even after increasing the number of mapped short reads per bin. In this case, there are no common structures at finer resolutions, suggesting that individual Hi-C datasets may have to be analyzed separately in the bin sizes smaller than the optimal one. Thus, quality assessments of individual datasets have a limited ability to determine the best bin size for all datasets. In this study, we propose a novel application of tensor decomposition (TD) based unsupervised feature extraction (FE) to choose the optimal bin sizes for the integration of multiple Hi-C datasets. TD-based unsupervised FE exhibit phase transition-like phenomena through which the smallest possible bin size (or the highest resolution) can be automatically estimated empirically, without the need to manually set a threshold value for the integration of multiple Hi-C datasets, retrieved from GEO with GEO ID, GSE260760 and GSE255264. To our knowledge, ours is the first one that can optimize bin sizes over multiple Hi-C profiles without any tunable parameters.

Keywords: Hi-C, genome, AI, tensor decomposition, feature extraction, advances in unsupervised learning

1 Introduction

The use of optimal bin sizes for Hi-C datasets is critical due to the significant effects that bin sizes can have on outcomes. Bin sizes that are too large (i.e., low resolution) might lead us to overlook biologically important factors that can be seen only at finer resolutions. On the other hand, excessively small bin sizes (i.e., high resolution) might result in a different problem; if short reads that are not large enough are mapped to the individual bins because of an increase in the number of bins, a small number of short reads mapped to a bin causes fluctuations that might prevent us from observing the biologically important structure. Thus, there is a trade-off between resolution and fluctuation. When suppressing sufficiently small fluctuations, it is difficult to achieve a sufficiently high resolution to capture biologically important fine structures. This highlights the need to estimate just how small bin sizes can be without inducing excessively large fluctuations.

Determining the optimal bin size in Hi-C data analysis is crucial, as it directly influences the resolution and quality of detected chromatin interactions. Recent advancements have introduced methods to enhance bin size selection, thereby improving data interpretation. One notable approach is deDoc [1], introduced by Li et al. in 2018. This method selects the bin size at which the structural entropy of the Hi-C matrix reaches a stable minimum, aiming to decode topologically associating domains (TADs) even with ultra-low resolution data. Another significant contribution is QuASAR (Quality Assessment of Spatial Arrangement Reproducibility) [2], developed by Sauria and Taylor. QuASAR assesses the quality of Hi-C data by comparing replicate scores to determine the maximum usable resolution, ensuring that the chosen bin size reflects reproducible spatial arrangements. Additionally, HiCPlus [3], developed by Zhang et al. in 2018, employs deep convolutional neural networks to enhance Hi-C data resolution. Remarkably, it can impute high-resolution Hi-C matrices using only a fraction (1/16) of the original sequencing reads, effectively allowing for smaller bin sizes without compromising data quality. These methodologies represent significant strides in optimizing bin size selection for Hi-C data, facilitating more accurate and efficient analysis of chromatin architecture.

The difficulty in estimating optimal bin sizes increases when integrating multiple Hi-C datasets since an optimal bin size needs to be found for all datasets, in addition to the need to identify an optimal bin size for the individual Hi-C datasets. In reality, it is difficult to know whether the strategy by which we can determine the smallest bin sizes under a reasonable amount of fluctuation for multiple Hi-C datasets simultaneously when integrating them is successful. For example, although Yardımcı et al. [4] performed quality assessment of various tools, HiCRep [5], GenomeDISCO [6], HiC-Spector [7], and QuASAR-Rep [2] to process multiple Hi-C datasets, their conclusions were "we do not recommend using reproducibility scores to attempt to select an appropriate resolution." The one tool that has been historically used to process multiple

Fig. 1 Starting from K Hi-C datasets or synthetic data represented as $N \times N$ matrix, a tensor $x_{ii'k} \in \mathbb{R}^{N \times N \times K}$ is generated. Applying TD to $x_{ii'k}$ gives $u_{\ell_1 i}$, which is attributed to ith bins or features. As long as c, which is a contribution of a hidden common structure, or the bin sizes are large enough, $\ell_1 = 1$ is correlated with a hidden common structure or functional sites. Optimal c or bin size is decided at the phase transition after which $\ell_1 = 1$ is no longer correlated with a hidden common structure or functional sites.

Hi-C datasets, namely HSA [8], is no longer available. And although multiHiCcompare [9] deals with multiple Hi-C datasets, it can only be used to perform pairwise comparisons. Thus, it cannot be used to simultaneously determine the optimal bin sizes for multiple datasets. Similarly, although Dedoc2 [10] can be used to determine the optimal bin size using entropy, it can only be applied to a single Hi-C dataset (i.e., to individual single cells) and cannot be applied in an integrated manner. As these examples show, although tools exist that can be used to find the optimal bin sizes for multiple Hi-C datasets, to the best of our knowledge, none of these enable determining the optimal bin sizes over multiple Hi-C datasets when these are integrated. To resolve this problem, we propose a novel application of TD-based unsupervised FE [11], which allows us to observe a phase transition through which the optimal bin sizes can be determined without specifying a threshold value (Fig. 1). To the best of our knowledge, this represents the first successful attempt to determine optimal bin sizes for multiple Hi-C datasets simultaneously when integrating them.

There are multiple reasons why TD-based unsupervised FE is suitable to address this problem, i.e., optimal bin sizes for multiple Hi-C data sets. In principal, TD-based unsupervised FE was applicable to wide ranged genomic problems [11], including gene expression, histone modification, DNA methylation, chromtine structures, and so on. Thus, we can expect that TD-based unsupervised FE can deal with Hi-C profiles as well. Especially, since we recently successfully have applied TD-based unsupervised FE to protein-protein interaction (PPI) [12–14], there are no reasons that we do not apply TD-based unsupervised FE to Hi-C profiles, since Hi-C and PPI are interaction between genomic loci in some sense.

2 Results

2.1 Synthetic data

First, we investigated the singular value vector, $u_{\ell_1 i}$, attributed to the ith feature, which corresponds to the ith bin when we consider real Hi-C data. This is associated with a hidden common (clustering) structure, y_i (see Methods) embedded into the synthetic dataset where there are 1,000 features (i), the top 10 of which are clustered with each other (for more details, see Methods). Figure 2 shows the dependence of the selected ℓ_1 on c, which represents the contribution of the hidden common structure among all datasets (see Methods). Although $\ell_1 = 1$, which has the largest contribution,

Fig. 2 The boxplot of ℓ_1 selected upon c

is always most highly correlated with a common structure for a larger c, the frequency of selecting ℓ_1 other than 1 increases as c decreases. Additionally, although ℓ_3, which is most highly associated with the selected ℓ_1, is always 1, which corresponds to simple averaging over the samples (Fig. 3), for large enough c, other ℓ_3s than 1 will be selected as c decreases (Fig. 4). In reality, although the correlation between the selected $u_{\ell_1 i}$ and hidden common structure y_i remains equal to one for a larger c, it decrease as c decreases below a certain threshold value (Fig. 5); for smaller values of c, the correlations are no longer significant (Fig. 6).

Lastly, we checked whether the TD-based unsupervised FE correctly selected the 10 features ($i \leq 10$) that were interconnected with each other (Table 1). Although FPs (i.e., $i > 10$ but wrongly associated with adjusted P-values less than 0.01) heavily fluctuated, TPs (i.e., $i \leq 10$ and correctly associated with adjusted P-values less than 0.01) monotonically decreased, and FNs (i.e., $i \leq 10$ but wrongly associated with adjusted P-values larger than 0.01) monotonically increased as c decreased after $c \leq 0.05$. This is consistent with the observation that a TD-based unsupervised FE cannot capture the hidden common structure y_i if c is too small. One could ask why we need

Fig. 3 Boxplot of $u_{\ell_3 k}$ over replicates ($1 \le k \le 10$) for various c values. The red horizontal broken line represents $u_{\ell_3 k} = 0$

Fig. 4 The boxplot of ℓ_3 selected upon c

TD if a simple average over replicates can achieve a better performance. In response, we can compute a correlation between a simple average $\langle x_{ii'k} \rangle$ and a hidden common structure, y_i, as well (Fig. 5 and 6) and compare these results with those of TD. From this, it is evident that the TD-based unsupervised FE outperforms the simple average, demonstrating that TD-based unsupervised FE is more worthwhile than the use of a simple average. Based on these observations, the threshold value, below which the hidden common structure is no longer a primary structure, is approximately $c = 0.05$. Although this specific c value may not be important, it is important to note that there is a threshold value above which u_{1i} is always selected and is highly coincident with the hidden common structure. This is analogous to phase transition. It is worth noting that we might be able to use this result for quality assessment; that is, the

Fig. 5 The boxplot of the Pearson's correlation coefficients between $u_{\ell_1 i}$ selected (left) or simple average $\langle x_{ii'k} \rangle_i$ (right) and a hidden common structure, y_i, as a function of c

Fig. 6 The boxplot of P-values in the logarithmic scale associated with the Pearson's correlation coefficient between $u_{\ell_1 i}$ selected (left) or simple average $\langle x_{ii'k} \rangle_i$ (right) and a hidden common structure, y_i, as a function of c. $P < 10^{-100}$ are truncated to be $P = 10^{-100}$.

results obtained by the integration of multiple profiles can be trusted only when they are above the threshold value, and *we do not have to specify the threshold value in advance because the threshold value is automatically decided when u_{1i} is not correlated with the hidden common structure, y_i.* Nevertheless, in real applications, we cannot know what the hidden common structure is. Thus, due to the fact that we need a hidden common structure in order to compute correlation coefficients, it may not be possible to estimate threshold values. In the following, we demonstrate how to estimate an accurate threshold value using the results obtained by integrating multiple profiles without knowing hidden common structures.

Table 1 Confusion matrix between sites selected (associated with adjusted P-values less than 0.01) by TD-based unsupervised FE and those interconnected sites ($y_i = 1, i \leq 10$). The correspondences to TP (true positive), FP (false positive), TN (true negative), and FN (false negatives) are also shown at the end of table.

	c	$i > 10$	$i \leq 10$	$i > 10$	$i \leq 10$	$i > 10$	$i \leq 10$	$i > 10$	$i \leq 10$
		0.5		0.4		0.3		0.2	
Adjusted	≥ 0.01	990.0	0.0	990.0	0.0	846.0	0.0	989.9	0.0
P-values	< 0.01	0.0	10.0	0.0	10.0	144.0	10.0	0.1	10
	c	0.1		0.05		0.04		0.03	
Adjusted	≥ 0.01	960.0	0.0	990.0	3.8	989.5	5.0	988.9	7.9
P-values	< 0.01	30.0	10.0	0.1	6.2	0.5	5.0	1.1	2.1
	c	0.02		0.01				**Legend**	
Adjusted	≥ 0.01	988.2	9.8	988.2	9.8			**TN**	**FN**
P-values	< 0.01	1.8	0.2	1.8	0.2			**FP**	**TP**

2.2 Hi-C dataset

In this section, the application of TD-based unsupervised FE to real Hi-C datasets and the use of the resulting phase transition for quality assessment, as mentioned above, is described for the selection of optimal bin sizes.

Herein, TD-based unsupervised FE was applied to two Hi-C datasets. Because the hidden common structures are unknown, known functional sites can be employed instead of hidden common structures (Tables 2, 3, 4, and 5). Here are explanation of functional sites. CTCF is the transcription factor, CTCF, binding sites. CTCF transcription factor is know to be related to chromatin structures. Thus, the coincidence with CTCF binding site is good measure to evaluate whether Hi-C profiles capture the functional sites. PLS, pELS, and dELS are know to be overlap with binding sites of TAZ, activation of which is known to result in chromatin architecture alterations [15]. Thus they are also good measutres to evaluate whether Hi-C profiles capture the functional sites.

Since $u_{\ell_1 i}$ associated with the highest absolute correlation coefficient is almost always more correlated with functional site than the simple average $\langle x_{ii'k} \rangle_i$ excluding dELS for GSE255264, it is reasonable to consider TD-based unsupervised FE as an advanced criteria for the assessment of the quality the Hi-C datasets in order to verify whether the Hi-C data is good enough to capture hidden common structure. A phase transition-like behavior was observed, as expected for the TD-based unsupervised FE applied to a real Hi-C dataset. For GSE260760, u_{1i} showed the highest absolute correlation with functional sites regardless of the type of functional site for a bin size of 1,000,000, but no longer had a bin size of 150,000. For GSE255264, u_{1i} showed the highest absolute correlation with functional sites regardless of the type of functional site for bin sizes of 1,000,000 and 150,000, but no longer had a bin size of 40,000. Thus, phase-transition-like phenomena are expected to occur between 1,000,000 and 150,000 for GSE260760 and between 150,000 and 40,000 for GSE255264. These results indicate that bin sizes less than or equal to 150,000 for GSE260760 and those less

Table 2 Absolute correlations between $u_{\ell_1 i}$ or simple average $\langle x_{ii'k}\rangle_i$ and CTCF binding sites. Bold is used to denote the highest absolute correlation coefficients.

CTCF PC	1	2	5	$\langle x_{ii'k}\rangle_i$
		GSE260760		
1000000				
Pearson	$\mathbf{4.98 \times 10^{-1}}$	1.23×10^{-1}		3.36×10^{-1}
P-value	1.43×10^{-175}	6.49×10^{-11}		5.64×10^{-75}
Spearman	$\mathbf{5.72 \times 10^{-1}}$	4.99×10^{-1}		5.18×10^{-1}
P-value	8.34×10^{-244}	7.69×10^{-177}		8.30×10^{-193}
150000				
Pearson	5.65×10^{-3}	2.75×10^{-2}	$\mathbf{4.42 \times 10^{-1}}$	3.14×10^{-1}
P-value	4.41×10^{-1}	1.76×10^{-4}	0	0
Spearman	3.66×10^{-1}	5.52×10^{-1}	$\mathbf{5.73 \times 10^{-1}}$	5.14×10^{-1}
P-value	0	0	0	0
		GSE255264		
1000000				
Pearson	$\mathbf{5.09 \times 10^{-1}}$	3.62×10^{-2}		4.45×10^{-1}
P-value	1.24×10^{-184}	5.52×10^{-2}		1.62×10^{-136}
Spearman	$\mathbf{6.87 \times 10^{-1}}$	3.15×10^{-1}		6.35×10^{-1}
P-value	0	1.10×10^{-65}		0
150000				
Pearson	$\mathbf{4.46 \times 10^{-1}}$	4.01×10^{-2}		3.88×10^{-1}
P-value	0	4.38×10^{-8}		0
Spearman	$\mathbf{6.25 \times 10^{-1}}$	2.54×10^{-1}		5.79×10^{-1}
P-value	0	3.40×10^{-271}		0
40000				
Pearson	2.88×10^{-3}	$\mathbf{3.89 \times 10^{-1}}$		3.32×10^{-1}
P-value	4.47×10^{-1}	0		0
Spearman	4.42×10^{-1}	$\mathbf{5.55 \times 10^{-1}}$		5.11×10^{-1}
P-value	0	0		0

than or equal to 40,000 for GSE255264 can no longer be regarded as good enough to capture hidden common structures.

2.3 Cluster structure detection of Hi-C datasets

Since TD-based unsupervised FE can be used to select bins associated with functional sites, it may also be used to detect common clustering structures within multiple HiC datasets. To evaluate this, we plotted 2424 and 447 $x_{ii'k}$s selected by u_{1i} and u_{2i} with bin size of 40,000 for GSE255264, respectively (Fig. 7). Since in this bin size for GSE255264, u_{1i} is not associated with the highest absolute correlation with functional sites, u_{1i} is not expected to be associated with the (unknown) hidden common structure. By contrast, u_{2i} is expected to be associated with the (unknown) hidden common structure since u_{2i} is associated with the highest absolute correlation with functional sites (Table 2, 3, 4, and 5). As expected, 2424 $x_{ii'k}$s selected by u_{1i} had a greater sample dependence than 447 $x_{ii'k}$s selected by u_{2i}, since the mean vs SD ratio of 447 $x_{ii'k}$s selected by u_{2i} was less than that of 2424 $x_{ii'k}$s selected by u_{1i} (Table

Table 3 Absolute correlations between $u_{\ell_1 i}$ or simple average $\langle x_{ii'k}\rangle_i$ and promoter-like signatures (PLS). Bold is used to denote the highest absolute correlation coefficients.

PLS PC	1	2	5	$\langle x_{ii'k}\rangle_i$
		GSE260760		
1000000				
Pearson	$\mathbf{4.51 \times 10^{-1}}$	7.08×10^{-2}		3.25×10^{-1}
P-value	1.06×10^{-140}	1.75×10^{-4}		4.59×10^{-70}
Spearman	$\mathbf{6.33 \times 10^{-1}}$	4.86×10^{-1}		6.00×10^{-1}
P-value	0	3.88×10^{-166}		6.31×10^{-274}
150000				
Pearson	4.41×10^{-3}	7.91×10^{-3}	$\mathbf{3.32 \times 10^{-1}}$	2.72×10^{-1}
P-value	5.47×10^{-1}	2.81×10^{-1}	0	0
Spearman	2.74×10^{-1}	4.74×10^{-1}	$\mathbf{5.19 \times 10^{-1}}$	4.77×10^{-1}
P-value	0	0	0	0
		GSE255264		
1000000				
Pearson	$\mathbf{6.39 \times 10^{-1}}$	1.36×10^{-3}		5.19×10^{-1}
P-value	0	9.43×10^{-1}		2.43×10^{-193}
Spearman	$\mathbf{7.64 \times 10^{-1}}$	4.50×10^{-1}		7.45×10^{-1}
P-value	0	5.65×10^{-140}		0
150000				
Pearson	$\mathbf{5.15 \times 10^{-1}}$	1.50×10^{-3}		4.17×10^{-1}
P-value	0	8.38×10^{-1}		0
Spearman	$\mathbf{5.87 \times 10^{-1}}$	2.90×10^{-1}		5.70×10^{-1}
P-value	0	0		0
40000				
Pearson	6.69×10^{-4}	$\mathbf{3.60 \times 10^{-1}}$		2.87×10^{-1}
P-value	8.60×10^{-1}	0		0
Spearman	2.75×10^{-1}	$\mathbf{3.93 \times 10^{-1}}$		3.68×10^{-1}
P-value	0	0		0

6). This result suggests that for a bin size of 40,000, the (unknown) hidden common structure is no longer a primary part of datasets, and this is in fact a secondary contribution. In reality, although 2424 $x_{ii'k}$s selected by u_{1i} are widely distributed along the whole genome, the distribution of 447 $x_{ii'k}$s selected by u_{1i} is restricted to the limited region along the whole genome (Fig. 7). This demonstrates that with a bin size of 40,000, the present dataset for GSE255264 is unable to capture the common structures within the dataset.

However, for GSE260760 where the bin size of 150,000 is far below the phase transition-like point, even u_{2i} is associated with the highest absolute correlation with functional sites, u_{5i} (Table 2, 3, 4, and 5). Fig. 8 shows the 225, 171, and 187 $x_{ii'k}$s selected by u_{1i}, u_{2i}, and u_{5i}. The 187 $x_{ii'k}$s selected by u_{5i} associated with the highest absolute correlation with functional sites cannot be regarded as more independent of some samples than others, since the Mean vs SD ratios are almost equivalent between u_{1i}, u_{2i}, and u_{5i} (Table 6). The fact that the number of selected bins was small (Fig. 8, 225, 171 and 187 $x_{ii'k}$s that are less than 1,000) also suggests that the integration was

Table 4 Absolute correlations between $u_{\ell_1 i}$ or simple average $\langle x_{ii'k}\rangle_i$ and proximal with enhancer-like signatures (pELS). Bold is used to denote the highest absolute correlation coefficients.

pELS PC	1	2	5	$\langle x_{ii'k}\rangle_i$
		GSE260760		
1000000				
Pearson	$\mathbf{5.43 \times 10^{-1}}$	8.50×10^{-2}		3.76×10^{-1}
P-value	2.89×10^{-215}	6.47×10^{-6}		4.77×10^{-95}
Spearman	$\mathbf{7.08 \times 10^{-1}}$	5.46×10^{-1}		6.75×10^{-1}
P-value	0	2.00×10^{-217}		0
150000				
Pearson	4.63×10^{-4}	1.84×10^{-2}	$\mathbf{4.08 \times 10^{-1}}$	3.23×10^{-1}
P-value	9.50×10^{-1}	1.20×10^{-2}	0	0
Spearman	3.32×10^{-1}	5.61×10^{-1}	$\mathbf{6.19 \times 10^{-1}}$	5.78×10^{-1}
P-value	0	0	0	0
		GSE255264		
1000000				
Pearson	$\mathbf{7.01 \times 10^{-1}}$	3.06×10^{-3}		5.82×10^{-1}
P-value	0	8.71×10^{-1}		1.07×10^{-253}
Spearman	$\mathbf{8.22 \times 10^{-1}}$	4.95×10^{-1}		8.03×10^{-1}
P-value	0	3.74×10^{-173}		0
150000				
Pearson	$\mathbf{5.78 \times 10^{-1}}$	1.65×10^{-3}		4.79×10^{-1}
P-value	0	8.22×10^{-1}		0
Spearman	$\mathbf{6.70 \times 10^{-1}}$	3.56×10^{-1}		6.54×10^{-1}
P-value	0	0		0
40000				
Pearson	9.76×10^{-4}	$\mathbf{4.17 \times 10^{-1}}$		3.40×10^{-1}
P-value	7.97×10^{-1}	0		0
Spearman	3.35×10^{-1}	$\mathbf{4.74 \times 10^{-1}}$		4.48×10^{-1}
P-value	0	0		0

substantially degraded. Based on the above observations, the optimal bin sizes for integrating GSE260760 and GSE255264 were 1,000,000 and 150,000, respectively, within the tested bin sizes. As fewer bin sizes are usually employed to investigate genome structures, we need a greater number of reads and smaller bin sizes as thresholds (i.e., to make phase transition-like phenomena occur at smaller bin sizes). The advantage of this strategy is that we can check whether the number of reads is sufficient before conducting a detailed investigation of the obtained contact map. Alternatively, if we are unable to suppress the appearance of phase transition-like phenomena even after increasing the number of mapped short reads, this suggests that there are no common structures at finer resolutions; in this case, multiple Hi-C datasets will need to be integrated at finer resolutions. The strategy presented here informs this type of decision-making. In conclusion, by replacing the correlation between a hidden common structure and that of functional sites, we obtained the following:

Table 5 Absolute correlations between $u_{\ell_1 i}$ or simple average $\langle x_{ii'k} \rangle_i$ and distal with enhancer-like signatures (dELS). Bold is used to denote the highest absolute correlation coefficients.

dELS PC	1	2	5	$\langle x_{ii'k} \rangle_i$	
		GSE260760			
1000000					
Pearson	$\mathbf{8.51 \times 10^{-1}}$	6.84×10^{-2}		6.59×10^{-1}	
P-value	0	2.89×10^{-4}		0	
Spearman	$\mathbf{8.62 \times 10^{-1}}$	6.45×10^{-1}		8.44×10^{-1}	
P-value	0	0		0	0
150000					
Pearson	6.69×10^{-3}	4.10×10^{-2}	$\mathbf{6.06 \times 10^{-1}}$	5.69×10^{-1}	
P-value	3.61×10^{-1}	2.10×10^{-8}	0	0	
Spearman	4.54×10^{-1}	7.32×10^{-1}	$\mathbf{8.15 \times 10^{-1}}$	8.02×10^{-1}	
P-value	0	0	0	0	
		GSE255264			
1000000					
Pearson	7.12×10^{-1}	1.48×10^{-2}		$\mathbf{7.93 \times 10^{-1}}$	
P-value	0	4.33×10^{-1}		0	
Spearman	8.22×10^{-1}	5.88×10^{-1}		$\mathbf{8.26 \times 10^{-1}}$	
P-value	0	2.63×10^{-260}		0	
150000					
Pearson	6.05×10^{-1}	9.10×10^{-3}		$\mathbf{6.63 \times 10^{-1}}$	
P-value	0	2.14×10^{-1}		0	
Spearman	7.38×10^{-1}	5.02×10^{-1}		$\mathbf{7.45 \times 10^{-1}}$	
P-value	0	0		0	
40000					
Pearson	3.61×10^{-3}	5.11×10^{-1}		$\mathbf{5.55 \times 10^{-1}}$	
P-value	3.40×10^{-1}	0		0	
Spearman	4.80×10^{-1}	6.50×10^{-1}		$\mathbf{6.51 \times 10^{-1}}$	
P-value	0	0		0	

Table 6 Mean vs SD ratios. Smaller values are indicative of more independent of samples (ks). Bold denotes the ℓ_1s most correlated with functional sites

$u_{\ell_1 i}$ used for selection ℓ_1	GSE255264		GSE260760		
	1	**2**	1	2	**5**
Mean vs SD ratio	0.629	0.302	0.472	0.436	0.475

1. A realization of the "phase transition-like" phenomena, below which we cannot expect that common structures are primary factors within a dataset (since u_{1i} is not associated with the highest absolute correlation with functional sites).
2. A more significant correlation with functional sites using TD-based unsupervised FE compared with the simple average $\langle x_{ii'k} \rangle_i$.

These results highlight the promising nature of this method.

Fig. 7 Top: 2424 $x_{ii'k}$s selected by u_{1i}, middle: 447 $x_{ii'k}$s selected by u_{2i} for GSE255264. From left to right, the seven datasets are aligned horizontally in ascending order of their GSM IDs. Bottom left: $\log_{10} u_{1i}$, bottom right $\log_{10} u_{2i}$. Red indicates the selected ones. The bin sizes are 40,000.

3 Discussion

Changes in bin sizes in the Hi-C data are analogous to changing c, which represents the contribution of the hidden common structure represented by y_i in the synthetic data. As the number of bins is increased and the size of the bin is decreased, the number of reads per individual bin decreases under the condition of a fixed total

Fig. 8 Top: 255 $x_{ii'k}$s selected by u_{1i}; middle: 171 $x_{ii'k}$s selected by u_{2i}; bottom: 187 $x_{ii'k}$s selected by u_{5i} for GSE260760. The bin sizes are 150,000. From left to right, the nine datasets are aligned horizontally. From left to right, the nine datasets are aligned horizontally in ascending order of the GSM IDs.

number of short reads. This results in a small number of reads in individual bins and an inaccurate estimation of the number of reads in individual bins. Thus, as the size of the bins decreases, the fluctuation in the number of reads in the bins increases, resulting in the divergence between the individual datasets. Thus, decreases of bin size should be analogous to those of the parameter "c" in the synthetic data. Thus, it is not surprising that the bin sizes decrease, since "c" decreases in the synthetic data, as observed through the phase transition-like phenomena. In addition, TD-based unsupervised FE can be used to assess the quality of the Hi-C measurements. Because the number of reads downloaded for individual datasets was fixed at 100,000,000, the number of expected reads in individual bins was also constant. Nevertheless, if the number of interactions differs between datasets, it becomes difficult to capture hidden

common structures within multiple Hi-C datasets. For this reason, a decrease in bin size corresponds to a decrease in c in the synthetic data. Thus, phase transition-like phenomena can occur, as in the case for synthetic datasets.

As for the comparison with previous studies, to our best knowledge, there are no other previous methods that can derive optimal bin sizes based upon multiple profiles without selecting no threshold values in advance. Although there are some deep-learning based methods [16–19], they are not applicable to Hi-C data as it is. Thus, instead of the performance comparison with other/previous methods, we compare the our results with various criteria generated by one of SOTA, HiCexplolar [20] (Table 7). For the consistency with our analysis, at first, we noticed that bin size 1,000,000,

Table 7 Various measures about Hi-C data quality provided by HiCexplorer. CCS:Compartment Clarity Score.

GSE269769				GSM81238XX					
XX	32	33	34	35	36	37	38	39	40
1000000	(binsize)								
Sparsity	80.03	57.04	74.32	50.48	55.89	43.67	64.58	67.18	32.91
Coverage	3392.37	5051.81	4102.69	5084.6	6653.28	6347.97	4024.74	2953.19	10791.09
TADs	151	163	144	170	156	160	160	169	154
CCS	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
150000	(binsize)								
Sparsity	99.18	97.68	98.97	96.97	98.21	97	97.9	98.26	96.79
Coverage	508.8068	757.6976	615.3432	762.6163	997.8959	952.1036	603.6518	442.9353	1618.507
TADs	786	1220	760	1282	953	1190	1291	1273	1062
CCS	0.06	0.06	0.05	0.06	0.06	0.06	0.06	0.06	0.06
similarity	0.715999	0.73567	0.729842	0.747258	0.732688	0.722467	0.727329	0.746207	0.702418
GSE255264				GSM80677XX					
XX	73	74	75	77	78	79	80		
1000000	(binsize)								
Sparsity	34.16	32.43	39.87	35.21	67.53	70.44	38.8		
Coverage	6045.88	6861.03	6252.25	6038.25	2759	2321.94	6217.18		
TADs	143	141	150	145	146	144	147		
CCS	0.15	0.15	0.15	0.15	0.15	0.15	0.14		
150000	(binsize)								
Sparsity	96.25	95.95	96.54	96.28	98.45	98.63	96.47		
Coverage	906.794	1029.055	937.7463	900.4138	408.4901	348.2573	932.4871		
TADs	1276	1277	1281	1278	1258	1224	1294		
CCS	0.06	0.06	0.06	0.06	0.06	0.06	0.06		
similarity	0.695706	0.673369	0.697345	0.685025	0.6736	0.680826	0.669958		
40000	(binsize)								
Sparsity	99.63	99.59	99.64	99.62	99.84	99.86	99.64		
Coverage	241.8052	274.4072	250.0589	241.5002	108.9277	92.86609	248.6565		
TADs	3664	3843	3761	3759	3355	3163	3698		
CCS	0.03	0.03	0.03	0.03	0.03	0.03	0.03		

which is judged to be acceptable in our analysis, is associated with sparsity less than 80 % (P-values computed by t test are 0.001239 for GSE269769 and 0.0006841 for

GSE255264, respectively). On the other hand, bin size 150,000 for GSE269769 and 40,000 for GSE255264, which is judged not to be acceptable in our analysis, are associated with sparsity larger than 80 %. Since sparsity less than 80 % is generally supposed to be acceptance condition of Hi-C profile quality, our analysis is primarily coincident with the critetia based upon sparsity. On the other hand, bin side 150,000 for GSE255264, which is judged to be acceptable in our analysis, is associated with sparsity larger than 80 %. Thus, our criteria can have ability to judge the bin size larger than 80% as acceptable. To see what causes the difference between our criterion and that based upon sparsity, we consider other quantity and try to find those distinct between bin size 150,000 for GSE269769 and bin size 150,000 for GSE255264 since the former is judged not to be acceptable in our criteria whereas the latter it judged to be acceptable in our analysis. Then we found that TADs numbers for GSE255264 are significantly larger than those for GSE269769 (P-value computed t test is 0.03517) and similarity for GSE255264 are significantly less than those for GSE269769 (P-value computed t test is 7.757×10^{-10}). This is reasonable since our criteria is based upon biological significance. The number of TADs is supposed to be related to other biological features, e.g, CTCF binding. Since our criteria do not require any threshold value to identify optimal bin sizes, for which HiCexplolar requires threshold value of sparsity 80%, our method is superior to the other method. Actually speaking, even if individual profiles are not problematic in the quality, this does not always mean that there are common structures among them. This suggests that we need another criteria apart from quality assessment of for the integrated analysis apart from individual quality assessment. One should also notice that the correlations between $\langle x_{ii'k} \rangle_i$ and functional sited are not distinct at all between bin sizes with sparsity less than 80 % and others. It also suggests that the present strategy is more useful to evaluate optimal bin sizes than simple average.

4 Conclusion

In this study, TD-based unsupervised FE was applied to multiple Hi-C datasets. We found phase transition-like phenomena that are boundaries if u_{1i} were those that were most highly correlated with the functional site, as observed in the synthetic data. Thus, we can specify the optimal bin size as the smallest bin size, provided that u_{1i} is the most highly correlated with the functional site. As a by-product, u_{1i} is usually more strongly correlated with functional sites than with simple averages over several datasets. Therefore, it can be used as a representative profile. In summary, in this study, a strategy for selecting the optimal bin size was developed when integrating multiple Hi-C datasets. As a by-product, we can have representative profiles, $u_{\ell_1 i}$s, which are more strongly correlated with functional sites than simple averages, $\langle x_{ii'k} \rangle_i$. The weak point of the present methodology is that it is fully unsupervised. Since it does not have any tunable parameters, if it fails, we have to simply give up analysing the data in the present method. Future improvement depends upon the development of TD-based unsupervised FE. For example, Bayesian work frame might be able to improve the method performance.

5 Methods

5.1 Synthetic data

The synthetic data used in this study was a tensor $x_{ii'k} \in \mathbb{R}^{1,000 \times 1,000 \times 10}$. Initially, all $x_{ii'k}$s were filled with 0. Then, 100 $x_{ii'k}$s for $1 \leq i, i' \leq 10$ were filled with 1. In addition to this, 1 was added to $x_{ii'k}$ for 200 randomly selected (i, i') pairs in individual ks (this means that randomly selected pairs are not common between distinct ks). The thirty-three $x_{ii'k}$s (replicates) were generated with distinct random seeds. Only 33 replicates were used because only 33 of the 100 replicates were associated with successful HOSVD; the other replicates were eliminated due to singularity.

5.1.1 Hidden common structures

We define y_i as

$$y_i = \begin{cases} 1, & i \leq 10 \\ 0, & i > 10 \end{cases} \tag{1}$$

y_i is called a hidden common structure in the analysis of the synthetic data in this study because it is distinct between those interconnected is, regardless of ks and the other is.

5.1.2 Correlation with hidden common structures

For synthetic data, the correlations between $u_{\ell_1 i}$ associated with the highest absolute correlation or the simple average

$$\langle x_{ii'k} \rangle_i = \frac{1}{33000} \sum_{i'=1}^{1000} \sum_{k=1}^{33} x_{ii'k} \tag{2}$$

and y_i were computed.

5.2 Hi-C datasets

Two Hi-C datasets were analyzed in this study.

5.2.1 GSE260760

Nine Hi-C profiles were downloaded from human knee chondrocytes [21].

5.2.2 GSE255264

Seven AK1 cell line Hi-C profiles [22], that were originally obtained from [23], were downloaded. Although there were nine AK1 datasets, only seven (GSM8067773, GSM8067774, GSM8067775, GSM8067777, GSM8067778, GSM8067779, and GSM8067780) were downloadable.

5.2.3 Downloading fastq files

To have same number of reads for all datasets, "-X 100000000" option, which limits the number of downloaded reads to as many as 10^8, was added to fastq_dump [24].

5.2.4 Mapping reads to the human genome

HiC-Pro [25] was used to map reads to the hg38 human genome, assuming bin sizes of 1,000,000, 500,000, 150,000, 40,000, and 20,000.

5.2.5 Preprocessing

The "raw" matrix files were used for the analyses. $x_{ii'k}$ was normalized as follows

$$x_{ii'k} \leftarrow \frac{x_{ii'k}}{\frac{1}{N^2} \sum_{i=1}^{N} \sum_{i'=1}^{N} |x_{ii'k}|} \tag{3}$$

5.3 Brief introduction of Tucker decomposition using Higher-order singular value decomposition

There are multiple ways to perform tensor decomposition (TD) [11]. Among them, we employed Tucker decomposition for TD-based unsupervised FE. Tucker decomposition decompose a tensor into a product sum of a small core tensor and matrices whose number is as many as number of indices; this means individual matrices represent bundle of various vectors attributed to each index and dependence upon indices. Usually, there can be several kind of dependence, each column of matrix corresponds to dependence upon index. Usually, TD is expected to reduce the degrees of freedom and to enable us to understand the complicated structure of tensor. Tucker decomposition can fulfill this requirement by expanding a matrix with a produce sum of a small tensor and matrices. It is very usual that small core tensor as well as small matrices can represent the original tensor well. Although there are multiple ways to compute Tucker decomposition, we employed Higher-order singular value decomposition (HOSVD) to perform Tucker decomposition. HOSVD is a simple algorithm since it performs singular value decomposition to a matrix generated from a tensor by unfolding. Thus Tucker decomposition with HOSVD is easy to perform and fitted to be applied to massive HOSVD data set.

5.4 TD-based unsupervised FE applied to the synthetic and Hi-C data

Higher-order singular value decomposition (HOSVD) [11] was applied to $x_{ii'k} \in \mathbb{R}^{N \times N \times K}$ to obtain

$$x_{ii'k} = \sum_{\ell_1=1}^{N} \sum_{\ell_2=1}^{N} \sum_{\ell_3=1}^{K} G(\ell_1 \ell_2 \ell_3) u_{\ell_1 i} u_{\ell_2 i'} u_{\ell_3 k} \tag{4}$$

where $G \in \mathbb{R}^{N \times N \times K}$ is a core tensor that represents the contribution of $u_{\ell_1 i} u_{\ell_2 i'} u_{\ell_3 k}$ to $x_{ii'k}$, $u_{\ell_1 i} = u_{\ell_2 i'} \in \mathbb{R}^{N \times N}$ and $u_{\ell_3 k} \in \mathbb{R}^{K \times K}$ are singular value and orthogonal matrices. HOSVD was performed by applying `irlba` [26] to unfolded tensor $x_{i(i'k)} \in \mathbb{R}^{N \times (NK)}$ in sparse matrix format using the Matrix package [27] since $x_{ii'k}$ was too large to be stored in a dense matrix format. Because HOSVD is a set of singular value decompositions (SVD) applied to an unfolded tensor [11], HOSVD can be easily replaced with SVD. $u_{\ell_1 i}$ of interest was selected either based on its correlation with y_i (for the synthetic data) or with known functional sites (for the Hi-C dataset). Once $u_{\ell_1 i}$ of interest was selected, P-values were attributed to i as

$$\langle u_{\ell_1 i} \rangle = \frac{1}{N} \sum_{i=1}^{N} u_{\ell_1 i} \tag{5}$$

$$P_i = P_{\chi^2}\left[> \left(\frac{u_{\ell_1 i} - \langle u_{\ell_1 i} \rangle}{\sigma_{\ell_1}} \right)^2 \right] \tag{6}$$

where $P_{\chi^2}[> x]$ is the cumulative χ^2 probability distribution, in which the argument is larger than x and σ_{ℓ_1} is the standard deviation of $u_{\ell_1 i}$, computed by optimization. The histogram of P_i was assumed to be flat if $u_{\ell_1 i}$ followed a Gaussian distribution. The optimization of σ_{ℓ_1} was performed such that the histogram of P_i was as flat as possible. To this end, first, the frequency of P_i in the sth bin, $h_s, 1 \leq s \leq S$, was computed by excluding is whose associated adjusted P-values (see below) were less than the threshold value because is whose associated adjusted P-values were less than the threshold value were expected to not obey a Gaussian distribution. Without excluding is whose associated adjusted P-values were less than the threshold value, σ_{ℓ_1} and P_i would be overestimated. Therefore, the number of is whose associated adjusted P-values were less than the threshold value would be wrongly reduced, as well as those of the selected is. Next, the standard deviation of h_s, σ_h, was computed as

$$\langle h_s \rangle = \frac{1}{S} \sum_{s=1}^{S} h_s \tag{7}$$

$$\sigma_h = \sqrt{\frac{1}{S} \sum_{s=1}^{S} (h_s - \langle h_s \rangle)^2} \tag{8}$$

Then, σ_{ℓ_1} that minimized σ_h was computed, and P_i was computed using σ_{ℓ_1}. It is worth noting that this amounts to a self-consistency computation because adjusted P-values must be computed in order to exclude those is associated with adjusted P-values below the threshold value to exclude these is from the computation of h_s. This process was iterated until the minimization of σ_h was complete. P_is were finally adjusted by the BH criterion [11] and those is associated with adjusted P-values less than the threshold value were selected. In the case that the readers are interested in the processes included in TD-based unsupervised FE, please refer to our recently published textbook [11], or to the vignettes of two Bioconductor Packages [28, 29].

5.4.1 Mean vs SD ratio

To quantify the differences of the selected $x_{ii'k}$ between dataset (k) within a set of selected is, Ω_i, the Mean vs SD ratio was defined as

$$\langle x_{ii'k}\rangle_{ii'} = \frac{1}{K}\sum_{k=1}^{K} x_{ii'k} \tag{9}$$

$$\langle x_{ii'k}\rangle = \frac{1}{N(\Omega_i)^2}\sum_{i,i'\in\Omega_i} \langle x_{ii'k}\rangle_{ii'} \tag{10}$$

$$\mathrm{SD} = \frac{1}{N(\Omega_i)^2}\sum_{i,i'\in\Omega_i} \sqrt{\frac{1}{K}\sum_{k=1}^{K}\left(x_{ii'k}-\langle x_{ii'k}\rangle_{ii'}\right)^2} \tag{11}$$

$$\mathrm{Mean\ vs\ SD\ ratio} = \frac{SD}{\langle x_{ii'k}\rangle}. \tag{12}$$

The summation of i, i' was considered in Ω_i and $N(\Omega_i)$ was used to denote the number of is in Ω_i.

5.5 Functional sites used to compute the correlation with $u_{\ell_1 i}$s or $\langle x_{ii'k}\rangle_i$ for the Hi-C datasets

5.5.1 Overlap with bins

Overlaps between bins were computed using the `findOverlaps` function in IRanges [30].

5.5.2 CTCF

The CTCF profile was retrieved from the AH104727 data in the AnnotationHub [31].

5.5.3 PLS, pELS, and dELS

The PLS, pELS, and dELS profiles were obtained from 41586_2020_2493_MOESM12_ESM.txt [32].

5.6 Similarity

Similarity in Table 7 is defined as the Jaccard coefficient of tads_domains.bed computed by hicFindTADs command in HiCExplorer between bin sizes 1,000,000 and 150,000; the Jaccard coefficient between distinct bin sizes is often used as the quality assessment of Hi-C profiles [33]. Computation was done by jaccard command in bedtools [34] as
`bedtools jaccard  -a file1 -b file2`
where file1 and file2 are bed files for bin size 1,000,000 and 150,000, respectively.

Declarations

Ethics approval and consent to participate

Not applicable

Competing interests

The authors have no conflicts of interest to declare.

Funding

This study was supported by KAKENHI Grant Number 24K15168.

Data availability

We have gotten all the data analysed in this study from GSE260760 and GSE255264.

Code availability

The code used to implement our method is publicly available from the GitHub repository at https://github.com/tagtag/TDbasedUFEHiC.

Author contribution

Y. H. T. planned the study and performed the analyses. Y.-H.T. and T.T. evaluated the results and wrote and reviewed the manuscript. All the authors have read and agreed to the published version of the manuscript. The conceptualization, data curation, analysis were performed by Y. H. T.

References

[1] Li, A., Yin, X., Xu, B., Wang, D., Han, J., Wei, Y., Deng, Y., Xiong, Y., Zhang, Z.: Decoding topologically associating domains with ultra-low resolution Hi-C data by graph structural entropy. Nature Communications **9**(1), 3265 (2018) https://doi.org/10.1038/s41467-018-05691-7

[2] Sauria, M.E., Taylor, J.: Quasar: Quality assessment of spatial arrangement reproducibility in hi-c data. bioRxiv (2017) https://doi.org/10.1101/204438 https://www.biorxiv.org/content/early/2017/11/14/204438.full.pdf

[3] Zhang, Y., An, L., Xu, J., Zhang, B., W, J.Z., Hu, M., Tang, J., Yue, F.: Enhancing Hi-C data resolution with deep convolutional neural network HiCPlus. Nature Communications **9**(1), 750 (2018) https://doi.org/10.1038/s41467-018-03113-2

[4] Yardımcı, G.G., Ozadam, H., Sauria, M.E.G., Ursu, O., Yan, K.-K., Yang, T., Chakraborty, A., Kaul, A., Lajoie, B.R., Song, F., Zhan, Y., Ay, F., Gerstein,

M., Kundaje, A., Li, Q., Taylor, J., Yue, F., Dekker, J., Noble, W.S.: Measuring the reproducibility and quality of Hi-C data. Genome Biology **20**(1), 57 (2019) https://doi.org/10.1186/s13059-019-1658-7

[5] Yang, T., Zhang, F., Yardımcı, G.G., Song, F., Hardison, R.C., Noble, W.S., Yue, F., Li, Q.: Hicrep: assessing the reproducibility of hi-c data using a stratum-adjusted correlation coefficient. Genome Research **27**(11), 1939–1949 (2017) https://doi.org/10.1101/gr.220640.117 http://genome.cshlp.org/content/27/11/1939.full.pdf+html

[6] Ursu, O., Boley, N., Taranova, M., Wang, Y.X.R., Yardimci, G.G., Stafford Noble, W., Kundaje, A.: GenomeDISCO: a concordance score for chromosome conformation capture experiments using random walks on contact map graphs. Bioinformatics **34**(16), 2701–2707 (2018) https://doi.org/10.1093/bioinformatics/bty164 https://academic.oup.com/bioinformatics/article-pdf/34/16/2701/48917757/bioinformatics_34_16_2701.pdf

[7] Yan, K.-K., Yardımcı, G.G., Yan, C., Noble, W.S., Gerstein, M.: HiC-spector: a matrix library for spectral and reproducibility analysis of Hi-C contact maps. Bioinformatics **33**(14), 2199–2201 (2017) https://doi.org/10.1093/bioinformatics/btx152 https://academic.oup.com/bioinformatics/article-pdf/33/14/2199/50314921/bioinformatics_33_14_2199.pdf

[8] Zou, C., Zhang, Y., Ouyang, Z.: HSA: integrating multi-track Hi-C data for genome-scale reconstruction of 3D chromatin structure. Genome Biology **17**(1), 40 (2016) https://doi.org/10.1186/s13059-016-0896-1

[9] Stansfield, J.C., Cresswell, K.G., Dozmorov, M.G.: multiHiCcompare: joint normalization and comparative analysis of complex Hi-C experiments. Bioinformatics **35**(17), 2916–2923 (2019) https://doi.org/10.1093/bioinformatics/btz048 https://academic.oup.com/bioinformatics/article-pdf/35/17/2916/50719885/bioinformatics_35_17_2916.pdf

[10] Li, A., Zeng, G., Wang, H., Li, X., Zhang, Z.: Dedoc2 identifies and characterizes the hierarchy and dynamics of chromatin tad-like domains in the single cells. Advanced Science **10**(20), 2300366 (2023) https://doi.org/10.1002/advs.202300366 https://onlinelibrary.wiley.com/doi/10.1002/advs.202300366

[11] Taguchi, Y.-h.: Unsupervised Feature Extraction Applied to Bioinformatics: A PCA Based and TD Based Approach, 2nd edn. Unsupervised and Semi-Supervised Learning. Springer, Switzland (2024)

[12] Taguchi, Y.H., Turki, T.: Novel artificial intelligence-based identification of drug-gene-disease interaction using protein-protein interaction. BMC Bioinformatics **25**(1), 377 (2024)

[13] Taguchi, Y.-h., Turki, T.: Advanced tensor decomposition-based integrated analysis of protein-protein interaction with cancer gene expression can improve coincidence with clinical labels. In: 2023 11th International Conference on Bioinformatics and Computational Biology (ICBCB), pp. 19–25 (2023). https://doi.org/10.1109/ICBCB57893.2023.10246633

[14] Taguchi, Y.-H., Turki, T.: Integrated analysis of gene expression and protein–protein interaction with tensor decomposition. Mathematics **11**(17) (2023) https://doi.org/10.3390/math11173655

[15] Liu, T., Zhou, J., Chen, Y., Fang, J., Liu, S., Frangou, C., Wang, H., Zhang, J.: Genome-wide characterization of taz binding sites in mammary epithelial cells. Cancers **15**(19) (2023) https://doi.org/10.3390/cancers15194713

[16] Li, Y., Liu, Y., Guo, Y.-Z., Liao, X.-F., Hu, B., Yu, T.: Spatio-temporal-spectral hierarchical graph convolutional network with semisupervised active learning for patient-specific seizure prediction. IEEE Transactions on Cybernetics **52**(11), 12189–12204 (2022) https://doi.org/10.1109/TCYB.2021.3071860

[17] Cui, W., Xiang, Y., Wang, Y., Yu, T., Liao, X.-F., Hu, B., Li, Y.: Deep multiview module adaption transfer network for subject-specific eeg recognition. IEEE Transactions on Neural Networks and Learning Systems, 1–14 (2024) https://doi.org/10.1109/TNNLS.2024.3350085

[18] Shi, B., Chen, J., Chen, H., Lin, W., Yang, J., Chen, Y., Wu, C., Huang, Z.: Prediction of recurrent spontaneous abortion using evolutionary machine learning with joint self-adaptive sime mould algorithm. Computers in Biology and Medicine **148**, 105885 (2022) https://doi.org/10.1016/j.compbiomed.2022.105885

[19] Lu, W., Zhao, H., He, Q., Huang, H., Jin, X.: Category-consistent deep network learning for accurate vehicle logo recognition. Neurocomputing **463**, 623–636 (2021) https://doi.org/10.1016/j.neucom.2021.08.030

[20] Wolff, J., Rabbani, L., Gilsbach, R., Richard, G., Manke, T., Backofen, R., Grüning, B.A.: Galaxy hicexplorer 3: a web server for reproducible hi-c, capture hi-c and single-cell hi-c data analysis, quality control and visualization. Nucleic Acids Research **48**(W1), 177–184 (2020) https://doi.org/10.1093/nar/gkaa220 https://academic.oup.com/nar/article-pdf/48/W1/W177/33433206/gkaa220.pdf

[21] Bittner, N., Shi, C., Zhao, D., Ding, J., Southam, L., Swift, D., Kreitmaier, P., Tutino, M., Stergiou, O., Cheung, J.T.S., Katsoula, G., Hankinson, J., Wilkinson, J.M., Orozco, G., Zeggini, E.: Primary osteoarthritis chondrocyte map of chromatin conformation reveals novel candidate effector genes. Annals of the Rheumatic Diseases **83**(8), 1048–1059 (2024) https://doi.org/10.1136/ard-2023-224945 https://ard.bmj.com/content/83/8/1048.full.pdf

[22] Nolan, B., Harris, H.L., Kalluchi, A., Reznicek, T.E., Cummings, C.T., Rowley, M.J.: Hicrayon reveals distinct layers of multi-state 3d chromatin organization. bioRxiv (2024) https://doi.org/10.1101/2024.02.11.579821 https://www.biorxiv.org/content/early/2024/02/12/2024.02.11.579821.full.pdf

[23] Harris, H.L., Gu, H., Olshansky, M., Wang, A., Farabella, I., Eliaz, Y., Kalluchi, A., Krishna, A., Jacobs, M., Cauer, G., Pham, M., Rao, S.S.P., Dudchenko, O., Omer, A., Mohajeri, K., Kim, S., Nichols, M.H., Davis, E.S., Gkountaroulis, D., Udupa, D., Aiden, A.P., Corces, V.G., Phanstiel, D.H., Noble, W.S., Nir, G., Pierro, M.D., Seo, J.-S., Talkowski, M.E., Aiden, E.L., M, J.R.: Chromatin alternates between A and B compartments at kilobase scale for subgenic organization. Nature Communications **14**(1), 3303 (2023) https://doi.org/10.1038/s41467-023-38429-1

[24] Leinonen, R., Sugawara, H., Shumway, o.b.o.t.I.N.S.D.C. Martin: The Sequence Read Archive. Nucleic Acids Research **39**(suppl_1), 19–21 (2010) https://doi.org/10.1093/nar/gkq1019 https://academic.oup.com/nar/article-pdf/39/suppl_1/D19/7624335/gkq1019.pdf

[25] Servant, N., Varoquaux, N., Lajoie, B.R., Viara, E., Chen, C.-J., Vert, J.-P., Heard, E., Dekker, J., Barillot, E.: HiC-Pro: an optimized and flexible pipeline for Hi-C data processing. Genome Biology **16**(1), 259 (2015) https://doi.org/10.1186/s13059-015-0831-x

[26] Baglama, J., Reichel, L., Lewis, B.W.: Irlba: Fast Truncated Singular Value Decomposition and Principal Components Analysis for Large Dense and Sparse Matrices. (2022). R package version 2.3.5.1. https://CRAN.R-project.org/package=irlba

[27] Bates, D., Maechler, M., Jagan, M.: Matrix: Sparse and Dense Matrix Classes and Methods. (2024). R package version 1.7-0. https://CRAN.R-project.org/package=Matrix

[28] Taguchi, Y.-h.: TDbasedUFE: Tensor Decomposition Based Unsupervised Feature Extraction. (2023). https://doi.org/10.18129/B9.bioc.TDbasedUFE . R package version 1.0.0. https://bioconductor.org/packages/TDbasedUFE

[29] Taguchi, Y.-h.: TDbasedUFEadv Advanced Package of Tensor Decomposition Based Unsupervised Feature Extraction. (2023). https://doi.org/10.18129/B9.bioc.TDbasedUFEadv . R package version 1.0.0. https://bioconductor.org/packages/TDbasedUFEadv

[30] Lawrence, M., Huber, W., Pagès, H., Aboyoun, P., Carlson, M., Gentleman, R., Morgan, M., Carey, V.: Software for computing and annotating genomic ranges. PLoS Computational Biology **9** (2013) https://doi.org/10.1371/journal.pcbi.1003118

[31] Morgan, M., Shepherd, L.: AnnotationHub: Client to Access AnnotationHub Resources. (2023). https://doi.org/10.18129/B9.bioc.AnnotationHub . R package version 3.8.0. https://bioconductor.org/packages/AnnotationHub

[32] Abascal, F., Acosta, R., Addleman, N.J., Adrian, J., Afzal, V., Ai, R., Aken, B., Akiyama, J.A., Jammal, O.A., Amrhein, H., Anderson, S.M., Andrews, G.R., Antoshechkin, I., Ardlie, K.G., Armstrong, J., Astley, M., Banerjee, B., Barkal, A.A., Barnes, I.H.A., Barozzi, I., Barrell, D., Barson, G., Bates, D., Baymuradov, U.K., Bazile, C., Beer, M.A., Beik, S., M, A.B., Bennett, R., Bouvrette, L.P.B., Bernstein, B.E., Berry, A., Bhaskar, A., Bignell, A., Blue, S.M., Bodine, D.M., Boix, C., Boley, N., Borrman, T., Borsari, B., Boyle, A.P., Brandsmeier, L.A., Breschi, A., Bresnick, E.H., Brooks, J.A., Buckley, M., Burge, C.B., Byron, R., Cahill, E., Cai, L., Cao, L., Carty, M., Castanon, R.G., Castillo, A., Chaib, H., Chan, E.T., Chee, D.R., Chee, S., Chen, H., Chen, H., Chen, J.-Y., Chen, S., J, M.C., Chhetri, S.B., Choudhary, J.S., Chrast, J., Chung, D., Clarke, D., Cody, N.A.L., Coppola, C.J., Coursen, J., D'Ippolito, A.M., Dalton, S., Danyko, C., Davidson, C., Davila-Velderrain, J., Davis, C.A., Dekker, J., Deran, A., DeSalvo, G., Despacio-Reyes, G., Dewey, C.N., Dickel, D.E., Diegel, M., Diekhans, M., Dileep, V., Ding, B., Djebali, S., Dobin, A., Dominguez, D., Donaldson, S., Drenkow, J., Dreszer, T.R., Drier, Y., Duff, M.O., Dunn, D., Eastman, C., Ecker, J.R., Edwards, M.D., El-Ali, N., Elhajjajy, S.I., Elkins, K., Emili, A., Epstein, C.B., Evans, R.C., Ezkurdia, I., Fan, K., Farnham, P.J., Farrell, N.P., Feingold, E.A., Ferreira, A.-M., Fisher-Aylor, K., Fitzgerald, S., Flicek, P., Foo, C.S., Fortier, K., Frankish, A., Freese, P., Fu, S., Fu, X.-D., Fu, Y., Fukuda-Yuzawa, Y., Fulciniti, M., Funnell, A.P.W., Gabdank, I., Galeev, T., Gao, M., Giron, C.G., Garvin, T.H., Gelboin-Burkhart, C.A., Georgolopoulos, G., Gerstein, M.B., Giardine, B.M., Gifford, D.K., Gilbert, D.M., Gilchrist, D.A., Gillespie, S., Gingeras, T.R., Gong, P., Gonzalez, A., Gonzalez, J.M., Good, P., Goren, A., Gorkin, D.U., Graveley, B.R., Gray, M., Greenblatt, J.F., Griffiths, E., Groudine, M.T., Grubert, F., Gu, M., Guigó, R., Guo, H., Guo, Y., Zheng, Y., Gursoy, G., Gutierrez-Arcelus, M., Halow, J., Hardison, R.C., Hardy, M., Hariharan, M., Harmanci, A., Harrington, A., Harrow, J.L., Hashimoto, T.B., Hasz, R.D., Hatan, M., Haugen, E., Hayes, J.E., He, P., He, Y., Heidari, N., Hendrickson, D., Heuston, E.F., Hilton, J.A., Hitz, B.C., Hochman, A., Holgren, C., Hou, L., Hou, S., Hsiao, Y.-H.E., Hsu, S., Huang, H., Hubbard, T.J., Huey, J., Hughes, T.R., Hunt, T., Ibarrientos, S., Issner, R., Iwata, M., Izuogu, O., Jaakkola, T., Jameel, N., Jansen, C., Jiang, L., Jiang, P., Johnson, A., Johnson, R., Jungreis, I., Kadaba, M., Kasowski, M., Kasparian, M., Kato, M., Kaul, R., Kawli, T., Kay, M., Keen, J.C., Keles, S., Keller, C.A., Kelley, D., Kellis, M., Kheradpour, P., Kim, D.S., Kirilusha, A., Klein, R.J., Knoechel, B., Kuan, S., Kulik, M.J., Kumar, S., Kundaje, A., Kutyavin, T., Lagarde, J., Lajoie, B.R., Lambert, N.J., Lazar, J., Lee, A.Y., Lee, D., Lee, E., Lee, J.W., Lee, K., Leslie, C.S., Levy, S., Li, B., Li, H., Li, N., Li, S., Li, X., Li, Y., Li, Y., Li, Y., Li, Y., Lian, J., Libbrecht, M.W., Lin, S., Lin, Y., Liu, D., Liu, J., Lu, A., Liu, T., X, S.L., Liu, Y., Liu, Y., Long, M., Lou, S., Loveland, J., Lu, A., Lu, Y., Lécuyer, E., Ma, L., Mackiewicz, M., Mannion, B.J., Mannstadt, M., Manthravadi, D., Marinov, G.K., Martin, F.J., Mattei, E.,

McCue, K., McEown, M., McVicker, G., Meadows, S.K., Meissner, A., Mendenhall, E.M., Messer, C.L., Meuleman, W., Meyer, C., Miller, S., Milton, M.G., Mishra, T., Moore, D.E., Moore, H.M., Moore, J.E., Moore, S.H., Moran, J., Mortazavi, A., Mudge, J.M., Munshi, N., Murad, R., Myers, R.M., Nandakumar, V., Nandi, P., Narasimha, A.M., Narayanan, A.K., Naughton, H., Navarro, F.C.P., Navas, P., Nazarovs, J., Nelson, J., Neph, S., Neri, F.J., Nery, J.R., Nesmith, A.R., J, S.N., Newberry, K.M., Ngo, V., Nguyen, R., Nguyen, T.B., Nguyen, T., Nishida, A., Noble, W.S., Novak, C.S., Novoa, E.M., Nuñez, B., O'Donnell, C.W., Olson, S., Onate, K.C., Otterman, E., Ozadam, H., Pagan, M., Palden, T., Pan, X., Park, Y., E, C.P., Paten, B., Pauli-Behn, F., Pazin, M.J., Pei, B., Pennacchio, L.A., Perez, A.R., Perry, E.H., Pervouchine, D.D., Phalke, N.N., Pham, Q., Phanstiel, D.H., Plajzer-Frick, I., Pratt, G.A., Pratt, H.E., Preissl, S., Pritchard, J.K., Pritykin, Y., Purcaro, M.J., Qin, Q., Quinones-Valdez, G., Rabano, I., Radovani, E., Raj, A., Rajagopal, N., Ram, O., Ramirez, L., Ramirez, R.N., Rausch, D., Raychaudhuri, S., Raymond, J., Razavi, R., Reddy, T.E., Reimonn, T.M., Ren, B., Reymond, A., Reynolds, A., Rhie, S.K., Rinn, J., Rivera, M., Rivera-Mulia, J.C., Roberts, B.S., Rodriguez, J.M., Rozowsky, J., Ryan, R., Rynes, E., Salins, D.N., Sandstrom, R., Sasaki, T., Sathe, S., Savic, D., Scavelli, A., Scheiman, J., Schlaffner, C., Schloss, J.A., Schmitges, F.W., See, L.H., Sethi, A., Setty, M., Shafer, A., Shan, S., Sharon, E., Shen, Q., Shen, Y., Sherwood, R.I., Shi, M., Shin, S., Shoresh, N., Siebenthall, K., Sisu, C., Slifer, T., Sloan, C.A., Smith, A., Snetkova, V., Snyder, M.P., Spacek, D.V., Srinivasan, S., Srivas, R., Stamatoyannopoulos, G., Stamatoyannopoulos, J.A., Stanton, R., Steffan, D., Stehling-Sun, S., J, S.S., Su, A., Sundararaman, B., Suner, M.-M., Syed, T., Szynkarek, M., Tanaka, F.Y., Tenen, D., Teng, M., Thomas, J.A., Toffey, D., Tress, M.L., Trout, D.E., Trynka, G., Tsuji, J., Upchurch, S.A., Ursu, O., Uszczynska-Ratajczak, B., Uziel, M.C., Valencia, A., Biber, B.V., Velde, A.G.v.d., Nostrand, E.L.V., Vaydylevich, Y., Vazquez, J., Victorsen, A., Vielmetter, J., Vierstra, J., Visel, A., Vlasova, A., Vockley, C.M., Volpi, S., Vong, S., Wang, H., Wang, M., Wang, Q., Wang, R., Wang, T., Wang, W., Wang, X., Wang, Y., Watson, N.K., Wei, X., Wei, Z., Weisser, H., Weissman, S.M., Welch, R., Welikson, R.E., Weng, Z., Westra, H.-J., Whitaker, J.W., White, C., White, K.P., Wildberg, A., Williams, B.A., Wine, D., Witt, H.N., Wold, B., Wolf, M., Wright, J., Xiao, R., Xiao, X., Xu, J., Xu, J., Yan, K.-K., Yan, Y., Yang, H., Yang, X., Yang, Y.-W., Yardımcı, G.G., Yee, B.A., Yeo, G.W., Young, T., Yu, T., Yue, F., Zaleski, C., Zang, C., Zeng, H., Zeng, W., Zerbino, D.R., Zhai, J., Zhan, L., Zhan, Y., Zhang, B., Zhang, J., Zhang, J., Zhang, K., Zhang, L., Zhang, P., Zhang, Q., Zhang, X.-O., Zhang, Y., Zhang, Z., Zhao, Y., Zheng, Y., Zhong, G., Zhou, X.-Q., Zhu, Y., Zimmerman, J., Moore, J.E., Purcaro, M.J., Pratt, H.E., Epstein, C.B., Shoresh, N., Adrian, J., Kawli, T., Davis, C.A., Dobin, A., Kaul, R., Halow, J., Nostrand, E.L.V., Freese, P., Gorkin, D.U., Shen, Y., He, Y., Mackiewicz, M., Pauli-Behn, F., Williams, B.A., Mortazavi, A., Keller, C.A., Zhang, X.-O., Elhajjajy, S.I., Huey, J., Dickel, D.E., Snetkova, V., Wei, X., Wang, X., Rivera-Mulia, J.C., Rozowsky, J., Zhang, J., Chhetri, S.B., Zhang, J., Victorsen, A., White, K.P., Visel, A., Yeo, G.W., Burge, C.B., Lécuyer, E., Gilbert, D.M.,

Dekker, J., Rinn, J., Mendenhall, E.M., Ecker, J.R., Kellis, M., Klein, R.J., Noble, W.S., Kundaje, A., Guigó, R., Farnham, P.J., J, M.C., Myers, R.M., Ren, B., Graveley, B.R., Gerstein, M.B., Pennacchio, L.A., Snyder, M.P., Bernstein, B.E., Wold, B., Hardison, R.C., Gingeras, T.R., Stamatoyannopoulos, J.A., Weng, Z.: Expanded encyclopaedias of DNA elements in the human and mouse genomes. Nature **583**(7818), 699–710 (2020) https://doi.org/10.1038/s41586-020-2493-4

[33] Forcato, M., Nicoletti, C., Pal, K., Livi, C.M., Ferrari, F., Bicciato, S.: Comparison of computational methods for hi-c data analysis. Nature Methods **14**(7), 679–685 (2017) https://doi.org/10.1038/nmeth.4325

[34] Quinlan, A.R., Hall, I.M.: Bedtools: a flexible suite of utilities for comparing genomic features. Bioinformatics **26**(6), 841–842 (2010) https://doi.org/10.1093/bioinformatics/btq033