Enhanced bacterial chemotaxis in confined microchannels: Optimal performance in lane widths matching circular swimming radius

Caijuan Yue[1,2], Chi Zhang[1,2,*], Rongjing Zhang[1,*], Junhua Yuan[1,*]

[1] Hefei National Research Center for Physical Sciences at the Microscale, and Department of Physics, University of Science and Technology of China, Hefei, Anhui, 230026, China

[2]These authors contributed equally.

*Corresponding authors:

Junhua Yuan, Rongjing Zhang or Chi Zhang, Hefei National Research Center for Physical Sciences at the Microscale, and Department of Physics, University of Science and Technology of China, Hefei, Anhui, 230026, China, email:

jhyuan@ustc.edu.cn; rjzhang@ustc.edu.cn; zhchi@ustc.edu.cn

Abstract

Understanding bacterial behavior in confined environments is helpful for elucidating microbial ecology and developing strategies to manage bacterial infections. While extensive research has focused on bacterial motility on surfaces and in porous media, chemotaxis in confined spaces remains poorly understood. Here, we investigate the chemotaxis of *Escherichia coli* within microfluidic lanes under a linear concentration gradient of L-aspartate. We demonstrate that *E. coli* exhibits significantly enhanced chemotaxis in lanes with sidewalls compared to open surfaces. We attribute this phenomenon primarily to the intrinsic clockwise circular motion of surface-swimming bacteria and the subsequent alignment effect upon collision with the sidewalls. By varying lane widths, we identify that an 8 μm width—approximating the radius of bacterial circular swimming on surfaces—maximizes chemotactic drift velocity. These results are supported by both experimental observations and stochastic simulations, establishing a clear proportional relationship between optimal lane width and the radius of bacterial circular swimming. Further geometric analysis provides an intuitive understanding of this phenomenon. Our results may offer insights into bacterial navigation in complex biological environments such as host tissues and biofilms, providing a preliminary step toward exploring microbial ecology in confined habitats and potential strategies for controlling bacterial infections.

Introduction

Microorganisms inhabit a variety of complex confined environments. Sperm swimming in the reproductive tract of a female animal (1), bacteria navigating through host cells and tissues (2), cells moving in the wrinkle of biofilm (3), and swarm cells maneuvering in crowded cell clusters (4) are all examples of organisms operating in geometrically confined environments. Furthermore, many diseases have been found to be related to bacterial motion in confinement, such as urinary tract infections and neonatal sepsis.

Previous research has explored the motion of bacteria in confined environments.

Studies have shown that flagellated bacteria tend to accumulate near both solid-liquid

(5, 6) and air-liquid interfaces (7), and exhibit a specific direction of circular swimming

(8). For example, *E. coli* swim clockwise when observed from above a solid surface (8-

11), whereas *Caulobacter crescentus* move in tight, counter-clockwise circles when

viewed from the liquid side. Moreover, Tang *et al.* found that flagellated bacteria orbit

within the thin fluid film around micrometer-sized particles (12). Bacteria also display

different motion behaviors in porous media and tubes (13-19), as well as in other types

of confinement (20-22). In narrow channels with width less than 4 μm, bacterial growth

(23), swimming trajectories (24) and swimming speeds (25) are significantly impacted

compared to bulk conditions. Furthermore, studies on bacterial transport in rectangular

microchannels under flow have demonstrated that confinement influences both

bacterial fluxes and spatial distribution, with cells exhibiting distinct transport

dynamics along channel edges (26). However, while motility in confinement is well-

documented, the specific rules governing bacterial chemotaxis within geometrically

constrained environments remain less understood.

E. coli can sense and move in chemical gradients through a set of chemotactic proteins

(27, 28). The transmembrane chemoreceptors detect attractants or repellents and

transmit signals into the cell by modulating the autophosphorylation of the histidine

kinase CheA. Attractant binding suppresses CheA autophosphorylation, while repellent

binding promotes it. This modulation alters the concentration of the phosphorylated

response regulator protein, CheY-P (28-31). CheY-P binds to the cytoplasmic domain

of flagellar motors, altering the probability of their clockwise rotation (32, 33).

Clockwise and counterclockwise rotations of motors lead to reorientation (tumble) and

smooth swimming (run) modes of the cell body, respectively (34). The adaptation

enzymes CheR and CheB methylate and demethylate the receptors, respectively,

mediating sensory adaptation (35, 36).

While the molecular mechanism is well-characterized, the physical environment plays

a crucial role in chemotactic efficiency. Bacterial chemotaxis has been observed under

various degrees of confinement, often yielding complex behaviors. For instance, in

quasi-2D microchannels with a depth of 2 μm, bacteria were found to adjust their run

lengths and tumble frequencies to respond to chemical gradients (37). Similarly, studies

in 10 μm-depth microchambers revealed that *E. coli* maintains chemotactic

performance in the presence of evenly spaced obstacles (38). While these studies

focused on confinement between top and bottom surfaces, recent work by Braham et al

showed that bacteria on a single solid surface can exhibit an escape response to high-

concentration chemorepellents (250 mM Ni(NO3)$_2$) (39). Conversely, other research

has shown that bacterial chemotactic drift velocity decreases sharply near sample

chamber surfaces compared to bulk liquid, a phenomenon attributed to circular cell

movement at these interfaces (40). This observation suggests that a single surface can

significantly impair bacterial chemotactic performance. Yet, a study of chemotaxis in

two-dimensional bacterial swarms on semisolid agar surfaces has demonstrated that *E.*

coli can exhibit effective chemotaxis in attractant gradients, especially at high cell

densities (4). This apparent contradiction is likely due to cell-cell interactions

mitigating surface effects in dense populations. Despite these investigations into

motility under surface effects, a comprehensive understanding of how specific

confinement geometries modulate chemotaxis remains limited.

Here, we study the chemotaxis of *E. coli* on surfaces within lanes of different widths,

exposed to a linear concentration gradient of L-aspartate using a hydrogel-based

microfluidic device. Our findings reveal enhanced chemotactic performance in the

presence of sidewalls compared to their absence. Cells in the middle area (MA)

exhibited no drift and did not contribute to overall chemotaxis. However, cells near the

left sidewall (LSW) and right sidewall (RSW) demonstrated negative and positive drift,

respectively, with the positive drift velocity from the RSW exceeding the negative drift

velocity from the LSW.

Furthermore, by comparing lanes of different widths within the same stable linear

gradient field, we observed that cells exhibited the highest drift velocity in 8 μm-wide

lanes, which approximates the peak value in the distribution of circular swimming radii

on surfaces. This optimal width for maximal chemotaxis resulted from the largest

percentage of cells occupying the right sidewalls. Stochastic simulations of bacterial

chemotaxis corroborated that the optimized lane width varies with the bacteria's circular

swimming radius. Our findings have important implications for the screening of

swimming organisms and the study of chemotactic behavior in real-world scenarios.

Results

Chemotaxis of *E. coli* within lane confinements

To study bacterial chemotaxis in confined environments such as tubes or interstitial

tissues, we developed a hydrogel-based microfluidic device featuring lanes of different

widths. The device design, illustrated in Fig. 1A, incorporates two 2% (w/v) agarose

walls inserted between three main channels: a sink channel, a cell channel, and a source

channel. These walls prevent cell passage while allowing chemical diffusion. The

agarose walls and main channels measure 100 μm and 400 μm in width, respectively,

with the device having a depth of 30 μm.

We established a linear concentration gradient (0.05 μM/μm) of L-aspartate, an

attractant sensed by the Tar receptor, by flowing motility medium through the sink

channel and 50 μM L-aspartate solution (prepared in motility medium) through the

source channel at a constant rate of 10 μL/min. The resulting gradient across the cell

channel is depicted in Fig. S1.

The lanes of various widths were created using parallel PDMS (polydimethylsiloxane)

pillars spaced at different distances. Each lane, approximately 160 μm in length, is

highlighted by a yellow rectangular box in Fig. 1A. *E. coli* cells, confined to the cell

channel, sensed the attractant gradient and performed chemotaxis within these lanes of

different widths.

To enhance imaging contrast, we introduced a plasmid expressing mCherry fluorescent

protein (pTrc99a-mcherry) into wild-type *Escherichia coli* HCB1, denoting it as HCB1-

pTrc99a-mcherry. A high-sensitivity CMOS camera was used to record bacterial

movement trajectories on the bottom surfaces of the lanes in the cell channel, where

most cells accumulate due to the combined effects of gravity and hydrodynamic wall

attraction in the Percoll-free medium.

We recorded the movement of HCB1-pTrc99a-mcherry cells on the liquid-glass surface

of a 44-μm-wide lane with and without a L-aspartate concentration gradient,

respectively. An example video is shown in Movie S1, and several representative

trajectories are illustrated in Fig. 1B.

Considering the potential escape into the third dimension at the edge (26), we calculated

the drift velocities v_d of the trajectories from both assays along the *x*-direction (up-

gradient) by fitting the relation $\langle x(i+n) - x(i) \rangle \sim n\Delta t$ (*n*=1, 3, 5, …, 39) with a linear

function, the slope of which is the drift velocity. Here, $x(i)$ represents the cell's *x*-

position in the *i*-th frame, and Δt denotes the time interval between two frames (0.05

s). This method yields a drift velocity that is independent of potential cell loss into the

third dimension. As shown in Fig. 1C, the drift velocity v_d was 1.6$\pm$0.3 μm/s and 0.2

$\pm$0.2 μm/s (mean$\pm$SD) for the gradient and control (no-gradient) assays, respectively.

Thus, bacteria in the L-aspartate gradient exhibited obvious chemotaxis on the lane

surfaces, contrasting with previous findings on liquid-solid surfaces without sidewalls

(40).

The cells in the right sidewall region dominated the chemotaxis of *E. coli* within

lane confinements.

To elucidate the mechanism of bacterial chemotaxis within lane confinements, we

analyzed cell trajectories, identifying three distinct motion states due to the presence of

sidewalls. As illustrated in Fig. 2A, cells exhibited straight-line swimming along

sidewalls, movement towards or away from sidewalls, or circular swimming. Fig. 2B

displays three representative trajectories. Circular swimming is characteristic of typical

E. coli surface motion (8). We further analyzed the trajectories of bacteria colliding with

the sidewalls. As shown in Fig. S2, cells colliding with the sidewalls tend to align with

and swim along the sidewalls, and the alignment timescale is negligible compared to

the typical wall residence time (6).

We distinguished these motion states by calculating the rotational exponent (γ_R) for

each trajectory, fitting the mean-squared orientational displacement ⟨MSOD⟩ for

$\tau < 0.4\,\text{s}$:

$$\langle \text{MSOD} \rangle = \langle \left(\theta(t+\tau) - \theta(t) \right)^2 \rangle = C_R \tau^{\gamma_R} \, ,$$

where $\theta(t)$ is the angle between the swimming direction and the positive *x*-axis

direction at time *t*, τ is the lag time, C_R is a constant, and γ_R is the rotational

exponent. Fig. 2C shows the γ_R values for the three trajectories in Fig. 2B, while Fig.

2D illustrates the relationship between γ_R and average *y*-coordinate. Trajectories

further from sidewalls exhibit larger γ_R, indicating more curved paths, while γ_R

decreases sharply as the cells approach sidewalls, representing straighter trajectories.

We also analyzed tumble kinematics for cells swimming along and away from sidewalls.

Fig. 2E and 2F show normalized tumble angle distributions for cells in sidewalls (SW)

and middle areas (MA), respectively. Red solid lines represent exponential function fits

$y = a * \exp(x/b)$, with fitted *b* values of $0.25\,\text{rad}$ (SW) and $1.35\,\text{rad}$ (MA). Consistent

with previous reports (41), we observed a higher occurrence of large reorientation

angles for surface-swimming cells in the MA region (Fig. 2F). Interestingly, we also

found large tumble angles in the SW region, albeit with a smaller characteristic angle

than in the MA region. Movie S2 demonstrates an example of a large reorientation angle

during tumbling.

Given the strong spatial dependence of trajectory characteristics, we classified the cells

into three distinct populations. The distribution of cells along the *y*-axis is shown in Fig.

2G. Based on mean distances from the sidewalls, we divided the lane into three areas

(viewing along the positive *x*-axis): the left sidewall (LSW), the middle area (MA), and

the right sidewall (RSW). As shown by different shaded colors in Fig. 2D and 2G, we

defined cells in LSW, RSW and MA for trajectories with $\langle x \rangle \leq d$, $\langle x \rangle \geq w - d$, and

$d < \langle x \rangle < w - d$, respectively. The threshold d was set at 3 μm (approximately the

average length of a cell body), and w represents the lane width. The proportion of

trajectories in different regions is shown in Fig. 2I. For the gradient assay, the

probabilities of trajectories being in LSW, MA and RSW regions were 0.20 ± 0.01, 0.59

± 0.02, and 0.21 ± 0.03, respectively. In the control assay without gradient, these values

were 0.18 ± 0.03, 0.70 ± 0.03, and 0.12 ± 0.01, respectively.

We then compared the drift velocity of cells in the three areas separately for both

gradient and control assays. As shown in Fig. 2H, cells in the LSW region tended to

display a negative drift with $v_d^{LSW} = $ -5.7±2.1 μm/s and -5.0 ± 2.0μm/s for gradient and

control assays, respectively. Cells in the MA region exhibited minimal drift with $v_d^{MA} = $

-0.3 ± 1.2 μm/s and 0.4 ± 0.6 μm/s for gradient and control assays, respectively. Cells

in the RSW region displayed a typical positive drift with $v_d^{RSW} = $ 14.8 ± 1.2 μm/s and

6.2 ± 1.9 μm/s for gradient and control assays, respectively. Thus, cells in the RSW

region dominated the difference in drift velocity between the two assays.

In summary, cells swim on the right-hand side under the effect of the bottom surface of

lanes (9). The LSW and RSW cells swim down and up the gradient, respectively, while

MA cells swim in circles without any drift. RSW cells demonstrated more persistent

swimming towards the attractant in the L-aspartate gradient, exhibiting a higher

positive drift velocity. Detailed information on the difference in drift velocity between

LSW and RSW cells can be found in the supplemental materials. Notably, the attractant

gradient minimally affects the ratio of bacteria in different regions.

The dependence of chemotactic performance on lane width

Having established that *E. coli* chemotaxis on lane surfaces is closely related to sidewall confinement, we investigated chemotaxis in lanes of different widths to mimic bacterial chemotactic behavior in interstitial tissues or tubes of varying sizes. We compared five lanes with widths of 6 μm, 8 μm, 10 μm, 25 μm, and 44 μm. Drift velocity was calculated using the same method as in Fig. 1C, with results shown in Fig. 3A. The mean drift velocities were 1.8 ± 1.3 μm/s, 7.5 ± 1.4 μm/s, 4.6 ± 1.7 μm/s, 2.5 ± 0.5 μm/s, and 2.6 ± 0.4 μm/s for lanes of width 6 μm, 8 μm, 10 μm, 25 μm, and 44 μm, respectively. Bacteria exhibited optimal chemotaxis (highest drift velocity) in lanes that were 8 μm wide. To rule out any potential ratchet effect caused by the asymmetric entrances, we performed control measurements using a setup with straight entrances; these results confirmed our findings and are shown in Fig. S3.

Noting that this optimal width is of the same order of magnitude as the radius of bacterial circular swimming on a solid surface, we measured the radius of circular swimming for cells in the MA region. As shown in Fig. 3B, the peak radius in the distribution of circular swimming radii is ~10 μm, which is close to the lane width supporting optimal chemotaxis.

It has been reported that bacteria swimming in capillaries of different radii possess different swimming speeds (42). Therefore, we calculated the cell swimming speeds for all lane widths. As shown in Fig. 3C, swimming speed remains relatively constant across different lane widths. This indicates that the optimized chemotaxis is not a result of varying swimming speeds.

The optimal chemotaxis resulted from more cells moving towards the attractant along the right sidewall.

To identify the underlying mechanism of optimal lane width for chemotaxis, we evaluated the drift velocity for cells in the LSW, MA, and RSW regions separately. The results are shown in Fig. 4A. Cells in the MA region did not exhibit effective drift, while LSW and RSW cells demonstrated negative and positive drift, respectively, consistent

with the findings in Fig. 2H. The drift velocity for RSW cells increased with lane width,

and remained relatively constant above a lane width of 8 μm, thus not exhibiting a

highest value in the 8 μm-wide lanes. Therefore, the width-dependent optimal

chemotaxis is not attributable to an optimal drift velocity for RSW cells.

We then sought a comparison of cell proportions in the three areas, as plotted in Fig.

4B. The proportion of cells in the MA region increased gradually with lane width due

to the increase in area. Notably, the largest proportion of RSW cells appears in the 8

μm-wide lane. In other words, the lane width-dependent optimal chemotaxis primarily

resulted from changes in cell numbers on the sidewalls. The relation between cell

enrichment and lanes' width was plotted in Fig. S4.

To further investigate changes in up- and down-gradient cell numbers in the RSW

region, we calculated the proportion of RSW-UG (cells swimming up-gradient in the

RSW) and RSW-DG (cells swimming down-gradient in the RSW) cells. As shown in

Fig. 4C, more cells moved towards the attractant in the 8 μm-wide lane. Thus, the

optimal chemotaxis in the 8 μm-wide lane resulted from a higher number of cells

moving towards the attractant along the right sidewall.

Simulation of *E. coli* chemotaxis within lane confinements

To explore the relationship between the circular swimming of bacteria on lane surfaces

and optimal chemotaxis, we simulated two-dimensional chemotaxis of bacteria with

varying circular swimming radii on lanes of different widths in a steady linear gradient

of L-aspartate.

In our simulation, cells were treated as self-propelled particles performing a random

walk in a run-and-tumble mode within a two-dimensional space. Cells could be in either

a run or tumble state, determined by the intracellular chemotaxis signal. During a run,

cells swam smoothly at a constant speed of v_0=20 μm/s. The effect of the bottom

surface on bacterial swimming was modeled by adding a constant angular velocity term

to the swimming direction:

$$\theta(t + \Delta t) = \theta(t) + \left(-\frac{v_0}{r}\right)\Delta t + \sqrt{2D_r\Delta t}\, n(0,1)$$

where θ denotes the angle between the swimming direction and the positive x-axis, Δt

is the time step, r is the radius of circular swim, D_r is the rotational diffusion

coefficient, and $n(0, 1)$ represents a random number drawn from a standard normal

distribution. When cells collided with sidewalls, their velocities instantly aligned with

the sidewall (43), and could potentially leave the sidewall after their next tumble.

During a tumble, cells stopped moving, and their swimming direction changed. The

change in θ was selected from the distribution of tumble angles observed in Fig. 2E and

F for different areas.

Initially, 100 cells were evenly distributed on the surface of a lane measuring 160 μm

in length and w in width. A linear concentration gradient of L-aspartate, identical to the

experimental conditions, was established along the x-axis according to:

$$c(x) = 0.05x + 22,$$

with the concentration c in μM and the position x in μm. The simulation for each set of

parameters ran for 150 s with a timestep of 0.05 s and was repeated 50 times.

Figure 5A illustrates the relationship between chemotactic drift velocity and lane width

for cells with a 10 μm-radius circular swim. The highest drift velocity was observed at

a lane width of 8 μm. Figure 5B shows the proportions of cells in the three regions

(LSW, MA, RSW) for different lane widths, presenting profiles similar to those

observed experimentally in Fig. 4B. The drift velocity for 3 regions was shown in Fig.

S5. Results for different swimming radii are presented in Fig. 5C, demonstrating that

the optimal lane width for chemotaxis is closely related to the radius of circular

swimming. It is important to note that our model treats bacteria as active particles and

does not explicitly account for the steric exclusion of the flagella and cell body. In

reality, these effects would restrict the cells' ability to turn freely in narrow lanes (≤ 6

μm), thereby reducing the cell density mismatch between the LSW and RSW and

decreasing the drift velocity compared to the simulation.

As shown in Fig. 5D, the relationship between optimal lane width (w) and circular

swimming radius (r) was fitted with a linear function $w = kr$, with $k = 0.66 \pm 0.03$. This

indicates a clear proportional relationship between the lane width for optimal

chemotaxis and the circular swimming radius of bacteria.

Geometrical analysis of optimal lane width for chemotaxis.

We have established that the optimal lane width for chemotaxis (8 μm) primarily results

from a higher proportion of cells in the RSW region swimming up-gradient.

Additionally, this optimal width is directly proportional to the circular swimming radius

of the bacteria. To further elucidate the underlying mechanism of this phenomenon, we

employed geometrical analysis.

We assumed an initial uniform distribution of cells across the lane width. As shown in

Fig. 6A-C, we divide the width of the lane into three scenarios:

1. $0 < w \leq r$: For a cell at any point P in the channel, its swimming direction can be

arbitrary. However, only cells swimming in directions between θ_1 and θ_2

(highlighted in green) can swim up-gradient in the RSW after their first collision with

the sidewall. The proportion of these cells can be calculated as:

334
$$\frac{1}{w} \int_0^w \frac{\theta_1 + \theta_2}{2\pi} dy = \frac{1}{2\pi w} \int_0^w dy \left(\text{acos} \frac{r - w + y}{r} + \text{acos} \frac{y}{r} \right)$$

335
$$= \frac{1}{2\pi m} \left[-(1 - m) \, \text{acos}(1 - m) + \sqrt{1 - (1 - m)^2} + m \, \text{acos} \, m \right.$$

336
$$\left. - \sqrt{1 - m^2} + 1 \right],$$

337 where $m = w/r \leq 1$.

339 2. $r < w \leq 2r$: Only the cells in the region $y < r$ and with velocity direction

340 between θ_1 and θ_2 can swim up-gradient in the RSW after their first collision

341 with the sidewall. The proportion of cells in this region is:

342
$$\frac{1}{w}\int_0^r \frac{\theta_1 + \theta_2}{2\pi}\,dy = \frac{1}{2\pi w}\int_0^r dy\left(2\arccos\frac{y}{r}\right) = \frac{1}{\pi m}$$

344   3. $w > 2r$: The proportion of cells that can swim up-gradient in the RSW is calculated

345   the same as in case 2:

346
$$\frac{1}{w}\int_0^r \frac{\theta_1 + \theta_2}{2\pi}\,dy = \frac{1}{\pi m}$$

The complete relationship between the proportion of cells that can swim up-gradient in

the RSW (P) and m is plotted in Fig. 6D. The maximum P occurs when $m \in (0.7, 0.8)$,

marked by the red shaded area. This value is consistent with the slope k in Fig. 5D and

results in the optimal width of about 8 μm in Fig. 3A for a circular swimming radius of

10 μm.

Crucially, the observed asymmetry arises because the angular ranges that geometrically

facilitate RSW-UG accumulation (Fig. 6A-C) coincide with the up-gradient direction.

Because cells moving up-gradient experience suppressed tumbling, they can maintain

the steady circular trajectories required to reach and align with the RSW. Conversely,

while a pure geometric analysis suggests a symmetric potential for LSW-DG

accumulation, these trajectories coincide with the down-gradient direction.

Consequently, these cells experience enhanced tumbling, which distorts the circular

trajectories. This prevents them from effectively reaching the LSW and also increases

the probability of them leaving the wall.

Discussions

Bacterial behavior in confined environments differs significantly from that in free

environments. Previous studies have reported that cells tend to swim in circles and

accumulate near a solid-liquid interface, leading to diminished chemotaxis. However,

recent research on chemotaxis of swarm cells suggests that crowded environments may

enhance bacterial chemotaxis on surfaces. In this study, we examined the chemotaxis

of *E. coli* on the bottom surface of microfluidic lanes, which simulate the spatial

constraints imposed by neighboring cells in a swarm, exploring the effects of lane confinement on bacterial chemotaxis.

We found that in the presence of sidewalls, cells that would otherwise have been unable to exhibit chemotaxis showed significant chemotactic behavior in a linear gradient of L-aspartate. Cells in different regions of the lanes demonstrated distinct motion behaviors. In the MA region, cells showed no drift, similar to observations in chemotaxis near surfaces. Conversely, cells exhibited positive and negative drift when in the RSW and LSW regions, respectively.

Further investigation into chemotaxis in lanes of varying widths demonstrated that cells exhibited the highest chemotactic drift velocity in lanes that were 8 μm wide. This width is close to the radius of bacterial swimming circles. By analyzing the proportion and drift velocity of cells in different regions, we determined that this optimal lane width was primarily due to the higher proportion of cells swimming up-gradient along the right sidewall.

To explore the relationship between chemotactic drift velocity and circular swimming radius of bacteria, we conducted systematic simulations of *E. coli* chemotaxis with different circular swimming radii in lanes of varying widths under a linear concentration gradient of L-aspartate. These simulations explicitly incorporated the clockwise circular motion of surface-swimming bacteria and the alignment effect induced by sidewall collisions. We found that optimal chemotaxis occurred when the swimming radius was close to the lane width, with $w = 0.66r$. This suggests a significant proportional relationship between the optimal lane width for chemotaxis and the circular swimming radius of bacteria.

To elucidate the mechanism underlying this phenomenon, we employed geometric analysis. We demonstrated that bacteria in lanes could swim up-gradient in the RSW with maximal probability when the lane width was 0.7-0.8 times the radius of circular

swimming. This finding is consistent with the experimental results presented in Fig. 4C.

Our findings have important implications for the screening of single-celled swimming organisms and the study of restricted chemotactic behavior. This research provides insights into how confinement affects bacterial chemotaxis and may inform the design of microfluidic devices for bacterial manipulation and analysis.

Bacteria frequently inhabit confined spaces such as soil pores, sediment interstices, rock crevices, biological tissues, and hydrogels. In these constrained environments, bacterial behavior often deviates significantly from that observed in unconfined conditions, typically resulting in reduced chemotactic ability. However, our findings challenge this notion, suggesting that certain types of environmental confinement may actually enhance bacterial chemotaxis. This discovery could contribute to our understanding of microbial ecology across various habitats, including soil, oceans, and the human body.

Furthermore, these insights could have potential applications. In biotechnology, optimizing confinement conditions could improve the efficiency of bioremediation processes or the production of microbial products. In medicine, understanding how pathogens navigate confined spaces within the body could lead to novel strategies for preventing or treating infections.

Materials and methods

Strain and plasmids

The plasmid pTrc99a-mCherry expresses mCherry under an IPTG-inducible promoter. The wild-type *E. coli* K12 strain AW405 (HCB1) transformed with pTrc99a-mCherry was used for fluorescent tracking of cell trajectories. Cells were streaked on a Petri dish containing 1.5% agar and lysogeny broth (1% tryptone, 0.5% NaCl, 0.5% yeast extract, supplemented with the appropriate antibiotic: 100 μg/ml ampicillin). A single colony was inoculated into lysogeny broth and grown overnight at 33 °C with 200 rpm rotation.

The saturated culture was then diluted 1:100 (100 μl in 10 ml) into tryptone broth (1%

tryptone, 0.5% NaCl, supplemented with the appropriate inducer and antibiotic: 0.1

mM IPTG, 100 μg/ml ampicillin) and grown at 33 °C with 200 rpm rotation to

OD_{600}=0.53. Cells were then harvested from culture media by centrifugation at 1.2×g

for 6 min at room temperature. The pellet was resuspended by gently mixing in motility

medium (10 mM potassium phosphate, 0.1 mM ethylenediaminetetraacetic acid

(EDTA), 10 mM lactic acid, and 1 μM methionine at pH 7.0). The cells were washed

three times to replace growth medium with motility medium. One hour after

fluorescence maturation in a 33°C incubator, cells were placed in a 4°C refrigerator

ready for microfluidic experiments.

Microfluidic device design and fabrication

A hydrogel-based microfluidic device containing lanes of different width was designed

using L-edit based on previous work (42). The silicon mold with the positive relief

features was fabricated using the standard soft lithography technique performed in our

laboratory. Firstly, a 4-inch diameter silicon wafer was spin washed sequentially using

water, acetone, methanol and isopropanol. The wafer was thoroughly dried on a 150 °C

hot plate to ensure that organics has volatilized completely. Then, the wafer was treated

with air plasma (Harrick plasma, PDC-002, 30W) for 10 min before the SU-8 2025

photoresist (Microchem) was spin-coated according to the products protocols. The spin-

coated wafer was placed on a hot plate at 65°C for 3 min followed by 6 min at 95°C,

then exposed to UV light using a maskless lithography machine (Heidelberg, μMLA)

at 800 mJ/cm^2 with defocus was set to 0. The post-exposure bake was performed at 65°C

for 2 min followed by 6 min at 95°C. Development procedure lasted about 6 minutes

with constant shaking in the SU-8 developer. The wafer was rinsed with fresh developer

followed by isopropanol. Finally, an approximately 30-μm-high photoresist layer was

created as the master mold. The mold was fixed on a glass petri dish using double-sided

tape.

Polydimethylsiloxane (PDMS) and curing agent was mixed with a 10:1 ratio (Sylgard

184, Dow Corning) and centrifuged at 3500 rpm for 5 min to remove air bubbles. The mixture was poured over the mold in glass petri dish and then placed at 4°C for an hour to avoid interference from very small air bubbles. The PDMS was cured at 80°C for 3 h, then separated from the wafer and cut into pieces, and holes were punched for inlets and outlets. The punched PDMS was cleaned with adhesive tape. The cleaned PDMS was bonded to a glass slide after air plasma treatment (Harrick plasma, PDC-002, 30W). The fabricated device was baked at 80°C overnight to establish covalent bonding.

The hydrogel agarose was used at 2% (w/v) concentration in motility medium to create diffusion-permeable walls. Agarose was slowly injected through the inlet port using a syringe pump at a constant flow rate of 2 μL/min, and the injection process was carried out in a drying oven at a constant temperature of 68 °C.

Microscopy and data acquisition

The PDMS microfluidic chip was placed on a Nikon Ti-E inverted optical microscope equipped with a specific filter set, a 20× objective (Nikon, CFI S Plan Fluor ELWD, 20×, NA 0.45), and a CMOS camera (Hamamatsu, ORCA-Flash4.0, pixel size = 6.5 μm). We set the objective lens's correction collar to 1.2 mm to match the glass slide thickness. A halogen lamp serves as the bright-field light source to help locate the observation area, while a xenon lamp serves as the excitation light source for fluorescence experiments. The depth of field is 3.7 μm.

1) Gradient profile calibration

Fluorescein solution (Sigma) was used for visualizing the chemical concentration field in the microfluidic device. 100 μM fluorescein and motility medium were flowed into the source and sink channels respectively, at a constant flow rate of 10 μL/min. One fluorescent image was captured per minute. To avoid the impact of photobleaching on the results, we only illuminated the sample during the imaging process.

2) Chemotaxis assays

The aspartic acid and motility medium solutions were respectively introduced into the

source and sink channels, and left for more than 1 hour to allow aspartic acid to diffuse through the agarose wall and form a stable concentration gradient field. Then, bacteria were introduced into the cell channel at a rate of 5 μL/min using a syringe pump for a duration of 90 seconds. After the bacteria injection was complete, the microvalves were closed to seal the cell channel. Bacteria then performed chemotaxis due to the perception of the concentration gradient field. After waiting for 2 minutes, the shutter was opened to illuminate the fluorescent bacteria with the excitation light, and video recording began. During the video acquisition process, fluorescence excitation light was continuously illuminated onto the bacteria. For each recording, 9600 frames (2048×2048 pixels) were captured at a frame rate of 20 fps and an exposure of 50 ms. Although the long-term illumination caused a decrease in the brightness of the fluorescent bacteria, the position information of the bacteria could still be accurately distinguished within the video duration (8 min).

Data analysis

Tracking. Image analysis was performed with the ImageJ (National Institutes of Health) TrackMate plugin. We chose the Log detector with an estimated blob diameter of 70 μm and a threshold of 800 μm to effectively recognize bacteria, based on the diameter of bacteria and the use of a 20× objective. Then, we used the LAP Tracker and set the maximum distance for frame-to-frame linking to 50 μm.

Swimming speed. The velocity is calculated using the fourth order central difference method by (44):

$$\vec{v}_i = \frac{8(\vec{x}_{i+1} - \vec{x}_{i-1}) - (\vec{x}_{i+2} - \vec{x}_{i-2})}{12T}$$

The magnitude of the velocity is given by $v_i = |\vec{v}_i|$. The speed of each trajectory is defined as the average of v_i. The swimming speeds of bacteria in lanes of different widths are represented by the mean and standard deviation of all trajectories.

Calculation of the radius of circular motion on the solid surface. A total of 382

trajectories with a rotational exponent greater than 1.6 in the MA region of the $w = 44$

μm lanes were selected for analysis. The trajectories were smoothed using the Savitzky-

Golay filter with a window size of 5. The least squares method was then applied to

solve the linear equations, yielding the center and radius of the fitted circles. The

principle of this process is briefly described as follows:

The standard equation of a circle can be written as:

$$(x - a)^2 + (y - b)^2 = r^2,$$

527 where (a, b) are the coordinates of the circle's center, and r is the radius. Expanding

528 and rearranging the standard equation of a circle, it can be rewritten as:

$$x^2 + y^2 = 2ax + 2by + c,$$

530 where $c = r^2 - a^2 - b^2$.

532 Rewriting the above equation in matrix form, we have:

$$B = A \cdot Coefficients$$

534 where

$$B = x^2 + y^2 = \begin{bmatrix} x_1^2 + y_1^2 \\ x_2^2 + y_2^2 \\ \vdots \\ x_n^2 + y_n^2 \end{bmatrix}$$

536 is the response vector, and

$$A = [x \quad y \quad 1] = \begin{bmatrix} x_1 & y_1 & 1 \\ x_2 & y_2 & 1 \\ \vdots & \vdots & \vdots \\ x_n & y_n & 1 \end{bmatrix}$$

538 is the design matrix. The coefficients are given by:

$$Coefficients = \begin{bmatrix} 2a \\ 2b \\ c \end{bmatrix} = (A^T A)^{-1}(A^T B).$$

Tumble angle. A tumble is defined as points where the velocity is lower than the

average velocity of the trajectory $\langle v_i \rangle$ and shows a substantial drop from the previous

time point. Specifically, a tumble is identified when:

$$\{v_{t1}, \cdots, v_{tn}\} < \langle v_i \rangle,$$

$$\{v_{t0} - v_{t1}, \ldots, v_{tn-1} - v_{tn}\} > \langle v_i \rangle \cdot \alpha,$$

where $n \geq 2$, $\alpha = 1/6$ is the threshold, and t_1 and t_n represent the start and end

times of a tumble, respectively.

Simulation of bacterial chemotaxis within lanes.

In our simulation, we introduced the effects of bottom surface and sidewalls into the 2-

dimensional chemotaxis of *E. coli*. The simulations were carried out in a rectangular

area of size 160 μm × w, where w denotes the lane width. Cells were treated as self-

propelled particles. They could sense and adapt to the ligand in the surrounding

environment via the intracellular chemotaxis signaling pathway, which could be

described by a coarse-grained model of bacterial chemotaxis (45, 46):

$$a = \frac{1}{1 + \exp\left(N\left(\alpha(m - m_0) + \ln\frac{1 + \frac{c}{K_{off}}}{1 + \frac{c}{K_{on}}}\right)\right)},$$

$$\frac{dm}{dt} = k_R(1 - a) - k_B a,$$

where a, m, and c represent the activity of the receptor-kinase complex, the

methylation level of receptors, and the ligand concentration, respectively. N denotes the

number of chemoreceptors in a Monod-Wyman-Changeux cluster (47). The values of

parameters we used were the same as before (4, 47, 48): $N = 4.6$, $K_{off} =$

1.7 μM, $K_{on} = 12$ μM, $\alpha = 1.7$, $m_0 = 1.0$, $k_R = 0.005 \text{ s}^{-1}$, $k_B = 0.010 \text{ s}^{-1}$.

The concentration of CheY-P, which changes due to the receptor-kinase

phosphorylation on CheY, could be calculated by $Yp = 7.86a$. Consequently, the CW

bias (B) of flagellar motors would also vary (49):

$$B = \frac{(Yp)^{10.3}}{(Yp)^{10.3} + 3.1^{10.3}}.$$

It has been reported that the average run time in the near-surface region for wildtype

cells is ~2.0 s (corresponding to a run-to-tumble rate of ~0.5 s^{-1}) (11), and the steady-

state motor CW bias is ~0.15 without a gradient. The run-to-tumble rate k was set to be

equivalent to the motor CCW-to-CW switching rate. As this rate increases linearly with

motor bias B (50), it was calculated using $k = \frac{B}{0.31}$ s^{-1}. The switching rate from tumble

to run was 5 s^{-1} due to the constant tumble duration of 0.2 s (51).

In this way, the motion states of each cell at any moment are determined. During a run,

cells swim smoothly with a constant speed of 20 μm/s, influenced by rotational

diffusion and the effect of the bottom surface on bacterial swimming:

$$\theta(t + \Delta t) - \theta(t) = \left(-\frac{v_0}{r}\right)\Delta t + n(0, 2D_r\Delta t),$$

$$x(t + \Delta t) - x(t) = v_0 \cos\theta\, \Delta t,$$

$$y(t + \Delta t) - y(t) = v_0 \sin\theta\, \Delta t,$$

where θ is the angle between the swimming direction and the positive x-axis, $v_0 =$

20 μm/s is the swimming speed, r is the radius of circular swimming due to the

effect of the bottom surface, and $n(0, 2D_r\Delta t)$ represents a normal distribution with

zero mean and variance $2D_r\Delta t$. The rotational diffusion coefficient was 0.062 rad^2/s

(52). During a tumble, cells stop swimming and a tumble angle is selected from the

distribution that we measured (Fig. 2E). We also imposed a maximum detention time

limit which, when combined with the variable tumble rate, results in an average wall

residence time of approximately 2 s, matching our experimental observations (Fig.

S6B). Cells will get a random y-coordinate at the other side when they swim through

the x boundary.

References

1. S. S. Suarez, A. A. Pacey, Sperm transport in the female reproductive tract. *Hum. Reprod.*
Update **12**, 23-37 (2005).

2. D. Bray, *Cell Movements: From Molecules to Motility* (Routledge, 1992).

3. S. Geisel, E. Secchi, J. Vermant, The role of surface adhesion on the macroscopic wrinkling of
biofilms. *eLife* **11** (2022).

4. M. Tian, C. Zhang, R. Zhang, J. Yuan, Collective motion enhances chemotaxis in a two-
dimensional bacterial swarm. *Biophys J* **120**, 1615-1624 (2021).

5. A. P. Berke, L. Turner, H. C. Berg, E. Lauga, Hydrodynamic attraction of swimming
microorganisms by surfaces. *Phys. Rev. Lett.* **101**, 038102 (2008).

6. G. Li, J. X. Tang, Accumulation of microswimmers near a surface mediated by collision and

603   rotational brownian motion. *Phys. Rev. Lett.* **103**, 078101 (2009).

604   7.   M. Michael, H. Athena, L. Guanglai, R. M. Martin , X. T. Jay Molecular Adsorption Steers
605   Bacterial Swimming at the Air/Water Interface. *Biophys J* **105**, 21-28 (2013).

606   8.   L. Eric, R. D. Willow, M. W. George, A. S. Howard, Swimming in Circles: Motion of Bacteria near
607   Solid Boundaries. *Biophys J* **90**, 400-412 (2006).

608   9.   W. R. DiLuzio *et al.*, *Escherichia coli* swim on the right-hand side. *Nature* **435**, 1271-1274 (2005).

609   10.   G. Junot *et al.*, Run-to-Tumble Variability Controls the Surface Residence Times of *E. coli*
610   Bacteria. *Phys. Rev. Lett.* **128**, 248101 (2022).

611   11.   M. Molaei, M. Barry, R. Stocker, J. Sheng, Failed escape: solid surfaces prevent tumbling of
612   *Escherichia coli*. *Phys. Rev. Lett.* **113**, 068103 (2014).

613   12.   G. Araujo, W. Chen, S. Mani, J. X. Tang, Orbiting of Flagellated Bacteria within a Thin Fluid Film
614   around Micrometer-Sized Particles. *Biophys J* **117**, 346-354 (2019).

615   13.   T. Bhattacharjee, S. S. Datta, Bacterial hopping and trapping in porous media. *Nat. Commun.*
616   **10**, 2075 (2019).

617   14.   T. Bhattacharjee, S. S. Datta, Confinement and activity regulate bacterial motion in porous
618   media. *Soft Matter* **15**, 9920-9930 (2019).

619   15.   Nicholas A. Licata, B. Mohari, C. Fuqua, S. Setayeshgar, Diffusion of Bacterial Cells in Porous
620   Media. *Biophys J* **110**, 247-257 (2016).

621   16.   D. Shrestha *et al.*, Bacterial mobility and motility in porous media mimicked by microspheres.
622   *Colloids Surf. B* **222**, 113128 (2023).

623   17.   N. Figueroa-Morales *et al.*, *E. coli* "super-contaminates" narrow ducts fostered by broad run-
624   time distribution. *Sci. Adv.* **6**, eaay0155 (2020).

625   18.   H. Wioland, E. Lushi, R. E. Goldstein, Directed collective motion of bacteria under channel
626   confinement. *New J. Phys.* **18**, 075002 (2016).

627   19.   V. Tokárová *et al.*, Patterns of bacterial motility in microfluidics-confining environments. *Proc.*
628   *Natl. Acad. Sci. U.S.A* **118**, e2013925118 (2021).

629   20.   P. C. Mushenheim, R. R. Trivedi, H. H. Tuson, D. B. Weibel, N. L. Abbott, Dynamic self-assembly
630   of motile bacteria in liquid crystals. *Soft Matter* **10**, 88-95 (2014).

631   21.   C. J. Woolverton, E. E. Gustely, L. Li, O. D. Lavrentovich, Liquid crystal effects on bacterial
632   viability. *Liq. Cryst.* **32**, 417 - 423 (2005).

633   22.   X. Chen, R. Zhang, J. Yuan, Vertical confinement enhances surface exploration in bacterial
634   twitching motility. *Environ. Micriobiol.* **26**, e16679 (2024).

635   23.   J. Männik, R. Driessen, P. Galajda, J. E. Keymer, C. Dekker, Bacterial growth and motility in sub-
636   micron constrictions. *Proc. Natl. Acad. Sci. U.S.A* **106**, 14861-14866 (2009).

637   24.   B. L. Jonathan *et al.*, Transitioning to confined spaces impacts bacterial swimming and escape
638   response. *Biophys J* **121**, 2653-2662 (2022).

639   25.   G. Vizsnyiczai *et al.*, A transition to stable one-dimensional swimming enhances E. coli motility
640   through narrow channels. *Nat. Commun.* **11**, 2340 (2020).

641   26.   N. Figueroa-Morales *et al.*, Living on the edge: transfer and traffic of E. coli in a confined flow.
642   *Soft Matter* **11**, 6284-6293 (2015).

643   27.   G. L. Hazelbauer, J. J. Falke, J. S. Parkinson, Bacterial chemoreceptors: high-performance
644   signaling in networked arrays. *Trends Biochem. Sci.* **33**, 9-19 (2008).

645   28.   V. Sourjik, Receptor clustering and signal processing in E. coli chemotaxis. *Trends Microbiol.* **12**,
646   569-576 (2004).

29. A. I. M. Salah Ud-Din, A. Roujeinikova, Methyl-accepting chemotaxis proteins: a core sensing
element in prokaryotes and archaea. *Cell. Mol. Life Sci.* **74**, 3293-3303 (2017).

30. J. J. Falke, G. L. Hazelbauer, Transmembrane signaling in bacterial chemoreceptors. *Trends*
Biochem. Sci. **26**, 257-265 (2001).

31. A. Bren, M. Eisenbach, How Signals Are Heard during Bacterial Chemotaxis: Protein-Protein
Interactions in Sensory Signal Propagation. *J. Bacteriol.* **182**, 6865-6873 (2000).

32. M. K. Sarkar, K. Paul, D. Blair, Chemotaxis signaling protein CheY binds to the rotor protein FliN
to control the direction of flagellar rotation in *Escherichia coli*. *Proc. Natl. Acad. Sci. U.S.A* **107**,
9370-9375 (2010).

33. G. H. Wadhams, J. P. Armitage, Making sense of it all: bacterial chemotaxis. *Nature reviews.*
Molecular cell biology **5**, 1024-1037 (2004).

34. M. D. Baker, P. M. Wolanin, J. B. Stock, Signal transduction in bacterial chemotaxis. *Bioessays*
28, 9-22 (2006).

35. K. Oosawa, Y. Imae, Demethylation of methyl-accepting chemotaxis proteins in *Escherichia coli*
induced by the repellents glycerol and ethylene glycol. *J. Bacteriol.* **157**, 576-581 (1984).

36. R. M. Weis, S. Chasalow, D. E. Koshland, Jr., The role of methylation in chemotaxis. An
explanation of outstanding anomalies. *The Journal of biological chemistry* **265**, 6817-6826
(1990).

37. M. R. Raza, J. E. George, S. Kumari, M. K. Mitra, D. Paul, Anomalous diffusion of E. coli under
microfluidic confinement and chemical gradient. *Soft Matter* **19**, 6446-6457 (2023).

38. S. Rashid *et al.*, Adjustment in tumbling rates improves bacterial chemotaxis on obstacle-laden
terrains. *Proc. Natl. Acad. Sci. U.S.A* **116**, 11770-11775 (2019).

39. A. Braham *et al.*, Surface conversion of the dynamics of bacteria escaping chemorepellents.
Eur. Phys. J. E **47**, 56 (2024).

40. M. Grognot, K. M. Taute, A multiscale 3D chemotaxis assay reveals bacterial navigation
mechanisms. *Commun. Biol.* **4**, 669 (2021).

41. L. Lemelle *et al.*, Tumble Kinematics of Escherichia coli near a Solid Surface. *Biophys J* **118**,
2400-2410 (2020).

42. L. Ping, V. Wasnik, E. Emberly, Bacterial motion in narrow capillaries. *FEMS Microbiol. Ecol* **91**
2, 1-7 (2015).

43. A. Tao, G. Liu, R. Zhang, J. Yuan, Bacteria Optimize Tumble Bias to Strategically Navigate Surface
Constraints. *Adv. Sci.* **12**, e02063 (2025).

44. L. Turner, L. Ping, M. Neubauer, H. C. Berg, Visualizing Flagella while Tracking Bacteria. *Biophys*
J **111**, 630-639 (2016).

45. L. Jiang, Q. Ouyang, Y. Tu, Quantitative Modeling of *Escherichia coli* Chemotactic Motion in
Environments Varying in Space and Time. *PLoS Comput Biol* **6**, e1000735 (2010).

46. Y. Tu, T. S. Shimizu, H. C. Berg, Modeling the chemotactic response of *Escherichia coli* to time-
varying stimuli. *Proc. Natl. Acad. Sci. U.S.A* **105**, 14855-14860 (2008).

47. N. Vladimirov, L. Løvdok, D. Lebiedz, V. Sourjik, Dependence of bacterial chemotaxis on
gradient shape and adaptation rate. *PLoS Comput Biol* **4**, e1000242 (2008).

48. S. Ren, C. Zhang, R. Zhang, The effect of receptor interaction on the bacterial chemotactic
adaptation rate. *JUSTC* **53**, 0703 (2023).

49. P. Cluzel, M. Surette, S. Leibler, An Ultrasensitive Bacterial Motor Revealed by Monitoring
Signaling Proteins in Single Cells. *Science* **287**, 1652-1655 (2000).

50.   R. He, R. Zhang, J. Yuan, Noise-Induced Increase of Sensitivity in Bacterial Chemotaxis. *Biophys.*
692   *J.* **111**, 430-437 (2016).
693   51.   H. C. Berg, D. A. Brown, Chemotaxis in Escherichia coli analysed by Three-dimensional Tracking.
694   *Nature* **239**, 500-504 (1972).
695   52.   N. Vladimirov, D. Lebiedz, V. Sourjik, Predicted auxiliary navigation mechanism of peritrichously
696   flagellated chemotactic bacteria. *PLoS Comput Biol* **6**, e1000717 (2010).
697
698

Acknowledgements. This work was supported by National Natural Science Foundation of China Grants (12090053, 12474204, and 12104436), Fundamental and Interdisciplinary Disciplines Breakthrough Plan of the Ministry of Education of China (JYB2025XDXM502), University of Science and Technology of China Research Funds of the Double First-Class Initiative (YD2030002501), and a grant from the Ministry of science and technology of China (2019YFA0709303).

Author Contributions. J. Y., R.Z., and C. Z. designed the work. C. Z. and C. Y. performed the experiments. All authors wrote the manuscripts.

Competing financial interests. The authors declare no competing financial interests.

Figure Legends

Fig. 1. **A.** Microfluidic device used in the experiment (top view). **B.** Thirty bacterial trajectories selected from the data of 44-μm-wide lane in gradient assays. These represent a subset of the trajectories analyzed in panel **C**. **C.** The relationship between Δx and nΔt calculated from all trajectories in the lanes with a width of 44 μm. The black dots represent the gradient assay (∇c=0.05 μM/μm) with a total of 3206 tracks from 6 movies, while the gray dots represent no gradient (∇c=0) with a total of 4755 tracks from 10 movies. The light-yellow and light-blue shadows represent the standard error of the mean (SEM) of different trajectories in the gradient assays and the control assays, respectively. Linear fitting was performed to obtain $V_d = 1.6 \pm 0.3$ μm/s (black solid line) and $V_d = 0.2 \pm 0.2$ μm/s (gray solid line) for gradient and control assays respectively. Error in drift velocity represents standard deviation.

Fig. 2. **A.** Schematic drawing of three typical motion states. **B.** Trajectories for three typical motion states. Red dots represent the start of each trajectory. **C.** Calculating the rotational exponent for each trajectory, γ_R, by fitting the mean-squared orientational displacement ⟨MSOD⟩. Dots were experimental data calculated from the tracks in Fig. 2B. Solid lines were fitting results with $\langle \text{MSOD} \rangle = C_R \tau^{\gamma_R}$. The fitted γ_R values are 0, 0.77, and 1.80 for gray, brown, and black tracks, respectively. **D.** Relationship between the rotational exponent γ_R and the mean y position of the bacterial trajectories. Errors denote SEM. Red and purple shaded area represent the region 3 μm from the LSW and RSW, respectively. Green shaded area represents the MA region. **E&F.** Normalized distribution of tumble angle for tracks along the sidewalls (**E**) and in the MA region (**F**). Red solid lines are fitting results with an exponential function: $y = a * \exp (x/b)$. **G.** Distribution of bacteria along the y-axis in the lanes with a width of 44 μm. The shades of different colors denote the same meaning as in Fig. 2D. **H.** Drift velocity of bacterial cells in the three regions. **I.** Proportions of bacterial trajectories in the three regions. Errors are standard deviations (SD).

Fig. 3. **A.** The drift velocity for the experiments in lanes of different widths. The error in drift velocity is the standard deviation. **B.** The distribution of the radius of circular swimming from 382 trajectories in the MA regions. The peak value of the radius is ~10 μm. **C.** The swimming speed of cells in lanes with different widths. The mean swimming speeds and standard deviations for lanes with widths of 6 μm, 8 μm, 10 μm, 15 μm, 25 μm, and 44 μm are 22.7 ± 8.7 μm/s, 25.4 ± 7.7 μm/s, 27.1 ± 7.9 μm/s, 21.9 ± 7.8 μm/s, 22.1 ± 7.7 μm/s, and 22.6 ± 7.5 μm/s, respectively.

Fig. 4. **A.** Mean drift velocities in the LSW, MA, and RSW regions of lanes with different widths. The errors are SD. **B.** The proportion of bacterial cells in the LSW, MA, and RSW regions of lanes with different widths. Errors represent SD. **C.** The proportion of RSW-UG (cells swimming up-gradient in the RSW) and RSW-DG (cells swimming down-gradient in the RSW) for lanes with different widths.

Fig. 5. Simulation of bacterial chemotaxis on the surface of lanes. **A.** The relationship between drift velocity V_d of cells with 10 μm-radius circular swim and the lane width w. Errors denote SEM. **B.** The proportion of bacterial trajectories in the LSW, MA, and RSW regions of lanes with different widths, for cells with 10 μm-radius circular swim. **C.** The drift velocity V_d of cells with different radii of circular swim in lanes of different widths. **D.** The relationship between circular swim radius and lane width for optimal chemotaxis (maximal drift velocity) in Fig. 5C. The widths were extracted by fitting the peak value of w in Fig. 5A with a gaussian function. The red solid line represents a linear fit. The slope is 0.66 ± 0.03. Errors denote SD.

Fig. 6. Geometrical analysis of optimal lane width for chemotaxis. **A.** Case 1: $0 < w \leq r$. **B.** Case 2: $r < w \leq 2r$. **C.** Case 3: $w > 2r$. The red arrows denote the velocity direction. The black solid lines represent the sidewalls. Dashed circles are trajectories. The up-gradient direction is along the positive x-axis. The green shade areas label the swim direction of cells that can swim up-gradient in the RSW. **D.** Relationship between probability (P) of cells swimming up-gradient in the RSW and m, where $m = w/r$. Red

770   shaded area denotes m for maximal P, $m \in (0.7, 0.8)$.

Fig. 1. **A.** Microfluidic device used in the experiment (top view). **B.** Thirty bacterial trajectories selected from the data of 44-μm-wide lane in gradient assays. These represent a subset of the trajectories analyzed in panel **C**. **C.** The relationship between Δx and $n\Delta t$ calculated from all trajectories in the lanes with a width of 44 μm. The black dots represent the gradient assay (∇c=0.05 μM/μm) with a total of 3206 tracks from 6 movies, while the gray dots represent no gradient (∇c=0) with a total of 4755 tracks from 10 movies. The light-yellow and light-blue shadows represent the standard error of the mean (SEM) of different trajectories in the gradient assays and the control assays, respectively. Linear fitting was performed to obtain $V_d = 1.6 \pm 0.3$ μm/s (black solid line) and $V_d = 0.2 \pm 0.2$ μm/s (gray solid line) for gradient and control assays respectively. Error in drift velocity represents standard deviation.

Fig. 2. **A.** Schematic drawing of three typical motion states. **B.** Trajectories for three typical motion states. Red dots represent the start of each trajectory. **C.** Calculating the rotational exponent for each trajectory, γ_R, by fitting the mean-squared orientational displacement $\langle$MSOD$\rangle$. Dots were experimental data calculated from the tracks in Fig. 2B. Solid lines were fitting results with $\langle$MSOD$\rangle = C_R \tau^{\gamma_R}$. The fitted γ_R values are 0, 0.77, and 1.80 for gray, brown, and black tracks, respectively. **D.** Relationship between the rotational exponent γ_R and the mean y position of the bacterial trajectories. Errors denote SEM. Red and purple shaded area represent the region 3 μm from the LSW and RSW, respectively. Green shaded area represents the MA region. **E&F.** Normalized distribution of tumble angle for tracks along the sidewalls (**E**) and in the MA region (**F**). Red solid lines are fitting results with an exponential function: $y = a * \exp(x/b)$. **G.** Distribution of bacteria along the y-axis in the lanes with a width of 44 μm. The shades of different colors denote the same meaning as in Fig. 2D. **H.** Drift velocity of bacterial cells in the three regions. **I.** Proportions of bacterial trajectories in the three regions. Errors are standard deviations (SD).

Fig. 3. **A.** The drift velocity for the experiments in lanes of different widths. The error in drift velocity is the standard deviation. **B.** The distribution of the radius of circular swimming from 382 trajectories in the MA regions. The peak value of the radius is ~10 μm. **C.** The swimming speed of cells in lanes with different widths. The mean swimming speeds and standard deviations for lanes with widths of 6 μm, 8 μm, 10 μm, 15 μm, 25 μm, and 44 μm are 22.7 ± 8.7 μm/s, 25.4 ± 7.7 μm/s, 27.1 ± 7.9 μm/s, 21.9 ± 7.8 μm/s, 22.1 ± 7.7 μm/s, and 22.6 ± 7.5 μm/s, respectively.

Fig. 4. **A.** Mean drift velocities in the LSW, MA, and RSW regions of lanes with different widths. The errors are SD. **B.** The proportion of bacterial cells in the LSW, MA, and RSW regions of lanes with different widths. Errors represent SD. **C.** The proportion of RSW-UG (cells swimming up-gradient in the RSW) and RSW-DG (cells swimming down-gradient in the RSW) for lanes with different widths.

Fig. 5. Simulation of bacterial chemotaxis on the surface of lanes. **A.** The relationship between drift velocity V_d of cells with 10 μm-radius circular swim and the lane width *w*. Errors denote SEM. **B.** The proportion of bacterial trajectories in the LSW, MA, and RSW regions of lanes with different widths, for cells with 10 μm-radius circular swim. **C.** The drift velocity V_d of cells with different radii of circular swim in lanes of different widths. **D.** The relationship between circular swim radius and lane width for optimal chemotaxis (maximal drift velocity) in Fig. 5C. The widths were extracted by fitting the peak value of *w* in Fig. 5A with a gaussian function. The red solid line represents a linear fit. The slope is 0.66 ± 0.03. Errors denote SD.

Fig. 6. Geometrical analysis of optimal lane width for chemotaxis. **A.** Case 1: $0 < w \leq r$. **B.** Case 2: $r < w \leq 2r$. **C.** Case 3: $w > 2r$. The red arrows denote the velocity direction. The black solid lines represent the sidewalls. Dashed circles are trajectories. The up-gradient direction is along the positive *x*-axis. The green shade areas label the swim direction of cells that can swim up-gradient in the RSW. **D.** Relationship between probability (*P*) of cells swimming up-gradient in the RSW and *m*, where *m* = *w*/*r*. Red shaded area denotes *m* for maximal *P*, $m \in (0.7, 0.8)$.