Enhanced bacterial chemotaxis in confined microchannels: Optimal performance in lane widths matching circular swimming radius

Caijuan Yue[1,2], Chi Zhang[1,2, *], Rongjing Zhang[1, *], Junhua Yuan[1, *]

[1] Hefei National Research Center for Physical Sciences at the Microscale, and Department of Physics, University of Science and Technology of China, Hefei, Anhui, 230026, China

[2]These authors contributed equally.

*Corresponding authors:

Junhua Yuan, Rongjing Zhang or Chi Zhang, Hefei National Research Center for Physical Sciences at the Microscale, and Department of Physics, University of Science and Technology of China, Hefei, Anhui, 230026, China, email:

jhyuan@ustc.edu.cn; rjzhang@ustc.edu.cn; zhchi@ustc.edu.cn

Abstract

Understanding bacterial behavior in confined environments is crucial for elucidating microbial ecology and developing strategies to manage bacterial infections. While extensive research has focused on bacterial motility on surfaces and in porous media, chemotaxis in confined spaces remains poorly understood. Here, we investigate the chemotaxis of *Escherichia coli* within microfluidic lanes under a linear concentration gradient of L-aspartate. We demonstrate that *E. coli* exhibits significantly enhanced chemotaxis in lanes with sidewalls compared to open surfaces, primarily due to cells aligning and swimming along the right sidewalls. By varying lane widths, we identify that an 8 μm width—approximating the radius of bacterial circular swimming on surfaces—maximizes chemotactic drift velocity. These results are supported by both experimental observations and stochastic simulations, establishing a clear proportional relationship between optimal lane width and the radius of bacterial circular swimming. Further geometric analysis provides an intuitive understanding of this phenomenon. Our results offer new insights into bacterial navigation in complex biological environments such as host tissues and biofilms, shedding light on microbial ecology in confined habitats and suggesting new avenues for controlling bacterial infections.

Introduction

Microorganisms inhabit a variety of complex confined environments. Sperm swimming in the reproductive tract of a female animal (1), bacteria navigating through host cells and tissues (2), cells moving in the wrinkle of biofilm (3), and swarm cells maneuvering in crowded cell clusters (4) are all examples of organisms operating in geometrically confined environments. Furthermore, many diseases have been found to be related to bacterial motion in confinement, such as urinary tract infections and neonatal sepsis.

Previous research has explored the motion of bacteria in confined environments.

Studies have shown that flagellated bacteria tend to accumulate near both solid-liquid

(5, 6) and air-liquid interfaces (7), and exhibit a specific direction of circular

swimming (8). For example, *E. coli* swim clockwise when observed from above a

solid surface (8-11). Moreover, Tang *et al.* found that flagellated bacteria orbit within

the thin fluid film around micrometer-sized particles (12). Bacteria also display

different motion behaviors in porous media and tubes (13-19), as well as in other

types of confinement (20-22).

E. coli can sense and move in chemical gradients through a set of chemotactic

proteins (23, 24). The transmembrane chemoreceptors detect attractants or repellents

and transmit signals into the cell by changing the concentration of the response

regulator protein CheY-P (24-27). CheY-P binds to the cytoplasmic domain of

flagellar motors, altering the probability of their clockwise rotation (28, 29).

Clockwise and counterclockwise rotations of motors lead to reorientation (tumble)

and smooth swimming (run) modes of the cell body, respectively (30). The adaptation

enzymes CheR and CheB(p) methylate and demethylate the receptors, respectively,

facilitating adaptation (31, 32).

Research has shown that bacterial chemotactic drift velocity decreases sharply near

sample chamber surfaces compared to bulk liquid, a phenomenon attributed to

circular cell movement at these interfaces (33). This observation suggests that surface

effects can significantly impair bacterial chemotactic performance. However, a study

of chemotaxis in two-dimensional bacterial swarms on semisolid agar surfaces has

demonstrated that *E. coli* can exhibit effective chemotaxis in attractant gradients,

especially at high cell densities (4). This apparent contradiction is likely due to

cell-cell interactions mitigating surface effects in dense populations. While previous

studies have investigated bacterial motility in confined environments, especially under

surface effects, research on chemotaxis under these conditions remains limited.

Here, we study the chemotaxis of *E. coli* on surfaces within lanes of different widths, exposed to a linear concentration gradient of L-aspartate using a hydrogel-based microfluidic device. Our findings reveal enhanced chemotactic performance in the presence of sidewalls compared to their absence. Cells in the middle area (MA) exhibited no drift and did not contribute to overall chemotaxis. However, cells near the left sidewall (LSW) and right sidewall (RSW) demonstrated negative and positive drift, respectively, with the positive drift velocity from the RSW exceeding the negative drift velocity from the LSW.

Furthermore, by comparing lanes of different widths within the same stable linear gradient field, we observed that cells exhibited the highest drift velocity in 8 μm-wide lanes, which approximates the peak value in the distribution of circular swimming radii on surfaces. This optimal width for maximal chemotaxis resulted from the largest percentage of cells occupying the right sidewalls. Stochastic simulations of bacterial chemotaxis corroborated that the optimized lane width varies with the bacteria's circular swimming radius. Our findings have important implications for the screening of swimming organisms and the study of chemotactic behavior in real-world scenarios.

Results

Chemotaxis of *E. coli* within lane confinements

To study bacterial chemotaxis in confined environments such as tubes or interstitial tissues, we developed a hydrogel-based microfluidic device featuring lanes of different widths. The device design, illustrated in Fig. 1A, incorporates two 2% (w/v) agarose walls inserted between three main channels: a sink channel, a cell channel, and a source channel. These walls prevent cell passage while allowing chemical diffusion. The agarose walls and main channels measure 100 μm and 400 μm in width, respectively, with the device having a depth of 30 μm.

We established a linear concentration gradient (0.05 μM/μm) of L-aspartate, an

attractant sensed by the Tar receptor, by flowing motility medium through the sink

channel and 50 μM L-aspartate solution (prepared in motility medium) through the

source channel at a constant rate of 10 μL/min. The resulting gradient across the cell

channel is depicted in Fig. S1.

The lanes of various widths were created using parallel PDMS (polydimethylsiloxane)

pillars spaced at different distances. Each lane, approximately 160 μm in length, is

highlighted by a yellow rectangular box in Fig. 1A. *E. coli* cells, confined to the cell

channel, sensed the attractant gradient and performed chemotaxis within these lanes

of different widths.

To enhance imaging contrast, we introduced a plasmid expressing mCherry

fluorescent protein (pTrc99a-mcherry) into wild-type *Escherichia coli* HCB1,

denoting it as HCB1-pTrc99a-mcherry. A high-sensitivity CMOS camera was used to

record bacterial movement trajectories on the bottom surfaces of the lanes in the cell

channel, where most cells accumulate.

We recorded the movement of HCB1-pTrc99a-mcherry cells on the liquid-glass

surface of a 44-μm-wide lane with and without a L-aspartate concentration gradient,

respectively. An example video is shown in Movie S1, and several representative

trajectories are illustrated in Fig. 1B.

We then calculated the drift velocities v_d of the trajectories from both assays along

the x-direction (up-gradient) by fitting the relation $\langle x(i+n) - x(i) \rangle \sim n\Delta t$ (n=1, 3,

5, …, 39) with a linear function, the slope of which is the drift velocity. Here, $x(i)$

represents the cell's x-position in the i-th frame, and Δt denotes the time interval

between two frames (0.05 s). As shown in Fig. 1C, the drift velocity v_d was 1.6±0.3

μm/s and 0.2±0.2 μm/s (mean±SD) for the gradient and control (no-gradient) assays,

respectively. Thus, bacteria in the L-aspartate gradient exhibited obvious chemotaxis

on the lane surfaces, contrasting with previous findings on liquid-solid surfaces

without sidewalls (33).

The cells in the right sidewall region dominated the chemotaxis of *E. coli* within

lane confinements.

To elucidate the mechanism of bacterial chemotaxis within lane confinements, we

analyzed cell trajectories, identifying three distinct motion states due to the presence

of sidewalls. As illustrated in Fig. 2A, cells exhibited straight-line swimming along

sidewalls, movement towards or away from sidewalls, or circular swimming. Fig. 2B

displays three representative trajectories. Circular swimming is characteristic of

typical *E. coli* surface motion (8).

We distinguished these motion states by calculating the rotational exponent (γ_R) for

each trajectory, fitting the mean-squared orientational displacement ⟨MSOD⟩ for

$\tau < 0.4 \, \text{s}$:

$$\langle \text{MSOD} \rangle = \langle \left(\theta(t + \tau) - \theta(t) \right)^2 \rangle = C_R \tau^{\gamma_R} \, ,$$

where $\theta(t)$ is the angle between the swimming direction and the positive *x*-axis

direction at time *t*, τ is the lag time, C_R is a constant, and γ_R is the rotational

exponent. Fig. 2C shows the γ_R values for the three trajectories in Fig. 2B, while Fig.

2D illustrates the relationship between γ_R and average *y*-coordinate. Trajectories

further from sidewalls exhibit larger γ_R, indicating more curved paths, while γ_R

decreases sharply as the cells approach sidewalls, representing straighter trajectories.

We also analyzed tumble kinematics for cells swimming along and away from

sidewalls. Fig. 2E and 2F show normalized tumble angle distributions for cells in

sidewalls (SW) and middle areas (MA), respectively. Red solid lines represent

exponential function fits $y = a * \exp(x/b)$, with fitted *b* values of 0.25 rad (SW) and

1.35 rad (MA). Consistent with previous reports, we observed a higher occurrence of

large reorientation angles for surface-swimming cells in the MA region (Fig. 2F).

Interestingly, we also found large tumble angles in the SW region, albeit with a

smaller characteristic angle than in the MA region. Movie S2 demonstrates an

example of a large reorientation angle during tumbling.

Given the strong spatial dependence of trajectory characteristics, we classified the

cells into three distinct populations. The distribution of cells along the *y*-axis is shown

in Fig. 2G. Based on mean distances from the sidewalls, we divided the lane into three

areas (viewing along the positive *x*-axis): the left sidewall (LSW), the middle area

(MA), and the right sidewall (RSW). As shown by different shaded colors in Fig. 2D

and 2G, we defined cells in LSW, RSW and MA for trajectories with $\langle y \rangle \le d$,

$\langle y \rangle \ge w - d$, and $d < \langle y \rangle < w - d$, respectively. The threshold d was set at 3 μm

(approximately the average length of a cell body), and w represents the lane width.

The proportion of trajectories in different regions is shown in Fig. 2I. For the gradient

assay, the probabilities of trajectories being in LSW, MA and RSW regions were 0.20

± 0.01, 0.59 ± 0.02, and 0.21 ± 0.03, respectively. In the control assay without

gradient, these values were 0.18 ± 0.03, 0.70 ± 0.03, and 0.12 ± 0.01, respectively.

We then compared the drift velocity of cells in the three areas separately for both

gradient and control assays. As shown in Fig. 2H, cells in the LSW region tended to

display a negative drift with v_d^{LSW} = -5.7±2.1 μm/s and -5.0 ± 2.0μm/s for gradient

and control assays, respectively. Cells in the MA region exhibited minimal drift with

v_d^{MA} = -0.3 ± 1.2 μm/s and 0.4 ± 0.6 μm/s for gradient and control assays, respectively.

Cells in the RSW region displayed a typical positive drift with v_d^{RSW} = 14.8 ± 1.2

μm/s and 6.2 ± 1.9 μm/s for gradient and control assays, respectively. Thus, cells in

the RSW region dominated the difference in drift velocity between the two assays.

In summary, cells swim on the right-hand side under the effect of the bottom surface

of lanes (9). The LSW and RSW cells swim down and up the gradient, respectively,

while MA cells swim in circles without any drift. RSW cells demonstrated more

persistent swimming towards the attractant in the L-aspartate gradient, exhibiting a

higher positive drift velocity. Detailed information on the difference in drift velocity

between LSW and RSW cells can be found in the supplemental materials. Notably,

the attractant gradient minimally affects the ratio of bacteria in different regions.

The dependence of chemotactic performance on lane width

Having established that *E. coli* chemotaxis on lane surfaces is closely related to

sidewall confinement, we investigated chemotaxis in lanes of different widths to

mimic bacterial chemotactic behavior in interstitial tissues or tubes of varying sizes.

We compared five lanes with widths of 6 μm, 8 μm, 10 μm, 25 μm, and 44 μm. Drift

velocity was calculated using the same method as in Fig. 1C, with results shown in

Fig. 3A. The mean drift velocities were 1.8 ± 1.3 μm/s, 7.5 ± 1.4 μm/s, 4.6 ± 1.7 μm/s,

2.5 ± 0.5 μm/s, and 2.6 ± 0.4 μm/s for lanes of width 6 μm, 8 μm, 10 μm, 25 μm,

and 44 μm, respectively. Bacteria exhibited optimal chemotaxis (highest drift velocity)

in lanes that were 8 μm wide.

Noting that this optimal width is of the same order of magnitude as the radius of

bacterial circular swimming on a solid surface, we measured the radius of circular

swimming for cells in the MA region. As shown in Fig. 3B, the peak radius in the

distribution of circular swimming radii is ~10 μm, which is close to the lane width

supporting optimal chemotaxis.

It has been reported that bacteria swimming in capillaries of different radii possess

different swimming speeds (34). Therefore, we calculated the cell swimming speeds

for all lane widths. As shown in Fig. 3C, swimming speed remains relatively constant

across different lane widths. This indicates that the optimized chemotaxis is not a

result of varying swimming speeds.

The optimal chemotaxis resulted from more cells moving towards the attractant

along the right sidewall.

To identify the underlying mechanism of optimal lane width for chemotaxis, we

evaluated the drift velocity for cells in the LSW, MA, and RSW regions separately.

The results are shown in Fig. 4A. Cells in the MA region did not exhibit effective drift,

while LSW and RSW cells demonstrated negative and positive drift, respectively,

consistent with the findings in Fig. 2H. The drift velocity for RSW cells increased

with lane width, and remained relatively constant above a lane width of 8 μm, thus

not exhibiting a highest value in the 8 μm-wide lanes. Therefore, the width-dependent

optimal chemotaxis is not attributable to an optimal drift velocity for RSW cells.

We then sought a comparison of cell proportions in the three areas, as plotted in Fig.

4B. The proportion of cells in the MA region increased gradually with lane width due

to the increase in area. Notably, the largest proportion of RSW cells appears in the 8

μm-wide lane. In other words, the lane width-dependent optimal chemotaxis primarily

resulted from changes in cell numbers on the sidewalls.

To further investigate changes in up- and down-gradient cell numbers in the RSW

region, we calculated the proportion of RSW-UG (cells swimming up-gradient in the

RSW) and RSW-DG (cells swimming down-gradient in the RSW) cells. As shown in

Fig. 4C, more cells moved towards the attractant in the 8 μm-wide lane. Thus, the

optimal chemotaxis in the 8 μm-wide lane resulted from a higher number of cells

moving towards the attractant along the right sidewall.

Simulation of *E. coli* chemotaxis within lane confinements

To explore the relationship between the circular swimming of bacteria on lane

surfaces and optimal chemotaxis, we simulated two-dimensional chemotaxis of

bacteria with varying circular swimming radii on lanes of different widths in a steady

linear gradient of L-aspartate.

In our simulation, cells were treated as self-propelled particles performing a random

walk in a run-and-tumble mode within a two-dimensional space. Cells could be in

either a run or tumble state, determined by the intracellular chemotaxis signal. During

a run, cells swam smoothly at a constant speed of 20 μm/s. The effect of the bottom

surface on bacterial swimming was modeled by adding a directional bias term to the

swimming direction:

$$\theta(t + \Delta t) = \theta(t) + b_{direction}\Delta t + \sqrt{2D_r \Delta t}\, n(0, 1)$$

where θ denotes the angle between the swimming direction and the positive x-axis,

Δt is the time step, $b_{direction}$ is the directional bias coefficient, D_r is the rotational

diffusion coefficient, and $n(0, 1)$ represents a random number drawn from a standard

normal distribution. When cells collided with sidewalls, their velocities instantly

aligned with the sidewall, and could potentially leave the sidewall after their next

tumble. During a tumble, cells stopped moving, and their swimming direction

changed. The change in θ was selected from the distribution of tumble angles

observed in Fig. 2E and F for different areas.

Initially, 100 cells were evenly distributed on the surface of a lane measuring 160 μm

in length and w in width. A linear concentration gradient of L-aspartate, identical to

the experimental conditions, was established along the x-axis according to:

$$c(x) = 0.05x + 22,$$

with the concentration c in μM and the position x in μm. The simulation for each set

of parameters ran for 150 s with a timestep of 0.05 s and was repeated 50 times.

Figure 5A illustrates the relationship between chemotactic drift velocity and lane

width for cells with a 10 μm-radius circular swim. The highest drift velocity was

observed at a lane width of 8 μm. Figure 5B shows the proportions of cells in the

three regions (LSW, MA, RSW) for different lane widths, presenting profiles similar

to those observed experimentally in Fig. 4B. Results for different swimming radii are

presented in Fig. 5C, demonstrating that the optimal lane width for chemotaxis is

closely related to the radius of circular swimming.

As shown in Fig. 5D, the relationship between optimal lane width (w) and circular

swimming radius (r) was fitted with a linear function $w = kr$, with $k = 0.66 \pm 0.03$.

This indicates a clear proportional relationship between the lane width for optimal

chemotaxis and the circular swimming radius of bacteria.

Geometrical analysis of optimal lane width for chemotaxis.

We have established that the optimal lane width for chemotaxis (8 μm) primarily

results from a higher proportion of cells in the RSW region swimming up-gradient.

Additionally, this optimal width is directly proportional to the circular swimming

radius of the bacteria. To further elucidate the underlying mechanism of this

phenomenon, we employed geometrical analysis.

We assumed an initial uniform distribution of cells across the lane width. As shown in

Fig. 6A-C, we divide the width of the lane into three scenarios:

1. $0 < w \leq r$: For a cell at any point P in the channel, its swimming direction can

be arbitrary. However, only cells swimming in directions between θ_1 and θ_2

(highlighted in green) can swim up-gradient in the RSW after their first collision with

the sidewall. The proportion of these cells can be calculated as:

$$\frac{1}{w}\int_0^w \frac{\theta_1 + \theta_2}{2\pi}\,dy = \frac{1}{2\pi w}\int_0^w dy\left(\text{acos}\frac{r-w+y}{r} + \text{acos}\frac{y}{r}\right)$$
$$= \frac{1}{2\pi m}\Big[-(1-m)\,\text{acos}(1-m) + \sqrt{1-(1-m)^2} + m\,\text{acos}\,m$$
$$- \sqrt{1-m^2} + 1\Big],$$

298 where $m = w/r \leq 1$.

300 2. $r < w \leq 2r$: Only the cells in the region $y < r$ and with velocity direction

301 between θ_1 and θ_2 can swim up-gradient in the RSW after their first collision

302 with the sidewall. The proportion of cells in this region is:

$$\frac{1}{w}\int_0^r \frac{\theta_1 + \theta_2}{2\pi}\,dy = \frac{1}{2\pi w}\int_0^r dy\left(2\,\text{acos}\frac{y}{r}\right) = \frac{1}{\pi m}$$

304 3. $w > 2r$: The proportion of cells that can swim up-gradient in the RSW is

305   calculated the same as in case 2:

$$\frac{1}{w}\int_0^r \frac{\theta_1 + \theta_2}{2\pi}\,dy = \frac{1}{\pi m}$$

307   The complete relationship between the proportion of cells that can swim up-gradient

308   in the RSW (P) and m is plotted in Fig. 6D. The maximum P occurs when $m \in$

309   (0.7,0.8), marked by the red shaded area. This value is consistent with the slope k in

310   Fig. 5D and results in the optimal width of about 8 μm in Fig. 3A for a circular

311   swimming radius of 10 μm.

Discussions

Bacterial behavior in confined environments differs significantly from that in free

environments. Previous studies have reported that cells tend to swim in circles and

accumulate near a solid-liquid interface, leading to diminished chemotaxis. However,

recent research on chemotaxis of swarm cells suggests that crowded environments

may enhance bacterial chemotaxis on surfaces. In this study, we examined the

chemotaxis of *E. coli* on the bottom surface of microfluidic lanes, exploring the

effects of lane confinement on bacterial chemotaxis.

We found that in the presence of sidewalls, cells that would otherwise have been

unable to exhibit chemotaxis showed significant chemotactic behavior in a linear

gradient of L-aspartate. Cells in different regions of the lanes demonstrated distinct

motion behaviors. In the MA region, cells showed no drift, similar to observations in

chemotaxis near surfaces. Conversely, cells exhibited positive and negative drift when

in the RSW and LSW regions, respectively.

Further investigation into chemotaxis in lanes of varying widths demonstrated that

cells exhibited the highest chemotactic drift velocity in lanes that were 8 μm wide.

This width is close to the radius of bacterial swimming circles. By analyzing the

proportion and drift velocity of cells in different regions, we determined that this

optimal lane width was primarily due to the higher proportion of cells swimming up-gradient along the right sidewall.

To explore the relationship between chemotactic drift velocity and circular swimming radius of bacteria, we conducted systematic simulations of *E. coli* chemotaxis with different circular swimming radii in lanes of varying widths under a linear concentration gradient of L-aspartate. We found that optimal chemotaxis occurred when the swimming radius was close to the lane width, with $w = 0.66r$. This suggests a significant proportional relationship between the optimal lane width for chemotaxis and the circular swimming radius of bacteria.

To elucidate the mechanism underlying this phenomenon, we employed geometric analysis. We demonstrated that bacteria in lanes could swim up-gradient in the RSW with maximal probability when the lane width was 0.7-0.8 times the radius of circular swimming. This finding is consistent with the experimental results presented in Fig. 4C.

Our findings have important implications for the screening of single-celled swimming organisms and the study of restricted chemotactic behavior. This research provides insights into how confinement affects bacterial chemotaxis and may inform the design of microfluidic devices for bacterial manipulation and analysis.

Bacteria frequently inhabit confined spaces such as soil pores, sediment interstices, rock crevices, biological tissues, and hydrogels. In these constrained environments, bacterial behavior often deviates significantly from that observed in unconfined conditions, typically resulting in reduced chemotactic ability. However, our findings challenge this notion, suggesting that certain types of environmental confinement may actually enhance bacterial chemotaxis. This discovery could contribute to our understanding of microbial ecology across various habitats, including soil, oceans, and the human body.

Furthermore, these insights could have potential applications. In biotechnology, optimizing confinement conditions could improve the efficiency of bioremediation processes or the production of microbial products. In medicine, understanding how pathogens navigate confined spaces within the body could lead to novel strategies for preventing or treating infections.

Materials and methods

Strain and plasmids

The plasmid pTrc99a-mCherry expresses mCherry under an IPTG-inducible promoter. The wild-type *E. coli* K12 strain AW405 (HCB1) transformed with pTrc99a-mCherry was used for fluorescent tracking of cell trajectories. Cells were streaked on a Petri dish containing 1.5% agar and lysogeny broth (1% tryptone, 0.5% NaCl, 0.5% yeast extract, supplemented with the appropriate antibiotic: 100 μg/ml ampicillin). A single colony was inoculated into lysogeny broth and grown overnight at 33 °C with 200 rpm rotation. The saturated culture was then diluted 1:100 (100 μl in 10 ml) into tryptone broth (1% tryptone, 0.5% NaCl, supplemented with the appropriate inducer and antibiotic: 0.1 mM IPTG, 100 μg/ml ampicillin) and grown at 33 °C with 200 rpm rotation to OD_{600}=0.53. Cells were then harvested from culture media by centrifugation at 1.2×g for 6 min at room temperature. The pellet was resuspended by gently mixing in motility medium (10 mM potassium phosphate, 0.1 mM ethylenediaminetetraacetic acid (EDTA), 10 mM lactic acid, and 1 μM methionine at pH 7.0). The cells were washed three times to replace growth medium with motility medium. One hour after fluorescence maturation in a 33°C incubator, cells were placed in a 4°C refrigerator ready for microfluidic experiments.

Microfluidic device design and fabrication

A hydrogel-based microfluidic device containing lanes of different width was designed using L-edit based on previous work (34). The silicon mold with the positive

relief features was fabricated using the standard soft lithography technique performed

in our laboratory. Firstly, a 4-inch diameter silicon wafer was spin washed

sequentially using water, acetone, methanol and isopropanol. The wafer was

thoroughly dried on a 150 °C hot plate to ensure that organics has volatilized

completely. Then, the wafer was treated with air plasma (Harrick plasma, PDC-002,

30W) for 10 min before the SU-8 2025 photoresist (Microchem) was spin-coated

according to the products protocols. The spin-coated wafer was placed on a hot plate

at 65°C for 3 min followed by 6 min at 95°C, then exposed to UV light using a

maskless lithography machine (Heidelberg, μMLA) at 800 mJ/cm^2 with defocus was

set to 0. The post-exposure bake was performed at 65°C for 2 min followed by 6 min

at 95°C. Development procedure lasted about 6 minutes with constant shaking in the

SU-8 developer. The wafer was rinsed with fresh developer followed by isopropanol.

Finally, an approximately 30-μm-high photoresist layer was created as the master

mold. The mold was fixed on a glass petri dish using double-sided tape.

Polydimethylsiloxane (PDMS) and curing agent was mixed with a 10:1 ratio (Sylgard

184, Dow Corning) and centrifuged at 3500 rpm for 5 min to remove air bubbles. The

mixture was poured over the mold in glass petri dish and then placed at 4°C for an

hour to avoid interference from very small air bubbles. The PDMS was cured at 80°C

for 3 h, then separated from the wafer and cut into pieces, and holes were punched for

inlets and outlets. The punched PDMS was cleaned with adhesive tape. The cleaned

PDMS was bonded to a glass slide after air plasma treatment (Harrick plasma,

PDC-002, 30W). The fabricated device was baked at 80°C overnight to establish

covalent bonding.

The hydrogel agarose was used at 2% (w/v) concentration in motility medium to

create diffusion-permeable walls. Agarose was slowly injected through the inlet port

using a syringe pump at a constant flow rate of 2 μL/min, and the injection process

was carried out in a drying oven at a constant temperature of 68 °C.

Microscopy and data acquisition

The PDMS microfluidic chip was placed on a Nikon Ti-E inverted optical microscope equipped with a specific filter set, a 20× objective (Nikon, CFI S Plan Fluor ELWD, 20×, NA 0.45), and a CMOS camera (Hamamatsu, ORCA-Flash4.0, pixel size = 6.5 μm). We set the objective lens's correction collar to 1.2 mm to match the glass slide thickness. A halogen lamp serves as the bright-field light source to help locate the observation area, while a xenon lamp serves as the excitation light source for fluorescence experiments.

1) Gradient profile calibration

Fluorescein solution (Sigma) was used for visualizing the chemical concentration field in the microfluidic device. 100 μM fluorescein and motility medium were flowed into the source and sink channels respectively, at a constant flow rate of 10 μL/min. One fluorescent image was captured per minute. To avoid the impact of photobleaching on the results, we only illuminated the sample during the imaging process.

2) Chemotaxis assays

The aspartic acid and motility medium solutions were respectively introduced into the source and sink channels, and left for more than 1 hour to allow aspartic acid to diffuse through the agarose wall and form a stable concentration gradient field. Then, bacteria were introduced into the cell channel at a rate of 5 μL/min using a syringe pump for a duration of 90 seconds. After the bacteria injection was complete, the microvalves were closed to seal the cell channel. Bacteria then performed chemotaxis due to the perception of the concentration gradient field. After waiting for 2 minutes, the shutter was opened to illuminate the fluorescent bacteria with the excitation light, and video recording began. During the video acquisition process, fluorescence excitation light was continuously illuminated onto the bacteria. For each recording, 9600 frames (2048×2048 pixels) were captured at a frame rate of 20 fps and an exposure of 50 ms. Although the long-term illumination caused a decrease in the brightness of the fluorescent bacteria, the position information of the bacteria could

still be accurately distinguished within the video duration (8 min).

Data analysis

Tracking. Image analysis was performed with the ImageJ (National Institutes of

Health) TrackMate plugin. We chose the Log detector with an estimated blob diameter

of 70 μm and a threshold of 800 μm to effectively recognize bacteria, based on the

diameter of bacteria and the use of a 20× objective. Then, we used the LAP Tracker

and set the maximum distance for frame-to-frame linking to 50 μm.

Swimming speed. The velocity is calculated using the fourth order central difference

method by (35):

$$\vec{v}_i = \frac{8(\vec{x}_{i+1} - \vec{x}_{i-1}) - (\vec{x}_{i+2} - \vec{x}_{i-2})}{12T}$$

The magnitude of the velocity is given by $v_i = |\vec{v}_i|$. The speed of each trajectory is

defined as the average of v_i. The swimming speeds of bacteria in lanes of different

widths are represented by the mean and standard deviation of all trajectories.

Calculation of the radius of circular motion on the solid surface. A total of 382

trajectories with a rotational exponent greater than 1.6 in the MA region of the $w = 44$

μm lanes were selected for analysis. The trajectories were smoothed using the

Savitzky-Golay filter with a window size of 5. The least squares method was then

applied to solve the linear equations, yielding the center and radius of the fitted circles.

The principle of this process is briefly described as follows:

The standard equation of a circle can be written as:

$$(x - a)^2 + (y - b)^2 = r^2,$$

475 where (a, b) are the coordinates of the circle's center, and r is the radius.

476 Expanding and rearranging the standard equation of a circle, it can be rewritten as:

$$x^2 + y^2 = 2ax + 2by + c,$$

477 where $c = r^2 - a^2 - b^2$.

479   Rewriting the above equation in matrix form, we have:

$$B = A \cdot Coefficients$$

480   where

$$B = x^2 + y^2 = \begin{bmatrix} x_1^2 + y_1^2 \\ x_2^2 + y_2^2 \\ \vdots \\ x_n^2 + y_n^2 \end{bmatrix}$$

481   is the response vector, and

$$A = \begin{bmatrix} x & y & 1 \end{bmatrix} = \begin{bmatrix} x_1 & y_1 & 1 \\ x_2 & y_2 & 1 \\ \vdots & \vdots & \vdots \\ x_n & y_n & 1 \end{bmatrix}$$

482   is the design matrix. The coefficients are given by:

$$Coefficients = \begin{bmatrix} 2a \\ 2b \\ c \end{bmatrix} = (A^T A)^{-1}(A^T B).$$

484   **Tumble angle.** A tumble is defined as points where the velocity is lower than the

485   average velocity of the trajectory $\langle v_i \rangle$ and shows a substantial drop from the

486   previous time point. Specifically, a tumble is identified when:

$$\{v_{t1}, \cdots, v_{tn}\} < \langle v_i \rangle,$$

$$\{v_{t0} - v_{t1}, \dots, v_{tn-1} - v_{tn}\} > \langle v_i \rangle \cdot \alpha,$$

where $n \geq 2, \alpha = 1/6$ is the threshold, and t_1 and t_n represent the start and end

times of a tumble, respectively.

Simulation of bacterial chemotaxis within lanes.

In our simulation, we introduced the effects of bottom surface and sidewalls into the

2-dimensional chemotaxis of *E. coli*. The simulations were carried out in a rectangular

area of size 160 μm × *w*, where *w* denotes the lane width. Cells were treated as

self-propelled particles. They could sense and adapt to the ligand in the surrounding

environment via the intracellular chemotaxis signaling pathway, which could be

described by a coarse-grained model of bacterial chemotaxis (36, 37):

$$a = \cfrac{1}{1 + \exp\left(N\left(\alpha(m - m_0) + \ln\cfrac{1 + \frac{c}{K_{off}}}{1 + \frac{c}{K_{on}}} \right) \right)},$$

$$\frac{dm}{dt} = k_R(1 - a) - k_B a,$$

where a, m, and c represent the activity of the receptor-kinase complex, the

methylation level of receptors, and the ligand concentration, respectively. N denotes

the number of chemoreceptors in a Monod-Wyman-Changeux cluster (38). The values

of parameters we used were the same as before (4, 38, 39): $N = 4.6$, $K_{off} =$

1.7 μM, $K_{on} = 12$ μM, $\alpha = 1.7$, $m_0 = 1.0$, $k_R = 0.005$ s^{-1}, $k_B = 0.010$ s^{-1}.

The concentration of CheY-P, which changes due to the receptor-kinase

phosphorylation on CheY, could be calculated by $Yp = 7.86a$. Consequently, the CW

bias (B) of flagellar motors would also vary (40):

$$B = \frac{(Yp)^{10.3}}{(Yp)^{10.3} + 3.1^{10.3}}.$$

It has been reported that the average run time in the near-surface region for wildtype

cells is ~2.0 s (11). Thus, the switching rate from run to tumble of cells was set to be

equivalent to that from CCW to CW rotation of the motors, which could be calculated

by $k = \frac{B}{0.31}$ s^{-1}. The switching rate from tumble to run was 5 s^{-1} due to the

constant tumble duration of 0.2 s (41).

In this way, the motion states of each cell at any moment are determined. During a run,

cells swim smoothly with a constant speed of 20 μm/s, influenced by rotational

diffusion and the effect of the bottom surface on bacterial swimming:

$$\theta(t + \Delta t) - \theta(t) = \left(-\frac{v_0}{r} \right)\Delta t + n(0, 2D_r\Delta t),$$

515   where θ is the angle between the swimming direction and the positive x-axis,

516   $v_0 = 20$ μm/s is the swimming speed, r is the radius of circular swimming due to

517   the effect of the bottom surface, and $n(0, 2D_r\Delta t)$ represents a normal distribution

518   with zero mean and variance $2D_r\Delta t$. The rotational diffusion coefficient was 0.062

rad^2/s (42). During a tumble, cells stop swimming and a tumble angle is selected from the distribution that we have measured. Cells will swim along the sidewalls for 2 s (the average dwell time from Fig. S2B), then escape from it with an angle selected from Fig. 2E. They will get a random y-coordinate at the other side when they swim through the x boundary.

References

1. S. S. Suarez, A. A. Pacey, Sperm transport in the female reproductive tract. *Hum. Reprod. Update* **12**, 23-37 (2005).
2. D. Bray, *Cell Movements: From Molecules to Motility* (Routledge, 1992).
3. S. Geisel, E. Secchi, J. Vermant, The role of surface adhesion on the macroscopic wrinkling of biofilms. *eLife* **11** (2022).
4. M. Tian, C. Zhang, R. Zhang, J. Yuan, Collective motion enhances chemotaxis in a two-dimensional bacterial swarm. *Biophys J* **120**, 1615-1624 (2021).
5. A. P. Berke, L. Turner, H. C. Berg, E. Lauga, Hydrodynamic attraction of swimming microorganisms by surfaces. *Phys. Rev. Lett.* **101**, 038102 (2008).
6. G. Li, J. X. Tang, Accumulation of microswimmers near a surface mediated by collision and rotational brownian motion. *Phys. Rev. Lett.* **103**, 078101 (2009).
7. M. Michael, H. Athena, L. Guanglai, R. M. Martin , X. T. Jay Molecular Adsorption Steers Bacterial Swimming at the Air/Water Interface. *Biophys J* **105**, 21-28 (2013).
8. L. Eric, R. D. Willow, M. W. George, A. S. Howard, Swimming in Circles: Motion of Bacteria near Solid Boundaries. *Biophys J* **90**, 400-412 (2006).
9. W. R. DiLuzio *et al.*, *Escherichia coli* swim on the right-hand side. *Nature* **435**, 1271-1274 (2005).
10. G. Junot *et al.*, Run-to-Tumble Variability Controls the Surface Residence Times of *E. coli* Bacteria. *Phys. Rev. Lett.* **128**, 248101 (2022).
11. M. Molaei, M. Barry, R. Stocker, J. Sheng, Failed escape: solid surfaces prevent tumbling of *Escherichia coli*. *Phys. Rev. Lett.* **113**, 068103 (2014).
12. G. Araujo, W. Chen, S. Mani, J. X. Tang, Orbiting of Flagellated Bacteria within a Thin Fluid Film around Micrometer-Sized Particles. *Biophys J* **117**, 346-354 (2019).
13. T. Bhattacharjee, S. S. Datta, Bacterial hopping and trapping in porous media. *Nat. Commun.* **10**, 2075 (2019).
14. T. Bhattacharjee, S. S. Datta, Confinement and activity regulate bacterial motion in porous media. *Soft matter* **15**, 9920-9930 (2019).
15. Nicholas A. Licata, B. Mohari, C. Fuqua, S. Setayeshgar, Diffusion of Bacterial Cells in Porous Media. *Biophys J* **110**, 247-257 (2016).
16. D. Shrestha *et al.*, Bacterial mobility and motility in porous media mimicked by microspheres. *Colloids Surf. B* **222**, 113128 (2023).

17. N. Figueroa-Morales *et al.*, *E. coli* "super-contaminates" narrow ducts fostered by broad run-time distribution. *Sci. Adv.* **6**, eaay0155 (2020).

18. H. Wioland, E. Lushi, R. E. Goldstein, Directed collective motion of bacteria under channel confinement. *New J. Phys.* **18**, 075002 (2016).

19. V. Tokárová *et al.*, Patterns of bacterial motility in microfluidics-confining environments. *Proc. Natl. Acad. Sci. U.S.A* **118**, e2013925118 (2021).

20. P. C. Mushenheim, R. R. Trivedi, H. H. Tuson, D. B. Weibel, N. L. Abbott, Dynamic self-assembly of motile bacteria in liquid crystals. *Soft Matter* **10**, 88-95 (2014).

21. C. J. Woolverton, E. E. Gustely, L. Li, O. D. Lavrentovich, Liquid crystal effects on bacterial viability. *Liq. Cryst.* **32**, 417 - 423 (2005).

22. X. Chen, R. Zhang, J. Yuan, Vertical confinement enhances surface exploration in bacterial twitching motility. *Environ. Micriobiol.* **26**, e16679 (2024).

23. G. L. Hazelbauer, J. J. Falke, J. S. Parkinson, Bacterial chemoreceptors: high-performance signaling in networked arrays. *Trends Biochem. Sci.* **33**, 9-19 (2008).

24. V. Sourjik, Receptor clustering and signal processing in E. coli chemotaxis. *Trends Microbiol.* **12**, 569-576 (2004).

25. A. I. M. Salah Ud-Din, A. Roujeinikova, Methyl-accepting chemotaxis proteins: a core sensing element in prokaryotes and archaea. *Cell. Mol. Life Sci.* **74**, 3293-3303 (2017).

26. J. J. Falke, G. L. Hazelbauer, Transmembrane signaling in bacterial chemoreceptors. *Trends Biochem. Sci.* **26**, 257-265 (2001).

27. A. Bren, M. Eisenbach, How Signals Are Heard during Bacterial Chemotaxis: Protein-Protein Interactions in Sensory Signal Propagation. *J. Bacteriol.* **182**, 6865-6873 (2000).

28. M. K. Sarkar, K. Paul, D. Blair, Chemotaxis signaling protein CheY binds to the rotor protein FliN to control the direction of flagellar rotation in *Escherichia coli*. *Proc. Natl. Acad. Sci. U.S.A* **107**, 9370-9375 (2010).

29. G. H. Wadhams, J. P. Armitage, Making sense of it all: bacterial chemotaxis. *Nat. Rev. Mol. Cell Biol.* **5**, 1024-1037 (2004).

30. M. D. Baker, P. M. Wolanin, J. B. Stock, Signal transduction in bacterial chemotaxis. *Bioessays* **28**, 9-22 (2006).

31. K. Oosawa, Y. Imae, Demethylation of methyl-accepting chemotaxis proteins in *Escherichia coli* induced by the repellents glycerol and ethylene glycol. *J. Bacteriol.* **157**, 576-581 (1984).

32. R. M. Weis, S. Chasalow, D. E. Koshland, Jr., The role of methylation in chemotaxis. An explanation of outstanding anomalies. *J Biol Chem* **265**, 6817-6826 (1990).

33. M. Grognot, K. M. Taute, A multiscale 3D chemotaxis assay reveals bacterial navigation mechanisms. *Commun. Biol.* **4**, 669 (2021).

34. L. Ping, V. Wasnik, E. Emberly, Bacterial motion in narrow capillaries. *FEMS Microbiol. Ecol* **91 2**, 1-7 (2015).

35. L. Turner, L. Ping, M. Neubauer, H. C. Berg, Visualizing Flagella while Tracking Bacteria. *Biophys J* **111**, 630-639 (2016).

36. L. Jiang, Q. Ouyang, Y. Tu, Quantitative Modeling of *Escherichia coli* Chemotactic Motion in Environments Varying in Space and Time. *PLoS Comput Biol* **6**, e1000735 (2010).

37. Y. Tu, T. S. Shimizu, H. C. Berg, Modeling the chemotactic response of *Escherichia coli* to time-varying stimuli. *Proc. Natl. Acad. Sci. U.S.A* **105**, 14855-14860 (2008).

38. N. Vladimirov, L. Løvdok, D. Lebiedz, V. Sourjik, Dependence of bacterial chemotaxis on gradient shape and adaptation rate. *PLoS Comput Biol* **4**, e1000242 (2008).

39. S. Ren, C. Zhang, R. Zhang, The effect of receptor interaction on the bacterial chemotactic adaptation rate. *JUSTC* **53**, 0703 (2023).

40. P. Cluzel, M. Surette, S. Leibler, An Ultrasensitive Bacterial Motor Revealed by Monitoring Signaling Proteins in Single Cells. *Science* **287**, 1652-1655 (2000).

41. H. C. Berg, D. A. Brown, Chemotaxis in Escherichia coli analysed by Three-dimensional Tracking. *Nature* **239**, 500-504 (1972).

42. N. Vladimirov, D. Lebiedz, V. Sourjik, Predicted auxiliary navigation mechanism of peritrichously flagellated chemotactic bacteria. *PLoS Comput Biol* **6**, e1000717 (2010).

Acknowledgements. This work was supported by National Natural Science

Foundation of China Grants (11925406, 12090053, and 12104436) and a grant from

the Ministry of science and technology of China (2019YFA0709303).

Author Contributions. J. Y., R.Z., and C. Z. designed the work. C. Z. and C. Y.

performed the experiments. All authors wrote the manuscripts.

Competing financial interests. The authors declare no competing financial interests.

Figure Legends

Fig. 1. **A.** Microfluidic device used in the experiment (top view). **B.** Thirty bacterial trajectories selected from the data of 44-μm-wide lane in gradient assays. **C.** The relationship between Δx and Δt calculated from all trajectories in the lanes with a width of 44 μm. The black dots represent the gradient assay (∇c=0.05 μM/μm) with a total of 3206 tracks from 6 movies, while the gray dots represent no gradient (∇c=0) with a total of 4755 tracks from 10 movies. The light-yellow and light-blue shadows represent the standard error of the mean (SEM) of different trajectories in the gradient assays and the control assays, respectively. Linear fitting was performed to obtain V_d = 1.6 ± 0.3 μm/s (black solid line) and V_d = 0.2 ± 0.2 μm/s (gray solid line) for gradient and control assays respectively. Error in drift velocity represents standard deviation.

Fig. 2. **A.** Schematic drawing of three typical motion states. **B.** Trajectories for three typical motion states. Red dots represent the start of each trajectory. **C.** Calculating the rotational exponent for each trajectory, γ_R, by fitting the mean-squared orientational displacement ⟨MSOD⟩. Dots were experimental data calculated from the tracks in Fig. 2B. Solid lines were fitting results with $\langle \text{MSOD} \rangle = C_R \tau^{\gamma_R}$. The fitted γ_R values are 0, 0.77, and 1.80 for gray, brown, and black tracks, respectively. **D.** Relationship between the rotational exponent γ_R and the mean y position of the bacterial trajectories. Errors denote SEM. Red and purple shaded area represent the region 3 μm from the LSW and RSW, respectively. Green shaded area represents the MA region. **E&F.** Normalized distribution of tumble angle for tracks along the sidewalls (**E**) and in the MA region (**F**). Red solid lines are fitting results with an exponential function: $y = a * \exp(x/b)$. **G.** Distribution of bacteria along the y-axis in the lanes with a width of 44 μm. The shades of different colors denote the same meaning as in Fig. 2D. **H.** Drift velocity of bacterial cells in the three regions. **I.** Proportions of bacterial trajectories in the three regions. Errors are standard deviations (SD).

Fig. 3. **A.** The drift velocity for the experiments in lanes of different widths. The error in drift velocity is the standard deviation. **B.** The distribution of the radius of circular swimming from 382 trajectories in the MA regions. The peak value of the radius is ~10 μm. **C.** The swimming speed of cells in lanes with different widths. The mean swimming speeds and standard deviations for lanes with widths of 6 μm, 8 μm, 10 μm, 15 μm, 25 μm, and 44 μm are 22.7 ± 8.7 μm/s, 25.4 ± 7.7 μm/s, 27.1 ± 7.9 μm/s, 21.9 ± 7.8 μm/s, 22.1 ± 7.7 μm/s, and 22.6 ± 7.5 μm/s, respectively.

Fig. 4. **A.** Mean drift velocities in the LSW, MA, and RSW regions of lanes with different widths. The errors are SD. **B.** The proportion of bacterial cells in the LSW, MA, and RSW regions of lanes with different widths. Errors represent SD. **C.** The proportion of RSW-UG (cells swimming up-gradient in the RSW) and RSW-DG (cells swimming down-gradient in the RSW) for lanes with different widths.

Fig. 5. Simulation of bacterial chemotaxis on the surface of lanes. **A.** The relationship between drift velocity V_d of cells with 10 μm-radius circular swim and the lane width w. Errors denote SEM. **B.** The proportion of bacterial trajectories in the LSW, MA, and RSW regions of lanes with different widths, for cells with 10 μm-radius circular swim. **C.** The drift velocity V_d of cells with different radii of circular swim in lanes of different widths. **D.** The relationship between circular swim radius and lane width for optimal chemotaxis (maximal drift velocity) in Fig. 5C. The widths were extracted by fitting the peak value of w in Fig. 5A with a gaussian function. The red solid line represents a linear fit. The slope is 0.66 ± 0.03. Errors denote SD.

Fig. 6. Geometrical analysis of optimal lane width for chemotaxis. **A.** Case 1: $0 < w \leq r$. **B.** Case 2: $r < w \leq 2r$. **C.** Case 3: $w > 2r$. The red arrows denote the velocity direction. The black solid lines represent the sidewalls. Dashed circles are trajectories. The up-gradient direction is along the positive x-axis. The green shade areas label the swim direction of cells that can swim up-gradient in the RSW. **D.**

694   Relationship between probability (P) of cells swimming up-gradient in the RSW and

695   m, where $m = w/r$. Red shaded area denotes m for maximal P, $m \in (0.7, 0.8)$.

Fig. 1. **A.** Microfluidic device used in the experiment (top view). **B.** Thirty bacterial trajectories selected from the data of 44-μm-wide lane in gradient assays. **C.** The relationship between Δx and Δt calculated from all trajectories in the lanes with a width of 44 μm. The black dots represent the gradient assay (∇c=0.05 μM/μm) with a total of 3206 tracks from 6 movies, while the gray dots represent no gradient (∇c=0) with a total of 4755 tracks from 10 movies. The light-yellow and light-blue shadows represent the standard error of the mean (SEM) of different trajectories in the gradient assays and the control assays, respectively. Linear fitting was performed to obtain V_d = 1.6 ± 0.3 μm/s (black solid line) and V_d = 0.2 ± 0.2 μm/s (gray solid line) for gradient and control assays respectively. Error in drift velocity represents standard deviation.

Fig. 2. **A.** Schematic drawing of three typical motion states. **B.** Trajectories for three

typical motion states. Red dots represent the start of each trajectory. **C.** Calculating

the rotational exponent for each trajectory, γ_R, by fitting the mean-squared

orientational displacement ⟨MSOD⟩. Dots were experimental data calculated from the

tracks in Fig. 2B. Solid lines were fitting results with $\langle \text{MSOD} \rangle = C_R \tau^{\gamma_R}$. The fitted

γ_R values are 0, 0.77, and 1.80 for gray, brown, and black tracks, respectively. **D.**

Relationship between the rotational exponent γ_R and the mean y position of the

bacterial trajectories. Errors denote SEM. Red and purple shaded area represent the

region 3 μm from the LSW and RSW, respectively. Green shaded area represents the

MA region. **E&F.** Normalized distribution of tumble angle for tracks along the

sidewalls (**E**) and in the MA region (**F**). Red solid lines are fitting results with an

exponential function: $y = a * \exp(x/b)$. **G.** Distribution of bacteria along the y-axis

in the lanes with a width of 44 μm. The shades of different colors denote the same

meaning as in Fig. 2D. **H.** Drift velocity of bacterial cells in the three regions. **I.**

Proportions of bacterial trajectories in the three regions. Errors are standard deviations

(SD).

Fig. 3. **A.** The drift velocity for the experiments in lanes of different widths. The error

in drift velocity is the standard deviation. **B.** The distribution of the radius of circular

swimming from 382 trajectories in the MA regions. The peak value of the radius is

~10 μm. **C.** The swimming speed of cells in lanes with different widths. The mean

swimming speeds and standard deviations for lanes with widths of 6 μm, 8 μm, 10 μm,

15 μm, 25 μm, and 44 μm are 22.7 ± 8.7 μm/s, 25.4 ± 7.7 μm/s, 27.1 ± 7.9 μm/s, $21.9 \pm$

7.8 μm/s, 22.1 ± 7.7 μm/s, and 22.6 ± 7.5 μm/s, respectively.

Fig. 4. **A.** Mean drift velocities in the LSW, MA, and RSW regions of lanes with different widths. The errors are SD. **B.** The proportion of bacterial cells in the LSW, MA, and RSW regions of lanes with different widths. Errors represent SD. **C.** The proportion of RSW-UG (cells swimming up-gradient in the RSW) and RSW-DG (cells swimming down-gradient in the RSW) for lanes with different widths.

Fig. 5. Simulation of bacterial chemotaxis on the surface of lanes. **A.** The relationship

between drift velocity V_d of cells with 10 μm-radius circular swim and the lane width

w. Errors denote SEM. **B.** The proportion of bacterial trajectories in the LSW, MA,

and RSW regions of lanes with different widths, for cells with 10 μm-radius circular

swim. **C.** The drift velocity V_d of cells with different radii of circular swim in lanes of

different widths. **D.** The relationship between circular swim radius and lane width for

optimal chemotaxis (maximal drift velocity) in Fig. 5C. The widths were extracted by

fitting the peak value of *w* in Fig. 5A with a gaussian function. The red solid line

represents a linear fit. The slope is 0.66 ± 0.03. Errors denote SD.

Fig. 6. Geometrical analysis of optimal lane width for chemotaxis. **A.** Case 1: $0 < w \leq r$. **B.** Case 2: $r < w \leq 2r$. **C.** Case 3: $w > 2r$. The red arrows denote the velocity direction. The black solid lines represent the sidewalls. Dashed circles are trajectories. The up-gradient direction is along the positive x-axis. The green shade areas label the swim direction of cells that can swim up-gradient in the RSW. **D.** Relationship between probability (P) of cells swimming up-gradient in the RSW and m, where $m = w/r$. Red shaded area denotes m for maximal P, $m \in (0.7, 0.8)$.

Supplemental materials

Explanation of difference in drift velocity between LSW and RSW cells.

We observed obvious chemotaxis of *E. coli* on the surface of lanes, closely related to cells swimming along sidewalls. As shown in Fig. S2A, cells swimming along sidewalls in an attractant gradient can be divided into four states: Cells on the right sidewall swimming up-gradient (RSW-UG), cells on the right sidewall swimming down-gradient (RSW-DG), cells on the left sidewall swimming up-gradient (LSW-UG), and cells on the left sidewall swimming down-gradient (LSW-DG). These cells can escape from sidewalls with rates:

$$k_{RSW-UG} = B^+ k_T$$

$$k_{RSW-DG} = B^- k_T + (1 - B^-)k_R$$

$$k_{LSW-UG} = B^+ k_T + (1 - B^+)k_R$$

$$k_{LSW-DG} = B^- k_T$$

where B^+ and B^- represent the probability of tumble when cells swim up-gradient and down-gradient, respectively, and k_T and k_R denote the escape rates during tumble and run, respectively. Cells swimming on the sidewalls experience a force f_s from the bottom surface, causing them to swim to the right. RSW-UG and LSW-DG cells can swim away from the sidewalls via tumble, while RSW-DG and LSW-UG cells can escape via tumble or run. The gradient field direction ensures that $0 \leq B^+ < B^- \leq 1$.

Dwell times for the four states are plotted in Fig. S2B, suggesting that $\tau_{RSW-UG} > \tau_{LSW-DG} > \tau_{RSW-DG} > \tau_{LSW-UG}$. Thus, $k_R > k_T > 0$.

The drift velocity for cells on right and left sidewall can be calculated as:

$$v_d^{RSW} = v_0 \left(\frac{1}{k_{RSW-UG}} - \frac{1}{k_{RSW-DG}} \right) = v_0 \frac{(B^- - B^+)k_T + (1 - B^-)k_R}{B^+ B^- k_T^2 + (1 - B^-)B^+ k_T k_R}$$

$$v_d^{LSW} = v_0 \left(\frac{1}{k_{LSW-UG}} - \frac{1}{k_{LSW-DG}} \right) = v_0 \frac{(B^- - B^+)k_T - (1 - B^+)k_R}{B^+ B^- k_T^2 + (1 - B^+)B^- k_T k_R}$$

788 where v_0 represents the swimming speed. Given that $0 \leq B^+ < B^- \leq 1$ and

789 $k_R > k_T > 0$, we can conclude that:

$$v_d^{RSW} > 0$$
$$v_d^{LSW} < 0.$$

Supplemental movies

Movie S1. An example video of HCB1-pTrc99a-mCherry cells chemotaxis in a

44-μm-wide lane under a linear gradient of L-aspartate. The source channel is on the

right side.

Movie S2. An example of a large reorientation angle during tumbling in the LSW of a

44-μm-wide lane under a linear gradient of L-aspartate. The source channel is on the

right side. The cell of interest is marked with a blue circle.

 Fig.S1. Gradient calibration of microfluidics with fluorescein **A.** Fluorescence image

 of the stable gradient field. **B.** Normalized gradient in lanes of different widths. Red,

 green, and blue lines represent relative concentration values of the substance at

 different x positions for lanes with widths of 15 μm, 25 μm, and 44 μm, respectively.

 The red rectangle represents the ROI in Fig. S1A. **C.** Change in concentration

 gradient perceived by bacteria over time in lanes of different widths. Red circles (15

810   μm), green diamonds (25 μm), and blue asterisks (44 μm) show 11 calibration

811   measurements. Shaded areas represent SEM.

Fig.S2. **A.** Four motion states of cells swimming along sidewalls. Black arrows denote the direction of force f_s generated by the bottom surface on the cell body. **B.** Dwell times of the four motion states from experiments in 44 μm-wide lanes. The values are 1.3 ± 0.04 s, 1.87 ± 0.36 s, 2.27 ± 0.5 s, and 1.75 ± 0.18 s for LSW-UG, LSW-DG, RSW-UG, and RSW-DG respectively. Errors represent SDs.