Title:

Mitigating nitrous oxide emission by an ultra-fast bioprocess enabling the removal of

high concentration N_2O

Authors:

Ryota Maeda[1], Mikiko Sato[1], Kiwamu Minamisawa[2] and Kengo Kubota[1,3,]*

Affiliations:

[1] Department of Frontier Sciences for Advanced Environment, Graduate School of

Environmental Studies, Tohoku University, 6-6-06 Aza-Aoba, Aramaki, Aoba-ku, Sendai,

Miyagi 980-8579, Japan

[2] Department of Ecological Developmental Adaptability Life Sciences, Graduate School of

Life Science, Tohoku University, 2-1-1 Katahira, Aoba-ku, Sendai, 980-18577, Japan

[3] Department of Civil and Environmental Engineering, Graduate School of Engineering,

Tohoku University, 6-6-06 Aza-Aoba, Aramaki, Aoba-ku, Sendai, Miyagi 980-8579, Japan

Corresponding Author:

*Kengo Kubota

Department of Frontier Sciences for Advanced Environment, Graduate School of

Environmental Studies, Tohoku University, 6-6-06 Aoba, Aramaki, Aoba-ku, Sendai, Miyagi

980-8579, Japan.

Tel. & Fax: +81-22-795-5011

E-mail: kengo.kubota.a7@tohoku.ac.jp

Abstract

Nitrous oxide (N_2O) is known as a greenhouse gas as well as an ozone-depleting substance.

Wastewater treatment process is one of the sources of N_2O emission, and the high

concentrations of N_2O in off-gas were reported from an anaerobic ammonium oxidation

process. This study developed a novel N_2O removal process using a down-flow hanging

sponge reactor to remove high concentrations of N_2O. More than 96% removal efficiencies

were achieved for up to 300 ppm N_2O with 3 min gas retention time (GRT), and more than

99% removal efficiency was obtained for 2,000 ppm N_2O with 18 min GRT. A maximum

removal rate of 161 ± 26 mg-N/L-reactor/day was achieved, that was over 10 times faster than

the pioneering process. Kinetic analysis indicated that the N_2O dissolution rate is a crucial

factor in determining the N_2O removal rate in the reactor. Various N_2O reducers were detected

in reactors, and *Azonexus* was thought to play a key role. Most of the *nosZ* genes obtained

belonged to clade I and only a few clade II *nosZ* genes were retrieved.

Keywords:

Down-flow hanging sponge (DHS); kinetics; metagenome; microelectrode; nitrous oxide

(N_2O); *nosZ* gene; 16S rRNA gene amplicon

1. Introduction

Nitrous oxide (N_2O) is a greenhouse gas and an ozone-depleting substance (Ravishankara et al., 2009). Its atmospheric concentration has increased significantly over the last 100 years, reaching 336 ppb in 2022 (IPCC, 2022; Tian et al., 2020). N_2O has approximately 273 times greater global warming potential than that CO_2 and has a lifetime of 114 years in the atmosphere. The recent increase in N_2O emissions exceeds the worst-emission scenario of the IPCC; therefore, the reduction of N_2O emissions is an urgent issue globally (Tian et al., 2020). The agricultural sector is the main source of N_2O emissions, accounting for more than half of human activity-related emissions. Although their contribution is much lower, the waste and wastewater treatment sectors are also sources of N_2O.

In wastewater treatment, N_2O is generated in both aerobic and anaerobic processes related to nitrogen removal (i.e. nitrification and denitrification) by biotic and abiotic transformation processes (e.g. nitrifier denitrification, hydroxylamine oxidation, and incomplete denitrification) (Hallin et al., 2018; Sabba et al., 2018). Earlier studies identified several factors that influence N_2O generation from wastewater treatment processes (e.g. dissolved oxygen (DO), nitrite and ammonium concentrations, and the chemical oxygen demand (COD) /N ratio) (Domingo-Félez and Smets, 2019; Kampschreur et al. 2009; Vasilaki et al. 2019; Wu et al. 2020). N_2O emission mitigation approaches, such as DO control (Duan et al., 2021) and COD/N ratio control through carbon source input (Hu et al., 2013; Peng et al., 2017) were reported. However, these approaches are not necessarily universal because they are only effective under specific conditions (Han et al., 2023; Oba et al., 2024). As an alternative approach, processes removing N_2O in off-gas using microbial reactions were developed (e.g., utilising a fixed bed reactor packed with Kaldnes rings (Frutos et al., 2016) or biofilters filled with polyurethane foam (Han et al., 2023; Yoon et al., 2019,

2017)). These studies targeted 100–300 ppm of N_2O in either N_2 (anaerobic) or air (aerobic)

and successfully reduced N_2O in the gaseous phase.

In addition to conventional nitrification-denitrification processes, anaerobic

ammonium oxidation (anammox) is being considered for the removal of nitrogen from

wastewater. More than 100 anammox-based full-scale plants are used globally to treat

industrial and municipal wastewater (Lackner et al., 2014). The generation of N_2O from

anoxic anammox tanks were reported (Ali et al., 2016; Kampschreur et al., 2009, 2008;

Okabe et al., 2011; Vasilaki et al., 2019) with concentrations reaching 1,300 ppm

(laboratory-scale) (Okabe et al., 2011) and 4,000 ppm (full-scale) (Kampschreur et al., 2008)

in off-gas, which is much higher than that of the previously tested concentrations for N_2O

removal (200 ppm in N_2) (Yoon et al., 2017).

To remove high concentrations of N_2O generated from anaerobic/anoxic wastewater

treatment processes, such as anammox processes, we focused on down-flow hanging sponge

(DHS) processes. DHS was originally developed for wastewater treatment, maintaining high

sludge biomass in sponge media and resulting in effluent water quality comparable to that of

conventional activated sludge processes. It allows aerobic treatment without aeration by

supplying oxygen from the air due to gas-liquid equilibrium, while wastewater flows from top

to bottom due to gravity (Kubota et al., 2024). The application of DHS reactors for gaseous

substances such as hydrogen sulfide and toluene were reported by using the closed reactors

(Tanikawa et al., 2022; Yamaguchi et al., 2018).

In this study, we developed a process that rapidly removed high concentrations of N_2O

using DHS. The N_2O removal performance of the DHS reactors was evaluated by feeding

different concentrations of N_2O (5–2,000ppm) and supplying the supernatant from an

anaerobic sewage sludge digester as a carbon source. Microelectrode experiments were

conducted to assess the kinetics of the N_2O reduction. Eventually, the microorganisms that

may be involved in N₂O removal were identified using 16S rRNA gene amplicon and shotgun

metagenome analyses.

2. Material and Methods

2.1 Reactor configuration and operation

A DHS reactor consisting of fifteen sponge carriers with polyethene plastic net rings was

placed in a closed column with a volume of 1.23 L. The carriers were vertically connected

and suspended in the column. The size of polyurethane sponge was 30 mm in diameter and 30

mm in height. The total sponge volume was 0.32 L, resulting in a packing density of 26%.

Anaerobic sludge obtained from an anaerobic digester treating sewage sludge under

mesophilic conditions was used as the seed sludge. The supernatant of the digested sludge

was used as a carbon source and fed from the top of the reactor with a hydraulic retention

time (HRT) of 3–24 hours based on the sponge volume. Feeding was performed intermittently

using a timer. N_2 gas containing 5, 40, 300 or 2,000 ppm N_2O was subjected to the closed

column from the inlet near the bottom of the reactor. The outlet for the treated gas was placed

near the top of the reactor, resulting in gas flow from the bottom to the top. The gas flow rate

was adjusted using a gas meter (RK1200; KOFLOC, Kyoto, Japan). The gas retention time

(GRT) was adjusted by varying the gas flow rate. The reactor was set in an incubation

chamber and operated anaerobically at 25ºC in the dark. The GRT was calculated by using a

gas volume at 25ºC and an effective reaction volume of 0.91 L. Nitrogen loading of the

reactor was calculated by using a reactor volume of 1.23 L and the amount of nitrogen under

the standard temperature (0ºC). A schematic of the experiment is shown in Fig.1.

Fig. 1. Schematic diagram of the experiment. The sludge samples collected from the 4th, 8th

and 11th sponges from the top were used for the microelectrode experiments. The 4th and

11th sponges were used for 16S rRNA amplicon and metagenome analyses.

2.2 Measurement of gaseous N_2O concentration

The effluent gas from the closed DHS reactor was measured every 1–2 days to evaluate

N_2O removal performance. In this study, two sets of electron capture detector gas

chromatography (ECD-GC) (GC-2014, Shimadzu, Kyoto, Japan) with different columns were

used, depending on the N_2O concentration. Both ECD-GCs were equipped with a 63Ni ECD,

and N_2 was used as the carrier gas. For the measurement of lower N_2O concentrations (<

approximately 40 ppm), an ECD-GC with a tandem Porapak Q column (80/100 mesh; 3.0 mm

× 1.0 m and 3.0 mm × 2.0 m, GL Sciences, Japan) was used. The temperatures were set at

80°C, 100°C, and 340ºC for the column, injector, and detector, respectively. For the

measurement of higher N_2O concentrations (> approximately 40 ppm), an ECD-GC with a

TC-BOND Q column (0.53 mm × 30 m, df=20 μm, GL Sciences, Japan) was used. The

temperatures were set at 50°C, 280°C, and 300°C for the column, injector, and detector,

respectively.

2.3 Water quality analysis and sludge sampling

Influent water and effluent water from the DHS reactor were sampled to evaluate

changes in water quality. COD was measured using a HACH water quality analyser (DR890,

HACH, Loveland, CO, USA).

Sludge samples were collected on the final experimental day. A sponge was immersed

in 0.05 × phosphate buffered saline (PBS; 130 mM NaCl, 10.8 mM Na_2HPO_4, 4.2 mM

NaH_2PO_4, pH 7.4) in a plastic bag, and sludge was suspended in PBS by squeezing the

sponges. Part of the suspended sludge was used for microelectrode experiments (see Section

2.4). The other part was centrifuged at 2935×g for 15 min at 4°C. After removing the

supernatant, a portion of the sludge was stored at -20°C for DNA extraction. The other part

was used to measure the suspended solids (SS) and volatile suspended solids (VSS) according

to the standard methods (APHA, 2017).

2.4 Microelectrode experiment for measuring N_2O consumption rate

The N_2O consumption rates of the sludge samples were measured using an N_2O

micro-respiration system with amperometric microsensors (Unisense, Aarhus, Denmark) (Fig.

S1). Measurements and subsequent data analyses were conducted in accordance with an

earlier study (Suenaga et al., 2018). Briefly, the sludge samples collected from the 4th, 8th

and 11th sponges (Fig. 1) were used for the experiments. The sludge samples were initially

diluted with anaerobic sludge digester supernatant, which was filter sterilised by using 0.22

μm Stericup® filter (S2GVU01RE, Merck Millipore, Germany) to make sludge concentration

suitable for the microelectrode experiment. Approximately 8 ml double-port chamber

(Unisense, Aarhus, Denmark) was filled with the sample and placed in a water bath controlled

at 25°C. N_2O sensors were inserted into the chamber, and a certain amount (30–40 µl) of N_2O

water prepared by aerating pure N_2O gas was injected into the chamber using a Hamilton

syringe. The sample was stirred at 600 rpm, and the N_2O concentration was continuously

recorded using SensorTrace Suite ver. 2.8.0 (Unisense). After the injected N_2O was

completely consumed, fresh N_2O water was injected, and N_2O consumption was measured.

For the data analysis, noise removal and plot smoothing were performed using Sigma

Plot 13.0 (Systat Software, San Jose, CA, USA). The theoretical maximum consumption rate

of N_2O (V_{max}) was obtained using the Michaelis-Menten equation and the Excel solver

function (Suenaga et al., 2018). The theoretical maximum N_2O removal rate per reactor

volume (mg-N/L-reactor/day) was calculated by multiplying V_{max} (N_2O removal rate per

VSS) by the amount of VSS in the reactor.

2.5 16S rRNA gene amplicon sequence analysis

Sludge samples collected from the 4th and 11th sponges of each reactor were

subjected to 16S rRNA gene amplicon sequencing analysis. DNA extraction was performed

using ISOIL for Beads Beating kits (Nippon Gene, Tokyo, Japan), according to the

manufacturer's instructions. Prokaryotic 16S rRNA genes were amplified using 341f

(5'-CCTAYGGGGRBGCASCAG-3') and 806r mix (806r (5'-

GGACTACHVGGGGTHTCTAAT-3') and 806r-P (GGACTACCAGGGTATCTAAG-3') in

a 30:1 ratio) (Matsubayashi et al., 2017). The PCR conditions for library preparation were as

described earlier (Ni et al., 2020). 16S rRNA gene amplicon sequencing using the MiSeq

Reagent Kit v3 600 cycles was outsourced to the Bioengineering Lab. Co., Ltd. (Kanagawa,

Japan). Nucleotide sequence data are available in the DDBJ Sequence Read Archive

accession number PRJDB18886.

Data analysis was conducted using QIIME2 ver. 2023.7 (Bolyen et al., 2019).

Quality trimming, primer sequence removal, paired-end assembly, and chimaera checking of

the raw 16S rRNA gene sequencing data were performed using DADA2 (Callahan et al.,

2016). The 16S rRNA gene sequences with ≥ 97% identity were clustered into operational

taxonomic units (OTUs) using VSEAECH (Rognes et al., 2016). The OTUs were classified

using the Greengens2 database (McDonald et al., 2023).

2.6 Shotgun metagenome analysis

DNA extracted from the 4th and 11th sponges in each reactor was subjected to

short-read metagenomic analysis. Library preparation and sequencing were outsourced to the

Bioengineering Lab. Co., Ltd.. In brief, sequencing libraries were prepared using the

MGIEasy FS DNA Library Prep Set (MGI Tech, Shenzhen, China) and 150 bp paired-end

reads were generated using DNBSEQ-G400 (MGI Tech). Nucleotide sequence data are

available in the DDBJ Sequence Read Archive accession number PRJDB18886.

The generated reads were subjected to SOAPnuke 2.0.6 (Chen et al., 2018) to

remove the adaptor sequences and low-quality reads. Assembly was performed using the

workflow "aviary assemble" in Aviary 0.8.3 (Newell et al., 2023). Contigs shorter than 600

bp were excluded from subsequent analyses. Contigs containing putative *nosZ* gene sequences

were retrieved using the BLASTN algorithm (Altschul et al., 1990) and a *nosZ* database

(Zheng et al., 2023). The coverage of contigs was analysed coverM 0.7.0 (Aroney et al.,

2024), and the relative abundance of each *nosZ* gene was calculated. The obtained contigs

were subjected to the workflow "aviary annotate" and Prokka 1.14.6 (Seemann, 2014) for

functional annotation. Eventually, contigs containing NosZ protein sequences with ≥ 300

amino acids were extracted to construct a phylogenetic tree.

A phylogenetic tree of the NosZ sequences obtained in this study was constructed using

known reference NosZ sequences. The reference sequences were obtained by clustering the

nosZ gene sequences (Zheng et al., 2023) with 70% sequence identity using VSEARCH

2.27.0. The reference sequences (n=574) were converted to amino acid sequences. The amino

acid sequences were aligned using MAFFT (Katoh et al., 2002) and trimmed using TrimAl

(Capella-Gutiérrez et al., 2009). A phylogenetic tree was constructed using IQ-tree2 (Minh et

al., 2020). The best-fit model was LG + F + R10, as determined using ModelFinder

(Kalyaanamoorthy et al., 2017). The phylogenetic tree was visualised using iTOL v6 (Letunic

and Bork, 2021).

3. Results

3.1 N$_2$O removal performance by DHS reactors

In this study, the continuous treatment of gaseous N$_2$O was conducted using DHS

reactors. The N$_2$O removal performance was evaluated using different concentrations of N$_2$O

in N$_2$ (5, 40, 300 and 2,000 ppm) under various N$_2$O loads by changing the gas flow rates

(shortest GRT of 3 min) (Fig. 2 and Tables S1 and S2). Hereafter, each reactor is denoted as 5,

40, 300, and 2,000 ppm N$_2$O reactor.

The 5 ppm N$_2$O reactor (Fig. 2a and Table S1) started with a GRT of 18 min. The N$_2$O

removal efficiency reached over 90% after one day, and high removal performance was kept

even at a GRT of 9.1 and 4.6 min. Finally, the removal efficiency of 97 ± 5.4% was obtained

under the GRT of 3.0 min with the N$_2$O removal rate of 2.0 ± 0.1 mg-N/L-reactor/day.

The 40 ppm N$_2$O reactor (Fig. 2b, Table S1) also showed high removal efficiency after

starting up, showing 95 ± 3.9% and 99 ± 0.9% removal efficiency under the GRT of 18 min

and 9.1 min by day 20, respectively. When the GRT was shortened to 6.1 min, the removal

efficiency dropped to 74 ± 17% (days 20–50) due to insufficient COD supply (Fig. 2b and

Tables S1 & S2). After supplying sufficient COD, N$_2$O removal became stable with the

removal efficiency of 96 ± 3.4% under the GRT of 3.6 min (days 71–85, removal rate; 13 ±

0.5 mg-N/L-reactor/day).

The N$_2$O removal performance of the 300 ppm N$_2$O reactor (Fig. 2c and Table S1) was

similar to the 40 ppm N$_2$O reactor. Over 99% removal efficiency was obtained under the GRT

as short as 6.1 min (days 61–70), except for the term of days 20–50, during which the COD

supply was deficient, and the removal efficiency dropped to $39 \pm 16\%$. On day 70, reactor

operation was stopped for unavoidable reasons (Fig. 2c). After a few weeks of suspension, the

reactor was restarted with new sponges and seed sludge by feeding 300 ppm N_2O gas with a

GRT of 6.1 min (the day of re-start-up was set as day 71 for convenience). An N_2O removal

rate of over 97% was achieved after four days of operation. The GRT was further shortened to

3.0 min, resulting in the N_2O removal efficiency of $94 \pm 1.5\%$ (days 108–117, removal rate;

113 ± 1.8 mg-N/L-reactor/day).

The 2,000 ppm N_2O reactor (Fig. 2d and Table S1) was initially operated at a GRT of 18

min. The removal efficiency in the first week was only $57 \pm 1.5\%$; therefore, the GRT was

extended to 36 min, resulting in the removal efficiency of $98 \pm 6.7\%$. The GRT was set at 18

min again, and low removal efficiency of $36 \pm 18\%$ was observed because of insufficient

COD supply (days 20–50) (Fig. 2d and Tables S1 and S2). High removal efficiency of $99 \pm$

0.6% was achieved with increased organic loading rate (days 61–70). The reactor was stopped

after 70 days of operation. Similar to the 300 ppm N_2O reactor, new seed sludge was

inoculated, and the reactor was restarted with a GRT of 18 min. The removal efficiency

reached $\geq 99\%$ again after 12 days of operation, and the stable and high removal efficiency of

$99 \pm 0.1\%$ was observed on days 83–86 (removal rate; 132 ± 0.1 mg-N/L-reactor/day) (Fig.

2d and Table S1). High removal efficiency was not achieved even under higher organic

loading rate at the GRT of 9.1 min. Lower N_2O removal efficiency of $61 \pm 10\%$ was obtained

(days 87–119), but the highest N_2O removal rate of 161 ± 26 mg-N/L-reactor/day was

achieved in this period.

◆ Influent gas   ● Effluent gas   ■ Organic loading rate (OLR)   — Gas retention time

Fig. 2. Nitrous oxide (N_2O) removal performance. Different concentrations of N_2O in

nitrogen gas were treated under different gas retention times and organic loadings. a; 5 ppm

N_2O, b; 40 ppm N_2O, c; 300 ppm N_2O, d; 2,000 ppm N_2O.

3.2 N_2O consumption rate

The N_2O consumption rates of the sludge collected from the 300 ppm and 2,000 ppm

N_2O reactors were measured using microelectrodes, as described earlier (Suenaga et al. 2018)

(Fig. S1). Theoretical maximum N_2O removal rates calculated using the Michaelis-Menten

equation were $1,189 \pm 257$ mg-N/L-reactor/day and $1,468 \pm 186$ mg-N/L-reactor/day at the

300 ppm and 2,000 ppm N_2O reactor, respectively (Table 1). Simultaneously, the actual

highest N_2O consumption rates of the reactors were 113 ± 1.8 mg-N/L-reactor/day (days

108–117 for the 300 ppm N_2O reactor) and 161 ± 26 mg-N/L-reactor/day (days 102–119 for

the 2,000 ppm N_2O reactor). These values were approximately 10% of the theoretical

maximum N_2O consumption rate.

Table 1. Nitrous oxide removal rates.

Reactor	Maximum N_2O removal rate of the reactor (mg-N/L-reactor/day)	The calculated theoretical N_2O removal rate (based on the Michaelis–Menten equation) (mg-N/L-reactor/day) [a]
300 ppm N_2O	113 ± 1.8 (days 108–117)	$1,189 \pm 257$
2,000 ppm N_2O	161 ± 26 (days 102–119)	$1,468 \pm 186$

[a] N_2O removal rate per reactor volume was calculated based on the amount of volatile

suspended solids retained in the reactor.

3.3 Microbial community involved in N_2O reduction

3.3.1 16S rRNA gene amplicon analysis

The microbial communities of the sludge samples evaluated by 16S rRNA gene

amplicon analysis are shown in Table S3, and the top 30 OTUs with average relative

abundances are summarised in Fig. 3. The microbial communities built in the reactors

differed from those in the seed sludge and substrate, as demonstrated by principal coordinate

analysis (PCoA) (Fig. S2). The microbial community structures changed with N_2O

concentrations and along the height of the reactors, although the N_2O concentrations had the

greatest effect.

Some OTUs with high relative abundance were similar to known N_2O-reducing

microorganisms (Fig. 3). OTU0001, which is close to *Azonexus_595978*, was the most

abundant member in all reactors. *Azonexus* is found in partial-denitrification-anammox

processes and anaerobic manure digestate and is expected to be involved in N_2O reduction

(Huang et al., 2024; Wang et al., 2023). In addition to *Azonexus*, several OTUs close to

known N_2O reducers were identified, including *Giesbergeria* (OTU0020) (Zhang et al., 2022),

Thauera_A_597130 (OTU0013) (Huang et al., 2024), *Denitrificimonas* (OTU0029) (Wang et

al., 2024), *Oblitimonas* (OTU0019) (Ramírez-Fernández et al., 2021), and *Sulfurivermis*

(OTU0010) (Liu et al., 2023). OTU0020 and OTU0029 were found in reactors with lower

N_2O concentrations of 5 and 40 ppm, respectively, whereas OTU0019 was found in reactors

with higher N_2O concentrations of 300 ppm and 2,000 ppm. OTU0010 was dominant only in

the 2,000 ppm N_2O reactor. Thus, the known N_2O-reducing microorganisms were enriched in

the DHS reactors with various concentrations of N_2O.

In addition to OTUs close to known N_2O reducers, the relative abundances of many

OTUs increased after feeding with N_2O. Although they are not close relatives of N_2O

reducers at the genus level, some OTUs belong to the same family as N_2O reducers (e.g.

OTU0005 and OTU0009) (Isokpehi et al., 2024). The OTUs increasing the relative

abundance could potentially reduce N_2O, although this was difficult to demonstrate using

only 16S rRNA gene amplicon analysis.

Fig. 3. Top 30 OTUs in the average relative abundance. The size of the circle indicates the

relative abundance of OTUs in each sample. 4th: the 4th sponge, 11th: the 11th sponge. Seed

sludge: sludge from a mesophilic anaerobic sewage sludge digester.

3.3.2 Metagenome analysis of *nosZ* gene

In total, 229 contigs, including a sequence homologous to *nosZ*, were obtained (matched

by BLASTN with sequences longer than approximately 600 bp) (Table S4). The most

abundant *nosZ* genes retrieved from all reactors were similar to those in *Azonexus*. In the

2,000 ppm N_2O reactor, other than *Azonexus nosZ* gene, *Sulfurivermis*-related *nosZ* gene was

obtained in high abundance. This *nosZ* gene was not detected in the other reactors.

Additionally, the *Aliarcobacter*-related *nosZ* gene was only found in the 40 ppm N_2O reactor,

which was identical to the amplicon analysis (i.e. OTU0009). Besides these microorganisms,

nosZ gene-harboring microorganisms detected in both 16S rRNA gene amplicons and

metagenomic analyses were *Giesbergeria* and *Thauera*.

The phylogenetic tree of *nosZ* extracted from metagenomic 229 contigs (Fig. 4) revealed

that clade I *nosZ* gene was more diverse and abundant than clade II *nosZ* gene in the reactors.

The major N_2O reducers, such as *Azonexus*, *Pseudomonas_C*, *Sulfurivermis, Giesbergeria*

and *Thauera,* belong clade I. Clade II *nosZ* genes higher than 1% relative abundance were

most obtained from 2,000 ppm N_2O reactor (e.g. *Aequorivit*, *Pelobium*, *Planobacterium*,

Kaistella and UBA7692). *Aequorivit*-related *nosZ* gene was ranked 4th in relative abundance

in the 2,000 ppm N_2O reactor. *Aequorivit* is known not to reduce nitrate (Bowman and

Nichols, 2002) and most likely reduce N_2O as a non-denitrifier, which is often found in clade

II *nosZ* gene-harbouring microorganisms (Hallin et al., 2018; Sanford et al., 2012). However,

many of these known clade II *nosZ* gene harbouring organisms were not detected or less than

0.1% in relative abundance, as determined by amplicon analysis.

Fig. 4. Phylogenetic tree of NosZ protein. The size of the circles indicates the relative

abundance of read counts of contigs with the *nosZ* gene. The colours represent the nitrous

oxide concentrations fed to the reactors. 4th: the 4th sponge, 11th: the 11th sponge.

4. Discussion

4.1 Ultra-fast bioprocess for mitigating high concentration N₂O emission

This study demonstrated that the DHS is able to remove N$_2$O in N$_2$ gas with removal

efficiencies of over 96% for concentrations of up to 300 ppm at 3 min GRT and 2,000 ppm at

18 min GRT with the supply of real wastewater, i.e., the supernatant of sewage sludge

digestate. The highest removal rate of 161 ± 26 mg-N/L-reactor/day was achieved when 2,000

ppm N$_2$O was supplied with a GRT of 9.1 min. One study investigated the removal of N$_2$O in

N$_2$ gas using a biofilter reactor packed with 2 cm × 2 cm × 2 cm polyurethane cubes (Yoon et

al., 2017). This study achieved a removal efficiency of ≥ 99% for 200 ppm N$_2$O in N$_2$ gas at

GRT of 8.9 min with synthetic wastewater and a removal efficiency of 80–90% at GRT of

32.2 min with wastewater from a primary sedimentation basin treating sewage. Our study

demonstrated a much faster treatment (over 10 times) capable of removing higher

concentrations of N_2O in N_2 gas compared to that of a previous study, even with the use of

real wastewater.

High concentrations of N_2O in off-gas were reported, especially from anammox

processes, e.g. 0.4–240 ppm (Ali et al., 2016) and 93–1,358 ppm (Okabe et al., 2011) from

lab-scale reactors and >4,000 ppm (Kampschreur et al., 2008) from a full-scale reactor

although the anammox reaction itself is thought not to produce N_2O (Harris et al., 2015;

Kartal et al., 2007). Although the highest concentration tested in this study (i.e., 2,000 ppm)

was lower than 4,000 ppm, it showed the potential to remove such high concentrations of N_2O

from nitrogen gas. A longer GRT is most probably needed, although a higher removal

efficiency can be achieved with a sufficient supply of electron donors, which is directly

related to the removal efficiencies of the reactor, as shown in Fig. 2bcd (days 20–50 for the 40,

300 and 2,000 ppm reactors).

To minimise the amount of N_2O emission from wastewater treatment processes, research

focusing solely on N_2O removal efficiency can be misleading. In this study, a removal

efficiency of approximately 99% was achieved with a GRT of 18 minutes when 2,000 ppm of

N_2O was supplied. However, approximately 20 ppm of N_2O still remained in the off-gas.

Particularly in cases where high concentrations of N_2O are treated, implementing an

additional treatment process for N_2O removal from the off-gas can further minimise the final

N_2O emissions from the process (e.g., a series of DHS reactors).

4.2 Kinetics of N_2O reduction in bioreactor

Microelectrode experiments showed an approximately 10-fold faster kinetic potential

(Table 1). This suggests that the microbial community inhabiting the reactor had a much

greater capacity to reduce N_2O to N_2. Dissolved N_2O was supplied directly to the stirred

sludge during the microelectrode experiments (Fig. S1). On the other hand, in the reactor,

gaseous N_2O needs to be initially dissolved in the liquid, and then microorganisms can utilise

the dissolved N_2O. Thus, the N_2O dissolution rate is the key to determine the removal rate in

the reactor.

The dissolution rate from gas to liquid can be explained using the Nernst-Noyes-Whitney

equation (Dokoumetzidis and Macheras, 2006; Noyes and Whitney, 1897). In the

Nernst-Noyes-Whitney equation, the dissolution rate constant (given by the diffusion

coefficient of the substance, volume of the solution, and thickness of the diffusion layer),

surface area, concentration of the dissolved substance at a given time t, and solubility

concentration of the substance were considered. Without N_2O consumption in the liquid phase,

the dissolution rate decreases as N_2O dissolves and eventually reaches equilibrium, at which

point no more N_2O is removed from the gas phase. However, when microorganisms are

present in the liquid phase and actively consume N_2O, the N_2O concentration in the liquid

remains low, and the diffusion layer becomes thinner, allowing the dissolution rate to remain

high.

To achieve faster dissolution rates, it is suggested to increase the surface area of the

carrier or enhance the microbial activity to decrease the dissolved N_2O concentration in the

liquid phase and reduce the thickness of the diffusion layer. One could consider supplying

different substrates utilised by other microorganisms to enhance microbial activity to enable

faster N_2O reduction. An earlier study (Yoon et al., 2017) reported a higher N_2O removal

efficiency with synthetic wastewater than that with real wastewater, i.e., effluent from a

primary sedimentation basin treating sewage. Additionally, increasing the temperature would

help accelerate the microbial N_2O reduction rate and increase the diffusion coefficient.

4.3 Nitrous oxide reducers in bioreactors

Sludge from the sponges in each reactor was collected on the last day of operation and

subjected to 16S rRNA amplicon sequencing analysis. A comparison of the microbial

community structure based on PCoA (Fig. S2) showed that the microbial communities in the

N_2O-reducing DHS reactors were different from those in the seed sludge, i.e., sludge from an

anaerobic sewage sludge digester, as well as those in the supernatant of an anaerobic sludge

digestate, i.e., the substrate for denitrification. It also showed a change in the microbial

community under different N_2O concentrations, as well as in the height of the reactor (Figs. 3

and S2). In a DHS reactor, COD load changes along the height (Kubota et al., 2014), i.e.,

higher and lower COD concentrations occur in the upper and lower part of the reactor,

respectively. Additionally, the supernatant of the anaerobic sludge digestate contains diverse

electron donors. These characteristics provide a habitat for a variety of microorganisms in the

reactors compared with that of earlier studies using a simple substrate for N_2O reduction (e.g.,

acetate for Conthe et al. 2018).

In the N_2O reducing DHS reactors, *Azonexus* was the most abundant genus after both

amplicon and metagenome analyses (Fig. 3 and Table S4). *Azonexus* can utilise intermediates

of anaerobic organic degradation such as acetate and propionate (Quan et al., 2006). The

digestate supernatant contained a small number of fatty acids. Additionally, the substrate may

be anaerobically degraded in the reactor, and the intermediates may be used by *Azonexus* as

carbon sources to reduce N_2O. An earlier study detected *Azonexus* in a bioreactor

continuously supplying N_2O and acetate under anaerobic conditions (Conthe et al., 2018).

Thus, *Azonexus* plays a key role in N_2O removal.

Other than *Azonexus*, *Sulfurivermis*, which can also utilise acetate and propionate for

nitrate reduction (Watanabe et al., 2019), was found to be the second most abundant

denitrifier, with high relative abundance (26% in the 4th sponge and 17% in the 11th sponge)

in the 2,000 ppm reactor. Additionally, *Aliarcobacter* was found in the 40 ppm N_2O reactor.

Because a slightly larger sponge medium (30 mm in diameter and 30 mm in height) was used,

a gradient of dissolved N_2O concentration occurred in the sponge media, which may have

involved a variety of microorganisms in N_2O reduction.

The *nosZ* genes retrieved from the reactors showed that clade I *nosZ* was more

predominant and diverse than clade II *nosZ* (Fig. 4). All the top three relatively abundant *nosZ*

genes belonged to clade I and only a small number of clade II *nosZ* genes were obtained with

low relative abundance. A higher number of clade II *nosZ* genes were obtained from the 2,000

ppm N_2O reactor. Generally, microorganisms that possess the clade II *nosZ* gene have lower

half-saturation constant (K_m) values and higher affinity than clade I N_2O-reducing

microorganisms and are more abundant in environments where low concentrations of N_2O are

available (Suenaga et al., 2018; Yoon et al., 2016). This suggests that niche

compartmentalisation of clade I N_2O-reduers and clade II N_2O-reducers may exist in sponge

media. Faster-growing-and-low-affinity microorganisms (i.e. those with clade I *nosZ* genes,

such as *Azonexus*) may be present in the outer layer of the sponge, whereas

slow-growing-and-high-affinity microorganisms (i.e. those with clade II *nosZ* genes) may be

present in the inner part of the sponge. In the 2,000 ppm N_2O reactor, the concentration

gradient of dissolved N_2O may have occurred deeper in the sponge, resulting in a more

suitable environment for those harbouring the clade II *nosZ* gene.

5. Conclusion

In this study, a novel ultra-fast N_2O removal process using a DHS reactor was

developed to remove high concentrations of N_2O generated from anaerobic/anoxic wastewater

treatment processes such as an anammox process. Continuous experiments revealed that more

than 96% removal rates were achieved for up to 300 ppm N_2O gas with 3 min GRT and 2,000

ppm N_2O with 18 min GRT. The maximum N_2O removal rate of 161 ± 26

mg-N/L-reactor/day was obtained when 2,000 ppm N_2O was supplied with the GRT of 9.1

min, which is over 10 times faster than the pioneering process. Additionally, the lack of

organic supply immediately deteriorates the N_2O removal performance. Kinetic analysis

indicated that the N_2O dissolution rate is a crucial factor in determining the N_2O removal rate

in the reactor. Amplicon and metagenome analyses showed that *Azonexus* played a key role in

N_2O removal. A gradient of dissolved N_2O concentration may occur in the sponge carriers,

resulting in the involvement of various microorganisms in N_2O reduction. Most of the *nosZ*

genes obtained from the reactors belonged to clade I and only a few fractions were clade II

nosZ genes, suggesting the possibility of niche compartmentalisation between clade I

N_2O-reducers and clade II N_2O-reducers in the sponge with gradient of dissolved N_2O

concentrations.

Acknowledgements

This study was supported by KAKENHI grants (JP19KK0371, JP21H01460) from the Japan

Society for the Promotion of Science (JSPS), the Moonshot project JPNP18016,

commissioned by the New Energy and Industrial Technology Development Organization

(NEDO) and the MEXT WISE Program for Sustainability in Dynamic Earth (SyDE), Japan.

RM was supported by a Grant-in-Aid for JSPS Fellows (JP24KJ0429).

References

Ali, M., Rathnayake, R.M.L.D., Zhang, L., Ishii, S., Kindaichi, T., Satoh, H., Toyoda, S.,

Yoshida, N., Okabe, S., 2016. Source identification of nitrous oxide emission pathways

from a single-stage nitritation-anammox granular reactor. Water Res. 102, 147–157.

https://doi.org/10.1016/j.watres.2016.06.034

Altschul, S.F., Gish, W., Miller, W., Myers, E.W., Lipman, D.J., 1990. Basic Local

Alignment Search Tool. J. Mol. Biol. 215, 403–410.

APHP, 2017. Standard methods for the examination of water and wastewater, 23rd ed,

American Public Health Association,Washington DC.

Aroney, S.T.N., Newell, R.J.P., Nissen, J., Camargo, A.P., Tyson, G.W., Woodcroft, B.J.,

2024. CoverM: Read coverage calculator for metagenomics (v0.7.0). Zenodo.

https://doi.org/10.5281/zenodo.10531254

Bolyen, E., Rideout, J.R., Dillon, M.R., Bokulich, N.A., Abnet, C.C., Al-Ghalith, G.A.,

Alexander, H., Alm, E.J., Arumugam, M., Asnicar, F., Bai, Y., Bisanz, J.E., Bittinger, K.,

Brejnrod, A., Brislawn, C.J., Brown, C.T., Callahan, B.J., Caraballo-Rodríguez, A.M.,

Chase, J., Cope, E.K., Da Silva, R., Diener, C., Dorrestein, P.C., Douglas, G.M., Durall,

D.M., Duvallet, C., Edwardson, C.F., Ernst, M., Estaki, M., Fouquier, J., Gauglitz, J.M.,

Gibbons, S.M., Gibson, D.L., Gonzalez, A., Gorlick, K., Guo, J., Hillmann, B., Holmes,

S., Holste, H., Huttenhower, C., Huttley, G.A., Janssen, S., Jarmusch, A.K., Jiang, L.,

Kaehler, B.D., Kang, K. Bin, Keefe, C.R., Keim, P., Kelley, S.T., Knights, D., Koester,

I., Kosciolek, T., Kreps, J., Langille, M.G.I., Lee, J., Ley, R., Liu, Y.X., Loftfield, E.,

Lozupone, C., Maher, M., Marotz, C., Martin, B.D., McDonald, D., McIver, L.J., Melnik,

A. V., Metcalf, J.L., Morgan, S.C., Morton, J.T., Naimey, A.T., Navas-Molina, J.A.,

Nothias, L.F., Orchanian, S.B., Pearson, T., Peoples, S.L., Petras, D., Preuss, M.L.,

Pruesse, E., Rasmussen, L.B., Rivers, A., Robeson, M.S., Rosenthal, P., Segata, N.,

Shaffer, M., Shiffer, A., Sinha, R., Song, S.J., Spear, J.R., Swafford, A.D., Thompson,

L.R., Torres, P.J., Trinh, P., Tripathi, A., Turnbaugh, P.J., Ul-Hasan, S., van der Hooft,

J.J.J., Vargas, F., Vázquez-Baeza, Y., Vogtmann, E., von Hippel, M., Walters, W., Wan,

Y., Wang, M., Warren, J., Weber, K.C., Williamson, C.H.D., Willis, A.D., Xu, Z.Z.,

Zaneveld, J.R., Zhang, Y., Zhu, Q., Knight, R., Caporaso, J.G., 2019. Reproducible,

interactive, scalable and extensible microbiome data science using QIIME 2. Nat.

Biotechnol. 37, 852–857. https://doi.org/10.1038/s41587-019-0209-9

Bowman, J.P., Nichols, D.S., 2002. Aequorivita gen. nov., a member of the family

Flavobacteriaceae isolated from terrestrial and marine Antarctic habitats. Int. J. Syst.

Evol. Microbiol. 52, 1533–1541. https://doi.org/10.1099/ijs.0.01976-0.The

Callahan, B.J., McMurdie, P.J., Rosen, M.J., Han, A.W., Johnson, A.J.A., Holmes, S.P., 2016.

DADA2: High-resolution sample inference from Illumina amplicon data. Nat. Methods

13, 581–583. https://doi.org/10.1038/nmeth.3869

Capella-Gutiérrez, S., Silla-Martínez, J.M., Gabaldón, T., 2009. trimAl: A tool for automated

alignment trimming in large-scale phylogenetic analyses. Bioinformatics 25, 1972–1973.

https://doi.org/10.1093/bioinformatics/btp348

Chen, Yuxin, Chen, Yongsheng, Shi, C., Huang, Z., Zhang, Y., Li, S., Li, Y., Ye, J., Yu, C.,

Li, Z., Zhang, X., Wang, J., Yang, H., Fang, L., Chen, Q., 2018. SOAPnuke: A

MapReduce acceleration-supported software for integrated quality control and

preprocessing of high-throughput sequencing data. Gigascience 7, 1–6.

https://doi.org/10.1093/gigascience/gix120

Conthe, M., Wittorf, L., Kuenen, J.G., Kleerebezem, R., Van Loosdrecht, M.C.M., Hallin, S.,

2018. Life on N_2O: Deciphering the ecophysiology of N_2O respiring bacterial

communities in a continuous culture. ISME J. 12, 1142–1153.

https://doi.org/10.1038/s41396-018-0063-7

Dokoumetzidis, A., Macheras, P., 2006. A century of dissolution research: From Noyes and

Whitney to the Biopharmaceutics Classification System. Int. J. Pharm. 321, 1–11.

https://doi.org/10.1016/j.ijpharm.2006.07.011

Domingo-Félez, C., Smets, B.F., 2019. Regulation of key N_2O production mechanisms during

biological water treatment. Curr. Opin. Biotechnol. 57, 119–126.

https://doi.org/10.1016/j.copbio.2019.03.006

Duan, H., Zhao, Y., Koch, K., Wells, G.F., Zheng, M., Yuan, Z., Ye, L., 2021. Insights into

Nitrous Oxide Mitigation Strategies in Wastewater Treatment and Challenges for Wider

Implementation. Environ. Sci. Technol. 55, 7208–7224.

https://doi.org/10.1021/acs.est.1c00840

Frutos, O.D., Quijano, G., Pérez, R., Muñoz, R., 2016. Simultaneous biological nitrous oxide

abatement and wastewater treatment in a denitrifying off-gas bioscrubber. Chem. Eng. J.

288, 28–37. https://doi.org/10.1016/j.cej.2015.11.088

Hallin, S., Philippot, L., Löffler, F.E., Sanford, R.A., Jones, C.M., 2018. Genomics and

Ecology of Novel N2O-Reducing Microorganisms. Trends Microbiol. 26, 43–55.

https://doi.org/10.1016/j.tim.2017.07.003

Han, H., Kim, D.D., Song, M.J., Yun, T., Yoon, H., Lee, H.W., Kim, Y.M., Laureni, M.,

Yoon, S., 2023. Biotrickling Filtration for the Reduction of N_2O Emitted during

Wastewater Treatment: Results from a Long-Term In Situ Pilot-Scale Testing. Environ.

Sci. Technol. 57, 3883–3892. https://doi.org/10.1021/acs.est.2c08818

Harris, E., Joss, A., Emmenegger, L., Kipf, M., Wolf, B., Mohn, J., Wunderlin, P., 2015.

Isotopic evidence for nitrous oxide production pathways in a partial nitritation-anammox

reactor. Water Res. 83, 258–270. https://doi.org/10.1016/j.watres.2015.06.040

Hu, Z., Zhang, J., Xie, H., Liang, S., Li, S., 2013. Minimization of nitrous oxide emission

from anoxic-oxic biological nitrogen removal process: Effect of influent COD/NH_4^+

ratio and feeding strategy. J. Biosci. Bioeng. 115, 272–278.

https://doi.org/10.1016/j.jbiosc.2012.09.016

Huang, K., He, Y., Wang, W., Jiang, R., Zhang, Y., Li, J., Zhang, X.X., Wang, D., 2024.

Temporal differentiation in the adaptation of functional bacteria to low-temperature

stress in partial denitrification and anammox system. Environ. Res. 244, 117933.

https://doi.org/10.1016/j.envres.2023.117933

IPCC, 2022. Summary for Policymakers. In: Climate Change 2022: Mitigation of Climate

Change, Cambridge University Press. https://doi.org/10.1017/9781009157926.001

Isokpehi, R.D., Kim, Y., Krejci, S.E., Trivedi, V.D., 2024. Ecological Trait-Based Digital

Categorization of Microbial Genomes for Denitrification Potential. Microorganisms 12,

791. https://doi.org/10.3390/microorganisms12040791

Kalyaanamoorthy, S., Minh, B.Q., Wong, T.K.F., Von Haeseler, A., Jermiin, L.S., 2017.

ModelFinder: Fast model selection for accurate phylogenetic estimates. Nat. Methods 14,

587–589. https://doi.org/10.1038/nmeth.4285

Kampschreur, M.J., Temmink, H., Kleerebezem, R., Jetten, M.S.M., van Loosdrecht, M.C.M.,

2009. Nitrous oxide emission during wastewater treatment. Water Res. 43, 4093–4103.

https://doi.org/10.1016/j.watres.2009.03.001

Kampschreur, M.J., van der Star, W.R.L., Wielders, H.A., Mulder, J.W., Jetten, M.S.M., van

Loosdrecht, M.C.M., 2008. Dynamics of nitric oxide and nitrous oxide emission during

full-scale reject water treatment. Water Res. 42, 812–826.

https://doi.org/10.1016/j.watres.2007.08.022

Kartal, B., Kuypers, M.M.M., Lavik, G., Schalk, J., Op Den Camp, H.J.M., Jetten, M.S.M.,

Strous, M., 2007. Anammox bacteria disguised as denitrifiers: Nitrate reduction to

dinitrogen gas via nitrite and ammonium. Environ. Microbiol. 9, 635–642.

https://doi.org/10.1111/j.1462-2920.2006.01183.x

Katoh, K., Misawa, K., Kuma, K.I., Miyata, T., 2002. MAFFT: A novel method for rapid

multiple sequence alignment based on fast Fourier transform. Nucleic Acids Res. 30,

3059–3066. https://doi.org/10.1093/nar/gkf436

Kubota, K., Hayashi, M., Matsunaga, K., Iguchi, A., Ohashi, A., Li, Y.Y., Yamaguchi, T.,

Harada, H., 2014. Microbial community composition of a down-flow hanging sponge

(DHS) reactor combined with an up-flow anaerobic sludge blanket (UASB) reactor for

the treatment of municipal sewage. Bioresour. Technol. 151, 144–150.

https://doi.org/10.1016/j.biortech.2013.10.058

Kubota, K., Otani, T., Hariu, T., Jin, T., Tagawa, T., Morikawa, M., Li, Y.Y., 2024.

Evaluation of sewage treatment performance and duckweed biomass production

efficiency in a primary sedimentation basin + duckweed pond + downflow hanging

sponge (PSB + DWP + DHS) system. J. Water Process Eng. 65, 105818.

https://doi.org/10.1016/j.jwpe.2024.105818

Lackner, S., Gilbert, E.M., Vlaeminck, S.E., Joss, A., Horn, H., van Loosdrecht, M.C.M.,

2014. Full-scale partial nitritation/anammox experiences – An application survey. Water

Res. 55, 292–303. https://doi.org/10.1016/j.watres.2014.02.032

Letunic, I., Bork, P., 2021. Interactive tree of life (iTOL) v5: An online tool for phylogenetic

tree display and annotation. Nucleic Acids Res. 49, W293–W296.

https://doi.org/10.1093/nar/gkab301

Liu, P., Zou, S., Zhang, H., Liu, Q., Song, Z., Huang, Y., Hu, X., 2023. Genome-resolved

metagenomics provides insights into the microbial-mediated sulfur and nitrogen cycling

in temperate seagrass meadows. Front. Mar. Sci. 10, 1245288.

https://doi.org/10.3389/fmars.2023.1245288

Matsubayashi, M., Shimada, Y., Li, Y.Y., Harada, H., Kubota, K., 2017. Phylogenetic

diversity and in situ detection of eukaryotes in anaerobic sludge digesters. PLoS One

12, e0172888. https://doi.org/10.1371/journal.pone.0172888

McDonald, D., Jiang, Y., Balaban, M., Cantrell, K., Zhu, Q., Gonzalez, A., Morton, J.T.,

Nicolaou, G., Parks, D.H., Karst, S.M., Albertsen, M., Hugenholtz, P., DeSantis, T.,

Song, S.J., Bartko, A., Havulinna, A.S., Jousilahti, P., Cheng, S., Inouye, M., Niiranen,

T., Jain, M., Salomaa, V., Lahti, L., Mirarab, S., Knight, R., 2023. Greengenes2 unifies

microbial data in a single reference tree. Nat. Biotechnol. 42, 715–718.

https://doi.org/10.1038/s41587-023-01845-1

Minh, B.Q., Schmidt, H.A., Chernomor, O., Schrempf, D., Woodhams, M.D., Von Haeseler,

A., Lanfear, R., Teeling, E., 2020. IQ-TREE 2: New Models and Efficient Methods for

Phylogenetic Inference in the Genomic Era. Mol. Biol. Evol. 37, 1530–1534.

https://doi.org/10.1093/molbev/msaa015

Newell, R.J.P., Aroney, S.T.N., Zaugg, J., Sternes, P., Tyson, G.W., Woodcroft, B.J., 2023.

Aviary : Hybrid assembly and genome recovery from metagenomes with Aviary (v0.8.3).

Zenodo. https://doi.org/10.5281/zenodo.10158086.

Ni, J., Hatori, S., Wang, Y., Li, Y.Y., Kubota, K., 2020. Uncovering Viable Microbiome in

Anaerobic Sludge Digesters by Propidium Monoazide (PMA)-PCR. Microb. Ecol. 79,

925–932. https://doi.org/10.1007/s00248-019-01449-w

Noyes, A.A., Whitney, W.R., 1897. The rate of solution of solid substances in their own

solutions. J. Am. Chem. Soc. 19, 930–934.

Oba, K., Suenaga, T., Yasuda, S., Kuroiwa, M., Hori, T., Lackner, S., Terada, A., 2024. Quest

for Nitrous Oxide-reducing Bacteria Present in an Anammox Biofilm Fed with Nitrous

Oxide. Microbes Environ. 39, ME23106. https://doi.org/10.1264/jsme2.ME23106

Okabe, S., Oshiki, M., Takahashi, Y., Satoh, H., 2011. N_2O emission from a partial

nitrification-anammox process and identification of a key biological process of N2O

emission from anammox granules. Water Res. 45, 6461–6470.

https://doi.org/10.1016/j.watres.2011.09.040

Peng, L., Carvajal-Arroyo, J.M., Seuntjens, D., Prat, D., Colica, G., Pintucci, C., Vlaeminck,

S.E., 2017. Smart operation of nitritation/denitritation virtually abolishes nitrous oxide

emission during treatment of co-digested pig slurry centrate. Water Res. 127, 1–10.

https://doi.org/10.1016/j.watres.2017.09.049

Quan, Z.X., Im, W.T., Lee, S.T., 2006. *Azonexus caeni* sp. nov., a denitrifying bacterium

isolated from sludge of a wastewater treatment plant. Int. J. Syst. Evol. Microbiol. 56,

1043–1046. https://doi.org/10.1099/ijs.0.64019-0

Ramírez-Fernández, L., Orellana, L.H., Johnston, E.R., Konstantinidis, K.T., Orlando, J.,

2021. Diversity of microbial communities and genes involved in nitrous oxide emissions

in Antarctic soils impacted by marine animals as revealed by metagenomics and 100

metagenome-assembled genomes. Sci. Total Environ. 788, 147693.

https://doi.org/10.1016/j.scitotenv.2021.147693

Ravishankara, A.R., Daniel, J.S., Portmann, R.W., 2009. Nitrous oxide (N_2O): The dominant

ozone-depleting substance emitted in the 21st century. Science 326, 123–125.

https://doi.org/10.1126/science.1176985

Rognes, T., Flouri, T., Nichols, B., Quince, C., Mahé, F., 2016. VSEARCH: A versatile open

source tool for metagenomics. PeerJ 4, e2584. https://doi.org/10.7717/peerj.2584

Sabba, F., Terada, A., Wells, G., Smets, B.F., Nerenberg, R., 2018. Nitrous oxide emissions

from biofilm processes for wastewater treatment. Appl. Microbiol. Biotechnol. 102,

9815–9829. https://doi.org/10.1007/s00253-018-9332-7

Sanford, R.A., Wagner, D.D., Wu, Q., Chee-Sanford, J.C., Thomas, S.H., Cruz-García, C.,

Rodríguez, G., Massol-Deyá, A., Krishnani, K.K., Ritalahti, K.M., Nissen, S.,

Konstantinidis, K.T., Löffler, F.E., 2012. Unexpected nondenitrifier nitrous oxide

reductase gene diversity and abundance in soils. Proc. Natl. Acad. Sci. U. S. A. 109,

19709–19714. https://doi.org/10.1073/pnas.1211238109

Seemann, T., 2014. Prokka: Rapid prokaryotic genome annotation. Bioinformatics 30,

2068–2069. https://doi.org/10.1093/bioinformatics/btu153

Suenaga, T., Riya, S., Hosomi, M., Terada, A., 2018. Biokinetic characterization and

activities of N_2O-reducing bacteria in response to various oxygen levels. Front.

Microbiol. 9, 697. https://doi.org/10.3389/fmicb.2018.00697

Tanikawa, D., Motokawa, D., Itoiri, Y., Kimura, Z.I., Ito, M., Nagano, A., 2022. Biogas

purification and ammonia load reduction in sewage treatment by two-stage down-flow

hanging sponge reactor. Sci. Total Environ. 851, 158355.

https://doi.org/10.1016/j.scitotenv.2022.158355

Tian, H., Xu, R., Canadell, J.G., Thompson, R.L., Winiwarter, W., Suntharalingam, P.,

Davidson, E.A., Ciais, P., Jackson, R.B., Janssens-Maenhout, G., Prather, M.J., Regnier,

P., Pan, N., Pan, S., Peters, G.P., Shi, H., Tubiello, F.N., Zaehle, S., Zhou, F., Arneth, A.,

Battaglia, G., Berthet, S., Bopp, L., Bouwman, A.F., Buitenhuis, E.T., Chang, J.,

Chipperfield, M.P., Dangal, S.R.S., Dlugokencky, E., Elkins, J.W., Eyre, B.D., Fu, B.,

Hall, B., Ito, A., Joos, F., Krummel, P.B., Landolfi, A., Laruelle, G.G., Lauerwald, R., Li,

W., Lienert, S., Maavara, T., MacLeod, M., Millet, D.B., Olin, S., Patra, P.K., Prinn,

R.G., Raymond, P.A., Ruiz, D.J., van der Werf, G.R., Vuichard, N., Wang, J., Weiss,

R.F., Wells, K.C., Wilson, C., Yang, J., Yao, Y., 2020. A comprehensive quantification

of global nitrous oxide sources and sinks. Nature 586, 248–256.

https://doi.org/10.1038/s41586-020-2780-0

Vasilaki, V., Massara, T.M., Stanchev, P., Fatone, F., Katsou, E., 2019. A decade of nitrous

oxide (N_2O) monitoring in full-scale wastewater treatment processes: A critical review.

Water Res. 161, 392–412. https://doi.org/10.1016/j.watres.2019.04.022

Wang, S., Yuan, C., Xu, C., Li, D., Zhang, H., Wang, J., Wang, X., Li, Y., Jiao, D., Yuan, S.,

Chen, H., Qiu, D., 2024. Denitrificimonas halotolerans sp. nov., a novel species isolated

from UASB sludge treating landfill leachate. Antonie van Leeuwenhoek, Int. J. Gen.

Mol. Microbiol. 117, 91. https://doi.org/10.1007/s10482-024-01987-5

Wang, X., Xiang, B., Li, J., Zhang, M., Frostegard, A., Bakken, L., Zhang, X., 2023. Using

adaptive and aggressive N_2O-reducing bacteria to augment digestate fertilizer for

mitigating N_2O emissions from agricultural soils. Sci. Total Environ. 903, 166284.

https://doi.org/10.1016/j.scitotenv.2023.166284

Watanabe, T., Kojima, H., Umezawa, K., Hori, C., Takasuka, T.E., Kato, Y., Fukui, M., 2019.

Genomes of neutrophilic sulfur-oxidizing chemolithoautotrophs representing 9

proteobacterial species from 8 genera. Front. Microbiol. 10, 00316.

https://doi.org/10.3389/fmicb.2019.00316

Wu, L., Peng, L., Wei, W., Wang, D., Ni, B.J., 2020. Nitrous oxide production from

wastewater treatment: The potential as energy resource rather than potent greenhouse gas.

J. Hazard. Mater. 387, 121694. https://doi.org/10.1016/j.jhazmat.2019.121694

Yamaguchi, Tsuyoshi, Nakamura, S., Hatamoto, M., Tamura, E., Tanikawa, D., Kawakami,

S., Nakamura, A., Kato, K., Nagano, A., Yamaguchi, Takashi, 2018. A novel approach

for toluene gas treatment using a downflow hanging sponge reactor. Appl. Microbiol.

Biotechnol. 102, 5625–5634. https://doi.org/10.1007/s00253-018-8933-5

Yoon, H., Song, M.J., Kim, D.D., Sabba, F., Yoon, S., 2019. A Serial Biofiltration System for

Effective Removal of Low-Concentration Nitrous Oxide in Oxic Gas Streams:

Mathematical Modeling of Reactor Performance and Experimental Validation. Environ.

Sci. Technol. 53, 2063–2074. https://doi.org/10.1021/acs.est.8b05924

Yoon, H., Song, M.J., Yoon, S., 2017. Design and Feasibility Analysis of a Self-Sustaining

Bio fi ltration System for Removal of Low Concentration N2O Emitted from Wastewater

Treatment Plants. https://doi.org/10.1021/acs.est.7b02750

Yoon, S., Nissen, S., Park, D., Sanford, R.A., Löffler, E., 2016. Clade I NosZ from Those

Harboring Clade II NosZ. Appl. Envioronmental Microbiol. 82, 3793–3800.

https://doi.org/10.1128/AEM.00409-16.Editor

Zhang, Z., Zhang, Y., Shi, Z., Chen, Y., 2022. Linking Genome-Centric Metagenomics to

Kinetic Analysis Reveals the Regulation Mechanism of Hydroxylamine in Nitrite

Accumulation of Biological Denitrification. Environ. Sci. Technol. 56, 10317–10328.

https://doi.org/10.1021/acs.est.2c01914

Zheng, X., Yan, Z., Zhao, C., He, L., Lin, Z., Liu, M., 2023. Homogeneous environmental

selection mainly determines the denitrifying bacterial community in intensive

aquaculture water. Front. Microbiol. 14, 1280450.

https://doi.org/10.3389/fmicb.2023.1280450

707