Title

CLCFM3: An advanced photogrammetry algorithm for high-precision plant 3D modeling

Authors

Atsushi Hayashi[1,2], Nobuo Kochi[1, 2, 3*], Kunihiro Kodama[1†], Sachiko Isobe[1†], Takanari Tanabata[1*]

Affiliations

[1] Kazusa DNA Research Institute, Chiba, 292-0818, Japan.

[2] National Agriculture and Food Research Organization, Ibaraki 305-8518, Japan.

[3] R&D Initiative, Chuo University, Tokyo, 112-8551, Japan.

[†] Present address: The University of Tokyo, Tokyo, 188-0002, Japan.

[*]Address correspondence to: imageapplabo@kochi.email.ne.jp and tanabata@kazusa.or.jp

Keywords

Photogrammetry, Structure from motion, Multi-view stereo, 3D reconstruction, 3D point cloud, Plant

Abstract

This research aims to develop a novel technique to acquire a large amount of high-density, high-

precision 3D point cloud data for plant phenotyping using photogrammetry technology. The

complexity of plant structures, characterized by overlapping thin parts such as leaves and stems,

makes it difficult to reconstruct accurate 3D point clouds. One challenge in this regard is occlusion,

where points in the 3D point cloud cannot be obtained due to overlapping parts, preventing accurate

point capture. Another is the generation of erroneous points in non-existent locations due to image-

matching errors along object outlines. To overcome these challenges, we propose a 3D point cloud reconstruction method, CLCFM3 (Closed-Loop Coarse-to-Fine method with Multi-Masked Matching). This method repeatedly executes a process that generates point clouds locally to suppress occlusion (multi-matching) and a process that removes noise points using a mask image (masked matching). Furthermore, we propose the Closed-Loop Coarse-to-Fine Method (CLCFM) to improve the accuracy of structure from motion, which is essential for implementing the proposed point cloud reconstruction method. CLCFM solves loop-closure by performing coarse-to-fine camera position estimation. By facilitating the acquisition of high-density, high-precision 3D data on a large number of plant bodies, as is necessary for research activities, this approach is expected to enable comparative analysis of visible phenotypes in the growth process of a wide range of plant species based on 3D information.

1. Introduction

The phenotypes of plants and plant organs are important information in plant functional analyses. With the development of molecular biology, it is becoming increasingly necessary to obtain large quantities of highly accurate data. Digital imaging technology is a simple, low-cost method that offers the advantage of nondestructive measurements of samples [1]. However, the images captured by cameras are 2D information, and there are limits to how accurately 2D cameras can obtain 3D shapes and structures, including depth. To precisely measure plant phenotypes during the growth process, technology is needed to accurately digitize shapes and structures in 3D space. The development of

measurement technology to support this is progressing [2, 3, 4].

Two main types of measurement technology are used to acquire 3D information about an object.

One is the active method, which uses a device that emits light such as laser light to perform

measurements, and the other is the passive method, which reconstructs 3D data from photographed

images of the target [5]. An example of the latter is photogrammetry SfM/MVS (Structure from

Motion/Multi-View Stereo) [6]. Photogrammetry can be implemented using commercially available

digital cameras. It offers two following advantages. First, the hardware cost is low. Second the

necessary measurements can be taken simply by photographing the target from all directions, so a

flexible measurement system can be constructed according to the measurement environment [7]. To

obtain phenotypic data for functional analysis, it is necessary to measure different plant bodies of

varying sizes and structural complexities, to perform measurements in various locations, and to

measure large numbers of individuals. Photogrammetry can solve these issues.

Photogrammetry is a method of reconstructing 3D point cloud data of an object using images taken

from various angles. This is realized by combining SfM processing and MVS processing. SfM

processing arranges the viewpoint positions (hereafter referred to as camera positions) of images

taken in three-dimensional space [8, 9]. MVS processing searches for the position in the image that

corresponds to the target point and combines this with the camera position information obtained by

SfM to ascertain the position of the point in three-dimensional space using stereo matching processing.

This process is repeated to reconstruct a dense 3D point cloud of the object in the image [10]. Given

its ability to generate dense 3D point clouds from images, this approach has been proposed for use in

phenotyping [11].

Plant structures are characterized by the overlapping of thin, narrow parts such as stems and leaves.

Thus, image matching using stereo matching is often unsuccessful because of occlusion. Image

matching is also likely to fail because leaf and stem surfaces are similar in color and texture. These

failures in image matching can lead to problems in estimating the camera position and can result in

incomplete sections of the plant body within the sought 3D point cloud [12] or the occurrence of noise

points in places other than the plant body [13]. Creating a plant 3D model with low accuracy is

relatively easy, but it remains challenging to construct high-precision 3D models at high throughput

for measurement purposes. Therefore, when using photogrammetry to measure plants, it is necessary

to solve the problem of failures in image matching that occur in SfM and MVS processing.

To address such issues in SfM processing, various proposals have been made to enhance the

accuracy of camera position estimation. These methods involve integrating reference points or GPS

devices to provide positional information during capture, such as utilizing images taken with 3D

reference points placed around the object to be measured [14, 15] or employing positional information

obtained from GPS [16]. On the other hand, as a solution in image processing, the loop closing method

has been proposed. This method minimizes estimation errors by linking the initial image captured

with the final image when all surrounding images of an object are taken [17]. In the image matching

process during camera position estimation, techniques have been proposed to pre-evaluate the entire

image's similarity and the relation between images. This approach aims to mitigate the buildup of

matching errors resulting from similar patterns [18, 19, 20].

A major issue with MVS processing is the creation of noise points. Zhang et al. reconstructed 3D models of sweet potato and paprika using SfM/MVS. They found that the 3D reconstruction failure was caused by the inaccuracy of background removal and shadows caused by lighting. Additionally, they noted that the lack of effective solutions for matching at the boundaries of the contours between the background and the object contributes to the inaccuracy of 3D reconstruction for plants [3, 21]. Some inaccuracies are projected as noise points. One reason for the presence of noise points is the occurrence of "flying pixels." These isolated points emerge at object boundaries where there is a depth change between objects. They are considered noise points as they appear in locations devoid of actual objects. Flying pixels occur more prominently in active methods such as laser scanners, LiDAR, and ToF cameras than in passive methods. Methods for removing them utilize the characteristics of the scanning data employed in active methods. The problem of flying pixels has been confirmed not only in active methods but also in passive methods that use images, such as stereo cameras [22]. The noise points of flying pixels in the passive method result from errors in the stereo matching process around the edges of the measurement target. In particular, the matching results become unstable at the boundary areas where the object and background are mixed in one pixel of the image, and noise points are generated according to these matching results. However, it is difficult to theoretically distinguish whether these points are background or object and to remove them in post-processing. This problem remains unresolved given the fundamental disparity between passive and active methods. Therefore, many methods have been proposed for plant research, with most of them involving the removal of noise points from the 3D point cloud data after reconstruction for post-

processing [23]. That is, the noise in the point cloud data is solved by filtering it out in post-processing.

For example, one proposed method uses the Euclidean clustering algorithm to segment the plant point

cloud data and remove irrelevant background as well as spatially discontinuous points [24].

This research aims to acquire 3D point clouds of individual plants for phenotypic evaluation of

plant organ shapes, individual structures, and so on. To this end, we have developed a technology that

uses photogrammetry to acquire a large amount of high-density, high-precision 3D point cloud data

of plants. Non-photogrammetric methods for reconstructing 3D point clouds using images have also

been proposed, with deep learning–based methods such as NeRF [25] being representative. These

methods entail training costs and, when high-resolution images are used as input images, a large

amount of flying pixel noise [26]. Moreover, the results have been confirmed to differ from the

original shape of the object, which has uneven surfaces on smooth planes and smooth curved surfaces

[27]. For this reason, these methods are not suitable for the acquisition of 3D point cloud data, which

is our objective. Furthermore, 3D point clouds with a spatial resolution of 1 mm for plants have been

reconstructed by utilizing photogrammetry techniques [28], demonstrating the effectiveness of the

use of photogrammetry.

This paper proposes a method, CLCFM3, for solving the problems of photogrammetry for plants.

CLCFM3 combines two newly proposed methods: MMM and CLCFM. MMM (Multi-Masked

Matching) combines the suppression of occlusion by locally generating point clouds (Multi-

Matching) using images with adjacent camera positions and Masked Matching, which removes flying

pixel noise that tends to occur at the boundary of the target object. Multi-matching generates a 3D

point cloud with reduced occlusion defects and then performs a noise point deletion process using

images taken from different angles surrounding those utilized in multi-matching. Masked matching

effectively reduces flying pixel noise, which has been considered difficult to remove until now. To

perform MMM processing, it is necessary to improve the accuracy of the camera position estimation

using SfM processing. To achieve this, we proposed CLCFM, which suppresses the accumulation of

camera position estimation errors. CLCFM3, which integrates MMM and CLCFM, can reconstruct

high-density 3D point clouds with fewer noise points and fewer missing points. We created an

analysis pipeline that implements CLCFM3 and applied the point cloud reconstruction process to

soybeans. The results showed that it is possible to reconstruct point clouds with fewer missing points

by reducing the noise caused by flying pixels. Moreover, the measurement accuracy achieved with

this method revealed that the 3D models constructed through it possess sufficient precision for plant

measurement. This suggests that the proposed method holds the potential to truly enable the

application of 3D models for precise plant measurements.

2. Materials and Methods

2.1. Plant material and cultivation

A total of four varieties were used: three soybean varieties—GmJMC092 (KUROHIRA),

GmJMC112 (FUKUYUTAKA), and HOJAK—were derived from the Genebank project, NARO

(https://www.gene.affrc.go.jp), while the fourth variety, MISUZUDAIZU, was derived from the

NBRP Lotus japonicus & Glycine max collection (https://nbrp.jp/en/resource/lotus-glycine-en/). The

seeds were sown in 1/5000a Wagner pots in 2018 using baked soil, and the plants were grown in a

greenhouse at the Kazusa DNA Research Institute. Water tubes were installed in the pots, with

irrigation occurring twice a day.

2.2.   *CLCFM3*: 3D reconstruction algorithm

We propose a 3D reconstruction method called CLCFM3, based on all-round images of a rotating

object taken in front of a camera, assuming that each image is accompanied by information on the

order in which it was taken. CLCFM3 consists of two processes: MMM and CFCFM, which utilize

information on the order in which images were taken. MMM selects adjacent images and performs

MVS processing locally to reduce the number of defects caused by occlusion. CLCFM first selects a

part of the captured image and performs SfM before iteratively adding portions of the captured image

to the SfM results for further processing. An important point of the proposed method is that it selects

images using order-of-capture information so as to surround the measurement target, thus minimizing

error accumulation common in SfM methods when images of the entire surrounding area are used.

MMM: **Multi-Masked Matching**

In MMM, our proposed 3D point cloud generation method, a cloud is generated by stereo matching

using images captured from closely positioned cameras locally (Multi-matching). This is followed by

iterative point removal using mask images derived from the surrounding viewpoint images utilized

during point cloud generation (Masked matching).

Figure 1 shows a representative example of the process. In this example, stereo matching is

performed using two images from adjacent camera positions (indicated by the pink squares in Fig.

1A) to generate a 3D point cloud, referred to as the *baseCloud*. This process is executed sequentially

using the Metashape API functions buildDepthMaps () and buildDenseCloud ().

Next, mask images from other viewpoint images are used to remove noise points of the *baseCloud*

(the 72 pink squares in Fig. 1B), taken from viewpoints within a 45-degree range to the left and right,

facilitating the point removal process from the *baseCloud*. The mask image is a binary representation

where the area of the plant region to be measured is set to 1, while other areas are designated as 0.

The execution of this process involves utilizing the Metashape API functions selectMaskedPoints ()

and removeSelectedPoints () in that order. For every image captured, this process is carried out for

all combinations of adjacent images to obtain the point cloud and remove noise points. The resulting

point clouds are amalgamated to construct a 3D point cloud of the target plant.

CLCFM: **Closed-Loop Coarse-to-Fine Method for SfM**

We propose the CLCFM to improve the stability and accuracy of camera position estimation for

images taken from all around the target. Instead of performing SfM simultaneously with all images

captured around the target, we utilize a small subset of the images for the initial SfM process. We

then iterate the process by incorporating subsets of the remaining images taken around the target. This

iterative process employs a small number of all-around images initially, then incorporates all images

to perform SfM to estimate the camera positions of all captured images. This method of performing

SfM sequentially rather than all at once improves the accuracy of the camera position estimation.

The principle of the method is illustrated through an example where a single camera captures

images of an object rotated in 5-degree increments (Fig. 2A). First, the images are categorized into

groups, with the 72 images around the object being divided into six groups in this instance. Next, the

order in which the SfM process is executed (GroupOrder) is determined. The GroupOrder is selected

so as to minimize the bias in the estimated camera positions. For example, if Group 1 is the first group

subjected to the SfM process, then Group 4, which includes the images halfway between the adjacent

images of Group 1, is selected as the second group to be processed, and Group 2, which is between

Group 1 and Group 4, is selected as the third.

Next, the procedure shown in Fig. 2B is followed to perform SfM sequentially for each group. The

images in Group 1 are used to estimate the first camera position. The main process for camera position

estimation in Fig. 2B, AlignProcess (), is executed for ImgList [] in the order of the Metashape API

functions matchPhotos (), alignCameras (), and optimizeCameras (). The results of the first camera

position estimation are then used as initial values, and a second SfM is performed by adding the

Group 4 images to the Group 1 images. Similarly, images are processed in the order specified by

GroupOrder, with SfM being sequentially executed using the camera position estimates obtained from

the previous step as initial values. The final camera position estimates are derived by processing all

groups. When images are captured using multiple cameras arranged vertically, those taken from the

same vertical angle are grouped together for processing.

2.3. 3D point cloud reconstruction pipeline program

We developed a 3D point cloud reconstruction pipeline that implements our proposed method. This pipeline consists of four subprograms executed sequentially, starting with the captured image as the initial input to reconstruct the 3D point cloud (Fig. 3).

1) CreateMask.cpp

This is a program for creating mask images. The program generates binary mask images where the plant areas vital for reconstructing the 3D point cloud and the relevant object regions are shown in white, while the remaining areas are black. Mask images are produced for all captured images, utilized for mask processing in CLCFM and noise elimination in MMM.

This program was developed using Visual C++ (Visual studio 2019) and OpenCV version 3.4.14.

2) align_camera.py

This script performs the camera position estimation process of the CLCFM algorithm, providing the camera position estimation information used in MMM.

This program was developed using Python 3.8, Metashape Professional Edition 1.8.5, and the Python 3 Module (Agisoft, https://www.agisoft.com).

3) build_densecloud.py

This script executes the MMM algorithm to construct a 3D point cloud and exports multiple 3D

221 point cloud data files in PLY format. The script was developed using Python 3.8, Metashape

222 Professional Edition 1.8.5, and the Python 3 Module. The results presented in this paper were obtained

223 using the following execution parameters for the processing functions within the Python 3 Module.

224   ● matchPhotos(): The images were processed at 100% scale with accuracy set to 'high'.

225   ● buildDepthMaps(): The images were processed at 1/4 scale (1500x1000 pixels)

226   with quality set to 'medium'.

4) merge_subsampling.py

This program integrates the diverse 3D point cloud data output by 'build_densecloud.py' and

performs subsampling processing at 0.5 mm intervals, resulting in the output of the 3D point cloud

of the target object.

This program was developed using Python 3.7 and open3D 0.15.

2.4. Imaging

To obtain the best images for the proposed CLCFM3 method, we built an imaging studio consisting

of a rotating stage with plants, a camera, LED lighting, and background panels (Fig. 4A). The

background panels, equipment, and cords were colored blue to facilitate the creation of mask images.

The imaging stage was devised to allow the rotation of the plant in front of the camera, capturing

a comprehensive image of the entire plant (Fig. 4B). SGSP-160YAW (Sigma Koki, Tokyo) and GIP-

101 (Sigma Koki) were connected to a personal computer using a serial USB converter (COM-

1(USB)H; Contec, Tokyo). The rotations were controlled by a program running on the personal

computer.

To hold the cultivation pot, an acrylic disc (35 cm in diameter) was made and attached to the SGSP-

160YAW. Small pieces of paper printed with coded targets were attached to the acrylic disc, and

additional coded targets were attached to the three pillars fixed outside the perimeter of the disc. The

coded targets were used as reference points for integrating the point cloud using MMM and to define

the scale that gives the actual dimensions [6]. The coded targets were attached to the following

positions: the center of the disc; eight positions at 45-degree intervals around the circumference, 15

cm from the center; and positions separated by 20 cm apart vertically on the pillars. Each of the three

pillars consisted of an aluminum frame of 2.5 cm width Í 1.5 cm thickness Í1 m length, to which was

attached a strip of paper printed with a random dot image. These random dots were used to ensure

that the feature points obtained in the CLCFM and MMM processing steps were stable [6]. The pillars

were attached to the side of the disc at uniform angles (Fig. 4B, left).

Images were captured using four digital SLR cameras (D5500; Nikon Corporation) and lenses (AF-

S Micro NIKKOR 60mm f/2.8G ED, Nikon Corporation). Figure 4C shows the camera arrangement

used to capture images of the plants used as targets with heights ranging from 400 to 1200 mm). The

cameras were connected to a personal computer via USB cables. The shooting conditions were:

shutter speed 1/15 sec, ISO sensitivity 100, aperture F/16. The acquired images was saved as

6000x4000 pixel JPG files.

3. Results

3.1. 'baseCloud' construction process in MMM

Figure 5 shows the results of an experiment to verify the optimal viewing angle for generating

baseCloud point clouds of the target plant. Figures 5a and 5b display portions of the *baseCloud*

reconstructed using only two adjacent images and four adjacent images, respectively, from different

camera positions. These images were captured by rotating the table holding the object in 5-degree

increments, resulting in viewing angles of 5 degrees for the *baseCloud* in Fig. 5a and 15 degrees for

that in Fig. 5b. For this object, no significant difference was observed between the *baseClouds* in Figs.

5a and 5b. Nonetheless, while reconstructing a separate sample with Metashape 1.6, we confirmed

that configuring the viewing angle to 5 degrees helped reduce the loss of point clouds (Fig. S3). The

reconstruction time with MMM diminishes with a reduction in the number of images employed.

Given these findings, we chose to generate the *baseCloud* using two adjacent images.

3.2. Viewing angle of the mask image used in the MMM point removal process

We next investigated the optimal viewing angle for the mask image used in the point removal

procedure of the *baseCloud* performed by MMM. To ascertain the optimal angle, we performed the

point removal process of *baseCloud* using MMM under four different viewing angles of the mask

image, similar to the method illustratedin Fig. 6. Figure 6 illustrates the outcomes when employing

the mask image at viewing angles of a) 50 degrees, b) 90 degrees, c) 180 degrees, and d) 360 degrees.

The results indicated that as the viewing angle of the surrounding mask increased, more points were

eliminated; however, this increase also led to the deletion of points in the plant body that should have

been retained. We therefore decided to set a 90-degree viewing angle of the mask image used in point

removal.

3.3. 3D point cloud reconstruction of soybean plants

Using the pipeline developed and the processing conditions established in the previous sections,

we successfully reconstructed 3D point clouds for four soybean varieties (Fig. 7a, Fig. S1). The results

demonstrated the proposed method's ability to reconstruct 3D point clouds of varying shapes, sizes,

and structural complexities. For comparison, the identical image sets underwent standard Metashape

functions to generate 3D point clouds. This comparison confirmed that the proposed method

effectively mitigated the appearance of blue dots as noise in the outlines of leaves and stems, while

also resolving the problem of point clouds failing to form in certain thin-stem regions (Fig. 7b, Fig.

S1, Fig. S2).

Figure 7c displays the outcome when the point removal process was omitted after   the *baseCloud*

was generated with MMM, while Fig. 7d showcases the result of the point removal process after the

baseCloud was generated with MMM. In both cases, point cloud reconstruction and point removal

processing were performed after SfM was executed using CLCFM. Without point removal processing,

noise points emerged in the background and other parts of the captured image (Fig. 7c), while point

removal processing resulted in the removal of noise points (Fig. 7d).

3.4. Effects of the point removal processes in MMM

We compared the differences in the reconstruction of 3D point clouds by MMM with and without point removal processing. The *Base clouds* were generated using the MMM point cloud reconstruction approach, leading to the production of 3D point clouds after applying point removal processing (Fig. 8a) and without such processing (Fig. 8b). These 3D point clouds were then overlaid and compared within a virtual space. To facilitate this comparison, only the plant body was extracted, while the support, pot, and rotating stage were manually removed. The distance between corresponding points in the aligned 3D point clouds was calculated. Points with distances of 3 mm or less were deleted, yielding a point cloud that represented the differences between the two 3D reconstructions (Fig. 8c). This process was repeated for distance intervals of 0–1 mm, 1–2 mm, 2–3 mm, and 3–22 mm, with the number of points constituting each point cloud recorded (Fig. 8d). The analysis revealed that in the point cloud post-point removal process, 78,637 points exhibited a distance variance of 3 mm or more, constituting 4.3% of the aggregate points within the point cloud (Fig. 8d).

3.5. Validation of position accuracy in the reconstructed point cloud

We assessed the position estimation errors for the 3D point cloud acquired through the CLCFM3 pipeline using the evaluation model shown in Figure 9. The evaluation model was arranged with 13 pairs of measurement points (Fig. 9 (1)-(13)), consisting of coded target pairs. The distance between these targets was measured manually with a caliper and compared with the value measured using the

3D point cloud generated by CLCFM3. The actual values were measured 10 times each, and the

average was used. The coded targets attached to the pillars were measured using a ruler to derive the

average value (Fig. 9 (14)). The reading errors for manual measurement were set at 0.02 mm for the

caliper and 1 mm for the ruler. The measurement using CLCFM3 was acquired by obtaining the

distances between the targets in the 3D point cloud reconstructed through the pipeline. This procedure

was repeated 10 times, and the average value was derived.

Table 1 shows the results. For measurement points (1) to (13), the maximum difference between

the manually measured values (actual values) and the values obtained from the 3D point cloud was

0.280 mm, with a maximum standard deviation of 0.0000346 mm for the 3D measurements.For

measurement point (14), the difference between the average manually measured value (actual value)

and the average value obtained of the measured values was -0.97 mm, and the standard deviation of

the measured values was 0.00012 mm. For measurement point (14), the difference between the

average manually measured value (actual value) and the average value obtained from the 3D point

cloud was -0.97 mm, with a standard deviation of 0.00012 mm for the 3D measurements.

4.   Discussion

4.1.   Generating local 3D points and removing noise with mask images

We proposed an approach to reduce the loss due to occlusion by constructing 3D point clouds using

images with narrow viewing angles. However, this process generates many flying pixels due to errors

in stereo matching when searching for corresponding points along the outline. We proposed to solve

these issues by eliminating points using a mask image of the peripheral field of view from the images

employed in point cloud reconstruction, reducing occlusion-related losses and achieving point cloud

reconstruction with fewer noise points.

Figure 10 shows a schematic of the image-matching process at a plant boundary.

To estimate the 3D position of point P on the object's contour line, we extract the coordinates of

point P_{A1} and point P_{A2}, representing point P's location in the images taken by cameras A1 and A2,

respectively. Using these coordinates and the camera position information for cameras A1 and A2

acquired through SfM, the depth distance DP between point P and the cameras is calculated. Based

on the outcome, the 3D position of point P is ascertained, leading to the creation of a point for the 3D

point cloud (Fig. 10A).

Here, we focus on point P in the outline of the plant body. Image matching is performed to find

position P_{A2} on the image taken by camera A2 relative to position P_{A1} on the image taken by camera

A1.

The DP value fluctuates according to the matching results. If the position of point P found by

camera A1 is correctly matched with point P in the image from camera A2, DP is assigned is accurate

value. Consequently, point P on the plant body will be generated in 3D space (Fig. 10A). However,

if point P is incorrectly matched and the matching result differs from the accurate point P (Fig. 10B),

the DP value deviates, leading to the acquisition of DP_m and $DP_{m'}$ values (Fig. 10A). Based on these

values, points are generated at positions Pm and Pm', which differ from the accurate position of point

P. These points, P_m and $P_{m'}$, are noise points that do not exist on the plant body. The causes of

inaccurate image matching include the resolution of the imaging camera's image sensor and the

matching process with points exhibiting textures akin to leaves and stems close to point P. To address

the issue of noise points caused by mismatching, our proposed method does not aim to rectify the

mismatches but instead identifies numerous candidate points, incorporating a post-processing step for

point removal. This approach reduces the number of noise points.

Figure 10C shows a schematic of the point removal process for MMM. Cameras A1, A2, B1, and

B2 represent the camera positions. The A1 and A2 images are used to generate the point cloud

(*baseCloud*), and the mask images generated from the images captured by all four cameras are used

for the point removal process (Fig. 10C). The mismatching at points on the contour line of the object

occurs in the vicinity of the intersection lines $P_{A1}P_{back}$ and $P_{A2}P'_{back}$ of Cameras A1 and A2. Using the

A1 and A2 mask images, the point removal process can eliminate mismatched points beyond the

object's boundaries. However, none of the mismatched points generated on the $P_{A1}P_{back}$ and $P_{A2}P'_{back}$

boundary lines can be removed. The mismatched points P_m and $P_{m'}$ on the boundary line shown in

Fig. 10C can be eliminated by excluding areas outside the object at the intersection lines $P_{B1}P_{b1}$ and

$P_{B2}P_{b2}$ of Cameras B1 and B2 in the mask image. This approach also enables the removal of

mismatched points along the line between $P_{A1}P_{back}$ and $P_{A2}P'_{back}$.

The proposed method uses surrounding mask images to detect flying pixel noise points. Therefore,

the accuracy of noise point detection depends on the results of the mask image region extraction,

making the image processing of the region extraction an important factor. The developed pipeline

employs a method that uses color differences for region extraction [29, 30]. Numerous image analysis

techniques have been proposed for area extraction, enabling the generation of tailored mask images

capable of eliminating noise points adapted to various plants and shooting environments. This

versatility allows MMM to be applied across a wide range of plants, facilitating the reconstruction of

3D point clouds with suppressed flying pixel noise.

The proposed method can remove noise points on the outside of the plant body using a point

removal process. However, noise points located inside the plant body cannot be detected and removed.

Developing a method for removing these internal noise points stands as a future issue.

4.2. Enhancing camera position accuracy for all-around images

In this study, we used all-around images taken by rotating the object at 5-degree intervals for 3D

point cloud reconstruction. In estimating camera position using SfM processing on omnidirectional

images with narrow angles of view, one challenge is that the estimation process is likely to fail due

to accumulated errors (Fig. 11A).

CLCFM estimates camera position while gradually adding panoramic images. First, camera

position is estimated using only images that surround the object but have an open viewpoint, and the

results are used as initial values. Next, we add a few more images and run the estimation process

again, updating the results. We reiterate this process until we have estimated the camera positions for

all the images in the full surround. This processing method is expected to reduce the failure of position

estimation due to error accumulation by suppressing the propagation of estimation errors that occur

in the estimation process (Fig. 11B).

However, there is a problem with implementing this algorithm. If the cameras are placed far apart

in the initial stage of processing, there are few common feature points between the images, making it

difficult to estimate camera position in the initial processing. We solved this problem by affixing

random patterns to the pillars when taking pictures (Fig. 4B). Securing numerous image feature points

within the area featuring the random pattern allowed for a bundle adjustment with self-calibration

[31]. This made it possible to stably obtain the camera's internal and external parameters. Finally,

since it is not necessary to perform internal and external calibration in advance, a key advantage is

the potential to attain high measurement accuracy without engaging in device setup or maintenance

[6].

5.   Conclusion

This paper introduced the CLCFM3 algorithm for the 3D reconstruction of all-around plant images.

Given that plants possess a distinctive morphology characterized by overlapping thin parts such as

leaves and stems, challenges arise when performing 3D point cloud reconstruction via

photogrammetry. These challenges include the inability to acquire points in the 3D point cloud due

to occlusion in the overlapping parts and the generation of points where the object does not exist due

to image matching errors along the object's outline.

To solve these problems, we proposed the MMM approach. MMM generates a point cloud using

images taken from a viewpoint close to the object to avoid occlusion (multi-matching) and then

repeatedly executes point cloud removal processing using surrounding mask images to remove the

noise points (mask matching) (Fig. 1).

To execute MMM, a highly accurate camera position estimation must first be obtained by SfM

processing. To meet this requirement, we proposed CLCFM, which estimates camera positions with

high accuracy for images encompassing the entire surroundings of the target. However, when SfM is

conducted using such images, estimation errors accumulate. CLCFM selects   images for SfM

processing and iterates the SfM procedureto suppress this accumulation of errors (Fig. 2). MMM and

CLCFM are based on the assumptions that the target is rotated and photographed from all sides and

that the order of the images is known. Using this information, we were able to implement the proposed

method by reconstructing local point clouds and selecting surrounding mask images for point removal

processing.

We built an imaging studio (Fig. 4) and an image analysis pipeline (Fig. 3) to implement the

proposed method and reconstructed 3D point cloudsfor soybean plants (Fig. 7). We validated the

feasibility of reconstructing a high-density 3D point cloud of a plant body that minimizes the loss of

thin stems, a characteristic shape of the plant body, as well as reducing noise from 3D points generated

in areas devoid of plant structure (Fig. 8).

In this paper, Metashape Professional Edition 1.8 was used to execute SfM/MVS. We found that

the different versions of Metashape yielded different results in MVS point cloud reconstruction (Fig.

S3, Fig. S4). However, regardless of the version, the proposed method is effective for reconstructing

3D point clouds of plant bodies characterized by overlapping organ shapes such as leaves and stems.

This effectiveness is based in the method's ability to reduce noise by through point cloud

reconstruction using local perspectives with MMM and point removal procedures involving mask

images.

Although numerous methods for constructing 3D models of plants have been proposed, practical

applications for measurement purposes remain limited except for rough assessments of community

dynamics in the field. The proposed method enables the robust construction of highly accurate 3D

models, a feature anticipated to advance the widespread use of 3D modeling for plant measurements

in plant research.

Supplementary Materials

Figure S1 Results of reconstruction of 3D point clouds of four soybean varieties using the proposed

method.

Figure S2 Results of reconstruction of 3D point clouds for the image in Fig. S1 using Metashape.

Figure S3 Results of running the analysis in Fig. 5 using Metashape 1.6.

Figure S4 Results of running the analysis in Fig. 6 using Metashape 1.6.

Declaration of Competing Interests

The authors declare that they have no known competing financial interests or personal relationships

that could have appeared to influence the work reported in this paper.

Acknowledgments

General: We would like to thank Keiko Saegusa, Rumi Fujihira, Satomi Nakayama, Chie

Kasashima, and Sayaka Kikuchi for their technical support at the Kazusa DNA Research Institute.We

also thank Prof. Ryo Akashi, Dr. Hidenori Tanaka, Dr. Masatsugu Hashiguchi, and Dr. Takuyu

Hashiguchi for providing soybean materials in this study.

Funding: This work was supported by a CREST Grant (No. JPMJCR16O1) from the Japan

Science and Technology Agency and the Kazusa DNA Research Institute Foundation.

Author contributions

HA, KN, IS, and TT contributed to the design of the study. HA developed the 3D reconstruction

pipeline programs. HA and TT made imaging hardware. HA, KN, and KK conducted experiments

and analyzed and interpreted data. HA, KN, IS, and TT wrote and revised the manuscript. KN and

TT supervised the study.

Data availability

The computer codes and scripts of MMM and CLCFM are deposited in a GitHub repository at

https://github.com/tanasoft/MMM-CLCFM. Download links to image and 3D point cloud data that

support the findings of this study are also provided at this GitHub repository.

References

[1] Li, Z., Guo, R., Li, M., Chen, Y., Li, G., 2020. A review of computer vision technologies for

plant phenotyping. Computers and Electronics in Agriculture. 176, 105672.

https://doi.org/10.1016/j.compag.2020.105672

[2] Okura, F., 2022. 3D modeling and reconstruction of plants and trees: A cross-cutting review across

computer graphics, vision, and plant phenotyping. Breeding Science. 72(1), 31-47.

https://doi.org/10.1270/jsbbs.21074

[3] Zhang, Y., Teng, P., Aono, M., Shimizu, Y., Hosoi, F., Omasa, K., 2018. 3D monitoring for plant

growth parameters in field with a single camera by multi-view approach. Journal of Agricultural

Meteorology. 74(4),129-139. https://doi.org/10.2480/agrmet.D-18-00013

[4] Kunita, I., Morita, M.T., Toda, M., Higaki, T., 2021. A Three-Dimensional Scanning System for

Digital Archiving and Quantitative Evaluation of Arabidopsis Plant Architectures. Plant and Cell

Physiology. 62(12),1975-1982. https://doi.org/10.1093/pcp/pcab068

[5] Paulus, S., 2019. Measuring crops in 3D: using geometry for plant phenotyping. Plant Methods.

15, 103. https://doi.org/10.1186/s13007-019-0490-0

[6] Kochi, N., Hayashi, A., Shinohara, Y., Tanabata, T., Kodama, K., Isobe, S., 2022. All-around 3D

plant modeling system using multiple images and its composition. Breeding Science. 72(1),75-84.

https://doi.org/10.1270/jsbbs.21068

[7] Salter, W.T., Shrestha, A, Barbour, M.M., 2021. Open source 3D phenotyping of chickpea plant

architecture across plant development. Plant Methods. 17(1), 95. https://doi.org/10.1186/s13007-021-

00795-6

[8] Snavely, N., 2008. Bundler: Structure from motion (sfm) for unordered image collections.

[accessed 30 Aug 2024] https://www.cs.cornell.edu/~snavely/bundler/

[9] Wu, C., 2013. Towards Linear-Time Incremental Structure from Motion. Proceedings of the 2013

International Conference on 3D Vision. 127-134. https://doi.org/10.1109/3DV.2013.25

[10] Furukawa, Y., Ponce, J., 2010. Accurate, Dense, and Robust Multiview Stereopsis. IEEE

Transactions on Pattern Analysis and Machine Intelligence. 32(8), 1362-1376.

https://doi.org/10.1109/TPAMI.2009.161

[11] Townsend, A.J., Retkute, R., Chinnathambi, K., Randall, J.W.P., Foulkes, J., Carmo-Silva E.,

Murchie, E. H., 2018. Suboptimal Acclimation of Photosynthesis to Light in Wheat Canopies. Plant

Physiology. 176(2), 1233–1246. https://doi.org/10.1104/pp.17.01213

[12] Santos, T.T., De oliveira, A. A., 2012. Image-based 3D digitizing for plant architecture analysis

and phenotyping. Proceedings of the Workshop on Industry Applications (WGARI) in SIBGRAPI

2012 (XXV Conference on Graphics, Patterns and Images). http://doi.org/10.13140/2.1.4576.1608

[13] Gibbs J.A., Pound, M.P., French, A.P., Wells, D.M., Murchie, E.H., Pridmore, T.P., 2019. Active

Vision and Surface Reconstruction for 3D Plant Shoot Modelling. IEEE/ACM transactions on

computational biology and bioinformatics. 17(6),1907-1917.

https://doi.org/10.1109/TCBB.2019.2896908

[14] Barazzetti, L., Forlani, G., Remondino, F., Roncella, R., Scaioni, M., 2011. Experiences and

achievements in automated image sequence orientation for close-range photogrammetric projects.

Proceedings of Videometrics, Range Imaging, and Applications XI. 80850F.

https://doi.org/10.1117/12.890116

[15] Anai, T., Kochi, N., Yamada, M., Sasaki, T., Otani, H., Sasaki, D., Nishimura, S., Kimoto, K.,

Yasui, N., 2015. Examination about influence for precision of 3D image measurement from the

ground control point measurement and surface matching. Joint Workshop with ISPRS WG IV/7 and

WG V/4. XL-4/W5,165-170. https://doi.org/10.5194/isprsarchives-XL-4-W5-165-2015

[16] Sattler, T., Torii, A., Sivic, J., Pollefeys, M., Taira, H., Okutomi, M.,Pajdla, T., 2017. Are Large-

Scale 3D Models Really Necessary for Accurate Visual Localization? Proceedings of the IEEE

Conference on Computer Vision and Pattern Recognition. 1637-1646.

[17] Scaramuzza, D., Fraundorfer, F., Pollefeys, M., 2010. Closing the loop in appearance-guided

omnidirectional visual odometry by using vocabulary trees. Robotics and Autonomous Systems.

58(6), 820-827. https://doi.org/10.1016/j.robot.2010.02.013

[18] Havlena, M., Torii, A., Pajdla, T., 2010. Efficient Structure from Motion by Graph Optimization.

Proceedings   of   the   11th   European   Conference   on   Computer   Vision.   110-113.

https://doi.org/10.1007/978-3-642-15552-9_8

[19] Sweeney, C, Sattler, T., Höllerer, T., Turk, M., Pollefeys, M., 2015. Optimizing the Viewing

Graph for Structure-from-Motion. Proceedings of the 2015 IEEE International Conference on

Computer Vision. 801-809.

[20] Schönberger, J.L., Frahm, J., 2016. Structure-from-Motion Revisited. Proceedings of the 2016

IEEE   Conference   on   Computer   Vision   and   Pattern   Recognition.   4104-4113.

https://doi.org/10.1109/CVPR.2016.445

[21] Zhang, Y., Teng, P., Shimizu, Y., Hosoi, F., Omasa, K., 2016. Estimating 3D leaf and stem shape

of nursery paprika plants by a novel multi-camera photography system. Sensors. 16(6),874.

https://doi.org/10.3390/s16060874

[22] Sabov, A., Krüger, J., 2008. Identification and correction of flying pixels in range camera data.

Proceedings of the 24th Spring Conference on Computer Graphics. 135-142.

https://dl.acm.org/doi/10.1145/1921264.1921293

[23] Harandi, N., Vandenberghe, B., Vankerschaver, J. et al., 2023. How to make sense of 3D

representations for plant phenotyping: a compendium of processing and analysis techniques. Plant

Methods. 19, 60. https://doi.org/10.1186/s13007-023-01031-z

[24] Li, Y., Liu, J.,Zhang, B., et al., 2022. Three-dimensional reconstruction and phenotype

measurement of maize seedlings based on multi-view image sequences. Frontiers in Plant Science.

13,974339. https://doi.org/10.3389/fpls.2022.974339

[25] Mildenhall, B., Srinivasan, P.P., Tancik, M., Barron, J.T., Ramamoorthi, R., Ng, R., 2020. NeRF:

Representing Scenes as Neural Radiance Fields for View Synthesis.

https://doi.org/10.48550/arXiv.2003.08934

[26] Croce, V., Billi, D., Caroti, G., Piemonte, A., De Luca, L., Véron, P.,2024. Comparative

Assessment of Neural Radiance Fields and Photogrammetry in Digital Heritage: Impact of Varying

Image Conditions on 3D Reconstruction. Remote Sensing. 16(2), 301.

https://doi.org/10.3390/rs16020301

[27] Tsukamoto, Y., Hayashi, A., Tokuda, K., Kochi, N., 2024. Comparative Verification of 3D

Reconstructed Point Cloud Data: Comparison of AI Estimation and Multi-View Stereo Methods using

Nerfstudio and Metashape. SICE Festival 2024 with Annual Conference, FrAT3.2

[28] Kochi, N., Isobe, S., Hayashi, A., Kodama, K., Tanabata, T., 2021. Introduction of All-Around

3D Modeling Methods for Investigation of Plants. International Journal of Automation Technology,

15(3), 301-312. https://doi.org/10.20965/ijat.2021.p0301

[29] Tanabata, T., Yamada, T., Shimizu, Y., Shinozaki, Y., Kanekatsu, M., Takano, M., 2010.

Development of automatic segmentation software for efficient measurement of area on the digital

images of plant organs. Horticultural research. 9(4),501–506. https://doi.org/10.2503/hrj.9.501

[30] Tanabata, T., Shibaya, T., Hori, K., Ebana, K., Yano, M., 2012. SmartGrain: High-throughput

phenotyping software for measuring seed shape through image analysis. Plant Physiology.   160(4),

1871-1880. https://doi.org/10.1104/pp.112.205120

[31] Karara, H.M., 1989. Chap. 5 Camera-calibration in non-topographic photogrammetry. Maryland

(USA). American Society for Photogrammetry and Remote Sensing.

Figure legends

Figure 1. Algorithm of MMM (Multi-Masked Matching).

A) Point clouds are generated locally using images from two adjacent viewpoints. B) Noise points

are removed using mask images derived from the surrounding viewpoint images. Processes 1 and 2

are repeated for each viewpoint, and the resulting point clouds are integrated.

Figure 2. Algorithm of *CLCFM* (Closed-Loop Coarse-to-Fine Method).

A) The sequentially captured images are divided into groups according to viewpoint. Six groups

consist of 72 images taken at 5-degree intervals. B) Procedure of CFCFM. First, SfM is performed

on group 1 images. Then, group 4 images are appended and SfM is performed. Similarly, groups 2,

5, 3, and 6 images are appended and SfM is performed.

Figure 3. 3D point cloud reconstruction pipeline program.

”CreateMaskImage.cpp” makes mask images. "align_camera.py" processes CFCFM.

"build_densecloud.py" and "merge_subsampling.py" are MMM processes. These programs are

executed sequentially with the captured image as the initial input to reconstruct the 3D point clouds.

Figure 4. Imaging studio for 3D point cloud reconstruction by CLCFM3.

A) The imaging studio consists of an imaging stage with a rotating platform on which plants are

placed, four cameras positioned in front, LED lights surrounding the plant, and a blue background

panel to facilitate mask image generation. B)   The imaging stage has three pillars on which random

dot patterns and coded targets for scale are attached.   C) Camera angles and distance from the object

are determined for soybeans ranging in height from 400 to 1200 mm.

Figure 5. Results of 'baseCloud' reconstruction with different numbers of images.

a) Two adjacent images. b) Four adjacent images. Processing time increases with the number of

images, while there is no significant difference between a) and b).

Figure 6. Results for different viewing angles of the mask image used in the point removal

process.

a) 50 degrees, b) 90 degrees, c) 180 degrees, d) 360 degrees. More points are deleted as the viewing

angle increases, while points consisting of leaves and stems are also deleted.

Figure 7. Differences in results between point removal   processes.

a) and d) Removed by MMM. b) Standard Metashape process.

c) Removed by MMM without the point removal process.

Figure 8. Results comparing point cloud reconstruction with and without the noise removal

process by MMM.

a) Point clouds with noise removal process by MMM. b) Point clouds without noise removal process

by MMM. c) Point clouds where the distance between a) and b) is 1-3 mm. d) Number of point clouds

categorized by distance ranges.

Figure 9. Model for evaluating accuracy and measurement positions.

CLCFM3 is processed 10 times individually, and the distances of measurement positions (1)-(14) are

measured respectively.

Figure 10. Image-matching process at the boundary.

A) Process of mismatching. B) Difference between correct point and mismatched point. C)   Point

removal process using masked images derived from surrounding viewpoint images (Masked

Matching).

Figure 11. Camera position estimation failure.

There is a risk of camera position estimation failure due to the accumulation of camera position

estimation errors for all-around images taken at short intervals in SfM. A) Without CFCFM and pillar.

B) With CFCFM and pillar.

Table 1. Evaluation of measurement accuracy by the proposed pipeline

Caliper values are obtained by measuring the length 10 times using a caliper for (1)-(13) and a ruler

for (14), and then calculating the average. CFCFM3 values are obtained using the point cloud data

obtained using CLCFM3. "Difference" is the difference in distance between the caliper and CFCFM3.

Figure. 1. Algorithm of MMM (Multi-Masked Matching).
A) Point clouds are generated locally using images from two adjacent
viewpoints. B) Noise points are removed using mask images derived from the
surrounding viewpoint images. Processes 1 and 2 are repeated for each
viewpoint, and the resulting point clouds are integrated.

A

Target plant

30 degree[s]

Image[72] → Group = 6
Image[1] → Group = 1
Image[2] → Group = 2
Image[3] → Group = 3
Image[4] → Group = 4
Image[5] → Group = 5
Image[6] → Group = 6
Image[7] → Group =1

Image[n] : Captured images, n=captured sequence number (1, 2,…, 72)

B

Perform SfM on the
Group 1 images.

Add the images from Group 4 to the results
from Group 1, then execute SfM.

Add the images from Group 2 to the results
of Groups 1 and 4, then execute SfM.

Add the images from Group 6 to the results of
Groups 1, 4, 2, 5, and 3, then execute SfM.

Figure 2. Algorithm of *CLCFM* (Closed-Loop Coarse-to-Fine Method).
A) The sequentially captured images are divided into groups according to viewpoint. Six groups consist of 72 images taken at 5-degree intervals. B) Procedure of CFCFM. First, SfM is performed on group 1 images. Then, group 4 images are appended and SfM is performed. Similarly, groups 2, 5, 3, and 6 images are appended and SfM is performed.

Captured images

↓

CreateMaskImage.cpp
Makes the background a "masked image"

↓

align_camera.py
Estimates the camera positions using the 'CLCFM' algorithm

↓

build_densecloud.py
Builds a "Local 3D point cloud" by '**MMM**'

↓

merge_subsampling.py
Integrates all local 3D point clouds

↓

3D point cloud of whole plant

Captured images

Camera 1   Camera 2   Camera 3   Camera 4

Masked images

Camera 1   Camera 2   Camera 3   Camera 4

Local 3D Point cloud

Cameras 1-2   Cameras 2-3   Cameras 3-4

3D point cloud of whole plant

Figure 3. 3D point cloud reconstruction pipeline program.
"CreateMaskImage.cpp" makes mask images. "align_camera.py" processes CFCFM. "build_densecloud.py" and "merge_subsampling.py" are MMM processes. These programs are executed sequentially with the captured image as the initial input to reconstruct the 3D point clouds.

Figure 4. Imaging studio for 3D point cloud reconstruction by CLCFM3.
A) The imaging studio consists of an imaging stage with a rotating platform on which plants are placed, four cameras positioned in front, LED lights surrounding the plant, and a blue background panel to facilitate mask image generation. B) The imaging stage has three pillars on which random dot patterns and coded targets for scale are attached. C) Camera angles and distance from the object are determined for soybeans ranging in height from 400 to 1200 mm.

| Camera positions | a) MVS executed with two images | b) MVS executed with four images |

The plants in this result are GmJMC092 (KUROHIRA).

Figure 5. Results of 'baseCloud' reconstruction with different numbers of images.
a) Two adjacent images. b) Four adjacent images. Processing time increases with the number of images, while there is no significant difference between a) and b).

| a) Viewing angle 50 degrees | b) Viewing angle 90 degrees | c) Viewing angle 180 degrees | d) Viewing angle 360 degrees |

The plants in this result are GmJMC092 (KUROHIRA).

Figure 6. Results for different viewing angles of the mask image used in the point removal process.
a) 50 degrees, b) 90 degrees, c) 180 degrees, d) 360 degrees. More points are deleted as the viewing angle increases, while points consisting of leaves and stems are also deleted.

a) MMM processed

b) Standard Metashape processed

c) Without the point removal process

d) With the point removal process

The plants in this result are GmJMC092 (KUROHIRA).

Figure 7. Differences in results between point removal processes.
a) and d) Removed by MMM. b) Standard Metashape process.
c) Removed by MMM without the point removal process.

a) Point removal
process performed
(proposed method)

b) Point removal
process NOT
performed

c) Difference points
between (a) and (b)
exceeding 3 mm

d) Comparison of the
number of points

Range (mm)	Number of points	%
0 ～ 3	1732066	95.7
3 ～	78637	4.3
Total	1810703	100.0

Figure 8. Results comparing point cloud reconstruction with and without the noise removal process by MMM.
a) Point clouds with noise removal process by MMM. b) Point clouds without noise removal process by MMM. c) Point clouds where the distance between a) and b) is 1-3 mm. d) Number of point clouds categorized by distance ranges.

Figure 9. Model for evaluating accuracy and measurement positions.
CLCFM3 is processed 10 times individually, and the distances of measurement
positions (1)-(14) are measured respectively.

Table 1. Evaluation of measurement accuracy by the proposed pipeline
Caliper values are obtained by measuring the length 10 times using a caliper for (1)-(13) and a ruler for (14), and then calculating the average. CFCFM3 values are obtained using the point cloud data obtained using CLCFM3. "Difference" is the difference in distance between the caliper and CFCFM3.

Measurement position		Caliper (mm)	CFCFM3		Difference (mm)
Number	Direction		Avg(mm)	SD	
(1)	width	124.24	124.352	0.0000314	-0.112
(2)	width	84.51	84.651	0.0000346	-0.141
(3)	height	120.05	120.104	0.0000271	-0.054
(4)	height	69.15	69.160	0.0000068	-0.010
(5)	height	63.11	63.151	0.0000115	-0.041
(6)	height	42.45	42.356	0.0000110	0.094
(7)	height	156.36	156.357	0.0000260	0.003
(8)	width	131.41	131.130	0.0000225	0.280
(9)	width	133.6	133.509	0.0000176	0.091
(10)	width	44.27	44.356	0.0000099	-0.086
(11)	height	101.05	101.183	0.0000201	-0.133
(12)	width	47.6	47.793	0.0000067	-0.193
(13)	height	144.38	144.579	0.0000191	-0.199
(14)	height	593	593.970	0.0001225	-0.970

Figure 10. Image-matching process at the boundary.
A) Process of mismatching. B) Difference between correct point and mismatched point. C) Point removal process using masked images derived from surrounding viewpoint images (Masked Matching).

Figure 11. Camera position estimation failure.

There is a risk of camera position estimation failure due to the accumulation of camera position estimation errors for all-around images taken at short intervals in SfM. A) Without CFCFM and pillar. B) With CFCFM and pillar.

GmJMC092 (KUROHIRA)

HOJAK

GmJMC112 (FUKUYUTAKA)

MISUZUDAIZU

Supplemental Fig. S1. Results of reconstruction of 3D point clouds of four soybean varieties using the proposed method.

The PLY data in this figure can be downloaded at https://github.com/tanasoft/MMM-CLCFM

GmJMC092 (KUROHIRA)

HOJAK

GmJMC112 (FUKUYUTAKA)

MISUZUDAIZU

Supplemental Fig. S2. Results of reconstruction of 3D point clouds for the same image in Fig. S1 using Metashape.

A

Executed MVS using four images
(Viewing angle 15 degrees)

Executed MVS using two images
(Viewing angle 5 degrees)

Difference in the number of images used in MMM

B

Viewing angle
240 degrees

Viewing angle
180 degrees

Viewing angle
90 degrees

Difference in the number of mask images used in point removal process

Supplemental Fig. S3. Results of running the analysis in Figs. 5 and 6 using Metashape 1.6.

MMM process without the point
removal process

MMM process with the point
removal process

Supplemental Fig. S4.
Results of running the analysis in Fig. 7 using Metashape 1.6.