Main Manuscript for

Protein Language Models Trained on Biophysical Dynamics Inform Mutation Effects

Chao Hou[1], Haiqing Zhao[4,5], Yufeng Shen[1,2,3,*]

1 Department of Systems Biology, Columbia University Irving Medical Center, New York, NY 10032

2 Department of Biomedical Informatics, Columbia University Irving Medical Center, New York, NY 10032

3 JP Sulzberger Columbia Genome Center, Columbia University, New York, NY 10032

4 Department of Biochemistry and Molecular Biology, University of Texas Medical Branch, Galveston, TX 77555

5 Sealy Center for Structural Biology and Molecular Biophysics, University of Texas Medical Branch, Galveston, TX 77555

* Corresponding author: Yufeng Shen

Email: ys2411@cumc.columbia.edu

Author Contributions: Y.S. and C.H. conceived the study. C.H. and H.Z. curated and processed the dataset, C.H. designed and implemented the methods, analyzed the data. C.H. drafted the manuscript. Y.S. and H.Z. critically revised the manuscript. All authors interpreted the results, reviewed, and approved the final version of the manuscript.

Competing Interest Statement: Disclose any competing interests here.

Classification: Biological Sciences / Biophysics and Computational Biology.

Keywords: molecular dynamics, protein language model, normal mode analysis, mutation effects.

This PDF file includes:

> Main Text
> Figures 1 to 5
> Table 1

Abstract

Structural dynamics are fundamental to protein functions and mutation effects. Current protein deep learning
models are predominantly trained on sequence and/or static structure data, which often fail to capture the
dynamic nature of proteins. To address this, we introduce SeqDance and ESMDance, two protein language
models trained on dynamic biophysical properties derived from molecular dynamics simulations and normal
mode analyses of over 64,000 proteins. Both models can be directly applied to predict dynamic properties of
unseen ordered and disordered proteins. SeqDance, trained from scratch, has attentions that capture dynamic
interaction and co-movement between residues, and its embeddings encode rich representations of protein
dynamics that can be further utilized to predict conformational properties beyond the training tasks via transfer
learning. SeqDance predicted dynamic property changes reflect mutation effect on protein folding stability.
ESMDance, built upon ESM2 (Evolutionary Scale Model II) outputs, substantially outperforms ESM2 in zero-
shot prediction of mutation effects for designed and viral proteins which lack evolutionary information.
Together, SeqDance and ESMDance offer a new framework for integrating protein dynamics into language
models, enabling more generalizable predictions of protein behavior and mutation effects.

Significance Statement

The sequence⎯structure (ensemble)⎯function relationship is central to biology. Protein dynamics in the
structure ensemble play a decisive role in determining function and mutation effects, and are widely used to
study thermodynamics, folding pathways, and dynamic interactions of ordered proteins, as well as the
conformational variability of intrinsically disordered proteins. However, current state-of-the-art protein deep
learning models, such as AlphaFold2,3 and ESM, focus on static structures and sequences, which failed to
directly capture protein dynamics. Here, we address this gap by developing protein language models to learn
dynamic properties of over 64,000 proteins. We show that the model's Transformer attentions capture protein
dynamic interactions, and our model can be applied to predict conformational properties and mutation effects.
24
Main Text
Introduction

Protein deep learning models have made significant progresses in predicting 3D structure (e.g., AlphaFold(1,
2), RoseTTAfold(3), and ESMFold(4)), protein function(5), stability(6), localization(7), and interactions(8). A
central challenge in developing effective models lies in the selection of information sources that models can
interpret and learn from. Broadly, these information can be classified into two main types: evolutionary and
biophysical(9).

Evolutionary information is derived from protein homologous sequences across species that have been
shaped by similar selection pressures. Multiple sequence alignments (MSAs) of homologs contain information
of conserved motifs and co-evolutionary pairs. Recently, protein language models (pLMs) like ESM1,2(4, 10),
ProtTrans(11), and ProGen(12), trained on large-scale protein sequence datasets, have emerged as powerful
tools to implicitly learn evolutionary information(13, 14). pLMs learn rich representations of evolutionary
information and perform well across diverse tasks, making them common baselines for evaluating new models.
MSAs and pLMs have been successfully applied to predict 3D structures(1, 4), predict pathogenic
mutations(15, 16), identify signal peptides(6), and even generate novel proteins(12). However, the
effectiveness of evolutionary information relies on the quality and quantity of available homologous sequences.
For instance, the confidences of structure predictions correlate to the number of homologous sequences(1,
4). As a result, evolutionary information is less effective for intrinsically disordered regions (IDRs), designed
proteins, rapidly evolving viral proteins, immune proteins, and those from under-studied species like
extremophiles(17), where homologous sequences are either sparse or highly divergent. Moreover,
evolutionary patterns in homologs are the outcomes of protein functions rather than the underlying causes
(Figure 1A). Overreliance on evolutionary information may bias models toward correlational patterns rather
than learning fundamental principles governing protein behaviors.

Biophysical information, primarily derived from protein structures, circumvents the limitations of evolutionary
information. Predicting protein behaviors from biophysical information aligns with the central paradigm that
sequence determines structure, and structure governs function (Figure 1A), thereby enabling models to
generalize more broadly across the protein universe. Biophysical information has been applied to a wide range
of biological questions. For example, predicted structures have been used to predict mutation effects and
functional sites(18). MaSIF(8) utilized biophysical and geometric features on protein surface to study protein
interactions. PScore(19) was trained to predict Pi-interactions derived from PDB(20) structures and can be

used to identify phase-separating proteins(21). Additionally, there have been initiatives to integrate biophysical
information into pLMs. ProSE(9) was trained to predict masked residues, contacts within static structures, and
structural similarities, while METL(22) was developed to predict biophysical properties derived from static
structures (Figure 1B). There were also pLMs that integrate structure token information(14, 23).

However, current protein models use biophysical information from static structures. These structural
snapshots lack crucial information about thermodynamics, allostery, folding, and dynamic interactions.
Moreover, static structures cannot describe the dynamic nature of IDRs, which constitute more than 30% of
the human proteome(24) and use their inherent flexibility to mediate essential biological processes. Protein
dynamics are fundamental to understand protein behaviors and mutation effects. Although evolutionary
information encodes aspects of protein dynamics(25, 26), it depends on the quality and quantity of
homologous sequences and cannot be directly extracted. Molecular dynamics (MD) simulations are routinely
used to study protein dynamics, generating ensembles of structures based on defined physical forces over
the simulation time. All-atom MD simulations are often computationally intensive to reach a converged
equilibrium state(27). Coarse-grained models simplify protein residues into beads and use specialized force
fields to reduce computation cost(24). Additionally, normal mode analysis (NMA)(28, 29) can describe protein
vibrations around the equilibrium conformation, with low-frequency modes capturing large-scale motions.
What's more, deep learning models have been developed to generate conformation ensembles(30, 31). While
these methods are wildly used to study protein dynamics, the produced data are often high-dimensional and
irregularly shaped. Thus, effectively and efficiently integrating these dynamic data into protein deep learning
models remains a significant challenge.

In this study, we present a deep learning framework to integrate dynamics data into protein language models.
Using dynamics profiles from 64,403 proteins, we pre-trained (i.e., train models on large scale, general
datasets to learn useful information before applying them to specific tasks) two models: SeqDance and
ESMDance. SeqDance is trained from scratch directly on protein dynamics data, whereas ESMDance is built
upon ESM2 outputs, which implicitly encode structural and evolutionary information. We demonstrated that
our models capture local dynamic properties and global conformational properties for proteins not included in
the training data. We also applied our models for zero-shot (applying models directly to a new task without
any additional training) prediction of mutation effects, achieving superior performance on designed and viral
proteins, where evolution-based methods typically underperform.

Results

Pre-training Protein Language Models on Dynamics Properties of over 64,000 Proteins.

To establish the protein dynamics dataset, we curated both high-resolution and low-resolution data sources.
High-resolution data includes experimental data and all-atom molecular dynamics (MD) simulation trajectories
from mdCATH(32), ATLAS(33), GPCRmd(34), PED(35). Since high-resolution data is limited, we further used
low-resolution dynamics data, including coarse-grained MD trajectories of human intrinsically disordered
regions (IDRs) from IDRome(24) and Normal mode analysis (NMA, we used the Gaussian Network Model(28)
(GNM) and the Anisotropic Network Model(29) (ANM))(28, 29) for representative structures in the PDB(36).
Overall, we collected 7,799 high-resolution data and 56,604 low-resolution data, covering ordered domains,
IDRs, membrane proteins, antibodies, and protein complexes (see Table 1 and SI Appendix Supplementary
Methods for details).

Table 1: Protein dynamic datasets

	Source	Description	Count	Method
	PED	Disordered regions	382	Experiment and others
High-resolution	GPCRmd	Membrane proteins	509	All-atom MD, ~500 ns $\times$ 3
	mdCATH	CATH domains	5,392	All-atom MD, ~464 ns $\times$ 5
	ATLAS	Ordered structures in PDB	1,516	All-atom MD, 100 ns $\times$ 3
Low-resolution	IDRome	Disordered regions	28,058	Coarse-grained MD
	Proteinflow	Ordered structures in PDB	28,546	Normal mode analysis

Figure 1: Information flow in protein study, representative protein language models, model pre-training and performance on test set.

A. Illustration of the "sequence - structure ensemble - function - evolution" paradigm. The sequence is the basis of a protein, which folds into a structural ensemble to perform its function. Functionally important region exhibits conserved patterns across homologs. **B**. Representative protein language models (pLMs) and their information sources. ESM1 and 2 were trained to predict masked residues and implicitly learned evolutionary information. ProSE was trained to predict masked residues, pairwise contact in static structures, and structure similarity. METL was trained to predict biophysical terms calculated from static structures. SeqDance and ESMDance were trained on protein dynamic properties from molecular dynamics (MD) simulations, experimental data, and normal mode analysis (NMA) of static structures. **C**. Diagram of the pre-training process. SeqDance and ESMDance take a protein sequence as input and predict residue-level and pairwise dynamic properties, which are extracted from structures ensembles and NMA. Both models use a Transformer encoder architecture identical to ESM2-35M, consisting of 12 layers with 20 heads per layer and an embedding dimension of 480. Linear layers are applied to the residue embeddings to predict residue-level properties. For pairwise property prediction, pairwise embeddings, constructed from residue embeddings, are concatenated with attention maps, a linear layer is then applied to predict pairwise properties. **D-E**. Comparison of SeqDance, ESMDance, and STARLING on 1,249 test IDRs (filtered to sequences ≤384 residues, since STARLING

We extracted residue-level and pairwise dynamic properties that describe the distribution of properties in
structure ensembles (Figure 1C, SI Appendix Table S1). Residue-level properties include normalized root
mean square fluctuation (RMSF), solvent accessible surface area (SASA), eight-class secondary structures,
and dihedral angles (*phi*, *psi*, *chi1*) which describe the rotations around bonds in the protein backbone and
side chains. Pairwise properties include the correlation of Cα movements and frequencies of hydrogen bonds,
salt bridges, Pi-cation, Pi-stacking, T-stacking, hydrophobic interactions, and van der Waals interactions. For
NMA data, we categorized normal modes of each structure into three frequency-based clusters. For each
cluster, we calculated residue fluctuation and pairwise movement correlation (see SI Appendix Table S1 and
Supplementary Methods for details).

We developed two models, SeqDance and ESMDance, both consisting of Transformer encoders and dynamic
property prediction heads (task-specific output layers). Both models take protein sequence as the only input,
use the encoder's final layer embeddings and attention maps to predict residue-level and pairwise dynamic
properties (Figure 1C). The Transformer encoder follows the same architecture as ESM2-35M (35 million
parameters) with 12 layers and 20 heads per layer, the dynamic property prediction heads contain 1.2 million
trainable parameters in total. The key difference between the two models lies in their initialization and use of
prior knowledge. In SeqDance, all parameters were randomly initialized, allowing the model to learn dynamic
properties from scratch. In contrast, ESMDance retains and freezes all parameters from ESM2-35M, enabling
it to leverage the evolutionary information already encoded in ESM2 to predict dynamic properties (see
Methods for details).

To balance contributions of different properties from different data sources, we adjusted their respective
weights in the loss function (see Methods for details). We clustered sequences using a 50% sequence identity
cutoff (same to ESM2 training), then randomly chose 95% of the clusters as the training set, reserving the
remaining 5% as the test set (no validation set was used, since we did not perform hyperparameter tuning;
see Methods). The training and test losses are shown in SI Appendix Figure S1. SeqDance and ESMDance
achieve comparable overall test losses, with SeqDance performing better on the IDRome test set and NMA
test set, while ESMDance performing better on the high-resolution test set. After pre-training, we observed
strong correlations between the weights of linear layers used to predict co-movement in MD simulations and
those used for co-movement in NMA, in both models (SI Appendix Figure S2). This result confirms that NMA
effectively captures dynamic motions similar to those observed in MD simulations, supporting its use as a
complementary source for augmenting model pre-training.

To assess the direct utility of SeqDance and ESMDance, we evaluated them on the test IDRome and high-
resolution datasets, comparing performance on IDRs against the IDR conformation generative model
STARLING(31) and on the high-resolution dataset against two NMA methods: GNM and ANM. We focused
on residue fluctuation and pairwise movement correlation (only residue pairs farther than five amino acids
were considered as recommended in CASP(37)), as they can be directly calculated from STARLING-
generated ensemble and normal modes. For test IDRs, SeqDance achieves median Pearson correlations of
0.87 for residue fluctuation and 0.89 for pairwise movement correlation, ESMDance achieves median
correlations of 0.82 and 0.83 for two tasks (Figure 1D–E). As a baseline, we used STARLING to generate 200
conformations for each test IDR, extracted dynamic properties from the generated ensemble. This approach
achieves median correlations of 0.82 and 0.85 for two tasks (Figure 1D–E), comparable to ESMDance but not
as good as SeqDance. For high-resolution ordered test proteins, SeqDance achieves median Pearson
correlations of 0.54 for residue fluctuation and 0.27 for pairwise movement correlation, while ESMDance
achieves 0.60 and 0.37, respectively (Figure 1F–G). As baselines, we used GNM and ANM (low-frequency 5
or 20 modes for GNM, 5×3 or 20×3 modes for ANM) to calculate dynamic properties. ESMDance is
comparable to ANM in predicting residue fluctuation and comparable to GNM with five modes in predicting
pairwise correlation, but overall, both SeqDance and ESMDance lag behind GNM and ANM when using 20
normal modes for ordered proteins (Figure 1F–G).

Taken together, by being trained on protein dynamic properties, SeqDance and ESMDance can be directly
applied to predict residue-level and pairwise dynamic properties for proteins dissimilar to those in the training
set. They demonstrate superior performance on IDRs for both residue-level and pairwise dynamics, and

satisfactory performance on residue-level dynamics of ordered proteins, using sequence as the only input
(NMA takes structure as input). SeqDance performs better on IDRs, whereas ESMDance performs better on
ordered proteins, consistent with the trends observed in the test losses (SI Appendix Figure S1) and in line
with the fact that evolutionary information is more informative for ordered proteins but less effective for IDRs.
In the following, we first assessed SeqDance's attention mechanism and embeddings, then compared its
predicted dynamic properties with mutation effect on protein stability, and examined the advantage of
ESMDance compared to ESM2 and SeqDance on predicting mutation effects.

SeqDance's Attentions Capture Dynamic Interactions and Co-movement.

The Transformer model employs self-attention mechanism(38) to aggregate information from other tokens,
with attention values representing the relationship between tokens (in protein context, amino acids). Here, we
evaluated whether SeqDance's attention mechanism captures dynamic interactions and residue co-movement.
The analysis was conducted on the test dataset, which included 404 high-resolution proteins, 1,355 IDRome
proteins, and 1,274 proteins with NMA. Additionally, we evaluated an independent test set comprising 29 MD
trajectories from the Dynamic PDB dataset(39). All test proteins share less than 50% sequence identity with
the SeqDance training sequences, allowing us to assess the model's ability to generalize to unseen proteins.
The Dynamic PDB test set was generated using a different MD force field to those used in pre-training,
enabling us to further evaluate SeqDance's generalization ability across different simulation conditions. For all
analyses, only residue pairs farther than five amino acids were considered as recommended in CASP(37).

Figure 2. SeqDance's attention mechanism captures dynamic interactions and co-movement in test sets.

For each attention head, Spearman correlation was calculated between attention values and pairwise dynamic properties, top five heads
of SeqDance and ESM2-35M are shown. **D-I** show results for positively correlated residue pairs. The boxplots show the distributions
of Spearman correlation on test proteins.

We compared the dynamic properties (interaction frequency and movement correlation) of residue pairs to
attention values from each attention head. We calculated Spearman correlations for all 240 attention heads

and highlighted the top five heads in Figure 2. For interaction frequency, the best attention heads of SeqDance
achieve median Spearman correlations of 0.41 on the high-resolution test set, 0.52 on the IDRome test set,
and 0.52 on the Dynamic PDB test set (Figure 2A-C; the best attention head for different data may be different).
For residue pairs with positive movement correlation in the MD ensemble, SeqDance performs particularly
well on the IDRome test set, achieving a median Spearman correlation of 0.74 for the best attention head. In
contrast, median Spearman correlations of best attention heads are just 0.22 for both ordered test set (high-
resolution and Dynamic PDB; Figure 2D-F), consistent with our results in Figure 1E, G. SeqDance's attention
do not capture residue pairs with negative movement correlation in the MD ensemble well (SI Appendix Figure
S3A-C). For NMA data, the best attention heads achieve median Spearman correlations of 0.34, 0.29, and
0.22 for positively correlated pairs in low-, medium-, and high-frequency modes, respectively (Figure 2G-I),
and Spearman correlations of –0.04, –0.26, and –0.35 for negatively correlated pairs in three frequency modes
(SI Appendix Figure S3D-F; negative correlation means better capturing this property).

We further evaluated ESM2-35M, as ESMDance was trained with ESM's parameters frozen and thus shares
identical attentions. We note that the test proteins are dissimilar to SeqDance's training data, but appear in,
or have homologs in, the ESM2 training data. Previous studies showed that ESM's attention heads capture
both native interactions observed in PDB structures(40) and non-native interactions observed in MD
simulations(25) via learning evolutionary information. Across all evaluations, ESM2-35M and SeqDance show
comparable performances (Figure 2; SI Appendix Figure S3). SeqDance performs slightly better on four
evaluations (interaction frequencies, negatively correlated pairs in the MD ensemble, and both positively and
negatively correlated pairs in NMA), while ESM2-35M performs slightly better on one evaluation (positively
correlated pairs in the MD ensemble). Overall, these results demonstrated that our pre-training strategy
enables SeqDance's attention to capture dynamic interactions and residue co-movement directly from
sequence, performing comparable to ESM2 on unseen proteins and different simulation conditions. ESM2's
ability to capture dynamic properties enabled us to train ESMDance, achieving comparable test loss to
SeqDance with far fewer trainable parameters (SI Appendix Figure S1).

SeqDance's Embeddings Encode Global Protein Conformation Properties.

Next, to assess SeqDance's generalization capability, we investigated whether SeqDance learns protein
conformational properties not included in the pre-training tasks. Specifically, we considered end-to-end
distance (R_e), asphericity, and radius of gyration (R_g), which quantify motion range, deviation from a spherical
shape, and compactness, respectively. Since these properties cannot be directly obtained from the model, we
trained linear regression models using its embeddings in a supervised manner. To ensure a fair comparison
with other pLMs in Figure 1B (ESMDance embedding is identical to ESM2-35M), we applied principal
component analysis to the mean-pooled embeddings from each method and used the top 200 components
as input for linear regression.

We first evaluated these pLMs on structure ensembles of IDRs(41) generated using a different coarse-grained
force field compared to SeqDance training set. After removing IDRs with over 20% sequence identity and 50%
coverage to any SeqDance training sequence, 28,717 IDRs remained (see Methods for details). We used
mean R_e, asphericity, and R_g in the ensemble (see Methods for how we account for the intrinsic length
dependence of R_g and R_e). The training and test sets were split in a 6:4 ratio using a 20% sequence identity
cutoff to prevent information leakage. Linear regression model was trained for each pLM, and the experiment
was repeated 20 times. SeqDance significantly outperforms the randomly initialized model prior to pre-training
and other pLMs (Figure 3A-C), reducing the MAEs (mean absolute errors) of the random model, ESM2-650M,
METL, and ProSE by 31%, 25%, 29%, and 31% on average, respectively.

For ordered proteins, obtaining conformational properties from structure ensembles is challenging due to the
computational cost of MD simulations. Therefore, we used R_g of over 10,000 static monomer structures in the
PDB database from the paper(42) (see Methods for details). Since SeqDance was trained on NMA of nearly
all representative PDB structures(36), we did not exclude sequences with homologs in SeqDance training set.
Using the same evaluation method described above, SeqDance outperforms the random model, ProSE, and
METL, and performs comparably to ESM2 (Figure 3D).

We also evaluated the performance using Pearson correlation and found similar results (SI Appendix Figure
S4A-D). Notably, even using the full embeddings instead of the first 200 principal components, SeqDance still
outperforms other pLMs in most tasks (SI Appendix Table S2), despite having the shortest embedding size.
Figure 3E–H shows the predictions of the linear model using full SeqDance embeddings on test proteins from
one experiment. SeqDance enables accurate predictions of conformational properties observed in MD

simulations of IDRs and in PDB structures of ordered proteins. We further compared SeqDance with
STARLING for IDRs and with ESMFold (3B parameters) for ordered proteins. We note that both STARLING
and ESMFold were trained on the same datasets used in our evaluation, meaning that a substantial fraction
of the test proteins was included in their training sets. For IDRs, SeqDance outperforms STARLING when
generating 20 conformations but underperforms STARLING when generating 200 conformations (Figure 3E–
G; SI Appendix Figure S4E–G). For ordered proteins, SeqDance embeddings and ESMFold yield comparable
performance (Figure 3H; SI Appendix Figure S4H). Thus, SeqDance provides an efficient alternative for
predicting protein conformational properties, achieving performance comparable to structure- and ensemble-
based methods while being orders of magnitude faster.

Figure 3. SeqDance's embeddings encode protein global conformational properties.

A-D. Performance comparison of SeqDance (35M parameters), METL, ProSE, and ESM2 (ESMDance embedding is identical to ESM2-
35M) in predicting the end-to-end distance of disordered regions (**A**), asphericity of disordered regions (**B**), radius of gyration of
disordered regions (**C**) and ordered proteins (**D**). The training and test split was 6:4 with a 20% sequence identity cutoff. Linear
regression model was trained to predict conformational property using the first 200 principal components of mean-pooled embeddings
from each method as input. Results presented are the distributions of the mean absolute error of 20 independent repeats. **E-G**.
Comparison of conformational properties of test IDRs obtained from coarse-grained MD simulations versus predictions from SeqDance
embeddings. **H**. Comparison of radius of gyration of test ordered proteins obtained from PDB structure versus predictions from
SeqDance embeddings. Results in **E-H** are predictions from linear regression models using the full embeddings rather than the first 200
principal components. Each dot represents a test protein, the blue line indicates the linear fit, and the dashed black line represents the
line of equality, marginal histogram shows the distribution of data.

SeqDance Predicted Dynamic Property Changes Reflect Mutation Effect on Protein Stability.

To evaluate whether SeqDance captures information about the biophysics of protein folding, we compared its
output with mutation effects on protein folding stability. We hypothesized that destabilizing mutations would
induce significant changes in protein dynamics, whereas mutations with minimal impact would induce smaller
dynamic changes. To test this hypothesis, we used SeqDance to predict dynamic properties for both wild-type
and mutated sequences, computed their relative changes, and compared these to experimentally measured
ΔΔG values (Figure 4A, see Methods for details). This approach was framed as a zero-shot prediction, as the
model was not specifically trained on mutation data. We applied this approach to the mega-scale protein
folding stability dataset(43), which includes ΔΔG values for 379,865 single mutations and 147,926 double
mutations across 412 proteins, encompassing both natural and designed proteins.

To evaluate the zero-shot predictive power of individual dynamic properties, we computed the Spearman
correlation between the relative change of each property and the corresponding ΔΔG values for mutations in
each protein. While the randomly initialized model prior to pre-training shows no predictive power, many
SeqDance-predicted properties achieve median Spearman correlations above 0.2 (Figure 4B; SI Appendix
Figure S5), confirming that pre-training enables SeqDance to capture meaningful biophysical dynamics.

Among individual properties, solvent-accessible surface area (SASA mean) emerges as one of the top-
performing properties, consistent with the fact that destabilizing mutations disrupt core packing and increase
solvent exposure. Dihedral angles *phi* and *psi* also rank highly, highlighting the role of backbone
conformational flexibility in protein stability. Additionally, pairwise movement correlations derived from MD
simulations and NMA demonstrate relatively high performance, further emphasizing the importance of
collective dynamics in predicting mutation effects. To integrate these dynamic properties, we used the
geometric mean of quantile-normalized relative changes (see SI Appendix Table S3 and Methods for details).
The unified score yields a median Spearman correlation of 0.24 across all 412 proteins.

Figure 4. Predicting mutation effect on protein folding stability.

A. Framework of using SeqDance (35M parameters) or ESMDance (35M parameters) to predict mutation effects. **B**. Distribution of
zero-shot prediction performance (Spearman correlation) on 412 proteins of different dynamic properties; the random model (color grey)
represents the randomly initialized model prior to pre-training. SASA mean, std: mean and standard deviation of solvent-accessible
surface area. NMA properties 1, 2, 3: properties calculated from low-, median-, and high-frequency normal modes. vdw: van der Waals
interaction; hbbb: backbone-to-backbone hydrogen bond; hbsb: side-chain-to-backbone hydrogen bond; hbss: side-chain-to-side-chain
hydrogen bond; hp: hydrophobic interaction; sb: salt bridge; pc: Pi-cation interaction; ps: Pi-stacking interaction; ts: T-stacking
interaction. **C**. SeqDance zero-shot prediction performance split by the most similar proteins in SeqDance training set. We used cutoff
of 95% sequence identity together with 95% coverage, 50% sequence identity together with 80% coverage, 20% sequence identity
together with 50% coverage. **D-F**. Relationship between zero-shot performance and the number of homologs (defined as 20% sequence
identity and 50% coverage) in training set. The line represents a polynomial regression of order two, with the shaded area indicating the
95% confidence interval. The x-axis shows the log-scaled number of homologs, with small random noises added to the x values to

reduce overlap. **G**. ESMDance zero-shot prediction performance split by the most similar proteins in ESMDance training set. **H-I**.
Performance of supervised linear regression models on test mutations from 412 proteins. For each protein, 50% of the mutations were
used to train the regression model, and the remaining 50% were reserved as the test set. For SeqDance and ESMDance, the regression
models used their 23 predicted dynamic property changes as input; for ESM2, the regression model used predictions from three models
(35M, 650M, and 15B) as input; and for SaProt, the zero-shot predictions of SaProt-35M were used as input.

To assess whether SeqDance's performance depends on the presence of homologs in its training set, we first
analyzed its performance relative to the most similar protein in the training set. SeqDance performs better on
proteins with close homologs of over 95% sequence identity in its training set (Figure 4C). For the 125 proteins
with such close homologs, the median Spearman correlation is 0.29, whereas for the 191 proteins with no
homologs in the training set, the median correlation is 0.20. Proteins with homologs of 20–95% sequence
identity show similar performance to those with no homologs. We also examined SeqDance's performance as
a function of the number of homologs (defined as over 20% sequence identity and 50% coverage) and
observed only a minor correlation (Figure 4D).

Furthermore, we compared SeqDance with ESM2, which can perform zero-shot prediction of mutation effects
by estimating the probability of 20 amino acids based on evolutionary information. ESM2-35M achieves a
median Spearman correlation of 0.33, outperforming SeqDance. This is consistent with the fact that
evolutionary information is highly effective in predicting mutation effects. However, the performance of ESM2
is strongly dependent on the number of homologs in its training set, UniRef50, particularly for proteins with
over 100 homologs (Figure 4E; ESM2-650M and -15B in SI Appendix Figure S6A, B). To isolate the effect of
homolog abundance, we evaluated a subset of 257 proteins that have a similar number of homologs (between
0 and 146) in both UniRef50 and the SeqDance training set. In this subset, ESM2-35M achieves a median
Spearman correlation of 0.22, comparable to SeqDance's performance of 0.24 (SI Appendix Figure S6C).
These results suggest that, given similar model size and training data abundance, SeqDance and ESM2
perform similarly in predicting mutation effect on protein stability. Overall, despite being pre-trained exclusively
on wild-type sequences and without reliance on evolutionary information, SeqDance is able to make
meaningful predictions about mutation effect on protein stability, even for proteins with no homologs in the
training set.

ESMDance Enhances Prediction of Mutation Effect on Protein Stability.

While both ESM2-35M, which leverages evolutionary information, and SeqDance, which captures protein
dynamic properties, can predict mutation effect on protein stability, their individual performance remains
modest at a model size of 35 million parameters. To harness the strengths of both approaches, we developed
ESMDance that integrates evolutionary and dynamic information, also with 35 million parameters. Using the
zero-shot approach illustrated in Figure 4A, ESMDance achieves a median Spearman correlation of 0.46
across 412 proteins (Figure 4F), significantly outperforming both ESM2-35M (0.33) and SeqDance (0.24).
Remarkably, ESMDance also matches or surpasses SaProt-35M(23) (0.45; SI Appendix Figure S6D), which
has similar model architecture but uses structure tokens as additional input, and much larger language models,
including ESM2-650M (0.46; SI Appendix Figure S6A) and ESM2-15B (0.43; SI Appendix Figure S6B).
Moreover, ESMDance demonstrates robust generalization: its performance is independent of the presence of
homologs in its training set or in UniRef50 (Figure 4F-G; SI Appendix Figure S6E). We note that proteins
without homologs in UniRef50 also lack homologs in the ESMDance training set. Thus, the performance gains
observed for these proteins are not attributable to the presence of their dynamic data in the ESMDance training.

These models' zero-shot predictions are correlated with ΔΔG, but not on the same physical scale. To align
them with ΔΔG, we fitted supervised linear regression models. For each protein, 50% of mutations were
randomly sampled for training and the remaining 50% were used for testing. Linear regression models of
SeqDance- and ESMDance-predicted dynamic property changes (23 relative changes, Figure 4B) achieve
median MAEs of 0.63 and 0.54 kcal/mol and median Spearman correlations of 0.44 and 0.58, respectively,
on test mutations from 412 proteins (Figure 4H-I), significantly outperforming their respective zero-shot
correlations. As a baseline, a linear regression model using zero-shot predictions from three ESM2 models
(35M, 650M, and 15B) achieves a median MAE of 0.56 kcal/mol, better than SeqDance but worse than
ESMDance (Figure 4H-I). We further trained regression models using predictions from multiple methods as
inputs. Adding SaProt-35M predictions to ESM2 decreases the MAE to 0.53 kcal/mol, while adding SeqDance
or ESMDance predictions yields larger improvements: ESM2 + SeqDance reaches 0.52 kcal/mol, ESM2 +
ESMDance reaches 0.48 kcal/mol, and combining ESM2, SeqDance, and ESMDance achieves the best
performance with a median MAE of 0.47 kcal/mol and a median Spearman correlation of 0.70 (Figure 4H–I).

Overall, these results demonstrate that by integrating evolutionary information learned by ESM2 with protein
dynamic properties, ESMDance achieves superior performance in predicting mutation effect on protein
stability. Furthermore, our models provide additional information to evolution-based models, and their
combination yields even greater predictive power.

Figure 5. Predicting mutation effects for designed and viral proteins.

A-D. Performance comparison between ESM2, SaProt (35M parameters), SeqDance (35M parameters), and ESMDance (35M parameters) for 135 designed proteins with no homologs in both UniRef50 and the SeqDance training set. Two highlighted proteins are further shown in E-F. **E-F.** Structure and the relationship between predictions and ΔΔG values for two designed proteins. The kernel density estimate plot shows the distribution of experimentally measured folding ΔΔG values and zero-shot prediction values for the three methods. The line represents the linear regression, with the shaded area indicating the 95% confidence interval. **G**. Relationship between experimental ΔΔG and relative solvent-accessible surface area of the mutation site. The line represents the linear regression fit. **H**. The SeqDance/ESMDance zero-shot prediction uses the geometric mean of 23 relative changes in dynamic properties, whereas the SeqDance/ESMDance linear-regression model uses a linear combination of the same 23 relative changes. For all linear-regression models, 50% of mutations were randomly sampled as training set for each protein, and the remaining 50% were used as test, the performances on test mutations were shown here. **I-J.** Zero-shot performance of ESM2, SaProt, SeqDance, and ESMDance on 23 viral proteins shorter than 1024 residues in ProteinGYM.

Biophysics-based Pre-training Improves Mutation Effect Prediction for Designed and Viral Proteins.

One limitation of ESM2 is that the evolutionary information it learns from natural proteins may fail to generalize to de novo designed proteins. To evaluate whether ESMDance can address this limitation, we analyzed a subset of 135 designed proteins that lack homologs in both UniRef50 and the SeqDance/ESMDance training set. ESM2-35M, -650M, and -15B achieve median Spearman correlations of 0.21, 0.32, and 0.29, respectively—significantly lower than their average performances (Figure 5A, 4E; SI Appendix Figure S6A, S6B). In contrast, ESMDance achieves a median Spearman correlation of 0.46, substantially outperforming SeqDance (0.20), SaProt-35M (0.06) and all ESM2 models (Figure 5A). Further analysis at the individual protein level revealed that the performances of different ESM2 models are highly correlated (Figure 5B). In contrast, both SeqDance and ESMDance exhibit orthogonal performance patterns to ESM2 (Figure 5C-D), with ESMDance showing significant improvements for most proteins compared to ESM2-35M (Figure 5D).

Furthermore, we visualized zero-shot predictions for two designed proteins (highlighted in Figure 5B-D). The first, r10_572_TrROS_Hall (Figure 5E), was designed using TrRosetta hallucination(43). Both SeqDance and ESMDance achieve significantly higher correlations (0.52 for both) compared to the ESM2 models (0.18, 0.25, and 0.20 for ESM2-35M, -650M, and -15B, respectively). The second, GG|run4_0284_0002 (Figure 5F), was designed using the EEHH method(43). Here, both ESM2 and SeqDance perform poorly (0.02, 0.09, -0.02, and 0.18 for ESM2-35M, -650M, -15B, and SeqDance, respectively), whereas ESMDance achieves a markedly higher correlation of 0.53. Linear regression models show similar results on test mutations of two proteins (SI Appendix Figure S7). This result underscores the advantage of ESMDance in directly integrating dynamic properties and evolutionary information during model training, outperforming separate predictions from two models.

Additionally, we benchmarked several established structure-based models. These included the inverse-folding model ProteinMPNN(44), which predicts sequence from structure and whose predicted sequence likelihood correlates with mutation effects on stability, as well as the biophysics-based models Rosetta(45) and FoldX(46) (see Methods for details), which directly estimate mutation ΔΔG values. We note that using the structure as input inherently simplifies stability prediction, since mutations in buried sites typically have larger effects, whereas surface mutations tend to have smaller effects (Figure 5G). We first evaluated Spearman correlation, ESMDance zero-shot outperforms ProteinMPNN but performs below FoldX and Rosetta, while ESMDance linear-regression performs comparably to FoldX and Rosetta (Figure 5H). We also assessed the mean absolute error (MAE), and our linear-regression models yield substantially lower MAE than both FoldX and Rosetta raw ΔΔG values. After calibrating FoldX and Rosetta raw ΔΔG values with experimental measurements using linear regression, their MAE becomes comparable to—but still slightly higher than—that of ESMDance linear-regression model (Figure 5H). Overall, these results suggest that our linear-regression models can serve as an alternative to traditional biophysics-based models while being orders of magnitude faster and requiring only sequence input.

Besides designed proteins, we also examined their performances on viral proteins, which evolve rapidly and are underrepresented in UniProt. For deep mutational scanning experiments in ProteinGYM(47), ESM2 models and SaProt-35M consistently perform worse on viral proteins compared to the other proteins regardless of model size (SI Appendix Figure S8). ESM2-35M achieves a median Spearman correlation around 0 on viral proteins (SI Appendix Figure S8). For 23 viral proteins shorter than 1024 residues, encompassing 187,902 mutations, SeqDance and ESMDance achieve median Spearman correlations of 0.18 and 0.25, respectively (Figure 5I-J), using the zero-shot approach in Figure 4A (which may not be the optimal strategy for mutational scanning beyond stability, see Discussion). They outperform ESM2-35M (0.03) and SaProt-35M (0.14) but are not as good as ESM2-15B (0.36; Figure 5I).

Discussion

In this work, we developed SeqDance and ESMDance, two protein language models (pLMs) pre-trained with dynamic properties derived from molecular dynamics (MD) simulations and normal mode analysis (NMA). SeqDance captures local dynamic interactions, residue co-movement, and global conformational properties after pre-training, using only single sequence input and without relying on evolutionary information. ESMDance integrates the evolutionary information encoded in ESM2 and the newly learned dynamic properties, significantly outperforms SeqDance and ESM2-35M in zero-shot prediction of mutation effects for designed and viral proteins.

In the pre-training process, we did not directly predict full structure ensembles due to the immense size of the dataset (over 60 million frames) and the complexity of modeling entire ensembles. Instead, we used simplified dynamic property descriptors such as the mean, standard deviation, and interval distribution of ensemble-derived properties. Prior study has demonstrated that mean values from structure ensembles provide significantly more information than those from static structures(48). This strategy enables SeqDance and ESMDance to learn from simplified but informative properties of protein dynamics, without the overwhelming computational demand of full ensemble modeling. During pretraining, the test losses plateaued early (SI Appendix Figure S1), but we continued training to enable models to learn dynamic information more effectively from the training set, as the training set was representative and relatively large, and extended training did not result in increased test loss. Using attention maps to predict pairwise properties constrains SeqDance to focus on interacting and co-moving residue pairs. This approach is crucial for learning biophysically meaningful information and improves SeqDance's ability to extrapolate to unseen proteins. Our results show that our pre-training strategy enables the transformer's attentions to effectively capture pairwise dynamic properties, using only 1/1000th of the training sequences compared to ESM2.

In Figures 1–2, both SeqDance and ESMDance achieve higher correlations for IDRs compared to ordered structures, likely because our models were trained on more IDR MD trajectories. In addition, the dynamics of IDRs are usually localized and easier to learn, whereas the dynamics of ordered structures often involve long-range interactions. SeqDance effectively learns global conformational properties of both ordered and disordered proteins (Figure 3), which are essential for understanding protein shape and flexibility. In comparison, METL(22) underperforms in predicting the radius of gyration (R_g) for ordered proteins (Figure 3D), despite having R_g prediction as a pre-training task. ProSE(9) performs well in predicting the conformational properties of ordered regions but struggles with IDRs (Figure 3), likely because its pre-training focused on ordered PDB structures. ESM2 performs well on both ordered and disordered proteins, as conformational properties are also conserved(41).

Current methods for zero-shot prediction of mutation effects use evolutionary information and static structure. These methods are less effective for proteins without sufficient homologs and structures. We applied SeqDance and ESMDance to predict mutation effects by calculating changes of dynamic properties between wild-type and mutated sequences. These results highlight the effectiveness and efficiency of integrating both evolutionary information and dynamic properties for understanding mutation effects, particularly for proteins that cannot be accurately predicted using evolutionary information or static structure. While, to our knowledge, we are the first to apply this kind of zero-shot strategy to predict mutation effects on protein, analogous approaches like Enformer(49) and Borzoi(50) have been used to predict effect of non-coding mutations in DNA sequences, where evolutionary information is also less effective. Our current zero-shot strategy uses changes across the entire protein, which is reasonable for predicting mutation effects on protein stability but not optimal for mutation effects on function, binding, or activity, where dynamic changes at functional sites, binding interfaces, or catalytic centers may be more relevant. Moreover, for SeqDance, the presence of highly similar proteins in the training set leads to improved performance on mutation effect (Figure 4C). Thus, running MD simulations for a protein of interest and using the extracted features to fine-tune SeqDance may yield better predictions, but this may not work for ESMDance (Figure 4G).

We did not compare our models to classical protein dynamics methods on specific proteins. This was a deliberate choice: our models are not intended as drop-in replacements for existing approaches, but rather as a first step toward a new paradigm that learn dynamic information with protein language models. In our work, all evaluations were performed on proteins shorter than 1,024 residues. We envision several directions to further improve the models. First, expanding protein dynamics data: while high-resolution data remain limited relative to the vast number of sequences, lower-resolution sources, such as coarse-grained MD simulations and NMA, can still provide valuable training signals. Second, training models on more detailed dynamic properties that describe higher-order relationships and time-dependent behaviors to capture more nuanced

aspects of protein motion. Third, employing more advanced model architectures (e.g., the Evoformer in
AlphaFold2(1)) and scaling up model size: as demonstrated in many areas of deep learning, larger models
can learn more complex patterns. Lastly, incorporating structural information as additional input may further
improve performance on ordered structures and mutation effect on stability.

In conclusion, SeqDance and ESMDance advance the integration of protein dynamic properties, captured
through molecular dynamics simulations and normal mode analysis, into deep learning frameworks. By
complementing widely used evolutionary and static structure-based models, our models reveal novel insights
into protein behavior and mutation effects, particularly for proteins lacking homologs, such as IDRs, designed
and viral proteins. This underscores the practical utility of dynamic properties as a critical, yet underexplored,
dimension in computational protein design and studies, offering a new tool to bridge the gap between
sequence, dynamics, and function.

Methods

Model Architecture

The models consist of a transformer encoder and the dynamic property prediction heads. The transformer
encoder uses the ESM2-35M architecture and the same sequence tokenizer. It comprises 12 layers with 20
attention heads each and employs rotational positional embeddings, with a final embedding dimension of 480.
The choice of the 35M model is due to both the relatively small training dataset (compared to hundreds of
millions of sequences) and our computational resources. Linear layers are added to predict residue-level
properties from the residue embeddings of the last transformer layer. For pairwise feature prediction, pairwise
embeddings are computed from residue embeddings as follows:

$$P_{ij} = concat(Q_i \odot Q_j, Q_i - Q_j) \tag{1}$$

$$Q = W_2\left(LayerNorm\left(GELU\left(W_1(E)\right)\right)\right) \tag{2}$$

where E represents the final residue embeddings, W_1 and W_2 are learnable linear matrices. i and j are residue
indexes, $\odot$ represents element-wise multiplication, The pairwise embeddings P_{ij}, along with attention values
from 240 heads, are passed through a linear layer to predict pairwise features. The dynamic property
prediction heads contain 1.2 million parameters in total.

Using attention maps and pairwise embeddings allows the model to capture the distinct characteristics of two
pairwise properties: the mean value of interaction frequency depends on the sequence length, as the
maximum number of interactions a residue can form is constrained, while the mean value of movement
correlation is length-independent. By combining length-dependent attention values (which sum to one after
SoftMax operation in attention calculation) with length-independent pairwise embeddings, the model can
capture both types of pairwise properties.

Different activation functions were used for different properties: For secondary structure and dihedral angles,
where the values for each property sum to one, SoftMax functions were used. For RMSF, which is normalized
to (0,1), Sigmoid functions were applied. For correlation properties, Tanh functions were used to maintain
values within (−1,1). For other non-negative properties, SoftPlus functions were applied (ReLU led to the dead
ReLU problem in our experiments).

Pre-training Procedure

Models were implemented and trained using PyTorch(51) (v2.5.1) and the Transformers library (v4.48.2,
https://huggingface.co/docs/transformers/index). Training was performed with a batch size of 128, parameters
were updated every three batches, each from high-resolution data, IDRome, and the NMA dataset.
Optimization was conducted using the AdamW optimizer, with a peak learning rate of 1×10^{-4}, an epsilon value
of 1×10^{-8}, betas of (0.9, 0.98), and a weight decay of 0.01. The learning rate was linearly warmed up over the
first 2,000 steps, followed by a linear decay to 1×10^{-5} over 90% of total training steps. To mitigate overfitting,
a dropout rate of 0.1 was applied in both the transformer encoder and the dynamic property prediction heads.

SeqDance was trained for 200,000 steps, with a maximum sequence length of 256 for the first 160,000 steps
and 1024 for the remaining 40,000 steps. ESMDance was trained for 60,000 steps, using a maximum

sequence length of 256 for the first 40,000 steps and 1024 for the final 20,000 steps. ESMDance has fewer
trainable parameters, both its training and test losses plateaued earlier (SI Appendix Figure S1). For
sequences exceeding the maximum length, a region of the max length was randomly selected, the selected
regions were different in each epoch. Two models were trained for ten days using four Nvidia L40s GPUs.
Due to computational constraints, hyperparameter tuning was not performed, which means the current model
configuration may not be the best.

Adjusting Weights of Dynamic Properties in the Loss Function

Root mean squared error (RMSE) was used as the loss function for pre-training. For interaction frequencies,
some interacting pairs exhibit frequencies close to zero, which are meaningful but treated similarly to zero in
RMSE. To address this, we applied a cube root transformation to scale up low-frequency interactions.

The models were pre-trained on multiple tasks of varying scales. To balance the losses across tasks, we used
the standard deviations of dynamic properties to calculate task-specific weights. The standard deviation of
each property for each protein in the training set was computed. For multi-class features, such as secondary
structures, the losses were calculated for each class and then averaged. These values were used to adjust
the task-specific weights. Given the higher complexity of pairwise properties compared to residue-level
properties, we set the pairwise-to-residue loss ratio to 3:1. For NMA data, this ratio was adjusted independently
for the three frequency ranges. The adjusted losses for SASA, RMSF, secondary structure, and dihedral
angles were kept equal. The adjusted losses for the nine interactions were kept equal. The ratio between the
summed interaction loss and the co-movement loss was set to 3:1. The final losses for high-resolution data,
IDRome data, and NMA data were further adjusted to be equal. The final weights for each property are
available at https://huggingface.co/datasets/ChaoHou/protein_dynamic_properties.

Attention analysis

The attention map and the interaction map are not symmetric (the interactions have direction), therefore, the
means of the original matrixes and its transposes were used. Only residues farther than five amino acids in
protein sequence are considered. The interaction frequencies of all nine interaction types were summed for
analysis. Only proteins shorter than 1,024 residues were analyzed.

Evaluation of Conformational Properties for IDRs and Ordered Structures

Conformational properties asphericity, end-to-end distance (R_e) and radius of gyration (R_g) from coarse-
grained MD trajectories of over 40,000 IDRs(41) were downloaded from https://zenodo.org/records/10198621.
Only IDRs ranging from 32 to 384 residues in length were included (the sequence cutoff was used because
we compared our model with STARLING, which can only generate conformation for sequence no longer than
384), IDRs with over 20% sequence identity and 50% coverage (determined using MMseqs2 search with
parameters: *-s 7 -a 1*) to any SeqDance training sequence were removed, resulting in a final set of 28,717
IDRs. R_g values were calculated for monomer PDB structures analyzed in the paper(42) using mdtraj, only
proteins no longer than 800 were analyzed (the sequence cutoff was used because we compared our model
with ESMFold, which runs out of GPU memory when processing long proteins).

Both R_e and R_g were first normalized to account for their inherent dependence on sequence length, as follows:

572
$$normalized\ R = \frac{R_0}{L^v} \tag{3}$$

Where *L* is the sequence length, and R_0 is a prefactor determined by the biochemical properties of the protein,
v is the scaling exponent. The v values for both R_e and R_g (for ordered protein and IDR separately) were
obtained by fitting a linear regression model between $log(R)$ and $log(L)$.

For both IDRs and ordered structures, MMseqs2 easy-cluster was used to cluster sequences with the
parameters: *--min-seq-id 0.2 -c 0.5 --cov-mode 0*. Sequences from 60% of randomly selected clusters were
used as the training set, while the remaining sequences formed the test set. SeqDance was compared with
METL (METL-G-50M-1D), ESM2 models, and ProSE. The last layer embeddings of SeqDance, METL, and
ESM2, and concatenated embeddings of all layers of ProSE (as suggested in their GitHub:

https://github.com/tbepler/prose) were used. All embeddings were mean-pooled along protein sequences.
Linear regression (scikit-learn v1.4.1) with default parameters was used to predict conformational properties
(asphericity, normalized R_e, and normalized R_g), trained separately for the embeddings from each method.
The predicted normalized R_e and normalized R_g were then multiplied with L^ν to get the final prediction.
Principle component analysis was conducted with scikit-learn.

STARLING was used to generate structure ensembles of IDRs with default parameters. ESMFold (3 billion
parameters) was used to predict structure of ordered protein.

Prediction of Mutation Effects

590 For SeqDance and ESMDance, the dynamic properties of both wild-type and mutated sequences were
591 predicted. For property i, the zero-shot score S_i is computed as:

$$S_i = mean\left(\left|\frac{P_i^{MT} - P_i^{WT}}{P_i^{WT}}\right|\right) \tag{4}$$

where P_i^{WT} and P_i^{MT} represent the predicted values of property i for the wild-type and mutated sequences,
respectively. The relative change was computed element-wise. For example, in the case of secondary
structure with eight classes, the resulting relative change matrix had a shape of $L×8$ for a protein of length L,
and the mean of absolute values of this matrix was used as the zero-shot score of secondary structure.

To combine scores from different methods, multiple aggregation strategies were evaluated, including mean,
max, weighted mean, and geometric mean, applied to both raw and quantile-normalized scores. Quantile
normalization ensures that different score distributions are same by aligning their values as mean of raw
values of each rank. Weighted mean and geometric mean were calculated as:

$$S_{\text{weighted}} = \frac{\sum_{i=1}^{M} S_i S_i}{\sum_{i=1}^{M} S_i} \tag{5}$$

$$S_{\text{geometric}} = \left(\prod_{i=1}^{M} S_i\right)^{\frac{1}{M}} \tag{6}$$

Where M is the number of all properties. All these zero-shot scores are non-negative. To compare them with
negative ΔΔG values, the negative of the zero-shot scores was used. Various strategies to combine the
relative changes of different dynamic properties were tried but not improvement over using individual
properties such as mean SASA or dihedral angle *psi* was observed. Users may use these two individual
properties for applications. SeqDance and ESMDance are not suitable for cross-protein prediction in our
experiment, as the effects of dynamic property changes vary between proteins.

For ESM2 models and SaProt, we followed the method used in ProteinGYM. Each residue in a protein was
sequentially masked, the model was used to predict the probabilities of 20 amino acids for the masked position.
For a protein of length L, the model was run L times to obtain the wild-type and mutated residue probabilities
at each site. The log-likelihood ratio (LLR) was then calculated for each mutation. For double mutations, the
LLR scores of the two single mutations were summed to approximate the combined effect. For ESM2-15B,
half-precision (float16) was used, as the model could not be loaded onto a single GPU with 48 GB of memory.
For SaProt, structure tokens were used as additional input. For ProteinMPNN(44) (vanilla_model_weight
v_48_020), full-sequence likelihoods were used to infer mutation effects. For FoldX(46), the structures were
first repaired using the RepairPDB command, and the BuildModel command was then applied to compute
ΔΔG values. For Rosetta, ΔΔG values were calculated using the RosettaDDGPrediction(45) protocol (Rosetta
version 2022.11, cartddg2020_ref2015). Because Rosetta is computationally expensive, 100 mutations per
protein were randomly sampled for evaluation. AlphaFold-predicted protein structures were used as input for
these models.

Mutation Datasets

For the evaluation of protein folding stability, the dataset
"Tsuboyama2023_Dataset2_Dataset3_20230416.csv" and AlphaFold-predicted protein structures were
downloaded from https://zenodo.org/records/7992926. Proteins were defined using the "WT_name" column

in the table. Insertions and deletions were removed, as well as substitution mutations without "ddG_ML" values.
The mean "ddG_ML" values for the same sequence were used. Homologs in both the SeqDance/ESMDance
model training set and UniRef50 (downloaded in February 2025) were identified using MMseqs2 search with
the parameters: *-s 7 -a 1 --max-seqs 1000.* The surface area was calculated using MDTraj, relative surface
area was calculated by dividing the solvent-accessible surface area of each residue by the maximum surface
area of the corresponding amino acid across all proteins.

ProteinGYM data and predictions for these mutations were downloaded from its website
(https://proteingym.org/) and GitHub in June 2025.

Acknowledgments
This work was supported by NIH grants (R35GM149527) and Simons Foundation SFARI #1019623. We thank
Dr. Guojie Zhong, Aziz Zafar, and Di Liu for helpful discussions and suggestions.

Data availability
The extracted dynamic properties (approximately 100 GB in total), sequences (including train-test splits), loss
weights for different properties, and all other data required to reproduce main results in this paper are available
at: https://huggingface.co/datasets/ChaoHou/protein_dynamic_properties.

Code availability
The codes for feature extraction, model training and evaluations are available on GitHub:
https://github.com/ShenLab/SeqDance.   Model   weights   are   available   at:
https://doi.org/10.5281/zenodo.15047777.

Competing interests
The authors declare no competing interests.

652
653

References

1. J. Jumper, *et al.*, Highly accurate protein structure prediction with AlphaFold. *Nature* (2021).
https://doi.org/10.1038/s41586-021-03819-2.

2. J. Abramson, *et al.*, Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature*
(2024). https://doi.org/10.1038/s41586-024-07487-w.

3. M. Baek, *et al.*, Accurate prediction of protein structures and interactions using a three-track neural network.
Science **373**, 871–876 (2021).

4. Z. Lin, *et al.*, Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*
379, 1123–1130 (2023).

5. M. Kulmanov, *et al.*, Protein function prediction as approximate semantic entailment. *Nature Machine*
Intelligence **6**, 220–228 (2024).

6. C. Hou, Y. Li, M. Wang, H. Wu, T. Li, Systematic prediction of degrons and E3 ubiquitin ligase binding via
deep learning. *BMC Biol* **20**, 162 (2022).

7. H. R. Kilgore, *et al.*, Protein codes promote selective subcellular compartmentalization. *Science* **387**, 1095–
1101 (2025).

8. P. Gainza, *et al.*, Deciphering interaction fingerprints from protein molecular surfaces using geometric deep
learning. *Nat Methods* **17**, 184–192 (2020).

9. T. Bepler, B. Berger, Learning the protein language: Evolution, structure, and function. *Cell Syst* **12**, 654-
669 e3 (2021).

10. A. Rives, *et al.*, Biological structure and function emerge from scaling unsupervised learning to 250 million
protein sequences. *Proc Natl Acad Sci U S A* **118** (2021).

11.   A. Elnaggar, *et al.*, ProtTrans: Toward Understanding the Language of Life Through Self-Supervised
Learning. *IEEE Trans Pattern Anal Mach Intell* **44**, 7112–7127 (2022).

12.   A. Madani, *et al.*, Large language models generate functional protein sequences across diverse families.
Nat Biotechnol **41**, 1099–1106 (2023).

13.   Z. Zhang, *et al.*, Protein language models learn evolutionary statistics of interacting sequence motifs.
Proc Natl Acad Sci U S A **121**, e2406285121 (2024).

14.   T. Hayes, *et al.*, Simulating 500 million years of evolution with a language model. *Science* **387**, 850–858
(2025).

15.   G. Zhong, Y. Zhao, D. Zhuang, W. K. Chung, Y. Shen, PreMode predicts mode-of-action of missense
variants by deep graph representation learning of protein sequence and structural context. *Nat Commun* **16**,
7189 (2025).

16.   H. Zhang, M. S. Xu, X. Fan, W. K. Chung, Y. Shen, Predicting functional effect of missense variants using
graph attention neural networks. *Nat Mach Intell* **4**, 1017–1028 (2022).

17.   F. Ding, J. Steinhardt, Protein language models are biased by unequal sequence sampling across the
tree of life. *bioRxiv* 2024.03.07.584001 (2024). https://doi.org/10.1101/2024.03.07.584001.

18.   M. Akdel, *et al.*, A structural biology community assessment of AlphaFold2 applications. *Nat Struct Mol*
Biol **29**, 1056–1067 (2022).

19.   R. M. Vernon, *et al.*, Pi-Pi contacts are an overlooked protein feature relevant to phase separation. *eLife*
7, e31486 (2018).

20.   H. M. Berman, *et al.*, The Protein Data Bank. *Nucleic acids research* **28**, 235–242 (2000).

21.   C. Hou, *et al.*, PhaSepDB in 2022: annotating phase separation-related proteins with droplet states, co-
phase separation partners and other experimental information. *Nucleic Acids Res* **51**, D460–D465 (2023).

22.   S. Gelman, *et al.*, Biophysics-based protein language models for protein engineering. *Nat Methods* **22**,
1868–1879 (2025).

23.   J. Su, *et al.*, SaProt: Protein Language Modeling with Structure-aware Vocabulary. *bioRxiv*
2023.10.01.560349 (2024). https://doi.org/10.1101/2023.10.01.560349.

24.   G. Tesei, *et al.*, Conformational ensembles of the human intrinsically disordered proteome. *Nature* (2024).
https://doi.org/10.1038/s41586-023-07004-5.

25.   A. Fung, A. Koehl, M. Jagota, Y. S. Song, The Impact of Protein Dynamics on Residue-Residue
Coevolution   and   Contact   Prediction.   *bioRxiv*   2022.10.16.512436   (2022).
https://doi.org/10.1101/2022.10.16.512436.

26.   H. K. Wayment-Steele, *et al.*, Predicting multiple conformations via sequence clustering and AlphaFold2.
Nature (2023). https://doi.org/10.1038/s41586-023-06832-9.

27.   S. Piana, K. Lindorff-Larsen, D. E. Shaw, Atomic-level description of ubiquitin folding. *Proceedings of the*
National Academy of Sciences **110**, 5915–5920 (2013).

28.   T. Haliloglu, I. Bahar, B. Erman, Gaussian Dynamics of Folded Proteins. *Physical Review Letters* **79**,
3090–3093 (1997).

29.   A. R. Atilgan, *et al.*, Anisotropy of fluctuation dynamics of proteins with an elastic network model. *Biophys*
J **80**, 505–15 (2001).

30.   S. Lewis, *et al.*, Scalable emulation of protein equilibrium ensembles with generative deep learning.
Science **0**, eadv9817 (2025).

31.   B. Novak, J. M. Lotthammer, R. J. Emenecker, A. S. Holehouse, Accurate predictions of conformational
ensembles   of   disordered   proteins   with   STARLING.   [Preprint]   (2025).   Available   at:
https://www.biorxiv.org/content/10.1101/2025.02.14.638373v1 [Accessed 9 October 2025].

32.   A. Mirarchi, T. Giorgino, G. De Fabritiis, mdCATH: A Large-Scale MD Dataset for Data-Driven
Computational Biophysics. *Sci Data* **11**, 1299 (2024).

33. Y. Vander Meersche, G. Cretin, A. Gheeraert, J. C. Gelly, T. Galochkina, ATLAS: protein flexibility
description from atomistic molecular dynamics simulations. *Nucleic Acids Res* **52**, D384–D392 (2024).

34. I. Rodriguez-Espigares, *et al.*, GPCRmd uncovers the dynamics of the 3D-GPCRome. *Nat Methods* **17**,
777–787 (2020).

35. H. Ghafouri, *et al.*, PED in 2024: improving the community deposition of structural ensembles for
intrinsically disordered proteins. *Nucleic Acids Res* **52**, D536–D544 (2024).

36. Y. Mi, S.-B. Marcu, V. V. B. Yallapragada, S. Tabirca, ProteinFlow: An advanced framework for feature
engineering in protein data analysis. *Biotechnology and Bioengineering* **121**, 3563–3571 (2024).

37. A. Kryshtafovych, T. Schwede, M. Topf, K. Fidelis, J. Moult, Critical assessment of methods of protein
structure prediction (CASP)-Round XIII. *Proteins* **87**, 1011–1020 (2019).

38. A. Vaswani, *et al.*, Attention is all you need in (2017), pp. 5998–6008.

39. C. Liu, *et al.*, Dynamic PDB: A New Dataset and a SE(3) Model Extension by Integrating Dynamic
Behaviors and Physical Properties in Protein Structures. [Preprint] (2024). Available at:
http://arxiv.org/abs/2408.12413 [Accessed 9 October 2025].

40. R. Rao, J. Meier, T. Sercu, S. Ovchinnikov, A. Rives, Transformer protein language models are
unsupervised structure learners. *bioRxiv* 2020.12.15.422761 (2020).
https://doi.org/10.1101/2020.12.15.422761.

41. J. M. Lotthammer, G. M. Ginell, D. Griffith, R. J. Emenecker, A. S. Holehouse, Direct prediction of
intrinsically disordered protein conformational properties from sequences. *Nat Methods* (2024).
https://doi.org/10.1038/s41592-023-02159-5.

42. J. J. Tanner, Empirical power laws for the radii of gyration of protein oligomers. *Acta Crystallogr D Struct*
Biol **72**, 1119–1129 (2016).

43. K. Tsuboyama, *et al.*, Mega-scale experimental analysis of protein folding stability in biology and design.
Nature **620**, 434–444 (2023).

44. J. Dauparas, *et al.*, Robust deep learning–based protein sequence design using ProteinMPNN. *Science*
378, 49–56 (2022).

45. V. Sora, *et al.*, RosettaDDGPrediction for high-throughput mutational scans: From stability to binding.
Protein Sci **32**, e4527 (2023).

46. J. Schymkowitz, *et al.*, The FoldX web server: an online force field. *Nucleic Acids Res* **33**, W382-8 (2005).

47. P. Notin, *et al.*, ProteinGym: Large-Scale Benchmarks for Protein Fitness Prediction and Design.
Advances in Neural Information Processing Systems **36**, 64331–64379 (2023).

48. S. Gu, *et al.*, Can molecular dynamics simulations improve predictions of protein-ligand binding affinity
with machine learning? *Brief Bioinform* **24** (2023).

49. Ž. Avsec, *et al.*, Effective gene expression prediction from sequence by integrating long-range
interactions. *Nature Methods* **18**, 1196–1203 (2021).

50. J. Linder, D. Srivastava, H. Yuan, V. Agarwal, D. R. Kelley, Predicting RNA-seq coverage from DNA
sequence as a unifying model of gene regulation. *Nature Genetics* (2025). https://doi.org/10.1038/s41588-
024-02053-6.

51. A. Paszke, *et al.*, PyTorch: An Imperative Style, High-Performance Deep Learning Library. [Preprint]
(2019). Available at: http://arxiv.org/abs/1912.01703 [Accessed 9 October 2025].