Deciphering RNA regulation with a foundation language model

Hanwen Zhou [1, 2, †], Yue Hu [3, †] *, Yulong Zheng [1, 2], Jiefu Li [1, 2], Jielong Peng [1, 2],

Guoqing Zhang [1, 2] *, Zefeng Wang [2, 4] *

[1] National Genomics Data Center & Bio-Med Big Data Center, CAS Key Laboratory

of Computational Biology, Shanghai Institute of Nutrition and Health, Chinese

Academy of Sciences, Shanghai, China.

[2] University of Chinese Academy of Sciences, Chinese Academy of Sciences, Beijing,

China.

[3] School of Medicine, Department of Pharmacy, University of North Carolina at Chapel

Hill, Chapel Hill, NC, USA

[4] School of Life Science, Southern University of Science and Technology, Shenzhen,

Guangdong, China

Keywords: RNA regulation, language model, splicing, translation, degradation

† These authors contributed equally to this work.

* Correspondence to: Yue Hu, Tel: +1 919 600 0000, E-mail: yue_hu@med.unc.edu;

Guoqing Zhang, Tel: (+86) 021-54920465, E-mail: gqzhang@picb.ac.cn; Zefeng Wang,

Tel: (+86) 021-54920416, E-mail: wangzefeng@picb.ac.cn

Abstract

RNAs are widely regulated in cellular processes by their *cis*-regulatory elements

and *trans*-acting RNA binding proteins, the information of which is encoded in RNA

sequences spanning evolutionary diversity. Deciphering the rules underlying RNA

regulation can provide new insights into molecular mechanisms and RNA therapies.

The large language models have demonstrated their efficacy in the analysis of human

languages and protein sequences. Considering the similarities in semantic and syntactic

features between RNA sequences and human language, we developed LAMAR, a

foundation <u>la</u>nguage <u>m</u>odel for RN<u>A</u> <u>r</u>egulation, aimed at capturing the intrinsic

characteristics of RNA sequences. The model was first pretrained on approximately 15

million sequences of genes and transcripts from 225 mammals and 1569 viruses. By

leveraging LAMAR as a foundational platform, we fine-tuned the pretrained model

with labeled datasets across various tasks. The resulting fine-tuned model outperformed

the best benchmark by up to 9% for predicting mRNA translation efficiency, and

improved by 7% for predicting the RNA half-life. We further applied LAMAR to

predict the splice sites of pre-mRNAs and internal ribosome entry sites driving cap-

independent translation, the performances of which were comparable with the state-of-

the-art methods. The results indicated that our foundation language model is applicable

for comprehensive regulatory analysis of RNA, providing new clues into molecular cell

biology and disease.

The code is available at https://github.com/rnasys/LAMAR.

Keywords: RNA regulation, language model, splice site, translation, degradation

Introduction

As an important component of the central dogma, RNAs play various roles in multiple biological processes, ranging from the templates for protein synthesis [1] to regulators of gene expression [2]. The cellular processes of RNA are regulated by its *cis*-regulatory elements and *trans*-acting recruited RNA binding proteins [3], the information of which are encoded in RNA sequences spanning evolutionary diversity. Deciphering the regulatory rules of RNA will provide new insights into molecular mechanisms and further design novel therapeutics.

With the advancement of biochemical technologies and bioinformatics, many researchers have developed computational tools to analyze the accumulated regulatory maps of RNA [4-8]. While well-designed algorithms were previously developed for specific question, a unified framework to learn the diverse regulation of RNA is lacking. The Large Language Models have demonstrated that unsupervised pretraining of a vast corpuses of text can significantly advance our comprehension [9] and generative capabilities of language [10]. The pretrained model serves as a foundation platform that can further be fine-tuned to solve multiple downstream tasks. In light of the similarity of semantic and syntactic features between RNA sequences and human language, some studies explored the potential of language models to capture the essence of RNA. RNA-MSA [11] and RNAErnie [12] were developed to predict the secondary structures of non-coding RNAs. RNA-FM was pretrained on non-coding RNAs and fine-tuned to solve multiple tasks including prediction of RNA tertiary structures and binding sites of RNA binding proteins [13]. However, the present foundation language models still lacked insights on RNA regulation. In addition, the current models were all pretrained on non-coding RNA sequences, and thus the extracted sequence features are mainly related to the functions and structures of non-coding RNAs. Therefore, the extracted sequence features may be biased to highly structured non-coding RNAs and insufficient in dissecting downstream tasks related to processing of RNA precursors and functions of mature mRNAs.

To address these challenges, we developed a foundation language model for RNA
regulation, named LAMAR, by unsupervised pretraining on approximately 15 million
RNA sequences with multiple functions across mammalians. LAMAR can effectively
distinguish between regulatory elements or transcripts with distinct functions within the
representation space, indicating that it has successfully captured the functional
attributes solely from sequences. By leveraging LAMAR as a foundation platform, we
were able to fine-tune this pretrained model with labeled datasets across a range of tasks
including supervised modeling of splice sites, translation efficiency, internal ribosome
entry sites (IRESs) and degradation. Our results showed that the performances of these
fine-tuned models were better than or comparable with the state-of-the-art methods that
were specially designed for each task, which demonstrated the power of large language
model in dissecting the diverse functions determined by the RNA sequences, providing
new clues for underlying cellular mechanisms.
88

Results

The pretrained RNA foundation model

We developed the RNA foundation model with the similar architecture as the

transformer encoders. We first pretrained the model with large-scale unlabeled RNA

sequences, and then fine-tuned the model with task-specific datasets to solve the

downstream tasks. To efficiently learn the sequence features and evolutionary

information of RNA, around 15 million nucleotide sequences of multiple functions

across species were downloaded and processed as training corpus from RefSeq and

RNACentral databases (Figure 1A). The mRNAs, non-coding RNAs and genes of

mammals and viruses were included, covering around 270 billion nucleotide tokens

(Figure 1B, C). In the pretraining stage, we used the mask learning strategy to train the

model. A portion of the nucleotides were masked and then predicted by contextual

sequences, enabling the model to learn the interactions between nucleotides (Figure 1E).

We pretrained two models with the context length of up to 2048 and 4096 tokens,

considering the sequence length of genes and transcripts and training resources (Figure

1D). In the fine-tuning stage, the task-specific predictor was stacked on the encoder for

downstream tasks. We will validate our RNA foundation model by four downstream

tasks: prediction of splicing sites, translation efficiency and IRES activity and

degradation rates of RNA (Figure 1F).

The pretrained model learned the functional features of RNAs

To investigate whether the model learned the biochemical properties of nucleotides

within pretraining, we compared the hidden embeddings of four classes of nucleotides.

Each nucleotide was represented as one vector by averaging the hidden embeddings of

nucleotides in 500 randomly selected human mRNAs and long non-coding RNAs. We

used the Principal Component Analysis to project the representative vectors into two-

dimensional space. As shown in Figure 2A, the adenine A and guanine G which are

dicyclic purines, the cytosine C and thymine T which are monocyclic pyrimidines are

the closest pair for the first dimension, indicating that the model learned the

biochemical properties of nucleotides from large-scale unlabeled sequences. The

distances of hidden embeddings were presented in Supplementary Figure 1.

To verify whether the pretrained model extracted the functional features of RNAs,

we input translation regulatory elements of different functions into the pretrained model

and observed the clusters of outputs. By calculating the mean of the hidden embeddings

at each position in sequence, each element was represented as a single vector and further

projected into two-dimensional space using t-Distributed Stochastic Neighbor

Embedding (tSNE). Compared with the random scatter of the outputs from the

untrained model (NMI=0.041), the RNA sequences with same functions were more

likely to be clustered together (NMI=0.531) (Figure 2B). The same results were also

found for RNAs with different function (NMI=0.060 for untrained model vs

NMI=0.327 for pretrained model) (Figure 2C). These results indicate that the model

successfully extracted the functional features of RNA sequences in unlabeled self-

supervised pretraining.

The fine-tuned model predicted splice sites accurately

In the process of eukaryotic gene expression, the spliceosome precisely identifies

splice sites and catalyzes the transformation of pre-mRNAs into mature transcripts [14].

Accurately predicting splice sites is crucial for understanding the link between genetic

mutations and their phenotypes [15, 16]. Currently, various computational tools such as

SpliceAI [5] have been developed to forecast splice sites within pre-mRNA sequences.

A large number of studies have shown that the human splice sites have regular

sequence motifs in their flanking sequences [17], suggesting that the splicing sites have

similar contextual information and the hidden embeddings of which from pretrained

model were expected be similar. To investigate the effect of pretraining, we used the

tSNE algorithm to project the hidden embeddings of the 5' and 3' splicing sites into the

two-dimensional space. As shown in Figure 3B, the splice sites and non-splicing sites

were grouped respectively, indicating that the pretrained model successfully learned the

contexts of splicing sites, which could be applied to subsequent fine-tuning.

We further fine-tuned the LAMAR to predict the probabilities of 5' and 3' splice

sites for each nucleotide in human pre-mRNA sequences. We used the same datasets

consistent with SpliceAI and set the sequence length as 1024 for fine-tuning (Figure

3A). A variety of strategies were tested: a) fine-tuning without pretrained weights, b)

fine-tuning with frozen pretrained weights and c) fine-tuning with all parameters. As

illustrated in Figure 3C, fine-tuning with all parameters achieved the best Precision-

Recall Area Under Curve (PRAUC) and outperformed strategies a and b by up to 0.013

and 0.050, respectively. We defined the best model as LAMAR-SS. It is worth noting

that fine-tuning with only a simple prediction head could achieve good result

(PRAUC=0.918), indicating the effectiveness of pretraining. We compared LAMAR-

SS with benchmark methods including SpliceAI and RNAFM. To control the sequence

length for fine-tuning, the sub-models spliceAI-400 and spliceAI-2k were selected

which predicted the splicing sites based on flanking 200nt and 1000nt sequences. Figure

3D showed that our method achieves better results than other methods. In particular,

LAMAR-SS outperforms spliceAI-400 by up to 0.036, spliceAI-2k by up to 0.02 and

RNAFM by up to 0.015 in terms of PRAUC (outperforms spliceAI-400 by up to 0.049,

spliceAI-2k by up to 0.035 and RNAFM by up to 0.057 in terms of Top-k accuracy).

The fine-tuned model predicted translation efficiency accurately

The 5' untranslated region (5' UTR) plays a major role in the control of translation

efficiency of mRNA [18]. Understanding the relationship between 5' UTR sequences

and levels of protein expression can help enhance the protein production to optimize

the potency of mRNA therapy [19, 20].

In this section, we fine-tuned LAMAR to predict the translation efficiency of

human mRNAs based on 5' UTR sequences (Figure 4A). The 10903 transcripts from

human embryonic kidney (HEK) 293T cell line was selected for training [19]. The

translation efficiency of these transcripts was measured by Ribo-seq. We fine-tuned

LAMAR with all parameters and achieved the best result in all strategies, which we

named it as LAMAR-TE (Supplementary Figure 2). Since UTR-LM outperformed than

classical methods in prediction of translation efficiency of 5' UTRs [21], we selected

UTR-LM and RNAFM as benchmarks. The results of 10-fold cross validation showed

that LAMAR-TE outperformed RNAFM and UTR-LM by up to 9% and 14% for the

mean squared error respectively (MSE) (Figure 4B), and by up to 7% and 18% for the

Spearman correlation coefficient (Figure 4C). UTR-LM was pretrained on sequences

and secondary structures of 5' UTRs using approximately 1 million parameters. The

superior performance of LAMAR-TE suggested that our model probably learned the

structural information of 5' UTRs exclusively from sequences with much more

parameters.

The fine-tuned model predicted IRES activity accurately

The internal ribosome entry sites (IRESs) drive the cap-independent translation of

some mRNAs under stressful conditions [22]. The translation of circular RNAs

(circRNAs) lacking 5' and 3' ends can also be initiated through IRESs [23, 24].

Although a small number of IRESs were identified from high-throughput screening

experiments [25-27], most of them have not been annotated.

In this section, we fine-tuned LAMAR to classify sequences with IRES activity

(Figure 5A). The 1,901 experimentally validated IRESs from IRESite [28], IRESbase

[29], and RFAM [30] databases were collected as positive sequences (Figure 5B). The

structural RNAs were sampled from RFAM database as negative sequences. We fine-

tuned the model with all parameters and achieved the best result in all fine-tuned

strategies, which was named as LAMAR-IRES (Supplementary Figure 3). Some

algorithms have been built to annotate the IRESs, such as IRESPred [31], IRESfinder

[32] and IRESpy [33]. Since these methods were trained on noisy experimental libraries,

we did not select them and fine-tuned RNAFM as the benchmark. Figure 5C showed

that both two fine-tuned models achieved the good AUC around 0.98.

To verify the effect of *in silico* screening of IRES, we used LAMAR-IRES to

classify the published experimental libraries sourced from viral and cellular mRNAs

[25-27]. As illustrated in Figure 5D, the median of predicted probabilities of putative

IRESs are significantly higher than those of remaining sequences, revealing the *in silico*

screening ability of LAMAR-IRES. We further tested the model with in-house

experimental data sourced from single strand viral genomes. The results showed that

the activities of predicted IRES were significantly higher than those of predicted not

IRES (Figure 5E), suggesting that our model integrated the causal relationship between

RNA sequence and IRES activity.

The fine-tuned model predicted RNA degradation rates accurately

As one of the most prominent sequences regulating mRNA decay, the 3'

untranslated regions (3' UTRs) recruit RNA binding proteins to promote or inhibit

degradation pathways [34].

In this section, we fine-tuned our LAMAR to predict the half-life of mRNAs

containing different 3' UTRs (Figure 6A). The half-lives of 1967 3 'UTRs were

measured by high-throughput experiments in the BEAS-2B cell line in David Erle

dataset [35]. Consistent with the previous section, we measured the model performance

in predicting the half-lives of 3' UTR with ten-fold cross-validation. We compared the

performances of various fine-tuning strategies and found that the full-parameter fine-

tuned model with the contextual length of 4096 tokens achieved the best result

(Supplementary Figure 4A, B). We named the fine-tuned model as LAMAR-DR and

benchmarked with other methods. Comparison with RNAFM, LAMAR-DR improved

the MSE by 7.4% (Figure 6B) and the correlation coefficient by 8.0% (Figure 6C).

We further tested LAMAR-DR by predicting the mutational effects with the

saturation mutation data on CXCL2 3' UTR. For each mutation, we take the difference

between the half-life of the mutant sequence and the natural sequence as the mutational

effect. The results showed that the mutation effect predicted by LAMAR-DR was

consistent with the experimental results, and revealed that there was a strong

degradation element, AU-rich element (ARE), in the upstream of 3' UTR (Figure 6D).

The Spearman correlation coefficient between predicted mutation effect and

experimental results was 0.515 (Supplementary Figure 4C).

Discussion

We presented a foundation language model LAMAR for multilayer regulation of

RNA. The model learned the semantic representations of RNA by unsupervised

pretraining on a large number of cross-species and multi-type RNA sequences. We fine-

tuned the model with labeled datasets for several tasks including prediction of splice

sites, translation efficiency, IRES activity and degradation rate. Our model

outperformed benchmark methods including RNAFM and UTR-LM, reflecting the

extraordinary performance of LAMAR in RNA regulation modeling. Interestingly,

although RNAFM was pretrained on non-coding RNA sequences from RNACentral

database, it could be finetuned to achieve good results in tasks about mRNA regulation,

indicative of the powerful generalization of the pretrained models.

Since LAMAR shared the similar architecture with transformer encoders

containing the self-attention layers, the number of parameters is proportional to the

square of the input length. Therefore, some ultra-long RNA sequences cannot be fully

input into the model during pre-training and fine-tuning due to the limitation of graphic

memory. Training with split sequence segments leads to the loss of distant

coevolutionary information in RNA. In addition, the attributes of RNAs such as

translation efficiency and degradation rate are dependent on entire sequences [36].

Training with partial sequence elements will lose the model performance. Fortunately,

several frameworks have been designed for ultra-long sequences recently [37, 38], and

we will explore these techniques in the next version of the model.

References

1. Brenner S, Jacob F, Meselson M: **An Unstable Intermediate Carrying Information from Genes to Ribosomes for Protein Synthesis.** *Nature* 1961, **190:**576-581.
2. Statello L, Guo C-J, Chen L-L, Huarte M: **Gene regulation by long non-coding RNAs and its biological functions.** *Nature Reviews Molecular Cell Biology* 2021, **22:**96-118.
3. Licatalosi DD, Darnell RB: **RNA processing and its regulation: global insights into biological networks.** *Nature Reviews Genetics* 2010, **11:**75-87.
4. Fan X, Chang T, Chen C, Hafner M, Wang Z: **Accurate prediction of RNA translation with a deep learning architecture.** *bioRxiv* 2023**:**2023.2007.2008.548206.
5. Jaganathan K, Kyriazopoulou Panagiotopoulou S, McRae JF, Darbandi SF, Knowles D, Li YI, Kosmicki JA, Arbelaez J, Cui W, Schwartz GB, et al: **Predicting Splicing from Primary Sequence with Deep Learning.** *Cell* 2019, **176:**535-548.e524.
6. Song Z, Huang D, Song B, Chen K, Song Y, Liu G, Su J, Magalhães JPd, Rigden DJ, Meng J: **Attention-based multi-label neural networks for integrated prediction and interpretation of twelve widely occurring RNA modifications.** *Nature Communications* 2021, **12:**4011.
7. Stroup EK, Ji Z: **Deep learning of human polyadenylation sites at nucleotide resolution reveals molecular determinants of site usage and relevance in disease.** *Nature Communications* 2023, **14:**7378.
8. Sun L, Xu K, Huang W, Yang YT, Li P, Tang L, Xiong T, Zhang QC: **Predicting dynamic cellular protein–RNA interactions by deep learning using in vivo RNA structures.** *Cell Research* 2021, **31:**495-516.
9. Devlin J, Chang M-W, Lee K, Toutanova K: **BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding.** In *North American Chapter of the Association for Computational Linguistics*. 2019
10. Brown TB, Mann B, Ryder N, Subbiah M, Kaplan J, Dhariwal P, Neelakantan A, Shyam P, Sastry G, Askell A, et al: **Language Models are Few-Shot Learners.** *ArXiv* 2020, **abs/2005.14165**.
11. Zhang Y, Lang M, Jiang J, Gao Z, Xu F, Litfin T, Chen K, Singh J, Huang X, Song G, et al: **Multiple sequence alignment-based RNA language model and its application to structural inference.** *Nucleic Acids Research* 2023, **52:**e3-e3.
12. Wang N, Bian J, Li Y, Li X, Mumtaz S, Kong L, Xiong H: **Multi-purpose RNA language modelling with motif-aware pretraining and type-guided fine-tuning.** *Nature Machine Intelligence* 2024, **6:**548-557.

293   13.   Chen J, Hu Z, Sun S, Tan Q, Wang Y, Yu Q, Zong L, Hong L, Xiao J,
294   King I, Li Y: **Interpretable RNA Foundation Model from Unannotated**
295   **Data for Highly Accurate RNA Structure and Function Predictions.**
296   *bioRxiv* 2022.
297   14.   Matera AG, Wang Z: **A day in the life of the spliceosome.** *Nature*
298   *Reviews Molecular Cell Biology* 2014, **15:**108-121.
299   15.   Xiong HY, Alipanahi B, Lee LJ, Bretschneider H, Merico D, Yuen RKC,
300   Hua Y, Gueroussov S, Najafabadi HS, Hughes TR, et al: **The human**
301   **splicing code reveals new insights into the genetic determinants of**
302   **disease.** *Science* 2015, **347:**1254806.
303   16.   Soemedi R, Cygan KJ, Rhine CL, Wang J, Bulacan C, Yang J, Bayrak-
304   Toydemir P, McDonald J, Fairbrother WG: **Pathogenic variants that**
305   **alter protein code often disrupt splicing.** *Nature Genetics* 2017,
306   **49:**848-855.
307   17.   Wang ZF, Burge CB: **Splicing regulation: From a parts list of**
308   **regulatory elements to an integrated splicing code.** *RNA* 2008,
309   **14:**802-813.
310   18.   Hinnebusch AG, Ivanov IP, Sonenberg N: **Translational control by 5′**
311   **-untranslated regions of eukaryotic mRNAs.** *Science* 2016,
312   **352:**1413-1416.
313   19.   Cao J, Novoa EM, Zhang Z, Chen WCW, Liu D, Choi GCG, Wong ASL,
314   Wehrspaun C, Kellis M, Lu TK: **High-throughput 5′ UTR engineering**
315   **for enhanced protein production in non-viral gene therapies.** *Nature*
316   *Communications* 2021, **12:**4138.
317   20.   Castillo-Hair S, Fedak S, Wang B, Linder J, Havens K, Certo M, Seelig
318   G: **Optimizing 5'UTRs for mRNA-delivered gene editing using deep**
319   **learning.** *Nature Communications* 2024, **15:**5284.
320   21.   Chu Y, Yu D, Li Y, Huang K, Shen Y, Cong L, Zhang J, Wang M: **A 5′**
321   **UTR language model for decoding untranslated regions of mRNA**
322   **and function predictions.** *Nature Machine Intelligence* 2024, **6:**449-
323   460.
324   22.   Yang Y, Wang Z: **IRES-mediated cap-independent translation, a path**
325   **leading to hidden proteome.** *Journal of Molecular Cell Biology* 2019,
326   **11:**911-919.
327   23.   Fan X, Yang Y, Chen C, Wang Z: **Pervasive translation of circular**
328   **RNAs driven by short IRES-like elements.** *Nature Communications*
329   2022, **13:**3751.
330   24.   Pamudurti NR, Bartok O, Jens M, Ashwal-Fluss R, Stottmeister C, Ruhe
331   L, Hanan M, Wyler E, Perez-Hernandez D, Ramberger E, et al:
332   **Translation of CircRNAs.** *Molecular Cell* 2017, **66:**9-21.e27.
333   25.   Chen C-K, Cheng R, Demeter J, Chen J, Weingarten-Gabbay S, Jiang
334   L, Snyder MP, Weissman JS, Segal E, Jackson PK, Chang HY:

Structured elements drive extensive circular RNA translation. *Molecular Cell* 2021, **81:**4300-4318.e4313.

26. Weingarten-Gabbay S, Elias-Kirma S, Nir R, Gritsenko AA, Stern-Ginossar N, Yakhini Z, Weinberger A, Segal E: **Systematic discovery of cap-independent translation sequences in human and viral genomes.** *Science* 2016, **351:**aad4939.

27. Yang Y, Fan X, Ye Y, Chen C, Ludwig SEJ, Zhang S, Lu Q, Will CL, Urlaub H, Sun J, et al: **Unbiased screen of human transcriptome reveals an unexpected role of 3′ UTRs in translation initiation.** *bioRxiv* 2021:2021.2005.2028.446092.

28. Mokrejš M, Mašek T, Vopálenský V, Hlubuček P, Delbos P, Pospíšek M: **IRESite—a tool for the examination of viral and cellular internal ribosome entry sites.** *Nucleic Acids Research* 2010, **38:**D131-D136.

29. Zhao J, Li Y, Wang C, Zhang H, Zhang H, Jiang B, Guo X, Song X: **IRESbase: A Comprehensive Database of Experimentally Validated Internal Ribosome Entry Sites.** *Genomics, Proteomics & Bioinformatics* 2020, **18:**129-139.

30. Kalvari I, Nawrocki EP, Ontiveros-Palacios N, Argasinska J, Lamkiewicz K, Marz M, Griffiths-Jones S, Toffano-Nioche C, Gautheret D, Weinberg Z, et al: **Rfam 14: expanded coverage of metagenomic, viral and microRNA families.** *Nucleic Acids Research* 2021, **49:**D192-D200.

31. Gritsenko AA, Weingarten-Gabbay S, Elias-Kirma S, Nir R, de Ridder D, Segal E: **Sequence features of viral and human Internal Ribosome Entry Sites predictive of their activity.** *PLOS Computational Biology* 2017, **13:**e1005734.

32. Zhao J, Wu J, Xu T, Yang Q, He J, Song X: **IRESfinder: Identifying RNA internal ribosome entry site in eukaryotic cell using framed k-mer features.** *Journal of Genetics and Genomics* 2018, **45:**403-406.

33. Wang J, Gribskov M: **IRESpy: an XGBoost model for prediction of internal ribosome entry sites.** *BMC Bioinformatics* 2019, **20:**409.

34. Mayr C: **Regulation by 3′-Untranslated Regions.** *Annual Review of Genetics* 2017, **51:**171-194.

35. Zhao W, Pollack JL, Blagev DP, Zaitlen N, McManus MT, Erle DJ: **Massively parallel functional annotation of 3′ untranslated regions.** *Nature Biotechnology* 2014, **32:**387-391.

36. Agarwal V, Kelley DR: **The genetic and biochemical determinants of mRNA degradation rates in mammals.** *Genome Biology* 2022, **23:**245.

37. Nguyen E, Poli M, Faizi M, Thomas AW, Sykes CB, Wornow M, Patel A, Rabideau C, Massaroli S, Bengio Y, et al: **HyenaDNA: long-range genomic sequence modeling at single nucleotide resolution.** In *Proceedings of the 37th International Conference on Neural Information Processing Systems.* pp. Article 1872. New Orleans, LA, USA: Curran

377   Associates Inc.; 2024:Article 1872.

38. Nguyen E, Poli M, Durrant MG, Thomas AW, Kang B, Sullivan J, Ng MY, Lewis A, Patel A, Lou A, et al: **Sequence modeling and design from molecular to genome scale with Evo.** *bioRxiv* 2024**:**2024.2002.2027.582234.

39. Lin Z, Akin H, Rao R, Hie B, Zhu Z, Lu W, Smetanin N, Verkuil R, Kabeli O, Shmueli Y, et al: **Evolutionary-scale prediction of atomic-level protein structure with a language model.** *Science* 2023, **379:**1123-1130.

40. O'Leary NA, Wright MW, Brister JR, Ciufo S, Haddad D, McVeigh R, Rajput B, Robbertse B, Smith-White B, Ako-Adjei D, et al: **Reference sequence (RefSeq) database at NCBI: current status, taxonomic expansion, and functional annotation.** *Nucleic Acids Research* 2016, **44:**D733-D745.

41. Consortium RN: **RNAcentral 2021: secondary structure integration, improved sequence search and new member databases.** *Nucleic Acids Research* 2021, **49:**D212-D220.

42. Dao T, Fu DY, Ermon S, Rudra A, Ré C: **FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness.** *arXiv e-prints* 2022**:**arXiv:2205.14135.

Methods

1. Model architecture

We developed a foundation language model for studying RNA regulation, named LAMAR. The model shares the similar architecture with ESM-2 [39] and consists of the embedding layer, encoder block and predictor. The encoder block contains 12 encoder layers, each of which has 12 self-attention heads. The specific predictor was designed for different tasks.

When RNA sequences are input into LAMAR, sequence x was tokenized into the list of tokens $(x_1, x_2, \ldots, x_L)$, and was added with [cls] and [eos] token at the beginning and end of the list, where $x_i \in$ ['A', 'T', 'C', 'G', 'N'] and L represents the length of RNA sequence. The tokens were converted into vectors with 768 dimensions by the embedding layer and finally the RNA sequence was represented as a (L+2, 768) dimensional embedding matrix. The Embedding matrix becomes the final embedding of the RNA sequence through the encoder block.

In the pretraining stage, we trained the model with masked language modeling. The 15% of the nucleotides in RNA sequences were randomly masked and then predicted with the remaining unmasked nucleotides. The predictor was consisted of two linear layers and a layer-normalization layer. The Loss function can be expressed as:

$$Loss = E_x E_M \sum_{i \in M} -logP(x_i | x_{\sim M}; \Theta) \tag{1}$$

In formula (1), M represents the indices of masked nucleotides, and $\sim M$ represents the complement of M, that is, the indices of unmasked nucleotides. Θ represents the trainable parameters of the model.

The downstream tasks were categorized into two types: token classification and sequence regression. For token classification, the functional class of each nucleotide was predicted through the two stacked linear layers. The classification loss was defined as the cross-entropy between the predicted and true labels of tokens. For sequence regression, the functional attributes of RNAs were predicted by the embedding of the

[cls] token followed by two stacked linear layers. The regression loss was calculated by

the squared error between the predicted and actual values.

2. Pretrained datasets

The pretrained datasets of LAMAR derived from four sources: 1) Protein coding

and non-coding transcripts of mammals from RefSeq [40]; 2) Non-coding transcripts

of mammals from RNACentral [41]; 3) Referenced genes of mammals from NCBI

Genome; 4) Referenced genes of viruses that infect mammals from NCBI Genome.

RefSeq (Release 221) contained 13,319,105 transcripts of 223 mammalian species

in 15 suborders. The sequences were downloaded as fna.gz format from website

https://ftp.ncbi.nlm.nih.gov/refseq/release/vertebrate_mammalian/. RNACentral

(Release 23) contained 2,649,775 non-coding transcripts from 4,669 mammals, 214 of

which were included to be consistent with species in RefSeq datasets. The sequences

could be downloaded from https://ftp.ebi.ac.uk/pub/databases/RNAcentral/releases/23

.0/sequences/. As of Dec 14 2023, NCBI Genome contained 222 mammalian reference

genomes annotated by RefSeq. The sequences and annotations were respectively

downloaded as fna.gz and gff.gz from the links on the metadata file

(https://ftp.ncbi.nlm.nih.gov/genomes/refseq/vertebrate_mammalian/assembly_summ

ary.txt). The 6,033,179 reference genes were extracted from the reference genomes by

bedtools with annotations. As of Jan 4 2024, NCBI Virus contained 15,037 viral

reference genomes, 1579 of which infected mammals were included into pretrain

datasets (https://ftp.ncbi.nlm.nih.gov/genomes/refseq/viral/assembly_summary.txt).

The 19,007 reference genes were extracted by bedtools with annotations. The above

data were merged into the initial corpus, 15,455,049 transcripts and 5,832,792 genes in

total.

For the initial pretrained corpus, the sequences less than 15nt in length were filtered.

In order to remove the redundant sequences, we used MMseq2 tool to respectively

cluster transcripts and genes (cluster mode=2, identity=0.8, coverage=0.8), and

obtained 6,673,915 and 4,557,965 clusters, respectively.

3. Training procedure

3.1 Pretraining stage

To access our pretrained model, we built a validation set by randomly leaving out
1% of gene and transcript clusters, and pretrained the model with the remaining clusters.
The representative sequences from each cluster and 50% of the member sequences were
included into pretraining corpus, with an upper limit of 200 members per cluster. In
addition, the testing corpus was composed of the representative sequences of testing
cluster. In all, the training corpus encompassed a total of 14,873,638 sequences, which
accounted for approximately 269 billion tokens. The testing corpus comprised 112,808
sequences, providing representative samples for validation.
We pretrained two models with contextual lengths of 2048 and 4096 tokens. When
the length of the pretraining sequences exceeded these limits, they were segmented into
fragments shorter than the contextual length. The overlap of 256 and 512 tokens were
ensured between adjacent fragments to maintain contextual information. For the
evaluation phase, we randomly extracted fragments with contextual length from testing
sequences that exceeded the pretraining length. Any testing sequences with more than
10% Ns were excluded. The 10,000 sequences were randomly sampled for validation.
Our model underwent 250,000 training steps to reach convergence, with batch sizes
set to 512 and 256 for context lengths of 2048 and 4096 tokens. We utilized the AdamW
optimizer which was regulated by a learning rate schedule involving warm up and decay.
The learning rate was warmed up during the first 10,000 steps to the maximum value
1e-4 and then decayed in remaining steps. The model was pretrained with FP16 mixed
precision and speeded up with FlashAttention library [42]. The pretraining was
conducted on 8 A800 80GB graphic process units, taking around 260 hours to finish
training.

3.2 Fine-tuning stage

We used 10-fold cross-validation to evaluate the performance of fine-tuned models except for prediction of splice sites. The optimal combination of hyperparameter was identified using a grid search of batch size, learning rate, and training steps. Consistent with the pretraining stage, the AdamW optimizer with linear decay of learning rate was selected. The model was fine-tuned with FP32 precision on the Sugon Z-100 16GB and Tesla V100 32GB clusters of graphic process units.

4. Analysis of RNA embedding

The encoder block transforms a sequence of length L into an embedding matrix of size (L+2, 768). The vector (i+1, 768) is set as the embedding for the i_{th} nucleotide, while the average of the embedding matrix is served as the embedding for the entire sequence.

5. Downstream tasks

5.1. Prediction of splice sites

We used the same dataset as SpliceAI [5] to predict the splice sites of human pre-mRNAs. The dataset consisted of 15,036 protein coding transcripts annotated by Gencode V24lift37. The transcripts from chromosome 2, 4, 6, 8, 10-22, X, Y were used to fine-tune the model (13,384 transcripts, 130,796 pairs of splice sites), and the other transcripts from chromosome 1, 3, 5, 7, 9 were included in validation set (1,652 transcripts, 14,289 pairs of splice sites). We used bedtools to extract the transcript sequences from hg19 reference genome with annotation files. The fine-tuning length was set to 1024 tokens due to limited graphic memory. The pre-mRNAs longer than 1024 tokens were segmented into fragments of 1024 tokens, with an overlap of 256 tokens. The labels of sequences were assigned using the annotation file, where the 5' splice site was encoded as 1, the 3' splice site as 2, and neither as 0. The middle regions

504 of 768 tokens were predicted by the entire fragments during fine-tuning.

5.2. Prediction of translation efficiency

We selected Cao dataset [19] to predict the translation efficiencies of mRNAs based
on 5' UTRs. The expression and translation efficiency of 10903 human transcripts were
measured by mRNA-seq and Ribo-seq in HEK293 cell line. The 5' UTRs were
extracted by bedtools from hg19 reference genome with GENCODE V17 annotation.
The fine-tuning length was set to 1024 tokens for this downstream task. When the 5'
UTR sequence exceeded 1024 tokens, the segment of 1024 tokens closest to the 3' end
was included in the fine-tuned set.

5.3. Annotation of IRES

The training set for IRES annotation were derived from IRESite [28], IRESbase [29]
and RFAM [30] databases. The 1,901 experimentally validated IRES sequences and
2,026,606 non-IRES sequences were collected. To avoid the data leakage caused by
sequence similarity, we used MMseqs2 to cluster positive sequence and negative
sequence respectively (identity=0.9, coverage=0.9), and obtained 903 positive clusters
and 810,096 negative clusters. We sampled the representative sequences from the
negative clusters so that the number of positive and negative sequences is the same and
the length distribution is similar. We randomly selected 50% of the positive and
negative clusters as the training set and the rest as the evaluation set. We repeated the
experiment 10 times to measure the performance of the model.

5.4. Prediction of degradation rates

We selected David Erle dataset [35] to predict the half-lives of mRNAs based on 3'
UTRs. The half-lives of 2790 3' UTRs were measured by Massive Parallel Reporter
Assays in BEAS-2B cell line. The 1967 3'UTRs of 160 nucleotides with detected half-
lives were included in fine-tuned dataset. The AU-rich element and context sequence

of CXCL2 3' UTR was saturated mutated [35]. The variant effect was assessed by

comparing the steady-state mRNA levels between control and mutated sequences.

Figures and figure legends

Fig 1. Pretraining an RNA foundation model for multilayer regulation of RNA.

(A) Schematic diagram of pretraining data processing. **(B)** The taxonomic makeup of

the pretraining species consisting of the mammals (top) and the viruses (bottom). **(C)**

The number of the nucleotide in the genes and transcripts. **(D)** The sequence length of

the genes and transcripts in the pretraining dataset. **(E)** Schematic diagram of the

pretraining model which predicts the likelihoods of the masked tokens given a sequence.

The encoder comprised the self-attention layers and fully-connected layers. **(F)**

Schematic diagram of the downstream tasks including supervised prediction of splice

site, translation efficiency, internal ribosome entry site (IRES) and degradation rate.

Fig 2. LAMAR learned the biological properties of nucleotides and the function features of RNAs.

Top, embeddings from pretrained model. Bottom, embeddings from untrained model. **(A)** The PCA plot visualizing the embeddings of four classes of nucleotides. **(B)** The tSNE plot visualizing the embeddings of translation regulated elements: 5' UTR, CDS and 3' UTR. **(C)** The tSNE plot visualizing the embeddings of RNAs: mRNA, lncRNA, snRNA, miRNA, snoRNA and tRNA.

Fig 3. Prediction of splice sites of pre-mRNAs.

(A) Schematic diagram of the fine-tuned model predicting splice sites. The model predicts the probability that a nucleotide is a 5' splice site, a 3' splice site or neither given the pre-mRNA segments that are 1024 nucleotides long. **(B)** The tSNE plots visualizing the embeddings of the splice sites and control sites output from the untrained model (top) and the pretrained model (bottom). **(C)** The Top-K accuracy and PRAUC of the models finetuned with different strategies. **(D)** The Top-K accuracy and PRAUC of LAMAR-SS and benchmarks including SpliceAI submodels and RNAFM.

Fig 4. Prediction of translation efficiencies of mRNAs base on 5' UTRs.

(A) Schematic diagram of the fine-tuned model predicting translation efficiencies of mRNAs based on 5' UTRs. **(B)** The mean squared error between observed translation efficiency and predicted values of LAMAR-TE and benchmarks including RNAFM and UTRLM. **(C)** The spearman correlation coefficient between observed translation efficiency and predicted values of LAMAR-TE and benchmarks. The P values were calculated with Wilcoxon signed rank test. *, P value < 0.05; **, P value < 0.01.

Fig 5. Annotation of IRES.

(A) Schematic diagram of the fine-tuned model annotating IRES. **(B)** The number of

collected experimentally validated IRESs sourced from IRESite, IRESbase and RFAM

databases. **(C)** The AUC curves of LAMAR-IRES and RNAFM. **(D)** The predicted

probabilities of sequences in three experimental libraries screening IRES. **(E)** The

activities of predicted IRESs and not-IRESs by LAMAR-IRES in HepG2 cell lines.

Fig 6. Prediction of degradation rates of 3' UTRs.

(A) Schematic diagram of the fine-tuned model predicting the half-times of mRNAs containing different 3' UTRs. **(B)** The mean squared error between observed half-times and predicted values of LAMAR-DR and benchmarks. **(C)** The spearman correlation coefficient between observed half-times and predicted values of LAMAR-DR and benchmarks. **(D)** The observed (Top) and predicted (Bottom) variant effects of CXCL2 3' UTR. The nucleotides of the AU-rich element were colored in orange. *P* values were calculated with Wilcoxon signed rank test. *, *P* value < 0.05; **, *P* value < 0.01.