A foundation language model to decipher diverse regulation of RNAs

Hanwen Zhou [1,2][†], Yue Hu [3,†][*], Yulong Zheng [1], Jiefu Li [1], Jielong Peng [1], Jiang Hu [4], Yun Yang [4], Guoqing Zhang [1][*], Zefeng Wang [1,2][*]

[1] Bio-Med Big Data Center, Chinese Academy of Sciences Key Laboratory of Computational Biology, Shanghai Institute of Nutrition and Health, University of Chinese Academy of Sciences, Chinese Academy of Sciences, Shanghai 200031, China

[2] School of Life Science, Guangming Advanced Research Institute, Southern University of Science and Technology, Shenzhen, Guangdong, China

[3] School of Medicine, Department of Pharmacy, University of North Carolina at Chapel Hill, Chapel Hill, NC, USA

[4] CirCode Biomedicine Inc., Shanghai, China

[†] These authors contributed equally to this work.

[*] Correspondence to: Yue Hu, Tel: +1 919 600 0000, E-mail: yue_hu@med.unc.edu; Guoqing Zhang, Tel: (+86) 021-54920465, E-mail: gqzhang@sinh.ac.cn; Zefeng Wang, Tel: (+86) 021-54920416, E-mail: wangzf@sustech.edu.cn

Abstract

RNA metabolism is tightly regulated by *cis*-elements and *trans*-acting factors. Most information guiding such regulation is encoded in RNA sequences. Considering the similarities in semantic and syntactic features between RNAs and human language, we developed LAMAR, a transformer-based foundation language model for RNA regulation, to decipher general rules underlying RNA processing. The model was pretrained on approximately 15 million sequences from both genome and transcriptome of 225 mammals and 1569 viruses, and further fine-tuned with labeled datasets for various tasks. The resulting fine-tuned models outperformed the state-of-the-art methods in predicting mRNA translation efficiency and mRNA half-life, while achieving comparable accuracy to specifically designed methods in predicting splice sites of pre-mRNAs and internal ribosome entry sites. Our results indicated that a single foundation language model is applicable in the comprehensive analysis of different aspects of RNA regulation, providing new insight into the design and optimization of RNA drugs.

Keywords: RNA regulation, language model, splicing, translation, degradation

Introduction

As an important component of the central dogma, RNAs play various roles in multiple biological processes, ranging from the templates of protein synthesis [1] to the regulators of gene expression [2]. The cellular processes of RNA are regulated by its *cis*-regulatory elements and *trans*-acting factor [3, 4], the information of which are encoded in RNA sequences spanning evolutionary diversity. In addition, the regulation of RNAs is often affected by RNA structures, which can either directly determine the RNA metabolism or affect the accessibility of RNA *cis*-elements recognized by the cognate RNA binding protein (RBPs) [5, 6]. Deciphering the regulatory rules of RNA will provide new insights into molecular mechanisms and further direct the designs of new RNA therapeutics.

With the advancement of biochemical and bioinformatic technologies, researchers have previously developed different computational tools to analyze the regulatory maps of RNAs [7-11]. While these well-designed algorithms were specifically developed for different aspects of RNA regulation, a unified framework to learn the diverse regulation of RNA is lacking. The large language models (LLM) have demonstrated that unsupervised pretraining of a vast corpuses of text can significantly advance our comprehension [12] and generative capabilities of language [13]. The pretrained model serves as a foundation platform that can be further fine-tuned to solve multiple downstream tasks. In light of the similarity of semantic and syntactic features between RNA sequences and human language, some studies explored the potential of language models to capture the essence of RNA. For example, RNA-MSA [14] and RNAErnie [15] were developed to predict the secondary structures of non-coding RNAs. RNA-FM was pretrained on non-coding RNAs and fine-tuned to solve multiple tasks including prediction of RNA tertiary structures and binding sites of RNA binding proteins [16]. However, current models were mostly pretrained on non-coding RNA sequences, and thus the extracted sequence features are mainly related to the functions of non-coding RNAs. As a result, these models may be biased to the highly structured non-coding

RNAs, therefore may not be suitable for downstream tasks that interpret different

aspects of RNA regulation. Meanwhile, the gene expression undergoes multi-layer

regulation at the RNA level, including alternative splicing, polyadenylation,

localization, modification, mRNA translation and degradation. The regulatory rules are

presumably encoded in the sequence, theoretically dictating the structure and the RBP

binding profile. However, uncovering such hidden information is technically

challenging due to the complexity, diversity and context-dependency nature of RNA

regulation. Additionally, the evolution information can provide crucial insights, helping

to distinguish conserved regulatory elements and to reveal their functional significance.

To address these challenges, we developed a foundation language model for RNA

regulation (LAMAR) by unsupervised pretraining using approximately 15 million RNA

sequences with multiple functions across mammalians. LAMAR can effectively

distinguish between functional regions or transcripts with distinct functions within the

representation space, indicating that it has successfully captured the functional

attributes solely from sequences. By leveraging LAMAR as a foundation platform, we

were able to fine-tune this model with labeled datasets across a range of tasks including

supervised modeling of splice sites, RNA stability, mRNA translation efficiency, and

internal ribosome entry sites (IRESs) for non-canonical translation. Our results showed

that the performances of the fine-tuned LAMARs were better than or comparable with

the state-of-the-art methods that were specially designed for each task, which

demonstrated the power of LLM in dissecting the diverse functions of RNAs using only

the primary sequences and provided new clues for underlying cellular mechanisms.

Results

The pretrained RNA foundation model

We developed an RNA foundation model, LAMAR, by first pretraining with large-scale unlabeled RNA sequences and subsequently fine-tuning with task-specific datasets to solve multiple downstream tasks across different layers of RNA regulation. To efficiently learn the sequence features and evolutionary information of RNA, the ~21 million sequences from all types of genes and transcripts across 225 mammals from 15 suborders (Supplementary Figure 1A) and 1569 viruses were downloaded and processed as training corpus from RefSeq and RNACentral databases (Figure 1A, also see methods). We further reduced the data redundancy by selecting representative sequences from different clusters (Supplementary Figure 1B, also see methods), resulting in a final dataset of 15 million sequences that encompass a broad range of species and length (Figure 1B).   These sequences included the mRNAs, non-coding RNAs and annotated genes from all these species, covering around 267 billion nucleotide tokens for the training of LAMAR. In the pretraining stage, we used the mask learning strategy in which a portion of the nucleotides were masked and then predicted by contextual sequences, enabling the model to learn the interactions between nucleotides (Figure 1C). Considering the sequence length of genes/transcripts and the available computational resources, we pretrained two models with the contextual length of up to 2048 and 4096 tokens, named LAMAR-2k and LAMAR-4k, resulting in two encoder models that are linked to different task-specific prediction heads (Figure 1C). With more than 50% accuracy in reconstructing masked tokens, the pretrained models successfully learned the exact contextual information after 250 thousand steps (Supplementary Figure 2). The task-specific predictor was then stacked on the encoder for each downstream tasks within the fine-tuning. To examine the performance and generality of LAMAR, we applied this RNA foundation model in different downstream tasks ranging from the RNA splicing, translation and degradation (Figure 1D).

Extraction of RNA intrinsic features with pretrained LAMAR

To investigate whether the model can learn the intrinsic biochemical properties of RNA during the pretraining stage, we first compared the hidden embeddings of the four nucleotides between the untrained and pretrained model (Figure 2A). In this test, each nucleotide was represented as a single vector by averaging the output embeddings of nucleotides in 500 randomly selected human transcripts (including both mRNAs and long non-coding RNAs). We then used the principal component analysis to project the representative vectors into two-dimensional space. We found that, while the nucleotides from the untrained model are scattered randomly, the four different nucleotides were clustered together after the pretraining. Additionally, we found that, in the first principal component (PC1), the adenine and guanine (purines) are closer to each other, while the cytosine and thymine (pyrimidines) are closely clustered. This result indicated that the model had somehow learned the biochemical properties of different nucleotides from large-scale unlabeled sequences (Figure 2A). The distances of hidden embeddings were presented in Supplementary Figure 3.

Encouraged by the ability of LAMAR in discerning different RNA bases, we further examined if the pretraining of LAMAR could, to a degree, extract some functional features of RNAs. We first test if the pretraining of LAMAR can distinguish different functional regions within mRNA (CDS *vs* UTRs) by representing different mRNA fragments as vectors using the untrained and the pretrained models, and subsequently projecting them in a two-dimensional plot using t-Distributed Stochastic Neighbor Embedding (tSNE) (Figure 2B). We found that the RNA sequences with same functions were more likely to be clustered together after pretraining (Normalized Mutual Information, NMI=0.53) compared to the random scattering of the same sequences in untrained model (NMI=0.04) (Figure 2B). The similar results were also obtained for different functional types of RNAs (NMI=0.060 in untrained model *vs* NMI=0.327 after pretraining) (Figure 2C). These results indicate that the model has successfully extracted the intrinsic functional features of RNA in self-supervised

150   pretraining with unlabeled sequences.

The fine-tuned LAMAR accurately predicts RNA splice sites

The majority of mammalian genes are transcribed as pre-mRNAs that contain
intervening introns and exons. During the process of pre-mRNA splicing, the
spliceosomes precisely recognize pairs of splice sites (SS) and subsequently remove the
introns, and the adjacent exons are joined together to produce mature mRNAs [17]. In
addition to authentic SS, pre-mRNAs contain numerous "decoy" SS that have similar
consensus motifs but are really spliced, probably because introns contain large number
of splicing silencer sequences to suppress the use of decoy SS [18]. Therefore
distinguishing the real SS among the large number of "decoy" sites become a central
question in splicing regulation [19], and the accurate prediction of SS from human
transcripts is also crucial for identifying disease-causing genetic variants [20]. Various
computational tools have been previously developed to predictively identify splice sites
within pre-mRNA sequences, among which the best performance was achieved by a
CNN-based method SpliceAI [8].
To examine if the LAMAR can be used to distinguish the authentic SS among the
decoy sites, we clustered the real SS and the decoy sites (non-splicing GT and AG sites)
by projecting their representative vectors into the two-dimensional space using tSNE.
We found that while the 5′ splice sites and other GT dinucleotides could not be
classified clearly for the untrained model (NMI=0.00), the pretrained LAMAR can
clearly separate these two types of sites with good clustering efficiency (NMI=0.49)
(Figure 3B). The same result was also observed for 3′ splice sites (NMI=0.00 in
untrained model *vs* NMI=0.45 in pretrained LAMAR), indicating that the pretrained
model has successfully learned the contexts of splice sites, which may be used in the
subsequent fine-tuning.
We further fine-tuned LAMAR to predict the 5′ and 3′ splice sites for each
transcript in human pre-mRNA sequences. We used the same datasets consistent with

SpliceAI and set the contextual length as 1024 tokens for the task-specific fine-tuning

(Figure 3A). Two fine-tuning strategies were tested for both LAMAR-2k and LAMAR-

4k: 1) fine-tuning frozen LAMAR (i.e., only the parameters in prediction head are

updated, and the LAMAR encoder is not changed during the fine-tuning stage), and 2)

fine-tuning all the parameters of LAMAR (i.e., both the prediction head and LAMAR

encoder are updated during the fine-tuning, see methods). As a control, we also fine-

tuned the untrained LAMAR with the same prediction head for comparison.   We used

precision-recall area under curve (PRAUC) and top-k accuracy as model metrics, and

found that the second strategy using global optimization outperformed the control

(untrained LAMAR) and the first strategy (frozen LAMAR), indicating the

effectiveness of pretraining and the parameter optimization of the pretrained model for

prediction (Figure 3C). It is worth noting that the frozen pretrained model with only a

simple prediction head (i.e., the first strategy) could also achieve pretty good result

(PRAUC=0.926 and top-k accuracy=0.886 for LAMAR-2k), suggesting that the

pretrained LAMAR has already captured many sequence features of the splice sites. We

defined the best prediction model, the LAMAR-4k with all parameters fine-tuned, as

LAMAR-SS and compared it with baseline methods including SpliceAI and RNA-FM.

To control the effect of contextual length on model performance, the sub-models

spliceAI-400 and spliceAI-2k were selected which predicted the splicing sites based on

flanking 200nt and 1000nt sequences.

The results show that LAMAR-SS achieved better results than the other baseline

methods in splice site predictions as judged by both PRAUC and top-k accuracy (Figure

3D). In particular, LAMAR-SS outperformed RNA-FM-SS by 0.041, spliceAI-400 by

0.037 and spliceAI-2k by 0.029 in terms of PRAUC (outperformed RNA-FM-SS by

0.055, spliceAI-400 by 0.051 and spliceAI-2k by 0.037 in terms of top-k accuracy),

showing the powerful performance of pretrained model.

Fine-tune LAMAR to decipher the translation regulation by 5′ UTR

The translation efficiency of mRNA is critical for the development of mRNA drugs,

which is tightly regulated by general and specific translation factors inside cells [21]. To

gain insight on how the RNA sequence may affect translation efficiency, we next

examined if the LAMAR model can be applied to predict the regulation of translation.

It is well accepted that the 5′ untranslated region (5′ UTR) of mRNA plays a major role

in the regulation of mRNA translation [22]. The structures and *cis*-elements located in

sequences including hairpins and Kozak sequences control the translation efficiency

(TE) of mRNA. In addition, recent experiments with massively parallel reporter assays

have suggested that the translation regulatory elements are very prevalent throughout

human 5′ UTRs [23, 24].

Using the available experimental data from high-throughput profiling of human 5′

UTR, we fine-tuned LAMAR to predict the translation efficiency of human mRNAs

based on 5′ UTR sequences (Figure 4A). The 10,903 transcripts from human embryonic

kidney (HEK) 293T cell line were selected for training [25]. To select the best fine-tuned

strategy, we compared the same fine-tuned strategies in prediction of splice sites. The

results showed that fine-tuned all the parameters of LAMAR-2k achieved the best result

(mean squared error MSE=0.409 and Spearman correlation coefficient=0.652), which

we named it as LAMAR-TE (Supplementary Figure 4). Since UTR-LM outperformed

than classical methods in prediction of translation efficiency of 5′ UTRs [26], we selected

UTR-LM and RNA-FM as benchmarks. The results of 10-fold cross validation showed

that LAMAR-TE outperformed RNA-FM and UTR-LM by 7% and 18% for the

Spearman correlation coefficient (Figure 4B), and by 9% and 14% for the MSE

respectively (Figure 4C). UTR-LM was pretrained on sequences and secondary

structures of 5′ UTRs using approximately 1 million parameters. Therefore the superior

performance of LAMAR-TE compared to UTR-LM may suggest that our model

probably learned the structural information of 5′ UTRs exclusively from sequences with

much more parameters.

Predict the effect of 3′ UTRs on RNA degradation using fine-tuned LAMAR

In general, mRNAs are degraded at the end of their live cycles by exo/endonucleases and associated factors [27]. The sequences in 3′ untranslated regions (3′ UTRs) are known to play major roles in regulating various degradation pathways by recruiting miRNAs or RBPs [28]. To study the effects of the *cis*-regulatory elements and genetic variants of 3′ UTRs on mRNA stability, the degradation rates (DR) of native and mutated 3′ UTR sequences have been measured in several massive parallel reporter assays [29, 30].

In this section, we fine-tuned our LAMAR to predict the half-lives of mRNAs containing different 3′ UTRs (Figure 5A). We used the data from a massive parallel reporter assay that measures the effect of 1,967 human 3′ UTRs on the half-lives of eGFP mRNAs containing different 3′ UTRs [30]. The model performance was tested by predicting the effect of 3′ UTRs on mRNA half-lives with ten-fold cross-validation. We compared the performances of various fine-tuning strategies, and found that the full-parameter fine-tuned LAMAR-4k, named LAMAR-DR, have achieved the best performance in predicting half-lives of the reporter mRNAs (MSE=0.176 and Spearman correlation coefficient=0.647) (Supplementary Figure 5A, B). The fine-tuned frozen LAMAR-4k achieved the modest result (MSE=0.223 and Spearman correlation coefficient=0.477), showing that LAMAR-4k extracted the sequence features of 3′ UTRs from unlabeled pretraining. As a comparison with baseline method, we fine-tuned the RNA-FM using the same dataset and strategy, which we named as RNA-FM-DR. We found that, while both foundation models showed ability in predicting mRNA half-lives, LAMAR-DR outperformed RNA-FM-DR by 8.0% for correlation coefficient (Figure 5B) and by 7.4% for MSE (Figure 5C), suggesting that LAMAR has a superior performance in model generalization.

We next evaluated LAMAR-DR by examining whether the model predicts how the 3′ UTR mutations may affect mRNA stability (Figure 5D). We used the 3′ UTR segment of CXCL2 mRNA that had been systematically mutated in a near saturated fashion [30].

For each mutation, we predicted the half-lives of the mutant mRNA and the natural

sequence using LAMAR-DR, and defined their difference as the variant effect. We

compared the predicted variant effect with the experimental results measuring the effect

of each CXCL2 mutation on the mRNA level [30], and found that the LAMAR-DR

prediction was largely correlated with the experimental measurement of mRNA levels

(Figure 5E). In addition, LAMAR-DR successfully identified a strong degradation

element, AU-rich element, in the upstream of 3′ UTR (Figure 5E). For all the mutations

on CXCL2 3′ UTR, the Pearson correlation coefficient between predicted variant effect

and experimental results was 0.58 (Supplementary Figure 5C). Considering the

difference in experimental measurement between mRNA half-lives and steady state

levels [30], the correlation between LAMAR-DR prediction and experimental

measurement is reasonably strong.

To examine the sequence features used by LAMAR-DR in predicting RNA

degradation, we applied perturbation analysis on each nucleotide to measure how they

affect the prediction of RNA stability (Figure 5D). We define the perturbation score of

a sequence as the differences of the LAMAR-DR score between the wildtype sequences

and the average scores of their mutations (see methods), and such *in silico* mutation

analysis can generate the regulatory elements in 3′ UTR that either promote or inhibit

degradation of mRNAs. Previously, a massively parallel functional assay was

conducted using the >450 kilobases of 3′ UTR sequences from >2000 human genes to

measure their effect on mRNA stability, identifying 150 short elements that positively

or negatively regulate mRNA stability [30].   We used the LAMAR-DR to computed the

average perturbation scores of these 150 regulatory elements [30], and found that the

positive regulators of mRNA stability indeed showed a significantly higher score than

the negative regulators (Figure 5F). In addition, the LAMAR-DR predicted regulatory

effects are positively correlated with observed values (Spearman correlation

coefficient=0.58, *P*=5.5 $\times$ 10^{-15}, Supplementary Figure 5D), demonstrating the

effectiveness and potential of our method in discovering new regulatory elements.

To predict new *cis*-elements that may regulate mRNA degradation, we computed

the LAMAR-DR perturbation scores of all hexamers in human 3′ UTRs, and analyzed

the hexamers with the highest and lowest scores (top or bottom 1%) as the stabilizing

and destabilizing elements that can be clustered into several groups to obtain the

consensus motifs (Figure 5G).   As the examples, two 3′ UTR containing the

stabilizing or destabilizing sites were included together with their perturbation scores

(Figure 5I).   Interestingly, we found that the destabilizing motifs contain several

known motifs to promote mRNA degradation, such as the AU-rich elements

(UAUUUAU), PUF binding elements (TGTAHATA) and m6A sites (DRACH) (Figure

5G), confirming the reliability of our prediction. However, most of the stabilizing

motifs, include GA-rich, U-rich and A-rich elements, seem to be novel (Figure 5H),

although the AAAAU motif resembles the known binding site of IGF2BP3 that is

involved in regulating mRNA stability [4, 31].

The fine-tuned LAMAR for IRES prediction

The internal ribosome entry sites (IRESs) can drive cap-independent translation of

eukaryotic mRNAs, which is essential for the viral mRNAs lacking 5′ caps or the

translation of certain mRNAs under stressful conditions [32]. Canonical IRESs were

mostly identified from the viral genomes, and some IRESs were reported in the

endogenous human genes [32]. Previously several algorithms, such as IRESPred [33],

IRESfinder [34] and IRESpy [35], have been built to computationally predict IRESs.

However, their performances are not satisfactory and unable to produce coherent and

reliable results for IRES prediction, probably due to data noise or insufficient training

data. Recently, a large number of IRESs were identified from high-throughput

screening of human and viral sequences [36-38], most of which have not been annotated

and analyzed thoroughly to generate a predictive model. On the other hand,

identification of IRESs is important for learning the mechanisms of cap-independent

translation and improving circRNA-based biomedical engineering.

With an RNA foundation model, we next seek to fine-tune LAMAR to predict new

sequences with IRES activity (Figure 6A). We collected 1,901 experimentally validated

IRESs from the three databases (IRESite [39], IRESbase [40] and RFAM [41]) as the positive

training sequences (Figure 6B), and used the structural RNAs randomly sampled from

RFAM database as the negative control sequences (see methods). We achieved the best

result by fine-tuning all the parameters of LAMAR-2k (named as LAMAR-IRES),

which was slightly better than LAMAR-4k (Supplementary Figure 6). Since the

previous IRES prediction methods were trained on short sequences that are inherently

noisy, we did not use them as benchmark, and instead fine-tuned RNA-FM as the

benchmark. We found that both of fine-tuned models from RNA-FM and LAMAR

achieved the good AUC around 0.98 (Figure 6C), suggesting that the RNA foundational

model have a strong power in extracting the features of known IRES datasets to make

a great prediction.

To examine the performance of LAMAR-IRES in predicting the novel IRESs

obtained from independent experimental screen, we used LAMAR-IRES to classify the

recently identified IRESs from the high throughput screens of a library derived from

viral and cellular mRNAs [36-38]. We found that the predicted probabilities of putative

IRESs are significantly higher than those of remaining sequences, revealing the *in silico*

screening ability of LAMAR-IRES (Figure 6D).

The circular RNAs (circRNAs) have been found to be able to translated into

functional protein in human cells [42, 43], and thus can served as a new generation of

mRNA therapy due to its high stability and low immunogenicity [44-46]. Since circRNAs

lack free 5′ or 3′ ends, they can only be translated through a cap-independent fashion

driven by IRESs or IRES-like elements [43, 47]. Therefore, the identification of highly

efficient IRESs is critical for the development of circRNA-based therapy, as the IRES-

mediated translation is generally less efficient compared to the canonical cap-dependent

translation. To address this issue, we next applied the LAMAR-IRES to screen 5′ UTRs

of viral genomes in order to predict new IRES sequences that are highly active in

promoting circRNA translation (Figure 6E). Specifically, we applied a series of filters

to selected 305 annotated 5′ UTRs or upstream regions from the genomes of positive-

sense single-stranded RNA viruses, and used LAMAR-IRES to score the probability of

the candidate sequences (see methods). We classified the candidates into three groups

based on the predicted probabilities: non-IRESs (probability<0.5), low-activity IRESs

($0.5 \leqslant$ probability<0.9) and high-activity IRESs ($0.9 \leqslant$ probability). To validate our

prediction, each group of sequences were subsequently inserted into the *in vitro*

synthesized circRNAs, and their protein expression in 13 frequently-used cell lines

were measured by quantitative luciferase assays (see methods, Supplementary Table 2).

The activity of IRES was assessed by calculating the relative expression levels of

circRNA and modified mRNA, both containing the identical reporter gene. We

compared the activities between three IRES groups and found that the high-activity

IRESs exhibited significantly higher activities than low-activity IRESs, which in turn

were significantly higher than those of non-IRES in each cell line (Figure 6F),

suggesting that our model integrated the causal relationship between RNA sequence

and IRES activity. In addition, we observed mostly consistent results for these

sequences in 13 cultured cell lines, suggesting that the prediction of LAMAR-IRES can

be validated in different cell contexts. Furthermore, we examined 14 highly active

IRESs (probability>0.9) predicted by LAMAR-IRES, and found that the protein

expression level driven by these IRESs surpassed the modified mRNA in specific cell

lines. For instance, the circRNA containing the IRES from parabovirus A4

(probability=0.91) exhibited 2.44-fold higher protein expression than the mRNA with

same ORF sequences in C2C12 cells.   However, four IRESs with high activities were

predicted with low probability (probability<0.5), suggesting that the sensitivity of

LAMAR-IRES prediction should be further improved with better training data quality.

Discussion

To study the multi-layer regulation of RNA, we build a foundation language model, LAMAR, which can extract semantic features of RNAs by unsupervised pretraining on unlabeled transcripts with diverse functions across mammals and viruses. The representation space learned from LAMAR reflected the biological functions of RNA in multiple levels including nucleotide, regulatory region and entire sequence. We further fine-tuned the pretrained LAMAR with labeled datasets for several downstream tasks, including prediction of splice sites, mRNA translation efficiency, mRNA degradation rate and IRES activity, and demonstrated that the foundation model showed high versatility and accuracy on handing these tasks. In particular, LAMAR achieved better or comparable performance than the baseline methods in nearly all tasks evaluated, reflecting the remarkable generality of LAMAR in modeling RNA regulation. The future application of LAMAR may be expanded to study other processes of RNA regulation including alternative polyadenylation, transportation/localization, editing and modification. More importantly, LAMAR can be applied to predict mutational effects of *cis*-regulatory elements and to identify novel regulatory elements, demonstrating the potential of this model in revealing new biological mechanisms and biomedical engineering.

LAMAR was pretrained on a diverse dataset comprising genomic and transcriptomic sequences from a wide range of species, ensuring its adaptability for downstream tasks. Since the RNA regulation includes multiple layers, the generality of LAMAR makes it easier to achieve robust performance across diverse regulatory mechanisms. For instance, gene sequences play a critical role in understanding RNA splicing regulation, as the selection of splice sites is influenced by regulatory elements within both introns and exons [17]. The pretraining with both genomic and transcriptomic sequences could give additional attention to the regions of mature transcripts that play more important biological roles. During the pretraining process, we clustered the genome and transcriptome sequences to reduce redundancy. However,

certain groups of RNAs may lack sufficient representation after clustering. Therefore,

fine-tuning the model is necessary to improve predictions for these underrepresented

groups.

LAMAR shared a similar architecture with some of the benchmark models like

RNA-FM and RNA-Ernie, however was pretrained on different corpus using datasets

containing a huge number of pre-mRNAs, mature mRNAs, and non-coding RNAs.

The diverse types of training data in LAMAR may be responsible for its superior

performance in downstream tasks related to co-/post-transcriptional regulation

compared to the other methods that were mainly pretrained on the non-coding RNAs

with high content of secondary structure. It is generally accepted that RNA structures

play critical roles in the gene expression. However, compared to the number of available

sequences, only a small number of accurate RNA structures are currently available,

which are insufficient to pretrain a large model. In addition, RNA structures are very

dynamic and affected by their binding factors as well as the cellular conditions [48], and

thus direct pretraining with RNA sequences and their structures would mislead the

learning of complex features. Even in the cases where the secondary structures of RNAs

can be predicted, the accuracy of structure prediction is not equally reliable for different

types of RNAs [49], introducing uncontrolled bias during the pretraining with a large set

of diverse RNAs. For all these reasons, we decide to not specially consider the RNA

structure during the pretraining stage, and instead acknowledge that the structural

information has already been embedded in the sequences and thus may be

sensed/learned by a powerful model. It may worth trying to combine the sequence

embeddings and structural information for the task-specific fine-tuning in the future

applications.

Since LAMAR uses the architecture of transformer encoders containing many self-

attention layers, the number of parameters is proportional to the square of the input

length. Due to the limitation of graphic memory, some ultra-long RNA sequences have

to be split into the overlapping short segments (with the length of 2k or 4k) during

pretraining and fine-tuning, which may lead to the loss of distant coevolutionary

information in RNA. Although the regulations of RNAs is mostly determined by the

interactions within local context, there are some functional attributes of RNAs, such as

translation efficiency and degradation rate, are dependent on entire sequences including

coding and untranslated regions [50]. Therefore, training with partial sequence elements

may reduce the model performance because the long-range interactions are likely be

diminished during the pretraining. Recently several frameworks have been designed for

ultra-long sequences [51], which will be explored in the updated version of LAMAR.

Although LAMAR has ~85 million parameters, the pretraining loss curve shows

that it may underfit the pretraining dataset (Supplementary Figure 2). The evolvement

of large language models in deciphering human languages [52] and protein structure [53, 54]

suggests that the model performance is roughly proportional to the model size, implying

the future potential of LAMAR with an expanding model scale and data diversity.   The

future expansion of such model probably requires the exploration of more efficient

architectures and/or new computational algorithm and hardware.

Developing a foundation model to understand RNA regulation and design

functional RNA components is an important application of artificial intelligence in the

field of RNA biology and therapeutics. We believe this study provide the opportunity

of a general-purpose model which can integrate fundamental properties of RNA and

design novel regulatory elements with desired functions. The future versions will be

optimized toward more efficient architectures, robust reasoning and enhanced

generation, and we will also include different combinations of training dataset for

additional pretraining.

Methods

1. Model architecture

In this work, we developed a foundation language model, LAMAR, to study diverse regulation of RNAs. LAMAR takes the RNA sequence as input and represents the nucleotides and RNAs. In LAMAR, the RNA sequence x of n nucleotides (nt) is tokenized as tokens $[x_1, x_2, ..., x_n]$, where $x_i \in V = \{\text{'A'}, \text{'T'}, \text{'C'}, \text{'G'}, \text{'N'}\}$. The special tokens $\langle cls \rangle$ and $\langle eos \rangle$ are added to the beginning and end of the tokens, which denotes the start and end of the sequence. Each token x_i is further embedded as $e_i \in \mathbb{R}^{h_D}$, and the sequence x is represented as the embedding matrix $e = [e_{cls}, e_1, e_2, ..., e_n, e_{eos}] \in \mathbb{R}^{(n+2) \times h_D}$, where hidden size h_D is set to be 768. Subsequently, the embedding e is further input into a multi-layer bidirectional Transformer encoder similar with ESM-2 [54] to get the final hidden embedding matrix $h = [h_{cls}, h_1, h_2, ..., h_n, h_{eos}] \in \mathbb{R}^{(n+2) \times h_D}$. At last, the final hidden embedding h representing the entire sequence is fed into the task-specific prediction head for different downstream tasks.

Specifically, the multi-layer bidirectional Transformer encoder contains 12 layers, each of which comprises a self-attention layer with 12 heads and a feed forward layer with intermediate size of 3072. To enhance the model performance on long sequences, the rotary position embedding is applied to integrate positional information into the learning process of the model [55].

2. Pretraining dataset

The pretrained datasets of LAMAR derived from four sources: 1) Protein coding and non-coding transcripts of mammals from RefSeq [56]; 2) Non-coding transcripts of mammals from RNACentral [57]; 3) Reference genome of mammals from NCBI Genome; 4) Reference genome of viruses that infect mammals from NCBI Genome.

RefSeq (Release 221) contained 13,319,105 transcripts of 223 mammalian species

in 15 suborders. The sequences were downloaded as fna.gz format from website

https://ftp.ncbi.nlm.nih.gov/refseq/release/vertebrate_mammalian/. RNACentral

(Release 23) contained 2,649,775 non-coding transcripts from 214 mammalian species.

The sequences could be downloaded from https://ftp.ebi.ac.uk/pub/databases/

RNAcentral/releases/23.0/sequences/. As of Dec 14 2023, NCBI Genome contained

222 mammalian reference genomes annotated by RefSeq. The sequences and

annotations were respectively downloaded as fna.gz and gff.gz from the links on the

metadata file (https://ftp.ncbi.nlm.nih.gov/genomes/refseq/vertebrate_mammalian/a

ssembly_summary.txt). The 6,033,179 reference genes were extracted from the

reference genomes by "bedtools" [58] with the genome annotations. As of Jan 4 2024,

NCBI Virus contained 15,037 viral reference genomes, 1579 of which infected

mammals were included into pretrain datasets (https://ftp.ncbi.nlm.nih.gov/gen

omes/refseq/viral/assembly_summary.txt). The 19,007 reference genes were extracted

by "bedtools" [58] with the genome annotations. The above data were combined into the

initial corpus, comprising 15,455,049 transcripts and 5,832,792 genes in total.

For the initial corpus, the sequences of the length fewer than 15 nt were filtered.

The IUPAC ambiguity codes in sequences were replaced by N. To reduce the data

redundancy, we used MMseq2 [59] to respectively cluster transcripts and genes based on

the sequence identity. Specifically, Clustering was performed with a minimum

threshold of 80% sequence identity and 80% coverage, and the longest sequences are

used as the representative sequence in each cluster (cluster mode=2, identity=0.8,

coverage=0.8). As a result, we obtained 6,673,915 transcript and 4,557,965 gene

clusters. During pretraining, 99% of transcript and gene clusters were randomly

selected to pretrain the model, while the remaining clusters were reserved for evaluation.

The representative sequences and 50% of the member sequences from each training

cluster were included into pretraining corpus, with an upper limit of 200 members per

cluster. In addition, the validation corpus was composed of the representative sequences

of testing cluster. In all, the training corpus encompassed a total of 15,000,406

sequences, which accounted for approximately 267 billion tokens. The testing corpus

comprised 112,797 sequences, providing representative samples for validation.

3. Pretraining LAMAR

In the pretraining stage, we trained the model with masked language modeling [12, 54].

We first randomly masked 15% of tokens in each sequence. For each masked token, we

replaced it with the $\langle mask \rangle$ token 80% of the time, the random token 10% of the time

and the unchanged token 10% of the time. After masking, we input the masked

sequence into the model and used the final hidden embedding $\boldsymbol{h}$ to predict the labels

of the masked tokens. The categorical cross-entropy loss between predicted

probabilities and the actual labels of the masked tokens was used to pretrain the model

[12]. The loss function was defined as:

$$Loss(x) = -\sum_{i \in M} \sum_{j \in V} y_{i,j} \cdot \log p(x_{i,j} | x_{\sim M}, \Theta) \tag{1}$$

where M and $\sim M$ represent the positions of masked nucleotides and unmasked

nucleotides, respectively. Θ represents the trainable parameters of the model and

$p(x_{i,j} | x_{\sim M}, \Theta)$ represents the probability of predicting the i_{th} masked token as class

j based on all the unmasked tokens. $y_{i,j}$ represents whether i_{th} masked token

belongs to class j, if so, $y_{i,j}$=1, otherwise, $y_{i,j}$=0.

We pretrained two models with contextual lengths of 2048 and 4096 tokens

respectively, to accommodate different cases, named as LAMAR-2k and LAMAR-4k.

When the length of the pretraining sequences exceeded these limits, they were

segmented into fragments shorter than the specified contextual length. The overlap of

256 and 512 tokens between adjacent fragments were ensured to maintain contextual

information. For the evaluation phase, we randomly extracted fragments with

contextual length from testing sequences that exceeded the pretraining length. Any

testing sequences with more than 10% Ns were excluded. To speed up evaluating the

model, 10,000 sequences were randomly sampled from the testing corpus to compute

the accuracy of predicting the labels of masked tokens.

To pretrain the models stably, we set the batch sizes as 512 and 256 sequences

(around 1M tokens) respectively for LAMAR-2k and LAMAR-4k. For optimization of

model pretraining, we utilized the AdamW optimizer [60] ($\beta_1 = 0.9$, $\beta_2 = 0.98$, $\varepsilon =$

10^{-8}) and L_2 weight decay of 0.01. In the pretraining stage, the learning rate was

warmed up during the first 10,000 steps to the peak value 1e-4 and then decayed in

remaining steps. To speed up pretraining without sacrificing accuracy, the models were

pretrained with FP16 mixed precision with Apex and FlashAttention library [61]. Our

models underwent 250,000 training steps to reach convergence, taking around 260

hours on 8 A800 80GB graphic process units.

4.   RNA representation by LAMAR

We took the final hidden embedding of LAMAR to represent the nucleotide, splice

site, functional region (UTR and CDS) and RNA for visualization of feature space.

For the representative embeddings of four nucleotides, we averaged the final

embeddings of the same class of nucleotides in RNA sequences X as formula:

$$h_{nucleotide}(nuc) = \frac{1}{|N_{nuc}|} \sum_{x \in X} \sum_{i \in M_{nuc}} h_i \in \mathbb{R}^{h_d}$$

$$M_{nuc} = \{ i \mid x_i = nuc \}, nuc = A, T, C, G \tag{2}$$

, where M_{nuc} represents all the positions of the nucleotide nuc in sequence x and

N_{nuc} represents the number of the positions of the nucleotide nuc in total sequences

X. To compare the nucleotide embeddings of pretrained and untrained models, we

sampled 500 human mRNAs and non-coding RNAs for 10 times to compute the

representative embeddings of nucleotides. We only sampled one RNA from each gene

and included sequences with lengths shorter than 4096 nt.

The splice site, functional region and RNA can be seen as sequence of different

length. For each sequence, the final representative embedding is obtained by averaging

the embeddings of all nucleotides in the sequence, as described by the formula (3).

$$h_{sequence}(x) = \frac{1}{n} \sum_{i=1}^{n} h_i \in \mathbb{R}^{h_d} \tag{3}$$

For the representative embeddings of splice sites and non-splice sites, we averaged

the final embeddings of two bases of the specific sites in pre-mRNA sequences. We first

recorded the positions of splice sites with RefSeq annotation file and used "bedtools"

[58] to extract the pre-mRNA sequences from human genome. For each pre-mRNA, the

non-splicing GT and AG sites with the same number of splice sites were sampled as

non-splice sites. The 1,000 pre-mRNAs with lengths shorter than 14,500 nt were

sampled and the 9,464 pairs of splice sites and non-splice sites were selected,

respectively.

We averaged the final hidden embeddings of the total positions of different

functional regions (UTR and CDS) in human mRNAs as their representative

embeddings. The mRNAs annotated by GENCODE V43 containing 5′ UTR, CDS and

3′ UTR were first selected. We only sampled one mRNA from each gene to avoid the

bias from high identities between mRNA alternative isoforms, and included 14,984

sequences with lengths shorter than 4096 nt. The hidden embeddings of functional

regions were computed by untrained or pretrained LAMAR for comparison.

For the representative embeddings of transcripts with different RNA types, we

averaged the final embeddings of all the positions in transcripts. All the transcripts

annotated by GENCODE V43 were first selected. We only sampled one transcript from

each gene and included transcripts with lengths shorter than 4096 nt. We selected the

functional types with the number more than 100, including mRNA, lncRNA, snRNA,

miRNA, snoRNA and tRNA. The representative vectors of transcripts were computed

by untrained or pretrained LAMAR for comparison.

5. Fine-tuning LAMAR

For different downstream tasks, the fine-tuning can be categorized into token-level

and sequence-level. For token-level tasks including prediction of splice site of pre-

mRNA, the entire embedding h from the encoder is fed into the prediction head which

contains one linear layer. As for sequence-level tasks including prediction of translation

efficiency, half-life and IRES, only the representation of the $\langle cls \rangle$ token h_{cls} is input

into the prediction head which contains two linear layers. Compared to the pretraining

stage, fine-tuning is inexpensive, which takes several hours to finish training.

During fine-tuning, we explored two strategies. The first one is to fine-tune the

frozen pretrained LAMAR, that is, the weights of the encoder are untrainable and only

the task-specific head is fine-tuned. In this condition, the fine-tuning is speeded up and

the memory usage is reduced. The second one is to fine-tune all the parameters end-to-

end, which fits LAMAR to specific datasets, improving the model performance

compared to the first strategy in all the tasks.

To evaluate the performance of the fine-tuned models for prediction of splice site

and IRES, we used the specific strategy (see section 6.1 and 6.4). As for prediction of

translation efficiency and degradation rate, we used cross-validation to evaluate the

performance of the fine-tuned models. Specifically, 10% of the dataset was served as

independent validation set and the remaining data was used for 10-fold cross-validation.

All the hyperparameters of the fine-tuned models were the same as the pretrained model,

except batch size, learning rate, warmup ratio and training steps. The warmup ratio was

set to be 0.05. Since the model performance was influenced by different

hyperparameters, the optimal hyperparameters (batch size, learning rate and training

steps) are decided by grid searching (Supplementary table 1). To speed up the query of

hyperparameters, we first fine-tuned the model with one random subset and ranked the

combinations of hyperparameters by the performance. Further, we evaluated the

performance of the top10 combinations of hyperparameters by 10-fold cross-validation.

At last, we used the median performance of the 10 sub-models on the independent

validation set as the final evaluation (Supplementary table 1). The model was fine-tuned

with FP32 precision for better performance on the Sugon Z-100 16GB and Tesla V100

32GB clusters of graphic process units.

6. Downstream tasks

6.1. Prediction of splice sites

We fine-tuned LAMAR with pre-mRNA sequences to predict the splice site. In the pre-mRNA sequence, each nucleotide is classified as the first site of 5′ splice site (1), the second site of 3′ splice site (2) or neither (0). Therefore, predicting the splice sites of human pre-mRNAs is a token-level three-class classification task. We used the same dataset as SpliceAI [8] to predict the splice sites of human pre-mRNAs, which consisted of 15,036 pre-mRNAs annotated by GENCODE V24lift37. The pre-mRNAs from chromosome 2, 4, 6, 8, 10-22, X, Y were used to fine-tune the model (13,384 transcripts, 130,796 pairs of splice sites), and the pre-mRNAs from chromosome 1, 3, 5, 7, 9 which did not have any paralogs were used for validation (1,652 transcripts, 14,289 pairs of splice sites). We used "bedtools" [58] to extract the pre-mRNA sequences between transcription start and end sites from the hg19/GRCh37 assembly.

We adopted the similar training strategy as SpliceAI [8] to fine-tune the model. The labels are predicted for a 768nt window each time, based on the sequence within the window and its flanking regions (128 nt on each side). In other words, the sequence of 1,024 nt was input into the model to classify the nucleotides in middle region (768 nt). Specifically, we first padded each pre-mRNA sequence with 'N' until the length became a multiple of 768, and further respectively padded 128 'N's at the beginning and end of the sequence. The padded sequences were then split into blocks of 1024 nt, where the i_{th} block ranged from $768(i-1)-128+1$ to $768i+128$, and the labels of nucleotides from $768(i-1)+1$ to $768i$ were predicted during fine-tuning.

The cross-entropy loss function of predicting splice sites is denoted as formula (4):

$$Loss(x) = -\sum_{i=1}^{768}\sum_{j=1}^{3} y_{i,j} \cdot \log p(x_{i,j}, \Theta) \tag{4}$$

where $p(x_{i,j}, \Theta)$ represents the probability of predicting i_{th} nucleotide as class j, and $y_{i,j}$ represents whether i_{th} nucleotide belongs to class j. We selected the optimum combination of hyperparameters by grid searching (Supplementary table 1).

As the training dataset is not balanced because most of the nucleotides are not splice

sites, we use top-k accuracy and area under the precision-recall curve (PRAUC) as

evaluation metrics [8]. The top-k accuracy for the specified class is defined as follows:

Suppose k positions belong to the class j in the testing set, the threshold of

classification will be selected so that exactly k samples are predicted as class j. The

top-k accuracy is computed as the proportion of k samples which are correctly

classified. The top-k accuracy and PRAUC for predicting 5′ and 3′ splice sites are

averaged for final evaluation.

6.2. Prediction of translation efficiency

The 5′ UTR sequences of mRNAs are input into LAMAR to predict the translation

efficiencies of mRNAs. Prediction of the translation efficiency is a sequence-level

regression task, only the embedding of $\langle cls \rangle$ token is fed into the task-specific head to

fit the translation efficiency. We collected the translation efficiency of each mRNA from

the Cao et al. dataset [25]. The dataset contained human transcripts of which the

expression and ribosome profiling were measured by RNA-seq and Ribo-seq in

HEK293 cell line. We included the protein coding transcripts satisfying the following

criterion: $RPKM_{RNA-seq} \geq 10$ and $RPKM_{Ribo-seq} \geq 10$. Consistent with the

methods of the original article [25], we extracted the 5′ UTR sequences annotated by

GENCODE V17 from hg19/GRCh37 assembly, and computed the translation

efficiency of mRNAs by $\frac{RPKM_{RNA-seq}}{RPKM_{Ribo-seq}}$. In all, we included 10,903 5′ UTRs ranging from

5 nt to 1,024 nt in length. For 5′ UTRs exceeding 1,024 nt, the segment of 1,024 nt at

the 5′ end of the start codon were extracted. We set the padding side as left in this fine-

tuning task for better performance.

We select the mean squared error (MSE) loss to fine-tune the model to fit the

translation efficiency, the function of which is denoted as formula (5):

$$Loss(x) = [p(x, \Theta) - y]^2 \tag{5}$$

661 where $p(x, \Theta)$ represents the predicted translation efficiency of mRNA x, and y

662 represents the observed value. The MSE and Spearman correlation coefficient between

663 predicted translation efficiencies and observed ones are selected as metrics to evaluate

664 the model.

6.3. Prediction of degradation rates

We fine-tuned LAMAR with the 3′ UTR sequences to predict the half-lives of

mRNAs. Prediction of the half-lives is also a sequence-level regression task, only the

embedding of $\langle cls \rangle$ is fed into the task-specific head to fit the half-lives detected from

the experiment. We obtained the half-lives from the Zhao et al. dataset [30]. The dataset

measured the half-lives of 2,790 mRNAs with different 3′ UTRs by the massive parallel

reporter assays in BEAS-2B cell line and reported the half-lives of 1,967 3′ UTR. We

used these 3′ UTR sequence and their half-lives to fine-tune the LAMAR. We selected

the MSE loss (see formula 5) to fine-tune the model, and compute MSE and Spearman

correlation coefficient for model evaluation.

To test whether the fine-tuned model accurately predicts the effects of 3′ UTR

variants on mRNA degradation, we selected the segment (67 nt) containing an AU-rich

element in 3′ UTR of CXCL2 which was saturated mutated as the positive control [30].

The observed variant effect of each site was assessed by computing the difference

between the steady-state mRNA levels of the wild-type and mutated sequences, and the

predicted variant effect was measured by comparing the predicted half-lives of the wild-

type and mutated sequences as the formula (6):

$$Predicted\ variant\ effect = 10 \cdot \left[f(x_{wild-type}) - f(x_{mutated}) \right]$$

where $x_{wild-type}$ means the native sequence, $x_{mutated}$ means the mutated

sequences and $f(x)$ means LAMAR-DR.

6.4. Prediction of IRES

We fine-tuned LAMAR with different RNA classes to predict the IRES. Predicting

the IRES is a sequence-level binary classification task, only the embedding of $\langle cls \rangle$

token is fed into the task-specific head to predict whether the RNA is IRES or not. We

first collected the RNA sequences from IRESite [39], IRESbase [40] and RFAM [41] databases

to build the training set. In total, the 1,901 experimentally validated IRES sequences

and 2,026,606 non-IRES sequences were collected. To avoid the data leakage caused

by sequence similarity, we used MMseqs2 [59] to cluster positive sequence and negative

sequence respectively (identity=0.9, coverage=0.9), and obtained 903 positive clusters

and 810,096 negative clusters. We sampled the representative sequences from the

negative clusters so that the number of positive and negative sequences is the same and

the distribution of sequence length is similar. We randomly selected 50% of the positive

and negative clusters as the training set and the rest as the evaluation set. We repeated

the experiment 10 times to measure the performance of the model.

We used the binary cross-entropy loss to fine-tune the model to classify the IRES.

The loss function was denoted as:

$$Loss(x) = y \cdot \log p(x, \Theta) + (1 - y) \cdot \log(1 - p(x, \Theta)) \tag{7}$$

where $p(x, \Theta)$ represents the probability of predicting the RNA x as IRES, and y

represents whether the RNA is IRES. We selected the optimum combination of

hyperparameters by grid searching (Supplementary table 1). The area under the receiver

operating characteristic (AUROC) was selected as evaluation metrics.

To validate the generalization of the fine-tuned model, we compared the predicted

probabilities of IRESs and non-IRESs screened by three high-throughput experiments.

For Weingarten et al. [37] dataset, the oligos derived from viral and human transcripts

were inserted into bicistronic reporters and screened by fluorescence activated cell

sorting (FACS). We filtered the oligos with promoter activity more than 0.2 and splicing

activity less than -2.5, and labeled the sequences with IRES activities exceeding 600 as

IRESs. Since a small part of oligos derived from IRESite database of which the

sequences were used for training, we excluded them from the dataset to avoid data

leakage. At last, 1,915 IRES and 17,047 non IRESs were included. The oligo library of

Chen et al. [36] was the same with that of Weingarten et al., but was screened by circRNA

reporter assays. Consistent with the original journal, we labeled the oligos with IRES

activities exceeding 3.466 as IRESs. The oligos derived from IRESite database were

filtered. At last, 9,185 IRESs and 11,353 non IRESs were included. For Yang et al. [38]

dataset, the oligos were derived from whole human transcripts, inserted into circRNA

reporters and screened by FACS. We labeled the oligos from post-sorting library as

IRES and the difference set between the pre-sorting and post-sorting libraries as non-

IRES. The oligos with lengths shorter than 50 nt or derived from IRESite database were

filtered. To reduce the redundancy of sequenced oligos, we used MMseqs2

(identity=1.0, coverage=0.5, coverage mode=1, cluster mode=2) to cluster the oligos

and selected the representative sequences. At last, 20,367 IRESs and 134,694 non

IRESs were included.

7. Comparing the performance of LAMAR with baseline methods

We compared the performance of LAMAR with baseline methods including RNA-

FM [16], spliceAI [8] and UTR-LM [26] across downstream tasks. The RNA-FM and UTR-

LM were language models with architectures similar to LAMAR, pretrained on non-

coding RNAs and 5′ UTRs, respectively. For fine-tuning, we used the same prediction

heads as LAMAR and initialized RNA-FM and UTR-LM with their pretrained weights.

All model parameters were fine-tuned, with identical input/output data formats, training

strategies and evaluation metrics as LAMAR. RNA-FM was fine-tuned for all

downstream tasks, while UTR-LM was fine-tuned specifically for prediction of

translation efficiency on 5′ UTRs.

SpliceAI was a convolutional neural network designed to predict splicing from pre-

mRNA sequences. It includes four architectures (SpliceAI-80, SpliceAI-400, SpliceAI-

2k and SpliceAI-10k) which predicts splice sites within a sliding window of 5,000 nt

using flanking sequences of different length (40nt, 200nt, 2,000 nt and 5,000 nt) on

each side, respectively. To align with training length of LAMAR, we selected SpliceAI-

400 and SpliceAI-2k as baseline methods for prediction of splice site. We directly

applied their trained weights to predict splice sites from full-length pre-mRNAs, using

the same evaluation metrics as LAMAR.

8. Identification of *cis*-elements regulating mRNA degradation

We used *in silico* mutation to identify *cis*-elements regulating RNA degradation. We

mutated each nucleotide of 3′ UTR segments and predicted the difference of half-lives

between native and mutated sequences, which we named the perturbation score for each

site. The perturbation score of the i^{th} nucleotide was defined by the formula:

$$perturbation\ score_i = 10 \cdot [f(x_{wild-type}) - \frac{1}{3}\sum\nolimits_{j=1}^{3} f(x_{i,j})] \qquad (8)$$

where, $x_{wild-type}$ means the native sequence, $x_{i,j}$ means the sequence whose i^{th}

site is mutated to j^{th} class of nucleotide and $f(x)$ means LAMAR-DR. To increase

the stability of prediction, we used ten sub-models to predict half-lives of native and

mutated sequences and averaged the perturbation scores as the final result.

The perturbation scores could represent the regulatory effect of the elements. The

negative perturbation score implied that the mutation breaks the destabilizing element

and extend the half-life of mRNA. The positive perturbation scores implied that the

mutation breaks the stabilizing element and shorten the half-life of mRNA.

To validate the rationality of perturbation score, we selected 150 reported regulatory

elements as positive controls [30]. These elements were screened based on Tet-Off system,

and their regulatory effects were measured by the difference in the fraction of mRNA

remaining after 4 h of doxycycline treatment between mutant and wild-type clones. We

averaged the perturbance score of each site in the element to predict its regulatory effect

for further studies.

As for identification of *cis*-elements with strong regulatory effects from the training

set, we averaged the perturbation scores of six consecutive nucleotides to represent the

regulatory effects of the hexamers. The hexamers with highest and lowest 1%

perturbation scores and frequency more than 10 were selected. The hexamers were

further multiple aligned by Cluster Omega [62] and clustered by pairwise distance to a

UPGMA phylogenetic tree. We plotted the motifs for each cluster by R package

ggseqlogo [63].

9. *In silico* screening of IRES

We used the fine-tuned model LAMAR-IRES to predict the putative IRESs and

validated their activities by experiments. We first downloaded the genome sequences

and GenBank annotations of positive-sense single-stranded RNA viruses (SARS-CoV-

2 excluded) from NCBI virus database. The annotated 5′ UTRs were thought as putative

IRESs and extracted from the genomes. If there was no annotated 5′ UTR, the segment

before the first CDS would be included. Further, we excluded the 5′ UTRs containing

too many 'N's and removed the duplicates. We used prokka [64] to predict the putative

coding regions in 5′ UTRs and deleted these sequences from the candidates. The

remaining 5′ UTRs with the length ranged from 500~1500 nt were clustered twice and

2,067 representative sequences of clusters were included. We preferentially selected

305 5′ UTRs of the viruses which infect vertebrates for *in silico* screening.

We used 10 sub-models of LAMAR-IRES to score the tested 5′ UTRs and

categorized them into 3 groups by the averaged probabilities: non-IRESs

(probability<0.5), low-activity IRESs (0.5≤probability<0.9) and high-activity IRESs

(0.9≤probability<1). To validate the correlation between predicted probability and

IRES activity, the efficiency of 5′ UTR promoting circRNA translation was measured.

Specifically, the sequences were inserted into the *in-vitro* synthesized Fluc-coding

circRNA and transfected into 13 kinds of cell lines (A204, A549, AGS, C2C12,

HCT116, HepG2, HFF1, JURKAT, Neruo-2a, RAW264.7, SY5Y, THP-1 and U87) with

96-well plate. The mock and modified Fluc-coding mRNA (CATUG Bio) were

transfected into cells as controls in each batch. Each sample had two replicates. At 24

h after transfection, cells were collected and lysed in the passive lysis buffer. The

protein expression level was measured via luminescence intensity. The mock

transfection was used as an internal control and its protein expression was subtracted.

The relative protein expression of circRNA and modified mRNA was computed and the

final IRES activity was defined by the following formula:

$$IRES\ activity = \log_{10}(relative\ protein\ expression \cdot 1e5 + 1) \qquad (9)$$

Data availability

The datasets used for pretraining and fine-tuning are all derived from databases and previous published studies. Here we include the official websites. RefSeq (Release 221): https://ftp.ncbi.nlm.nih.gov/refseq/release/vertebrate_mammalian/; RNACentral (Release 23): https://ftp.ebi.ac.uk/pub/databases/RNAcentral/releases/23.0/sequences/; NCBI Genome: https://ftp.ncbi.nlm.nih.gov/genomes/refseq/vertebrate_mammalian /assembly_summary.txt; NCBI Virus: https://ftp.ncbi.nlm.nih.gov/genomes/refseq/ viral/assembly_summary.txt; SpliceAI dataset: https://basespace.illumina.com/s/5 u6ThOblecrh. RFAM (Release 14.9): https://rfam.org/search?q=IRES%20AND %20entry_type:%22Family%22. IRESite: http://www.iresite.org; IRESbase: http ://reprod.njmu.edu.cn/cgi-bin/iresbase/index.php. The translation efficiency dataset was obtained from Cao J, et al. and the degradation dataset was obtained from Zhao W, et al. Three IRES datasets (Figure 6D) were obtained from Weingarten-Gabbay S et al, Chen C-K et al and Yang Y et al. Source data are provided with this paper.

Code availability

The scripts used in this study are available in Github repository (https://github.com/rnasys/LAMAR).

Acknowledgments

This work is supported by the National Key Research and Development Program of China (2021YFA1300503), the Strategic Priority Research Program of Chinese Academy of Sciences (XDB38040100) and the National Natural Science Foundation of China (32030064 and 32250013) to Z.W. This work is also supported by Shanghai Science and Technology Innovation Action Plan (23JS1401500) and Shanghai Municipal Science and Technology Major Project (GTP) to G.Z.

Competing interests

Z.W. and Y.Y. has co-founded a company, CirCode Biotech, to commercialize the application of circular RNA as template of protein production/expression. They applied a patent in the optimization of IRES for circRNA translation. The other authors declare no competing interests.

References

1. Brenner, S., Jacob, F. & Meselson, M. An Unstable Intermediate Carrying Information from Genes to Ribosomes for Protein Synthesis. *Nature* **190**, 576-581 (1961).

2. Statello, L., Guo, C.-J., Chen, L.-L. & Huarte, M. Gene regulation by long non-coding RNAs and its biological functions. *Nature Reviews Molecular Cell Biology* **22**, 96-118 (2021).

3. Licatalosi, D.D. & Darnell, R.B. RNA processing and its regulation: global insights into biological networks. *Nature Reviews Genetics* **11**, 75-87 (2010).

4. Van Nostrand, E.L. et al. A large-scale binding and functional map of human RNA-binding proteins. *Nature* **583**, 711-719 (2020).

5. Wan, Y., Kertesz, M., Spitale, R.C., Segal, E. & Chang, H.Y. Understanding the transcriptome through RNA structure. *Nature Reviews Genetics* **12**, 641-655 (2011).

6. Cao, X., Zhang, Y., Ding, Y. & Wan, Y. Identification of RNA structures and their roles in RNA functions. *Nature Reviews Molecular Cell Biology* **25**, 784-801 (2024).

7. Fan, X., Chang, T., Chen, C., Hafner, M. & Wang, Z. Accurate prediction of RNA translation with a deep learning architecture. *bioRxiv*, 2023.2007.2008.548206 (2023).

8. Jaganathan, K. et al. Predicting Splicing from Primary Sequence with Deep Learning. *Cell* **176**, 535-548.e524 (2019).

9. Song, Z. et al. Attention-based multi-label neural networks for integrated prediction and interpretation of twelve widely occurring RNA modifications. *Nature Communications* **12**, 4011 (2021).

10. Stroup, E.K. & Ji, Z. Deep learning of human polyadenylation sites at nucleotide resolution reveals molecular determinants of site usage and relevance in disease. *Nature Communications* **14**, 7378 (2023).

11. Sun, L. et al. Predicting dynamic cellular protein–RNA interactions by deep learning using in vivo RNA structures. *Cell Research* **31**, 495-516 (2021).

12. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In North American Chapter of the Association for Computational Linguistics (2019).

13. Brown, T.B. et al. Language Models are Few-Shot Learners. *ArXiv* **abs/2005.14165** (2020).

14. Zhang, Y. et al. Multiple sequence alignment-based RNA language model and its application to structural inference. *Nucleic Acids Research* **52**, e3-e3 (2023).

15. Wang, N. et al. Multi-purpose RNA language modelling with motif-aware pretraining and type-guided fine-tuning. *Nature Machine Intelligence* **6**, 548-557 (2024).

16. Chen, J. et al. Interpretable RNA Foundation Model from Unannotated Data for Highly Accurate RNA Structure and Function Predictions. *bioRxiv* (2022).

17. Matera, A.G. & Wang, Z. A day in the life of the spliceosome. *Nature Reviews Molecular Cell Biology* **15**, 108-121 (2014).

18. Wang, Z. et al. Systematic Identification and Analysis of Exonic Splicing Silencers. *Cell* **119**, 831-845 (2004).

19. Wang, Z.F. & Burge, C.B. Splicing regulation: From a parts list of regulatory elements to an integrated splicing code. *RNA* **14**, 802-813 (2008).

20. Xiong, H.Y. et al. The human splicing code reveals new insights into the genetic determinants of disease. *Science* **347**, 1254806 (2015).

21. Sahin, U., Karikó, K. & Türeci, Ö. mRNA-based therapeutics — developing a new class of drugs. *Nature Reviews Drug Discovery* **13**, 759-780 (2014).

22. Hinnebusch, A.G., Ivanov, I.P. & Sonenberg, N. Translational control by 5′-untranslated regions of eukaryotic mRNAs. *Science* **352**, 1413-1416 (2016).

23. Sample, P.J. et al. Human 5′ UTR design and variant effect prediction from a massively parallel translation assay. *Nature Biotechnology* **37**, 803-809 (2019).

24. Lewis, C.J.T. et al. Quantitative profiling of human translation initiation reveals elements that potently regulate endogenous and therapeutically modified mRNAs. *Molecular Cell* **85**, 445-459.e445 (2025).

25. Cao, J. et al. High-throughput 5′ UTR engineering for enhanced protein production in non-viral gene therapies. *Nature Communications* **12**, 4138 (2021).

26. Chu, Y. et al. A 5′ UTR language model for decoding untranslated regions of mRNA and function predictions. *Nature Machine Intelligence* **6**, 449-460 (2024).

27. Houseley, J. & Tollervey, D. The Many Pathways of RNA Degradation. *Cell* **136**, 763-776 (2009).

28. Mayr, C. Regulation by 3′-Untranslated Regions. *Annual Review of Genetics* **51**, 171-194 (2017).

29. Griesemer, D. et al. Genome-wide functional screen of 3′ UTR variants uncovers causal variants for human disease and evolution. *Cell* **184**, 5247-5260.e5219 (2021).

30. Zhao, W. et al. Massively parallel functional annotation of 3′ untranslated regions. *Nature Biotechnology* **32**, 387-391 (2014).

31. Ray, D. et al. A compendium of RNA-binding motifs for decoding gene
regulation. *Nature* **499**, 172-177 (2013).

32. Yang, Y. & Wang, Z. IRES-mediated cap-independent translation, a path
leading to hidden proteome. *Journal of Molecular Cell Biology* **11**, 911-
919 (2019).

33. Gritsenko, A.A. et al. Sequence features of viral and human Internal
Ribosome Entry Sites predictive of their activity. *PLOS Computational*
Biology **13**, e1005734 (2017).

34. Zhao, J. et al. IRESfinder: Identifying RNA internal ribosome entry site in
eukaryotic cell using framed k-mer features. *Journal of Genetics and*
Genomics **45**, 403-406 (2018).

35. Wang, J. & Gribskov, M. IRESpy: an XGBoost model for prediction of
internal ribosome entry sites. *BMC Bioinformatics* **20**, 409 (2019).

36. Chen, C.-K. et al. Structured elements drive extensive circular RNA
translation. *Molecular Cell* **81**, 4300-4318.e4313 (2021).

37. Weingarten-Gabbay, S. et al. Systematic discovery of cap-independent
translation sequences in human and viral genomes. *Science* **351**,
aad4939 (2016).

38. Yang, Y. et al. Unbiased screen of human transcriptome reveals an
unexpected role of 3ʹ UTRs in translation initiation. *bioRxiv*,
2021.2005.2028.446092 (2021).

39. Mokrejš, M. et al. IRESite—a tool for the examination of viral and cellular
internal ribosome entry sites. *Nucleic Acids Research* **38**, D131-D136
(2010).

40. Zhao, J. et al. IRESbase: A Comprehensive Database of Experimentally
Validated Internal Ribosome Entry Sites. *Genomics, Proteomics &*
Bioinformatics **18**, 129-139 (2020).

41. Kalvari, I. et al. Rfam 14: expanded coverage of metagenomic, viral and
microRNA families. *Nucleic Acids Research* **49**, D192-D200 (2021).

42. Wang, Y. & Wang, Z.F. Efficient backsplicing produces translatable
circular mRNAs. *RNA* **21**, 172-179 (2015).

43. Pamudurti, N.R. et al. Translation of CircRNAs. *Molecular Cell* **66**, 9-
21.e27 (2017).

44. Wesselhoeft, R.A., Kowalski, P.S. & Anderson, D.G. Engineering circular
RNA for potent and stable translation in eukaryotic cells. *Nature*
Communications **9**, 2629 (2018).

45. Chen, C. et al. A flexible, efficient, and scalable platform to produce
circular RNAs as new therapeutics. *bioRxiv*, 2022.2005.2031.494115
(2022).

46. Sun, M. & Yang, Y. Biological functions and applications of circRNAs—
next generation of RNA-based therapy. *Journal of Molecular Cell Biology*
15, mjad031 (2023).

47. Fan, X., Yang, Y., Chen, C. & Wang, Z. Pervasive translation of circular RNAs driven by short IRES-like elements. *Nature Communications* **13**, 3751 (2022).

48. Wang, X.-W., Liu, C.-X., Chen, L.-L. & Zhang, Q.C. RNA structure probing uncovers RNA structure-dependent biological functions. *Nature Chemical Biology* **17**, 755-766 (2021).

49. Justyna, M., Antczak, M. & Szachniuk, M. Machine learning for RNA 2D structure prediction benchmarked on experimental data. *Briefings in Bioinformatics* **24**, bbad153 (2023).

50. Agarwal, V. & Kelley, D.R. The genetic and biochemical determinants of mRNA degradation rates in mammals. *Genome Biology* **23**, 245 (2022).

51. Nguyen, E. et al. in Proceedings of the 37th International Conference on Neural Information Processing Systems Article 1872 (Curran Associates Inc., New Orleans, LA, USA; 2024).

52. Kaplan, J. et al. Scaling Laws for Neural Language Models. *ArXiv* **abs/2001.08361** (2020).

53. Rives, A. et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences* **118**, e2016239118 (2021).

54. Lin, Z. et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science* **379**, 1123-1130 (2023).

55. Su, J.L. et al. RoFormer: Enhanced transformer with Rotary Position Embedding. *NEUROCOMPUTING* **568** (2024).

56. O'Leary, N.A. et al. Reference sequence (RefSeq) database at NCBI: current status, taxonomic expansion, and functional annotation. *Nucleic Acids Research* **44**, D733-D745 (2016).

57. Consortium, R.N. RNAcentral 2021: secondary structure integration, improved sequence search and new member databases. *Nucleic Acids Research* **49**, D212-D220 (2021).

58. Quinlan, A.R. & Hall, I.M. BEDTools: a flexible suite of utilities for comparing genomic features. *Bioinformatics* **26**, 841-842 (2010).

59. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nature Biotechnology* **35**, 1026-1028 (2017).

60. Loshchilov, I. & Hutter, F. Decoupled Weight Decay Regularization. *Arxiv* (2019).

61. Dao, T., Fu, D.Y., Ermon, S., Rudra, A. & Ré, C. FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness. *arXiv e-prints*, arXiv:2205.14135 (2022).

62. Sievers, F. et al. Fast, scalable generation of high‑quality protein multiple sequence alignments using Clustal Omega. *Molecular Systems Biology* **7**, 539 (2011).

1000   63.   Wagih, O. ggseqlogo: a versatile R package for drawing sequence logos.
1001   *Bioinformatics* **33**, 3645-3647 (2017).
1002   64.   Seemann, T. Prokka: rapid prokaryotic genome annotation.
1003   *Bioinformatics* **30**, 2068-2069 (2014).
1004
1005

1006   **Figures and figure legends**

1007

Figure 1. Pretraining an RNA foundation model for multilayer regulation of RNA.

(A) Schematic for processing of the pretraining dataset. **(B)** The statistics of pretraining

dataset. Left, the taxonomic makeup of the mammals (top) and the viruses (bottom)

used for pretraining. Right, the number of the nucleotide (top) and sequence length

(bottom) of the genes and transcripts in the pretraining dataset. **(C)** In the pretraining

stage, LAMAR learns the sequence features of RNA by predicting the likelihoods of

the masked tokens in the sequence. LAMAR comprises of 12 transformer layers and a

task-specific prediction head. **(D)** LAMAR is fine-tuned for the downstream tasks

including supervised prediction of splice site, translation efficiency, degradation rate

and internal ribosome entry site (IRES).

1018

Figure 2. LAMAR learned the biological properties of nucleotides and the function

features of RNAs.

(A) Schematic for the representative embedding by LAMAR. The LAMAR pretrained

encoder of represents the RNA sequence of n nucleotides as the hidden embedding

with the shape of $n \times 768$. The hidden embedding was further averaged as the

representative embedding of the nucleotide and RNA for visualization of their feature

space. **(B-D)** Visualization of the embeddings from the pretrained model (top) and the

untrained model (bottom). NMI, normalized mutual information. **(B)** The PCA plot

visualizing the embeddings of four classes of nucleotides. **(C)** The tSNE plot

visualizing the embeddings of functional regions (5′ UTR, CDS and 3′ UTR). **(D)** The

tSNE plot visualizing the embeddings of RNAs (mRNA, lncRNA, snRNA, miRNA,

snoRNA and tRNA).

1031

Figure 3. Prediction of splice sites in pre-mRNAs.

1032

(A) Schematic for prediction of splice sites in pre-mRNAs by fine-tuned LAMAR. First,

LAMAR represents the pre-mRNA segments of 1024 nt as the hidden embeddings of

the shape 1024×768. Then, the hidden embeddings were input into the prediction

head to predict the probability that a nucleotide is a 5′ splice site, a 3′ splice site or

neither. **(B)** The tSNE plots visualizing the hidden embeddings of the splice sites and

non-splice sites output from the untrained model (top) and the pretrained model

(bottom). **(C)** The top-k accuracy and PRAUC of LAMAR in predicting splice sites,

evaluated under different fine-tuning strategies. **(D)** The top-k accuracy and PRAUC of

LAMAR-SS and baseline methods (including SpliceAI sub-models and RNA-FM-SS)

in predicting splice sites.

1043

Figure 4. Prediction of translation efficiencies of mRNAs by 5′ UTRs.

(A) Schematic for prediction of translation efficiencies of mRNAs based on 5′ UTRs

by fine-tuned LAMAR. **(B, C)** The Spearman correlation coefficient and mean squared

error between observed and predicted translation efficiency for LAMAR-TE and

baseline methods, including RNA-FM-TE and UTR-LM. The *P* values were calculated

with Wilcoxon signed rank test. **, P value < 0.01.

1050

Figure 5. Prediction of degradation rates of mRNAs by 3′ UTRs.

(A) Schematic for fine-tuning LAMAR to predict the half-lives of mRNAs with different 3′ UTRs. **(B, C)** The Spearman correlation coefficient and mean squared error

between observed and predicted half-lives for LAMAR-DR and RNA-FM-DR. **(D)**

Each nucleotide of 3′ UTR was mutated *in silico* and the half-lives of mutated

sequences were predicted by LAMAR-DR. The Δhalf-lives between the mutated and

wild-type 3′ UTRs were computed to predict the mutation effect, and the perturbation

scores were analyzed to identify *cis*-regulatory elements. **(E)** The observed (top) and

predicted (bottom) mutation effects of 3′ UTR segment of CXCL2. The nucleotides of

the AU-rich element were colored in orange. **(F)** The distribution of perturbation scores

of the short elements which positively and negatively regulate the half-life of mRNA.

(G, H) The identified destabilizing and stabilizing hexamers which were clustered into

5 and 4 classes by the polygenetic tree, respectively. The names of reported motifs were

listed at the right of the clusters. **(I)** The examples of the LAMAR-identified

destabilizing and stabilizing motifs were presented by the profile of perturbation score

in 3′ UTR segments of TRIO and STMN4 genes. *P* values were calculated with

Wilcoxon signed rank test. **, *P* value < 0.01.

1068

Figure 6. Prediction of IRES.

(A) Schematic for fine-tuning LAMAR to predict IRESs. **(B)** The IRESs collected from

IRESite, IRESbase and RFAM databases were used as training data. **(C)** The ROC

curves of LAMAR-IRES and RNA-FM-IRES. **(D)** The predicted probabilities of oligos

in three high-throughput experimental libraries screening IRES. **(E)** Schematic of *in*

silico screening of IRES. The putative IRESs were extracted from positive-sense single-

strand RNA viruses and their probabilities were predicted by LAMAR-IRES. The IRES

activities of the candidates were subsequently validated by the circRNA-based

luciferase assays. **(F)** The IRES activities of candidate sequences classified by

LAMAR-IRES scores were tested in 13 cell lines. P values were calculated with

Wilcoxon rank sum test. *, P value < 0.05; **, P value < 0.01.

1080

A

B

Supplementary Figure 1. Summary of pretraining dataset.

(A) Phylogenetic tree of mammals in pretraining dataset. The 225 mammals whose

genes/transcripts were used in pretraining were clustered into 15 suborders by the

phylogenetic tree. The mammals belong to different suborders are represented by

different colors. **(B)** The number of gene/transcript cluster are plotted against the cluster

size. Inset plot shows distribution of cluster size below 500.

1088

1089

Supplementary Figure 2. Evaluation of the pretraining steps.

The loss curve for LAMAR-2k and LAMAR-4k models during the pretraining (rea

lines). The accuracy of these models in predicting the masked tokens were also plotted

in each step of pretraining (blue lines).

1095

Supplementary Figure 3. The distances between the nucleotide embeddings.

The cosine distances between the nucleotide embeddings from untrained model (top)
and pretrained model (bottom). *P* values were calculated with two-sided Wilcoxon rank
sum test. **, *P* value < 0.01; ns, not significant.

1100

1101

Supplementary Figure 4. The performance of LAMAR fine-tuned with different strategies in predicting translation efficiency.

The Spearman correlation coefficient **(A)** and mean squared error **(B)** between observed and predicted translation efficiency for LAMAR fine-tuned with different strategies. *P* values were calculated with Wilcoxon signed rank test. **, *P* value < 0.01; ns, not significant.

1108

Supplementary Figure 5. The performance of LAMAR fine-tuned with different

strategies in predicting degradation rate.

The Spearman correlation coefficient **(A)** and mean squared error **(B)** between observed

and predicted half-life for LAMAR fine-tuned with different strategies. **(C)** The scatter

plot depicting the predicted (x axis) and observed variant effect (y axis) of each position

in 3′ UTR segment of CXCL2. **(D)** The scatter plot depicting the perturbation score (x

axis) and observed regulatory effect (y axis) of the short elements which positively and

negatively regulating the half-live of mRNA. *P* values were calculated with Wilcoxon

signed rank test. **, *P* value < 0.01.

1118

1119 **Supplementary Figure 6. The performance of LAMAR fine-tuned with different**

1120 **strategies in predicting IRES.**

1121 The AUC of LAMAR in classifying IRES, evaluated under different fine-tuning

1122 strategies. *P* values were calculated with Wilcoxon signed rank test. **, *P* value < 0.01;

1123 ns, not significant.

1124