In silico generation of synthetic cancer genomes using generative AI

Ander Díaz-Navarro,[1,2,†] Xindi Zhang[1], Wei Jiao[1], Bo Wang,[3,4,5,6,7] and Lincoln Stein[1,2,5,†]

[1]Ontario Institute for Cancer Research, Toronto, ON, Canada
[2]Department of Molecular Genetics, University of Toronto, Toronto, ON, Canada
[3]Peter Munk Cardiac Centre, University Health Network, Toronto, ON, Canada
[4]Department of Computer Science, University of Toronto, Toronto, ON, Canada
[5]Vector Institute, Toronto, ON, Canada
[6]Department of Medical Biophysics, University of Toronto, Toronto, ON, Canada
[7]Department of Laboratory Medicine and Pathobiology, University of Toronto, Toronto, ON, Canada

† Corresponding authors

Abstract

Cancer originates from alterations in the genome, and understanding how these changes lead to disease is crucial for achieving the goals of precision oncology. Connecting genomic alterations to health outcomes requires extensive computational analysis using accurate algorithms. Over the years, these algorithms have become increasingly sophisticated, but the lack of gold-standard datasets presents a fundamental challenge. Since genomic data is considered personal health information, only a limited number of deeply sequenced cancer genomes are available for distribution. As a result, tool benchmarking is often conducted on a small set of genomes with uncertain ground truths, which makes it difficult to measure the accuracy of analytic workflows.

To address this issue, we developed a novel generative AI tool called OncoGAN to generate synthetic cancer genomes based on training sets derived from large-scale genomic projects by employing generative adversarial networks and tabular variational autoencoders. Our results demonstrate that this approach accurately reproduces the number and frequency of mutations and their characteristics. Furthermore, it captures the genomic position of the mutations following the patterns specifically found for each tumor, and it enables us to replicate tumor-specific mutational signatures. To evaluate the fidelity of the simulations, we tested the synthetic genomes using DeepTumour, a software capable of identifying tumor types based on mutational patterns, and demonstrated a high level of concordance between the synthetic genome tumor type and DeepTumour's prediction of the type.

This tool will allow the generation of a large realistic training and testing set of cancer genomes containing known genome alterations. This represents an advance for computational biologists, who will now have access to a publicly available set of realistic synthetic genomes with no privacy concerns, which can be used to develop new algorithms, improve the accuracy of existing tools, and benchmarking.

Background

The vast majority of cancers arise from damage to the genome which alter the expression or activity of key genes involved in the pathways that regulate cell proliferation, programmed cell death, and interaction with surrounding tissues. The promise of precision oncology is that by cataloging these genomic alterations, clinicians can apply therapies that target these altered pathways for improved patient outcomes and decreased side effects. Cancer genome alterations have been extensively explored through multiple large-scale genomic projects, starting with the International Cancer Genome Consortium[1] and The Cancer Genome Atlas[2], and continuing to this day with such large-scale projects as the PanCancer Analysis of Whole Genomes (PCAWG)[3], the 100,000 Genomes Project[4] or the Hartwig Medical Foundation[5]. Collectively, these projects have analyzed over 20,000 whole-genomes from patients with different types of tumors, detecting a large number of point mutations, as well as structural variants (SVs) and copy number alterations (CNAs)[4,6–8]. Using these extensive datasets, researchers have utilized the frequency of these genomic alterations alongside clinical characteristics to identify the key drivers of the cancer phenotype.

To analyze this data, a series of complex computational pipelines have been developed that employ multiple variant "callers"[9–13], each one tuned to detect and identify better a specific range of mutations[3]. However, a fundamental issue with these tools is that there is no gold standard set of cancer genomes with known mutations to test the callers against. Computational biologists instead benchmark their mutation calling tools against a small set of approximately 50 legacy genomes derived from cancer cell lines[14,15], datasets compiled by the Genome In A Bottle Consortium with high-confidence variant calls[16], or alternatively test their tools to normal genomes that have been spiked with a known series of *in silico*-generated mutations[17,18]. Unfortunately, neither of these approaches is able to capture the mutational diversity of true cancer genomes from patients' tumors, which vary widely according to the tissue of origin, treatment history, and the patient's environmental exposures. Compounding this are the restrictions on sharing human genomic data, which make it logistically difficult to assemble and share large numbers of cancer genomes[19–21]. Together these challenges have slowed the development of cancer genome analysis tools.

Recent advances in deep learning techniques such as generative adversarial networks[22] (GANs) or variational autoencoders[23] (VAEs), may represent an opportunity to create open synthetic datasets that can be used to improve the programs currently applied to the analysis of tumor genomes. Notably, Yelmen et al. demonstrated the utility of GANs in genomics by constructing a model capable of generating high-quality artificial genomes that simulate haplotype segments across different ethnicities[24]. Briefly, GANs consist of two convolutional neural networks working together. The first one, the generator, creates a result from random data, while the second one, the discriminator or critic, attempts to differentiate real data from synthetic data. By repeatedly pitting the generator against the discriminator, both neural networks incrementally improve, ultimately allowing the GAN to achieve highly realistic simulations. VAEs are a type of neural network that

learns to encode input data into a compressed, probabilistic latent space and then decodes it back to reconstruct the original input. Unlike traditional autoencoders, VAEs introduce randomness by sampling from the latent space, allowing them to generate new, similar data during the decoding process. Although GANs and VAEs were originally used for image generation tasks, several new models have been published for tabular data, including TGAN[25], CTGAN[26], CopulaGAN[26], TableGAN[27] or CTAB-GAN+[28] for GAN architectures, as well as TVAE[26] for variational autoencoder-based approaches.

Here, we present OncoGAN, a pipeline that uses GANs, TVAEs and a random sampling approach trained on large quantities of real cancer genome sequencing data to generate an unlimited number of realistic simulated cancer genomes with known ground truths. Using OncoGAN, we have generated and released 800 simulated genomes across 8 cancer types which are free of distribution restrictions and ready for use in the design of new and more efficient genome analysis programs.

Results

Multi-Model Ensemble Pipeline for Synthetic Tumor Generation

OncoGAN is a comprehensive pipeline designed to generate synthetic tumor samples in variant call format (VCF) for eight distinct cancer types (Figure 1). Cancer genomes are characterized by the accumulation of genetic alterations, which can be broadly categorized into 'driver' and 'passenger' events. Driver mutations directly contribute to cancer development by conferring growth advantages to cells, while passenger mutations are the result of the genomic instability in cancer cells. These mutations can take various forms, including single nucleotide changes, insertions, deletions, and structural rearrangements, all of which contribute to the complexity of cancer genomes. To accurately simulate the complex mutational landscape, we trained five different models using the PCAWG data (*see Methods*), organized into two primary categories: donor and mutation characteristics. Donor characteristics include: i) the number of different mutation types (single/di/tri nucleotide polymorphisms, SNP/DNP/TNP; small insertions, INS; small deletions, DEL), and ii) the number and type of driver mutations, also referred to here as drivers' intercorrelation (i.e., driver co-occurrence and mutual exclusion), present in each donor. By training these models independently, we are able to replicate the tumor heterogeneity observed in real data (*see the next section*). Mutation characteristics cover iii) mutational signature contexts, iv) genomic positions, and v) variant allele frequencies (VAF). Since these features are independent and present unique challenges during training, we developed a separate model for each, which are then integrated to enhance overall performance.

We utilized three distinct strategies for training the models: generative adversarial networks (GANs), tabular variational autoencoders (TVAE), and random sampling. CTAB-GAN+ was employed for three of the five models –specifically, the number of each type of mutation and drivers for each donor, and mutational signature contexts– due to their high accuracy in capturing and simulating intra-feature relationships. To predict genomic positions, we combined CTGAN and TVAE architectures with a discretization process (*see Methods*), enabling us to accurately capture mutation density along the genome. Allele frequencies were simulated by first randomly selecting the mean variant allele frequency per donor, based on distributions observed in real patients, and then randomly choosing VAFs according to the expected distribution for that particular mean frequency.

These models are integrated into an automated pipeline, OncoGAN, which enables the simulation of realistic tumor samples. The pipeline begins by generating donor characteristics, including determining the number of each mutation type within each sample and the mean variant allele frequency of the donor. Subsequently, the number of mutations for each driver gene is simulated, maintaining drivers' intercorrelation. Since driver mutations cannot be randomly generated, they are selected from a tumor-type-specific list derived from real patient data published previously by the PCAWG[3,29,30]. Following this, the donor's gender is selected based on actual frequency data, and passenger mutations along with their genomic positions are simulated. Given that the models lack reference genome information (i.e., the ability to map coordinates to their DNA sequences), they cannot directly match the mutation's trinucleotide reference context with its position. Consequently, after all mutations are simulated, these two characteristics are aligned by searching for the reference context within the sequence extracted from the coordinates. A window size of 100 nucleotides around the predicted position is used to search for the expected trinucleotide context, and if no match is found, a new position is simulated to ensure minimal deviation from the initial prediction. Finally, a variant allele frequency is assigned to each mutation, resulting in a VCF file for each simulated donor.

Figure 1. Overview of the OncoGAN ensemble pipeline. OncoGAN integrates five distinct models, each trained on data from eight different tumor types sourced from the PCAWG dataset. The architecture of each model, which includes generative adversarial networks (GANs), tabular variational autoencoders (TVAE) and random sampling, is specifically selected based on the input features to ensure accurate simulation. This multi-model ensemble pipeline allows us to generate realistic synthetic donors for the trained tumor types.

OncoGAN Mimics Tumor Heterogeneity and Clonality

To evaluate whether OncoGAN can simulate donors with characteristics that reflect the tumor heterogeneity observed among patients, we generated 100 samples for each of the eight tumor types and compared their characteristics, including the number and types of mutations, their variant allele frequency, and the relationships between driver genes.

First, we visually examined the distribution of the number of mutations in both real and simulated donors (Figure 2A and Supplementary Figure S1). This involved comparing the number of each mutation type against the total number of mutations per donor, allowing us to assess not only the range of specific mutations but also their proportion relative to the total mutation count. The resulting scatter and density distributions for the real and simulated data were highly similar, meaning that we are simulating heterogeneous donors. To quantify this similarity, we measured the intersection distance between real and synthetic population histograms for each type of mutation (Figure 2B and Supplementary Figure S2, Supplementary Table S1), where a smaller distance indicates greater similarity. For all simulations, except for certain mutation types in Liver-HCC and Prost-AdenoCa, the results were comparable to those observed in comparisons between subpopulations from the PCAWG dataset, suggesting that the simulated and real populations are virtually identical. In the case of Liver-HCC, the differences in intersection distances may be attributed to its large sample size, which makes donors with very low or high mutation counts rarer and more challenging to simulate. Nonetheless, the scatter and density plots (Supplementary Figure S1 - Liver -HCC) show that the simulated populations are quite similar. For Prost-AdenoCa, the main difference lies in the simulation of TNPs, likely attributable to the very low frequency of this mutation type, which only represents 0.006% of the total number of mutations, meaning that the differences are minimal. There is also a minor discrepancy in the simulation of deletions. However, the scatter and density plots show no real differences between both populations (Supplementary Figure S1 - Prost-AdenoCa). We also examined the similarity between different tumor types in terms of total mutation counts to determine if OncoGAN simulations exhibit the same patterns as real tumors. To do this, we compared the intersection distances of the different tumors from the PCAWG dataset and our simulations. As shown in Figure 1C, the relationships among tumor types in both cases are nearly identical (Pearson coefficient = 0.966 [0.944, 0.979]).

Another characteristic simulated by OncoGAN is the donor variant allele frequency, which reflects sample purity. This is generated using a simple approach where the donor VAF is sampled from the real distribution, and mutation-specific VAFs are subsequently sampled according to the distribution for that particular donor VAF. As seen in Supplementary Figure S3 and Supplementary Table S2, there are no differences between PCAWG donor VAFs and our simulations, except for CNS-PiloAstro (Wilcoxon-test p-value = 0.008). However, the median VAF was 0.222 (q1 = 0.196; q3 = 0.260) and 0.238 (q1 = 0.221; q3 = 0.257) for PCAWG and OncoGAN donors, respectively, with identical variance (F-score = 0.992 and F-test p-value = 0.964 for CNS-PiloAstro), overall indicating that both populations are very similar. When examining VAF for individual mutation types, the distribution is also quite similar between real and simulated data, with two notable differences (Supplementary Figure S4). Tri-nucleotide polymorphisms tend to have a lower VAF in the original dataset, likely due to the small number of TNPs present, while Lymph-CLL indels (insertions and deletions) show a higher overall VAF, possibly resulting from variant callers being less effective at detecting indels at lower frequencies.

Mutations simulated by our models are randomly generated to mimic mutational patterns found in real tumors, which means it is not suitable for the simulation of driver mutations. Therefore, driver mutations are sampled from a list specific to each tumor type published by the PCAWG. However, because driver mutations do not appear at the same frequency and some are mutually exclusive, we trained a model to replicate coding and non-coding driver mutation frequencies and their intercorrelation. After the simulation, the correlation between the frequency and inter-relationships of real and simulated driver mutations was very high, with a Pearson coefficient above 0.9 for most of the tumor types (Supplementary Figure S5, Supplementary Table S3). The tumor with the lowest correlation was Eso-AdenoCa (Pearson coefficient = 0.767 [0.759, 0.776]), likely due to the large number of selected drivers for this tumor (10 coding and 60 non-coding), making it more challenging to train an accurate model given the number of available donors.

Figure 2. Quality control plots for donor characteristics. A) Scatter and density plots comparing the number of specific mutation types to the total number of mutations for each donor (real in orange, simulated in black) in the Breast-AdenoCa dataset. PCAWG and OncoGAN distributions are highly similar. B) Violin plots for the Breast-AdenoCa tumor type, showing the distribution of intersection distances between two randomly sampled populations from the PCAWG dataset (1000 iterations) and the scores comparing OncoGAN simulations to the actual dataset. The lower the score, the more similar the populations are. For Breast-AdenoCa, all the mutation types have an intersection distance similar to that found in the real data. C) Heatmap of intersection distances comparing different tumors from the PCAWG dataset (left) and OncoGAN simulations (right). A Pearson correlation of 0.966 indicates a high degree of similarity in the relationship between simulated and real donors. A lower intersection distance indicates greater similarity between the two populations. *SNP/DNP/TNP, single/double/triple nucleotide polymorphisms; INS, insertions; DEL, deletions.*

Synthetic Tumors Resemble Tissue-Specific Mutational Patterns

We next sought to confirm whether the mutational patterns specific to each type of cancer were accurately generated by our model. While the majority of mutations are passengers, their genomic locations are tumor-type-specific and depend on the cell of origin[6,31,32]. To create high-quality synthetic cancer genomes, it is essential to replicate these specific mutation patterns along the genome. We compared the percentage of mutations found across the genome (in 1Mb regions) between the PCAWG and OncoGAN datasets, demonstrating that both real and simulated patterns are very similar (Pearson coefficient for Breast-AdenoCa dataset = 0.878 [0.869, 0.886]), with minor differences in some specific regions (Figure 3A, Supplementary Figure S6). A clear example of this accuracy is observed in Lymph-CLL, where we successfully reproduced the mutational peaks associated with somatic hypermutation of the immunoglobulin genes. Similar consistency is also observed when comparing the percentage of mutations detected per region in both datasets (R^2 for PCAWG = 0.679 [0.638, 0.709]; R^2 for OncoGAN = 0.772 for Breast-AdenoCa) (Figure 3B, Supplementary Figure S7, Supplementary Table S4). This indicates that regions with lower percentages of mutations in real data also have lower percentages in our simulations.

The tumor type with less similarity between real and simulated genomic coordinates is CNS-PiloAstro, with a Pearson coefficient of 0.683 and R^2 of 0.466. However, this tumor type has a very low mutational burden, with a mean of 261 mutations per patient, making it easier to identify a sparse correlation. This is further explained by the R^2 calculated when comparing two samples from the PCAWG dataset, which is 0.276 [0.247, 0.301], a low value compared to other tumors with higher mean number of mutations, such as Eso-AdenoCa (R^2 = 0.977 [0.969, 0.982]), Liver-HCC (R^2 = 0.983 [0.98, 0.985]) or Kidney-RCC (R^2 = 0.967 [0.946, 0.982]) (Supplementary Table S4).

Similarly, we examined whether the simulations maintained the same relationships among different tumor types regarding the genomic pattern of mutations as observed in the original donors. The results demonstrate that the simulations not only resemble the original data but also preserve the relationships between tumor types (Supplementary Figure S8, Supplementary Table S5).

Each tumor type also has distinct mutational signatures related to different biological or external mechanisms. For example, SBS4 is associated with tobacco smoking, SBS7 with ultraviolet light exposure, and SBS9 with the somatic hypermutation activity of the activation-induced cytidine deaminase (AID) in lymphoid cells[6]. To accurately replicate these signatures, we need to simulate the frequency of donors with each signature for a specific tumor type, the density at which each signature is found in each donor, and the relationships between different signatures (e.g., some may be mutually exclusive). Thus, we predict the number of mutations for each mutational signature simultaneously with the number of specific mutation types. As shown in Supplementary Figure S9, our model successfully simulates the tumor heterogeneity in mutational signature distribution across tumor types, as confirmed by SigProfiler[33] (Figure 3C, Supplementary Figure

S10). The SigProfiler plots demonstrate that the density of mutations detected for each signature is highly similar to that observed in real donors, with our simulations accurately capturing the variability among donors. Regarding the number of signatures detected per tumor type, we were able to identify all simulated signatures across tumor types except for Eso-AdenoCa (SBS10c, SBS8) and Panc-Endocrine (SBS19, SBS30), where two signatures were missing. This limitation is related to the technique we are using. Low-frequency mutational signatures, like SBS10c in Eso-AdenoCa and SBS19 in Panc-Endocrine, are underrepresented in the training dataset (5% of donors) and belong to complex tumor types with eight and ten different mutational signatures, making it more challenging for the model to learn the context distribution among the remaining mutations. For example, signatures SBS19 and SBS23, present in the same percentage of donors, are well-represented in the CNS-PiloAstro tumor type, but this tumor has only five different signatures, making it easier for the model to distinguish them. On the other hand, the failure to generate and detect SBS8 and SBS30 in Eso-AdenoCa and Panc-Endocrine, respectively, may be due to a bias in the training dataset or a lower accuracy of the auxiliary component of the CTAB-GAN+ model, which may misclassify this particular signature. To further explore this, we decided to compare the mutational profile of the SBS30 mutational signature available in COSMIC, which is used by SigProfiler for its predictions, with the one present in the training set and the one simulated by OncoGAN for this same signature. We found that OncoGAN accurately simulates the mutation distribution present in the training set, but this does not perfectly correspond to the COSMIC profile, which may prevent it from being detected (Supplementary Figure S11). This discrepancy between COSMIC and the training set may be due to how we generated the latter, where each mutation is assigned a mutational signature based on the probability that SigProfiler assigns to each trinucleotide context of belonging to each signature. This may have caused the assigned distribution to slightly differ from the original by chance.

Since each simulated mutation is annotated with its corresponding signature, we compared the number of specific signature mutations simulated by OncoGAN with those detected by SigProfiler for each donor. We found that for most donors, these two numbers were highly correlated (Pearson coefficient = from 0.827 (Liver-HCC) to 0.997 (Kidney-RCC)) (Supplementary Figure S12, Supplementary Table S6-S7). There were only a few donors where OncoGAN simulated a specific signature that was not detected by SigProfiler. However, in those cases, the simulated signature was present at a very low frequency, indicating that they may be under the detection limit of the tool.

Another feature we are simulating, along with the mutational context, is the length of the indels. We compared the indel length distributions in both the PCAWG and OncoGAN datasets and found that they are within the same range, following the same pattern (Supplementary Figure S13). There are some statistical differences for certain indel lengths and tumor types due to sample size, but these do not significantly affect the quality of the simulation.

Finally, we explored the consequences of the mutations in the genome using the Ensembl Variant Effect Predictor tool[34], comparing the results between real and simulated donors. As shown in Supplementary Figure S14, for each of the tumor types, the proportion of mutations per donor assigned to the possible consequences are highly similar, with comparable variability across both datasets. Intergenic and intronic variants are the most common categories in all cases, followed by downstream and upstream variants. On average, missense mutations account for 0.64% and 0.66% of the total number of mutations in PCAWG and OncoGAN donors, respectively.

Figure 3. Quality control plots for tissue-specific mutational patterns for Breast-AdenoCa tumors. A) Histogram displaying the total percentage of mutations across the genome in 1Mb bins. Real and simulated donors are displayed in orange and black, respectively, and the difference is shown in green. A Pearson correlation of 0.878 indicates high similarity between PCAWG and OncoGAN results. B) Scatter plot comparing the percentage of mutations in each 1Mb genomic region between two random samples from the Breast-AdenoCa dataset (left) and OncoGAN simulations (right) against the entire Breast-AdenoCa dataset. Each dot represents a region, with color indicating density; lighter colors mean higher densities. C) Distribution of mutation signatures, showing the number of somatic mutations per megabase and the percentage of donors exhibiting each signature. Signatures in the PCAWG dataset are accurately reproduced by OncoGAN, matching both the proportion of affected patients and the mutation density per megabase. Dots represent individual donors; the red line illustrates the mean number of somatic mutations per megabase. *SBS, single base substitutions.*

Improving Algorithms Performance Combining Real and Synthetic Datasets

As we have shown previously, the individual characteristics we have simulated closely resemble the original data. To validate that the final result of the simulation, i.e., each individual simulated donor, corresponds to the expected tumor type, we utilized DeepTumour, a tool that predicts the tumor tissue of origin based on the list of detected somatic mutations[35], which is the direct output of OncoGAN. We ran DeepTumour on the synthetic donors and achieved very high prediction accuracy, nearly 100% for most of the tumor types (Supplementary Table S8). However, when examining the 5-fold cross-validation results of the original model, we observed that some tumor types had lower performance (Figure 4C - Baseline metrics). In particular, we investigated Lymph-MCLL and Eso-AdenoCa datasets in more detail to understand the drop in performance for these tumor types.

Figure 4. DeepTumour prediction analysis. A) PCA of Eso-AdenoCa real donors using the total number of each mutation type and mutational signatures as features. The four most significant features are highlighted in red boxes. B) Histogram showing the distribution of accurate and misclassified Eso-AdenoCa donors by DeepTumour according to the number of SNPs. Donors with fewer mutations are more frequently misclassified (48% vs. 11%). C) Comparison of precision, recall, and F1 metrics between the baseline DeepTumour model (light green) and a model trained with the original dataset plus 100 simulated donors for each of the eight tumor types (beige). Metrics that decreased in the new model compared to the baseline are marked in red text.

Lymph-CLL is a disease characterized by two distinct subtypes, U-CLL and M-CLL, based on the mutational status of the immunoglobulin heavy-chain variable region (IGHV), with M-CLL presenting three mutation peaks at the IGHV genes (chr2-IGK, chr14-IGH, and chr22-IGL, (Supplementary Figure S6) and the mutational signature SBS9, while U-CLL lacks these features[36]. When analyzing the 5-fold cross-validation results from DeepTumour, we observed that the recall for Lymph-MCLL was the lowest, with only 63% (22/35) of donors correctly classified, and the remaining 37% (13/35) misclassified as B-cell non-Hodgkin lymphoma (Lymph-BNHL) (Supplementary Table S8). This misclassification can be attributed to the nearly identical mutational patterns between these two tumors, with a Pearson coefficient of 0.941 and R^2 of 0.887 (Supplementary Figure S15). The primary difference occurs in the three regions that correspond with the IGHV genes, which have a lower percentage of mutations, as only 73% of Lymph-BNHL cases present the SBS9 signature, compared to 100% of M-CLL donors. Furthermore, of the 95 Lymph-CLL donors used to train DeepTumour, only 35 (37%) were M-CLL, indicating that a larger sample size may be necessary to improve the prediction accuracy for this tumor type.

On the other hand, Eso-AdenoCa had the lowest precision (76%) and the second lowest recall (80%) among the tumor types. To investigate the Eso-AdenoCa donors, we performed a PCA analysis based on the number of each type of mutation and signature. As shown in Figure 4A, misclassified donors can be mainly distinguished from the rest by their number of SNPs. Specifically, when dividing the donors by their total number of SNPs, we found that those with the fewest mutations (first quartile, n=25) were more frequently misclassified (48% vs. 11%) (Figure 4B). This suggests that these samples may represent cases that are underrepresented in the training dataset.

Given these findings, we decided to train a new DeepTumour model using a mixed dataset of real and synthetic donors to determine whether this could enhance the model's accuracy. We trained DeepTumour with the same 5-fold cross-validation strategy, but adding 100 OncoGAN-simulated donors to 8 of 29 tumor types present in the training dataset. For this new model, the overall accuracy improved by 0.9% (from 89.26% to 90,16%) (Supplementary Figure S16). For the eight studied tumor types, the 5-fold cross-validation precision, recall, and F1 scores increased by 1%, 1.58% and 1.34%, respectively. Additionally, tumor types with fewer donors in the original DeepTumour training dataset benefited the most from the supplementary training, such as Lymph-MCLL (n=35) and Lymph-UCLL (n=60), with F1 score increases from 75% to 84% and from 97% to 99%, respectively (Figure 4C). On the other hand, two tumor types experienced a drop in one of the metrics: CNS-PiloAstro (-0.4% precision) and Panc-Endocrine (-0.9% precision), likely due to an increase in Thy-AdenoCa donors misclassified as CNS-PiloAstro, and CNS-Oligo donors misclassified as Panc-Endocrine, possibly due to the low number of donors available for those tumor types (n=48 and n=18, respectively) (Supplementary Figure S16).

Open Access Repository of Simulated Cancer Genomes

In this study, in addition to the OncoGAN pipeline that can be used to generate an unlimited number of samples, we have generated and validated 800 highly realistic simulated cancer genome VCFs, representing a diverse set of tumor types. These VCFs are now publicly available for download and redistribution through our project repositories on HuggingFace (https://huggingface.co/datasets/anderdnavarro/OncoGAN-syntheticVCFs) and Zenodo (https://zenodo.org/records/13946727), with additional tumor types and features to be included in future releases as we continue to train and refine the models. Importantly, since VCF is a widely accepted standard for mutation calling files, these datasets can be easily integrated into existing range of bioinformatic tools, facilitating their adoption by researchers in the field.

Discussion

Here, we presented OncoGAN, a generative AI pipeline that leverages deep learning algorithms to simulate highly realistic synthetic cancer genomes. We have demonstrated that OncoGAN reproduces features found in various tumor types with a high level of similarity while also capturing the heterogeneity inherent in tumors. However, in some cases, OncoGAN did not fully simulate certain aspects, such as specific mutational signatures (e.g., SBS30 in Panc-Endocrine) or longer-range patterns in the distribution of mutation and signature counts (e.g., Liver-HCC). Despite this, this limitation affects only a very small percentage of the donors, meaning that the majority are simulated accurately, and it does not impact the other tumor types as the trained models are independent. This is further supported by DeepTumour, which correctly identifies the tumor type of origin for the majority of simulated donors. In fact, we demonstrated that using OncoGAN simulations to augment DeepTumour's training dataset improves the overall performance of the model.

We believe that these highly realistic synthetic cancer genomes can help address some of the current challenges in genomics, such as data accessibility[19–21], by promoting data sharing while protecting patient confidentiality[37]. Since synthetic genomes do not contain any patient-specific information, they can be open access and fully accessible to the research community. This approach aligns with initiatives like the Common Infrastructure for National Cohorts in Europe, Canada, and Africa (CINECA)[38] or the work by D'Amico et al.[39], which have synthesized cohort datasets containing phenotypic data. Moreover, data augmentation using synthetic genomes can help resolve class imbalance and small sample size issues[37,40], providing valuable resources for training new algorithms or improving existing ones, as demonstrated with DeepTumour. This approach has also been successfully applied in other fields, including medical image analysis[41], survival analysis[42,43] or single-cell data[44,45].

In recent years, several alternative approaches have been developed for the simulation of synthetic genomes, each employing one of three main strategies. BAMsurgeon[18], Xome-Blender[46], and SomatoSim[47] use a real sequencing alignment file (BAM) as input, add the alterations, and output the modified BAM along with a list of the incorporated mutations. In contrast, insiM[17] takes a similar approach by using a BAM file as input, but it outputs paired reads in FASTQ format. Finally, simuG[48] and Mutation-Simulator[49] use the reference genome in FASTA format as input, producing an altered FASTA file, which can then be converted into FASTQ reads using any read simulator, such as InSilicoSeq[50] or Sandy[51]. However, all of these tools primarily focus on integrating random mutations and/or more complex alterations, which do not accurately represent real tumor characteristics. In comparison, OncoGAN is the only method capable of simulating realistic mutational profiles specific to different tumor types, and can be integrated with any of the previous approaches to generate more realistic *in silico* sequencing files, enabling synthetic genomes to address more complex tasks.

Currently OncoGAN generates VCF files representing the position and allele frequency of each simulated mutation. In the future, we plan to extend this work to better capture low-frequency mutational signatures and extend its capabilities to simulate a broader range of tumor features, including indel signatures, copy number alterations and structural variants. Overall, it will allow us to create realistic simulated raw sequencing data for use in the sequence alignment, variant calling steps and mutational signatures discovery of cancer genome analysis.

In conclusion, OncoGAN represents a significant advance in the generation of synthetic cancer genomes. It offers a solution to current challenges in data accessibility and privacy while also serving as a powerful tool for enhancing algorithm development and benchmarking.

Methods

Data preprocessing

The original file used to extract all features for training the different models was the `final_consensus_passonly.snv_mnv_indel.icgc.public.maf.gz` (GRCh37) from the ICGC 25K data portal[3]. This file contains all final mutations detected by whole genome sequencing (WGS) for each donor across the 25 tumor types studied in the PCAWG. Twelve tumor types were discarded due to an insufficient number of samples for model training (<50 donors). From the remaining thirteen tumor types, we selected eight, ensuring a heterogeneous dataset based on factors such as the tumor mutational burden, the number of available donors and the tumor subtype. The selected studies were: Breast-AdenoCa, CNS-PiloAstro, Eso-AdenoCa, Kidney-RCC, Liver-HCC, Lymph-CLL, Panc-Endocrine and Prost-AdenoCa. For each mutation, we retained the following information: study (tumor type), donor ID, chromosome, position, length, type of mutation, reference and alternative bases, trinucleotide context and variant allele frequency.

Mutations were categorized into five groups: single nucleotide polymorphisms (SNPs; A > C), double nucleotide polymorphisms (DNPs; AA > CC), triple nucleotide polymorphisms (TNPs; AAA > CCC), insertions (INS; A > AA) and deletions (DEL; AA > A). Mutations without variant allele frequency were excluded.

To associate each SNP with its corresponding mutational signature (single base substitution; SBS) from the COSMIC catalogue (https://cancer.sanger.ac.uk/signatures/sbs/), individual variant call format files were extracted for each donor. SigProfiler[33] (v1.1.21) was then run, individually for each tumor type, using its default configuration except for the `--maximum_signatures` option, which was set to 8. The `De_Novo_MutationType_Probabilities.txt` file was used to sample the most probable signature each SNP belongs to, based on donor ID and mutational context. SBSs present in 5% or fewer (rounded) of donors were removed from the dataset, as more data would be required to accurately train the models.

Since categorical columns in tabular data are converted into one-hot encoding, we simplified the dataset by removing the chromosome column. Thus, positions were transformed into a continuous range along the genome (e.g., if chromosome 1's length is 1000, position 1 on chromosome 2 would be 1001).

The preprocessed file was then used to prepare the training files for all the models described below.

Model training

Detailed hyperparameters settings for all the models can be found in Supplementary Table S9.

Donor characteristics

Donor characteristics refer to the number and types of mutations and signatures present in each donor. To generate this dataset, we counted the number of each mutation type per donor, replacing SNPs with the assigned SBSs to avoid duplicating information in the training file.

We trained a separate model for each of the tumor types studied, using CTAB-GAN+[28] with 720 different hyperparameter combinations (epochs: 100 to 500 in increments of 20; batch size: 10 to 30 in increments of 5; learning rate: 0.001 to 0.01 in increments of 0.001). The best model or models were selected based on the similarity of scatter and density plots comparing the simulations to the original data. Due to the complexity of tumors (with varied relationships between mutational types and signatures), we combined different models and applied manual filters to improve the simulation of low-frequency mutational signatures.

Driver genes

Since OncoGAN randomly generates positions and trinucleotide contexts, the resulting mutations represent only passenger mutations. Therefore, OncoGAN cannot directly simulate driver mutations, as it lacks the biological information necessary for this task. To address this limitation, we first selected a list of driver genes published by PCAWG and available at the ICGC 25K data portal (`TableS1_compendium_mutational_drivers.xlsx`). We classified mutations in driver genes as either "coding" or "non-coding," creating a new ID (e.g., TP53_coding / TP53_intron). Driver IDs were filtered to include only those present in at least 5% of donors for coding mutations and 10% for non-coding mutations. The remaining mutations were used to create a database from which mutations could be drawn during the simulation.

However, driver IDs cannot be randomly selected, as some drivers are more common than others, and some tend to occur together or be mutually exclusive. To simulate these driver's intercorrelation, we trained a specific model. The training file for this model consisted of a count of how many driver mutations each donor had for each driver ID.

The same approach used for training donor characteristics models was applied here, with one model trained for each tumor type (CTAB-GAN+[28] with 720 hyperparameter combinations). The best models were manually selected based on the frequency of mutations for each driver ID and the correlation between driver's intercorrelations.

Variant allele frequency

Variant allele frequency was simulated using a straightforward approach since it is related to tumor purity and independent of the donor and mutation characteristics described above. First, we calculated the mean VAF for each donor and ranked them into 100 VAF bins (1% increments, from 0 to 1) to determine the percentage of donors that fall into each bin, independently for each tumor type. Then, within each of these ranks, we selected the mutations belonging to donors within each bin and further ranked them according to 40 VAF bins (2.5% VAF increments, from 0 to 1), to calculate the percentage of mutations in each bin. To simulate a donor, we first sample a mean donor VAF from the first file using the calculated probabilities and then sample mutation VAFs using the probabilities calculated in the second file for that specific mean donor VAF.

Genomic position

The genomic position of mutations is a variable with a very wide range, spanning from 1 to 3 billion base pairs (3Gbp), making it difficult for generative models to capture this variability. To address this, we performed a two-step discretization of the genome. First, we compressed the 3Gbp genome into 30Mbp (a 1:100 ratio) to reduce the complexity, as single-base resolution is not necessary for passenger mutations. Next, we divided the compressed genome into 105 bins of 0.3Mbp each, matching each mutation's position to its corresponding bin, discarding bins with fewer than two mutations. We then used the CTGAN[26] model to simulate new bins at the same frequency found in the original data. In the second step, we trained a small tabular variational

autoencoder (TVAE)[26] model independently for each bin, using the positions rather than the bins as input for the training. Finally, the simulated positions were expanded to the actual genome size. The use of both architectures is necessary because the GAN model better captures the overall frequency of the bins, but it is unable to accurately reproduce the specific mutation positions when working with a larger range.

Mutational signatures

To simulate the mutations, we prepared a training file containing the following features: position, length, VAF, reference and alternative contexts, and signature. The context is represented with individual bases in separate columns (r.ctx1, r.ctx2, r.ctx3, a.ctx1, a.ctx2, a.ctx3). Although we trained specific models for genomic position and VAF, we included these features in this training file as well, as they stabilized and improved model performance, preventing exploding issues in the gradient penalty during the GAN model's training phase.

We used a CTAB-GAN+[28] architecture for these models, defining the variables as follows: 'r.ctx1', 'r.ctx2', 'r.ctx3', 'a.ctx1', 'a.ctx2', 'a.ctx3', and 'signature' as categorical; length as a mixed type (with 0 representing "no indel" as a categorical value, >0 representing insertion size and <0 for deletion size); position as an integer; and VAF as a default float. Hyperparameters were selected based on tumor characteristics, with individual optimization for each tumor type. Batch size was set to the mean number of mutations per donor, the learning rate to 2e-4, and epochs ranged from 280 to 3200 to adapt the training time to an average of five days. The 'signature' variable was not simulated directly by the GAN model but was instead predicted by the auxiliary component of the CTAB-GAN+ model, based on the other simulated variables. This classifier was trained using a test ratio of 0.3. Since the goal of these models is to reproduce mutational signatures, the model's performance was tested by simulating donors and running SigProfiler to detect the simulated signatures. During the training phase, we experimented with different configurations and observed that the use of fewer epochs caused SigProfiler to detect new signatures (artifacts) not present in the catalog.

Quality control metrics

Donor characteristics

To assess the similarity between real and simulated populations, we calculated the histogram intersection distance for each type of mutation using the HistogramTools (v0.3.2) R package. First, we determined the number of each mutation type per donor. Then, we generated histograms for both the real and simulated datasets using the same bins (nbin = 10, spanning from the minimum to maximum values for each mutation type). Histogram counts were normalized by the total number of donors to make the histograms comparable. We calculated three different intersection distances to evaluate the differences between the populations: i) The histogram intersection distance between the PCAWG and OncoGAN datasets. ii) A bootstrap analysis (n = 1,000) for the above comparison to calculate confidence intervals. iii) A control analysis in which the PCAWG dataset was split into two random subgroups, and the intersection distance was calculated within

them (n = 1,000). The closer the intersection distance is to 0, the more similar the two populations are.

To compare the simulations not only to their corresponding real tumors but also to other tumor types, we calculated the histogram intersection distances across the eight studied tumor types. In this case, we used the total number of mutations per donor as the comparison metric. Using the minimum and maximum values across the eight tumor types, we defined 100 bin ranges to ensure consistency across all comparisons. We compared the PCAWG dataset against itself to determine the true relationship between the tumor types and then compared the OncoGAN dataset against PCAWG. For a more realistic comparison when calculating the intersection distance within the same tumor type for the PCAWG dataset (e.g., Breast-AdenoCa vs. Breast-AdenoCa), we randomly split the dataset into two subgroups and performed the intersection distance calculation 200 times, reporting the mean intersection distance. Finally, to evaluate the similarity between real and simulated distributions, we calculated the Pearson correlation.

Driver genes
To verify the accuracy of simulating driver gene co-occurrence, we calculated the percentage of donors harboring each possible 1-vs.-1 driver combination for both the real and simulated datasets. The four possible combinations were: i) neither driver was present; ii) only "driver A" was present; iii) only "driver B" was present; and iv) both drivers were present. Pearson correlation was then calculated independently for each of the eight studied tumor types, considering all combinations. The number of selected drivers and combinations can be found in Supplementary Figure S5 and Supplementary Table S3.

Variant allele frequency
To confirm that the mean variant allele frequency per donor was simulated according to the real distribution, we performed a two-sided Wilcoxon test comparing real and simulated donor VAFs independently for each tumor type. Additionally, a two-sided F-test was conducted to compare the variances of real and simulated populations.

Genomic position
To evaluate how accurately the locations of mutations were simulated according to patterns found in real tumors, we employed three approaches: i) The human genome was divided into 3,097 bins (1Mbp) and the percentage of mutations in each bin for both the real and simulated datasets was calculated. Pearson correlation was then estimated for each of the studied tumor types using these values. ii) A linear regression was performed to compare the PCAWG dataset against itself, and OncoGAN vs. PCAWG datasets to determine whether there were differences in the simulation of mutation positions between regions with lower or higher density of mutations, reporting the R^2 value. When comparing the same tumor type (e.g. Breast-AdenoCa vs. Breast-AdenoCa), we split the PCAWG dataset into two random subgroups and ran the linear regression 200 times, reporting the mean values. iii) Similar to our approach for comparing donor characteristics across different

tumor types, we assessed the similarity of the genomic pattern. Using the same mutation percentages by bin for each studied tumor type, we compared their similarity within the other tumors in the PCAWG dataset or between OncoGAN simulations and the PCAWG dataset, calculating Pearson correlations. Again, for the comparison of the same tumor type with itself, the dataset was randomly divided into two subgroups, and Pearson correlation was calculated 200 times, reporting the mean value.

Mutational signatures

To detect mutational signatures present in OncoGAN simulations, we employed the same preprocessing approach used for the PCAWG dataset, using SigProfiler (v1.1.21) with its default configuration, except the `--maximum_signatures` option was set to 8. Signatures were then manually compared to determine whether all expected signatures were simulated and to check for any new signatures or artifacts. We also compared the percentage of donors harboring the mutations with the corresponding percentages found in the real data. To investigate any discrepancies between what OncoGAN simulated and what SigProfiler detected, we visualized the percentage of mutations, both simulated and detected, associated with each signature for each donor. We explored the discrepancy for SBS30 in the Panc-Endocrine dataset by downloading the trinucleotide context usage pattern from COSMIC (https://cancer.sanger.ac.uk/signatures/sbs/sbs30/) and comparing it to the pattern in the PCAWG training file and the one generated by OncoGAN. Pearson correlations were calculated to assess the similarity between the patterns.

Indel distribution

To evaluate whether the distribution of indel sizes in the simulations closely matched that observed in the real data, we performed a Wilcoxon test between the two datasets for each indel size. For this analysis, we calculated the percentage that each indel length contributed to the total number of indels for each donor. The analysis was restricted to indels up to 5 nucleotides in length, as these account for an average of 88.5% of all indels.

Mutational consequences

The Docker version of the Ensembl Variant Effect Predictor tool (v.112)[34] was used to predict the effects of real and simulated mutations. The cache for the *Homo sapiens* GRCh37 version of the genome was downloaded from the Ensembl SFTP server (https://ftp.ensembl.org/pub/release-112/variation/indexed_vep_cache/), and results were obtained only for canonical transcripts using the following command: `vep --offline --format vcf --dir_cache /cache/ --force_overwrite --total_length --numbers --ccds --canonical --biotype --pick --no_stats --assembly GRCh37`. To enhance plot readability, Y axes were broken using the R package ggbreak (v.0.1.2)[52].

DeepTumour testing and training

DeepTumour is a fully connected feedforward deep neural network that in its latest version classifies 29 common cancer types based on mutation positional and context distributions (https://deeptumour.oicr.on.ca/)[35]. To generate the positional distributions, DeepTumour divides the genome into 2,897 bins (1Mbp) and counts the number of somatic mutations within each bin. Additionally, it calculates the distribution of 150 different mutation types in their single (e.g. C > G), dinucleotide (e.g. AC > AG), and trinucleotide contexts (e.g. ACA > AGA). The count for each mutation type is then normalized by the total number of SNVs in the sample and then transformed into z-scores for each feature. These positional and contextual mutation distributions result in a total of 3,047 features. We used this version of DeepTumour as a quality control tool to predict the tumor type of origin for our simulations, providing the predicted tumor type and the probability of the sample belonging to any other possible tumor types. To explain the Eso-AdenoCa results, we performed a PCA using the PCAtools (v.2.14.0) R package and the main donor characteristics (number of mutations for each type and mutational signature). For Lymph-MCLL, we compared their genomic position metrics with those from Lymph-BNHL.

To observe changes in DeepTumour's performance with simulated samples generated by OncoGAN, we trained a new model using the same architecture as for the baseline model. Originally for the baseline model, the 2016 release of 2,778 PCAWG data was filtered for tumor types with 18 or more samples, resulting in 29 cancer types. These samples were then split into 80% training data, 10% validation data, and 10% testing data, repeated five times since the model was trained following a 5-fold cross validation. Using each of the five training partitions, the model was trained with Adam50, employing a batch size of 32 for 400 epochs in PyTorch 1.9.1 with CUDA 10.2 support. Hyperparameter optimization was conducted by improving the model's performance on the corresponding split of validation data using the 'gp_minimize' function from the scikit-optimize 0.9.0 Python library. The new model was trained using a consistent approach, incorporating 100 additional simulated samples generated by OncoGAN for each tumor type studied in the original 80% of the training data. The code was written in Python 3.7.16.

To compare the performance of DeepTumour trained with simulated samples to the baseline model, we evaluated traditional performance metrics, including accuracy, precision, recall, and F1 score, independently using the corresponding test partitions. To calculate the overall accuracy, we calculated the proportion of correct classification. This metric is applied only when summarizing the performance of the classifier across all 29 tumor types. Recall was calculated as the proportion of samples from a specific cancer type that were correctly classified as that type, while precision measures the proportion of samples assigned to a particular type that truly belong to that type. The F1 score represents the harmonic mean of recall and precision. When reporting independent Lymph-MCLL and Lymph-UCLL metrics, Lymph-CLL donors and misclassified donors from other tumor types were divided based on the presence or absence of the SBS9 mutational signature, respectively.

Availability of data and materials

The OncoGAN software is publicly available on GitHub (https://github.com/LincolnSteinLab/oncoGAN) and DockerHub (https://hub.docker.com/r/oicr/oncogan) to enhance reproducibility. The training files, trained models, and the 800 simulated donors (VCFs) used in this paper have been uploaded to HuggingFace (https://huggingface.co/collections/anderdnavarro/oncogan-67110940dcbafe5f1aa2d524) and Zenodo (https://zenodo.org/records/13946727).

Acknowledgements

We thank Valli Subasri and Phil Fradkin for their useful suggestions. This work was performed using High Performance Computing resources from the Ontario Institute for Cancer Research.

Funding

D-N.A was supported by the Ontario Genomics-CANSSI Ontario Postdoctoral Fellowship program in Genome Data Science. Z.X, W.B and S.L were supported by funding from the Province of Ontario, Canada.

Contribution

D-N.A.: Conceptualization (equal); Data curation (lead); Formal analysis (lead); Investigation (lead); Methodology (lead); Project administration (equal); Software (lead); Visualization (lead); Writing – Original Draft Preparation (lead); Writing – Review & Editing (equal). Z.X.: Formal analysis (supporting); Methodology (supporting); Visualization (supporting); Writing – Original Draft Preparation (supporting); Writing – Review & Editing (supporting). J.W.: Formal analysis (supporting); Methodology (supporting). W.B.: Funding acquisition (supporting); Project administration (supporting); Supervision (supporting); Writing – Review & Editing (supporting). S.L.: Conceptualization (equal); Funding acquisition (lead); Project administration (equal); Resources (lead); Supervision (lead); Writing – Review & Editing (equal)

Bibliography

1. The International Cancer Genome Consortium. International network of cancer genome projects. *Nature* **464**, 993–998 (2010).

2. Cancer Genome Atlas Research Network *et al.* The Cancer Genome Atlas Pan-Cancer analysis project. *Nat. Genet.* **45**, 1113–1120 (2013).

3. ICGC/TCGA Pan-Cancer Analysis of Whole Genomes Consortium. Pan-cancer analysis of whole genomes. *Nature* **578**, 82–93 (2020).

4. Sosinsky, A. *et al.* Insights for precision oncology from the integration of genomic and clinical data of 13,880 tumors from the 100,000 Genomes Cancer Programme. *Nat. Med.* **30**, 279–289 (2024).

5. Priestley, P. *et al.* Pan-cancer whole-genome analyses of metastatic solid tumours. *Nature* **575**, 210–216 (2019).

6. Alexandrov, L. B. *et al.* The repertoire of mutational signatures in human cancer. *Nature* **578**, 94–101 (2020).

7. Li, Y. *et al.* Patterns of somatic structural variation in human cancer genomes. *Nature* **578**, 112–121 (2020).

8. Gerstung, M. *et al.* The evolutionary history of 2,658 cancers. *Nature* **578**, 122–128 (2020).

9. Jones, D. *et al.* cgpCaVEManWrapper: Simple Execution of CaVEMan in Order to Detect Somatic Single Nucleotide Variants in NGS Data. *Curr. Protoc. Bioinforma.* **56**, (2016).

10. Fan, Y. *et al.* MuSE: accounting for tumor heterogeneity using a sample-specific error model improves sensitivity and specificity in mutation calling from sequencing data. *Genome Biol.* **17**, 178 (2016).

11. Benjamin, D. *et al. Calling Somatic SNVs and Indels with Mutect2.* http://biorxiv.org/lookup/doi/10.1101/861054 (2019) doi:10.1101/861054.

12. Raine, K. M. *et al.* cgpPindel: Identifying Somatically Acquired Insertion and Deletion Events from Paired End Sequencing. *Curr. Protoc. Bioinforma.* **52**, 15.7.1-15.7.12 (2015).

13. Rimmer, A. *et al.* Integrating mapping-, assembly- and haplotype-based approaches for calling variants in clinical sequencing applications. *Nat. Genet.* **46**, 912–918 (2014).

14. Abaan, O. D. *et al.* The exomes of the NCI-60 panel: a genomic resource for cancer biology and systems pharmacology. *Cancer Res.* **73**, 4372–4382 (2013).

15. Park, E. S. *et al.* Integrative analysis of proteomic signatures, mutations, and drug responsiveness in the NCI 60 cancer cell line set. *Mol. Cancer Ther.* **9**, 257–267 (2010).

16. Zook, J. M. *et al.* Extensive sequencing of seven human genomes to characterize benchmark reference materials. *Sci. Data* **3**, 160025 (2016).

17. Patil, S. A., Mujacic, I., Ritterhouse, L. L., Segal, J. P. & Kadri, S. insiM. *J. Mol. Diagn.* **21**, 19–26 (2019).

18. ICGC-TCGA DREAM Somatic Mutation Calling Challenge participants *et al.* Combining tumor genome simulation with crowdsourcing to benchmark somatic single-nucleotide-variant detection. *Nat. Methods* **12**, 623–630 (2015).

19. Learned, K. *et al.* Barriers to accessing public cancer genomic data. *Sci. Data* **6**, 98 (2019).

20. Molnár-Gábor, F. *et al.* Bridging the European Data Sharing Divide in Genomic Science. *J. Med. Internet Res.* **24**, e37236 (2022).

21. Bonomi, L., Huang, Y. & Ohno-Machado, L. Privacy challenges and research opportunities for genomic data sharing. *Nat. Genet.* **52**, 646–654 (2020).

22. Goodfellow, I. J. *et al.* Generative Adversarial Networks. (2014) doi:10.48550/ARXIV.1406.2661.

23. Kingma, D. P. & Welling, M. Auto-Encoding Variational Bayes. Preprint at https://doi.org/10.48550/ARXIV.1312.6114 (2013).

24. Yelmen, B. *et al.* Deep convolutional and conditional neural networks for large-scale genomic data generation. *PLOS Comput. Biol.* **19**, e1011584 (2023).

25. Xu, L. & Veeramachaneni, K. Synthesizing Tabular Data using Generative Adversarial Networks. (2018) doi:10.48550/ARXIV.1811.11264.

26. Xu, L., Skoularidou, M., Cuesta-Infante, A. & Veeramachaneni, K. Modeling Tabular data using Conditional GAN. (2019) doi:10.48550/ARXIV.1907.00503.

27. Park, N. *et al.* Data Synthesis based on Generative Adversarial Networks. *Proc. VLDB Endow.* **11**, 1071–1083 (2018).

28. Zhao, Z., Kunar, A., Birke, R. & Chen, L. Y. CTAB-GAN+: Enhancing Tabular Data Synthesis. Preprint at http://arxiv.org/abs/2204.00401 (2022).

29. PCAWG Drivers and Functional Interpretation Working Group, PCAWG Consortium, Shuai, S., Gallinger, S. & Stein, L. Combined burden and functional impact tests for cancer driver discovery using DriverPower. *Nat. Commun.* **11**, 734 (2020).

30. Rheinbay, E. *et al.* Analyses of non-coding somatic drivers in 2,658 cancer whole genomes. *Nature* **578**, 102–111 (2020).

31. Polak, P. *et al.* Cell-of-origin chromatin organization shapes the mutational landscape of cancer. *Nature* **518**, 360–364 (2015).

32. Yaacov, A. *et al.* Cancer Mutational Processes Vary in Their Association with Replication Timing and Chromatin Accessibility. *Cancer Res.* **81**, 6106–6116 (2021).

33. Islam, S. M. A. *et al.* Uncovering novel mutational signatures by de novo extraction with SigProfilerExtractor. *Cell Genomics* **2**, 100179 (2022).

34. McLaren, W. *et al.* The Ensembl Variant Effect Predictor. *Genome Biol.* **17**, 122 (2016).

35. Jiao, W. *et al.* A deep learning system accurately classifies primary and metastatic cancers using passenger mutation patterns. *Nat. Commun.* **11**, 728 (2020).

36. Nadeu, F., Diaz-Navarro, A., Delgado, J., Puente, X. S. & Campo, E. Genomic and Epigenomic Alterations in Chronic Lymphocytic Leukemia. *Annu. Rev. Pathol.* **15**, 149–177 (2020).

37. Rajotte, J.-F. *et al.* Synthetic data as an enabler for machine learning applications in medicine. *iScience* **25**, 105331 (2022).

38. CINECA -Synthetic Cohort Datasets.

39. D'Amico, S. *et al.* Synthetic Data Generation by Artificial Intelligence to Accelerate Research and Precision Medicine in Hematology. *JCO Clin. Cancer Inform.* **7**, e2300021 (2023).

40. Nikolenko, S. I. Synthetic Data for Deep Learning. Preprint at https://doi.org/10.48550/ARXIV.1909.11512 (2019).

41. Yi, X., Walia, E. & Babyn, P. Generative adversarial network in medical imaging: A review. *Med. Image Anal.* **58**, 101552 (2019).

42. Kim, J. & Seok, J. ctGAN: combined transformation of gene expression and survival data with generative adversarial network. *Brief. Bioinform.* **25**, bbae325 (2024).

43. Guttà, C., Morhard, C. & Rehm, M. Applying a GAN-based classifier to improve transcriptome-based prognostication in breast cancer. *PLOS Comput. Biol.* **19**, e1011035 (2023).

44. Marouf, M. *et al.* Realistic in silico generation and augmentation of single-cell RNA-seq data using generative adversarial networks. *Nat. Commun.* **11**, 166 (2020).

45. Xu, Y. *et al.* scIGANs: single-cell RNA-seq imputation using generative adversarial networks. *Nucleic Acids Res.* **48**, e85–e85 (2020).

46. Semeraro, R., Orlandini, V. & Magi, A. Xome-Blender: A novel cancer genome simulator. *PLOS ONE* **13**, e0194472 (2018).

47. Hawari, M. A., Hong, C. S. & Biesecker, L. G. SomatoSim: precision simulation of somatic

single nucleotide variants. *BMC Bioinformatics* **22**, 109 (2021).

48. Yue, J.-X. & Liti, G. simuG: a general-purpose genome simulator. *Bioinformatics* **35**, 4442–4444 (2019).

49. Kühl, M. A., Stich, B. & Ries, D. C. Mutation-Simulator: fine-grained simulation of random mutations in any genome. *Bioinformatics* **37**, 568–569 (2021).

50. Gourlé, H., Karlsson-Lindsjö, O., Hayer, J. & Bongcam-Rudloff, E. Simulating Illumina metagenomic data with InSilicoSeq. *Bioinformatics* **35**, 521–522 (2019).

51. Miller, T. L. A. *et al. Sandy: A User-Friendly and Versatile NGS Simulator to Facilitate Sequencing Assay Design and Optimization*. http://biorxiv.org/lookup/doi/10.1101/2023.08.25.554791 (2023) doi:10.1101/2023.08.25.554791.

52. Xu, S. *et al.* Use ggbreak to Effectively Utilize Plotting Space to Deal With Large Datasets and Outliers. *Front. Genet.* **12**, 774846 (2021).

Supplementary Data

Supplementary Figure S1. Scatter and density plots comparing the number of specific mutation types to the total number of mutations for each donor, with real donors from PCAWG shown in orange, and simulated donors from OncoGAN shown in black. In all cases, the distributions are very similar, although there are minor challenges in simulating donors with very low mutational burdens in Eso-AdenoCa and Kidney-RCC tumor types.

Supplementary Figure S2. Violin plots illustrating the distribution of intersection distances between two randomly sampled populations from the PCAWG dataset (1000 interations) and the scores comparing OncoGAN simulations to the actual dataset. For most mutation and tumor types, the simulations correspond closely with the obtained results from comparisons between two subpopulations in the real data, indicating a high degree of similarity between the PCAWG and OncoGAN distributions. Lower scores indicate greater similarity between the populations.

Supplementary Figure S3. Comparative density and box plots showing donor's distributions of mean variant allele frequency (VAF) across eight tumor types. Each panel compares the VAFs from real samples (PCAWG) in orange and simulated samples (OncoGAN) in black. Notably, only the CNS-PiloAstro panel shows a statistically significant difference, which may not be biologically relevant as both distributions are very similar with median VAFs of 0.222 and 0.238, respectively. This underscores the accuracy of the OncoGAN simulations in reflecting real data. The Wilcoxon test was used to compare the groups.

Supplementary Figure S4. Density plots for the variant allele frequency (VAF) for each type of mutation and tumor. The densities are very similar between real (orange) and simulated (black) VAFs. The number of each type of mutation in each dataset is also reported. The greatest differences are observed in TNPs due to its low frequency.

Supplementary Figure S5. Driver correlation analysis plot for the seven tumor types. The X-axis shows all possible combinations between two driver genes, with each dot representing one 1-vs-1 combination. The Y-axis represents the percentage of donors in which that combination occurs. The number of drivers used and the total number of combinations are reported in the caption for each tumor type. The Pearson coefficient, with values exceeding 0.9 in almost all tumors, indicates a strong simulation of driver relationships. The data used to create this plot, including all possible driver combinations and their values, is listed in SuppTableS3.

Supplementary Figure S6. Histograms displaying the total percentage of mutations across the genome in 1Mb bins for the remaining seven tumor types. Real donors are shown in orange, and simulated ones in black, with differences highlighted in green. Pearson correlations between PCAWG and OncoGAN genomic profiles are provided for each specific plot.

Supplementary Figure S7. Scatter plot comparing the percentage of mutations in each 1Mb genomic region between two samples from the PCAWG dataset (left) and OncoGAN simulations against the entire PCAWG dataset (right) for each of the remaining tumor types. Each dot represents a region, with color indicating density; lighter colors mean higher densities. R^2 values are displayed for each of the comparisons.

Supplementary Figure S8. Pearson coefficients comparing the genomic positional pattern (percentage of mutations along the genome in 1Mb bins) of donors from each studied tumor type against all tumors available in the PCAWG dataset. For each tumor type (represented by a red dot/line), the left panel (PCAWG) illustrates the correlation when compared with the rest of the real tumors, while the right panel (OncoGAN) shows the comparison between its simulation and the real tumors. The Y-axis displays the order from the PCAWG panel. A blue dashed line indicates the mean Pearson coefficient. The correlation value displayed for the PCAWG dataset where the tumor type is compared against itself was calculated by comparing two different samples from the cohort (n=200). The similarity between the studied tumor and the rest of the tumors is consistent across both PCAWG and OncoGAN comparisons.

Supplementary Figure S9. Scatter and density plots comparing the number of specific signature mutations to the total number of mutations for each donor, with real donors from PCAWG shown in orange, and simulated donors from OncoGAN shown in black. OncoGAN values correspond to those directly simulated by the tool.

Supplementary Figure S10. Mutational signatures distributions detected by SigProfiler showing the number of somatic mutations per megabase and the percentage of donors exhibiting each signature for the remaining tumor types. Dots represent individual donors; the red line illustrates the mean number of somatic mutations per megabase. *SBS, single base substitutions*.

Supplementary Figure S11. Comparison of the mutational pattern for the SBS30 signature in the Eso-AdenoCa tumor type across the PCAWG, OncoGAN, and COSMIC datasets. A) For all trinucleotide contexts the percentage each specific context contributes to the signature. B) Focusing on the C>T context, as it is the predominant altered context in this signature.

Supplementary Figure S12. Comparison of the percentage of mutations directly simulated (OncoGAN, green) and detected (SigProfiler, blue) for each mutational signature across donors within the eight studied tumor types. Red dashed line indicates the lowest percentage of mutations detected by SigProfiler. *SNP: Single nucleotide polymorphism.*

Supplementary Figure S13. Boxplots comparing indel length distribution between PCAWG (orange) and OncoGAN (black). Negative X values represent deletions, and positive X values represent insertions. The Y-axis shows the contribution (%) of each specific indel length relative

to the total number of indels per donor. Only indels up to a size of 5 are plotted. The Wilcoxon test was used to compare the groups.

Supplementary Figure S14. Boxplots comparing the frequency of predicted effects for real (orange) and simulated (black) mutations per donor using the Variant Effect Predictor (VEP) tool. The X-axis lists the possible mutation consequences considered by VEP, while the Y-axis shows the percentage of mutations corresponding to each consequence per donor.

Supplementary Figure S15. Comparison of real Lymph-MCLL and Lymph-BNHL tumor types illustrating their similarity in terms of genomic mutation profiles. A) Histogram displaying the total percentage of mutations across the genome in 1Mb bins. Real donors are shown in orange, and simulated ones in black, with differences highlighted in green. The Pearson correlation is 0.941, indicating a high degree of similarity. B) Scatter plot comparing the percentage of mutations in each 1Mb genomic region between both tumor types. Each dot represents a region, with color indicating density; lighter colors indicate higher densities.

Supplementary Figure S16. DeepTumour heatmap displaying the accuracy of the baseline and the new classifier using a held-out portion of the PCAWG data set for evaluation (5-fold cross-validation). Baseline model was trained using only PCAWG samples, whereas the new model employs a mix of real and synthetic samples. Each row corresponds to the true tumor type and columns correspond to the class predictions emitted by DeepTumour. Cells are labeled with the percentage of donors of a particular type that were classified by DeepTumour as a particular type. The recall and precision of each classifier are shown in the color bars at the top and left sides of the matrix. All values represent the mean of 5 runs using selected data set partitions.

Supplementary Table S1. Mean intersection distances and confidence intervals for the distribution of number of mutations, comparing PCAWG (Sampled population 1 vs. Sampled population 2) with OncoGAN (OncoGAN vs. PCAWG) donors.

Supplementary Table S2. Results of Wilcoxon and F-tests comparing the distributions of donor variant allele frequencies and the equality of their variances (PCAWG vs. OncoGAN).

Supplementary Table S3. Driver correlation analysis table displaying the percentage of donors that carry each combination of driver mutations.

Supplementary Table S4. Linear regression results showing the R^2 for comparisons between two samples from the PCAWG dataset (n=200) and OncoGAN simulations versus the PCAWG regarding the percentage of mutations distributed across the genome (1Mb bin size).

Supplementary Table S5. Pearson coefficients with their confidence intervals comparing the genomic positional pattern (percentage of mutations along the genome in 1Mb bins) of donors

from each studied tumor type against all tumors available in the PCAWG dataset for both PCAWG and OncoGAN datasets. The correlation value displayed for the PCAWG dataset where the tumor type is compared against itself was calculated by comparing two different samples from the cohort (n=200).

Supplementary Table S6. For each type of cancer and mutational signature, the number of donors for which the specific signature was simulated by OncoGAN and the number of donors in which the signature was detected using SigProfiler.

Supplementary Table S7. Pearson coefficients representing the correlation between the percentages of each mutational signature simulated (OncoGAN) and those detected (SigProfiler) in simulated donors. *study_error* indicates the discrepancy between the number of donors that were intended to be simulated with a specific mutational signature and those actually detected.

Supplementary Table S8. DeepTumour baseline model predictions for the OncoGAN dataset and 5-fold cross-validation results for the PCAWG dataset.

Supplementary Table S9. List of hyperparameters used to train the models.