Moving towards more holistic machine learning-based approaches for classification

problems in animal studies

Authors: Charlotte Christensen+[1,2,3], André C. Ferreira+[1], Wismer Cherono[2], Maria

Maximiadi[4], Brendah Nyaguthii[2,5], Mina Ogino[1,2,3], Daniel Herrera C[1], Damien R.

Farine[1,3,5,6]

1. University of Zurich, Department of Evolutionary Biology and Environmental Studies,

Winterthurerstrasse 190, 8057 Zurich, Switzerland

2. Mpala Research Centre, P.O. Box 555, Nanyuki 10400, Kenya

3. Max Planck Institute for Animal Behavior, Am Obsterberg, Radolfzell 78315,

Germany

4. University of Patras, Department of Biology, Panepistimioupoli Rio, Patras, GR

26500, Greece

5. National Museums of Kenya, Museum Hill, Nairobi, Kenya.

6. Australian National University, Research School of Biology, 134 Linnaeus Way, Acton

ACT 2601, Australia

*+ joint-first authors

ORCID

CC: 0000-0001-7697-9903

ACF: 0000-0002-0454-1053

BN: 0000-0002-5716-0684

MO: 0000-0002-3780-2942

DRF: 0000-0003-2208-7613

Corresponding authors:

CC: charlotte.christensen@uzh.ch

ACF: andre.marquescondecoferreira@uzh.ch

DRF: damien.farine@anu.edu.au

Conflict of interest statement

The authors declare no conflicts of interest.

Authors contribution

CC, ACF and DRF conceptualised the study. CC and BN led the data collection of the accelerometer and video data in the field. CC wrote the ethogram and CC, WC and MM annotated the videos. DH corrected the time alignment between annotation and video data. CC trained the random forest model and performed the statistical analyses for the inter-observer agreement and the biological validations. DRF conducted the simulations. ACF collected the data and trained the deep learning models for the worked example in the Supplementary material. MO conducted the food supplementation experiment for one of the biological validations. CC and ACF wrote the first draft of the manuscript with the input of DRF. All authors read, improved and approved the final version of the manuscript.

Acknowledgements

We would like to thank the Vulturine Guineafowl Research Programme field team: Monicah Wambui, Kennedy Kipkorir, John Wanjala and Mary Waithira Ngugi for their work in deploying tags, downloading biologging data and collecting videos that were annotated for model training. We would like to thank Mpala Research Centre for logistical support and allowing us to work on the conservancy. We would like to thank National Museums of Kenya (NMK), the National Commission for Science, Technology and Innovation (NACOSTI) and the Wildlife Research and Training Institute (WRTI) for approval of our work. CC and ACF were funded by European Research Council (grant agreement no. 850859 awarded to DRF). CC was supported by a UZH post doc grant (no. K-74312-02-01). MO received additional funding from the Swiss Federal Commission for Scholarships. DRF was funded by an Eccellenza Professorship Grant of the Swiss National Science Foundation (Grant Number PCEFP3_187058).

Statement of inclusion

Our study brings together authors from a number of different countries, including scientists based in the country where the study was carried out.

Data availability

Data and code will be made available on Figshare once the manuscript is accepted for publication.

Abstract

Machine-learning (ML) is revolutionizing field and laboratory studies of animals. However, a challenge when deploying ML for classification tasks is ensuring the models are reliable. Currently, we evaluate models using performance metrics (e.g., precision, recall, F1), but these can overlook the ultimate aim, which is not the outputs themselves (e.g. detected species or individual identities, or behaviour) but their incorporation for hypothesis testing. As improving performance metrics has diminishing returns, particularly when data are inherently noisy (as human-labelled, animal-based data often are), researchers are faced with the conundrum of investing more time in maximising metrics versus doing the actual research. This raises the question: how much noise can we accept in ML models? Here, we start by describing an under-reported factor that can cause metrics to underestimate model performance. Specifically, ambiguity between categories or mistakes in labelling validation data produces hard ceilings that limit performance metrics. This likely widespread issue means that many models could be performing better than their metrics suggest. Next, we argue and show that imperfect models (e.g. low F1 scores) can still be useable. Using a case study on ML-identified behaviour from vulturine guineafowl accelerometer data, we first propose a simulation framework to evaluate robustness of hypothesis testing using models that make classification errors. Second, we show how to determine the utility of a model by supplementing existing performance metrics with 'biological validations'. This involves applying ML models to unlabelled data and using the models' outputs to test hypotheses for which we can anticipate the outcome. Together, we show that effects sizes and expected biological patterns can be detected even when performance metrics are relatively low (e.g., F1: 60-70%). In doing so, we provide a roadmap for validation approaches of ML classification models tailored to research in animal behaviour, and other fields with noisy, biological data.

Keywords

Hypothesis testing; Machine learning; Model training and evaluation; Performance.

Highlights

1. **Evaluating machine learning (ML) models must go beyond performance metrics**

2. **Mislabels in validation data leads to underestimation of model's performance**
3. **Underestimated metrics can cause research delays despite models being useful**
4. **We propose simulations and biological validations to evaluate model performance**
5. **Models with low standard metrics can still be powerful for hypothesis testing**

Introduction

Advances in technology have dramatically enhanced our capacity to gather data on animals (Kays *et al.* 2015; Caravaggi *et al.* 2017), giving us insight into where animals go (e.g., GPS: Cagnacci *et al.* 2010), what they are doing (e.g., tri-axial accelerometers: Brown *et al.* 2013) and with whom they interact with (e.g., proximity tags: Ryder *et al.* 2012). This drastic increase in data collection has also been accompanied with advances in computer science, namely in machine learning (ML), allowing us to process, categorise and analyse large amounts of complex data. For example, ML has been used to classify species of animals from millions of pictures from camera traps in a fraction of the time of a human performing the same task (Willi *et al.* 2019; Norouzzadeh *et al.* 2021; Whytock *et al.* 2021). Similarly ML-based classification has been used to identify individuals (Schneider, Taylor & Kremer 2022), detect behavioural states (Riaboff *et al.* 2022; Aulsebrook, Jacques-Hamilton & Kempenaers 2024) and capture social associations (Valletta *et al.* 2017; Smith & Pinter-Wollman 2021), tremendously increasing the data available to address fundamental questions in behavioural ecology. ML is particularly powerful in the context of data collection as it allows us to solve classification tasks that turn raw data into interpretable data for posterior hypothesis testing. For instance, in a study on flatback turtles (*Natator depressus*), multi-sensor data from tags was classified into distinct behaviours, including foraging. These foraging predictions were then used in a regression model to show how turtles feed more at high tide to access intertidal food resources (Hounslow *et al.* 2023). Nevertheless, for all the published studies that successfully used ML models for classification problems, there are potentially many others where low model performance (e.g. low F1 scores) made the results less

appealing for publication. This has likely driven a publication bias comprising of artificially high model performance and an over-optimism about ML performance (e.g., Jennions & Moeller 2002; Saidi, Dasarathy & Berisha 2024), as well as substantial loss of research time seeking high model performance that seems unattainable.

Low scores on performance metrics (see: Rainio, Teuho & Klén 2024 for a review on commonly used evaluation metrics) understandably lead researchers to invest in a time-consuming process of ML model refinements before getting to hypothesis testing. These refinements can include trying different hyper-parameters, model architectures, or collecting additional training data. However, the improvements yielded through what is effectively trial-and-error exploration are typically marginal (Probst, Boulesteix & Bischl 2019; Sipper 2022). Increasing the training dataset is usually the most effective way of improving models' performance, which can motivate a large time and/or financial investment. Collecting more data is, however, often not viable either due to the data collection period being limited in space and time (e.g., within a delineated field season: Shuert, Pomeroy & Twiss 2018; Christensen *et al.* 2023) or because certain biological phenomena or species are hard to observe making it challenging to collect more data (Hounslow *et al.* 2019; Zhong *et al.* 2021). Moreover, even if more data are collected, the collation and annotation of training data is time and resource intensive (e.g., labelling photos of animals with the species names: Norouzzadeh *et al.* 2021; or labelling hours video second-by-second: Christensen et al., 2023). Improving model performance can therefore be a frustrating and time-consuming endeavour.

We propose that more effective use of researcher time can be achieved by better understanding the sources of model (apparent) errors, how classification errors made by the model affect (or not) posterior hypothesis testing, and how models perform when deployed to realistic empirical tests. When comparing different methods and tweaking parameters fails to make the desired improvements, poor model performance is typically ascribed to insufficient or non-representative training data or to high class similarity (e.g., being groomed while sitting, lying or standing: Christensen *et al.* 2023). In some cases, categories that are being misclassified for one another may be merged into broader categories (Ladds *et al.* 2017) without jeopardizing the initial hypotheses (e.g., if the act of being groomed rather than postural data is of importance: Christensen *et al.* 2023). However, the true blame for (apparent) low

performance may not lie solely at the feet of incomplete training data or the similarity of different classes, but rather in the assumptions about our training data. While ML models are often used to aid data collection by categorising large and highly dimensional datasets into distinct categories, data are often naturally continuous. For example, classifying behaviours is especially challenging because these often include transitional states (Reyes-Ortiz *et al.* 2016; Riaboff *et al.* 2022), such as switching from feeding to moving, making it hard to delineate exactly when in time the change occurred. Subtle differences between seemingly similar categories (e.g. an animal having different intentions when raising its head for predator vigilance versus looking for the next food patch) can also make labelling ambiguous, even for experienced observers. The inherent ambiguity and noise associated with biological systems naturally introduce inaccuracies in the labelled data used to train and (importantly) evaluate ML models.

Inaccuracies in the labelling process represent an under-appreciated challenge for our ability to evaluate classification models. While it may seem logical that inaccuracies limit models from achieving maximal performance because the models have to learn from data with errors, it appears that ML models can be resilient to some mislabels (Rolnick *et al.* 2017; see also Supplementary material). Instead, what has been almost completely overlooked is that mislabels during the training process hinder our ability to *evaluate* model performance, rather than limiting the true performance of the model. This is because a model that predicts a correct label will still get penalised (i.e. reported performance in terms of accuracy, recall, F1 score, etc.) when human-assigned labels in the validation set contain errors (see Supplementary material for a worked example). Errors in the labelling, which are common in biological data, can therefore make it impossible for models to achieve perfect performance metric scores during evaluation, even if they are in fact performing very well. Thus, accurately determining a model's performance can and should go beyond simply relying on performance metrics.

Even when models demonstrate genuine underperformance, this should not automatically preclude their application to animal data. Contrary to computer scientists that are motivated to push the boundaries of the state of the art in ML by maximizing model performance (Birhane *et al.* 2022), biologists are primarily interested in using ML models as a tool to facilitate data processing and ultimately test biologically

relevant hypotheses (Hilborn & Mangel 2013). In ecology and evolution, (statistical)

model performance is typically evaluated in terms of its ability to provide robust tests

of hypotheses (and estimating corresponding overall effect sizes), with much less

emphasis put on the ability of models to make predictions for specific data points

(Houlahan *et al.* 2017). Because of the noisy nature of biological data, our hypothesis

testing tools, e.g., linear regression models (Bolker *et al.* 2009) or Bayesian inference

(Ellison 2004), are already built to handle (random) errors in our data (Young 2018).

Our ability to statistically account for noise (in this case errors in prediction) pulls into

question whether—in the context of biological hypotheses testing—performance

metric maximization (e.g. maximizing F1 scores) is a useful pursuit, or whether there

are more informative ways of deciding when we should stop the training process and

move towards model deployment for hypothesis testing. Here we argue that while

current performance metrics are useful during model training and to compare different

approaches, biologists should look beyond pure metric maximization. Instead, we

should ask whether a model is able to perform well enough to confront the biological

hypotheses of interest with the data that the model predicted.

In this paper, we outline new perspectives and solutions on how to assess ML model

performance when classifying data for the purpose of posterior hypothesis testing. As

a case study, we focus on the identification of behaviour from accelerometer (ACC)

data collected on a free-ranging population of vulturine guineafowl (*Acryllium*

vulturinum). Combining ACC data with ML approaches to infer behaviour is a powerful

way of determining the behaviour of animals without the need to observe them directly.

We first use a popular ML approach (random forest models) to classify behaviours

using labels assigned from videos. To better understand sources of error and how

these affect model performance metrics we compare the behavioural labels from

different annotators. Annotator disagreement indicates one source of error in the

evaluation process that can result in the underestimation of the performance of the

model for some behaviours (see Supplementary material for a worked example).

Our models, like most classification models, still produce a number of prediction

mistakes that could not be directly attributed to mislabels in the validation dataset. We

therefore also investigate whether we can still use our model to test our biological

hypotheses of interest. First, we develop a simulation framework to evaluate whether

the classification from an imperfect model can still generate useful data for hypothesis

testing. In doing so, we shift the focus from model performance metrics to the contribution that the model makes towards detecting true biological effects. We highlight that this is critical for studies in the biological sciences because prediction errors will have different impacts depending on the hypothesis that is being tested. Finally, to confirm the utility of ML models, we propose an additional 'biological validation' procedure that uses model predictions on unlabelled data to test simple hypotheses that we know *a priori* to be supported in our study system (see also: Brewster *et al.* 2018; Wang 2019; Rast *et al.* 2020; Giese *et al.* 2021; Lok *et al.* 2023; Aulsebrook, Jacques-Hamilton & Kempenaers 2024) for other studies that used biological validations). In this way, we can evaluate the model's ability to predict data to test biological relevant questions before using it to test the hypothesis of interest (see: Ferreira *et al.* 2020a for a similar approach in social network analyses).

Case study methods

Collecting, labelling, and matching video data with ACC data

We use data from a population of vulturine guineafowl that are part of a long-term project at the Mpala Research Centre, Laikipia, Kenya. Birds are fitted with solar-powered GPS and accelerometer tags (15 g Bird Solar, e-obs Digital Telemetry, Grünwald, Germany, for more details see: Papageorgiou *et al.* 2021; He *et al.* 2022) which can be remotely re-programmed to collect accelerometer and GPS data (see Table S1 for details on ACC birds). Videos of n=14 birds (individually recognisable from unique colour bands) were collected (using Panasonic HC-V777) in the field from a stationary car. At the start of the video, the date and exact GPS-time stamp were filmed to time-match the video with the ACC data. Videos were annotated by two trained observers (co-authors: *name 2 redacted*, *name 3 redacted*) using the ELAN software (version 6.4) following an agreed upon Ethogram (Table S2). The ethogram consisted of four modes of locomotion (walking, trotting, running, flying), two modes of foraging (pecking at ground, nipping at foliage), two modes of self-directed care (preening and dustbathing), resting (seated, lying or in combination with preening or pecking), and standing alert. Note that vulturine guineafowl are almost entirely terrestrial, flying only rarely. Event behaviours (e.g., social interactions) and transitions

between behaviours were categorised as 'other' during the video annotations. We
annotated 13.4 hours of video (n=258 videos).

We conducted all data processing and analyses in R (version 4.1.1; R studio
2024.04.2). After merging accelerometer data to video data using the timestamp, we
visually confirmed alignment of labels and corrected misaligned labels (example of
accelerometer data and label alignment: Figure S1). Some videos (n=18) did not have
distinct enough accelerometer profiles to confidently confirm or correct the alignment
between ACC data and annotations, and these were removed from the training and
validation data. These removals, together with periods where no bird was present in
the video (1.5 hours) resulted in a dataset of 11.9 hours across the 14 birds. Annotated
behaviours were merged into biologically similar categories or into a category called
'other' if behaviours were rare (drinking, social interactions) or not of interest
(transitions) (Figure S2). This resulted in 7 behaviours for training the random forest
model (Table S3 for sample sizes). After matching annotated video data to 1Hz ACC
data (see below), seconds that included more than one annotation were assigned the
category that took up the larger proportion of that second.

Metric calculation and random forest model fitting

We summarised each second of 20 Hz ACC data into 1 Hz data with 14 variables:
static acceleration (Xst, Yst, Zst), dynamic acceleration (dyX, dyY, dyZ), raw VeDBA,
smoothed VeDBA using a running mean of 2 seconds, and the first and second power
spectrum densities for all three axes using Fast-Fourier transformation also at an
interval of 2 seconds (adapted from: Fehlmann *et al.* 2017; Christensen *et al.* 2023).
The random forest models were built the R package 'randomForest' using the default
setting of n=500 trees and mtry=3.

We ran a random forest model with seven behaviours (Table S3). We trained the
random forest model using a leave-one-individual-out (LOIO) approach (Chakravarty
et al. 2019). This approach avoids overestimating model's performance, which
originates from autocorrelation between the training and validation data (by having
data from the same individuals in both training and validation datasets) and gives a
more accurate reflection of the performance of the model when generalised to data
from birds that were not included in the original training dataset (Ferdinandy *et al.*
2020). During the validation procedure, for the models in which two behaviours took

place within the same second, the prediction would be labelled as 'correct' as long as
it corresponded to one of those two behaviours. We then calculated a confusion matrix
was produced (Table S4) and precision, recall and F1 scores, using the standard
formulas (see Supplementary material). Finally, we trained a random forest model
containing all of the labelled data to allow us to classify behaviours from new data (see
'*Biological validation can directly test the utility of imperfect models*').

Figure 1: **Evaluation of the performance of random forest model using standard**
evaluation metrics is capped by mislabels during the training process (a)
Precision and recall for 7 behaviours. (b) Correlation between the F1-scores of the
annotators (i.e., inter-observer agreement) and the model F1-scores (note axes start
at 0.4, rather than 0.0 for easier visualisation)

Inter-observer disagreement illustrates imperfections in labelled data

The reliance of human labelling—the current 'gold standard' (Culverhouse *et al.* 2003;
Hooge *et al.* 2018; Mannix *et al.* 2021) —has largely overlooked the issue of ambiguity

and errors when creating the 'ground truthed' classification data, at least in ecology (but see examples from computer science: Sheng, Provost & Ipeirotis 2008; Yan *et al.* 2014). Here, we quantify inter-observer disagreement (mislabels) to illustrate why labelling errors create a 'cap' on our model performance metrics, leading us to potentially underestimate the true performance of our models. To estimate inter-observer disagreement, we used data from 62 minutes of video encompassing all 7 behaviours that were labelled by the person who wrote the ethogram (*name 1 redacted*) and one of the two trained observers (*name 2 redacted* and *name 3 redacted*). We built a confusion matrix (Supplementary Material) and calculated F1 scores with the labels from *name 1 redacted* considered as the "ground truth". As expected, we found substantive disagreement—14.7% of the labels—between annotators (Table 1) despite all following the same ethogram (Table S2) and being trained by the same person with whom their data were compared. We might predict that behaviours with lower inter-observer agreement (as a proxy for mislabels) are more difficult to classify due to errors in the training and validation datasets. Indeed, we find a moderate positive correlation (0.57) between F1 score and the agreement between observers (Fig 1; Table 1). However, mislabels does not completely explain some low F1 scores, particularly for behaviours with relatively high concordance (e.g. 'Preening' has the highest concordance but only ranks 4th on the model's F1 scores; Table 1). Such low performance can be a result of low sample size or because some behaviours that are easily distinguished on video can generate very similar streams of accelerometer data (Shuert, Pomeroy & Twiss 2018; Chambers *et al.* 2021). Further, we find that both annotator disagreement and model error are class dependent (some classes are never confused, and almost all confusions occur among a limited set of classes; Table S4 and Table S5). We expect that such errors will be almost uniformly distributed in studies that classify animal-based data (especially behaviours), and that this could result in substantial under-estimations of true model performance (see Supplementary material for a worked example) and utility for hypothesis testing.

Table 1. Labelling errors correlate moderately with the performance of ML models. Precision (model ability to minimize false positives), Recall (model ability to minimize false negatives) and F1 score (the harmonic mean of Precision and Recall)

345   of the random forest model, and F1 score for annotators (as a measure of inter-

346   observer agreement). Macro F1 is the average F1 score across all 7 categories.

	Precision	Recall	F1 (model)	F1 (annotators)
Alert	68.3	71.8	70.0	78.5
Feeding	81.9	85.2	83.5	95.4
Locomoting	63.2	65.0	63.9	82.4
Other	48.4	53.7	50.9	64.4
Preening	69.3	68.9	69.1	98.1
Searching	66.5	56.7	61.2	84.6
Sitting	85.1	72.8	78.4	93.7
Macro F1			**68.1**	**85.3**

Imperfect models can still be powerful for hypothesis testing

Our end goal when using ML is often not the predictions themselves, but rather to use

these predictions for hypothesis testing (e.g., using the categorised behaviours as a

response variable in a regression). In this section, we develop a simulation framework

that allows us to test the utility of ML models for hypothesis testing—specifically

determining the ability to detect a given effect size, and rates of resulting false-

positives and false-negatives, using a statistical model fitted to data containing

imperfect predictions. We start by generating an observed second-by-second

behaviour dataset that spans 10 days (collecting 7200 samples per day, e.g. 2 hours

of 1 Hz accelerometer data). For each simulated second, we allocate a behaviour

using the real probabilities of these behaviours taking place (based on the prevalence

in the labelled guineafowl dataset), and then generate inferred behaviours by sampling

from the confusion matrix (i.e. the probability that the real behaviour is inferred as each

of the other behaviours) from the random forest model (Table S4). For the purpose of

this simulation, we considered that the confusion matrix is not influenced by annotator

disagreement in the labels (i.e. it represents "ground-truth" confusion matrix). To create a biological effect, we alter the frequency at which a specific behaviour was expressed during five of the days (e.g. increasing 'searching' from one time period to another by between 0 to 20% of the time budget in increments of 1.25% while reducing all other behaviours proportionately). We repeat this process 100 times for each effect size. For each study (a simulated 'observed' dataset), we regress the rate of the focal behaviour against treatment (period 1 vs period 2) and report the true effect (i.e. the effect size from the simulated data) and the observed effect (i.e. the effect size after classification error is introduced using the confusion matrix), as well as the P value for each model. Because misclassifications are non-randomly distributed, we expect that one possible source of false positives would be in a behaviour that is commonly mistaken with the observed behaviour (e.g. in the case of 'searching' the most commonly confused behaviour is 'locomoting'; Fig. 2e). Thus, for each study we also calculated the effect on the behaviour that is most commonly mistaken with the behaviour of interest (Fig. 2; Table 2 for 'searching'; Table S6 for remaining behaviours). We predict that misclassifications would lead the to an underestimation of the focal behaviour and that this could lead to an overestimation of the most commonly confused behaviour(s).

Figure 2. **Behaviours that are increased in a dataset ('simulated change') can be detected despite classification error ('detected change').** As the simulated

frequency of a behaviour is increased (0.0 to 0.2 in increments of 0.0125; x-axis) so

does the inferred rate of that behaviour from the model (y-axis, black lines and points).

We find that while the frequency is underestimated, we detect no positive increase in

the most frequently confused behaviour (red lines and points). Silhouettes by [name

redacted].

Table 2. Imperfect ML models can be used to make robust biological inferences.

Results from simulation where the propensity of 'searching' (true behaviour) is

increased between two periods in the data by a given amount (simulated change, see

Fig. 2e). Detected mean change captures the mean of the change between the two

periods over all 100 simulated studies. Proportion of P < 0.05 is the proportion of the

simulated studies that detected a statistically significant change. Detected mean

change captures the mean change detected between the two periods over 100

simulations. Note that the propensity of 'locomoting' (confused behaviour) decreased

(along with other behaviours identified in the model) to accommodate increase in

'searching' because the overall time available for all behaviours stays fixed, and this

decrease was also detected by the model fitted to the confused data. Results for the

other behaviours are presented in the Supplementary Material (Table S6).

Simulated change	Detected mean change	Proportion of *P* < 0.05	Detected mean change	Proportion of *P* < 0.05
	Searching (true behaviour)		*Locomoting (confused behaviour)*	
0	<0.001	0.1	<0.001	0
0.0125	0.008	0.7	<0.001	0
0.025	0.015	1.0	<0.001	0
0.05	0.027	1.0	-0.001	0
0.075	0.045	1.0	-0.003	0.1
0.01	0.06	1.0	-0.002	0.0
0.125	0.073	1.0	-0.004	0.1

0.15	0.088	1.0	-0.003	0.4
0.175	0.104	1.0	-0.005	0.4
0.2	0.118	1.0	-0.007	0.9

Our simulations show that although models produce classification errors when
predicting data (in our case behaviours), the data predicted from these models can
still contribute to robust biological hypothesis testing when using regressions to
account for error (Table 2; Table S6; Fig. 2). We found that even small changes in
behaviour can be reliably detected (i.e. high rates of significant models). Importantly,
the behaviour most commonly confused with 'searching' (i.e., 'locomoting') does not
increase meaningfully as 'searching' increases (effect sizes remain 1-2 orders of
magnitude smaller than those of the real effect), suggesting that biased
misclassifications (in our example) should not be expected to be a high source of false
positives. Misclassified behaviours instead show a slight decrease, corresponding with
the reduced time spent to make way for an increase in the focal behaviour. Further,
models with no effect (simulated change = 0) also have low rates of false positives
(rates of significant models is <0.1). Finally, it is worth noting that classification errors
can result in underestimates of the true effect size for behaviours with low F1 scores
(e.g., searching F1 = 61.2; Table 1). From our simulations, we conclude that while
imperfect models can be useful, reporting the results of models should consider the
relative strengths of the effects detected or report expected effect sizes beforehand
that would be considered biologically meaningful (Steidl & Thomas 2001). This is a
common issue in the era of big data, as very small effects can be highly significant
simply because of large datasets, which is one reason for P values being unreliable
(Greenland *et al.* 2016; Colquhoun 2017).

Biological validation can directly test the utility of imperfect models

One major challenge for applications of ML in ecology and evolution is the general
necessity to apply models to data collected outside of the scope of the training data.

For example, we may fit accelerometer tags to new individuals during the study, use data collected after the training period has ended, or test hypotheses on data collected in different locations to those where we collected the training data. Few studies on wild animals have quantified the validity of using data collected outside of the scope of the training data (but see: Wang *et al.* 2015; Brewster *et al.* 2018; Giese *et al.* 2021; Christensen *et al.* 2023). Here we propose an approach that can both (i) test if a model allows for the identification of biologically sound patterns in true field conditions (i.e. extending the validation beyond simulation presented above), and (ii) test if a model is likely to remain useful once applied to unseen data (i.e. good generalizability). Our approach is based on biological validation, i.e., confirming that the data can identify effects known *a priori* to exist. For example, walking long distances is (in most animals) incompatible with long periods of resting or foraging. We should also expect higher rates of foraging behaviours in areas where food is abundant compared to, for example, roosting areas as animals respond to the resources in the landscape. Here we illustrate the concept of biological validation for ML models by developing four cases in which we test a "simple" hypothesis (with a known outcome) as a means of examining the performance of a model at addressing a real biological problem. While these "simple" hypotheses and *a priori* knowledge will always be species and context specific, some or all of the examples proposed here could easily be adapted to most study systems. We also note that not all behaviours may have a suitable "simple test" and that this may lead to issues of 'coverage' (Pei *et al.* 2017), which means not all branches of a model may be biologically validated (e.g., we have no clear prediction for the category 'Other' in our case study). However, we cover the behaviours of interest (i.e., that will be used to test hypotheses in future studies).

Biological validation 1: vulturine guineafowl spend more time foraging in proximity to food supplements

To test the detection of feeding versus searching behaviours (Table S4), we take advantage of food supplementation that was available to the population between 3rd June and 12th July 2023 as part of another experiment in this population. Small patches of distributed millet grain (5 by 5 meters) were visited by vulturine guineafowl early in the morning. We expect that feeding behaviour should be detected more frequently in

close proximity to a patch. By contrast, the easily-confounded searching behaviour (associated with slow-paced walking and scanning the ground for food) should not increase in these areas. It might even decrease, as animals have limited time (Dunbar, Korstjens & Lehmann 2009) and if they increase feeding, other behaviours should decrease. For n=8 birds, we extracted the GPS data from 06:00 to 07:30 and calculated the proximity to a foraging patch (< 15 m or > 15 m). We then use generalized linear mixed effect models (R package 'lmerTest') with 'proportion behaviour per minute' fit as a binomial response variable and proximity (< 15 or > 15 m) as a categorical fixed effect, and 'bird ID' and 'Date' as random effects. Of the total 429 hours of GPS data that satisfied the time criteria, 38 hours were within 15 m of the foraging patch with the remaining (391 hours) being outside the 15 m perimeter. The results (Table 3; Fig. 3a) confirm that guineafowl in closer proximity to the millet patch spend more time foraging. By contrast, there are very small (and negative) changes in searching behaviour.

Table 3. Biological validation demonstrating that the random forest model can detect an increase in foraging close to a known food patch. Results of a generalized linear mixed model on the inferred proportion of time spent (a) feeding and (b) searching when in proximity (<15 m) of a known food patch relative to the baseline (>15 m). Data for 8 birds across 41 unique dates with 25747 1-minute blocks.

Predictor	Estimate	SE	z-value	*p*
(a) Feeding				
Patch (<15 m)*	1.516	0.007	215.53	<0.001
(b) Searching				
Patch (<15 m)*	-0.128	0.009	-14.74	<0.001

Biological validation 2: vulturine guineafowl spend more time locomoting when making larger displacements

To test the ability to distinguish between locomoting and searching (Table S4), we use the GPS data to calculate the distance travelled over 10-minute periods during which the accelerometer was also collecting data. We then match this to the time spent locomoting and searching in those same 10 minutes. We expect that moving larger distances should be strongly and positively correlated with locomoting (travelling in a directed fashion). By contrast, we do not expect to find support for such a relationship for searching behaviour (travelling while looking for food). We fit generalized linear mixed effect models with proportion of the 10-minute window spent doing the behaviour of interest ('locomoting' or 'searching') as the response variable and GPS-distance travelled was the predictor variable (scaled from 0-1 using R package 'scales'), controlling for bird ID and Date as random effects (in a binomial model). We use the whole dataset from the same periods as biological validation 1. Our analysis confirms that larger GPS displacements positively predict the proportion of 'locomoting' detected, but not searching (Table 4; Fig. 3b).

Table 4. Biological validation demonstrating that the random forest model can detect greater locomotion during periods when individuals make large displacements. Results of generalized linear mixed models on the inferred proportion of time spent (a) locomoting and (b) searching as a function of the distance travelled for 8 birds across 41 unique dates with 2830 10-minute blocks.

Predictor	Estimate	SE	z-value	*p*
(a) Locomoting				
Distance (scaled)	3.536	0.013	267.61	<0.001
(b) Searching				
Distance (scaled)	-0.036	0.016	-22.38	<0.001

Biological validation 3: vulturine guineafowl spend more time 'sitting' at night than during the day

To evaluate the ability to distinguish between 'sitting' and 'alert' (Table S4), we test whether night time is associated with an increase in 'sitting' relative to a matched day-time window. Vulturine guineafowl spend the night at communal roost sites (Papageorgiou *et al.* 2024). While some wakefulness is expected at the roost, the night should be generally associated with more 'sitting' (stationary) relative to morning hours when vulturine guineafowl are observed to forage with intermittent bouts of alertness. The tags of three vulturine guineafowl were reprogrammed between 25th May 2023 and 6th July 2023 to collect data from 18:00 to 11:00 the next day. We use these data to test whether the proportion of time spent sitting was higher between 00:00 and 02:00 (middle of the night) than 07:00 and 09:00 (morning activity hours when birds are observed to forage on the open glades), controlling for 'bird ID' and 'Date'. We show that birds spend more time 'sitting' at night than during the morning hours (Table 5; Fig. 3c).

Table 5. Biological validation demonstrating that the random forest model can detect changes in sitting and alertness as a function of the time of the day. Results of generalized linear mixed models on the inferred proportion of time spent (a) sitting and (b) alert at night (00:00 to 02:00) versus during the morning (07:00 to 09:00; baseline) for 3 birds across 12 unique dates with 5844 1-minute blocks.

Predictor	Estimate	SE	z-value	*p*
(a) Sitting				
Time of day (Night)	5.272	0.034	154.857	*<0.001*
(b) Alert				
Time of day (Night)	-0.203	0.109	-18.507	*<0.001*

Biological validation 4: vulturine guineafowl show higher within-group than between-group synchrony in their activity

In some cases, *a priori* predictions about which behaviours will increase or decrease could be difficult to make, or experimental manipulations may not be feasible. In the case of group-living animals (such as the vulturine guineafowl), we can use the expectation that individuals in closer proximity (e.g. those from the same group) should be temporally more synchronised in their behaviours than dyads that are farther apart. These patterns are likely because individuals in close proximity experience more similar ecological forces, while maintaining cohesion also requires some synchronisation of activity (Davis, Crofoot & Farine 2022). with the caveat that some behaviours might also happen asynchronously, (e.g., alternating bouts of sentinel behaviour in meerkats: Santema & Clutton-Brock 2013). We use this prediction to test the performance of our model by taking the behavioural data from one vulturine guineafowl and time matching it to the data from a group member and a non-group member for 8 consecutive days (between 3rd and 10th of June 2022). For every second in these data, we calculated whether the behaviour was the same or not. Note that all three individuals live in close proximity, have overlapping home ranges, and experience largely identical ecological conditions. The model outputs confirm a substantially greater increase in synchronisation among individuals in the same group (mean±SD 28.2±0.04% of the time) than among individuals in different groups (0.05±0.01% of the time, Figure 3d).

Figure 3. Biological validation provides confirmation that the machine learning model is capable of testing biologically relevant hypotheses. (a) A higher rate of feeding but not searching is detected around a supplemented millet patch. (b) A higher GPS displacement corresponds to a higher proportion locomoting but not searching. (c) A higher rate of sitting (resting behaviour) is detected at night than during the day, whereas a higher rate of alert behaviour (also immobile) is detected during the day. (d) An individual has 5 to 8 times higher overlap in second-by-second behaviour with another individual moving within the same group compared to an individual in a different group. Silhouettes by [name redacted].

Ethical Note

The study was conducted under a research authorisation (KWS/BRP/5001) and capture permit from the Kenyan Wildlife Service (KWS/SCM/5705), the National Commission for Science, Technology and Innovation of Kenya (NACOSTI/P/21/6996),

the National Environment Management Authority (NEMA/AGR/068/2017) and Wildlife

Research & Training Institute (WRTI-0307-04-23). All the research was done in

collaboration with the Ornithology Section of the National Museums of Kenya. Capture

and GPS fitting was reviewed by the Max Planck Ethikrat Committee and the

Australian National University Animal Ethics Committee (A2023/20).

Capture and handling of birds were performed by trained personnel, following methods

approved by the Kenyan Wildlife Service and the Ornithology Section of the National

Museums of Kenya. Birds are captured in a large, baited walk-in trap activated by a

manually controlled mechanism (i.e., the trap is triggered only when it is safe to do so

for the birds). After capture, they are transferred to holding cages that are covered with

a tarp to minimise stress and placed in the shade. Typically, 3-4 birds per social group

carry GPS tags. The total weight of backpacks (Teflon string, rubber pad) and tags

combined is approximately 20.5 g, less than 2% of their body weight (females are

>1280 g, males are >1440 g), which is below the generally recommended 3-5% rule

(Kenward 2000). More recent evidence suggests that researchers must consider tag

attachment style and animal lifestyle alongside weight (Wilson *et al.* 2021). In our case,

the tags are fitted on the back, thereby fitting snugly to the centre of mass of the bird

and creating limited drag during movement, unlike collars which can exert large force

on the neck (Wilson *et al.* 2021). Moreover, foraging does not involve high-intensity

pursuits in guineafowl (as they forage predominantly on grass, seeds and insects),

meaning that the tag should not interfere with this critical activity. After capture, birds

were released in groups of four to eight at a time (including tagged and untagged

individuals) to avoid isolation and reduce the risk of exposure to predators. Follow-up

observations confirmed that tagging had no adverse impact on birds' ability to move,

forage or stay with their social group. Table S1 contains details on the tagged animals

for this study (sex and duration tags collected accelerometer data for). Tagged

individuals typically carry their tag for 1-2 years, after which the tag is either removed

manually during capture, the tag falls off due to the fabric wearing down or the bird is

predated. Video follows of the tagged birds were conducted from a car to which the

birds are habituated, keeping a minimum distance of 10 meters to avoid disturbance.

Discussion

In this work we highlight the difficulty in accurately estimating performance metrics of

ML models based on biological data, and how this can cause misguided investments

or undue critiques of models. While we demonstrate this issue using behavioural data,

which is ideally suited to illustrate issues of label ambiguity and its consequences for

ML models, the following findings may also be more broadly applicable to other fields

of ecology and evolution that use ML models to predict data for downstream analyses.

We first demonstrate a moderate correlation between the ability of humans to classify

data and the performance of the model at making the same classification, suggesting

that errors in the validation dataset create a ceiling on metric performance. This ceiling

causes an underestimation of true model performance that can have an impact on

decisions of where to invest limited resources for research. Next, we suggest that while

models are likely to always output a proportion of erroneous predictions, this may not

necessarily hinder the utility of the model because our aim is often to test hypotheses

rather than making predictions *per se*. We give an example of how simulations can be

used to evaluate the utility of models for hypothesis testing, which suggest that models

can still be useful even if imperfect. Finally, we propose methods for implementing

validation approaches that align with the ultimate aim of using models for hypothesis

testing, demonstrating that our own 'imperfect' models can reliably detect a number of

predicted patterns in behaviour. In doing so, we provide tools for developing and

evaluating models that are not only more robust but also better aligned with their

intended scientific objectives.

The results of our inter-individual disagreement analysis build on the well-established

finding that observers can disagree on the classification or exact temporal delineation

of a behaviour (Garcia, Junior & Marino-Neto 2010; Burghardt *et al.* 2012). While rates

of inter-individual disagreement do not translate directly to rates of mislabels, they

show that errors in labelling are in many cases unavoidable. Some steps can be taken

to improve inter-observer agreement, including extensive training, more clearly

defined ethograms, shorter observation sessions to avoid fatigue and recruiting

observers with long-term experience observing the animals in question (Kiddie &

Collins 2014; Dai *et al.* 2020). Nevertheless, some cases are by their very nature

difficult to assign, such as subtle (Dai *et al.* 2020), variably executed (Brouwers *et al.*

2023) or transitionary (Nguyen *et al.* 2021; Li *et al.* 2022) behaviours. When evaluating

ML models, researchers should bear in mind the potential for mislabels, as these can

penalise the reported performance metrics even if the model performs well (see Supplementary material for a worked example). Reviewing the confusion matrix and evaluating examples of incorrect predictions on the validation set can help identify any patterns in errors. For instance, errors may occur more often between transitional behaviours such as shifting from walking to running. Understanding the limitations of our human-labelled validation dataset (particularly when it comes to 'noisy' data) can help to set more realistic expectations for evaluation metrics and can inform decisions about when to stop training, which can avoid endlessly testing alternative models and algorithms.

Another important factor to keep in mind, is that the impact of errors in the predictions by ML-based models is not equal across all research questions. Some questions will be naturally more robust to errors, while others will be more sensitive. Imagine a ML model that is used to predict the identity of individuals interacting with one another from videos or pictures has a rate of erroneous identification (assigning the wrong identity to a detected individual). If the aim of our study was to test whether the social network of individuals is assorted by sex (Farine 2014), then even a model that makes frequent errors would still allow us to test the hypothesis robustly because assortment is very robust to imperfect sampling (Kaur *et al.* 2024) (i.e. the vast majority of edges would still accurately contribute to the test of the hypothesis). By contrast, if we wanted to instead study the spread of a contagious disease in the population, then our hypothesis may be substantially more sensitive to errors. This is because identification errors rewire the social network (Davis, Crofoot & Farine 2018). It can also artificially increase the density of edges because misclassifying individual identities can introduce connections between individuals that were never (or could never have been) observed together. The addition of just a few edges could then change the properties of spread through a social network. Thus, an error rate that could yield accurate estimations for the test of one hypothesis (network assortment) could also lead to errors for another hypothesis (e.g. dramatically overestimating the potential rate of disease transmission in the population). Similarly, some errors in behavioural predictions from accelerometery tags may be less problematic if the aim of the study is to monitor relative changes in behaviour (e.g., an increase in preening in response to higher ectoparasite load: Møller 1991). In contrast, if the exact onset of a behaviour that was previously absent is of interest

(e.g., the timing of mating-related behaviours: McDonald 1989), misclassifications

could make these harder to detect (or lead to false detections of such events).

In most cases, models will perform worse than hoped for on standard metric tests.

One common pattern is that model performance is lower when there are more

categories to classify (this is expected). In such cases, rather than testing the

applicability of the 'imperfect' model (as presented here in our simulations),

researchers are often tempted to merge categories that are frequently confused by the

model and/or have similar biological functions (Ladds *et al.* 2017; Christensen *et al.*

2023) as a way of obtaining higher values in the evaluation metrics. We note that

having fewer categories will almost always increase model performance across all

metrics (Ladds *et al.* 2017). The reason is mathematical: a completely naïve model

will have a higher probability of making a correct guess if there are fewer categories

to guess from. However, merging categories does not necessarily mean that the new

model is more useful. For example, combining two foraging behaviours that are often

confused—such as browsing a bush and pecking at ground level—might reduce the

reported error, but if these behaviours are still mistaken with other non-foraging-related

behaviours that the model can predict (e.g. locomoting), then merging these

behaviours might not add to any conclusion about foraging in relation to the non-

foraging behaviours. Instead, merging categories for the purpose of increasing

evaluation metrics may even narrow the model's applicability and hinder hypothesis

testing. For instance, merging foraging-related categories could limit our ability to test

individual foraging mode/diet preferences (Toscano *et al.* 2016; Gharnit *et al.* 2022) or

seasonal variation in foraging modes (Owen-Smith, Fryxell & Merrill 2010). The results

from our simulations provide researchers with an additional pathway to convincingly

demonstrate the applicability of their models without jeopardizing the initial research

questions of interest (e.g. by losing resolution by merging categories).

High performance metrics might also be misleading and lead to overconfidence in the

model. Beyond the common pitfalls that might lead to overfitting models (e.g. having

the same or correlated data both in training and validation datasets; Ferreira *et al.*

2020b; Aulsebrook, Jacques-Hamilton & Kempenaers 2024), performance metrics do

not always capture the different contexts in which categories might occur. For

example, a binary classification model that is 99% accurate (evaluated on a balanced

validation dataset) in detecting the presence vs absence of birds in a frame of a video

might still produce many more false positives than actual correct predictions for the
less common category (in this example, presence of birds) if the number of frames
without birds is hundreds of times more common than frames with birds during the real
application of the model (e.g., Silva *et al.* 2024). We argue that estimating the ability
to detect effect sizes and validating models by using biological hypotheses derived
using *a priori* knowledge is a more reliable method to evaluate model performance
because it more closely replicates how the model will be used in the future.

Biological validation is not without its challenges. For example, we cannot give clear
guidelines on how many validations to perform or guarantee that failing to detect an
effect during biological validation was not because our 'simple hypothesis' was
incorrect as opposed to the model generating too many incorrect predictions. Finally,
the model might work for clear signals that rise above model classification error noise
(or a delineated case, such as during an experimental treatment) but not in more
complex cases, where animal responses (e.g., behavioural change) may be more
subtle or masked by other simultaneous changes. For all of these reasons, validating
models through simulations and testing "simple" hypotheses should not be seen as
last resort to validate apparent low performing models, but as a way of obtaining
greater knowledge about the future classified data, about where the strengths and
weaknesses of the model may be, and about how the model (and its performance)
might fit in the whole pipeline from data collection through to finalising the results (as
has been proposed for statistical hypothesis testing more generally: Zuur, Ieno &
Elphick 2010; Rubin & Donkin 2024).

Finally, our proposed validation approaches should not be used as a loophole to
excuse poorly trained models. In the same way that reported traditional evaluation
metrics can be high for low performing models (e.g. overfitted models: Bejani &
Ghatee 2021), poorly trained models could output data that can appear to detect
expected effect directions but totally misrepresent the effect size. The true value of
validating models through simulations and hypotheses testing lies on pushing
researchers to openly and critically think about the potential biases of their models and
consider whether their models are vulnerable to producing misleading scientific
outcomes (as discussed above), instead of evaluating them shallowly. We hope that
these additional quality control layers can improve the ability for researchers to switch
from model refinement to hypothesis testing while increasing the quality of ML-based

proof-of-concepts works and applications. This can help mitigate the proliferation of publications featuring overfitted models, a trend already observed in other research fields (Navarro *et al.* 2021; Berisha *et al.* 2022; Saidi, Dasarathy & Berisha 2024). Biological validation adds a final layer of quality control by simulating real-world applications of the models before their publication and/or before using them to address real biological questions of interest. Such final layer of validation should elevate the standards of ML-related publication in behaviour ecology, ecology and evolution.

Data availability statement

Data and code are available on Figshare:

https://figshare.com/s/f015439a649d626d5aa0

References

Aulsebrook, A.E., Jacques-Hamilton, R. & Kempenaers, B. (2024) Quantifying mating behaviour using accelerometry and machine learning: challenges and opportunities. *Animal Behaviour,* **207,** 55-76.

Bejani, M.M. & Ghatee, M. (2021) A systematic review on overfitting control in shallow and deep neural networks. *Artificial Intelligence Review,* **54,** 6391-6438.

Berisha, V., Krantsevich, C., Stegmann, G., Hahn, S. & Liss, J. (2022) Are reported accuracies in the clinical speech machine learning literature overoptimistic? *Interspeech*, pp. 2453-2457.

Birhane, A., Kalluri, P., Card, D., Agnew, W., Dotan, R. & Bao, M. (2022) The values encoded in machine learning research. *Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency*, pp. 173-184.

Bolker, B.M., Brooks, M.E., Clark, C.J., Geange, S.W., Poulsen, J.R., Stevens, M.H.H. & White, J.-S.S. (2009) Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology & Evolution,* **24,** 127-135.

Brewster, L., Dale, J., Guttridge, T., Gruber, S., Hansell, A., Elliott, M., Cowx, I., Whitney, N. & Gleiss, A. (2018) Development and application of a machine learning algorithm for classification of elasmobranch behaviour from accelerometry data. *Marine biology,* **165,** 62.

Brouwers, S.P., Simmler, M., Savary, P. & Scriba, M.F. (2023) Towards a novel method for detecting atypical lying down and standing up behaviors in dairy cows using accelerometers and machine learning. *Smart Agricultural Technology,* **4,** 100199.

Brown, D.D., Kays, R., Wikelski, M., Wilson, R. & Klimley, A.P. (2013) Observing the unwatchable through acceleration logging of animal behavior. *Animal Biotelemetry,* **1,** 20.

Burghardt, G.M., Bartmess-LeVasseur, J.N., Browning, S.A., Morrison, K.E., Stec, C.L., Zachau, C.E. & Freeberg, T.M. (2012) Perspectives–minimizing observer bias in behavioral studies: a review and recommendations. *Ethology,* **118,** 511-517.

Cagnacci, F., Boitani, L., Powell, R.A. & Boyce, M.S. (2010) Animal ecology meets GPS-based radiotelemetry: a perfect storm of opportunities and challenges. The Royal Society.

Caravaggi, A., Banks, P.B., Burton, A.C., Finlay, C.M., Haswell, P.M., Hayward, M.W., Rowcliffe,
M.J. & Wood, M.D. (2017) A review of camera trapping for conservation behaviour
research. *Remote Sensing in Ecology and Conservation, 3,* 109-122.
Chakravarty, P., Cozzi, G., Ozgul, A. & Aminian, K. (2019) A novel biomechanical approach for
animal behaviour recognition using accelerometers. *Methods in Ecology and
Evolution, 10,* 802-814.
Chambers, R.D., Yoder, N.C., Carson, A.B., Junge, C., Allen, D.E., Prescott, L.M., Bradley, S.,
Wymore, G., Lloyd, K. & Lyle, S. (2021) Deep learning classification of canine behavior
using a single collar-mounted accelerometer: Real-world validation. *Animals, 11,*
1549.
Christensen, C., Bracken, A.M., O'Riain, M.J., Fehlmann, G., Holton, M., Hopkins, P., King, A.J.
& Fürtbauer, I. (2023) Quantifying allo-grooming in wild chacma baboons (Papio
ursinus) using tri-axial acceleration data and machine learning. *Royal Society open
science, 10,* 221103.
Colquhoun, D. (2017) The reproducibility of research and the misinterpretation of p-values.
Royal Society open science, 4, 171085.
Culverhouse, P.F., Williams, R., Reguera, B., Herry, V. & González-Gil, S. (2003) Do experts
make mistakes? A comparison of human and machine indentification of
dinoflagellates. *Marine Ecology Progress Series, 247,* 17-25.
Dai, F., Leach, M., MacRae, A.M., Minero, M. & Dalla Costa, E. (2020) Does thirty-minute
standardised training improve the inter-observer reliability of the horse grimace scale
(HGS)? A case study. *Animals, 10,* 781.
Davis, G.H., Crofoot, M.C. & Farine, D.R. (2018) Estimating the robustness and uncertainty of
animal social networks using different observational methods. *Animal Behaviour,
141,* 29-44.
Davis, G.H., Crofoot, M.C. & Farine, D.R. (2022) Using optimal foraging theory to infer how
groups make collective decisions. *Trends in Ecology & Evolution*.
Dunbar, R.I., Korstjens, A.H. & Lehmann, J. (2009) Time as an ecological constraint. *Biological
reviews, 84,* 413-429.
Ellison, A.M. (2004) Bayesian inference in ecology. *Ecology Letters, 7,* 509-520.
Farine, D.R. (2014) Measuring phenotypic assortment in animal social networks: weighted
associations are more robust than binary edges. *Animal Behaviour, 89,* 141-153.
Fehlmann, G., O'Riain, M.J., Hopkins, P.W., O'Sullivan, J., Holton, M.D., Shepard, E.L. & King,
A.J. (2017) Identification of behaviours from accelerometer data in a wild social
primate. *Animal Biotelemetry, 5,* 6.
Ferdinandy, B., Gerencsér, L., Corrieri, L., Perez, P., Újváry, D., Csizmadia, G. & Miklósi, Á.
(2020) Challenges of machine learning model validation using correlated behaviour
data: evaluation of cross-validation strategies and accuracy measures. *PloS one, 15,*
e0236092.
Ferreira, A.C., Covas, R., Silva, L.R., Esteves, S.C., Duarte, I.F., Fortuna, R., Theron, F.,
Doutrelant, C. & Farine, D.R. (2020a) How to make methodological decisions when
inferring social networks. *Ecology and Evolution, 10,* 9132-9143.
Ferreira, A.C., Silva, L.R., Renna, F., Brandl, H.B., Renoult, J.P., Farine, D.R., Covas, R. &
Doutrelant, C. (2020b) Deep learning-based methods for individual recognition in
small birds. *Methods in Ecology and Evolution, 11,* 1072-1085.
Garcia, V.A., Junior, C.F.C. & Marino-Neto, J. (2010) Assessment of observers' stability and
reliability—A tool for evaluation of intra-and inter-concordance in animal behavioral

recordings. *2010 Annual International Conference of the IEEE Engineering in Medicine*
and Biology, pp. 6603-6606. IEEE.

Gharnit, E., Dammhahn, M., Garant, D. & Réale, D. (2022) Resource availability, sex, and
individual differences in exploration drive individual diet specialization. *The American*
Naturalist, **200,** 1-16.

Giese, L., Melzheimer, J., Bockmühl, D., Wasiolka, B., Rast, W., Berger, A. & Wachter, B.
(2021) Using machine learning for remote behaviour classification—Verifying
acceleration data to infer feeding events in free-ranging cheetahs. *Sensors,* **21,** 5426.

Greenland, S., Senn, S.J., Rothman, K.J., Carlin, J.B., Poole, C., Goodman, S.N. & Altman, D.G.
(2016) Statistical tests, P values, confidence intervals, and power: a guide to
misinterpretations. *European journal of epidemiology,* **31,** 337-350.

He, P., Klarevas-Irby, J.A., Papageorgiou, D., Christensen, C., Strauss, E.D. & Farine, D.R.
(2022) A guide to sampling design for GPS-based studies of animal societies.
Methods in Ecology and Evolution, **14,** 1887-1905.

Hilborn, R. & Mangel, M. (2013) *The ecological detective: confronting models with data*
(MPB-28). Princeton University Press.

Hooge, I.T., Niehorster, D.C., Nyström, M., Andersson, R. & Hessels, R.S. (2018) Is human
classification by experienced untrained observers a gold standard in fixation
detection? *Behavior research methods,* **50,** 1864-1881.

Houlahan, J.E., McKinney, S.T., Anderson, T.M. & McGill, B.J. (2017) The priority of prediction
in ecological understanding. *Oikos,* **126,** 1-7.

Hounslow, J., Brewster, L., Lear, K., Guttridge, T., Daly, R., Whitney, N. & Gleiss, A. (2019)
Assessing the effects of sampling frequency on behavioural classification of
accelerometer data. *Journal of experimental marine biology and ecology,* **512,** 22-30.

Hounslow, J.L., Fossette, S., Chong, W., Bali, R., Tucker, A.D., Whiting, S.D. & Gleiss, A.C.
(2023) Behaviour-specific spatiotemporal patterns of habitat use by sea turtles
revealed using biologging and supervised machine learning. *Journal of applied*
ecology, **60,** 1828-1840.

Jennions, M.D. & Moeller, A.P. (2002) Publication bias in ecology and evolution: an empirical
assessment using the 'trim and fill'method. *Biological reviews,* **77,** 211-222.

Kaur, P., Ciuti, S., Salter-Townshend, M. & Farine, D.R. (2024) Using an agent based model to
inform sampling design for animal social network analysis. *bioRxiv*, 2024.2005.
2025.595870.

Kays, R., Crofoot, M.C., Jetz, W. & Wikelski, M. (2015) Terrestrial animal tracking as an eye on
life and planet. *Science,* **348,** aaa2478.

Kenward, R.E. (2000) *A manual for wildlife radio tagging*. Academic press.

Kiddie, J.L. & Collins, L.M. (2014) Development and validation of a quality of life assessment
tool for use in kennelled dogs (Canis familiaris). *Applied Animal Behaviour Science,*
158, 57-68.

Ladds, M.A., Thompson, A.P., Kadar, J.-P., J Slip, D., P Hocking, D. & G Harcourt, R. (2017)
Super machine learning: improving accuracy and reducing variance of behaviour
classification from accelerometry. *Animal Biotelemetry,* **5,** 1-9.

Li, J., Green-Miller, A.R., Hu, X., Lucic, A., Mohan, M.M., Dilger, R.N., Condotta, I.C., Aldridge,
B., Hart, J.M. & Ahuja, N. (2022) Barriers to computer vision applications in pig
production facilities. *Computers and electronics in agriculture,* **200,** 107227.

Lok, T., van der Geest, M., Bom, R.A., de Goeij, P., Piersma, T. & Bouten, W. (2023) Prey ingestion rates revealed by back-mounted accelerometers in Eurasian spoonbills. *Animal Biotelemetry,* **11,** 5.

Mannix, E.J., Wei, S., A. Woodham, B., Wilkinson, P. & Robinson, A.P. (2021) Automating the assessment of biofouling in images using expert agreement as a gold standard. *Scientific Reports,* **11,** 2739.

McDonald, D.B. (1989) Correlates of male mating success in a lekking bird with male-male cooperation. *Animal Behaviour,* **37,** 1007-1022.

Møller, A.P. (1991) The preening activity of swallows, Hirundo rustica, in relation to experimentally manipulated loads of haematophagous mites. *Animal Behaviour,* **42,** 251-260.

Navarro, C.L.A., Damen, J.A., Takada, T., Nijman, S.W., Dhiman, P., Ma, J., Collins, G.S., Bajpai, R., Riley, R.D. & Moons, K.G. (2021) Risk of bias in studies on prediction models developed using supervised machine learning techniques: systematic review. *bmj,* **375.**

Nguyen, C., Wang, D., Von Richter, K., Valencia, P., Alvarenga, F.A. & Bishop–Hurley, G. (2021) Video-based cattle identification and action recognition. *2021 Digital Image Computing: Techniques and Applications (DICTA)*, pp. 01-05. IEEE.

Norouzzadeh, M.S., Morris, D., Beery, S., Joshi, N., Jojic, N. & Clune, J. (2021) A deep active learning system for species identification and counting in camera trap images. *Methods in Ecology and Evolution,* **12,** 150-161.

Owen-Smith, N., Fryxell, J.M. & Merrill, E.H. (2010) Foraging theory upscaled: the behavioural ecology of herbivore movement. *Philosophical Transactions of the Royal Society B: Biological Sciences,* **365,** 2267-2278.

Papageorgiou, D., Cherono, W., Gall, G., Nyaguthii, B. & Farine, D.R. (2024) Testing the information centre hypothesis in a multilevel society. *Journal of Animal Ecology,* **93,** 1147-1159.

Papageorgiou, D., Rozen-Rechels, D., Nyaguthii, B. & Farine, D.R. (2021) Seasonality impacts collective movements in a wild group-living bird. *Movement ecology,* **9,** 1-12.

Pei, K., Cao, Y., Yang, J. & Jana, S. (2017) Deepxplore: Automated whitebox testing of deep learning systems. *proceedings of the 26th Symposium on Operating Systems Principles*, pp. 1-18.

Probst, P., Boulesteix, A.-L. & Bischl, B. (2019) Tunability: Importance of hyperparameters of machine learning algorithms. *Journal of Machine Learning Research,* **20,** 1-32.

Rainio, O., Teuho, J. & Klén, R. (2024) Evaluation metrics and statistical tests for machine learning. *Scientific Reports,* **14,** 6086.

Rast, W., Kimmig, S.E., Giese, L. & Berger, A. (2020) Machine learning goes wild: Using data from captive individuals to infer wildlife behaviours. *PloS one,* **15,** e0227317.

Reyes-Ortiz, J.-L., Oneto, L., Samà, A., Parra, X. & Anguita, D. (2016) Transition-aware human activity recognition using smartphones. *Neurocomputing,* **171,** 754-767.

Riaboff, L., Shalloo, L., Smeaton, A.F., Couvreur, S., Madouasse, A. & Keane, M.T. (2022) Predicting livestock behaviour using accelerometers: A systematic review of processing techniques for ruminant behaviour prediction from raw accelerometer data. *Computers and electronics in agriculture,* **192,** 106610.

Rolnick, D., Veit, A., Belongie, S. & Shavit, N. (2017) Deep learning is robust to massive label noise. *arXiv preprint arXiv:1705.10694.*

Rubin, M. & Donkin, C. (2024) Exploratory hypothesis tests can be more compelling than confirmatory hypothesis tests. *Philosophical Psychology,* **37,** 2019-2047.

Ryder, T.B., Horton, B.M., van den Tillaart, M., Morales, J.D.D. & Moore, I.T. (2012) Proximity data-loggers increase the quantity and quality of social network data. *Biology Letters,* **8,** 917-920.

Saidi, P., Dasarathy, G. & Berisha, V. (2024) Unraveling overoptimism and publication bias in ML-driven science. *arXiv preprint arXiv:2405.14422*.

Santema, P. & Clutton-Brock, T. (2013) Meerkat helpers increase sentinel behaviour and bipedal vigilance in the presence of pups. *Animal Behaviour,* **85,** 655-661.

Schneider, S., Taylor, G.W. & Kremer, S.C. (2022) Similarity learning networks for animal individual re-identification: an ecological perspective. *Mammalian Biology,* **102,** 899-914.

Sheng, V.S., Provost, F. & Ipeirotis, P.G. (2008) Get another label? improving data quality and data mining using multiple, noisy labelers. *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 614-622.

Shuert, C.R., Pomeroy, P.P. & Twiss, S.D. (2018) Assessing the utility and limitations of accelerometers and machine learning approaches in classifying behaviour during lactation in a phocid seal. *Animal Biotelemetry,* **6,** 1-17.

Silva, L.R., Ferreira, A.C., Doutrelant, C. & Covas, R. (2024) From raw footage to behaviour: an automated pipeline for activity monitoring and behaviour identification in the wild. *bioRxiv***,** 2024.2010. 2025.620052.

Sipper, M. (2022) High per parameter: A large-scale study of hyperparameter tuning for machine learning Algorithms. *Algorithms,* **15,** 315.

Smith, J.E. & Pinter-Wollman, N. (2021) Observing the unwatchable: Integrating automated sensing, naturalistic observations and animal social network analysis in the age of big data. *Journal of Animal Ecology,* **90,** 62-75.

Steidl, R.J. & Thomas, L. (2001) Power analysis and experimental design. *Design and analysis of ecological experiments,* **2,** 415.

Toscano, B.J., Gownaris, N.J., Heerhartz, S.M. & Monaco, C.J. (2016) Personality, foraging behavior and specialization: integrating behavioral and food web ecology at the individual level. *Oecologia,* **182,** 55-69.

Valletta, J.J., Torney, C., Kings, M., Thornton, A. & Madden, J. (2017) Applications of machine learning in animal behaviour studies. *Animal Behaviour,* **124,** 203-220.

Wang, G. (2019) Machine learning for inferring animal behavior from location and movement data. *Ecological Informatics,* **49,** 69-76.

Wang, Y., Nickel, B., Rutishauser, M., Bryce, C.M., Williams, T.M., Elkaim, G. & Wilmers, C.C. (2015) Movement, resting, and attack behaviors of wild pumas are revealed by tri-axial accelerometer measurements. *Movement ecology,* **3,** 2.

Whytock, R.C., Świeżewski, J., Zwerts, J.A., Bara-Słupski, T., Koumba Pambo, A.F., Rogala, M., Bahaa-el-din, L., Boekee, K., Brittain, S. & Cardoso, A.W. (2021) Robust ecological analysis of camera trap data labelled by a machine learning model. *Methods in Ecology and Evolution,* **12,** 1080-1092.

Willi, M., Pitman, R.T., Cardoso, A.W., Locke, C., Swanson, A., Boyer, A., Veldthuis, M. & Fortson, L. (2019) Identifying animal species in camera trap images using deep learning and citizen science. *Methods in Ecology and Evolution,* **10,** 80-91.

Wilson, R.P., Rose, K.A., Gunner, R., Holton, M.D., Marks, N.J., Bennett, N.C., Bell, S.H.,
Twining, J.P., Hesketh, J. & Duarte, C.M. (2021) Animal lifestyle affects acceptable
mass limits for attached tags. *Proceedings of the Royal Society B,* **288,** 20212005.

Yan, Y., Rosales, R., Fung, G., Subramanian, R. & Dy, J. (2014) Learning from multiple
annotators with varying expertise. *Machine learning,* **95,** 291-327.

Young, D.S. (2018) *Handbook of regression methods*. Chapman and Hall/CRC.

Zhong, M., Taylor, R., Bates, N., Christey, D., Basnet, H., Flippin, J., Palkovitz, S., Dodhia, R. &
Ferres, J.L. (2021) Acoustic detection of regionally rare bird species through deep
convolutional neural networks. *Ecological Informatics,* **64,** 101333.

Zuur, A.F., Ieno, E.N. & Elphick, C.S. (2010) A protocol for data exploration to avoid common
statistical problems. *Methods in Ecology and Evolution,* **1,** 3-14.