Harnessing Smartphone RGB Imagery and LiDAR Point Cloud for Enhanced Leaf Nitrogen and Shoot Biomass Assessment - Chinese Spinach as a Case Study

Aravind Harikumar[1,2], Itamar Shenhar[1,2,3], Miguel R. Pebes-Trujillo[1,2], Qin Lin[4], Menachem Moshelion[2,3], Jie He[2,4], Kee Woei Ng[1,2,5], Matan Gavish[2,6], and Ittai Herrmann[2,3†]

[1]School of Materials Science and Engineering, Nanyang Technological University, Singapore.

[2]Singapore-HUJ Alliance for Research and Enterprise (SHARE), Singapore.

[3]Robert H. Smith Institute of Plant Sciences and Genetics in Agriculture, The Hebrew University of Jerusalem, Rehovot 7610001, Israel.

[4]National Institute of Education, Nanyang Technological University, Singapore.

[5]Nanyang Environment and Water Research Institute (NEWRI), Singapore.

[6]School of Computer Science and Engineering, The Hebrew University, Jerusalem, Israel.

[*]Address correspondence to: ittai.herrmann@mail.huji.ac.il

Abstract

Accurate estimation of leaf nitrogen concentration and shoot dry-weight biomass in leafy vegetable crops is essential for effective yield management, stress assessment, nutrient dosing optimization, and the implementation of precision agriculture practices. However, obtaining this information often requires access to reliable plant physiological and biophysical data, which typically involves sophisticated equipment, such as high-resolution in-situ sensors and cameras. These tools, however, are associated with substantial costs. In contrast, smartphone-based sensing offers a relatively low-cost, manual alternative for acquiring accurate plant data.

In this study, we propose an innovative approach for estimating leaf nitrogen concentration and shoot biomass by integrating smartphone RGB imagery with Light Detection and Ranging (LiDAR) data, using Chinese spinach (Amaranthus dubius) as a case study. The influence of varying nitrogen dosages on individual spectral and structural features derived from smartphone RGB imagery and LiDAR data was modeled. Additionally, the spectral indices from RGB imagery and structural indices from LiDAR data were combined to model both leaf nitrogen concentration and shoot biomass.

The performance of crop parameter modeling was evaluated using three machine learning models: support vector regression (SVR), random forest regression (RF), and lasso regression. Results demonstrate that the combined use of smartphone RGB imagery and LiDAR data can accurately estimate leaf total reduced nitrogen (TRN) concentration, leaf nitrate (NO_3) concentration, and shoot dry-weight (DW) biomass, with average relative root mean square errors (rRMSE) as low as 0.06, 0.16, and 0.05, respectively. Furthermore, the optimal nitrogen dosage for maximizing biomass yield in Chinese spinach was estimated based on these spectral and structural features. This study lays the groundwork for smartphone-based sensing to estimate leaf nitrogen concentration and shoot biomass, supporting the future of accessible, precision agriculture practices.

1 Introduction

Nitrogen is a cornerstone mineral nutrient essential for regulating the yield and overall health of crop plants, as it is a key component of plant amino acids, proteins, and nucleic acids. Subtropical leafy vegetable crops, such as Chinese spinach (Amaranthus dubius), are experiencing a growing global market demand due to their exceptional nutritional profile and relatively affordable price [1]. These crops respond notably well to nitrogen fertilization, attributed to their efficient nitrogen uptake mechanisms paired with less efficient nitrogen reductive systems [2, 3]. However, the nitrogen fertilizer use efficiency for leafy vegetable crops typically remains below 50% of the applied amount [4], reducing profitability and contributing to substantial nitrogen loss to the environment. Such loss leads to increased nitrogen runoff into water bodies and elevated greenhouse gas emissions [5]. Balancing crop nitrogen needs with fertilizer application is thus critical to optimizing crop performance, enhancing nutritional quality, protecting the environment, and maximizing returns for farmers. Given nitrogen's vital role in improving both the nutritional value and market appeal of leafy vegetables, accurate estimation of leaf nitrogen concentration and shoot dry-weight biomass is essential for determining the specific nitrogen requirements of crop species and, consequently, for optimizing fertilizer application to maximize yield and profitability.

Traditional methods for assessing leaf nitrogen concentration, such as laboratory-based micro Kjeldahl analysis [6], and for determining shoot dry-weight biomass through drying, rely on destructive sampling, making them impractical and costly in terms of time, financial resources, and labor. This necessitates the development of innovative approaches that allow timely, non-destructive estimation of these plant parameters. Smartphone sensing provides a non-destructive method for analyzing crop dynamics, representing a promising pathway to high-throughput plant phenotyping that can transform crop management practices [7]. Extensive research has consistently demonstrated a robust relationship between Red-Green-Blue (RGB) imagery and leaf nutrient composition [8, 9]. For example, studies indicate that leaf chlorophyll concentration, which correlates positively with leaf nitrogen levels, provides a reliable indicator of nitrogen concentration [10]. The emergence of optical smartphone RGB imaging has thus provided a cost-effective approach for capturing crop traits compared to the use of expensive cameras. The widespread availability and affordability of smartphones have driven the development of methods that use smartphone-based RGB imagery to estimate leaf nitrogen concentration in staple crops, such as rice and wheat [11, 12]. However, a key limitation of RGB imagery is

its lack of structural data, which is needed to estimate traits like crop plant height and shoot dry-weight biomass [13].The recent integration of Light Detection and Ranging (LiDAR) sensors into smartphones marks a groundbreaking advancement, enabling the collection of structural plant data, including biomass estimation. Combining smartphone RGB data with LiDAR data offers potential for estimating both biophysical and physiological traits in leafy vegetable crops. For instance, Bar-sella et al. successfully estimated leaf transpiration in maize using smartphone RGB imagery and LiDAR data collected with an iPhone 13 Pro Max smartphone [14].

A comprehensive literature review reveals a significant research gap in the integration of relatively low-cost smartphone RGB and LiDAR data for estimating plant traits, including leaf nitrogen concentration and shoot biomass. Moreover, few studies have focused on nitrogen concentration and biomass estimation specifically for high-demand tropical leafy vegetables, such as Chinese spinach (Amaranthus dubius). Additionally, many of the existing studies have been conducted in open-field conditions, which are subject to considerable variations by biotic and abiotic factors [14, 15], whereas the current study focuses on semi-controlled outdoor conditions. Specifically, this study aims to achieve three main objectives: (a) to evaluate the effectiveness of combined smartphone-based RGB imagery and LiDAR data for accurately estimating leaf nitrogen concentration and shoot biomass in leafy vegetable crops within a semi-controlled greenhouse setting, (b) to quantify the relevance of various RGB and LiDAR-based vegetation indices for estimating leaf nitrogen concentration and shoot dry-weight biomass in Chinese spinach, and (c) to identify the optimal nitrogen dosage for maximizing crop dry-weight biomass yield using integrated smartphone RGB imagery and LiDAR data.

2 Materials

2.1 Study Site, Experimental Setup and Crop Management

The experiment was conducted in a semi-controlled outdoor greenhouse facility that is (Oasis Living Lab, Singapore), specifically dedicated to leafy vegetable production, from September to November 2023. A total of 84 Chinese spinach (Amaranthus dubius) plants, known for their high productivity and nutritious value, were selected for this study (Fig. 1). Seeds were initially sown in seedling trays and nurtured for 3–4 weeks to ensure optimal growth prior to transplantation [16]. At the appropriate growth stage, the plants were transplanted into 4-L pots (Tefen Ltd., Nahsholim, Israel) filled with coco-peat substrate (Riococo Ltd., Sri Lanka) at the experiment's commencement.

To assess the impact of varying nitrogen dosages on plant growth and performance, plants were divided into eight distinct treatment groups, each with 10 or 11 replicates. Each group received one of the following nitrogen dosages: 20, 40, 80, 120, 160, 200, 400, or 800 parts per million (ppm), administered in an aqueous solution. Nitrogen application was meticulously managed using precision pumps (Shurflo 5050-1311-H011, Pentair, MN, USA) under the control of the PlantArray system (Plant-Ditech, Yavne, Israel), as described in [17].

At the conclusion of the experiment, plant shoots were harvested and manually separated into leaves and stems. The harvested shoots were then dried in an oven at a constant temperature of 60°C for one week to ensure thorough desiccation before laboratory analysis. These dried samples were analyzed to determine leaf total reduced nitrogen (TRN) concentration, leaf nitrate (NO_3) concentration, and shoot dry-weight (DW) biomass. Here, TRN represents the total nitrogen

content in its reduced forms, including nitrogen incorporated into amino acids, proteins, and other organic compounds, while NO_3 denotes the inorganic nitrogen absorbed by plants from the soil.

Figure 1: Experimental setup of 84 Chinese spinach (Amaranthus dubius) plants in the semi-controlled greenhouse at the OasisLab, Singapore. Nitrogen dosing for each plant is precisely regulated using the PlantArray system, allowing controlled assessment of varying nitrogen treatments (in randomized block design) on plant growth and performance.

2.2   Smartphone Data Collection

In this study, an iPhone 14 Pro Max smartphone (Apple, Cupertino, CA, USA) with a field of view (FoV) of 69°, pixel size (PL) of 1.9 μm, and focal length (F) of 26 mm was mounted on a manually held ZHIYUN Smooth 5 gimbal platform (Guilin Zhishen Information Technology Co., Ltd., Shenzhen, China) to acquire RGB imagery from a nadir perspective (Fig. 2a). RGB images for all 84 Chinese spinach (Amaranthus dubius) plants were captured within a 10-minute timeframe under clear skies, between 11:30 am and 12:00 pm, on the day preceding harvest. The RGB data acquisition height was set to ensure the entire plant crown fell within the camera's field of view, specifically at 50 $\pm$ 5 cm above the highest point of the plant crown. Precise horizontal alignment and smartphone orientation during data capture were verified using the Pocket Bubble Level iPhone application (ExaMobile S.A., Bielsko-Biała, Poland) to maintain a level device position throughout the imaging process. At the end of data collection, an RGB image of a 99.9% circular white reference panel was taken to facilitate the conversion of raw RGB digital numbers to reflectance values.

Additionally, 3D LiDAR point cloud data of each plant was captured using the iPhone 14 Pro Max's in-built LiDAR sensor, operated via the Polycam 3D scanning application. The LiDAR sensor specifications are consistent across iPhone 13 and iPhone 14 Pro models, allowing them to be used interchangeably for 3D data acquisition. Plants were positioned against a dark background, 10–20 cm from the pot, to reduce background noise and enhance point cloud quality. The Polycam application's LiDAR capture mode collected high-density point cloud data, achieving a resolution exceeding 100 points per square centimeter. During LiDAR data acquisition, the smartphone was maneuvered in a circular path around and above each plant (Fig. 2b) to obtain a comprehensive, detailed representation of the plant's crown structure. The Polycam application generated the final raw 3D point cloud, with each point containing R, G, and B value attributes, within 20–30 seconds of scan completion and preprocessing initiation.

<center>(a)   (b)</center>

Figure 2: Schematic representation of the smartphone-based data acquisition setup in the indoor greenhouse. (a) RGB imagery acquisition setup showing the smartphone mounted on a gimbal platform and the PlantArray system managing nitrogen dosing for individual plants. (b) 3D LiDAR point cloud data acquisition setup, where the smartphone is maneuvered around the plant to capture detailed structural data of the plant crown

3   Methods

The proposed approach characterizes physiological and biophysical crop traits by leveraging spectral and structural data obtained from smartphone RGB imagery and LiDAR point cloud data (Fig. 3). RGB imagery processing includes generating reflectance values to account for environmental variations in solar illumination, followed by leaf segmentation and extraction of spectral-reflectance features. Structural feature extraction from LiDAR data involves denoising and segmenting the 3D point cloud to isolate plant data from background objects and noise.

Figure 3: Block diagram of the smartphone-based leaf nitrogen concentration and shoot dry-weight biomass estimation setup for Chinese spinach (Amaranthus dubius). Spectral features derived from smartphone RGB imagery and structural features from LiDAR point cloud data are combined to estimate key crop parameters.

<center>5</center>

3.1 Spectral Data Processing

The inherent sensor-electronic noise present in the measured values was mitigated by performing dark image subtraction on the raw optical smartphone RGB images. A dark image was generated by covering the smartphone's rear camera with a dark cloth. The resulting RGB images were then converted to reflectance values by dividing each digital number (DN) value by the average DN value from a 99.9% white reference image [18].

The individual RGB reflectance images captured during our experiment contained extraneous details, including background objects such as pots and other experimental hardware (Fig. 4a). To minimize estimation errors, accurate delineation of plant leaves from the background was essential. We employed the Mask Convolutional Neural Networks (MaskCNN) algorithm [19] for automatic leaf segmentation, chosen for its precision in identifying leaf structures (i.e., the objects of interest) within images. The CNN was trained on 245 individual leaf images, each carefully annotated by an expert from 150 randomly selected plant images. To enhance dataset size, diversity, and robustness, data augmentation techniques—such as rotations (45°, 90° and 135°) and scalings (0.10, 0.25, 0.50, 0.75, and 1.25) - were applied to each original image, resulting in a total of 2,250 leaf samples for model training.The MaskCNN algorithm used distinct leaf traits such as shape, texture, and color to automatically extract leaf boundaries from the background (Fig. 4b). The output of the MaskCNN segmentation process was a mask layer overlaying the original RGB reflectance image, where pixels corresponding to plant leaves were assigned a value of 1 and background pixels a value of 0. This binary mask effectively isolated the leaf regions from the background by multiplying it with the vegetation spectral index image, providing a clean extraction of the plant leaves in the vegetation spectral index imagery (Fig. 4c).

To evaluate the accuracy of the MaskCNN-based leaf delineation, we used the Intersection over Union (IoU) metric (Equation (1)), calculated by comparing the estimated mask with a manually delineated mask. An IoU value of 1 indicates perfect overlap, while a value of 0 indicates no overlap [20]. MaskCNN segmentation performance was assessed using a set of 245 manually extracted leaves from 25 randomly selected plants across all nitrogen fertigation treatments.

$$IoU = \frac{C \cap C_{gt}}{C \cup C_{gt}} \tag{1}$$

where C denotes a predicted mask area and C_{gt} denotes the manually delineated mask area. An IoU of 1 represents maximum overlap, and an IoU equal to 0 corresponding to no overlap.

The leaf regions identified by the MaskCNN segmentation algorithm were then extracted from the RGB reflectance images to estimate vegetation indices. These segmented leaf regions were used to calculate various vegetation indices that serve as proxies for different plant traits. The RGB spectral indices were quantitative measures derived from plant leaf reflectance values, reflecting their sensitivity to specific plant characteristics, such as chlorophyll content and overall vegetation vigor.

Chlorophyll concentration in leaves is a critical parameter for assessing plant health, as it reflects photosynthetic capacity, growth vigor, and shoot biomass [21, 22]. The Excess Green Index (ExG), Green Leaf Index (GLI), and Normalized Green-Red Difference Index (NGRDI) are commonly used to evaluate chlorophyll content in leaves [23, 24]. The ExG index, calculated by subtracting the red and blue reflectance from twice the green reflectance, is highly responsive

to changes in chlorophyll concentration. The GLI measures vegetation "greenness" by assessing green reflectance relative to other wavelengths [25]. Similarly, the NGRDI, which normalizes the difference between green and red reflectance, also serves as an indicator of chlorophyll concentration.

In addition to chlorophyll content, certain indices are designed to evaluate other leaf characteristics, such as pigmentation, stress, and structure. For example, the Triangular Greenness Index (TGI) [26] and Normalized Difference Yellowness Index (NDYI) [27] are valuable in this regard. Healthier leaves often have certain thicknesses and internal structures that influence light absorption and reflection; therefore, variations in TGI values can indicate differences in leaf morphology, such as thickness or density, affecting light interaction [26]. The NDYI, which measures the difference between green and blue reflectance, provides insights into yellow pigments, suggesting potential stress or senescence [27]. Both indices are instrumental for monitoring vegetation health and detecting stress conditions [28, 29].

In this study, we used a total of 15 widely recognized RGB spectral indices from the literature. Table 1 provides a detailed summary of these RGB spectral indices, including the parameters and calculations used to derive them from the smartphone-based RGB imagery. The average value of all leaf pixels were computed to obtain a plant-level RGB feature estimate for each index.

Table 1: The spectral indices derived from the smartphone RGB imagery of plants.

Index Name	Index Code	Formula	Reference
Green Leaf Index	GLI	$(2G - R - B)/(2G + R + B)$	[25]
Modified Green Red Vegetation Index	$MGRVI$	$(G^2 - R^2)/(G^2 + R^2)$	[30]
Red Green Blue Vegetation Index	$RGBVI$	$(G - R * B)/(G + R * B)$	[30]
Excess Green Index	ExG	$(2G - R - B)$	[31]
Excess Red Index	ExR	$(1.4R - G)/(G + R + B)$	[32]
Triangular Greenness Index	TGI	$-0.5((\lambda_R - \lambda_B)(R - G) - (\lambda_R - \lambda_G)(R - B))$	[26]
Visible Atmospherically Resistant Index	$VARI$	$(G - R)/(G + R - B)$	[33]
Normalized Red Index	NRI	$R/(R + G + B)$	[34]

Index Name	Index Code	Formula	Reference
Normalized Green Index	NGI	$G/(R+G+B)$	[34]
Normalized Blue Index	NBI	$B/(R+G+B)$	[34]
Green Minus Red Index	$GMRI$	$G-R$	[34]
Green Red Ratio Index	$GRRI$	G/R	[35]
Excess Green Minus Excess Red Index	$EGMERI$	$ExGI - ExRI$	[36]
Normalized Green Red Difference Index	$NGRDI$	$(G-R)/(G+R)$	[37]
Normalized Difference Yellowness Index	$NDYI$	$(G-B)/(G+B)$	[27]

R, G, B, are Red, Green and Blue bands, respectively with wavelengths λ_R, λ_G and λ_B

3.2 Structural Data Processing

The LiDAR 3D point cloud obtained from the smartphone provides valuable structural information about the plant canopy (Fig. 4d). Each point in the raw point cloud represents a specific location in three-dimensional space, characterized by its X, Y, and Z coordinates, as well as its R, G and B attribute values. However, the raw point cloud often contains noise which arise from various sources such as suspended particles in the air, glitches in electronics, or errors in data acquisition and processing, this noise is unwanted and termed noisy points. To ensure accurate downstream analysis, it is essential to remove these noisy points from the point cloud. This denoising process involved several steps: a) voxelization: The volume covered by the 3D point cloud was divided into V_q regular cubic voxels, each with sides of equal length (i.e., 1cm), b) point density (PD) calculation: The number of points contained within each voxel was calculated, c) points with a voxel PD below a certain threshold were identified as noisy points and subsequently removed from the point cloud. The threshold value was chosen carefully to minimize both omission (failure to detect noisy points) and commission (incorrectly identifying valid points as noisy) errors. In our case this threshold has been identified to be equal to 4 data points. By implementing this denoising procedure, the resulting point cloud was cleansed of isolated points, ensuring that subsequent analyses, such as vegetation segmentation or structural parameter extraction, were based on reliable and accurate data (Fig. 4e).

The subset of points $G_p \subset P$ which is entirely part of the plant object was identified by using the two-class (i.e., $K = 2$) K-means clustering approach. This clustering method delineates the

background data points from the plant data jointly using the R, G, and B attributes. By clustering the points into two distinct classes, one representing the black background and the other representing the green plant, we can effectively separate the vegetation from other objects in the scene (Fig. 4f). This segmentation process played a crucial role in isolating the plant canopy from the surrounding environment, enabling more accurate analysis and interpretation of the structural parameters derived from the LiDAR point cloud.

Structural attributes encapsulating the physiological characteristics of the plant were derived from G_p. These attributes encompass essential matrices such as plant height, maximum crown span, point density, and crown volume, providing valuable insights into the plant's structural composition. The plant height (HT) was determined as the elevation of the highest point within the plant point cloud G_p. Meanwhile, the maximum crown span (CW), was calculated as the greatest distance between any two points within the point cloud G_p when projected onto the ground plane (X-Y plane), effectively capturing the lateral extent of the plant canopy. To assess the density of the crown (CD), we calculated the average point count within each 1cm voxel containing at least one point. This voxel-based approach provides a robust measure of crown density, offering insights into the spatial distribution of foliage within the plant canopy. The crown volume (VOL) was estimated as the volume enclosed by the convex hull formed around G_p (Fig. 4f). The other structural traits included point count, point density and point density variance. The number of points above 75%, 50% and 25% of the plant height were represented as N_{75}, N_{50} and N_{25}, respectively. By encapsulating the plant canopy within a convex envelope, this metric provides a holistic measure of the plant's VOL, facilitating a comprehensive understanding of the plant structure. The 9 plant-level LiDAR structural features used in the study are defined in Table 2.

Table 2: The structural indices derived from the smartphone LiDAR point cloud of plants.

Index Name	Index Code	Formula
Plant Height	HT	$max(p_i(z)); 0 < i < N$
Crown Width	CW	$max(E(p_i(x,y), p_j(x,y))); 0 < i, j < N$
Crown Volume	CV	V_{Hull}
Point Count	PC	N_p
Point Density	PD	N_p/V_{Hull}
Point Density Variance	CR	$var(V_i^P); i = [1, V_q]$
Point count above 75% height	PC_{75}	$\sum_{i=1}^{N_p} 1(p_i(z) \geq percentile(p_i(z), 75))$

Continued on next page

Index Name	Index Code	Formula
Point count above 50% height	PC_{50}	$\sum_{i=1}^{N_p} 1(p_i(z) \geq percentile(p_i(z), 50))$
Point count above 25% height	PC_{25}	$\sum_{i=1}^{N_p} 1(p_i(z) \geq percentile(p_i(z), 25))$

$E(A, B)$ corresponds to Euclidean distance between points A and B.

V_i^P is the number of points in the i^{th} voxel cell.

Figure 4: (Top row) Top view (a) RGB image of a Chinese spinach plant captured using a smartphone. (b) Spectral index image, with boundaries delineated using Mask-CNN for leaf segmentation. (c) Resulting leaf-segmented image. (Bottom row) (d) 3D LiDAR point cloud of the plant, (e) filtered 3D point cloud after K-means clustering to isolate plant data, and (f) convex hull fitted to the filtered plant point cloud to extract structural features.

3.3 Plant Traits Characterization

Leaf nitrogen concentration and shoot biomass modelling were performed using three machine learning regression modelling techniques including Support Vector Regression (SVR), Random Forest Regression (RF) and Lasso Regression (Lasso), using the RGB spectral features and the LiDAR structural features defined in Table 1 and 2, respectively. The SVR model was used with a linear kernel to accurately model the different plant parameters, for its exception ability to

model underlying relationship in the feature space. Equation (2) shows the objective function and constraints of SVR with the linear kernel.

$$J(w) = \frac{1}{2}.w^T w + C \sum_{i=1}^{n} (\xi_i + \xi_i^*)$$

subject to

$$\forall_i : y_i - (x_i w + b) \leq \epsilon + \xi_i$$
$$\forall_i : (x_i w + b) - y_i \leq \epsilon + \xi_i^*$$
$$\forall_i : \xi_i^* \geq 0$$
$$\forall_i : \xi_i \geq 0$$

$$(2)$$

where, w vector contains the scalar weights associated with individual features in the feature set. ξ_i^* and ξ_i are the slack variables associated with each data point. The C is the hyperparameter which was estimated using grid search on C for the range [1, 100]. The modelling was repeated 100 times using a random set of training and testing sets to identify optimal model parameters. The total available labelled data were divided in to training (70%) and testing (30%) sets.

The RF Regression [38] follows an ensemble learning approach, where multiple decision trees are constructed and their predictions are averaged to obtain a final result. The number of trees in the forest and maximum depth of each tree was set to 100 and 5, respectively.

We also model the plant parameters using the Lasso Regression [39] which is a widely used linear regression technique that incorporates feature regularization to enhance the performance and interpretability of the parameter modelling.

The accuracy assessment of the regression models was quantified using the Mean Error (ME), Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), Relative Root Mean Squared Error (rRMSE), and Coefficient of Determination (R^2) matrices, using the equations below.

$$\text{ME} = \frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{y}_i) \tag{3}$$

$$\text{MAE} = \frac{1}{n} \sum_{i=1}^{n} |y_i - \hat{y}_i| \tag{4}$$

$$\text{RMSE} = \sqrt{\frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{y}_i)^2} \tag{5}$$

$$\text{rRMSE} = \frac{\text{RMSE}}{\bar{y}} \times 100\% \tag{6}$$

$$R^2 = 1 - \frac{\sum_{i=1}^{n} (y_i - \hat{y}_i)^2}{\sum_{i=1}^{n} (y_i - \bar{y})^2} \times 100\% \tag{7}$$

where n is the number of observations, yi is the actual value of the i^{th} observation, $\hat{y}$ is the predicted value of the i^{th} observation, and $\bar{y}$ is the average value of the i observation.

4   Results and Discussion

Fifteen RGB features for individual Chinese spinach (Amaranthus dubious) plants were derived from RGB leaf data, segmented using the MaskCNN algorithm, which achieved a high Intersection over Union (IoU) ratio of 0.92. Additionally, nine LiDAR structural features were estimated from the plant point cloud segment identified through a two-class K-means clustering algorithm. Variations in nitrogen dosing affected all 24 features, each serving as a proxy for specific plant traits or overall stress indicators. For example, RGB spectral features such as the Visible Atmospherically Resistant Index (VARI) and the Modified Green-Red Vegetation Index (MGRVI)-proxies for chlorophyll concentration and greenness—initially increased with nitrogen dosage but declined beyond a certain level. In contrast, indices like the Excess Red (ExR) and the Red-Green-Blue Vegetation Index (RGBVI), which are associated with plant stress, displayed an inverse relationship with nitrogen dosage. Figure 5 illustrates the effect of nitrogen dosage on the RGB spectral and the LiDAR structural feature values.

The visual assessments in Figure 6 provide further insight into the effect of nitrogen treatments. Specifically, plants treated with both the lowest and highest nitrogen dosages exhibited reduced yields in terms of plant height and biomass, suggesting that extreme nitrogen levels may inhibit growth and development in Chinese spinach.

The relationship between nitrogen dosing and individual RGB and LiDAR features was modeled using various functions, including linear, second-order, and third-order polynomials. The second-order polynomial model provided the best fit, effectively capturing the non-linear relationships between features and nitrogen dosage. To address the initially skewed distribution of nitrogen dosages, a square-root transformation was applied, which normalized the distribution and improved the linearity of the modeled relationships. This transformation enhanced the accuracy of plant parameter estimation based on smartphone-derived data. Figure 5 displays second-order polynomial models (dotted blue lines) that illustrate the relationships between various smartphone-derived indices and nitrogen dosages.

Combining RGB spectral and LiDAR structural features offered complementary information on leaf nitrogen concentration and shoot biomass, thereby improving the precision and reliability of crop trait monitoring—especially in indoor greenhouse environments for crops like Chinese spinach. This complementarity is further evidenced in Figure 7, where low correlations are observed between the RGB spectral and LiDAR structural feature sets, while higher correlations are found within each feature set. This finding indicates that RGB imagery and LiDAR data provide unique, complementary insights.

To model three key plant parameters—leaf total reduced nitrogen (TRN) concentration, leaf nitrate (NO_3) concentration, and shoot dry weight (DW)—we employed three machine learning algorithms: Support Vector Regression (SVR), Random Forest Regression (RF), and Lasso Regression. Modeling was conducted using three distinct feature-set configurations: RGB spectral features only, LiDAR structural features only, and A combination of both RGB spectral and LiDAR structural features. This multi-configuration approach allowed us to evaluate the unique contributions of each feature set and their combinations in predicting key plant parameters. Across all feature-set configurations, the RF model consistently performed well, yielding relatively lower Root Mean Squared Error (RMSE) and higher R^2 values compared to SVR and Lasso, particularly when using the combined feature set. Lasso Regression, however, showed high Mean Error (ME) and Mean Absolute Error (MAE) for the structural feature set (e.g.,

Figure 5: Second-order polynomial regression models illustrating the non-linear relationship between (a) RGB spectral features and (b) LiDAR structural features with nitrogen dosage in leaves. A square-root transformation was applied to the independent variable to normalize the initially skewed distribution. The minimum and maximum index values in each plot are indicated by the vertical dashed line.

Figure 6: RGB images of Chinese spinach (Amaranthus dubius) plants treated with varying nitrogen dosages: (a) 20 ppm, (b) 40 ppm, (c) 80 ppm, (d) 120 ppm, (e) 160 ppm, (f) 200 ppm, (g) 400 ppm, and (h) 800 ppm. Scale bars represent 10 cm.

ME of 12.53 g), indicating possible overfitting or instability in Lasso's performance for DW estimation.

Additionally, a clear pattern emerged across the different feature sets: for TRN and NO_3 estimation, the RGB feature set yielded the lowest prediction errors, while for shoot DW, the structural feature set provided the most accurate estimates with the lowest errors. Overall, the results demonstrate the effectiveness of combining RGB imagery and LiDAR data in crop parameter modeling and highlight the robustness of the RF algorithm in managing complex multivariate data. The model estimation performance for TRN concentration, NO_3 concentration, and shoot DW - quantified using ME, MAE, RMSE, relative RMSE (rRMSE), and R^2 values—is provided in Table 3 and Table 4.

Beyond plant parameter estimation, we also focused on determining the optimal nitrogen dosage to maximize plant biomass and vigor using smartphone-derived RGB and LiDAR data. The optimal nitrogen dosage is defined as the dosage level that maximizes or minimizes individual RGB spectral and LiDAR structural features, each serving as a proxy for specific plant traits, such as chlorophyll concentration, leaf senescence, and shoot biomass. Since all smartphone features were modeled using second-order polynomials, peak values of individual features were determined by calculating the second derivative of each polynomial and setting it to zero. This process allowed us to pinpoint the critical nitrogen dosage that optimizes each plant trait. In this study, the optimal nitrogen dosage for Chinese spinach was estimated to be 149.9 ppm. Notably, this value is close to the optimal dosage of 120.0 ppm derived from in-situ transpiration data collected using the PlantArray system, as reported in [16]. The agreement between the smartphone-derived optimal dosage and the dosage estimated through sophisticated transpiration data further validates the accuracy and reliability of our approach using smartphone RGB and LiDAR data. However, it is important to note that [16] did not investigate nitrogen dosages between 120.0 ppm and 160.0 ppm, making precise validation of the optimal nitrogen dosage

Figure 7: Correlation matrix of RGB spectral indices and LiDAR structural indices derived from smartphone RGB imagery and LiDAR data. The matrix illustrates the relationships between different indices, with color intensity indicating the strength and direction of the correlation (red for positive, blue for negative correlations).

challenging with the available data.

A detailed feature relevance analysis was conducted to assess the importance of various RGB and LiDAR-derived features in predicting key target variables: leaf total reduced nitrogen (TRN) concentration, leaf nitrate (NO_3) concentration, and shoot dry weight (DW) biomass. Feature relevance was inferred based on the weights assigned to each feature during Support Vector Regression (SVR) model training. These weights were averaged across 100 modeling iterations, with each iteration using randomly generated training and test data sets to ensure robustness. The results indicate that feature importance varied significantly across models, reflecting the specific demands of each prediction task. For example, models developed to predict TRN and NO_3 concentration assigned higher importance to the RGB features, likely because these spectral indices are closely related to nitrogen content, which affects reflectance in the visible spectrum. In contrast, models estimating shoot DW generally assigned greater weight to structural features obtained from LiDAR data, reflecting that biomass estimation can be more reliably modeled using plant morphology rather than spectral characteristics. Specifically, DW estimation showed high reliance on LiDAR-derived structural indices such as crown volume

(CV) and point count at 75% height (PC_75), which describe the plant's physical structure and distribution. Conversely, for TRN and NO_3 estimation, the models placed more emphasis on spectral features such as the Triangular Greenness Index (TGI) and Excess Green (ExG), both closely related to chlorophyll content and leaf greenness. These findings suggest a clear pattern: LiDAR-derived structural features are more effective for estimating morphological traits like biomass, while RGB features are better suited for predicting physiological traits like nitrogen and chlorophyll concentration. This distinction underscores the complementary nature of smartphone RGB imagery and LiDAR data in crop parameter modeling, with each sensor type contributing uniquely to different aspects of plant structure and function (Fig. 8).

Figure 8: Normalized weights from the Support Vector Regression (SVR) model, indicating the relative importance of each RGB spectral and LiDAR structural feature in estimating leaf total reduced nitrogen (TRN), leaf nitrate (NO_3), and shoot dry weight (DW).

To evaluate our methodology, we compared its performance with a leading state-of-the-art leaf nitrogen concentration estimation approach (SoA-NC) that relies solely on smartphone RGB imagery. This benchmark method uses the Dark Green Color Index $(DGCI)$, derived from intensity, hue, and saturation metrics of the plant leaves [40]. However, using only a single RGB image feature index limits its accuracy in estimating leaf nitrogen concentration. Our results illustrate the superior performance of our models, which consistently produced more accurate and precise estimates of leaf TRN and NO_3 concentrations compared to the SoA-NC method. This improvement highlights the advantage of integrating advanced machine learning algorithms with both spectral and structural features derived from smartphone RGB and LiDAR sensors. Unlike the SoA-NC method, which focuses solely on spectral data, our approach leverages the complementary strengths of RGB features (e.g., color indices) and LiDAR structural features (e.g., plant height and canopy shape).

However, high variance in individual feature index values, even within a nitrogen treatment group, due to non-uniform lighting or shading on plant leaves, is a known source of error, which manifests as large variance in TRN and NO_3 estimates. This suggests that while the proposed method holds significant promise for leaf nitrogen estimation in crop research, its ability to detect fine changes in leaf nitrogen concentration is limited.

We also compared shoot DW estimation performance with a state-of-the-art leaf-area-based shoot DW estimation (SoA-DW) method [41]. The SoA-DW method estimates shoot DW by: (a) segmenting plant leaves using Otsu's thresholding on the green channel, (b) calculating leaf area (LA_p) as the product of the total number of plant pixels (PPN) in the image, the individual pixel length (PL) of the phone camera, and the magnification factor (MF) of the

phone camera, and (c) estimating shoot DW using a linear model based on LA_p and actual DW values obtained from destructive sampling. Our proposed shoot DW estimation method more accurately tracked actual shoot DW compared to the SoA-DW method. The reduced performance of the SoA-DW method likely results from its inability to capture plant height from images and from errors in leaf delineation due to non-uniform lighting and shading.

A direct comparison between the TRN, NO_3, and DW estimates obtained from our non-destructive model and those derived from traditional destructive sampling methods is also provided to further validate the accuracy and reliability of our methodology (Fig. 9). The results demonstrate that the proposed handheld smartphone-based system can accurately estimate leaf TRN, leaf NO_3, and shoot DW without the need for manual harvesting, outperforming state-of-the-art methods that rely solely on RGB data.

Table 3: The ME, MAE, $RMSE$, $rRMSE$, and R^2 for leaf nitrogen concentration estimations done using the SVR, the RF, and the Lasso Regression.

Parameter	Feature Set	MLA	Accuracy Estimates				
			ME $\left(\frac{mgN}{gDW}\right)$	MAE $\left(\frac{mgN}{gDW}\right)$	$RMSE$ $\left(\frac{mgN}{gDW}\right)$	$rRMSE$	R^2
TRN	Spectral	SVR	11.77	1.18	15.31	0.07	0.23
		RF	10.73	0.71	14.42	0.06	0.29
		Lasso	11.00	-0.01	14.10	0.06	0.33
	Structural	SVR	13.77	-1.71	17.01	0.08	-0.02
		RF	10.91	1.24	15.19	0.07	0.22
		Lasso	13.75	-0.07	16.28	0.07	0.10
	Combined	SVR	10.64	-0.25	13.94	0.06	0.37
		RF	10.12	0.53	**13.38**	0.06	0.34
		Lasso	10.12	0.55	13.98	0.06	0.34
NO_3	Spectral	SVR	1.16	-0.27	1.49	0.18	0.21
		RF	1.09	0.08	1.46	0.15	0.24
		Lasso	1.15	0.01	1.45	0.16	0.27
	Structural	SVR	1.46	-0.39	1.94	0.23	-0.25
		RF	1.26	0.17	1.66	0.17	0.01
		Lasso	1.51	-0.03	1.84	0.21	-0.15
	Combined	SVR	1.16	-0.15	1.52	0.17	0.26
		RF	1.09	0.07	**1.46**	0.15	0.27
		Lasso	1.13	0.01	1.47	0.16	0.29

Table 4: The ME, MAE, $RMSE$, $rRMSE$, and R^2 for shoot DW estimation done using the SVR, the RF, and the Lasso Regression.

Parameter	Feature Set	MLA	Accuracy Estimates				
			$ME(g)$	$MAE(g)$	$RMSE(g)$	$rRMSE$	R^2
DW	Spectral	SVR	4.21	0.12	5.12	0.09	0.46
		RF	3.63	0.07	4.73	0.08	0.51
		Lasso	4.07	-0.04	5.06	0.09	0.45
	Structural	SVR	2.81	-0.65	3.58	0.06	0.73
		RF	2.27	-0.03	2.91	0.05	0.82
		Lasso	12.53	-0.12	3.18	0.05	0.78
	Combined	SVR	2.43	-0.44	3.08	0.05	0.80
		RF	2.15	0.04	**2.75**	0.05	0.84
		Lasso	2.29	-0.16	2.82	0.05	0.84

Figure 9: Model estimation performance for (a) plant total reduced nitrogen (TRN), (b) nitrate (NO_3), and (c) dry weight (DW) in Chinese spinach across different nitrogen dosages. Results are shown for the proposed method, state-of-the-art (SoA) nitrogen concentration (SoA-NC) and dry weight (SoA-DW) estimation approaches, with reference data obtained through destructive leaf analysis.

5   Summary and Conclusion

Smartphone-based RGB imagery and LiDAR data show strong potential for modeling the biophysical and structural parameters of Chinese spinach (Amaranthus dubius), serving as a case study for subtropical leafy vegetable crops. The combined use of spectral and structural features derived from smartphone RGB and LiDAR data, integrated with Random Forest regression, enables accurate modeling of leaf nitrogen concentration and shoot dry-weight biomass in Chinese spinach. Experimental results indicate that smartphone-derived RGB and LiDAR data can reliably estimate leaf total reduced nitrogen (TRN), nitrate (NO_3), and dry weight (DW) with average RMSE values as low as 3.9 mg N/g DW, 1.46 mg N/g DW, and 2.7 mg, respectively. Spectral indices were found to be more effective for estimating leaf nitrogen concentration, whereas structural indices provided better performance for shoot biomass estimation. The optimal nitrogen dosage for maximizing yield and fertilizer use efficiency in Chinese spinach was determined to be 149.9 ppm, based on RGB spectral and LiDAR structural features. Future research will focus on expanding the application of this methodology to assess plant requirements for other essential mineral nutrients. The promising results from this study suggest strong potential for industrial-scale implementation, leveraging affordable and accessible smartphone technology. Integration of the approach into automated robotic systems such as gantries and drones has the potential to enable real-time data capture and analysis, providing farmers with convenient, precise insights to optimize fertilizer usage and crop health.

Acknowledgement

The Israel-Singapore Urban Farm (iSURF) is supported by the National Research Foundation, Prime Minister's Office, Singapore, under its Campus for Research Excellence And Technological Enterprise (CREATE) programme [NRF2020-THE003-0008]. This work was supported in part by the Hebrew University of Jerusalem Center for Interdisciplinary Data Science Research (CIDR). We gratefully acknowledge assistance from iSURF program collaborators Netatech Pte Ltd, Singapore and Mr. David Tan.

References

1. Natesh H, Abbey L, and Asiedu S. An overview of nutritional and antinutritional factors in green leafy vegetables. Horticult Int J 2017;1:00011.

2. Cantliffe DJ. Nitrate accumulation in vegetable crops as affected by photoperiod and light duration1. Journal of the American Society for Horticultural Science 1972;97:414–8.

3. Qiu Z, Ma F, Li Z, Xu X, Ge H, and Du C. Estimation of nitrogen nutrition index in rice from UAV RGB images coupled with machine learning algorithms. Computers and Electronics in Agriculture 2021;189:106421.

4. Valkama E, Salo T, Esala M, and Turtola E. Nitrogen balances and yields of spring cereals as affected by nitrogen fertilization in northern conditions: A meta-analysis. Agriculture, ecosystems & environment 2013;164:1–13.

5. Valenzuela H. Optimizing the nitrogen use efficiency in vegetable crops. Nitrogen 2024;5:106–43.

6. Bradstreet RB. Kjeldahl method for organic nitrogen. Analytical Chemistry 1954;26:185–7.

7. Julitta T et al. Optical proximal sensing for vegetation monitoring:Texas Tech Press, Lubbock, Texas, 2015.

8. Sun G, Ding Y, Wang X, Lu W, Sun Y, and Yu H. Nondestructive determination of nitrogen, phosphorus and potassium contents in greenhouse tomato plants based on multispectral three-dimensional imaging. Sensors 2019;19:5295.

9. Lee KJ and Lee BW. Estimation of rice growth and nitrogen nutrition status using color digital camera image analysis. European Journal of Agronomy 2013;48:57–65.

10. Lu N, Wang W, Zhang Q, et al. Estimation of nitrogen nutrition status in winter wheat from unmanned aerial vehicle based multi-angular multispectral imagery. Frontiers in plant science 2019;10:1601.

11. Aranjuelo I, Sanz-Sáez Á, Jauregui I, et al. Harvest index, a parameter conditioning responsiveness of wheat plants to elevated CO_2. Journal of Experimental Botany 2013;64:1879–92.

12. Sun Y, Tong C, He S, Wang K, and Chen L. Identification of nitrogen, phosphorus, and potassium deficiencies based on temporal dynamics of leaf morphology and color. Sustainability 2018;10:762.

13. Gausman HW. Plant leaf optical properties in visible and near-infrared light.Texas Tech Press, Lubbock, TX, USA., 1985.

14. Bar-Sella G, Gavish M, and Moshelion M. From Selfies to Science–Precise 3D Leaf Measurement with iPhone 13 and Its Implications for Plant Development and Transpiration. 2024. DOI: 10.1101/2023.12.30.573617. URL: https://www.biorxiv.org/content/early/2024/10/18/2023.12.30.573617.

15. Lenka S, Singh AK, and Lenka NK. Soil water and nitrogen interaction effect on residual soil nitrate and crop nitrogen recovery under maize–wheat cropping system in the semi-arid region of northern India. Agriculture, ecosystems & environment 2013;179:108–15.

16. Shenhar I, Harikumar A, Pebes Trujillo MR, et al. Nitrogen ionome dynamics on leafy vegetables in tropical climate. 2024. DOI: 10.1101/2024.10.17.618770. URL: https://www.biorxiv.org/content/early/2024/10/21/2024.10.17.618770.

17. Halperin O, Gebremedhin A, Wallach R, and Moshelion M. High-throughput physiological phenotyping and screening system for the characterization of plant–environment interactions. The Plant Journal 2017;89:839–50.

18. Näsi R, Honkavaara E, Lyytikäinen-Saarenmaa P, et al. Using UAV-based photogrammetry and hyperspectral imaging for mapping bark beetle damage at tree-level. Remote Sensing 2015;7:15467–93.

19. Zhang L, Zou L, Wu C, Jia J, and Chen J. Method of famous tea sprout identification and segmentation based on improved watershed algorithm. Computers and Electronics in Agriculture 2021;184:106108.

20. Thoma M. A survey of semantic segmentation. arXiv preprint arXiv:1602.06541 2016.

21. Pavlović D, Nikolić B, urović S, Waisi H, Anelković A, and Marisavljević D. Chlorophyll as a measure of plant health: Agroecological aspects. Pesticidi i fitomedicina 2014;29:21–34.

22. Wagner J. Comparing Chlorophyll Concentrations and Plant Vigor Characteristics Between Strawberry (Fragaria X Ananassa) Accessions. PhD thesis. Acadia University, 2022.

23. Rasmussen J, Ntakos G, Nielsen J, Svensgaard J, Poulsen RN, and Christensen S. Are vegetation indices derived from consumer-grade cameras mounted on UAVs sufficiently reliable for assessing experimental plots? European Journal of Agronomy 2016;74:75–92.

24. Bassine FZ, Errami A, and Khaldoun M. Vegetation recognition based on UAV image color index. In: *2019 IEEE international conference on environment and electrical engineering and 2019 IEEE industrial and commercial power systems Europe (EEEIC/I&CPS Europe)*. IEEE. 2019:1–4.

25. Louhaichi M, Borman MM, and Johnson DE. Spatially located platform and aerial photography for documentation of grazing impacts on wheat. Geocarto International 2001;16:65–70.

26. Hunt Jr ER, Daughtry C, Eitel JU, and Long DS. Remote sensing leaf chlorophyll content using a visible band index. Agronomy journal 2011;103:1090–9.

27. Sulik JJ and Long DS. Spectral considerations for modeling yield of canola. Remote Sensing of Environment 2016;184:161–74.

28. Barton CV. Advances in remote sensing of plant stress. Plant and Soil 2012;354:41–4.

29. Zhang C and Kovacs JM. The application of small unmanned aerial systems for precision agriculture: a review. Precision agriculture 2012;13:693–712.

30. Bendig J, Yu K, Aasen H, et al. Combining UAV-based plant height from crop surface models, visible, and near infrared vegetation indices for biomass monitoring in barley. International Journal of Applied Earth Observation and Geoinformation 2015;39:79–87.

31. Woebbecke DM, Meyer GE, Von Bargen K, and Mortensen DA. Color indices for weed identification under various soil, residue, and lighting conditions. Transactions of the ASAE 1995;38:259–69.

32. Meyer GE and Neto JC. Verification of color vegetation indices for automated crop imaging applications. Computers and electronics in agriculture 2008;63:282–93.

33. Gitelson AA, Kaufman YJ, Stark R, and Rundquist D. Novel algorithms for remote estimation of vegetation fraction. Remote sensing of Environment 2002;80:76–87.

34. Jia L, Bürkert A, Chen X, Roemheld V, and Zhang F. Low-altitude aerial photography for optimum N fertilization of winter wheat on the North China Plain. Field Crops Research 2004;89:389–95.

35. Gamon J and Surfus J. Assessing leaf pigment content and activity with a reflectometer. The New Phytologist 1999;143:105–17.

36. Neto JC. A combined statistical-soft computing approach for classification and mapping weed species in minimum-tillage systems. The University of Nebraska-Lincoln, 2004.

37. Hunt ER, Cavigelli M, Daughtry CS, Mcmurtrey JE, and Walthall CL. Evaluation of digital photography from model aircraft for remote sensing of crop biomass and nitrogen status. Precision Agriculture 2005;6:359–78.

38. Ho TK. Random decision forests. In: *Proceedings of 3rd international conference on document analysis and recognition*. Vol. 1. IEEE. 1995:278–82.

39. Tibshirani R. Regression shrinkage and selection via the lasso. Journal of the Royal Statistical Society: Series B (Methodological) 1996;58:267–88.

40. Paleari L, Movedi E, Vesely FM, et al. Estimating plant nitrogen content in tomato using a smartphone. Field Crops Research 2022;284:108564.

41. Li C, Adhikari R, Yao Y, et al. Measuring plant growth characteristics using smartphone based image analysis technique in controlled environment agriculture. Computers and Electronics in Agriculture 2020;168:105123.