PSTP: Decoding Latent Sequence Grammar for Protein Phase

Separation through Transfer Learning and Attention

Mofan Feng[1,2], Liangjie Liu[1,2], Zhuo-Ning Xian[3], Xiaoxi Wei[1], Keyi Li[1,2],

Wenqian Yan[1,2], Qing Lu[1*], Yi Shi[1,2*], Guang He[1,2*]

1 Bio-X Institutes, Key Laboratory for the Genetics of Developmental and Neuropsychiatric

Disorders, Shanghai Jiao Tong University, Shanghai, China.

2 The Collaborative Innovation Center for Brain Science, and Brain Science and Technology

Research Center, Shanghai Jiao Tong University, Shanghai, China.

3 School of Environmental Science & Engineering, Shanghai Jiao Tong University, Shanghai,

China

* Corresponding author:

Qing Lu: luqing67@sjtu.edu.cn

Yi Shi: yishi@sjtu.edu.cn

Guang He: heguang@sjtu.edu.cn

17
18

Abstract

Phase separation (PS) is essential in various biological processes, necessitating

high-accuracy predictive algorithms for studying numerous uncharacterized

sequences, and accelerating experimental validation. However, many recent

prediction methods face challenges in generalizability due to their reliance on

engineered features. Furthermore, accurately identifying protein regions involved in

PS remains challenging. To address this, we propose PSTP, a model employing a

dual-language model embedding strategy and a lightweight attention module. The

attention layer enables reliable residue-level phase separation predictions, identifying

84% of PS regions in PhaSePro and substantially improving correlation coefficient

compared to existing models. PSTP also demonstrates robust performance in

predicting PS propensity across various types of PS proteins and shows potential for

predicting artificial proteins. By analyzing 160,000+ variants, PSTP characterizes the

link between the incidence of pathogenic variants and residue-level PS propensities.

PSTP's predictive power and broad applicability make it a valuable tool for

understanding biomolecular condensates and disease mechanisms.

Introduction

Biomolecular condensates formed through phase separation (PS) are found throughout eukaryotic cells[1, 2, 3], enabling a wide range of functions across multiple scales[4]. For example, at the molecular level, they regulate biochemical reaction rates such as photosynthesis[5, 6] and mRNA degradation[7], and participate in immune signaling[8, 9, 10] and macromolecule folding[11, 12, 13]. At the mesoscale, condensates organize protein densities at neuronal synapses[14, 15] and the nucleolus[16, 17], and help coordinate DNA damage response[18]. At the cellular level, condensates function to mediate subcellular localization[19, 20, 21, 22], and buffer against stochastic cellular noises[23, 24]. Dysregulation of PS is linked to numerous diseases, including cancer and neurodegeneration[25, 26].

PS is a complex and not fully understood process[27, 28], driven by multivalent interactions involving various physicochemical forces[29, 30, 31, 32, 33]. Both structured regions and intrinsically disordered regions (IDRs) contribute to driving PS[1, 2]. Recent studies on IDR ensembles have revealed a strong relationship between the conformational properties of IDRs, particularly their chain compaction, and their ability to drive PS[34, 35, 36]. Considering the vast amount of uncharacterized sequence data, developing reliable methods to predict PS and identifying the sequences responsible for this process is crucial for advancing our understanding of biomolecular condensates, their functional roles, and the mechanisms underlying disease development.

To predict PS, 'first-generation' algorithms were developed, focusing primarily on specific protein sequence characteristics[29, 37, 38, 39, 40, 41]. More advanced, integrated feature-based models[42, 43, 44, 45, 46] have since been introduced, combining multiple sequence features with novel attributes such as immunofluorescence imaging, post-translational modifications (PTMs), protein-protein interactions (PPIs), and functional annotations. Recently, models have emerged that predict co-phase separation[47] and differentiating PS proteins from those forming amyloids[48, 49].

Nevertheless, many recent high-performing models rely heavily on engineered features from various sources, such as protein annotations and imaging data, which

limits their generalizability to proteins, including variants and isoforms—that lack

such detailed annotations. Moreover, current methods that provide residue-level PS

scores often focus on one or a few specific sequence properties, making it challenging

to accurately predict PS-driving regions due to the complex and diverse sequence

patterns involved. These limitations hinder progress in uncovering key biological

mechanisms and highlight the need for more flexible and broadly applicable models.

To address these critical issues, we developed a model, termed PSTP (**P**hase

Separation's **T**ransfer-learning **P**rediction) (Fig. 1). PSTP utilizes a dual-language

model embedding strategy (Fig. 1A) to process and encode protein sequences.

Specifically, we employ one large language model[50] to extract latent biological

features encoded in protein sequences; along with a modified molecular dynamics

simulations-based language model[34], encoding the sequence grammar underlying the

physical and dynamic conformational properties of IDRs. This sequence-based feature

embedding shows robust performance in predicting both self-assembly PS proteins

and those whose PS behaviors are regulated by partner components, such as other

proteins or nucleic acids (PS-Part proteins).

Importantly, recognizing that PS is often driven by specific regions rather than the

entire protein[51, 52, 53, 54, 55, 56], we developed a lightweight attention-based model

PSTP-Scan, to extract local information from sequence embeddings to focus on these

key regions (Fig. 1C). Using 143 experimentally validated PS regions in PhaSePro[57],

we systematically evaluated existing residue-level PS predictors and found that

PSTP-Scan's attention weights significantly enhance the identification of PS-driving

regions, without specific residue-level training. Notably, it identified 120 out of 143

PS regions, and improved the correlation coefficient to ~150% of that of existing

models.

In addition, we demonstrate the applicability and generalizability of PSTP across

various protein types, such as artificial intrinsically disordered proteins (A-IDPs) and

truncated proteins that undergo PS. Leveraging the high-throughput capability of

PSTP, we characterized the relationship between pathogenicity and protein PS in low

conservation regions, whose variants are much less studied compared to structured

domains, using over 160,000 variants from ClinVar[58, 59]. We believe PSTP will

facilitate a deeper understanding of cellular processes and aid in disease research and

therapeutic development.

PSTP models were designed with ease of use and portability in mind. To ensure low

memory consumption, we implemented a sliding window approach, making the large

language model embedding and prediction within seconds on both standard CPUs and

GPUs. We provide a locally installable version of PSTP, offering full access to the

algorithms. Additionally, a user-friendly web server has been developed that enables

prediction for easy prediction of sequences of interest.

Results

Phase separation proteins and IDR conformational properties

IDRs play important roles in driving protein phase separation[1, 2] (PS), and recent

findings[34, 35] show that their ability to drive PS is closely tied to their degree of chain

compaction. Specifically, compact IDRs favor PS[35, 60], while expanded IDRs disfavor

it[36, 61, 62]. Several sequence features, such as charge distribution[34, 63, 64], hydrophobic[32,

65] patterning and aromatic residue content[32, 34, 35], significantly influence the

compaction of IDRs.

We first investigated different types of phase-separating proteins (PS proteins) and the

conformational properties of their IDRs. We assessed the chain compaction of IDRs in

various PS protein types by predicting their Flory scaling exponent (v)[35], the

conformational entropy per residue (S_{conf}/N)[35], and Aspericity[34] (Fig. 2 A and B),

using models trained on molecular dynamics (MD) simulations data of IDRs. Higher

values of these metrics indicate more expanded conformations, while lower values

represent more compact ones. As expected, IDRs from PS proteins exhibited more

compact conformations compared to those from the background proteome (Fig. 2 A

and B). Notably, IDRs in proteins that self-assemble to form condensates (PS-Self

proteins) are more compact than those in partner-dependent PS Proteins (PS-Part

proteins), whose PS is regulated by partner components. This increased compaction

correlates with the high PS propensity observed in PS-Self proteins. Besides IDRs, PS

can also be driven by structured domains[2, 66, 67, 68], and some proteins undergo PS in

the absence of IDRs[69]. We collected 128 PS proteins that lack IDRs[69] and only

identified 28 IDRs from this group. These IDRs are significantly more expanded

compared to other PS proteins, and even more so than those in the background

proteome (Fig. 2 A and B). This expanded nature may facilitate multivalent

interactions between structured regions that drive PS.

Protein embeddings capture IDR conformational property

In the previous section, we demonstrated the distinct conformational properties of

IDRs across various types of PS proteins. Given that language model-based

embeddings offer great flexibility and generalization in encoding protein sequences,

and considering the relationship between IDR chain compaction and PS, we explored

whether these models can effectively capture the conformational properties of IDRs.

We collected the IDRome[35] dataset, which contains 28,058 IDRs along with the

conformation ensembles generated using CALVADOS[35, 36, 70], an MD simulations

model that shows a high correlation with experimental results. We then assessed

whether language model-based embeddings could capture meaningful latent

information related to sequence chain compaction by applying these methods to the

IDRs. This was tested by visualizing the embedding representations for these

sequences.

We first selected and colored extremely compact IDRs ($v < 0.45$, n = 599) and

expanded IDRs ($v > 0.60$, n = 469) (Fig. 2C). Representations generated by the large

language model ESM-2[50] were able to distinguish between compact and expanded

IDRs (Fig. 2D). Specifically, the visualization of the embedding space clearly shows

that sequences are clustered into distinct groups, as demonstrated by both the smallest

version of ESM-2 (8 million parameters) and the larger 650-million-parameters

version. More pronounced distinctions were observed in the hidden output layer of

ALBATROSS[34], a deep neural network trained on MD simulation data (Fig. 2D,

'ALBATROSS').

We next evaluated the word2vec skip grams approach[71] (Method), which was adopted

in several PS prediction methods such as PSPredictor[72], DeePhase[43] and PSPHunter[44].

In contrast, we observe no significant differentiation between compact and expanded

IDRs with this approach (Fig. 2D, 'Word2vec'). We also visualized the vectors

generated by an engineered-based approach based on van Mierlo et al.[42], which

considers amino acid composition, several dozen biophysical properties, and sequence

low-complexity properties (a total of 52 features). We found that while compact and

expanded IDRs are somewhat separated, the distinction is not significant as they still

form overlapping clusters (Fig. S1). This shows the difficulties of engineered features

for capturing the conformational information of IDRs.

We then divided the IDRs based on conformational entropy per residue (S_{conf}/N),

which is strongly correlated with v. Using this metric, we classified IDRs as compact

($S_{conf}/N < 10$, n = 7,019) or expanded ($S_{conf}/N > 10.25$, n = 4,412) (Fig. 2E). The

results were consistent with those observed using v (Fig. 2F). These findings suggest

that embeddings generated from both MD-based language models and the large

language model capture meaningful information about IDRs, particularly with regard

to chain conformational properties.

Transfer learning contributes to phase separation prediction

Leveraging the conformational properties of IDRs and the underlying information

decoded by protein large language models, we propose a residue-level protein feature

embedding method (Fig. 1A). Specifically, for a given protein, we encode the IDRs'

chain conformation information by extracting the hidden layer outputs for three

sub-ALBATROSS models trained on MD data to predict radius of gyration (Rg),

end-to-end distance (Re), and asphericity, respectively. These outputs were

concatenated to form a sequence-length×330-dimension matrix (IDR conformation

feature). In parallel, we incorporated the residue-level layer representations from the

ESM-2 model (8-million-parameters version), resulting in a

sequence-length×320-dimensional matrix (large language model feature). To reduce

memory and computational demands associated with long-distance attention

calculations, a sliding window approach was applied for sequences longer than 256

residues (methods). By combining the outputs from ALBATROSS and ESM-2, we

generated a sequence-length×650-dimension feature matrix, referred to as PSTP

(**P**hase **S**eparation's **T**ransfer-learning **P**rediction) embeddings.

To assess PSTP embeddings' effectiveness in encoding essential information for PS

proteins, we first averaged the embedding matrix along the residue dimension (Fig.

1B). Using curated data from PhaSePred[45], we trained and evaluated Logistic

Regression (LR) and Random Forest (RF) models with default parameters to test the

embeddings' predictive power (Fig. 1B).

Cross-validation results show that PSTP embeddings achieved median AUCs of ~0.89

and ~0.80 with PSTP-LR for PS-Self and PS-Part, respectively, (Fig. 3A and B, S2A)

demonstrating predictive ability across PS proteins from various species. To assess

whether our dual-language embedding approach captures sufficient information, we

tested its performance by adding both the word2vec embeddings and engineered

features evaluated in the previous section. We observed that incorporating these

features, or using them independently, did not improve performance, in some cases,

even reduce it, as shown through cross-validation and independent testing with both

LR (Fig. 3A) and RF (Fig. S2A). This shows the capability of PSTP embedding.

Notably, using only the IDR conformational feature (330-dimension vector) yielded

only an average AUC of 0.81 for predicting PS-Self proteins and 0.72 for PS-Part

proteins (Fig. S2C). Excluding IDR conformation features resulted in a significant

performance drop across both cross-validation and the test set, underscoring the

critical role of IDR conformational features in predicting PS (Fig. 3B).

Next, we independently validated PSTP-LR using the same training and independent

validation set as PhaSePred, a state-of-the-art PS predictor. The SaPS-10 and PdPS-10

version of PhaSePred are meta-predictors that integrate multiple sequence-based

algorithms, and multidimensional features such as immunofluorescence imaging and

PTMs. Without additional feature selection or hyperparameter tuning, and using the

sequence as the sole input, PSTP-LR achieved predictive accuracy comparable to

SaPS-10 for PS-Self proteins, while showing an improvement in AUC (a 3% increase

to PdPS-10) for predicting human PS-Part proteins (Fig. 3C). This PSTP-LR model

also outperformed PhaSePred-10 on the hPS-test set, whether trained with PS-Self or

PS-Part data (Fig. 3C, right panel).

The sliding window embedding approach with a length threshold of 256 residues for

long sequences, did not lead to significant performance reduction. Increasing this

threshold to 1024 residues (the maximum length during ESM-2 training[50]) showed no

markedly accuracy gains (Fig. S2D), confirming the robustness of our initial

configuration for handling longer sequences.

We further assessed PSTP's performance in predicting membrane-less organelles

(MLOs) participants localized to various intracellular locations using known

MLO-associated protein datasets. These participants likely undergo PS or co-phase

separation with other proteins to form MLOs. PSTP trained to predict PS-Part proteins

demonstrated strong performance in identifying these proteins (Fig. S2F).

The high predictive accuracy underscores the significance of conformational features in

PS and demonstrates the capability of pre-trained language models to capture the latent

sequence grammar essential for PS.

Model architecture of PSTP-Scan

In the previous section, the residue dimension-averaged PSTP embedding vectors

showed robust performance. Since PS is often driven or regulated by one or a few

specific regions within a protein, we suggest that leveraging the averaged feature

vector of these local regions, rather than the full protein, may capture important

information about these PS-prone areas. Drawing inspiration from image-based

spatial attention neural networks, which generate attention scores for each pixel using

local contextual information[73, 74, 75, 76], we developed a model architecture named

PSTP-Scan. This architecture provides attention scores that reflect residue-level PS

profiles while simultaneously predicting the overall PS propensity of the protein.

For each sequence, the PSTP-Scan model takes the sequence-length×650-dimension

PSTP feature matrix as input. The attention weight for each residue position is

generated using a convolution-like operation. This involves processing a local

window of features around each position through an average pooling layer, followed

by a trainable shared-weights two-layer multilayer perceptron (MLP) kernel (Fig. 1C,

Method). The sequence-length unnormalized vector serves as the residue-level

attention score.

The maximum attention weight represents the PS propensity of the region most likely

to undergo PS, serving as the predicted PS propensity for the protein. This value is

also used to update the shared-weights MLP through backpropagation during training,

while the full vector of attention weights provides residue-level PS predictions.

Given that the lengths of PS-driving regions vary from tens to hundreds of residues

(Fig. 4A), during training, the model employs multiple window sizes for the MLP

kernel to capture information at different scales, enhancing robustness (Methods, Fig.

S3C).

253 PSTP-Scan provides reliable PS prediction

Comparable to PSTP-LR, PSTP-Scan model also achieves robust performance in

predicting both PS-Self and PS-Part proteins (Fig. S2E). This demonstrates that

focusing solely on the most influential regions does not compromise the overall

predictive accuracy.

To further evaluate PSTP's robustness, we utilize a PS dataset curated by a more

recent study[44]. The dataset ('Mix' dataset) consists of three PS sub-datasets,

comprising a total of 892 PS proteins curated from various sources, including

LLPSDB[77], PhaSepDB[78], DrLLPS[79] and PhaSePro[57], along with a background dataset

of 8897 single-domain human proteins.

After applying CD-Hit[80] to remove redundant sequences with a 0.4 threshold, we

obtained a human-specific PS protein sub-dataset containing 136 proteins and a

background set of 6259 human proteins ('Mix' test set), which served as the

independent test set. We also obtained 375 PS proteins and 17,288 background

proteins from other species, which were utilized as the training dataset ('Mix' training

set, Methods).

PSTP-LR, PSTP-RF and PSTP-Scan all demonstrated strong performance in

distinguishing human PS proteins from the human background proteins (Fig. 3D and F, Fig. S2G). We also evaluated individual the performance of a single PSTP-Scan block with different window sizes and observed consistently robust results (Fig. S2H), showing the robustness of PSTP-Scan, and insensitivity to window size variation.

We then conducted a head-to-head comparison of PSTP-Scan with current representative PS methods, excluding proteins used in the training datasets of those methods from the evaluation. The methods compared included PhaSePred[45], which utilizes multi-dimensional integrated features; DeePhase[43], which combines a word2vec language model with engineered features; PLAAC[37, 38], which predicts prion-like propensities; PSAP[42], which utilizes engineered biochemical and biophysical features; and ParSe[41], a structure-based PS predictor. For comparison with PSPHunter[44], we constructed features following its sequence encoding method. Additionally, we evaluated other sequence-based predictors, including catGRANULE[39], FuzDrop[40] and PScore[29]. PSTP-Scan achieves an AUC of ~0.9 for all comparisons, better than these representative methods (Fig. 3 E and G).

These findings demonstrate that by leveraging large language models and deep learning models that encode IDR conformation information, PS-related features can be efficiently embedded. This approach provides a reliable and simplified method for PS prediction using only protein sequences as input.

The training and testing datasets in this section were combined together to form a 'Mix' dataset, that we used to train PSTP (Mix) model. We also trained a PSTP (SaPS) model using the PS-Self dataset as well as a PSTP (PdPS) model using the PS-Part dataset.

PSTP-Scan improves identification of PS driving region

To evaluate PSTP-Scan's ability to predict PS-driving regions at the residue level, we assessed the residue-level PS scores (the attention layer output) generated by PSTP-Scan (Fig. 1C). We utilize the experimentally validated PS regions documented in the PhaSePro[57] database, derived from proteins across different species. Although PSTP-Scan's training did not involve any residue-level information about PS regions,

we specifically trained each sub-model evaluated here (SaPS, PdPS and Mix) after

excluding proteins already included in the PhaSePro database (Fig. S4A) to avoid

potential self-validation.

We found that, out of 143 experimentally validated PS regions documented in

PhaSePro, 120 overlapped with the PSTP-Scan's PS regions, which is a notable

improvement over the 109 overlaps achieved by FuzDrop, a model directly trained on

PhaSePro PS regions (Fig. 4B, Fig. S4 C and D). In terms of amino acid-level overlap

between predicted PS and experimentally validated regions, PSTP-Scan recovered

28,378 residues, compared to 25,014 residues recovered by FuzDrop (Fig. 4B, Fig. S4

C and D). Furthermore, PSTP-Scan outperformed PSPHunter, a method recently

reported to predict key regions for PS (Fig. S4 C and D).

Next, we systematically compared PSTP-Scan with other residue-level PS predictors

in discerning PS regions. T-test statics showed that, compared to other predictors,

PSTP-Scan has the strongest discriminative power in distinguishing residues located

in PS driving regions from those in non-PS regions within PS proteins (Fig. 4C).

Additionally, we computed the Spearman correlation between the residue-level scores

of each predictor and the experimentally validated PS regions in PhaSePro (where a

position is assigned 1 if it belongs to a PS region and 0 if not) (Fig. 4D). We

calculated both the overall Spearman correlation and protein-specific correlations for

each protein. PSTP-Scan achieved significantly higher correlations compared to other

predictors, reaching approximately 150% of FuzDrop's performance. In terms of

protein-specific correlation, PSTP-Scan also demonstrated much higher performance

over other methods (Fig. 4E and Fig. S4B).

In Fig. 4 F and G, and Fig. S5, we present examples of the PSTP-Scan prediction

results. The Scan-SaPS model, trained on PS-Self proteins, identifies regions that

drive PS, such as the low-complexity domain (LCD) repeats in cortactin[53], and the N

terminus IDR of Ddx4, which contains containing repeating net charge block and FG,

RG blocks[81]. The Scan-PdPS model, trained on PS-Part proteins, outperforms

Scan-SaPS in predicting PS-driving regions that rely on interactions with partners.

This includes the phosphotyrosine motif of the Nephrin and the proline-rich domain

of N-WASP (Fig. 4G) which form multivalent interactions with the SH2 and SH3 domains of NCK, respectively[55]. For proteins that contain both RNA-recognition motifs (RRMs) and LCDs, such as PAB1[52] and Nab3[54], Scan-PdPS identifies the RRMs, while Scan-SaPS focuses on the LCDs (Fig. 4G).

We next extracted records for PS-Self and PS-Part proteins, and found that PSTP-Scan achieves an overall correlation of 0.4 for PS-Self proteins (58 records, Fig. S4 E and H), second is PLAAC, a method to screen prion-like regions. All models showed significantly reduced performance for PS-Part proteins, with PSTP-Scan still performing the best (50 records, Fig. S4 F and I). Lower performance for PS-Part proteins may result from some protein-protein interaction sites are also denoted as PS-regions in the PhaSePro database, the prediction of which requires prior knowledge of specific protein interactions. For instance, PSTP-Scan did not predict the tri-RG motif in Buc that interacts with the regulator Tdrd6a[82], but successfully predicted the prion-like domain responsible for Buc's self-assembly[51] (Fig. S5B), which is absent in the PhaSePro database. Similarly, while PSTP-Scan predicted the tandem repeats for the scaffold protein EPYC1, neither PSTP-Scan nor FuzDrop predicted the alpha-helices of Rubisco that bind to EPYC1[56] (Fig. S5C). Incorporating models that focus on predicting protein-protein interactions may provide better insights into these types of PS mechanisms.

The limited performance of current methods may also stem from the highly flexible definitions of PS-driving segments or key regions. For example, PSTP-Scan achieves a 0.43 correlation with PS regions identified by NMR experiments (Fig. S4 G and J), significantly higher than the overall correlation. Nevertheless, given that PSTP-Scan predicts diverse PS-driving regions without being specifically trained on distinct PS regions, its ability to directly generate these predictions effectively demonstrates its validity, offering detailed insights into protein PS behavior.

PSTP-Scan provides a broader range of prediction

Studying truncated proteins is essential for understanding protein function and pathogenicity, as NMD-escaping mutations that fail to trigger NMD often result in the

expression of truncated proteins[83]. We evaluate PSTP-Scan as well as other

sequence-based predictors on a test dataset of 93 experimentally truncated PS proteins

and 242 non-PS proteins by collecting data from a recent study[84]. To avoid

information leakage, each PSTP model evaluated here (PSTP-SaPS, PSTP-PdPS and

PSTP-Mix) was specifically trained by excluding proteins corresponding to the

protein fragment in the test dataset from the training dataset (Fig. S6A). We predicted

these proteins using PSTP-Scan as well as PSTP-Scan's MLP kernel, and evaluated

their performance (Fig. 5B and Fig. S6B). We observed that compared with other

representative sequence-based predictors, PSTP achieves the highest performance in

both AUC and AUPR (Fig. 5B), while the MLP kernel from the PSTP-Scan (Mix)

achieves the best performance at an AUC of 0.88 (Fig. 5B). This demonstrates

PSTP-Scan's robustness and effectiveness in predicting PS in truncated proteins.

In addition, a recent study[85] designed artificial intrinsically disordered proteins

(A-IDPs) to investigate the influence of amino-acid sequence patterns on the

regulation of PS. This study created 11 artificial polypeptides based on prior

knowledge from earlier research[86, 87], each consisting of a 200-residue sequence

formed by repeating an octapeptide 25 times, which exhibited PS at micromolar

concentrations. Most of these A-IDPs underwent PS at room temperature, while some

required higher temperatures.

The PSTP-Scan (Mix) kernel assigned high scores to these peptides. To compare, we

generated 10,000 random background proteins by truncating 200-residue segments

from UniProt-reviewed proteins. All models, except PLAAC, significantly

distinguished A-IDPs from these background proteins, highlighting the unique

sequence properties of the A-IDPs (Fig. 5C). However, PSAP produced relatively low

scores, that failed to predict these peptides. Next, we generated control peptides by

randomly repeating octapeptides 25 times, using the same amino acid composition as

the A-IDPs (Fig. 5C, AA-weighted random). Interestingly, PSTP-Scan predicted

lower scores for these control peptides (p-value = 0.0085), while other predictors did

not show significant differences. This indicates that PSTP-Scan understands these

A-IDPs by capturing information on both amino acid composition and the specific

order of residues.

Both results indicate PSTP-Scan's sensitivity to sequence information and its

predictive power across a broad range of proteins. Leveraging the high-throughput

nature of PSTP, we predict over 42,000 proteins in the human proteome, including

canonical and isoforms, as well as over 570,000 Uniprot-reviewed proteins. We found

that approximately 35% of human proteome and isoform proteins, and 27% of

UniProt-reviewed proteins, contain potential PS regions (PSTP-Scan residue-level

score > 0.5) (Fig. 5E). This proportion increases to 39% and 35%, respectively, when

restricted to proteins with at least one IDR (Fig. 5F).

Improved prediction of PSP that lack IDRs

To address the high disorder propensity (Fig. S7A) of current PS datasets, we also

developed a predictor focused on PS scaffolds and regulators that lack IDRs. Utilizing

a curated dataset from PSPire[69], which includes 128 PS proteins and 10,251

background proteins, we trained and evaluated a PSTP-LR and a PSTP-RF model.

Compared to PSPire, which utilizes structural information from AlphaFold2[88], the

PSTP models demonstrated greater robustness and reliability, achieving a ~50%

increase in AUPR (Fig. S7B and C).

Incidence of pathogenic variants

Evolutionary conservation is currently a major factor in interpreting disease variants

[89, 90, 91, 92, 93], and using this feature alone can predict the majority of known

pathogenic variants[92]. IDRs tend to be less evolutionary conserved and lack fixed

structures in comparison to structured and functionally essential regions[1]. As a result,

studies on the pathogenicity of IDR variants have progressed slowly, leaving

numerous variants of uncertain significance (VUSs) (~ 530,000, ~52% of ClinVar

VUSs) unsolved in IDRs. Given the role of low-complexity IDRs in driving PS, we

investigate the potential relationship between PS-driving propensity and the incidence

of pathogenic variants in these low-evolutionary-conserved IDRs.

We analyzed PSTP-Scan residue-level scores for ClinVar variants located in

low-conservation IDRs, defined by AlphaFold2 pLDDT score (pLDDT < 50) (Fig.

6A). The pLDDT scores, which reflects AlphaFold2 prediction confidence and is highly correlated with evolutionary conservation, is considered a state-of-the-art predictor for IDRs[35, 94]. We obtained 4756 pathogenic and 37,291 benign variants, and observed that, compared to benign variants, pathogenic variants tend to be located in positions with higher residue-level PS propensity (Fig. 6B). All sub-models of PSTP-Scan detected this difference, with Mann-Whitney p-values below 1×10^{-10}. Examples of pathogenic IDR variants located in high-PS regions (above 0.8 in any PSTP-Scan sub-model) include P39L in HSPB1[95, 96], F89I in DNAJB6[97], and A315T in TARDBP[98, 99], associated with Charcot-Marie-Tooth disease type 2 (CMT-2), limb-girdle muscular dystrophy type 1D (LGMD1D), and amyotrophic lateral sclerosis (ALS), respectively. These variants promote abnormal protein aggregation[95, 97, 98] but are predicted as either VUS or benign by EVE[92], an evolutionary-based top-performance pathogenicity predictor.

A similar residue-level score distribution was observed for variants located in IDRs defined by IUPred3 (IUPred score > 0.5) (Fig. S6E). However, this distinction was weaker, possibly due to that IUPred-predicted IDRs also include evolutionary conserved IDRs[94]. Next, we evaluated this correlation based on allele frequency (AF), as variants with very low AF are likely to be pathogenic, while highly frequent variants are less likely to be[100, 101]. We collected variants from gnomAD V4.1.0 and found that, within low conservation regions, variants with low AF (AF < 1×10^{-5}, 3,841,613 variants) tend to be located in positions with higher residue-level PS score region than variants with higher AF (AF ≥ 0.001, 25,673) (Fig. S6 D and F). In contrast, this correlation between PS and disease was not observed for variants located in structured regions (pLDDT ≥ 70) (Fig. S6C), where pathogenicity is influenced by factors including protein evolution and function.

We observed that within the disordered regions, particularly those with high phase separation (PS) propensity, glycine mutations are the most prevalent (Fig. 6 C and D), including neurodegeneration-related mutations such as G294V[102] and G298S[103] in TARDBP. These mutations, which replace Glycine with more rigid or charged residues, may alter the dynamics provided by Glycine and disrupt the original

multivalent interaction pattern of specific key PS regions.

Our findings suggest that alterations in PS driving regions, are on average, more likely

to lead to be pathogenic than alternation in non-PS regions, even though these PS

driving regions are evolutionary less conserved.

In addition to missense variants, we also extracted 17,304 protein-altering variants,

including nonsense, in-frame deletions, and frameshift variants (Fig. 6E). We

computed the change in PSTP-Scan scores before and after mutation, and compared

the distribution of these changes between pathogenic and benign variants using a

two-sample KS test. We observed that pathogenic variants are more likely to alter PS

propensity than benign variants, as indicated by the significant p-values of the KS test

(Fig. 6F). This trend holds true both for the entire dataset (Fig. 6F) and when

considering only the most frequent in-frame deletion mutation type (Fig. S6 G-I).

Our findings suggest that altering in PS driving regions, even in less-conserved

disordered regions, are factors that contribute to pathogenicity. Combining effect on

PS with traditional structure- and function-based pathogenicity analyses may enhance

our understanding of disease mechanisms.

Discussion

Protein language models have made significant progress in recent years. ESM-2 is a

sequence-input-only encoder that provides a much faster and more flexible encoding

compared to AlphaFold2[88], which relies on computationally intensive multiple

sequence alignments (MSAs). Although language-model-based embeddings may be

less interpretable than engineered features, they capture comprehensive sequence

characteristics more objectively, thus improving generalizability. Recent research

shows the potential of the large language model in predicting PS[49, 104]. For broader

applicability, we used the smallest version of the ESM-2 model and employed a

sliding window approach to reduce memory usage, as its performance already

demonstrates the effectiveness of the proposed approach.

While language models can extract rich evolutionary information from sequences,

intrinsically disordered regions (IDRs) are relatively less conserved. Recent studies

suggest that, while IDRs may undergo significant sequence variation throughout

evolution, they can maintain stable conformational properties[34, 35]. Therefore, we

consider that the conformational information of IDRs, which is closely linked to phase

separation (PS) propensity, might be better captured by models specifically trained

using MD simulation data. To address this, we designed an embedding approach that

utilizes a pre-trained long short-term memory (LSTM) neural network to encode the

dynamic properties of IDRs. While both types of embeddings alone can provide PS

predictions using traditional machine learning models like logistic regression or

random forest, their combination performs significantly better, confirming the

effectiveness of our dual-language model embedding.

Unlike existing predictors such as FuzDrop[40] or PScore[29], which employ supervised

learning models trained at each residue position, PSTP-Scan was trained without

incorporating residue-level PS information, allowing it to learn autonomously. Due to

the highly flexible definitions of PS-driving or regulating regions, the performance of

current methods is often limited. However, PSTP-Scan's design, which leverages

local sequence information, makes it successfully predicts many PS driving segments,

outperforming other models, and providing important insights into numerous

uncharacterized sequences. PSTP-Scan also provides accurate protein-level PS

prediction by focusing on the local region most likely to drive PS, aligning with the

role of PS-driving regions in facilitating multivalent interactions with other protein

regions[51, 52, 53, 82, 105, 106].

Given that the training data size for phase-separating proteins is relatively small

compared to other deep learning fields, to prevent overfitting, we avoided using

overly complex deep models like transformer-based attention layers with

query-key-value mechanisms[107]. We also chose not to use attention weights from the

ESM-2 model, as they may emphasize structural and functional regions, introducing

potential noise. Instead, we constructed an attention calculation method where only

the weights of a multilayer perceptron (MLP) network are trainable.

To better handle dataset imbalance caused by using a large 'background dataset' as

negative samples—a common training approach for current PS predictors[42, 43, 44, 45, 69],

we prevented the neural network from fitting the same data in every iteration.

Specifically, in each epoch of PSTP-Scan training, we randomly select a small subset of

proteins from the background dataset to serve as the negative dataset. This

randomization helps prevent overfitting on background proteins that have not been

experimentally confirmed as non-PS.

The disordered nature of IDRs not only makes the interpretation of their variants

challenging but also limits the effectiveness of evolutionary or structure-based variant

effect predictors like EVE[92] or AlphaMissense[101]. This hinders the discovery and study

of pathogenic variants. Our results reveal a link between the pathogenicity of

low-conservation IDR variants and PS. Diseases related to PS often involve both

abnormal protein aggregation and may also be linked to dosage effects[84]. To better

interpret these variants' pathogenicity, advanced methods are needed to capture and

understand the evolution of IDRs, given their sequence divergence yet conformational

conservation[34, 35].

Biomolecular condensates perform essential cellular functions through complex and

diverse interaction patterns. With its high performance, robustness, and sequence-only

input nature, PSTP serves as a reliable tool for predicting biomolecular condensate

formation. We believe PSTP will support a deeper understanding of cellular processes,

aiding in disease research and therapeutic development.

Methods

IDR conformational property

Visualizing space distribution of IDRs of different properties

We collected curated datasets from several sources: self-assembly PS proteins (SaPS)

(201 proteins), partner-dependent PS proteins (PdPS) (327 proteins) as well as

non-redundant multi-species background proteins (60,220 NoPS proteins) from

PhaSePred[45]. PS proteins that lack IDRs were collected from PSPire[69] (128 proteins).

In addition, we grouped PS proteins from several literatures[44, 45, 69] to obtain a 'Mix

PSPs' group (811 proteins after removing redundancy). For each group, we adopted IUPred3[108] to predict residue-level disorder scores for each protein, following a process similar to Tesei et al.[35] to filter IDRs. Specifically, residues with IUPred3 scores ≥ 0.5 were first labeled as disordered and those < 0.5 as folded. Regions shorter than ten residues were classified as gaps. These gaps were labeled as disordered if they were either flanked by disordered regions or terminal and adjacent to disordered regions. IDRs shorter than 30 residues or exceeding 1,500 residues were discarded.

The SVR model developed by Tesei et al.[35] (https://github.com/KULL-Centre/_2023_Tesei_IDRome) is used to predict v and S_{conf}/N of IDRs. ALBATROSS developed by Lotthammer et al.[34] (https://github.com/idptools/sparrow) is used to predict the asphericity of IDRs.

The predicted conformational properties were compared between different IDR groups using the two-sided Mann–Whitney U test.

Visualizing space distribution of IDRs of different properties

The set of 28,058 IDRs used for visualization, along with their conformational properties generated by MD simulations[35], were obtained from (https://sid.erda.dk/cgi-sid/ls.py?share_id=AVZAJvJnCO). Each IDR was vectorized using two models from ESM-2[50]: esm2_t6_8M_UR50D and esm2_t33_650M_UR50D, which output metrics with dimensions of sequence-length$\times 320$, and sequence-length$\times 1280$ respectively. Each matrix was then averaged into vectors of lengths 320 and 1280 for each IDR.

Additionally, a trained word2vec embedding method[109] based on the skip-gram model was tested. The outputs for all contiguous 3-mer sequences of each IDR were summed to form a 100-length vector, which was also averaged to mitigate the impact of sequence length.

To evaluate the embeddings generated by ALBATROSS, we concatenated the hidden layer outputs from three sub-models for each input IDR into a sequence-length$\times 330$-dimensional matrix (see the 'Feature Engineering' section for more details) and averaged it to obtain a 330-dimensional vector.

Dimensionality reduction was performed using the UMAP algorithm, implemented

565   through the Python 'umap' package.

PS proteins dataset

Self-assembly PS and partner-dependent PS datasets

We utilize the curated datasets used for training and evaluating PhaSePred[45], which

were obtained from the supplementary materials provided with its published literature.

A total of 201 SaPS proteins, 327 PdPS proteins, and 60,220 NoPS background

proteins were collected. The acquired data included training and cross-validation (CV)

datasets: SaPS (128 proteins), hSaPS (59 proteins), PdPS (214 proteins), hPdPS (96

proteins), NoPS (48,158 proteins), hNoPS (8801 proteins). The independent test sets

comprised SaPS-test (73 proteins), hSaPS-test (34 proteins), PdPS-test (113 proteins),

hPdPS-test (60 proteins), NoPS-test (12,062 proteins), hNoPS-test (2,200 proteins),

PS-test (53 proteins), hPS-test (23 proteins).

Additional dataset for independent validation

To build an additional validation set, we utilize a PS dataset curated by a more recent

study[44]. Among this data collection, we utilized the 'hPS167' datasets containing 167

human-specific PS proteins along with human background proteins as the independent

test dataset, and the remaining PS proteins along with non-human background

proteins as the training dataset. After reducing the sequence redundancy by CD-Hit at

a threshold of 0.4, we obtained 136 human PS proteins, 375 non-human PS proteins

and 6280 human background proteins. According to the ratio of non-human to human

PS proteins, we randomly selected 2.75 times the size of the human background

proteins from the NoPS dataset (60,220 proteins) proteins and obtained 17,270

proteins (PS proteins were filtered out). We next filtered both background proteins to

ensure they were not longer than the longest human PS proteins (5,537 length), we

finally got 6259 human background proteins and 17,268 non-human background

proteins.

Feature engineering

Feature embedding with protein large language model:

We adopted two embedding matrices for each protein. The first matrix is the

embedding computed by ESM-2[50], we applied the esm2_t6_8M_UR50D (ESM2-8M

in   short)   from   the   python   'esm'   package:

(https://github.com/facebookresearch/esm/tree/main.)   ESM2-8M takes sequence as

input and the sixth representation layer is output to return a 320-dimension vector for

each position within each sequence. For each sequence, to reduce excessive memory

usage as well as reduce the time required for long-distance attention computing, we

apply a sliding window process similar to AlphaFold2[88] and AlphaMissense[101] when

dealing with long sequences. Specifically, we applied a 256-length sliding window to

scan through the sequence with a step size of 50 (For example, given a 520-length

sequence, the sliding windows would be positioned at [1, 256], [51, 306], …

[251,506], [265, 520]). For each residue position, if it appears in more than one

window, we applied the residue embedding vector from the sliding window in which

the position is most centered (farthest from both edges).

The speed of ESM2-8M is much faster compared to other ESM-2 versions on both

CPU and GPU. Take an AMD Ryzen 7 3700X 8-Core Processor 3.7 G Hz CPU

combined with 16 G memory as an example, for each 256-length-sequence (single

sequence   each   batch),   an   average   of   3.47   seconds   is   required   for

esm2_t6_8M_UR50D, while only an average of 0.11 seconds is required for

esm2_t6_8M_UR50D (ESM2-8M). This makes it easier and faster for users to predict

sequences using PSTP.

Feature embedding with ALBATROSS:

The second embedding approach we adopted is the ALBATROSS program[34]

(https://github.com/idptools/sparrow). ALBATROSS is trained with MD simulation

data of IDRs, and contains pre-trained LSTM-BRNN models to predict conformation

properties. To capture as much conformational information as possible, we adopted

three   ALBATROSS   submodels: the   'asphericity'   model,   the

'radius_of_gyration_scaled' model, and the 'end_to_end_distance_scaled' model.

These three models share the same structure.

For each model of the three models, a protein sequence is inputted, and the hidden

layer output of each timestep was adopted as the ALBATROSS embedding for each

protein position, which returns a sequence-length×110-dimension vector for each

input sequence. These values range from -1 to 1. The vectors are then concatenated to

a sequence-length×330-dimension for each input sequence.

Traditional machine-learning models

Two traditional machine learning models were applied to evaluate the feature

embeddings we constructed. We applied a 'LogisticRegression' model using the

'linear_model' module and a 'RandomForestClassifier' model using the 'ensemble'

module from the Python Sci-kit learn package. Both models were set with parameter

class_weight = 'balanced' and other parameters were kept on default, and no

normalization was applied to the dataset, neither was hyper parameter selection

procedure. In each test scenario, to evaluate the LR and RF models during both 5-fold

cross-validation (CV) and independent validation, the PS protein dataset was

supplemented with randomly selected proteins (from the corresponding background

dataset) at twice the size of the PS set. To ensure robustness, this sampling and

validation process was repeated at least 50 times to calculate the average

performance.

PSTP-Scan neural network

Model architecture

PSTP-Scan takes the sequence-length×650-dimension (320 for large language model

embedding and 330 for IDR conformation embedding) feature matrix as input for

each protein sequence. The model is implemented using the 'pytorch' package on

Python.

Within each PSTP-Scan block: 1. The first layer is an average pool layer with 'same'

padding, that for each protein position, a local window of feature matrix is averaged

along the residue dimension to create a 650-dimensional vector. 2. To mitigate the

effects of 'same' padding, a scaling step adjusts the values at the sequence ends to

ensure they reflect the actual averages of the sequence elements rather than padded

zeros. Thus, the representation obtained for each position i can be written as below,

where the window size is $2k + 1$, $x_{j,d}$ represents the d th value of the

650-dimensional input vector input for position j, and L represents the

sequence-length:

$$R_{i,d} = \frac{1}{min(i+k,L) - max(1,i-k)} \sum_{j=max(1,i-k)}^{min(i+k,L)} x_{j,d} \quad d = 1,2,\dots,650 \#(1)$$

3. Next, a shared, trainable multilayer perceptron (MLP) kernel processes the

averaged vector R_i. The MLP architecture consists of an initial layer with 20 neurons,

followed by a LeakyReLU activation, a hidden layer with 5 neurons, and a final

output layer with one neuron followed by a Sigmoid activation to produce a score

between 0 and 1 for each residue position. These residue-level scores for each residue

position form the sequence-length attention vector. So, the attention computation

using the representation R_i at each position can be written as the function (2). 4. The

last is a max pooling layer that selects the maximum value of the attention vector,

providing the sequence-level sequence propensity prediction, as shown in function

(3).

$$a_i = \mathrm{MLP}(R_i), \quad i = 1,2,\dots,L \#(2)$$

$$O = max_{i=1}^{L} a_i \#(3)$$

Given that the lengths of known phase-separating (PS) regions range from tens to

hundreds of residues (Fig. 4A), three parallel blocks with identical architectures but

different average pooling window sizes are used to capture PS information from

sequence fragments of varying lengths. The pooling sizes are set to 256 + 1, 128 + 1,

and 32 + 1, corresponding to powers of 2, with the extra 1 ensuring symmetric 'same'

padding on both sides. We demonstrated the robustness of model performance across

different window sizes (Fig. S2H) when a single PSTP-Scan block was applied for

both training and validation. The predicted propensities (single-value sequence-level

propensity) from these blocks are averaged to produce the final output, which is

optimized through backpropagation to update the MLP parameters.

Model training

We initialized the network parameters using 'kaiming_normal_' with default settings.

A modified LASSO regularization[110] was applied to penalize the weights for ESM-2

embeddings ($320 \times m$-dimension) and IDR embeddings ($330 \times m$-dimension) and in

the first layer of the MLP, respectively, with the penalty weight set α to 0.003

(shown as formula (4), where W represents the parameter weight matrix of the first

layer, m represents the output neuron number).

$$R(W) = \alpha\left(\sqrt{\sum_{j=1}^{m}\sum_{k=1}^{320}\left(W_{j,k}\right)^2} + \sqrt{\sum_{j=1}^{m}\sum_{k=321}^{650}\left(W_{j,k}\right)^2}\right) \tag{4}$$

L1 regularization was applied to the other MLP layers, also with a penalty weight of

0.003. Binary cross-entropy loss was used. The Adam optimizer was applied with a

learning rate of 0.003, without additional hyperparameter tuning. During the training

process, for each iteration (50 epochs in total), we held out a random subset of

proteins for the size of the positive dataset from the background dataset as the

negative dataset. This approach was applied to address sample imbalance.

Model performance benchmarks

Area Under the Receiver Operating Characteristic Curve (AUC), and Area Under the

Precision-Recall Curve (AUPR) were applied during each validation. For the

head-to-head comparison with PhaSePred and other PS predictors, we randomly

selected proteins twice the size of the PS dataset from the background proteins and

merged them with the positive dataset. Performance was evaluated using AUC and

AUPR, and this process was repeated 50 times to calculate the average performance

to ensure robustness.

Evaluation of PS-Driving Region Identification

We collected PS proteins and their corresponding experimentally validated PS regions

from the PhaSePro[57] database (https://phasepro.elte.hu/download_full.tsv). To

prevent self-validation, we trained each PSTP-Scan model (SaPS, PdPS and Mix)

after excluding proteins already included in PhaSePro[57]. We set the average pool size

at 33 (the minimum value of the average pool size when training PSTP-Scan) when

generating the residue level scores for these proteins. We define the PSTP-Scan PS

regions using the prediction values of the three models, that windows where scores

were continuously over 0.5 more than 20 AAs by the maximum of three models were

considered PS regions.

To systematically evaluate PSTP-Scan's residue-level PS scores, we assigned

residue-level scores to each protein based on the highest protein-level PS predicted

value among the three sub-models: PSTP-Scan-Mix, PSTP-Scan-SaPS, and

PSTP-Scan-PdPS. For example, if PSTP-Scan-PdPS yielded the highest predicted

propensity for a protein—indicating it is likely to undergo partner-dependent PS—we

used the residue-level scores from the PSTP-Scan-PdPS model for that protein.

We calculated Spearman correlation coefficients between these residue-level scores

and the binary annotation of actual PS regions (assigning a value of 1 to positions

within PS regions and 0 otherwise) to assess predictive performance.

Final PSTP models

For the final PSTP (PSTP-LR, PSTP-RF and PSTP-Scan) models, we trained three

versions, using the PS-Self data, PS-Part data and Mix PS data, respectively. The

training and testing datasets for each task were combined to train the final model. For

each of the three models, 10 sub-models were trained, and the average output of these

10 models was used as the final result at both the residue and protein levels.

Other PS models

For each of PScore[29], PLAAC[37], PSAP[42], ParSe[41], and PSPHunter[44], the prediction

software was obtained from their respective GitHub repositories, as documented in

the corresponding literature. PhaSePred[45] scores for self-assembly PS proteins

('SaPS-10fea_rnk') and partner-dependent PS proteins ('PdPS-10fea_rnk') were

downloaded from (http://predict.phasep.pro/download/). Prediction scores for

FuzDrop[40] were obtained from (https://fuzdrop.bio.unipd.it/). Prediction functions,

as well as feature vectors and model parameters for catGRANULE[39], were obtained

from its corresponding supplementary information and methods. During the

independent testing (Fig. 3 D to G), proteins that were included in the PS samples for

each method were excluded from both positive and negative datasets.

PS and Pathogenicity

For the pathogenicity analysis, we downloaded variants from ClinVar

(https://ftp.ncbi.nlm.nih.gov/pub/clinvar/tab_delimited/variant_summary.txt.gz) as of

April 2024, and from gnomAD V4.1.0 (https://gnomad.broadinstitute.org/).

Data and code availability

738 All data mentioned in this paper is public data and can be obtained through the

739 corresponding description in the results or methods. An installable Python package for

740 the software is available at (https://github.com/Morvan98/PSTP).

References

1.   Tsang B, Pritišanac I, Scherer SW, Moses AM, Forman-Kay JD. Phase Separation as a Missing
Mechanism for Interpretation of Disease Mutations. *Cell* **183**, 1742-1756 (2020).

2.   Gao Y, Li X, Li P, Lin Y. A brief guideline for studies of phase-separated biomolecular
condensates. *Nat Chem Biol* **18**, 1307-1318 (2022).

3.   Alberti S. Phase separation in biology. *Curr Biol* **27**, R1097-1102 (2017).

4.   Lyon AS, Peeples WB, Rosen MK. A framework for understanding the functions of
biomolecular condensates across scales. *Nat Rev Mol Cell Biol* **22**, 215-235 (2021).

5.   Oltrogge LM, Chaijarasphong T, Chen AW, Bolin ER, Marqusee S, Savage DF. Multivalent
interactions between CsoS2 and Rubisco mediate α-carboxysome formation. *Nat Struct Mol*
Biol **27**, 281-287 (2020).

6.   Wang H*, et al.* Rubisco condensate formation by CcmM in β-carboxysome biogenesis. *Nature*
566, 131-135 (2019).

7.   Sheu-Gruttadauria J, MacRae IJ. Phase Transitions in the Assembly and Function of Human
miRISC. *Cell* **173**, 946-957.e916 (2018).

8.   Su X*, et al.* Phase separation of signaling molecules promotes T cell receptor signal transduction.
Science **352**, 595-599 (2016).

9.   Wu J*, et al.* Cyclic GMP-AMP is an endogenous second messenger in innate immune signaling
by cytosolic DNA. *Science* **339**, 826-830 (2013).

10. Xiao Q, McAtee CK, Su X. Phase separation in immune signalling. *Nat Rev Immunol* **22**,
188-199 (2022).

11.   Frottin F, *et al.* The nucleolus functions as a phase-separated protein quality control
774   compartment. *Science* **365**, 342-347 (2019).

776   12.   Yang P, *et al.* G3BP1 Is a Tunable Switch that Triggers Phase Separation to Assemble Stress
777   Granules. *Cell* **181**, 325-345.e328 (2020).

779   13.   Nott TJ, Craggs TD, Baldwin AJ. Membraneless organelles can melt nucleic acid duplexes and
780   act as biomolecular filters. *Nat Chem* **8**, 569-575 (2016).

782   14.   Banani SF, Lee HO, Hyman AA, Rosen MK. Biomolecular condensates: organizers of cellular
783   biochemistry. *Nat Rev Mol Cell Biol* **18**, 285-298 (2017).

785   15.   Zeng M, *et al.* Reconstituted Postsynaptic Density as a Molecular Platform for Understanding
786   Synapse Formation and Plasticity. *Cell* **174**, 1172-1187.e1116 (2018).

788   16.   Yao RW, *et al.* Nascent Pre-rRNA Sorting via Phase Separation Drives the Assembly of Dense
789   Fibrillar Components in the Human Nucleolus. *Mol Cell* **76**, 767-783.e711 (2019).

791   17.   Falahati H, Wieschaus E. Independent active and thermodynamic processes govern the
792   nucleolus assembly in vivo. *Proc Natl Acad Sci U S A* **114**, 1335-1340 (2017).

794   18.   Singatulina AS, *et al.* PARP-1 Activation Directs FUS to DNA Damage Sites to Form
795   PARG-Reversible Compartments Enriched in Damaged DNA. *Cell Rep* **27**, 1809-1821.e1805
796   (2019).

798   19.   Maday S, Twelvetrees AE, Moughamian AJ, Holzbaur EL. Axonal transport: cargo-specific
799   mechanisms of motility and regulation. *Neuron* **84**, 292-309 (2014).

801   20.   Liao YC, *et al.* RNA Granules Hitchhike on Lysosomes for Long-Distance Transport, Using
802   Annexin A11 as a Molecular Tether. *Cell* **179**, 147-164.e120 (2019).

804   21.   Liu X, *et al.* Mitotic Implantation of the Transcription Factor Prospero via Phase Separation
805   Drives Terminal Neuronal Differentiation. *Dev Cell* **52**, 277-293.e278 (2020).

807   22.   Strom AR, Emelyanov AV, Mir M, Fyodorov DV, Darzacq X, Karpen GH. Phase separation
808   drives heterochromatin domain formation. *Nature* **547**, 241-245 (2017).

810   23.   Riback JA, *et al.* Composition-dependent thermodynamics of intracellular phase separation.
811   *Nature* **581**, 209-214 (2020).

813   24.   Klosin A, *et al.* Phase separation provides a mechanism to reduce noise in cells. *Science* **367**,
814   464-468 (2020).

816   25.   Alberti S, Dormann D. Liquid-Liquid Phase Separation in Disease. *Annu Rev Genet* **53**, 171-194

817   (2019).

819   26.   Nedelsky NB, Taylor JP. Bridging biophysics and neurology: aberrant phase transitions in
820   neurodegenerative disease. *Nat Rev Neurol* **15**, 272-286 (2019).

822   27.   Pappu RV, Cohen SR, Dar F, Farag M, Kar M. Phase Transitions of Associative
823   Biomacromolecules. *Chem Rev* **123**, 8945-8987 (2023).

825   28.   Mittag T, Pappu RV. A conceptual framework for understanding phase separation and addressing
826   open questions and challenges. *Mol Cell* **82**, 2201-2214 (2022).

828   29.   Vernon RM, *et al.* Pi-Pi contacts are an overlooked protein feature relevant to phase separation.
829   *Elife* **7**, e31486 (2018).

831   30.   Wang J, *et al.* A Molecular Grammar Governing the Driving Forces for Phase Separation of
832   Prion-like RNA Binding Proteins. *Cell* **174**, 688-699.e616 (2018).

834   31.   Dignon GL, Best RB, Mittal J. Biomolecular Phase Separation: From Molecular Driving Forces
835   to Macroscopic Properties. *Annu Rev Phys Chem* **71**, 53-75 (2020).

837   32.   Martin EW, *et al.* Valence and patterning of aromatic residues determine the phase behavior of
838   prion-like domains. *Science* **367**, 694-699 (2020).

840   33.   Brangwynne Clifford P, Tompa P, Pappu Rohit V. Polymer physics of intracellular phase
841   transitions. *Nature Physics* **11**, 899-904 (2015).

843   34.   Lotthammer JM, Ginell GM, Griffith D, Emenecker RJ, Holehouse AS. Direct prediction of
844   intrinsically disordered protein conformational properties from sequence. *Nat Methods* **21**,
845   465-476 (2024).

847   35.   Tesei G, *et al.* Conformational ensembles of the human intrinsically disordered proteome.
848   *Nature* **626**, 897-904 (2024).

850   36.   Tesei G, Schulze TK, Crehuet R, Lindorff-Larsen K. Accurate model of liquid-liquid phase
851   behavior of intrinsically disordered proteins from optimization of single-chain properties. *Proc
852   Natl Acad Sci U S A* **118**,   (2021).

854   37.   Lancaster AK, Nutter-Upham A, Lindquist S, King OD. PLAAC: a web and command-line
855   application to identify proteins with prion-like amino acid composition. *Bioinformatics* **30**,
856   2501-2502 (2014).

858   38.   Alberti S, Halfmann R, King O, Kapila A, Lindquist S. A systematic survey identifies prions and
859   illuminates sequence features of prionogenic proteins. *Cell* **137**, 146-158 (2009).

861   39.   Bolognesi B*, et al.* A Concentration-Dependent Liquid Phase Separation Can Cause Toxicity
862   upon Increased Protein Expression. *Cell Rep* **16**, 222-231 (2016).
863

864   40.   Hardenberg M, Horvath A, Ambrus V, Fuxreiter M, Vendruscolo M. Widespread occurrence of
865   the droplet state of proteins in the human proteome. *Proc Natl Acad Sci U S A* **117**, 33254-33262
866   (2020).
867

868   41.   Paiz EA, Allen JH, Correia JJ, Fitzkee NC, Hough LE, Whitten ST. Beta turn propensity and a
869   model polymer scaling exponent identify intrinsically disordered phase-separating proteins. *J
870   Biol Chem* **297**, 101343 (2021).
871

872   42.   van Mierlo G, Jansen JRG, Wang J, Poser I, van Heeringen SJ, Vermeulen M. Predicting protein
873   condensate formation using machine learning. *Cell Rep* **34**, 108705 (2021).
874

875   43.   Saar KL*, et al.* Learning the molecular grammar of protein condensates from sequence
876   determinants and embeddings. *Proc Natl Acad Sci U S A* **118**, e2019053118 (2021).
877

878   44.   Sun J*, et al.* Precise prediction of phase-separation key residues by machine learning. *Nat
879   Commun* **15**, 2662 (2024).
880

881   45.   Chen Z*, et al.* Screening membraneless organelle participants with machine-learning models that
882   integrate multimodal features. *Proc Natl Acad Sci U S A* **119**, e2115369119 (2022).
883

884   46.   Liang Q, Peng N, Xie Y, Kumar N, Gao W, Miao Y. MolPhase, an advanced prediction
885   algorithm for protein phase separation. *The EMBO Journal* **43**, 1898-1918 (2024).
886

887   47.   Zhang S, Lim CM, Occhetta M, Vendruscolo M. AlphaFold2-based prediction of the
888   co-condensation propensity of proteins. *Proc Natl Acad Sci U S A* **121**, e2315005121 (2024).
889

890   48.   Liao S*, et al.* A sequence-based model for identifying proteins undergoing liquid-liquid phase
891   separation/forming fibril aggregates via machine learning. *Protein Sci* **33**, e4927 (2024).
892

893   49.   Frank M, Ni P, Jensen M, Gerstein MB. Leveraging a large language model to predict protein
894   phase transition: A physical, multiscale, and interpretable approach. *Proc Natl Acad Sci U S A*
895   **121**, e2320510121 (2024).
896

897   50.   Lin Z*, et al.* Evolutionary-scale prediction of atomic-level protein structure with a language
898   model. *Science* **379**, 1123-1130 (2023).
899

900   51.   Boke E*, et al.* Amyloid-like Self-Assembly of a Cellular Compartment. *Cell* **166**, 637-650
901   (2016).
902

903   52.   Riback JA*, et al.* Stress-Triggered Phase Separation Is an Adaptive, Evolutionarily Tuned
904   Response. *Cell* **168**, 1028-1040.e1019 (2017).

906 53. Saito M, *et al.* Acetylation of intrinsically disordered regions regulates phase separation. *Nat*
907    *Chem Biol* **15**, 51-61 (2019).

909 54. Loya TJ, O'Rourke TW, Simke WC, Kelley JB, Reines D. Nab3's localization to a nuclear
910    granule in response to nutrient deprivation is determined by its essential prion-like domain.
911    Preprint at http://europepmc.org/abstract/MED/30557374
912 https://journals.plos.org/plosone/article/file?id=10.1371/journal.pone.0209195&type=printable
913 https://doi.org/10.1371/journal.pone.0209195
914 https://europepmc.org/articles/PMC6296506
915 https://europepmc.org/articles/PMC6296506?pdf=render (2018).

917 55. Banjade S, Wu Q, Mittal A, Peeples WB, Pappu RV, Rosen MK. Conserved interdomain linker
918    promotes phase separation of the multivalent adaptor protein Nck. *Proc Natl Acad Sci U S A* **112**,
919    E6426-6435 (2015).

921 56. Mackinder LCM, *et al.* A repeat protein links Rubisco to form the eukaryotic
922    carbon-concentrating organelle. *Proceedings of the National Academy of Sciences* **113**,
923    5958-5963 (2016).

925 57. Mészáros B, *et al.* PhaSePro: the database of proteins driving liquid–liquid phase separation.
926    *Nucleic Acids Research* **48**, D360-D367 (2019).

928 58. Landrum MJ, Kattman BL. ClinVar at five years: Delivering on the promise. *Hum Mutat* **39**,
929    1623-1630 (2018).

931 59. Landrum MJ, *et al.* ClinVar: improvements to accessing data. *Nucleic Acids Res* **48**, D835-d844
932    (2020).

934 60. Ibrahim AY, *et al.* Intrinsically disordered regions that drive phase separation form a robustly
935    distinct protein class. *Journal of Biological Chemistry* **299**, (2023).

937 61. Bremer A, *et al.* Deciphering how naturally occurring sequence features impact the phase
938    behaviours of disordered prion-like domains. *Nat Chem* **14**, 196-207 (2022).

940 62. Lin YH, Chan HS. Phase Separation and Single-Chain Compactness of Charged Disordered
941    Proteins Are Strongly Correlated. *Biophys J* **112**, 2043-2046 (2017).

943 63. Das RK, Pappu RV. Conformations of intrinsically disordered proteins are influenced by linear
944    sequence distributions of oppositely charged residues. *Proceedings of the National Academy of*
945    *Sciences* **110**, 13392-13397 (2013).

947 64. Sawle L, Ghosh K. A theoretical method to compute sequence dependent configurational
948    properties in charged polymers and proteins. *J Chem Phys* **143**, 085101 (2015).

950   65.   Zheng W, Dignon G, Brown M, Kim YC, Mittal J. Hydropathy Patterning Complements Charge
951   Patterning to Describe Conformational Preferences of Disordered Proteins. *J Phys Chem Lett* **11**,
952   3408-3415 (2020).

954   66.   Li P*, et al.* Phase transitions in the assembly of multivalent signalling proteins. *Nature* **483**,
955   336-340 (2012).

957   67.   Lin Y, Protter DS, Rosen MK, Parker R. Formation and Maturation of Phase-Separated Liquid
958   Droplets by RNA-Binding Proteins. *Mol Cell* **60**, 208-219 (2015).

960   68.   Zeng M, Shang Y, Araki Y, Guo T, Huganir RL, Zhang M. Phase Transition in Postsynaptic
961   Densities Underlies Formation of Synaptic Complexes and Synaptic Plasticity. *Cell* **166**,
962   1163-1175.e1112 (2016).

964   69.   Hou S, Hu J, Yu Z, Li D, Liu C, Zhang Y. Machine learning predictor PSPire screens for
965   phase-separating proteins lacking intrinsically disordered regions. *Nat Commun* **15**, 2147
966   (2024).

968   70.   Tesei G, Lindorff-Larsen K. Improved predictions of phase behaviour of intrinsically disordered
969   proteins by tuning the interaction range. *Open Res Eur* **2**, 94 (2022).

971   71.   Mikolov T, Sutskever I, Chen K, Corrado G, Dean J. Distributed representations of words and
972   phrases and their compositionality. In: *Proceedings of the 26th International Conference on*
973   *Neural Information Processing Systems - Volume 2*). Curran Associates Inc. (2013).

975   72.   Chu X*, et al.* Prediction of liquid-liquid phase separating proteins using machine learning. *BMC*
976   *Bioinformatics* **23**, 72 (2022).

978   73.   Arar M, Shamir A, Bermano AH. Learned Queries for Efficient Local Attention. In: *2022*
979   *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*) (2022).

981   74.   Chu X*, et al.* Twins: Revisiting the Design of Spatial attention in Vision Transformers. In: *35th*
982   *Conference on Neural Information Processing Systems (NeurIPS 2021)*) (2021).

984   75.   Ramachandran P, Bello I, Parmar N, Levskaya A, Vaswani A, Shlens J. Stand-Alone
985   Self-Attention in Vision Models. In: *33rd Conference on Neural Information Processing*
986   *Systems (NeurIPS 2019)*) (2019).

988   76.   Dai Z, Liu H, Le QV, Tan M. CoAtNet: Marrying Convolution and Attention for All Data Sizes.
989   In: *35th Conference on Neural Information Processing Systems*) (2021).

991   77.   Wang X*, et al.* LLPSDB v2.0: an updated database of proteins undergoing liquid-liquid phase
992   separation in vitro. *Bioinformatics* **38**, 2010-2014 (2022).

994   78.   You K, *et al*. PhaSepDB: a database of liquid-liquid phase separation related proteins. *Nucleic*
995   *Acids Res* **48**, D354-d359 (2020).

997   79.   Ning W, *et al*. DrLLPS: a data resource of liquid-liquid phase separation in eukaryotes. *Nucleic*
998   *Acids Res* **48**, D288-d295 (2020).

1000   80.   Fu L, Niu B, Zhu Z, Wu S, Li W. CD-HIT: accelerated for clustering the next-generation
1001   sequencing data. *Bioinformatics* **28**, 3150-3152 (2012).

1002

1003   81.   Nott Timothy J, *et al*. Phase Transition of a Disordered Nuage Protein Generates
1004   Environmentally Responsive Membraneless Organelles. *Molecular Cell* **57**, 936-947 (2015).

1005

1006   82.   Roovers EF, *et al*. Tdrd6a Regulates the Aggregation of Buc into Functional Subcellular
1007   Compartments that Drive Germ Cell Specification. *Developmental Cell* **46**, 285-301.e289
1008   (2018).

1009

1010   83.   Supek F, Lehner B, Lindeboom RGH. To NMD or Not To NMD: Nonsense-Mediated mRNA
1011   Decay in Cancer and Other Genetic Diseases. *Trends Genet* **37**, 657-668 (2021).

1012

1013   84.   Yang L, *et al*. Phase separation as a possible mechanism for dosage sensitivity. *Genome Biol* **25**,
1014   17 (2024).

1015

1016   85.   Rekhi S, *et al*. Expanding the molecular language of protein liquid-liquid phase separation. *Nat*
1017   *Chem* **16**, 1113-1124 (2024).

1018

1019   86.   Dzuricky M, Rogers BA, Shahid A, Cremer PS, Chilkoti A. De novo engineering of intracellular
1020   condensates using artificial disordered proteins. *Nat Chem* **12**, 814-825 (2020).

1021

1022   87.   Dai Y, *et al*. Programmable synthetic biomolecular condensates for cellular control. *Nat Chem*
1023   *Biol* **19**, 518-528 (2023).

1024

1025   88.   Jumper J, *et al*. Highly accurate protein structure prediction with AlphaFold. *Nature* **596**,
1026   583-589 (2021).

1027

1028   89.   Raimondi D, *et al*. DEOGEN2: prediction and interactive visualization of single amino acid
1029   variant deleteriousness in human proteins. *Nucleic Acids Res* **45**, W201-w206 (2017).

1030

1031   90.   Rentzsch P, Witten D, Cooper GM, Shendure J, Kircher M. CADD: predicting the
1032   deleteriousness of variants throughout the human genome. *Nucleic Acids Res* **47**, D886-d894
1033   (2019).

1034

91.   Li G, Panday SK, Alexov E. SAAFEC-SEQ: A Sequence-Based Method for Predicting the
Effect of Single Point Mutations on Protein Thermodynamic Stability. *Int J Mol Sci* **22**, 606

(2021).

92.   Frazer J*, et al.* Disease variant prediction with deep generative models of evolutionary data.
Nature **599**, 91-95 (2021).

93.   Liu Y, Zhang T, You N, Wu S, Shen N. MAGPIE: accurate pathogenic prediction for multiple
variant types using machine learning approach. *Genome Med* **16**, 3 (2024).

94.   Alderson TR, Pritisanac I, Kolaric D, Moses AM, Forman-Kay JD. Systematic identification of
conditionally folded intrinsically disordered regions by AlphaFold2. *Proc Natl Acad Sci U S A*
120, e2304302120 (2023).

95.   Clouser AF, Baughman HE, Basanta B, Guttman M, Nath A, Klevit RE. Interplay of disordered
and ordered regions of a human small heat shock protein yields an ensemble of 'quasi-ordered'
states. *Elife* **8**,   (2019).

96.   Capponi S*, et al.* HSPB1 and HSPB8 in inherited neuropathies: study of an Italian cohort of
dHMN and CMT2 patients. *J Peripher Nerv Syst* **16**, 287-294 (2011).

97.   Sarparanta J*, et al.* Mutations affecting the cytoplasmic functions of the co-chaperone DNAJB6
cause limb-girdle muscular dystrophy. *Nature Genetics* **44**, 450-455 (2012).

98.   Guo W*, et al.* An ALS-associated mutation affecting TDP-43 enhances protein aggregation,
fibril formation and neurotoxicity. *Nat Struct Mol Biol* **18**, 822-830 (2011).

99.   Moujalled D*, et al.* TDP-43 mutations causing amyotrophic lateral sclerosis are associated with
altered expression of RNA-binding protein hnRNP K and affect the Nrf2 antioxidant pathway.
Hum Mol Genet **26**, 1732-1746 (2017).

100.   Wu Y, Li R, Sun S, Weile J, Roth FP. Improved pathogenicity prediction for rare human
missense variants. *Am J Hum Genet* **108**, 1891-1906 (2021).

101.   Cheng J*, et al.* Accurate proteome-wide missense variant effect prediction with AlphaMissense.
Science **381**, eadg7492 (2023).

102.   Kreiter N*, et al.* Age-dependent neurodegeneration and organelle transport deficiencies in
mutant TDP43 patient-derived neurons are independent of TDP43 aggregation. *Neurobiol Dis*
115, 167-181 (2018).

103.   Wang W*, et al.* The inhibition of TDP-43 mitochondrial localization blocks its neuronal toxicity.
Nature Medicine **22**, 869-878 (2016).

104.   Miyata K, Iwasaki W. Seq2Phase: language model-based accurate prediction of client proteins
in liquid-liquid phase separation. *Bioinform Adv* **4**, vbad189 (2024).

1081

105. Lin Y-H, *et al.* The intrinsically disordered N-terminal domain of galectin-3 dynamically mediates multisite self-association of the protein through fuzzy interactions. *The Journal of biological chemistry* **292**, 17845-17856 (2017).

106. Kostylev MA, *et al.* Liquid and Hydrogel Phases of PrP-C Linked to Conformation Shifts and Triggered by Alzheimer's Amyloid-β Oligomers. *Molecular cell* **72**, 426-443.e412 (2018).

107. Vaswani A, *et al.* Attention is all you need. In: *Proceedings of the 31st International Conference on Neural Information Processing Systems*). Curran Associates Inc. (2017).

108. Erdős G, Pajkos M, Dosztányi Z. IUPred3: prediction of protein disorder enhanced with unambiguous experimental annotation and visualization of evolutionary conservation. *Nucleic Acids Res* **49**, W297-w303 (2021).

109. Asgari E, Mofrad MR. Continuous Distributed Representation of Biological Sequences for Deep Proteomics and Genomics. *PLoS One* **10**, e0141287 (2015).

110. Shi Y, *et al.* DeepAntigen: a novel method for neoantigen prioritization via 3D genome and deep sparse learning. *Bioinformatics* **36**, 4894-4901 (2020).

Acknowledgment

This project is supported by the National Key Research and Development Program (2022YFE0125300 to Y.S, 2020YFA0509700 to Q.L), Innovation Program of Shanghai Municipal Education Commission (2023ZKZD16) to G.H, the National Natural Science Foundation of China (82071262) to G.H, Shanghai Municipal Science and Technology Major Project (2017SHZDZX01 to Y.S, 20JC1418600 to G.H), Key Technology Breakthrough Program of Ningbo Sci-Tech Innovation YONGJIANG 2035 (2024Z221) to G.H, and Shanghai Jiao Tong University STAR Grant (YG2023ZD26, YG2023LC14, and YG2024QNA59 to G.H, YG2022ZD024, YG2022QN111 to Y.S, 23X010300421 to Q.L).

Author contributions

M.F, Q.L, G.H and Y.S conceived the concept; M.F, L.L curated datasets, and designed computational algorithms and experiments; M.F, L.L, X.W, K.L and Q.Y performed computational experiments with assistance from Q.L, G.H and Y.S; M.F and Z.X analyzed data; G.H led the project with assistance from M.F, Q.L, Y.S, and X.W; M.F, Q.L, G.H and Y.S wrote the manuscript with input from all co-authors.

Competing Interests Statement

The authors declare no competing interests.

Figures

Fig. 1

Fig. 1. Schematic of PSTP embedding and machine learning (ML) architecture.

(A) Protein sequences are converted into feature matrices using the hidden layer outputs of the ALBATROSS LSTM-BRNN and the final layer representations from the ESM-2 (8M parameters version) language model. For each sequence, the outputs from three ALBATROSS sub-models are extracted to form a matrix with dimensions of sequence-length×330, while ESM-2 generates a matrix of sequence-length×320. For sequences longer than 256, ESM-2 is applied in a sliding window manner to reduce time and memory costs. The combined result is a matrix of sequence-length×650 for each sequence. sequence-length: length of the protein sequence.

(B) Training and validation of traditional ML models using the PSTP embedding. The sequence-length×650 embedding matrix is averaged to a vector of length 650 for each sequence. Four categories of phase separation (PS) proteins are considered: self-assembly PS proteins (PS-Self), partner-dependent PS proteins (PS-Part), mixed PS proteins (PS-Mix types), and PS proteins lacking IDRs (PS-Lack IDR).

(C) Schematic of the PSTP-Scan block. The embedding matrix generated in (A) is used

as input to produce attention scores, which serve as residue-level PS scores to detect PS

regions. The maximum attention score for each sequence is output as the

sequence-level PS propensity score. Here, we present N-WASP as an example, where

PSTP-Scan predicts the proline-rich motif that forms multivalent interactions with its

PS partner, Nck. MLP: multilayer perceptron.

1151

   Fig. 2

Fig. 2. Analysis of IDR chain compaction properties and UMAP visualization of IDRs

with varying chain compaction.

(A and B) Comparison of conformational property metrics of intrinsically disordered

regions (IDRs) across different protein types. Metrics reflecting IDR global

conformation include v and S_{conf}/N in (A), and asphericity in (B) (PSP: Phase

separating proteins; ****P < 0.0001, ***P < 0.001, **P < 0.01, *P < 0.05; two-sided

Mann–Whitney U test; boxplot components within each violin, from top to bottom are

maxima, upper quartile, median, lower quartile, and minima.).

(C) Distribution of v values for IDRs. IDRs with $v < 0.45$ are classified as extremely

compact, while those with $v > 0.55$ are classified as expanded. To balance data size,

IDRs with $v > 0.6$ were selected for the expanded group.

(D) UMAP visualization of IDRs, categorized into compact ($v < 0.45$) and expanded

groups ($v > 0.6$), illustrating the vectorized embeddings produced by different models.

ESM2-8M and ESM2-650M represent the averaged layer representations from the 8M

and 650M parameters versions of the ESM-2 model, respectively. Word2Vec

represents embeddings produced by the skip-gram approach. ALBATROSS represents

the averaged hidden layer outputs of the ALBATROSS model.

(E and F) A parallel analysis to (C and D), considering IDRs with $S_{conf}/N < 10$ as

compact and IDRs with $S_{conf}/N > 10.25$ as expanded.

1173

 Fig. 3

1175

Fig. 3. Evaluation of PSTP model performance.

(A and B) Model performance of different feature combinations in predicting PS-Self

and PS-Part proteins, evaluated through cross-validation and independent testing.

Performance metrics were calculated using 50 replicates of subset sampling from the

background dataset. (LR: Logistic Regression, RF: Random Forest; ****$P < 0.0001$,

***$P < 0.001$, *$P < 0.05$; two-tailed Student's t-test; boxplot components within each

violin, from top to bottom are maxima, upper quartile, median, lower quartile, and

minima.). (A) Performance of different feature combinations using LR. 'dual': default

PSTP-embedding, 'w2v': word2vec embedding, 'ef': engineered features. (B)

Comparison of the default PSTP embeddings versus excluding IDR embeddings.

Excluding IDR conformational embeddings (using only ESM-2 embeddings) reduced

performance, while adding other features did not improve performance.

(C) Comparison of PSTP-LR with PhaSePred (SaPS-8, SaPS-10, PdPS-8 and

PdPS-10) as well as other representative models. PSTP-LR was trained and evaluated

on the independent validation set following the same dataset split for PhaSePred.

Results for PhaSePred and other PS predictors were sourced from the PhaSePred

literature.

(D) Model performances of different PSTP models on the independent validation

dataset of PS-Mix proteins. Performance evaluated using 100 replicates of subset

sampling from the background dataset is shown.

(E) Head-to-head comparison between PSTP-Scan and other representative PS

predictors. PSTP-Scan returns score for all proteins; the comparison with each method

is thus performed on a set of proteins that can be predicted by that method, excluding

those used in training for that method. AUC (Area under the Receiver Operating

Characteristic curve) values were computed and visualized. Data are shown as mean ±

SD (Standard Deviation), with scatter points representing performance across

sampling repeats.

(F and G) Parallel evaluations to (D and E) but focusing on the AUPR (Area Under

the Precision-Recall Curve) values.

1205

1206

 Fig. 4

1208

Fig. 4. Evaluation of residue-level prediction scores generated by PSTP-Scan and

other PS predictors under experimentally validated PS-driving regions in the

PhaSePro database (143 PS regions from 121 proteins).

(A) Distribution of sequence lengths for regions that drive PS.

(B) Comparison of PS regions predicted by PSTP-Scan against those documented in

PhaSePro. This panel highlights the overlap between predicted regions and the

corresponding overlap at the individual amino acid level.

(C) Distribution of the residue-level scores for PS regions versus non-PS regions in

proteins documented in PhaSePro. All components have p-values < 0.0001. The

boxplot components within each violin, from top to bottom are maxima, upper

quartile, median, lower quartile, and minima.

(D) Spearman correlation coefficient computed between residue-level scores and PS

regions documented in PhaSePro for each method. The coefficients are computed

between joint residue-level score vectors for each protein and a binary vector, where

corresponding positions in PS regions are assigned 1 and others are assigned 0.

(E) Median Spearman correlation coefficients at the protein level, computed between

residue-level scores and PS regions for each protein.

(F and G) Example of residue-level scores predicted by three PSTP-Scan models,

with experimentally validated PS regions highlighted in gray. pTyr motif:

phosphotyrosine motif; P-rich motif: Proline-rich motif; RRM: RNA-recognition

motifs; LCD: Low-complexity domain; PrLD: Prion-like domain

1230

1231

Fig. 5

1233

Fig. 5. Extended scope of PS protein prediction.

(A) Schematic of truncated protein prediction using the trained MLP kernel from

PSTP-Scan.

(B) Performance evaluation of different models for predicting experimentally

validated truncated PS proteins and non-PS truncated proteins, assessed by AUC (left)

and AUPR (right).

(C) Score distribution comparison across models for predicting 11 artificial

intrinsically disordered proteins (A-IDPs) that undergo PS, alongside random proteins.

'Random' represents scores for random 200-residue segments from UniProt-reviewed

proteins (n = 10,000), while 'AA weighted random' refers to scores for control

peptides, generated by repeating octapeptides 25 times as the A-IDPs, matching both

the amino acid composition and repeating patterns of the A-IDPs.

(D) PSTP-Scan-generated sequence-level and residue-level predictions for over

570,000 proteins from UniProt.

(E) Distribution of PSTP-Scan scores across the human proteome, including both

canonical proteins and isoforms (left), and for all UniProt-reviewed proteins (right).

PSTP-Scan scores are determined by selecting the highest residue-level score from the

three sub-models.

(F) A parallel evaluation as (E), but with the inclusion of only proteins containing at

least one IDR (IUPred > 0.5, length unrestricted).

1254

1255 **Fig. 6**

1256

Fig. 6. Analysis of the incidence of pathogenic variants and PS propensity.

(A) Proportion of variants of uncertain significance (VUSs) based on pLDDT scores.

(B) Distribution of PSTP-Scan residue-level scores for ClinVar variant positions with

low-pLDDT (pLDDT < 50), classified as pathogenic (Pathogenic/Likely pathogenic)

and benign (Benign/Likely benign).

(C) Top 20 high-frequency mutations among low-pLDDT (pLDDT < 50) pathogenic

variants. For each mutation type, ΔFrequency is computed as the difference in

proportion between the low-pLDDT (pLDDT < 50) pathogenic group and other

pathogenic variants (pLDDT ≥ 50).

(D) Top 20 high-frequency mutations among low-pLDDT (pLDDT < 50) pathogenic

variants with high PSTP-Scan residue-level scores (score > 0.5 from any sub-model).

(E) Proportion of ClinVar protein-altering variants, excluding missense variants.

(F) Distribution of PSTP-Scan score variations before and after mutations for

pathogenic and benign ClinVar variants described in (E). Pathogenic variants show

significantly higher PSTP-Scan score variations compared to benign variants.

1272

1273 **Supplementary figures**

1274 **Fig. S1**

1275

1276 Fig. S1. UMAP visualization of IDRs with varying chain compaction, related to Fig. 2.

1277 Parallel analysis to Fig. 2D (left) and 2F (right), with each IDR represented by

1278 engineered feature vectors incorporating various physicochemical properties.

1279

 Fig. S2.

Fig. S2. Model performance benchmark, related to Fig. 3.

(A) Parallel evaluation to Fig. 3A, but using a random forest model to evaluate the

performance of different feature combinations. ns: not significant.

(B) Parallel evaluation to Fig. 3B, performed on the PS-Self (SaPS) and PS-Part

(PdPS) cross-validation sets using 5-fold cross-validation.

(C) Performance evaluation using only the 330-dimension IDR conformation features

using the LR model under 5-fold cross-validation.

(D) Comparison of sliding window embeddings (ESM-2 large language model

embeddings) with 256-length and 1024-length thresholds across different

cross-validation and independent testing. Scatter points represent the performance

scores from repeated sampling. The performance of both window lengths is

comparable. (*$P < 0.05$, ns: not significant; two-tailed Student's t-test; boxplot

components within each violin, from top to bottom are maxima, upper quartile,

median, lower quartile, and minima.).

(E) Performance comparison of PSTP-LR and PSTP-Scan on the SaPS and PdPS test

set. Performance was evaluated using 50 replicates of subset sampling from the

background dataset, with scatter points representing performance scores from these

repeats. Both models show similar performance (ns: not significant, *$P < 0.05$;

two-tailed Student's t-test).

(F) Prediction performance of PSTP-LR models trained on PS-Self data (PSTP-SaPS)

and PS-Part data (PSTP-PdPS) in predicting MLO participants from those localized to

intracellular locations (left) and four MLO datasets (right). These participants are

curated from the PhaSePred literature. AUC values were calculated using proteins in

these MLO datasets as positive samples and the human NoPS dataset as negative

samples, excluding those in the model training data.

(G) The discriminative power of PSTP-Scan models on the independent test set ('Mix'

dataset).

(H) Performance of PSTP-Scan block with different window sizes. Unlike Fig. 3 D to

G, where the default three parallel PSTP-Scan blocks were used, each model here

represents a single-block PSTP-Scan with a specific window size. The 'kernel' model

configuration refers to passing the averaged vector directly to the trained MLP kernel

in the default PSTP-Scan setup to generate output during test set evaluation.

1314

1316 **Fig. S3.**

1317

Fig. S3. Schematic of the PSTP model, related to Fig. 1.

(A) IDR conformational embedding: For each LSTM-BRNN sub-model in

ALBATROSS, the sequence-length × 110-dimension hidden layer output is extracted

prior to predicting the final property value.

(B) Large language model embedding: Residue-level layer representations from the

ESM-2 model (8 million parameters version) are extracted, resulting in a

sequence-length ×320-dimensional matrix for each input sequence.

(C) PSTP-Scan model training and inference: Three parallel PSTP-Scan blocks with

identical architectures but different average pooling window sizes are employed to

capture sequence information at varying local lengths. The predicted sequence-level

propensities (single-value output from each block) are averaged to produce the final

output. This output is optimized via backpropagation to update the weights of the

MLP.

1331

 Fig. S4

1333

Fig. S4. Evaluation of residue-level prediction scores for proteins documented in the

PhaSePro database, related to Fig. 4.

(A) Illustration of the validation process for PSTP-Scan in predicting PS driving

regions. In this test, Each PSTP-Scan model was specifically trained excluding

proteins documented in PhaSePro to prevent self-validation and data leakage.

(B) Distribution of the protein-level Spearman correlation coefficients computed

between the residue-level scores and the binary vector representing the PS region(s)

for each protein, corresponding to Fig. 4E. Scatter points represent individual

coefficient values, while the boxplot components within each violin, from top to

bottom, represent upper quartile, median, lower quartile.

(C and D) Comparison of PS regions predicted by PSTP-Scan, FuzDrop, and

PSPHunter against those documented in PhaSePro, related to Fig. 4B. FuzDrop was

trained using PhaSePro proteins. This panel illustrates the overlap between predicted

regions (C) and the corresponding overlap at the individual amino acid level (D).

(E and H) Parallel evaluations to Fig. 4C (E) and Fig. S4B (H), focusing exclusively

on PS regions of PS-Self proteins (58 records).

(F and I) Parallel evaluations to Fig. 4C (F) and Fig. S4B (I), focusing exclusively on

PS regions of PS-Part proteins (50 records).

(G and J) Parallel evaluations to Fig. 4C (G) and Fig. S4B (J), focusing exclusively on

NMR-validated PS regions (14 records).

1354

1355

Fig. S5.

1357

Fig. S5. Examples of residue-level scores predicted by three PSTP-Scan models,

related to Fig. 4, with experimentally validated PS regions highlighted in gray. RRM:

RNA-recognition motifs.

1358

1359

1360

1361

1362

1364

Fig. S6. Extended scope of PS protein prediction and analysis of disease variants,

related to Fig. 6.

(A) Illustration of the validation process for PSTP-Scan in predicting truncated

proteins. In this test, PSTP-Scan models were specifically trained after excluding

proteins that overlap (share the same UniProt entry) with those in the truncated

protein validation dataset.

(B) AUC and AUPR evaluations of different PSTP-scan models for predicting

truncated PS proteins. 'kernel' refers to using only the trained MLP kernel from the

corresponding PSTP-Scan model to predict based on the averaged feature vector of

each protein. PSTP-SaPS, PSTP-PdPS, and PSTP-Mix refer to the three trained

PSTP-Scan models, respectively, with a single block applied and the window size set

to 32+1.

(C) PSTP residue-level scores for high pLDDT (pLDDT $\geq$ 70) pathogenicity and

benign ClinVar variants.

(D) PSTP residue-level scores for variants with high allele frequency (AF) and low

allele frequency (AF) from gnomAD, located within low pLDDT (pLDDT < 50)

regions.

(E) PSTP residue-level scores for pathogenicity and benign ClinVar variants located

in disordered regions as defined by IUPred3 (IUPred $\geq$ 0.5).

(F) PSTP residue-level scores for high AF and low AF variants from gnomAD,

located in disordered regions as defined by IUPred3 (IUPred $\geq$ 0.5).

(H-I) A parallel evaluation to Fig. 6E but focusing on in-frame deletion. Pathogenic

variants show significantly higher PSTP-Scan score variations compared to benign

variants.

1389

 Fig. S7.

Fig. S7. Model performance in predicting PS proteins lacking IDRs.

(A) Distribution of IUPred3 scores, reflecting protein disorder across different types

of proteins. PSP: PS protein; Low-IDR PSP: PS Proteins that lack IDRs; Human

background: Proteins from the human proteome; SaPS: Self-assembly PS proteins;

PdPS: Partner-dependent PS proteins; Mix PS: Mixture of different types of PS

proteins.

(B and C) Performance of PSTP-RF (PSTP-RF-nonIDR) and PSTP-LR

(PSTP-LR-nonIDR) in predicting PS proteins. Both models were evaluated using the

same training and independent datasets used for validating PSPire[69]. A head-to-head

comparison was performed between PSTP models and PSPire, with the performance

of PSPire extracted from the literature[69]. PSTP models were trained exclusively using

the large language model features. For the computation of F1-Score, Precision,

Matthews Correlation Coefficient (MCC), Accuracy, False Negative Rate (FNR),

False Positive Rate (FPR), and Sensitivity, we set the cutoff at 0.4.

1406