Multi-context seeds enable fast and high-accuracy read mapping

Ivan Tolstoganov[1], Marcel Martin[2], Nicolas Buchin[1], Kristoffer Sahlin[1,*]

[1] Department of Mathematics, Science for Life Laboratory, Stockholm University, 106 91, Stockholm, Sweden

[2] Department of Biochemistry and Biophysics, National Bioinformatics Infrastructure Sweden, Science for Life Laboratory, Stockholm University, Box 1031, SE-17121 Solna, Sweden

[*]ksahlin@math.su.se

Abstract. A key step in sequence similarity search is to identify shared seeds between a query and a reference sequence. A well-known tradeoff is that longer seeds offer fast searches but reduce sensitivity in variable regions. We introduce multi-context seeds (MCS), which allow to store seeds with different lengths in the same index structure, thus retaining the advantages of both short and long seeds. We demonstrate the applicability of MCS by implementing them in strobealign. Strobealign with MCS substantially improves accuracy compared to the previous version with little cost in runtime and no memory overhead.

Keywords: read mapping, seeds, Illumina, k-mers, strobemers

Background

In bioinformatics, a *seed* refers to a short substring or subsequence of a biological sequence that is used to initiate a sequence similarity search between sequences, e.g., between a read and a reference genome. Seeds are crucial for heuristic (i.e., not guaranteed to find the optimal solution) algorithms for sequence comparison such as read mapping algorithms [1, 38]. In the seeding step, the seeds help to quickly identify potential *matches*, reducing the search space. A match (also sometimes referred to as an anchor) is a seed that occurs both in the query and the reference.

A k-mer is a string of length k and is commonly used in sequence similarity search algorithms such as read mapping. In read mapping, choosing k is a tradeoff: Longer k-mers enhance seed specificity and therefore mapping speed, but shorter k-mers increase sensitivity as they are less affected by sequencing errors and biological mutations. Several alternative methods have been proposed to enable using longer seeds that can match in the regions between mismatches and indels. These include spaced seeds [28], TensorSketching [17], context-aware seeds [44], k-min-mers [9], strobemers [36], BLEND [12], and SubSeqHash [27, 26]. Some of these seed types were shown to be efficient for short [37] and long-read mapping [10, 12, 17] and can enable one or two orders of magnitude speedup over using k-mers [10, 37, 12, 17]. At a high level, the seeds in [10, 37, 12] are based on joining together several k-mers into a single seed, thus providing a longer range of a match, which gives more unique seeds and, thus, fewer candidate locations to explore. However, long seeds, although they allow approximate matches, come with an undesirable reduction in accuracy, which results in widespread usage of the more resource-intensive but accurate short seed-based alternatives [22, 24, 25, 40].

The tradeoff between seed length and accuracy makes the idea of having seeds at multiple levels or resolutions compelling. The longer seeds would provide speed through their low match redundancy, while one could fall back on shorter seeds in case no longer matches were found. The concept of using different k-mer sizes for various resolutions has been used in, e.g., genome assembly [33, 3, 2], transcriptome assembly [35], RNA-Seq analysis [19], metagenomic mapping [41] through LexicHash [14] and k-mer counting [18]. In read mapping, variable-length seeds such as MEMs [6, 24] (constructed with the FM-index [11] or Enumerated Radix Tree [42]) and MCAS [16] are used, but they are slow to query. This is because the query process to construct such seeds needs to access scattered locations in memory. Moreover, aforementioned multi-resolution methods only increase or decrease the resolution with one nucleotide [24] or utilize multiple sizes of k [3], which results in a runtime increase proportional to the number of k sizes used.

Results

Method overview

A *strobemer* is a seed that consists of two or more k-mers called *strobes*. We propose using strobemers that support queries at multiple resolutions, making it possible to query all or a certain subset of these k-mers in the index. Naively, we could store both k-mers and strobemers with $2, \ldots n$ k-mers in the same index. However, this would increase space requirements and would also slow down mapping through cache misses if the seeds are scattered in memory. Instead, we present *multi-context seeds* (MCS). MCS are strobemers produced with the randstrobe method [36] that distribute the bits allocated to store the (hash of the) seed separately between k-mers in the strobemer. The primary idea of MCS is as follows. For an L bits allocation of a seed hash value, an MCS will store the leftmost $l_1 < L$ bits to represent the first k-mer in the strobemer, the following $l_2 < L$ bits for the second k-mer, etc., with $l_1 + l_2 + \ldots = L$. See Fig. 1 for a conceptual illustration. When indexed efficiently, for example as a vector sorted by hash values paired with a look-up table, as is standard in k-mer based mapping [25, 46, 37], this seed enables cache-efficient lookup for both *full matches* covering the whole strobemer and *partial matches* covering the first several strobes.

Being able to search for seed matches at several resolutions compared to the binary "match or no match" of the full seed increases both accuracy and percentage of aligned reads. We first demonstrate that MCS improve sequence matching characteristics over randstrobes and k-mers but retain roughly the same seed uniqueness benefits as randstrobes. We then show the practical applicability of MCS by implementing them in strobealign [37] in addition to randstrobes. We benchmark strobealign with MCS and compare it to strobealign with randstrobes and other state-of-the-art alignment tools using simulated Illumina reads of different lengths from four genomes at various sizes and sequence complexities. Strobealign with MCS improves mapping-only and extension-based read alignment accuracy over strobealign with randstrobes in all experiments with typical Illumina read lengths ≤ 150 nt for both single-end and paired-end data, without a substantial slowdown. Particularly, as sequence variability gets high, MCS have a higher relative increase in accuracy over strobealign with randstrobes. Unlike strobealign with randstrobes, strobealign with MCS now surpasses minimap2 accuracy in extension alignment mode in nearly all experiments, while remaining substantially faster. When compared with the gold standard BWA-MEM, strobealign with MCS has comparable accuracy on datasets with high diversity, but with much lower mapping and indexing time.

Evaluation overview

We first compare multi-context seeds with randstrobes and k-mers, taking into account sequence matching coverage to assess sensitivity and seed uniqueness to assess specificity. This is a general-purpose sequence

Fig. 1. Multi-context seeds concept. **A** A reference sequence consisting of five similar copies with some variation (colored shapes), and a strobemer seed sampled from one of the copies. **B** The forward multi-context seed representation of the strobemer consisting of a $(64 - sx)$-bit prefix for the base strobe, and x-bit prefixes for the s remaining strobes. In this example, $s = 2$ and $x = 3$. **C** Read mapping of a read without sequencing errors (read 1) and a read with a sequencing error or non-reference mutation in the third strobe (read 2). While read 2 cannot produce a full match, the part of the seed limited to the first two strobes is still able to produce a match to the reference.

similarity search benchmark to assess the repetitiveness of seeds and match sensitivity in a general setting. We then implement multi-context seeds in addition to randstrobes in the read mapping tool strobealign [37] (published as v0.17.0). We benchmark the multi-context seeds version against the randstrobe version of strobealign, BWA-MEM (v0.7.19) [24], and minimap2 (v2.30) [25] using simulated and biological short-read data. We compare against BWA-MEM and minimap2 as they were the competitors with the highest accuracy (BWA-MEM) and most desirable speed-to-accuracy tradeoff (minimap2) to strobealign in a previous benchmark [37] that included other tools such as Bowtie2 [22], SNAP2 [5], and Accel-Align [46]. Additionally, we report benchmark results for the recently released X-Mapper tool [13] in the supplement (see Suppl. Section 4 for details). We also benchmark MCS against randstrobes and a k-mer only version of strobealign as well as minimap2 in a proof-of-concept long-read mapping benchmark. Support for long reads is in development and only available in mapping-only mode in strobealign v0.17.0 (i. e., without base-level alignments).

Datasets

For the general-purpose sequence matching benchmark, we simulate pairs of nucleotide sequences of length 10,000 with mutation rates 0.01, 0.05, and 0.1 (insertions, deletions, or substitutions occurring with equal probability 1/3). Each sequence pair is replicated 1000 times to reduce sample variability. We refer to these pairs of simulated sequences as the **SIM-R** dataset. Such experiment setup was performed in [36] to evaluate different strobemer constructions. For the uniqueness evaluation, we measure the fraction of unique seeds (occurring once) and the E-hits [37] in the human cell line CHM13 assembly [31], referred to as **CHM13**.

For the read alignment benchmark, we generate three datasets with different mutation rates that we call **SIM0**, **SIM4**, and **SIM6**. **SIM4** has already been used in an earlier study [37].

Simulated reads were generated from the CHM13 (3.1 Gbp), fruit fly (144 Mbp), maize (2.2 Gbp) and rye [23] (7.3 Gbp) genomes. Libraries of paired-end reads of various lengths ranging from 50–500 nt are

generated, and single-end libraries are obtained by omitting the second reads of paired-end reads. We also

simulate single-end reads of lengths 1000, 5000, and 10,000 nt (long reads).

SIM0 consists of reads without errors and without variants, i. e., the reads are substrings of the reference.

SIM4 and **SIM6** are generated with Mason [15] simulating Illumina reads at different mutation rates.

Variants simulated for **SIM4** occur at a rate somewhat higher than expected between humans. The rate is

much higher for **SIM6** (see Suppl. Section 5 for details). Note that even the long reads were generated using

the Illumina read profile (using Mason) as a way to generate PacBio-HiFi-like reads (see Suppl. Section 5).

We also performed a SNV and indel calling benchmark as performed in [37], using bcftools as the variant

caller with two simulated (**SIM150**, **SIM250**) and two biological (**BIO150**, **BIO250**) datasets.

Sequence matching experiment

Benchmark. We perform the sequence matching benchmark of seeds similarly to the procedure described in

[36]. Given a pair of simulated sequences (s, s') from the **SIM-R** dataset, we construct k-mers, randstrobes,

and MCS from every possible starting position of the two sequences. We count the number of matches between

seeds generated from s and seeds generated from s' (including partial matches for MCS) for every type of

seed construct. Similarly to the strobemers study [36], we compute match percentage, sequence coverage,

and the island E-size metric as defined in [36]. Briefly, match percentage m is the fraction of seed matches,

sequence coverage sc is the percentage of sequence in s covered by the actual strobes of a seed. The island

E-size is a measure of the size of gaps (islands [4]) without matches. We describe these metrics in detail in

Supplementary Section 3. An additional match coverage metric, which is a percentage of sequence spanned

by seed matches, is included in Suppl. Tab. S1, with results similar to sequence coverage. As expected, the

multi-context seeds result in the same or higher number of matches and sequence coverage compared to

k-mers with the same k parameter and randstrobes with the same parametrization, with the exception of

multi-context seeds with $(2, 15)$ parametrization, which result in slightly lower sequence coverage metric than

15-mers. This discrepancy can be explained by the fact that randstrobes are not sampled if the distance from

the start position to the end of the sequence does not exceed $2k + w_{\min}$. Therefore, k-mer matches located

close to the end of the sequence will not have corresponding partial MCS matches.

		SIM-R								
		0.01			0.05			0.1		
		m	sc	E-size	m	sc	E-size	m	sc	E-size
kmers	30	74.5	96.0	1.1	22.3	54.6	43.7	4.7	18.2	289.8
kmers	20	82.4	97.9	0.3	37.3	72.6	11.0	13.4	38.6	62.6
kmers	15	86.7	98.6	0.1	48.3	81.7	4.2	22.6	54.0	22.3
kmers	10	90.4	99.2	**0.0**	62.3	91.2	0.9	38.8	75.8	4.2
randstrobes	(2, 15)	70.7	98.2	**0.0**	18.1	72.7	8.2	3.4	31.2	117.0
randstrobes	(3, 10)	66.7	98.8	**0.0**	14.7	78.3	1.1	2.5	33.8	68.5
multi-context	(2, 15)	86.7	98.6	**0.0**	48.3	81.6	2.8	22.6	53.9	20.9
multi-context	(3, 10)	**91.2**	**99.4**	**0.0**	**62.9**	**92.2**	**0.1**	**39.3**	**77.0**	**1.6**

Table 1. Match statistics for k-mers, randstrobes, and MCS under mutation rates of 0.01, 0.05, and 0.1. Here, m denotes the number of matches (both full and partial for MCS) as a percentage of the total number of extracted subsequences for the protocol, sc (sequence coverage) is shown as the percentage of the total sequence length, and $E\text{-}size$ is the expected island size. The randstrobes and multi-context seeds were constructed with the window parameters $w_{\min} = 25$ and $w_{\max} = 50$

Results. Table 1 shows the mean match percentage, total sequence coverage, and island E-size for the **SIM-R** dataset. We benchmarked randstrobes and MCS with parametrizations $(2, 15)$ and $(3, 10)$ with total strobemer length 30 (as used in [36]). For the k-mers, we chose k size 30 corresponding to the total strobemer size, and k sizes 10, 15, and 20 corresponding to all the possible partial match sizes of the multi-context seed parametrizations. As expected, we observe that k-mers of size 10 and MCS with parametrization $(3, 10)$ have the highest fraction of matches, since the seeds of smaller size are more likely to be preserved between mutation positions. Between the seeds of the same length, i. e. randstrobes, MCS, and k-mers of size 30, MCS with parametrization $(3, 10)$ show the highest match percentage due to production of both full and partial matches. MCS have higher match coverage and sequence coverage than randstrobes due to the presence of additional partial matches.

MCS demonstrate significant advantage over randstrobes with the same parameters. For example, for the parametrization $(3, 10)$ and mutation rate 0.1, the match percentage is 39.3% for MCS and 2.5% for randstrobes, sequence coverage is 77% for MCS and 33.8% for randstrobes, and the expected island size is only 1.6 for MCS and 68.5 for randstrobes. Also, the improvement of MCS over randstrobes for the two-strobe setting $(2, 15)$ is almost as large as for the three-strobe setting.

Seed uniqueness

Benchmark. While MCS show higher match coverage than randstrobes and k-mers due to the presence of partial matches, they are also expected to result in a larger amount of spurious matches for the same reason. The previous experiment was designed to be without repeats to accurately measure (true) coverage of matches. In order to assess the potential increase in the spurious matches, we benchmarked MCS against

Seed construct	Tot. seed length	Parameters	% Unique	E-hits	#Distinct (millions)
randstrobes	48	(3,16)	98.1	103.0	2,808.3
multi-context	48	(3,16)	97.4	105.2	2,757.0
k-mers	48	48	97.4	152.9	2,706.9
multi-context	48	(2,24)	97.9	164.5	2,777.4
randstrobes	48	(2,24)	97.7	181.7	2,754.5
k-mers	32	32	96.7	429.9	2,528.8
k-mers	24	24	96.0	1051.2	2,365.8
multi-context, first two strobes	32	(3,16)	95.0	1298.9	2,450.4
multi-context, first strobe	24	(2,24)	95.6	2049.8	2,355.7
k-mers	16	16	43.3	2120.2	800.2
multi-context, first strobe	16	(3,16)	43.3	10268.1	800.0

Table 2. Uniqueness statistics for k-mers, randstrobes, and MCS. For the MCS, every given seed is estimated separately as its full hash value, subhash corresponding to the first strobe, and subhash corresponding to the first two strobes for 3rd order MCS. The column "Tot. seed length" indicates total nucleotides included in the seed. "% Unique" denotes the percentage of the total number of seeds of the given type that have unique hash value, "E-hits" denotes the E-hits metric of the given seed type, and "#Distinct" shows the number of distinct seeds of the given type (in millions). The rows are sorted by the E-hits value. The randstrobes and multi-context seeds were constructed with the window parameters $w_{\min} = 36$ and $w_{\max} = 72$. For both the randstrobes and multi-context seeds, we used 56-bit hashes, with 32 bits reserved for the MCS base hash.

k-mers and randstrobes on the CHM13 reference genome using three metrics, namely the percentage of unique seeds, number of distinct seeds, and the E-hits metric [37]. Roughly, E-hits measures the expected number of occurrences of a seed if a seed is selected uniformly at random in the database, see [37] for details. We measure the seed uniqueness metrics by indexing the CHM13 reference genome and counting the seed occurrence distribution. We estimate the k-mer occurrence distribution using KMC [21] k-mer counter tool, and strobealign for calculating randstrobes and MCS occurrence distribution. For this experiment, we use all k-mers in the reference in strobealign, i.e., we do not use the open-syncmers downsampling in strobealign. For the MCS, we provide the number of partial hits separately from the number of full hits. We use a range of typical k-mer sizes used for human genome applications and resulting matching strobemer parameterizations (dividing the k-mer size by 2 or 3). We used 56 bit hashes (the number of bits allocated to a seed hash value in strobealign) for randstrobes and multi-context seeds. In MCS, 40 bits were reserved for the first hash, and 16 bits for the second (in the case of 2-strobe MCS) or 8 bits for the second and for the third (in the case of 3-strobe MCS).

Results. We observe that MCS (full hits) and randstrobes are nearly identical in uniqueness (Table 2). This suggests that even though MCS splits the bits in the hash value representation to enable multi-level search, it does not result in significant hash collisions for full matches compared to randstrobes, at least not in a human genome. As expected, partial matches are more redundant than full matches. Also, the partial hits of the MCS show similar proportion of unique seeds and higher E-hits to k-mers of the same length, and in the three-strobe setting, the partial hit with first two strobes is less unique than k-mers of the same length

Fig. 2. Accuracy of single-end (top row) and paired-end (bottom row) read alignment for the **SIM0** (left), **SIM4** (middle), and **SIM6** (right) datasets. Mode "align" is extension-alignment mode (SAM output), mode "map" is mapping-only mode (coordinate output). The x-axis (read length) is scaled logarithmically.

32. This difference between k-mers and partial hits can be attributed to the hash collisions, since the second strobe is encoded in 8-bit hash in this benchmark.

Read mapping evaluation

We compared strobealign-MCS to strobealign with randstrobes, BWA-MEM and minimap2. For the single-end and paired-end reads experiments, we show the accuracy and runtime for the **SIM0**, **SIM4** and **SIM6** datasets for CHM13 in Fig. 2 and Fig. 3. As in [37], we consider a read correctly mapped if the reported mapping coordinates overlap with the provided ground truth reference coordinates for the read. Otherwise, it is incorrectly mapped. Accuracy is computed as the fraction of correctly mapped reads. Results for all four genomes (also rye, fruit fly, and maize) and measurements of memory usage and mapping rate (percentage of aligned reads) are found in Suppl. Figs. S8–S14.

High-variation profile. Similarly to minimap2's several mapping profiles, we implemented two profiles, a high-quality profile (same parameters as strobealign for short-reads) and a high-variation profile that we label *noisy*. The noisy profile sets $k = 16$, $s = 2$, $w_{min}=2$, $w_{max}=2$, which, in practice, produces 2-layer k-mers, where the smaller k-mer is 16 and the larger is 26 (in expectation; depending on downstream syncmer offset).

Short-read mapping results. For paired-end reads, strobealign-MCS improves both accuracy (Figure 2, Suppl.
Fig. S9) and the percentage of aligned reads (Suppl. Fig. S13) over strobealign with randstrobes, both in
mapping-only and extension-alignment modes in all genomes. The improvement of MCS over randstrobe
seeds in the alignment mode is present for all datasets, and is most apparent for reads up to length 100 bp
(mean accuracy increase 0.7%) in the **SIM4** dataset (moderate mutation rate), and for all read lengths in
the **SIM6** dataset (mean increase 17.2%). This is expected as the partial seed matches can produce hits
around variations and other divergent regions where no full matches or randstrobes were produced. In the
mapping-only mode (no extension alignment), the increase in accuracy is noticeable (mean 2.2%) for read
lengths 300 bp or lower in the **SIM4** dataset and for all read lengths in the **SIM6** dataset (mean 28.2%).
The mapping-only mode is useful for rapid metagenomics analysis with the AEMB mode [32]. In both read-
mapping and extension modes, strobealign with MCS further narrows the mean accuracy gap for shorter
reads compared to gold-standard BWA-MEM, while still being $6\times$ faster on average in the alignment mode
(Suppl. Fig. S11).

For single-end reads, the relative increase in accuracy of strobealign-MCS compared to strobealign with
randstrobes is even larger, visible for reads shorter than 200 bp in the alignment mode (Figure 2, Suppl.
Fig. S8). Relatively better performance in the single-end mode can be explained by strobealign's rescue
procedure in paired-end mode, which utilizes the matches of a read to recover its unmapped mate. In
addition, strobealign with MCS also substantially improves the percentage of mapped reads over strobealign
with randstrobes for shorter read lengths (Suppl. Fig. S12).

For SIM0 and SIM4 datasets, the runtime overhead of strobealign-MCS to strobealign with randstrobes
is minimal, with substantial accuracy gains for shorter read lengths. For SIM6, strobealign-MCS is slightly
slower than strobealign with randstrobes (Figure 3, Suppl. Figs. S10 and S11), due to the higher redundancy
and extra lookups of partial hits, as well as the extra alignment sites produced by partial matches found by
strobealign in the absence of full matches.

Proof-of-concept long-read mapping results. To assess MCS outside of short-read mapping, we implemented
a proof-of-concept long-read mapping mode in strobealign by adding a seed chaining algorithm (described in
Suppl. Section 8). We consider it proof-of-concept because this mode currently only works in mapping-only
mode (no base-level alignments), nor are supplementary mappings implemented (needed for, e.g., structural
variation detection with long reads). We simulated long-reads (read lengths 1,000, 5,000, and 10,000 nt,
Suppl. Section 5.3) for long-read mapping.

Results are shown in Suppl. Figs. S6 and S7. Firstly, strobealign-MCS substantially outperform strobealign
with randstrobes, particularly in modest to high variation settings, while also being faster in most cases.

Fig. 3. Runtime of single-end (top row) and paired-end (bottom row) read alignment for the **SIM0** (left), **SIM4** (middle), and **SIM6** (right) datasets

Additionally, compared to state-of-the-art long-read mapper minimap2, strobealign with MCS is 3-5× and 1.2-2.3× faster with both default and noisy profiles, respectively. Additionally, the two profiles are also often more accurate than minimap2. For example, on CHM13 with no or modest variation (SIM0 and SIM4) strobealign has higher accuracy than minimap2. Overall, across the 27 experiments (genomes, variation levels, and read lengths), strobealign demonstrates comparable accuracy levels to minimap2, while improving runtime.

Strobealign seed lookup strategies. With the implementation of MCS in strobealign, it can now use different seeding approaches; randstrobes-only, k-mer-only (only searching for the base hash corresponding to a single syncmer; see methods), and MCS. We compared these settings in strobealign (Suppl. Fig. S5). Overall, we see that MCS produce favorable accuracy over randstrobes mode while producing comparable results to k-mer-only. However, for larger and more repetitive datasets, MCS is faster than k-mer-only.

3-strobe based approach While the current version of strobealign is based on MCS consisting of two strobes, we developed an additional 3-strobe based version to assess how increasing the number of search layers would affect accuracy and runtime (see Suppl. Sec. 7 for details). Within strobealign's mapping framework, our 3-strobe implementation did not result in any additional benefits compared to 2-strobe version (Suppl. Figs. S15 and S16).

Indexing time. Indexing speed is not measurably affected by enabling the MCS hash function. Using four threads and leaving all other indexing parameters (k, s, etc.) unchanged, strobealign takes $2\,\mathrm{s}$, $32\,\mathrm{s}$, $47\,\mathrm{s}$ and $111\,\mathrm{s}$ to index fruit fly, maize, CHM13, and rye, respectively. For reference, BWA and minimap2 take $2420\,\mathrm{s}$ and $52\,\mathrm{s}$, respectively, to index CHM13 on the same machine (using four threads for minimap2; BWA does not parallelize index creation).

Variant calling. We ran the variant calling benchmark on two simulated and two biological Illumina datasets as performed in [37] (Suppl. Fig. S17). In terms of F-score, the tools perform roughly similar. BWA-MEM has highest SNV recall for all datasets, while the tools perform similarly on indels. Note however that we use bcftools to call variants. Some callers may be developed or tuned based on popular aligners' mapping quality (MAPQ) scores. Specifically, it has been shown that *bcftools call* was the variant caller that produced the best results with BWA-MEM alignments out of seven variant calling tools [47]. Therefore, we view this analysis as a sanity check rather than a perfect indicator of mapping quality. As with the simulated data, strobealign is substantially faster than minimap2 and BWA-MEM. There is no significant difference between strobealign versions in calls. While MCS enables looking for partial matches and would enable split or supplementary mapping, it is not yet implemented in strobealign. We hope to include split read mapping in future work, which may improve variant calling further.

Methods

Preliminaries

Notation Let R be a string over the alphabet $\Sigma = \{A, C, G, T\}$. We refer to a string obtained by deleting a subset of characters in R as a *subsequence* of R. We define the consecutive subsequence as a *substring*. We will use zero-indexed notation for strings. Given nucleotide string R, a *k-mer* is defined as a substring of R of length k. Let $R[i, k]$ denote a *k-mer* covering the positions from i to $i + k - 1$. We use h_L to denote a hash function that maps k-mers to L-bit strings $h_L : \Sigma^k \to \{0, 1\}^L$. The l-bit prefix of the L-bit hash h_L is denoted as h_L^l.

Strobemers Strobemers were introduced in [36] as a way of handling indels and reads with a high mutation rate. Strobemers are constructed from an array $K = (s_1, \ldots, s_N)$ obtained by decomposing a string R into N consecutive k-mers, where $s_i = R[i, k]$. Given K and parameters $(n, k, w_{\min}, w_{\max})$, a *strobemer* of order n is defined as a subsequence of n k-mers $t = (s_{i_1}, s_{i_2}, \ldots, s_{i_n})$ in K. The $w_{\min}$ and $w_{\max}$ parameters limit the distance between consecutive k-mers in t, i.e. for every $j \in [1, n - 1]$, we have $i_{j+1} \in [i_j + w_{\min}, i_j + w_{\max}]$. The k-mers selected for a strobemer are called *strobes*.

Strobemers as initially described were constructed from complete k-mer arrays K of a reference. However,
strobemers can also be constructed from a subset of k-mers. For example, in strobealign [37], strobemers
are constructed from the array of *open syncmers* [8] generated in the reference. In this work, we abstract
over the array of k-mers from which a strobe is chosen by denoting $\mathcal{W}_j$ to be the indices of k-mers available
in a window where strobe j is selected. When selecting strobes from all k-mers, the window corresponds to
the consecutive indices of a substring of the reference of length $w_{\max} - w_{\min} + 1$, while it is a subsequence
of reference indices with larger span if selecting over a subset of k-mers such as minimizers [39, 34, 30] or
syncmers [8].

Randstrobes Various strategies for selecting the next strobe were described in [36, 29]. Randstrobes are
constructed iteratively from the starting strobe s_{i_1}. If strobes $s_{i_1}, \ldots, s_{i_j}$ were already selected for a rand-
strobe, the strobe $s_{i_{j+1}}$ is selected as

$$s_{i_{j+1}} = \operatorname*{argmin}_{\ell \in \mathcal{W}_{j+1}} f(s_\ell, s_{i_1}, \ldots, s_{i_j}), \tag{1}$$

266 where f is a function that maps a strobe to an integer. Several functions were investigated in [20]. For
267 example, strobealign uses

$$s_{i_{j+1}} = \operatorname*{argmin}_{\ell \in \mathcal{W}_{j+1}} B\big((h(s_\ell) \oplus h(s_{i_1}) \oplus \cdots \oplus h(s_{i_j}) \, \& \, P\big), \tag{2}$$

where h is a hash function from a sequence to a 64-bit number, B is the number of set bits, P is a bitmask
with its p least significant bits set, and $\oplus$ is the bitwise XOR operator. The B and p make strobealign pick
strobes earlier in the window more often, which is deemed suitable for the shortest reads (for details, see
[37]). To combine the hashes of individual strobes into a single hash value for the randstrobe, strobealign
v0.15.0 and earlier uses $(h(a, b) = h(b, a))$ hash function $h(s_{i_1}, \ldots, s_{i_n}) = \sum_j h(s_{i_j})$ to hash strobes from
two different orientations into the same hash value, as described in [37]. Since v0.16.0 strobealign uses multi-
context seed hash function (Eq. 3) to construct a randstrobe hash value in order to enable randstrobes and
multi-context seeds within the same index.

Multi-context seeds

277 We introduce multi-context seeds, a seeding strategy based on the strobemers [36] technique. Strobemers
278 consist of several k-mers, or *strobes*, such that the distance between two consecutive k-mers does not exceed
279 a constant parameter. While this strategy allows to effectively increase the length of the seed, it results

in lower sensitivity, especially in shorter reads. To alleviate this, we change the strobemer hash function to a concatenation of prefixes of individual strobe hashes. This hash function allows searching for the first consecutive strobes instead of the whole strobemer by using a prefix of the hash in a search, as illustrated in Figure 1. Effectively, this means that for strobe length s, seeds of lengths $s, 2s, \ldots, ns$ are stored simultaneously in a single index. A formal description of multi-context seeds and their implementation in strobealign [37] follows.

Multi-context seeds Given integers L, n, and l_1, $\ldots$, l_n such that $\sum_{i=1}^{n} l_i = L$, the *multi-context* seed is a strobemer consisting of strobes s_{i_1}, $\ldots$, s_{i_n}, which is stored as

$$h(s_{i_1}, \ldots, s_{i_n}) = \overline{h_L^{l_1}(s_{i_1}) h_L^{l_2}(s_{i_2}) \ldots h_L^{l_n}(s_{i_n})} \tag{3}$$

where $\overline{t_1 \ldots t_n}$ denotes the concatenation of bit strings t_1, $\ldots$, t_n.

For example

$$h(s_{i_1}, s_{i_2}) = \overline{h_{64}^{40}(s_{i_1}) h_{64}^{24}(s_{i_2})}$$

describes a strobemer with two strobes hashed in a 64-bit integer where the first strobe is represented with 40 bits and the second strobe with 24 bits. For an illustration, see Fig. 1. We say that the first l_1 bits of the MCS hash are the *base part* of the hash, and the following allocations are (shorter) *digests*. Typically, these are given more bits than downstream strobes to avoid hash collisions of the base k-mer.

Implementation in strobealign

Open syncmers Open syncmers is a k-mer subsampling method [8]. Given positive integer parameters (k, s, t), where $s \leq k$ and $t \in [0, k - s + 1]$, a k-mer is selected as an *open syncmer* iff the smallest of its $k - s + 1$ consecutive s-mers occurs at position t. The smallest s-mer is defined based on a hash function. In order to process queries from both the forward and the reverse strands efficiently, we store a canonical representation of the open syncmers, i.e., only the smallest syncmer out of the forward and the reverse-complement s-mers.

Multi-context seeds in strobealign As in the randstrobe version of strobealign, we use the canonical open syncmers in order to create the sequence of strobes for multi-context seed construction. We construct open syncmers using the parameters k, s, and $t = \lceil (k - s + 1)/2 \rceil$, where parameters k and s are dependent on the read length (see details in the Supplementary Section 1). Depending on the value of t, $14 - 20\%$ of k-mers are selected as strobes. Following the construction of the sequence of open syncmers $S = (s_1, \ldots, s_N)$

from the input references, we employ the *skewed randstrobe* selection strategy described in strobealign [37]
for both randstrobe and multi-context seed constructs. Every syncmer s_i from S is used once as the first
strobe in the seed construction, with the subsequent strobes chosen using Eq. 2. Both randstrobes and MCS
are constructed as described above in the Randstrobes section, with the parameters $w_{\min}$ and $w_{\max}$ chosen
based on read length.

Indexing The individual MCS are stored as tuples $V_i = (h_i, p_i, o_i, r_i)$, where h_i is the MCS hash $h(t_1, \ldots, t_n)$,
p_i is the starting position of the first strobe in the reference sequence, o_i is the offset of the last $n-1$ strobes
(i.e. the distance between the start of the current strobe and the start of the previous strobe), and r_i is the
reference index. In memory, V_i takes up 16 bytes: 7 bytes for h_i, 4 bytes for p_i, 1 byte for o_i, and 4 bytes for
r_i.

The V_i tuples are stored in a vector V accompanied by an indexing structure *AEMB index* [32]. We
describe it briefly here for self-containment. Given vector V of tuples V_i sorted in increasing order by h_i
values, and a parameter $b < 64$, the AEMB index defines an array I_b, which stores in position j the
first occurrence position i in V such that a bit representation of j is a b-prefix of i. If there is no tuple
$(h_i, p_i, o_i, r_i, f_i)$ in V such that j is a b-prefix of h_i, a value from the preceding position $I_b[j-1]$ is stored
instead. We define $I_b[0]$ as 0, so a preceding value always exists. Since V is sorted by hash values h_i, hashes
in V with the same b-prefixes are stored in a single consecutive block. I_b is sometimes referred to as a
prefix-lookup vector and has been used in other sequence mapping algorithms [7]. The default value for the
parameter b depends on the total reference length $Length$, strobe length s, and k, specifically

$$b = \max(8, \lfloor \log_2(Length/(k - s + 1)) \rfloor).$$

If the hash h is queried in V, the first position in the block in V is the value $I_b[h^b]$. The last position of
the block is the minimum value in I_b which follows h^b and is different from $I_b[h^b]$. The block in V can then
be searched for the exact match h using either linear or binary search.

Querying Our implementation of strobealign with MCS contains all the same algorithm steps as strobealign,
with the difference that MCS are used to search for partial matches in case a full match was not found. In
more detail, for a query (read), strobealign [37] searches for seed matches in the index, chains the matches (for
details, see Suppl. Section 8), and performs an extension alignment step (if strobealign is run in extension-
mode). The seeds are constructed from the forward and reverse-complemented read in tuples V_i. The rand-
strobe version of strobealign differs from the multi-context version in selecting matches from the constructed

seeds. In the randstrobe version, the seed is considered a match if its hash is present in the index and if it is not hard masked (i.e. occurs less than 1000 times in the index). In the multi-context version, a seed can be either a full match or a partial match if the full hash value or only the base hash value is present in the index, respectively. The full match criteria are the same as for the randstrobe seed. If a query is not a full match, we search for a base part of a query hash in the index if it was not searched previously. If the base part of a hash is present in the index and is not hard masked, we select it as a partial match. Pseudocode for this procedure can be found in Supplementary Section 1.

Note that since the index V is sorted by the hash value, the prefix of the queried hash can also be searched in the index using the same algorithm as for the full hash search, as long as the prefix is longer than the parameter b. For MCS, we use this property of the AEMB index to search for *partial matches*, entries in V with the same base part of the hash as the query. Thus, looking up the hash of the base (search for partial hit) is cheap as the part of the vector is often in the cache after the full seed has been searched. We refer to the approach described above as strobealign-MCS in the benchmark.

Bit allocation of the base and the digests

We want to allocate a fraction of bits to represent the base hash value such that it minimizes hash collisions of both full and partial searches. The optimal bit allocation depends on the underlying genome repeat structure, size of k, and the number of available bits B. However, since the repeat structure is unknown, we aimed to select a reasonable bit partition based on simulated experiments. We computed the fraction of bits allocated to the base hash that minimized the sum of E-hits [37] for full and partial matches with two strobes, for various combinations of k, $w = |\mathcal{W}|$, B, given a genome size $G = 2^{16}$. We investigate both a fully random genome and one with a simulated repeat structure. The details of the experiment are found in Suppl. Section 2. In brief, we found that when B is small compared to G, we want to allocate more bits to the base. At the same time, for relatively large B, the fraction tends towards 0.5 for both genomes (Suppl. Fig. 1). We also observed that the value of k in relation to G matters since it affects k-mer uniqueness. Finally, w did not have an impact on the optimal fraction. We acknowledge that biological reference sequences are more repetitive than random strings, and may therefore benefit from using a larger fraction allocated to B, compared to that of a random string. We use $B = 56$ in all our benchmarks (and in strobealign), which is sufficient for most genomic databases, and picked a fraction $B = 40/56$. The remaining 16 bits are allocated to the digest of the second strobe in 2-order MCS, and 8 bits are allocated to the digests of the second and the third strobe in 3-order MCS.

Discussion and conclusions

We presented a new seeding approach, multi-context seeds (MCS), that allows multiple layers of matches to be searched. A multi-context seed is a hash value representation of a strobemer, where each strobe in the strobemer is represented by a separate substring of bits in the hash value. This allows the seed to be queried at multiple levels. Particularly, in a sorted array such as the AEMB index (the index used in strobealign), this enables both full and partial matches to be searched in a cache-efficient manner. We show that multi-context seeds produce more matches than k-mers and randstrobes with the same subsequence size (Table 1), which indicates increased mapping sensitivity. Additionally, we show that multi-context seeds are as unique as randstrobes and k-mers if the full hash is searched (Table 2).

We believe that MCS can be useful in applications where sequence searches at multiple resolutions are useful and where efficiency is needed. We demonstrate the benefit of MCS in one such case by implementing MCS in the read mapper strobealign. We show that strobealign with MCS significantly increases accuracy in single-end and paired-end read alignment and mapping modes compared to strobealign with randstrobes for short read lengths and modest to high variation (SIM4 and SIM6) (Figure 2, Suppl. Fig. S8, S9). Strobealign with MCS has low runtime overhead to strobealign randstrobes, where the overhead depends on the variation levels, while being noticeably faster than BWA-MEM (Figure 3, Suppl. Figs. S10 and S11). BWA-MEM has a slightly faster but much more memory-consuming variant, BWA-MEM2 [43], which we have benchmarked against strobealign [37]. However, optimized implementations for strobealign [45]) also exist that double the speed. MCS is now the default seeding method used in strobealign (v0.17.0). We also implemented a proof-of-concept long-read mapping in strobealign to assess how MCS perform for long-read mapping. We observed that strobealign with MCS was consistently faster than minimap2 while demonstrating comparable and often favorable accuracy, particularly on a human genome (CHM13).

As future work, we aim to use MCS to enable better split-read breakpoint detection with short reads and long-read alignment and to further explore the idea of using MCS for multiple k-mer levels. Our experiments of fixing the offset of the second syncmer generated a two-level dynamic k-mer index, which showed improvement over other approaches for high diversity datasets (Figure 2, Suppl. Fig. S8 and S9) and to state-of-the-art long-read mapper minimap2 in the proof-of-concept long-read mapping benchmark (Figure 2, Suppl. Fig. S6 and S7). Finally, as our proof-of-concept long-read mapping implementation demonstrated state-of-the-art long-read mapping accuracy, we aim to make strobealign with MCS a complete long-read aligner including piecewise extension alignment and supplementary alignments, features that are necessary for structural variation detection.

Declarations

Availability of data and materials. Strobealign 0.17.0 is available under the MIT license from https://doi.org/10.5281/zenodo.17974973 and the development version can be found at https://github.com/ksahlin/strobealign. The bit allocation analysis is found at https://github.com/ksahlin/misc/tree/main/mcs. The code for the sequence matching results is located at https://github.com/Itolstoganov/strobemers/tree/multi-context-benchmarks. The code for the uniqueness benchmark is available at https://github.com/Itolstoganov/strobealign/tree/uniqueness_benchmark. The code for the read alignment experiments is available at https://github.com/NBISweden/strobealign-evaluation/. Biological datasets BIO150 (Illumina WGS 2x150bp, HG004) and BIO250 (Illumina WGS 2x250bp, HG004) analyzed in this study are found at https://github.com/genome-in-a-bottle/giab_data_indexes.

Acknowledgements. The computations were enabled by resources provided by the National Academic Infrastructure for Supercomputing in Sweden (NAISS), partially funded by the Swedish Research Council through grant agreement no. 2022-06725.

Funding. Kristoffer Sahlin was supported by the Swedish Research Council (SRC, Vetenskapsrådet) under Grant No. 2021-04000. Part of this work was supported by the SciLifeLab & Wallenberg Data Driven Life Science Program, Knut and Alice Wallenberg Foundation (grants: KAW 2020.0239 and KAW 2017.0003), and by the National Bioinformatics Infrastructure Sweden (NBIS) at SciLifeLab.

Authors' contributions. KS and IT conceived the concept of multi-context seeds. IT, MM, and KS implemented MCS in strobealign. IT analyzed the seed constructs using uniqueness and coverage metrics. MM and IT benchmarked strobealign-MCS against state-of-the-art alignment tools and analyzed the results. NB implemented chaining in strobealign and wrote the supplementary section on chaining. IT and KS performed the variant calling analysis. IT and KS drafted the paper with input from MM. All authors read and contributed to the final manuscript.

Ethics approval and consent to participate. Not applicable.

Consent for publication. Not applicable.

Competing interests. The authors declare no competing interests.

Bibliography

[1] Mohammed Alser, Jeremy Rotman, Dhrithi Deshpande, Kodi Taraszka, Huwenbo Shi, Pelin Icer Baykal, Harry Taegyun Yang, Victor Xue, Sergey Knyazev, Benjamin D. Singer, Brunilda Balliu, David Koslicki, Pavel Skums, Alex Zelikovsky, Can Alkan, Onur Mutlu, and Serghei Mangul. Technology dictates algorithms: recent developments in read alignment. *Genome Biology*, 22(1):249, 2021.

[2] Anton Bankevich, Andrey V. Bzikadze, Mikhail Kolmogorov, Dmitry Antipov, and Pavel A. Pevzner. Multiplex de Bruijn graphs enable genome assembly from long, high-fidelity reads. *Nature Biotechnology*, 40(7):1075–1081, 2022.

[3] Anton Bankevich, Sergey Nurk, Dmitry Antipov, Alexey A Gurevich, Mikhail Dvorkin, Alexander S Kulikov, Valery M Lesin, Sergey I Nikolenko, Son Pham, Andrey D Prjibelski, Alexey V Pyshkin, Alexander V Sirotkin, Nikolay Vyahhi, Glenn Tesler, Max A Alekseyev, and Pavel A Pevzner. SPAdes: a new genome assembly algorithm and its applications to single-cell sequencing. *J Comput Biol*, 19(5):455–477, May 2012.

[4] Antonio Blanca, Robert S. Harris, David Koslicki, and Paul Medvedev. The statistics of k-mers from a sequence undergoing a simple mutation process without spurious matches. *Journal of Computational Biology*, 29(2):155–168, February 2022.

[5] William J. Bolosky, Arun Subramaniyan, Matei Zaharia, Ravi Pandya, Taylor Sittler, and David Patterson. Fuzzy set intersection based paired-end short-read alignment. *bioRxiv*, 2021.

[6] Arthur L. Delcher, Adam Phillippy, Jane Carlton, and Steven L. Salzberg. Fast algorithms for large-scale genome alignment and comparison. *Nucleic Acids Research*, 30(11):2478–2483, June 2002.

[7] Alexander Dobin, Carrie A Davis, Felix Schlesinger, Jorg Drenkow, Chris Zaleski, Sonali Jha, Philippe Batut, Mark Chaisson, and Thomas R Gingeras. STAR: ultrafast universal RNA-seq aligner. *Bioinformatics*, 29(1):15–21, January 2013.

[8] Robert Edgar. Syncmers are more sensitive than minimizers for selecting conserved k-mers in biological sequences. *PeerJ*, 9:e10805, February 2021.

[9] Barış Ekim, Bonnie Berger, and Rayan Chikhi. Minimizer-space de Bruijn graphs: Whole-genome assembly of long reads in minutes on a personal computer. *Cell Syst*, 12(10):958–968, October 2021.

[10] Barış Ekim, Kristoffer Sahlin, Paul Medvedev, Bonnie Berger, and Rayan Chikhi. Efficient mapping of accurate long reads in minimizer space with mapquik. *Genome Research*, 2023.

[11] Paolo Ferragina and Giovanni Manzini. Opportunistic data structures with applications. volume 2000, pages 390–398, February 2000.

[12] Can Firtina, Jisung Park, Mohammed Alser, Jeremie S Kim, Damla Senol Cali, Taha Shahroodi, Nika Mansouri Ghiasi, Gagandeep Singh, Konstantinos Kanellopoulos, Can Alkan, and Onur Mutlu. BLEND: a fast, memory-efficient and accurate mechanism to find fuzzy seed matches in genome analysis. *NAR Genom Bioinform*, 5(1):lqad004, March 2023.

[13] Jeffry M. Gaston, Eric J. Alm, and An-Ni Zhang. X-Mapper: fast and accurate sequence alignment via gapped x-mers. *Genome Biology*, 26:15, January 2025.

[14] Grant Greenberg, Aditya Narayan Ravi, and Ilan Shomorony. LexicHash: sequence similarity estimation via lexicographic comparison of hashes. *Bioinformatics*, 39(11):btad652, October 2023.

[15] M. Holtgrewe. Mason: A read simulator for second generation sequencing data. *Technical Report FU Berlin*, October 2010.

[16] Chirag Jain, Arang Rhie, Nancy F. Hansen, Sergey Koren, and Adam M. Phillippy. Long-read mapping to repetitive reference sequences using Winnowmap2. *Nature Methods*, 19(6):705–710, 2022.

[17] Amir Joudaki, Alexandru Meterez, Harun Mustafa, Ragnar Groot Koerkamp, André Kahles, and Gunnar Rätsch. Aligning distant sequences to graphs using long seed sketches. *Genome Research*, 2023.

[18] Chelsea J.-T. Ju, Jyun-Yu Jiang, Ruirui Li, Zeyu Li, and Wei Wang. Tahcoroll: fast genomic signature profiling via thinned automaton and rolling hash. *Medical Review*, 1(2):114–125, December 2021.

[19] Chelsea J.-T. Ju, Ruirui Li, Zhengliang Wu, Jyun-Yu Jiang, Zhao Yang, and Wei Wang. Fleximer: Accurate quantification of RNA-seq via variable-length k-mers. In *Proceedings of the 8th ACM International Conference on Bioinformatics, Computational Biology,and Health Informatics*, ACM-BCB '17, pages 263—272, New York, NY, USA, 2017. Association for Computing Machinery.

[20] Moein Karami, Aryan Soltani Mohammadi, Marcel Martin, Barış Ekim, Wei Shen, Lidong Guo, Mengyang Xu, Giulio Ermanno Pibiri, Rob Patro, and Kristoffer Sahlin. Designing efficient randstrobes for sequence similarity analyses. *Bioinformatics*, 40(4):btae187, April 2024.

[21] Marek Kokot, Maciej Długosz, and Sebastian Deorowicz. KMC 3: counting and manipulating k-mer statistics. *Bioinformatics*, 33(17):2759–2761, May 2017.

[22] Ben Langmead and Steven L. Salzberg. Fast gapped-read alignment with Bowtie 2. *Nature Methods*, 9(4):357–359, April 2012.

[23] Guangwei Li, Lijian Wang, Jianping Yang, Hang He, Huaibing Jin, Xuming Li, Tianheng Ren, Zhenglong Ren, Feng Li, Xue Han, Xiaoge Zhao, Lingli Dong, Yiwen Li, Zhongping Song, Zehong Yan, Nannan Zheng, Cuilan Shi, Zhaohui Wang, Shuling Yang, Zijun Xiong, Menglan Zhang, Guanghua Sun, Xu Zheng, Mingyue Gou, Changmian Ji, Junkai Du, Hongkun Zheng, Jaroslav Doležel, Xing Wang Deng, Nils Stein, Qinghua Yang, Kunpu Zhang, and Daowen Wang. A high-quality genome assembly high-

lights rye genomic characteristics and agronomically important genes. *Nature Genetics*, 53(4):574–584, March 2021.

[24] Heng Li. Aligning sequence reads, clone sequences and assembly contigs with BWA-MEM, 2013.

[25] Heng Li. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics*, 34(18):3094–3100, May 2018.

[26] Xiang Li, Ke Chen, and Mingfu Shao. Efficient seeding for error-prone sequences with SubseqHash2. *bioRxiv*, 2024.

[27] Xiang Li, Qian Shi, Ke Chen, and Mingfu Shao. Seeding with minimized subsequence. *Bioinformatics*, 39(Supplement_1):i232–i241, June 2023.

[28] Bin Ma, John Tromp, and Ming Li. PatternHunter: faster and more sensitive homology search. *Bioinformatics*, 18(3):440–445, March 2002.

[29] Benjamin Dominik Maier and Kristoffer Sahlin. Entropy predicts sensitivity of pseudorandom seeds. *Genome Research*, May 2023.

[30] Guillaume Marçais, Dan DeBlasio, and Carl Kingsford. Asymptotically optimal minimizers schemes. *Bioinformatics*, 34(13):i13–i22, June 2018.

[31] Sergey Nurk, Sergey Koren, Arang Rhie, Mikko Rautiainen, Andrey V. Bzikadze, Alla Mikheenko, Mitchell R. Vollger, Nicolas Altemose, Lev Uralsky, Ariel Gershman, Sergey Aganezov, Savannah J. Hoyt, Mark Diekhans, Glennis A. Logsdon, Michael Alonge, Stylianos E. Antonarakis, Matthew Borchers, Gerard G. Bouffard, Shelise Y. Brooks, Gina V. Caldas, Nae-Chyun Chen, Haoyu Cheng, Chen-Shan Chin, William Chow, Leonardo G. de Lima, Philip C. Dishuck, Richard Durbin, Tatiana Dvorkina, Ian T. Fiddes, Giulio Formenti, Robert S. Fulton, Arkarachai Fungtammasan, Erik Garrison, Patrick G. S. Grady, Tina A. Graves-Lindsay, Ira M. Hall, Nancy F. Hansen, Gabrielle A. Hartley, Marina Haukness, Kerstin Howe, Michael W. Hunkapiller, Chirag Jain, Miten Jain, Erich D. Jarvis, Peter Kerpedjiev, Melanie Kirsche, Mikhail Kolmogorov, Jonas Korlach, Milinn Kremitzki, Heng Li, Valerie V. Maduro, Tobias Marschall, Ann M. McCartney, Jennifer McDaniel, Danny E. Miller, James C. Mullikin, Eugene W. Myers, Nathan D. Olson, Benedict Paten, Paul Peluso, Pavel A. Pevzner, David Porubsky, Tamara Potapova, Evgeny I. Rogaev, Jeffrey A. Rosenfeld, Steven L. Salzberg, Valerie A. Schneider, Fritz J. Sedlazeck, Kishwar Shafin, Colin J. Shew, Alaina Shumate, Ying Sims, Arian F. A. Smit, Daniela C. Soto, Ivan Sović, Jessica M. Storer, Aaron Streets, Beth A. Sullivan, Françoise Thibaud-Nissen, James Torrance, Justin Wagner, Brian P. Walenz, Aaron Wenger, Jonathan M. D. Wood, Chunlin Xiao, Stephanie M. Yan, Alice C. Young, Samantha Zarate, Urvashi Surti, Rajiv C. McCoy, Megan Y. Dennis, Ivan A. Alexandrov, Jennifer L. Gerton, Rachel J. O'Neill, Winston Timp, Justin M.

Zook, Michael C. Schatz, Evan E. Eichler, Karen H. Miga, and Adam M. Phillippy. The complete sequence of a human genome. *Science*, 376(6588):44–53, April 2022.

[32] Shaojun Pan, Ivan Tolstoganov, Kristoffer Sahlin, Marcel Martin, Xing-Ming Zhao, and Luis Pedro Coelho. AEMB: efficient abundance estimation for metagenomic binning. *bioRxiv*, 2025.

[33] Yu Peng, Henry C. M. Leung, S. M. Yiu, and Francis Y. L. Chin. *IDBA – A Practical Iterative de Bruijn Graph De Novo Assembler*, page 426–440. Springer Berlin Heidelberg, 2010.

[34] Michael Roberts, Wayne Hayes, Brian R. Hunt, Stephen M. Mount, and James A. Yorke. Reducing storage requirements for biological sequence comparison. *Bioinformatics*, 20(18):3363–3369, July 2004.

[35] Gordon Robertson, Jacqueline Schein, Readman Chiu, Richard Corbett, Matthew Field, Shaun D Jackman, Karen Mungall, Sam Lee, Hisanaga Mark Okada, Jenny Q Qian, Malachi Griffith, Anthony Raymond, Nina Thiessen, Timothee Cezard, Yaron S Butterfield, Richard Newsome, Simon K Chan, Rong She, Richard Varhol, Baljit Kamoh, Anna-Liisa Prabhu, Angela Tam, YongJun Zhao, Richard A Moore, Martin Hirst, Marco A Marra, Steven J M Jones, Pamela A Hoodless, and Inanc Birol. De novo assembly and analysis of rna-seq data. *Nature Methods*, 7(11):909–912, October 2010.

[36] Kristoffer Sahlin. Effective sequence similarity detection with strobemers. *Genome Research*, 31(11):2080–2094, October 2021.

[37] Kristoffer Sahlin. Strobealign: flexible seed size enables ultra-fast and accurate read alignment. *Genome Biology*, 23(1), December 2022.

[38] Kristoffer Sahlin, Thomas Baudeau, Bastien Cazaux, and Camille Marchet. A survey of mapping algorithms in the long-reads era. *Genome Biology*, 24(1):133, 2023.

[39] Saul Schleimer, Daniel S. Wilkerson, and Alex Aiken. Winnowing: local algorithms for document fingerprinting. In *Proceedings of the 2003 ACM SIGMOD international conference on Management of data*, SIGMOD/PODS03. ACM, June 2003.

[40] Fritz J. Sedlazeck, Philipp Rescheneder, Moritz Smolka, Han Fang, Maria Nattestad, Arndt von Haeseler, and Michael C. Schatz. Accurate detection of complex structural variations using single-molecule sequencing. *Nature Methods*, 15(6):461–468, 2018.

[41] Wei Shen and Zamin Iqbal. Lexicmap: efficient sequence alignment against millions of prokaryotic genomes. *bioRxiv*, 2024.

[42] Arun Subramaniyan, Jack Wadden, Kush Goliya, Nathan Ozog, Xiao Wu, Satish Narayanasamy, David Blaauw, and Reetuparna Das. Accelerated seeding for genome sequence alignment with enumerated radix trees. In *2021 ACM/IEEE 48th Annual International Symposium on Computer Architecture (ISCA)*. IEEE, June 2021.

[43] Md. Vasimuddin, Sanchit Misra, Heng Li, and Srinivas Aluru. Efficient architecture-aware acceleration of bwa-mem for multicore systems. In *2019 IEEE International Parallel and Distributed Processing Symposium (IPDPS)*, pages 314–324, 2019.

[44] Hongyi Xin, Mingfu Shao, and Carl Kingsford. Context-aware seeds for read mapping. *Algorithms for Molecular Biology*, 15(1):10, 2020.

[45] Lifeng Yan, Zekun Yin, Jinjin Li, Yang Yang, Tong Zhang, Fangjin Zhu, Xiaohui Duan, Bertil Schmidt, and Weiguo Liu. Rabbitsalign: Accelerating short-read alignment for cpu-gpu heterogeneous platforms. In Wei Peng, Zhipeng Cai, and Pavel Skums, editors, *Bioinformatics Research and Applications*, pages 83–94, Singapore, 2024. Springer Nature Singapore.

[46] Yiqing Yan, Nimisha Chaturvedi, and Raja Appuswamy. Accel-align: a fast sequence mapper and aligner based on the seed–embed–extend method. *BMC Bioinformatics*, 22(1):257, 2021.

[47] Zhen Yao, Frank M You, Amidou N'Diaye, Ron E Knox, Curt McCartney, Colin W Hiebert, Curtis Pozniak, and Wayne Xu. Evaluation of variant calling tools for large plant genome re-sequencing. *BMC Bioinformatics*, 21:1–16, 2020.