1 **How relevant is the prior? Bayesian causal inference for dynamic perception in volatile**
2 **environments**
3

David Meijer[1], Roberto Barumerli[1,2], Robert Baumgartner[1]

[1]Acoustics Research Institute, Austrian Academy of Sciences, Vienna, Austria
[2]Department of Neurosciences, Biomedicine and Movement Sciences, University of Verona,
Verona, Italy

<u>Abstract</u>

Our brains predict future sensory input based on their current beliefs about the world around
us, but interpreting prediction errors can be challenging in a volatile environment because they
can be caused by stochastic noise or by outdated predictions. Noisy signals should be
integrated with prior beliefs to improve precision, but the two should be segregated when
environmental changes render prior beliefs irrelevant. Bayesian inference provides a
statistically optimal solution to deal with situations in which there is uncertainty about the
cause of the prediction errors. However, the method quickly becomes memory intensive and
computationally intractable when applied consecutively.

Here, we systematically evaluate the predictive performance of Bayesian causal inference for
human perceptual decisions in a spatial prediction task based on noisy audiovisual sequences
with occasional changepoints. We elucidate the simplifying assumptions of a previously
proposed reduced Bayesian observer model, and we compare it to an extensive set of models
based on alternative simplification strategies.

Model-free analyses revealed the hallmarks of Bayesian causal inference: participants seem to
have integrated sensory evidence with prior beliefs to improve accuracy when prediction errors
were small, and prior influence gradually decreased as prediction errors grew larger, signalling
probable irrelevance of the prior due to a changepoint. Model comparison results further
supported the hypotheses that participants computed probability-weighted averages over the
causal options (noise or changepoint) and that they iteratively summarized their beliefs while
accounting for causal uncertainty akin to the reduced Bayesian observer model. However, we
also found that participants' reliance on prior beliefs was systematically smaller than predicted
by the model, and this was best explained by individually fitting lower-than-optimal parameters
for the a-priori probability of prior relevance.

We conclude that perceptual belief updating in volatile environments with stochastic noise is
well described by a simplified model of consecutive Bayesian causal inference. Observers
utilize priors flexibly to the extent that they are deemed relevant, though also conservatively
with a lower tendency to bind than an ideal Bayesian observer.

<u>Keywords</u>

Perceptual decision making, Bayesian causal inference, Changepoint detection, Prior
relevance, Consecutive belief updating

1. Introduction

Perception is inherently uncertain. Sensory signals are disturbed by noise from external sources
and our nervous system suffers from imperfect processing and transmission (Faisal et al.,
2008). Besides, the limited information that is conveyed by the sensory signals is often
insufficient by itself to obtain an unambiguous understanding of our environment. One efficient
way to nevertheless form a coherent model of the world around us is to supplement and
compare incoming sensory information with expectations based on our current beliefs (Friston,
2010; Clark, 2013). Upon a mismatch, we may choose to update our beliefs if we think that they
were wrong, or if something has changed in the environment. However, such decisions are not
always easy, because we must keep in mind that both novel evidence and existing beliefs are to
some extent unreliable due to sensory ambiguity and noise, at present and in the past.

Bayesian inference is a probabilistic approach to deal with such perceptual uncertainty in a
manner that has the potential to be statistically optimal (Ma, 2012). Accordingly, it has been
proposed that our brains attenuate the detrimental impact of random noise, thus improving
perceptual precision, by integrating redundant information across sensory cues and prior
beliefs by means of reliability-weighted averaging (Knill & Pouget, 2004). Indeed, there is an
abundance of reports that collectively demonstrate that what we perceive is often biased by our
expectations and by concurrent sensory signals in accordance with Bayesian integration (de
Lange et al., 2018, Meijer & Noppeney, 2020) and that our brains are in principle capable of such
probabilistic computations (Pouget et al., 2013).

However, one should not integrate sensory information that does not originate from the same
real-world object or event (i.e., cause). Within the Bayesian inference framework, one can
naturally account for the possibility of multiple sensory sources by a hierarchical extension of
the prior (Shams & Beierholm, 2010). For example, in an audiovisual ventriloquism paradigm, an
observer must entertain two competing causal structures: either the auditory and visual signals
stem from the same source location, or they come from two different locations (Körding et al.,
2007). Moderately small spatial disparities between the sensory signals could have easily been
caused by noise, so an observer may falsely infer a common source and thus integrates the two
sensory signals, leading to the ventriloquist illusion. Yet, the illusion does not occur for larger
spatial disparities when it is more likely that the two signals originated from two different
locations. Results from a multitude of psychophysics and neuroimaging studies support the
claim that our brains apply such Bayesian causal inference to determine whether to integrate or
segregate sensory signals (Shams & Beierholm, 2022).
34
Another field of research in which Bayesian inference has been successful at explaining human
perceptual decisions is concerned with learning in changing environments (O'Reilly, 2013; Kang
et al., 2024). Of specific interest to us here is the problem of changepoint detection: i.e., how
does one determine whether their current model of the world has become irrelevant because of
a sudden change in their surroundings? In other words, when should one integrate noisy
sensory evidence with previously held beliefs to improve precision, and when should one
segregate the two because the latest sensory signal stems from a novel reality? The problem is
thus essentially one of causal inference (noise or changepoint?) and Bayesian probability theory
prescribes the optimal approach to dynamically deal with the combined uncertainty from
stochastic and volatile generative processes (Adams & MacKay, 2007; Fearnhead and Liu,
2007).

The fully Bayesian solution to the changepoint detection problem allows an agent to retrospectively evaluate evidence about changepoints that occurred several observations in the past. While such inference with hindsight leads to the most precise beliefs about the current state of the world, it also requires extensive memory and computational capacity that seems implausible for the human brain. Hence, simplified near-Bayesian changepoint models were developed that approximate the optimal solution and provide more realistic algorithms that may be implemented by the brain (Nassar et al., 2010, 2012; Wilson et al., 2013). Indeed, available psychophysical, neuroimaging and neurophysiological work in combination with computational modelling generally support the hypothesis that the brain relies on approximately-Bayesian inference for adaptive learning in changing environments (Yu et al., 2021, Razmi & Nassar, 2022).

Here, our main contributions are threefold. First, we attempt to bridge a gap between the fields of learning and sensory cue integration by presenting near-Bayesian changepoint detection in a way that is readily understandable by those familiar with the Bayesian causal inference models for sensory cue integration. In doing so, we show that the mathematical foundation of these models is identical and corroborate the notion of Bayesian causal inference as a unifying neuroscience theory (Shams & Beierholm, 2022). By stripping the model to its core components, we lay-out its key predictions for consecutive cue integration and introduce testable hypotheses for an extension of Bayesian causal inference into the domain of dynamic belief updating.

Second, we evaluate the model's performance in explaining spatial predictions of participants in a changepoint detection task wherein expectations had to be formed and updated during the ongoing presentation of stimulus sequences. Participants were prompted for a response at unpredictable times when the sequence suddenly stopped. This experimental design is in stark contrast to the more commonly used procedure where participants are required to make a prediction response after every stimulus (Nassar et al., 2010, 2012, 2019, 2021, McGuire et al., 2014). By using a task design that requires covert evidence accumulation rather than overt serial decision-making, we aim to examine Bayesian causal inference as a mechanism of implicit sequential perception, while aspiring to avoid explicit choice history biases (Talluri et al., 2018; Bévalot & Meyniel, 2023). We adopt the rich behavioral dataset that was previously analysed by Krishnamurthy, Nassar, Sarode and Gold (2017), but we limit our analysis to the audiovisual sequences and the prediction responses, whereas their original publication focused on pupillometry recordings and localization responses about sounds that followed those predictions.

Third, we derive the fully Bayesian solution for this experimental paradigm and subsequently systematically introduce simplifications and alternative assumptions. This allows us to build a factorial framework of model variations with varying complexity and decisional strategies. We then fit all models to the behavioral data and perform a model comparison to evaluate which of the tested algorithmic components are most probably utilized by the brain. As such, we provide a systematic evaluation of memory and complexity reduction in near-Bayesian changepoint detection models for human perceptual decision making in volatile environments.

<u>2. Results</u>

Twenty-nine participants performed a spatial prediction task in which they indicated the

anticipated location of an upcoming stimulus by means of a mouse response on a semi-circular

arc after having been presented with a sequence of audiovisual stimuli (Figure 1A). Responses

were self-paced, and the median reaction time was 1.72 (IQR: 1.49–2.35) seconds. The

sequences mostly allowed for reasonable predictions because the stimuli locations (at times t),

x_t, were sampled from a normal distribution, centred on the 'generative mean' μ_t and with width

defined by the 'experimental noise' σ_{exp} (SD = 10° or 20° in blocked low or high noise conditions,

respectively). Hence, the mean location of the preceding stimuli provides a good prediction for

the location of the next stimulus. However, at every timepoint t, there was a 15% chance for a

changepoint (hazard rate $H_{cp} = 0.15$), in which case the generative mean μ_t was resampled at

random from within the space boundaries (uniform distribution from $a = -90°$ to $b = +90°$,

relative to straight ahead). Participants were instructed on the nature of the changepoint

process, and they had the opportunity to learn the values of the task's parameters (H_{cp}, σ_{exp}) in

a practice session (not analysed). See section 4.1 for more details on the experimental

procedure or consult the original publication by Krishnamurthy, Nassar, et al. (2017).

Figure 1. The reduced Bayesian observer model puts the causality question centre stage

after every stimulus: Did the latest observation originate from the same generative mean

location as the prior (with added noise), or has there been a changepoint (cp)?

A). Example trial in which an observer is presented with ten audiovisual stimuli. The

generative mean changes twice after the start of the sequence: at *t*=4 and at *t*=6. Five

consecutive stimuli are presented after the last cp (SAC 5), after which the participant

responds with a prediction for the location of the upcoming stimulus. Ideally, the response

location approximates the mean of the stimuli since the last cp. The sequential inference

process to estimate this mean location is illustrated for three stimuli. Upon experiencing a

large precision-weighted prediction error, a cp is inferred, and the prior becomes irrelevant

for the current generative mean. So, the posterior (and next prior) is based on the likelihood

only (*t*=4). Instead, small prediction errors indicate a low probability of a cp, thus likelihood

and prior are integrated to improve precision of the mean estimate (*t*=5). But what to do

when there is (causal) uncertainty about the occurrence of a cp (*t*=6)? The relatively large

prediction error suggests a cp, but the overlap between prior and likelihood indicates that they could have also originated from a common generative mean, i.e., $\mu_6 = \mu_5$. A fully Bayesian observer computes a posterior as a weighted mixture of two posterior components (dashed lines), each conditional on a causal hypothesis (cp or not). Alternatively, the reduced Bayesian observer summarizes that mixture distribution by its mean and variance, and thus simplifies the posterior (and next prior) to a single normal distribution.

B-D). The prior relevance measure (Π) is key to the inference process of the reduced Bayesian observer. Panel B depicts its logit transformation (Q, i.e., the posterior log-odds of no changepoint) as a function of absolute prediction error $|\tilde{\mu}_t - x_t|$, for two experimental noise conditions, two levels of prior reliability (τ), and two changepoint hazard rates (H_{cp}). Panel C shows the resulting normalized bias towards the prior (at 1, relative to the last stimulus), which equals the product of prior relevance and prior reliability. Panel D illustrates how spatial uncertainty about the generative mean depends on the latest prediction error: it is low for small errors due to integration of prior and likelihood, it is identical to the experimental noise for large prediction errors, and highest in-between because of causal uncertainty.

2.1 Reduced Bayesian observer model

Bayesian inference provides a statistically optimal method of dealing with the uncertainty that is caused by the combined presence of noise and changepoints in order to minimize the squared prediction errors. In section 4.3, we have derived the fully Bayesian solution for this task design (Adams & MacKay, 2007). However, since that ideal observer model relies on an infinitely large memory capacity and is computationally complex, we instead consider the reduced Bayesian observer model that was introduced by Nassar et al. (2010, 2012). This model presents a more plausible inference algorithm to be utilized by the brain and it has the additional benefit that it makes the causal inference process (i.e., changepoint or not) very explicit and insightful due to its simplicity.

Since the upcoming stimulus location x_{t+1} is equal to its generative mean μ_{t+1} plus some random noise, the reduced Bayesian observer makes predictions about x_{t+1} based on its best prediction for μ_{t+1}: i.e., $\tilde{x}_{t+1} = \tilde{\mu}_{t+1}$. Here, the tilde indicates that these are predictions. To compute its prediction about the upcoming generative mean, the modelled agent attempts to compute the mean of the preceding stimuli since the last changepoint. If a changepoint occurred at the latest timepoint, $cp_t = 1$, then only the last stimulus is relevant, and the associated uncertainty is given by the learned estimate (indicated by circumflex) of the experimental noise:

$$\tilde{\mu}_{t+1}|(cp_t = 1) = x_t$$

$$\tilde{\sigma}_{t+1}^2|(cp_t = 1) = \hat{\sigma}_{exp}^2$$

(Eq. 1)

On the other hand, if there was no changepoint at timepoint t, then there are multiple relevant stimuli over which the agent should compute the mean. Fortunately, one does not have to remember all stimuli locations since the last changepoint. Instead, Bayesian observers compute the mean iteratively via reliability-weighted integration (which implies that they only have to remember the current mean and associated variance):

$$\tilde{\mu}_{t+1}|(cp_t = 0) = (1 - \tau_t)x_t + \tau_t\tilde{\mu}_t = x_t + \tau_t(\tilde{\mu}_t - x_t)$$

$$\tilde{\sigma}_{t+1}^2|(cp_t = 0) = \tau_t\tilde{\sigma}_t^2 \tag{Eq. 2}$$

where the weight τ_t, termed 'prior reliability', is computed as a relative measure of prior precision (i.e., reciprocal of variance):

$$\tau_t = \frac{\tilde{\sigma}_t^{-2}}{\hat{\sigma}_{exp}^{-2} + \tilde{\sigma}_t^{-2}} = \frac{\hat{\sigma}_{exp}^2}{\hat{\sigma}_{exp}^2 + \tilde{\sigma}_t^2} \tag{Eq. 3}$$

Notice how we expressed the predicted generative mean as a sum of the last stimulus location and a bias towards the prior. The normalized bias size (between 0 and 1, for predictions at x_t and $\tilde{\mu}_t$, respectively) is equal to the prior reliability τ_t. Notice further how the spatial uncertainty about the generative mean decreases with integration because $0 \le \tau_t < 1$. In the absence of changepoints, the spatial uncertainty would be reduced by a factor that is equal to the inverse of the number of observations (c.f. standard error of the mean).

New evidence should be integrated with prior beliefs (Eq. 2) when the two relate to the same generative mean, and they should be segregated (Eq. 1) when they belong to different generative means, i.e., after a changepoint (Figure 1A). But how does one know whether a changepoint has occurred? A Bayesian observer infers this from the posterior probability of no changepoint, Π_t, termed 'prior relevance' (Krishnamurthy, Nassar, et al., 2017). Since it is a posterior measure, Π_t depends on a combination of pre-existing beliefs and an evaluation of the newest observation. To be able to separate these two contributions, we present the formula for the posterior log odds of no changepoint, Q_t, i.e., the logit transform of Π_t:

$$Q_t = \log\left(\frac{\Pi_t}{1 - \Pi_t}\right) = \log\left(\frac{(\hat{H}_{cp}^{-1} - 1)(b - a)}{\sqrt{2\pi}\sqrt{(\tilde{\sigma}_t^2 + \hat{\sigma}_{exp}^2)}}\right) - \frac{1}{2}\frac{(\tilde{\mu}_t - x_t)^2}{(\tilde{\sigma}_t^2 + \hat{\sigma}_{exp}^2)}$$

$$\tag{Eq. 4}$$

$$\Pi_t = \frac{1}{1 + e^{-Q_t}}$$

where the unbounded quantity Q_t is back-transformed to the posterior probability, $0 \le \Pi_t \le 1$, via the monotonic logistic function.

The first term (within the logarithm) represents an a-priori belief about the prior's relevance that is independent of the last stimulus location x_t. The prior's relevance decreases with a larger changepoint hazard rate estimate, $\hat{H}_{cp}$, it increases with a larger spatial range of the generative mean $(b - a)$, and it decreases with more uncertainty about the location of the upcoming stimulus ($\tilde{\sigma}_t^2 + \hat{\sigma}_{exp}^2$, i.e., summed variance of prior on μ_t and experimental noise). The second term specifies by how much the (logit-transformed) prior relevance decreases as a function of the squared prediction error, i.e., after having observed x_t (Figure 1B). Importantly, a particular squared prediction error reduces the prior relevance by a smaller amount when the a-priori uncertainty about the stimulus location was larger. This precision-weighted squared prediction error term can thus be intuitively interpreted as a measure of surprise about the latest stimulus location x_t that is conditional on the prior's relative location and uncertainty (see section 4.4).

Finally, the reduced Bayesian observer computes its prediction for the generative mean as a weighted combination of the two causal structures: changepoint or not. The weights are determined by the prior relevance:

$$\tilde{\mu}_{t+1} = (1 - \Pi_t)\tilde{\mu}_{t+1}|(cp_t = 1) + \Pi_t\tilde{\mu}_{t+1}|(cp_t = 0) = x_t + \Pi_t\tau_t(\tilde{\mu}_t - x_t)$$

$$\tilde{\sigma}^2{}_{t+1} = (1 - \Pi_t)\hat{\sigma}^2_{exp} + \Pi_t\tau_t\tilde{\sigma}^2_t + \Pi_t(1 - \Pi_t)\tau_t^2(\tilde{\mu}_t - x_t)^2 \qquad \text{(Eq. 5)}$$

where we have once again expressed the prediction for the generative mean as a sum of the last stimulus location and a bias towards the prior. The normalized bias size is equal to the product of prior reliability τ_t and prior relevance Π_t (Figure 1C; see also section 4.5). Note that the predicted spatial uncertainty is formed by a weighted average of the variances of the two causal structures plus a third term that indicates the additional variance due to the causal uncertainty, $\Pi_t(1 - \Pi_t)$, which further depends on the squared prediction error and prior reliability. The contribution of this causal uncertainty term can be considerable. Because of it, the spatial uncertainty about the generative mean based on multiple stimuli can even exceed the spatial uncertainty based on a single stimulus ($\hat{\sigma}^2_{exp}$) in situations where there is a high degree of causal uncertainty about whether or not a changepoint occurred (Figure 1D).

While it may seem counterintuitive to update one's beliefs with the (weighted) average of two distinct possibilities (changepoint or not), thus placing one's best prediction for upcoming stimuli somewhere in the middle where neither causal explanation matches particularly well, we emphasize that such concerns are unjustified. The prior relevance drops to near-zero for large prediction errors, so that the weighted average does not significantly bias one's belief towards the prior (Figure 1C). Instead, the resulting prediction would be near the latest sensory evidence, in accordance with what one should expect after a noticeable changepoint. As the prediction error decreases in size, the prior relevance and resulting bias increase, and the updated belief will be exactly in the middle when $\Pi_t\tau_t = 0.5$. However, as the prediction error decreases, we also effectively increase the amount of overlap between the two posterior component distributions, conditional on a changepoint or not (Eqs. 1-2; Figure 1A, dashed yellow lines in bottom panel). This means that the weighted average prediction $\tilde{\mu}_{t+1}$ in such cases will actually be relatively well supported by both causal explanations.

2.2 Qualitative evaluation

In this section, we will compare general patterns and trends in the predictions of the reduced Bayesian observer model (Eqs. 3-5) against the behavioral responses of the participants. To gain further insights about the model and participants' perceptual decision making, we will also contrast them against predictions of two other hypothetical observers.

The first hypothetical observer is naïve to the generative process of the stimuli sequences or chooses to ignore it. The naïve observer bases its prediction responses on the last observed stimulus location exclusively: $\tilde{\mu}_{t+1} = x_t$. Within the computational framework of the reduced Bayesian observer this behavior can be achieved by setting the estimate of the changepoint hazard rate equal to one, $\hat{H}_{cp} = 1$, which results in a constant prior relevance of zero, $\Pi_t = 0$. The naïve observer is non-Bayesian because it never integrates new evidence with prior beliefs. Hence, it is unable to decrease its prediction errors after observing multiple stimuli from the same generative mean. However, one could argue that the naïve observer opts for a cost-effective strategy in an uncertain environment: it avoids complex computations entirely in exchange for moderately larger but unbiased prediction errors (Eissa et al., 2022).

The second hypothetical observer is omniscient with regards to the changepoints. In other words, this unrealistic observer has full knowledge over when changepoints occur and thus

experiences no causal uncertainty. It correctly sets the prior relevance Π_t to either zero ($cp_t = 1$) or to one ($cp_t = 0$) and it subsequently updates its beliefs about the generative mean according to Eqs. 3 and 5. Predictions of the omniscient observer are thus based on the mean location of all observed stimuli since the last changepoint. The omniscient observer sets a comparative benchmark for performance under conditions without causal uncertainty.

In a first analysis, we compare the predicted generative means of the omniscient observer against participants' prediction responses (Figure 2A). In general, they are highly correlated (Pearson's ρ = 0.98 [0.96 – 0.99] and ρ = 0.95 [0.94 – 0.96], for the low and high noise conditions, respectively. N.b. we consistently report group-level median [Q1 – Q3]). There was only a very small bias towards the centre of space for the participants' responses overall (regression slope = 0.96 [0.92 – 0.98] and 0.94 [0.90 – 0.98]). These minor biases are in accordance with the reduced Bayesian observer model, and they are predominantly caused by a regression to the mean due to partial integration with stimuli prior to unnoticed changepoints. Importantly, a fully Bayesian ideal observer model portrays much larger central biases, because it attempts to mitigate potentially large prediction errors in case of a changepoint at the upcoming timepoint by multiplying its estimate of the current generative mean by a factor that depends on the changepoint hazard rate ($1 - \widehat{H}_{cp}$, i.e., regression slopes < 0.85; see section 4.6). We conclude that participants did not adjust their predictions for the possibility of an upcoming changepoint, and instead they seem to have provided responses based on their belief about the current generative mean. This has been reported previously (Nassar et al., 2010) and was thus implemented in the reduced Bayesian observer model (and all other model variations that were tested here, see section 2.4).

Figure 2. Participants' prediction responses are reasonably accurate, but the reduced Bayesian observer model with default parameters performs better.

A). On average, participants' responses correlate well with the omniscient observer model for the two experimental noise conditions (left and right panels). The fully Bayesian observer biases its predictions towards the centre of space to accommodate potentially upcoming changepoints. This bias is not present for participants, and it is therefore not modelled for the other observers (naïve, omniscient, and reduced Bayesian, with default parameters or with parameters that were fit to the participants' data; see section 2.3).

B-C). The response error relative to the true generative mean (unknown) decreases with larger SAC levels due to integration of consecutive stimuli, but participants' absolute error remains larger than the naïve observer because of additional response noise (panel B). When the errors are normalized with respect to the naïve observer's responses (at 1), then the random response noise averages out and the relative accuracy improvement becomes visible (panel C).

The traces in all panels depict the group-level median of the individuals' median response, per SAC bin (in B-C), or using a rolling kernel method (in A). Note that the rolling median results in small edge artifacts (panel A), with an apparent central bias for peripheral locations even for the naïve observer (and in addition to the integration-based bias for the other observers). The blue shaded region depicts the range between the group-level 25% (Q1) and 75% (Q3) participants.

Perhaps the most important prediction that any Bayesian observer model makes is that its accuracy should (generally) improve by integrating the newest evidence with prior beliefs. We would thus expect the average absolute error to decrease in size as more stimuli are integrated. Figure 2B shows that this is certainly true for the omniscient observer, whose errors relative to the true generative mean μ_t decrease as the number of stimuli after [the last] changepoint (SAC) increases. Participants also reduced their errors relative to SAC level 1, but they did not improve further when more than two stimuli were observed after the last changepoint: A 2 x 5 repeated measures ANOVA shows a main effect of low vs. high noise, $F(1,28) = 397$, $p < .001$, and a main effect of SAC level, $F(4,112) = 25.2$, $p < .001$; post hoc tests with Holm correction confirm the differences between SAC 1 and all other levels, $p < .001$, but no other pairwise differences reach significance, $p > 0.05$.

So, participants reduced their errors when more than one stimulus was available after a changepoint. Nevertheless, they did not outperform the naïve observer that simply predicts the next stimulus at the location of the last stimulus. This may suggest that it would have been better for participants to adopt the same naïve strategy instead of attempting to infer when changepoints occur and integrate relevant stimuli. However, we argue that participants' worse performance can be explained by additional random noise in the response phase, i.e., following the perceptual decision (see section 4.8, but not included in the models for this analysis). Such response noise could, for example, arise due to imprecision of the sensorimotor system or because of a self-imposed speed-accuracy trade-off. Support for the hypothesis of additive post-decision response noise comes from the analysis of errors that were normalized with respect to the naïve observer (Figure 2C). Single-trial normalization was achieved by dividing the actual error ($response - \mu_t$) by the difference between last stimulus and generative mean ($x_t -$

μ_t), such that a response at x_t receives a normalized error of 1 (constant for the naïve observer),
while a response at μ_t naturally results in a normalized error of 0 (see section 4.11). Contrary to
the absolute errors (Figure 2B), this procedure enables us to average out random response
noise in the normalized errors. The analysis clearly demonstrates that participants reduced
their average normalized errors relative to the naïve observer as they integrated evidence over
multiple stimuli (sign tests: $p < .005$ for all SAC > 1 in both noise conditions, Bonferroni
corrected).

The reduced Bayesian observer model predicts smaller errors (both absolute and normalized)
than those of the participants. However, its performance is worse than the omniscient observer,
thus illustrating the effect of causal uncertainty, i.e., the ambiguity about the veracity of
changepoints. Errors will be larger if a true changepoint is misinterpreted as an outlier due to
random noise (SAC 1), and vice versa, errors will also be larger if a changepoint cannot be ruled
out after observing an actual outlier (SAC > 1). One can see that the reduced Bayesian observer
struggles more with causal uncertainty in the high noise condition, as the difference with the
omniscient observer's performance is larger in the high noise condition as compared to the low
noise condition, especially for low SAC levels. Note that the Bayesian observer performs worse
than the naïve observer at SAC 1 (higher absolute error, Figure 2B), thus indicating a trade-off in
adopting Bayesian causal inference: it improves performance overall, but it exacerbates errors
after environmental changes. Participants, on the other hand, may have used a more
conservative, risk-averse strategy in which they only moderately benefit from integration, but
also attempt to avoid making large errors after changepoints.

Accuracy improvement with increasing SAC levels is achieved in the reduced Bayesian observer
model by biasing its beliefs towards the prior, relative to the latest evidence. In Figure 3A we
show that participants also exhibit such biases. Since it is impossible to know the covert prior
beliefs of participants, we instead used the predicted prior beliefs of the omniscient observer
(i.e., the mean of all stimuli since the last changepoint) to compute the normalized biases (for
both participants and modelled data). This prior location is probably not precise, but it allows us
to approximate the experienced prediction error for the latest observation within a reasonable
margin, i.e., $(\tilde{\mu}_t - x_t) \approx (\tilde{\mu}_{t,omni} - x_t)$. We thus computed participants' normalized bias
towards the prior as $(response - x_t)/(\tilde{\mu}_{t,omni} - x_t)$, where a response at $\tilde{\mu}_{t,omni}$ results in 1,
and a response at x_t indicates no bias. Note that this normalized bias corresponds to the
product of prior relevance and reliability, $\Pi_t \tau_t$, in Eq. 5 (although for the figure we computed the
modelled biases in the same way as for the participants' responses).

In Figure 3A, we have limited the analysis to SAC 1 trials only in order to clearly demonstrate the
effect of increasingly large prediction errors. The pattern of a gradually decreasing normalized
bias is similar to what is predicted by the reduced Bayesian observer model. This suggests that
participants do indeed compute a prior relevance measure (Eq. 4) and use it to adaptively scale
their bias towards the prior (Eq. 5). In doing so, they effectively computed a weighted average of
the two causal structures (changepoint or not) and thus incorporated causal uncertainty into
their updated belief. Furthermore, we also observe an effect of the experimental noise
condition. Relative to the low noise condition, the maximal bias for the high noise condition is
smaller for small prediction errors (Wilcoxon signed rank test on biases at 20° prediction error: z
= -1.98, $p = 0.048$, low noise = 0.17 [0.10 – 0.42], high noise = 0.13 [0.06 – 0.27]), but the bias
remains higher for moderately large prediction errors (Wilcoxon signed rank test on biases at 40°
prediction error: $z = 2.02$, $p = 0.043$, low noise = 0.09 [0.02 – 0.13], high noise = 0.10 [0.07 –
0.14]). Both of these effects were predicted by Eq. 4 of the reduced Bayesian observer model via

the noise dependence in the denominators of the a-priori relevance (peak bias for small
2   predictions errors) and surprise term (reduction of relevance with prediction error size).

Figure 3. Normalized bias towards the prior (at 1) for SAC 1 trials (panel A) and signed bias
towards the prior (positive sign) for SAC 2 and SAC 3 trials (panel B), as a function of the
experienced prediction error. The prior's location was approximated by means of the
omniscient observer.

The traces depict the group-level median of the individuals' local median response, as
computed via a rolling kernel method. For appropriateness of that procedure, the
prediction errors were non-linearly scaled to approximate a constant density of trials over
the x-axis. Note that the rolling median results in small edge artifacts which cause the
signed bias to appear larger than zero for the smallest prediction errors.

The blue shaded region depicts the range between the group-level 25% (Q1) and 75% (Q3)
participants. For the modelled observers we only depict the group-level medians (naïve,
omniscient, and reduced Bayesian, with default parameters or with parameters that were
fit to the participants' data; see section 2.3).

Next, we looked at the biases for SAC levels 2 and 3 (Figure 3B). Since the effect of small
misestimations of participants' prior (i.e., $\tilde{\mu}_t \neq \tilde{\mu}_{t,omni}$) leads to excessive amounts of noise in
the normalized biases at small prediction errors (see shaded area in Figure 3A), we instead
focus here on non-normalized biases ($response - x_t$). However, we modified the bias signs to
ensure that a positive bias always points towards the predicted prior location ($\tilde{\mu}_{t,omni}$).

Importantly, we only included SAC 2 trials for this analysis if they were preceded by a large prediction error (>52.7°, as determined by a median split), such that the preceding changepoint had likely been noticed. Hence, the spatial prior for these SAC 2 trials should have been based on the preceding stimulus only. Likewise, we limited the analyses of SAC 3 trials to those trials that were associated with a large changepoint prediction error (>52.7°), followed by a relatively small disparity between the next stimuli (i.e., $|x_{t-2} - x_{t-1}|$ had to be <13.7° or <27.4° for the low and high noise conditions, respectively; where the threshold values were based on excluding one third of the trials with the largest disparities). Hence, the spatial prior for these SAC 3 trials should have been based on the average of the two preceding stimuli, and the prior's spatial uncertainty ($\tilde{\sigma}_t^2$) for these SAC 3 trials should thus be smaller than the prior's uncertainty for the SAC 2 trials.

The general pattern of the signed biases in Figure 3B is similar as predicted by the reduced Bayesian observer model: the bias towards the prior increases in size with increasing prediction errors, but then starts to flatten and eventually decrease at larger prediction errors as a result of the smaller prior relevance (Π_t). The peak of participants' signed biases is approximately reached at a prediction error that is similar to the experimental noise, 10° and 20°. For larger prediction errors, participants apparently already start to question whether a changepoint has occurred. The reduced Bayesian observer model peaks later, at approximately 29° and 26° with low noise and 53° and 47° in the high noise condition, for SAC 2 and SAC 3 trials respectively. The predicted differences between the SAC levels occur because the spatial uncertainty of the prior $\tilde{\sigma}_t^2$ is smaller for SAC 3 than SAC 2, which increases the surprise (2nd term in Eq. 4), thus lowering the prior relevance at smaller prediction errors. These predicted small differences are not clearly observed in the participants' data. However, another model prediction is that the size of the biases are larger for SAC 3 than for SAC 2, independent of the prediction error, because of a difference in the prior reliability τ_t (Eq. 3). Participants show this effect in the high noise condition (Wilcoxon signed rank test on biases at 20° prediction error: z = 2.15, p = 0.031, SAC 2 = 2.31° [1.02° – 6.25°], SAC 3 = 5.40 [2.23 – 7.74]), but not in the low noise condition (Wilcoxon signed rank test on biases at 10° prediction error: z = 0.42, p = 0.67, SAC 2 = 2.67° [1.08° – 4.54°], SAC 3 = 2.34 [1.28 – 5.73]).

2.3 Parameter optimization

In the above analyses we have shown that hallmarks of Bayesian causal inference are present in the response patterns of the participants. However, quantitatively, the reduced Bayesian observer model with default parameters ($\hat{H}_{cp} = 0.15$ and $\hat{\sigma}_{exp} = 10°$ or 20°, for low and high noise conditions, respectively) does not show a very good fit. In particular, the model severely overestimates participants' biases towards the prior. Assuming that the principal mechanisms for Bayesian causal inference are present in the brain (Sham & Beierholm, 2022), one plausible suggestion to reconcile the experimental results to the theoretical predictions is that participants were using incorrect estimates of the model's parameters (Nassar et al., 2010). For example, larger changepoint hazard rate estimates, $\hat{H}_{cp}$, would have the effect of decreasing the prior relevance Π_t independent of the prediction error, thus resulting in smaller biases overall.

Participants were given the opportunity to learn about the changepoint hazard rate (H_{cp}) and the amount of experimental noise (σ_{exp}) in both conditions in a practice session. However, learning these parameters by merely observing the stimuli locations is no easy task (Wilson et al., 2010; Piray & Daw, 2021). A large prediction error may indicate that a changepoint occurred. If many

changepoints are inferred, then the subjective hazard rate estimate should be larger. But prediction errors can alternatively be interpreted as due to random noise, in which case the subjective experimental noise estimate should be larger. Inference about the parameters of the generative process thus essentially revolves around a volatility (changepoint) vs. stochasticity (noise) trade-off, similar to the causal inference problem itself. Therefore, we would expect the two parameter estimates, $\widehat{H}_{cp}$ and $\hat{\sigma}_{exp}$, to be anticorrelated.

One method that the brain may apply to learn such 'environmental parameters' is based on an objective to minimize overall surprise (Friston, 2010). Without specifying how such a learning algorithm may work, we here computed the overall surprise that a reduced Bayesian observer would experience in the current experiment (i.e., summed over all stimuli) for a large number of predetermined parameter combinations ($\widehat{H}_{cp}$ and $\hat{\sigma}_{exp}$) on a regular grid (see section 4.10). The predicted amounts of surprise are visualized as a background colour coding in Figure 4A. One can see that an agent with parameter estimates near the true values ($\widehat{H}_{cp}$ = 0.15 and $\hat{\sigma}_{exp}$ = 10° or 20°) minimizes the overall surprise. Some parameter combinations are predicted to lead to excessively high amounts of surprise (e.g., low $\widehat{H}_{cp}$ and low $\hat{\sigma}_{exp}$), thus indicating that such parameter estimates would lead to a significant mismatch between the stimuli locations that are predicted and those that are experienced. However, for many parameter combinations near the true values, surprisal remains relatively low. This suggests that all such estimates are reasonably likely for near-Bayesian observers that effectively learn the statistics of their sensory environment. The expected anticorrelation between the hazard rate and experimental noise estimates is highlighted as a dashed line (indicating the value of $\hat{\sigma}_{exp}$ that minimizes surprisal for a particular value of $\widehat{H}_{cp}$).

Figure 4. Fitted parameter values of the reduced Bayesian observer model.

Panel A. depicts the fitted changepoint hazard rate ($\widehat{H}_{cp}$) and experimental noise ($\widehat{\sigma}_{exp}$)
estimates of the individual participants (separately for both experimental noise
conditions, in left and right panel) on top of a modelled surface of overall (summed)
surprisal levels that a reduced Bayesian observer would experience with such parameter
values. Surprisal is minimized for parameter estimates that are equal to the true generative
parameter values (thin dotted black lines). The dashed black lines illustrate the expected
negative correlation between hazard rate and experimental noise estimates.

Panels B and C show the same fitted hazard rates and experimental noise estimates, but
now as a comparison of the noise conditions.

Individuals' colour coding depends on the model comparison results (section 2.4 and
Figure 6B): dark red for participants that are better fit by models with a larger memory
capacity, light red for participants that are better fit by the reduced Bayesian observer
model with limited memory capacity, and grey otherwise.

To obtain estimates of the parameters that participants may have used during the task we fitted
the reduced Bayesian observer model to each set of responses from one individual and one
experimental noise condition (by means of maximum likelihood estimation, see section 4.9). As
expected by the relatively low biases (see Figure 3), we found that the fitted hazard rates for
most participants were much higher than the true hazard rate (Figure 4B). While there was
considerable variance of the fitted hazard rates across participants, the values per participant
were quite consistent across the two experimental conditions (Pearson's correlation coefficient
ρ = 0.81). Furthermore, we found that the fitted experimental noise parameters (Figure 4C) were
reasonably accurate for most participants, though not for all, and they were smaller in the low
noise condition than in the high noise condition (low noise $\widehat{\sigma}_{exp}$ = 15.4° [12.2° – 25.4°], high
noise $\widehat{\sigma}_{exp}$ = 20.4° [16.5° – 25.5°], Wilcoxon signed rank test: z = -2.17, p = 0.030). Interestingly,
we did not observe the predicted negative correlation between the fitted hazard rates and log-
transformed experimental noise parameters (Pearson's ρ = -0.04 and ρ = -0.02, for low and high
noise condition respectively, but these correlations were not significant: p > 0.8). In fact, most
of the largest experimental noise parameters were for participants whose hazard rate estimates
were also large (Figure 4A). Those participants showed overall small biases (large $\widehat{H}_{cp}$) that were
nonetheless non-zero even at large prediction errors (large $\widehat{\sigma}_{exp}$).

Allowing the changepoint hazard rate and experimental noise parameters to be fitted freely
significantly improved the quality of the fits in terms of the coefficient of determination: R^2 =
0.97 [0.92 – 0.98] and R^2 = 0.94 [0.88 – 0.97], for low and high noise conditions, respectively. This
is marginally higher (~1% point) than the reduced Bayesian observer model with default
parameter values, i.e., with $\widehat{H}_{cp}$ = 0.15 and $\widehat{\sigma}_{exp}$ = 10° or $\widehat{\sigma}_{exp}$ = 20° (Wilcoxon signed rank tests: z
> 4, p < .001, for both conditions), and equally better than the naïve observer model (z > 4, p <
.001, for both conditions). A more informative measure for the model's improvement in quality
of fit is the amount of explained variation in participants' errors ($response - \mu_t$, i.e., as in
Figures 2B and 2C). The group-level medians are R^2 = 0.45 vs. 0.36 vs. 0.28, and R^2 = 0.67 vs.
0.53 vs. 0.57, for the three models (reduced Bayesian model with fitted parameters, vs. with
default parameters, vs. the naïve observer model) in the low and high noise conditions,
respectively. N.b. remaining response variance was explained by the fitted reduced Bayesian

observer model by means of occasional lapses (lapse rates λ = 0.017 [0.008 - 0.045] and λ =

0.043 [0.021 - 0.063], for low and high noise conditions, respectively) and by random response

noise (σ_{resp} = 5.64° [3.65° – 8.26°] and σ_{resp} = 5.93° [3.90° – 11.0°]). Nevertheless, depicted

predictions for the model with optimized parameter values in Figures 2 and 3 (dashed lines) do

not include such lapses or response noise.

<u>2.4 Model comparison</u>

The reduced Bayesian observer model is a simplification of the fully Bayesian observer model.

While the latter is unrealistic because of its complexity, the former is certainly not the only

plausible inference algorithm. Here, we will compare the reduced Bayesian observer model

against variations of itself that rely on different modelling assumptions.

Figure 5. Illustration of the modelling framework with four factors: memory capacity (A),

late truncation simplification (B), decision strategy (C), and pruning function (D).

A). The three panels depict a sequence of three stimuli (top to bottom) that illustrate the

inference difference between a reduced Bayesian observer (M = 1, posterior depicted as

dashed red line) and a similar Bayesian model with larger memory capacity (M ≥ 3, solid

orange line with shaded area). Posterior distributions of models with extended memory

consist of a weighted mixture of multiple nodes (dashed orange lines with a, b, and c letter

indicators). The node's weight indicates its relative posterior relevance for the inferred

location of the generative mean. In this sequence, the second stimulus leads to high

causal uncertainty (nearly equal weight for both nodes: a. latest cp at *t=1*, b. latest cp at

***t*=2), but the third stimulus increases the inferred relevance of the node that codes for the**

hypothesis that no changepoint took place (a): i.e., it is most probable that all three stimuli stem from the same generative mean, and it is least probable that a changepoint took place at *t*=3 (c). The reduced Bayesian observer cannot retrospectively reassign weights to nodes and is therefore slightly less accurate (here: small bias towards penultimate stimulus) and less precise (larger spatial uncertainty) than a near-Bayesian observer with larger memory capacity.

B). The late truncation simplification implies that the space boundaries are ignored until a response has to be given. At that point, the observer's best prediction is moved to within the generative mean range, only if necessary. Without the simplification, observers compute the expectation (i.e., mean) of the truncated normal distribution as their best prediction, and this will bias their response towards the centre of space. Here, the difference is illustrated for a response at *t*=1 (from panel A). With the simplification, the observer responds to the mean of the (non-truncated) normal distribution: subsequent movement of the intended response location to within the generative mean range is unnecessary in this example.

C). Whenever the posterior distribution consists of more than one node, the observer needs to decide on how to make a response (here depicted for *t*=2). The model averaging decision function computes the expectation of the weighted mixture distribution as its best prediction, thus essentially averaging two models of the world (i.e., nodes a and b). Instead, the model selection decision function deterministically selects the node with the highest weight (i.e., inferred relevance) as a base for its prediction response.

D). The node pruning function determines how an observer satisfies the memory capacity limit *M*. Whenever the number of posterior nodes exceeds the memory capacity, the pruning function ensures that the prior for *t+1* consists of no more than *M* nodes. Here, this is depicted for the case at *t*=3, with a memory capacity of M=2. The keep_*WAVG* pruning function merges the oldest two nodes (a and b) by computing a weighted average node (while the newest node, c, for a cp at t=3, remains in memory as well, despite its small weight). The keep_*MAXP* pruning function keeps the node with the highest weight of the oldest two nodes and discards the other (i.e., node a is kept, b is discarded), whereas the keep_*RCNT* pruning function always keeps the most recent of the two oldest nodes (i.e., node b is kept, a is discarded). The node that is kept in memory also receives the weight of the discarded node, such that it now represents the hypothesis of a cp at t ≤ 2.

The most striking simplification of the reduced Bayesian observer model is its limited memory requirement. The prior distribution at any timepoint is described by merely two parameters: the mean and uncertainty estimates about the generative mean ($\tilde{\mu}_{t+1}$ and $\tilde{\sigma}_{t+1}^2$, respectively). That prior distribution approximates the weighted mixture of the two conditional prior distributions for each causal structure with regards to the preceding stimulus: there was a changepoint, or not. The fully Bayesian observer model (Adams & MacKay, 2007) does not compute such approximate summary distributions. Instead, it remembers the conditional distributions and their associated weights (i.e., relevance). The advantage is that the weights of the conditional distributions can still be adjusted after new observations become available. For example, an agent may be uncertain about a possible changepoint at first, but this uncertainty may disappear if the next observation returns to a location that fits better with the previous prior. In that case, the spatial prediction of a fully Bayesian observer would correctly be dominated by

the mean of all relevant stimuli, despite the temporary causal uncertainty that accompanied the penultimate stimulus. On the other hand, the memory-constrained reduced Bayesian observer's prediction would generally be (slightly) less accurate (and more uncertain) because the observations are not weighted optimally: weight cannot be returned to observations whose relevance was once questioned (Figure 5A).

So, being able to juggle multiple competing hypotheses simultaneously is beneficial for task performance. Moreover, it seems intuitive that humans are able to remember the approximate locations of at least a few recent stimuli, while also maintaining uncertainty about the presence of recent changepoints. Therefore, one of the primary factors of interest in our model comparison was the model's memory capacity. We compared models whose predictive mixture distributions consisted of up to four conditional distributions, i.e., memory capacity $M \in$ {1,2,3,4}. These conditional distributions are often referred to as 'nodes' of the full mixture distribution (e.g., Wilson et al., 2010, where the terminology is based on a graphical model depiction). Here, each node is represented by three parameters: its mean, variance, and weight (see section 4.3).

The reduced Bayesian observer model limits the memory capacity to $M = 1$ by summarizing its two conditional distributions via a weighted average (Eq. 5) after every observation. Essentially, it thus merges two nodes into one at every timepoint. We can flexibly extend the model's memory capacity by merging progressively older nodes. The newest nodes, that are conditional on the hypothesis of a recent changepoint, and whose contributing stimuli are still fresh in memory, remain unchanged. For example, a model with a memory capacity of $M = 4$ would summarize its oldest two nodes such that the merged node is associated with the hypothesis that the last changepoint occurred four *or more* stimuli ago, while the latest three nodes are also kept in memory (see section 4.5).

Besides merging nodes via a *weighted average* (i.e., keep_*WAVG* node), one can also constrain the memory requirements via different rules (Figure 5D). For example, it has been suggested that humans may simply forget the oldest node once memory capacity has been exceeded (Skerritt-Davis & Elhilali, 2018). In that case an agent would only remember evidence that is associated with the hypotheses of a changepoint at any of the *recent* timepoints (keep_*RCNT*). A third option that was proposed previously (Adams & MacKay, 2007) is to discard nodes based on their inferred relevance (i.e., the nodes' weights). In our implementation here, we keep either of the two oldest nodes, whichever has a *larger probability* of being relevant (keep_*MAXP*). We refer to these three procedures as node pruning functions (Wilson et al., 2010). Note that a model with the keep_*RCNT* pruning function and with minimal memory capacity, $M = 1$, is identical to the naïve observer model that we introduced in section 2.2.

Whenever the prior distribution consists of more than one node at the end of a trial ($M > 1$), the observer needs to decide on how to form a single prediction response out of the mixture distribution (see section 4.6). A Bayesian observer that attempts to minimize its squared errors computes a weighted average of the nodes' means as its best prediction for the generative mean. Since each node is associated with a particular model of the world (i.e., causal structure), specifying when the last changepoint occurred, this decision strategy is known as 'model averaging' (Wozny et al., 2010). The consequence of model averaging is that an agent accepts to be somewhat wrong about the state of the world most of the time, but it avoids occasionally making excessively large errors. However, different strategies are also possible (Figure 5C). For example, under the 'model selection' decision strategy, an agent would instead

attempt to maximize its accuracy most of the time, while occasionally accepting a large error.
This agent selects the mean of the node with the largest weight (i.e., relevance) as its best
prediction for the location of the generative mean.

A final factor that we consider in our model comparison is related to the computational
complexity that arises as a result of the finite spatial interval of the generative mean μ_t (i.e., here
between -90° and 90°). Bayesian observers account for the interval when they update the
weights of the nodes by means of a complex computation that depends on the distance of the
stimulus location to the interval's boundaries (section 4.3) and again in the response decision
phase when they compute the spatial expectations of the nodes (section 4.6). However, these
complex computations can be omitted at the cost of a limited accuracy loss by only considering
the interval constraint at the very end of the decision-making process. Under the late truncation
simplification hypothesis (Figure 5B) spatial predictions are initially formed using simplified
computations which do not account for the locations of the stimuli relative to the spatial
boundaries, but the final prediction is moved to the nearest boundary if it would otherwise be
outside of the generative mean interval (section 4.7). Note that the reduced Bayesian observer
model makes use of the late truncation simplification.

In the above, we have described a framework of near-Bayesian models in which we combine the
following factors: 1) memory capacity, 2) node pruning function, 3) decision strategy, and 4) late
truncation simplification (Figure 5). In total, we fitted 42 model variations. There were 6 models
with a minimal memory capacity ($M = 1$), one for each of the three pruning functions
(keep_*WAVG*, keep_*MAXP*, and keep_*RCNT*) with and without the late truncation simplification.
The other 36 model versions with larger memory capacity were organized factorially for $M \in$
$\{2, 3, 4\}$, the three pruning functions, two decision strategies, and with and without truncation
simplification. Since we fitted each model separately to the responses of both experimental
noise conditions (to be able to compare the fitted parameters independently, see Figure 4),
there were 84 model fits per subject. The models' abilities to predict participants responses
were compared by means of the log model evidence (*lme*; higher values indicate better fits),
which is based on a sum of the maximized log likelihoods of the two conditions (see section
4.9).

Figure 6A depicts the group-level results for a fixed effects analysis (i.e., summed *lme* over
participants). That analysis serves as a useful overview of the relative differences in predictive
performance of all the models. However, we will draw conclusions from a selection of family-
wise random effects analyses that are more robust to outlier subjects by allowing for group-
level heterogeneity (Stephan et al., 2009; Rigoux et al., 2014; Acerbi et al., 2018). First, we focus
on a comparison of the six models with $M = 1$. A 3 x 2 factorial analysis revealed a strong
preference for the keep_*WAVG* pruning function (protected exceedance probability *pxp* = 1.00
for keep_*WAVG vs. 0.00* for both keep_*MAXP* and keep_*RCNT*) and a moderate preference for
the late truncation simplification (*pxp* = 0.73 vs. 0.27). Next, we examined the 36 larger memory
capacity models in a 3 x 3 x 2 x 2 factorial analysis. The result confirmed the preferences for the
keep_*WAVG* pruning function and the late truncation simplification (*pxp* = 0.93 for keep_*WAVG*
vs. 0.04 for keep_*MAXP* vs. 0.03 for keep_*RCNT*; and *pxp* = 0.96 vs. 0.04 in favour of the
simplification). Moreover, the model averaging decision strategy seems to be crucial for larger
memory models to fit participants' responses well (*pxp* = 0.97 for model averaging vs. 0.03 for
model selection). The fixed effects analysis, as depicted in Figure 6A, demonstrates that the
choice of pruning function loses importance as the model's memory capacity increases, while

the model-averaging decision strategy becomes increasingly decisive as more nodes are
available for a response decision.

Figure 6. Model Comparison Results. Panel A shows the fixed effects model comparison
for the 42 models. The y-axis denotes the log model evidence (*lme*) of each model,
summed across participants, relative to the reduced Bayesian observer model (memory
capacity *M* = 1, keep_*WAVG* pruning function, model averaging decision strategy, and with
late truncation simplification). The *lme* difference is dominated by the pruning function
(colour coding) at low memory capacity (x-axis), while it is dominated by the decision
strategy (light vs. dark) at larger memory capacities. Models with the model averaging
decision strategy fit participants' data better with the late truncation simplification, while
models with the selection decision strategy generally fit better without the simplification.
Panel B zooms in on the individual results of the memory capacity factor (x-axis), for
models with keep_*WAVG* pruning function, model averaging decision strategy, and with
late truncation simplification. Each line depicts the *lme* differences for one participant.
The colour coding separates participants that were better fit by models with larger memory
capacity (dark red), and participants who responded more like reduced Bayesian observers
(light red), from participants without a clear preference (grey).

To be able to fairly compare all four memory capacity settings against each other, we selected
the four models that incorporated the late truncation simplification, the keep_*WAVG* pruning
function, and the model averaging decision strategy (i.e., the preferred settings based on the
previous analyses). The comparison was inconclusive, with an almost equal preference for each
memory capacity (*pxp* = 0.25 vs. 0.24 vs. 0.25 vs. 0.26, for M from 1 to 4, respectively). The
ambiguous result can be explained by a combination of two reasons that become clear when
we plot the log model evidence of these four models for each individual (Figure 6B). First, most
participants don't seem to show a significant preference for any of the memory capacity
settings (*lme* differences < 1, i.e., corresponding Bayes Factors < 3). Second, there is some

heterogeneity in the population with six participants that are better fit by the larger memory
capacity models, whereas the reduced Bayesian observer model ($M = 1$) is the best-fitting
model for four other participants. Figure 6B also demonstrates that there are only minimal
differences in the goodness-of-fit between the three larger memory capacity models. This is
because these models make very similar predictions. So, while a memory extension to $M = 2$ is
preferred to $M = 1$ by some participants (but not by others; a direct comparison is non-decisive:
pxp = 0.31 vs. 0.69 in favour of $M = 2$), adding more model complexity through further memory
extensions ($M > 2$) is not warranted by these results.

Finally, we note that there were only minimal differences between the fitted parameter values of
the reduced Bayesian observer model ($M = 1$) and its model variation with larger memory ($M = 2$).
2). The Pearson correlation coefficients, across participants, were ρ = 0.989 and ρ = 0.988 for
(log-) experimental noise parameters, and ρ = 0.997 and ρ = 0.998 for the hazard rates (low and
high noise conditions, respectively). Interestingly, we noticed a trend in the fitted parameter
values of the four participants with a preference for the M = 1 memory setting: they all had
relatively low hazard rates (<0.55, for both conditions; Figure 4B). This may potentially be
indicative of individual differences in decision strategies. However, we are cautious about any
such conclusion given the low number of participants with a clear model preference.

3. Discussion

In the current paper we have analysed the problem of changepoint detection in noisy
environments from a perspective of Bayesian causal inference (Shams & Beierholm, 2022). The
fundamental question that observers face is whether novel sensory signals should be integrated
with prior beliefs to improve precision, or whether an environmental change has occurred that
has rendered the prior irrelevant. The reduced Bayesian observer model (Nassar et al., 2010,
2012) puts this question centre stage after every new observation and then summarizes the
probabilistic result to keep complexity at a minimum. As such, it provides an elegantly simple
algorithm for iterative Bayesian causal inference that can be utilized to process consecutive
sensory input in volatile environments.

We tested the model's performance on a behavioral dataset wherein participants made
prediction responses after having been presented a sequence of noisy observations with
occasional changepoints (Krishnamurthy, Nassar, et al., 2017). Our analyses brought forth three
main findings: 1. The reduced Bayesian observer model predicted the response patterns
qualitatively well. 2. It required freely fitting the model's parameters to also quantitatively fit
well. 3. Model comparison favoured the reduced Bayesian observer model over many model
variations, but it was inconclusive with regards to the model's memory capacity. In what
follows, we shall discuss these three findings one by one and relate them to relevant literature in
general and previous reports of learning in volatile environments in particular.

3.1. Hallmarks of Bayesian causal inference

We have shown that observers were partially able to average out noise from sequential
observations during ongoing stimulus streams and thereby improved the accuracy of their
predictions when more than one stimulus was available to base their decision on. In line with
findings from cue integration experiments, they achieved this by weighing new sensory evidence
versus existing beliefs according to their relative reliabilities (Eq. 3; prior attraction is larger for
SAC 3 than for SAC 2 in the high noise condition). However, reliability is not the only factor that
determines integration weights (Meijer et al., 2019; Rahnev & Denison, 2018). Since observers
found themselves in a volatile environment, wherein prior information was not always relevant
for their predictions, they dynamically reduced the prior's weight in accordance with its inferred
relevance.

According to the reduced Bayesian observer model, the weight of the prior should be
determined by the product of prior reliability and prior relevance (Eq. 5). The latter depends on
an a-priori belief about the prior's relevance as well as a surprise-based posterior evaluation
(Eq. 4). In agreement with the model's predictions, we found that reliance on the prior was larger
in the low experimental noise condition than in the high experimental noise condition, at least
for relatively small spatial disparities between the prior's prediction and the latest observation.
As the prediction error grew larger, the prior's inferred relevance declined, and so we saw a
gradual decrease of the normalized bias towards the prior (i.e., a measure of the prior's weight).
Moreover, the biases decreased faster in the low noise condition, because moderate prediction
errors result in a larger surprise when the prior's predictive precision is larger. Vice versa, the
experimental condition with more stochastic noise led to flatter curves, thus less modulation of
the prior's weight (Ryali et al., 2018).

Smooth transitions from a large bias towards highly relevant priors, to near-zero biases for
irrelevant priors, as we observed here, are modelled via a weighted average between two causal
structures (i.e., models of the world that explain the causes of sensory signals: either the latest
observation came from the same source as the prior beliefs, or it came from a different source
because of a changepoint). In the reduced Bayesian observer model with limited memory (M=1)
weighted averaging is established via the keep_*WAVG* pruning function, while for models with
larger memory capacities this occurs primarily via the model averaging decision strategy.
Regardless, models that compute a weighted average over the causal structures explained
participants' responses significantly better than models that did not (e.g., model selection
decision strategy).

By computing a weighted average, an observer essentially accounts for the uncertainty about
the inferred causal structure. In the case of the reduced Bayesian observer model, the causal
uncertainty is also literally incorporated into the updated belief about the source location via an
additive term for the spatial uncertainty (Eq. 5). This effectively ensures that appropriately low
reliability is attributed to the updated prior at the next timestep if there was considerable
uncertainty about the occurrence of a changepoint at the current timestep (Nassar et al., 2012).
Interestingly, it was recently reported that patients with schizophrenia do not consistently
compute a weighted average over the causal structures, and instead more often select either
one or the other option (Nassar et al., 2021), thus potentially resulting in a false sense of
certainty about incorrect beliefs.

In the learning literature there has been a long-standing debate about the use of the prior
relevance measure as a flexible moderator for the extent to which beliefs should be updated
after a new observation. In that field it is common to speak of learning rates (taking perspective
from the current belief) instead of biases towards the prior (from the perspective of the latest
sensory signal), but in the current changepoint paradigm they are mathematically
interchangeable: the momentary learning rate is equal to one minus the normalized bias (i.e.,
$lr_t = 1 - \Pi_t \tau_t$). In the seminal delta rule model by Rescorla & Wagner (1972) learning rates were
assumed to be constant. However, later models, e.g., by Pearce & Hall (1980), allowed learning
rates to adjust flexibly to the size of the prediction error (Lee et al., 2020). As discussed, our
results indicate that learning rates are indeed flexibly adjusted by the interaction of prior
reliability and prior relevance.

Nevertheless, there are other recent studies that report a preference for a simpler heuristic with
a constant learning rate (e.g., exponential decay or leaky accumulator models; Ryali et al.,
2018; Norton et al., 2019). We believe that such contradictory findings may be explained in two
ways. First, the experimental task design may not provide sufficient variety in the surprise term
of the prior relevance, such that the learning rates only vary insignificantly even if an optimal
adaptive strategy is applied (i.e., observations are information-poor; Ryali et al., 2018). For
example, this may be the case in tasks that require observers to estimate a probability or to
weigh two alternatives probabilistically. In such tasks, a single observation cannot be decisive
evidence for a changepoint (or not), so the prior relevance does not take extreme values near
zero (or one). This will also be the case for experiments with relatively large amounts of
stochastic noise (e.g., experimentally induced, but potentially also due to sensory noise). As
explained above, the prior relevance curve of an ideal observer in more noisy situations should
be relatively flat. A second possibility is that humans choose to use an adaptive learning rate in
some tasks but select a cost-effective simpler heuristic in other tasks (Tavoni et al., 2022;
Verbeke & Verguts, 2024). Nonetheless, it is worth emphasizing that our results strongly suggest

that changepoint designs, such as the task that was used here (Krishnamurthy, Nassar, et al.,
2017), introduce highly dynamic learning where observers adapt their use of the prior in
accordance with its inferred relevance, alike to what is predicted by Bayesian causal inference.

<u>3.2. Reduced reliance on prior</u>

We found that the reduced Bayesian observer model generally overestimated the biases
towards the prior when its parameters were set to the correct values, i.e., the experimental
noise and changepoint hazard rate that were used to generate the stimuli sequences. In other
words, we reproduced previous reports that humans systematically used higher learning rates
than an ideal observer would have done (Nassar et al., 2010; Lee et al., 2020, Bakst & McGuire,
2023). One may hypothesize that lower-than-ideal bias sizes can be explained by misestimation
of the changepoint hazard rate. Specifically, if observers expect there to be more changepoints,
then this would reduce the a-priori relevance of their priors. However, if participants did indeed
overestimate the changepoint hazard rate, then we hypothesized that their experimental noise
estimates should also be smaller than the true value. This is because of the expected trade-off
between noise and changepoint inference rates for relatively large prediction errors (Payzan-
LeNestour & Bossaerts, 2011; Piray & Daw, 2021).

We proceeded by fitting the reduced Bayesian observer model to the response data. The
optimized hazard rate parameters were indeed (much) larger than the true changepoint rate,
although there were considerable individual differences. Larger hazard rates reduced the
modelled prior relevance, and therefore the biases, thus resulting in improved model fits to the
response data. However, the optimized noise parameters were reasonably accurate; they were
certainly not smaller than the true values, as would be expected from the presumed trade-off
between experienced volatility and stochasticity. We interpret the lack of a trade-off as an
indication that the fitted hazard rate parameters are not illustrative for the rate with which
participants experienced changepoints. Instead, we believe that the optimized parameter
values signify a reduced a-priori trust in the relevance of the prior, or a strategic choice to not
rely on the prior as much as the reduced Bayesian observer. In other words, the probability $1 -$
$\hat{H}_{cp}$ (or the non-negative quantity $\hat{H}_{cp}^{-1} - 1$ in Eq. 4) should rather be viewed as an individual's
tendency to bind novel sensory signals with existing beliefs. Similar binding tendencies, their
plasticity and individual differences are an active area of research in the field of sensory cue
integration (Quintero et al., 2022).

The lower-than-ideal binding tendencies for consecutive cues are in curious contradiction with
the fact that human observers are often biased towards preceding stimuli and responses, also
in experiments when there is no consistent relationship between successive stimuli or trials
(thus when there is no benefit of such a bias). One explanation for these so-called serial
dependence biases is that observers have learned that the world is generally stable, thus prior
beliefs persist to stabilise perception even when objectively irrational within a rapidly changing
experimental context (Kiyonaga et al., 2017). So, why would observers not make full use of prior
information in experiments where it is actually useful to do so (like here)?

One plausible reason may be specific to the artificially volatile environment in changepoint
paradigms. This may prompt participants to explicitly focus on the causality question
(changepoint or not), thus making them overly attentive for deviations from stability. Relatedly,
multisensory cue integration experiments have demonstrated that tasks that require explicit

causal decisions result in more segregated percepts as compared to implicit causal inference tasks (Acerbi et al., 2018). Hence, being very aware of the constant potential for a changepoint could markedly reduce the extent to which one integrates consecutive sensory signals, independent of the actual hazard rate. By focusing on not missing any of the changepoints, participants may have adopted a suboptimal strategy for dealing with the changepoint versus noise trade-off. Bayesian ideal observers occasionally falsely infer 'no changepoint' (on SAC 1 trials), and so they bias their responses towards an irrelevant prior. In exchange, they more often than not correctly integrate successive stimuli (SAC > 1) and thus gain accuracy overall. Instead, it seems that participants opted for a more conservative strategy that avoids making relatively large errors by incorrectly biasing their responses towards irrelevant priors after changepoints, and in exchange they accept a moderate precision reduction overall, i.e., increased response variance but less bias. The choice of strategy can thus be seen as an instance of the bias-variance trade-off, which has previously been proposed to underlie individual differences in learning rates (Glaze et al., 2018; Eissa et al., 2022). Additionally, participants' behavior is in line with the Ellsberg paradox (Trimmer et al., 2011), according to which humans prefer quantifiable risk (i.e., errors with sizes defined by the experimental noise) over ambiguity (unpredictable and potentially large errors on changepoint trials).

Another factor that may have contributed to adopting a conservative strategy is the fact that observers were likely facing more uncertainty than we have included into the Bayesian model. For example, they may have been unsure about the structure of the generative process for the spatial locations of the stimuli sequences (e.g., the generative mean μ_t could have slowly drifted through space in addition to the sudden changepoints), and they were probably not certain about the precise values of their estimates for changepoint rate and experimental noise (Payzan LeNestour & Bossaerts, 2011). Such additional (out-of-model) uncertainty makes a conservative heuristic algorithm more attractive because the performance improvement that is gained via complex inference may only be realised when the assumed generative model is accurate (Tavoni et al., 2022). Besides merely experiencing uncertainty about the generative process, participants may have actually had a different generative model in mind than the one we used for the Bayesian model (section 4.2). For example, participants may have falsely incorporated the idea of a drifting generative mean (Nassar et al., 2010; 2019), or they may have accounted for disturbances to their prior beliefs, e.g., from memory decay (Krishnamurthy, Nassar et al., 2017). Both examples would lead observers to undervalue the prior's reliability relative to our models, in accordance with the experimental data.

Lastly, diverse psychophysiological processes may have also affected the tendency to bind sensory signals with prior beliefs. For example, the arousal system has been implicated in adjusting the extent to which novel sensory information affects current beliefs (Nassar et al., 2012), as well as the extent to which prior beliefs bias the perception of sensory signals (Krishnamurthy et al., 2017). It has been suggested that laboratory experiments bring participants in an aroused (or sleepy) state, which therefore leads to higher (or lower) learning rates (Lee et al., 2020). In support of the hypothesis that cognitive states influence perceptual inference, it was found that a trial's reward value, although otherwise irrelevant to task performance, nonetheless affected observers' learning rates (McGuire et al., 2014).

3.3. Alternative models

We have derived the reduced Bayesian observer model (Nassar et al., 2010; 2012) from the fully
Bayesian solution for the generative model of this changepoint task design (Adams & MacKay,
2007). In doing so, we clarified the assumptions and simplifications that underly the reduced
model, and it begs the question whether different modelling choices would have led to better
fits of the data.

A first consideration is that the reduced Bayesian observer model, contrary to an ideal Bayesian
observer that attempts to minimize its squared errors, makes predictions about the upcoming
stimulus location based on the latest posterior belief about the current generative mean. This
model assumption was found to be true, as participants did not adjust their prediction
responses with a bias towards the centre of space to account for the possibility of an upcoming
changepoint. This finding was very clear and has been reported before (Nassar et al., 2010), so
we did not consider the central bias in any of our model comparisons. But we do note that this is
another indication that the fitted hazard rate parameters should not be interpreted as the
expected probability of an upcoming changepoint. After all, if some participants would predict a
90% chance of a changepoint for every upcoming stimulus, then why would they not just
respond near the centre of space all the time?

Second, the reduced Bayesian observer model neglects the spatial boundaries of the generative
mean while it iteratively updates its beliefs. Unlike the fully Bayesian observer, it does not
induce small central biases for beliefs that are near those bounds. Our model comparison
analysis clearly demonstrated that incorporating the complex space truncation computations
from the fully Bayesian solution made the model fits worse. This result suggests that the spatial
boundaries were only accounted for when preparing to make a mouse response on the finite
semicircular arc on the screen, and that the preceding computations for evidence
accumulation and causal inference take place in an apparently unbounded internal
representation of space. We remind the reader of the other parts of the task (not analysed here)
where participants had to localize a subsequently presented sound without a concurrent visual
signal. Hence, it made sense for them to pay particular attention to the auditory components of
the stimuli, and only map the result to the visual arc on the screen when it was necessary to do
so for a response (Krishnamurthy, Nassar, et al., 2017). Moreover, ignoring space truncation
significantly simplifies the computations at a minimal loss of accuracy, and therefore presents a
logical option for an agent with limited resources (Tavoni et al., 2022; Piasini et al., 2023).

Third, we found that extending the memory capacity of the reduced Bayesian observer model
did not significantly improve the fits for most of the participants. The memory limit is probably
the most striking simplification in the reduced model because it deviates so much from the
infinite memory requirement of a fully Bayesian observer. Yet, our analyses suggest that there is
hardly any difference in the predictions of the models with various memory capacity settings as
long as the weighted average pruning function (keep_*WAVG*) is used to reduce the memory load
(Nassar et al., 2010; 2012). The two other pruning functions that we tested (keep_*MAXP* and
keep_*RCNT*) performed objectively worse in terms of accuracy, because they explicitly discard
(i.e., forget) potentially useful information (Adams & MacKay, 2007; Skerritt-Davis & Elhilali,
2018). More importantly, they also reduced the quality of the fits to participants' responses.
These results suggest that near-optimal Bayesian causal inference can be achieved with limited
memory requirements by efficiently summarizing the retained prior information, and that
human observers are likely to use a very similar strategy (although not nearly achieving
optimality because of reasons that we discussed in the previous section).

Alternative modelling approaches have also been described in the literature. Wilson et al., (2013) proposed an interesting model variant that eludes the need for a pruning function to reduce memory load by instead attributing weights to a fixed number of nodes with predefined learning rates. Processing of sensory evidence leads to a change in the weights, and the eventual predictions are computed as a weighted average. Because of its ability to adaptively adjust the learning rates, the model's behavior will be qualitatively similar to the reduced Bayesian observer that we evaluated here. Furthermore, probabilistically weighing multiple nodes allows one to retain causal uncertainty (about the occurrence of a changepoint), and so it resembles the behaviour of our models with memory capacities greater than one ($M \geq 2$). However, it remains unclear how the predefined learning rates have to be determined and how they limit the model's flexibility to fit to participants' responses.

We took inspiration for a variable memory capacity from the DREX model by Skerritt-Davis & Elhilali (2018, 2021). They introduced the concept of forgetting the oldest nodes, which we implemented in the keep_*RCNT* pruning function, and for which we have shown that it still requires a considerable memory ($M = 4$) in order to explain the behavioral results well. Another major contribution of the DREX model is an extension of the number of dimensions that are being tracked. Specifically, the DREX model is able to track higher order statistics of the temporal dependencies in the stimuli sequences, i.e., not just the mean, but also the variance and covariance across time. The model can detect changepoints in any one of these statistics. Such an extension to multiple dimensions would be a potentially powerful addition to the reduced Bayesian observer model, so that it can be used for the analysis of perceptual inference about dynamic patterns in volatile sequences.

Finally, we address an interesting avenue for future research. As we have argued, the changepoint paradigm requires agents to evaluate the relevance of the prior with respect to the source of the latest noise-disturbed sensory signal (i.e., current generative mean) and bias their belief about it accordingly. After an inferred changepoint, one may simply forget one's previous beliefs, because they have no role in the experiment anymore. The opposite is true in an oddball paradigm. There, agents have to assess the relevance of the sensory signals with respect to their current beliefs and adjust their learning rate accordingly (Nassar et al., 2019, Bakst & McGuire, 2023). Occasional oddballs (outlier signals with a different generative cause) should not be integrated with prior beliefs, but those beliefs should persist despite their temporary irrelevance for the current sensory input (n.b. low bias to prior *and* low learning rate!). This is akin to real world situations in which multiple objects coexist, even if temporarily obscured or silent. One can extend this line of thinking to more realistic experiments wherein causal inference is required to correctly establish the source of sensory signals: one of multiple known objects or a new source after a potential environmental change. An extended Bayesian causal inference model that is based on perceptual clustering via the Chinese restaurant process has recently been developed to deal with such multisource problems in perception (Larigaldie et al., 2021). It was successfully applied to explain human performance in an auditory stream segregation experiment, but there remain many open research questions in this direction (also see Yu et al., 2021).

 4. Methods

The methods section is structured as follows. First, we provide details on the experimental task
(section 4.1) and how the trial generation process can be translated to a generative model
(section 4.2). We then derive the fully Bayesian inference solution (section 4.3), with a special
emphasis on the prior relevance (section 4.4). Second, we provide details on the
implementation of model variations via the pruning function (section 4.5), decision strategy
(section 4.6), and late truncation simplification (section 4.7). Third, we describe the
construction of a response distribution based on the inferred prediction (section 4.8), which is
subsequently used to fit model parameters to participants' responses, for various models,
whose predictive performance we can then compare (section 4.9). The final two sections
elaborate on the methodology that was used to compute an a-priori likelihood surface for the
model parameters (section 4.10) and on specifics of the qualitative analysis for response
accuracy and biases (section 4.11).

All analyses were run in Matlab 2019b (The MathWorks, Inc.) and JASP 0.19.1 (https://jasp-
stats.org/). The analysis code and behavioral data are available on:
https://github.com/YIRG-Dynamates/priorRelevance/.

4.1 Task and data

The current study is a novel analysis of the experimental data that was acquired and published
by Krishnamurthy, Nassar, Sarode & Gold (2017). They made the data available to us upon
request and they gave permission for us to share the relevant data for this publication in the
public repository that is mentioned above.

The dataset that we received consisted of data from twenty-nine subjects who participated in
between three and six experimental sessions on different days. Each session was subdivided
into four main task blocks. Within each block, participants were presented with a sequence of
six hundred audiovisual stimuli whose angular locations were modulated (frontal azimuth
between -90° and +90°; elevation was kept constant at 0°). The sequences were paused at
pseudorandom times about thirty times per block, but always after at least eight consecutive
stimuli had been presented. During the pauses, participants were asked to make a prediction
response about the angular location of a single sound stimulus that would be presented shortly
thereafter. Participants' pupil size was recorded in a 2.5 second delay period following the
sound, after which participants made an estimation response about the sound's location and a
binary confidence judgement about that estimate. This marked the end of the pause, and the
audiovisual sequence would then continue. Here, we treat each partial sequence up to the end
of a pause as a separate trial, and we limit our analysis to the audiovisual stimuli and the
subsequent prediction responses only, i.e., we henceforth ignore the single sound
presentations and their associated pupillometry measurements, estimation responses and
confidence judgments. So, for our analysis purposes, there were approximately thirty trials per
main task block, each consisting of an audiovisual stimulus sequence followed by a prediction
response.

The auditory and visual signals were presented in synchrony with a duration of 300 milliseconds
(ms) and the interstimulus interval was 150 ms. The visual signals consisted of spatial markers
on a semicircular arc that was continuously present on an isoluminant visual display in front of
the participants. Responses were made on that same arc by moving a mouse cursor to the
predicted location of the next stimulus. The auditory signals consisted of five 50 ms white noise
pulses (incl. 5 ms on- and offset cosine ramps) that were separated by 10 ms silence. The

sounds were spatialized by convolution with a head-related transfer function (HRTF), and they were presented through headphones. Each individual underwent a short test at the beginning of the first session to select an HRTF from the IRCAM database (http://recherche.ircam.fr/equipes/salles/listen/download.html) that gave the best circular experience for a sound sequence that moved through the horizontal plane in regular steps.

The spatial locations of the stimuli were sampled according to the pseudorandom generative process that is described in the next section (4.2). However, small modifications were implemented to assure that stimuli locations did not exceed the range between -90° and 90° (noise was resampled if this occurred). Furthermore, while the probability for a changepoint was in principle equal for all stimuli and the number of stimuli per trial was unpredictable, care was taken such that the last stimulus in each trial occurred equally often between 1 and 5 stimuli after the last changepoint. In other words, there was an approximately equal number of trials for stimulus-after-changepoint (SAC) levels 1 to 5. Moreover, the number of stimuli in each trial was controlled such that the average trial length (roughly twenty stimuli) was approximately equal across those five SAC levels. These mechanisms operated on a per-block basis, such that they also ensured a balanced design for two conditions with high and low levels of experimental noise that were fixed within- and alternated across blocks. The data of the first session of each participant was not analysed, i.e., the first two blocks of both noise conditions were ignored, because we assumed that participants needed this time to familiarize themselves with the task, learn about the generative structure, and estimate the changepoint probability and the amount of stochasticity in the noise conditions. Hence, between 120 and 300 trials per participant for each noise condition were included in the analyses.

4.2 Generative model

The pseudorandom generative process is graphically depicted in Figure 7. For each timepoint t a random draw from a Bernoulli distribution (B) determines whether or not a changepoint occurs, $cp_t = 1$ or $cp_t = 0$. The beginning of each trial always starts with a changepoint. At all other timepoints there is a constant hazard rate that determines the probability of a changepoint, $H_{cp} = 0.15$. Hence, $H_1 = 1$ and $H_t = H_{cp}$ for all $t > 1$. On a changepoint, the generative mean μ_t is drawn at random from a uniform distribution on the interval $[a = -90°, b = 90°]$. If no changepoint occurs, then the generative mean remains the same as on the previous timepoint, $\mu_t = \mu_{t-1}$. Finally, stimulus location x_t is drawn at random from a normal distribution with mean μ_t and variance σ_{exp}^2, which depends on the experimental condition: $\sigma_{exp} = 10°$ and $\sigma_{exp} = 20°$ for the low and high noise conditions, respectively.

Figure 7. The generative model describes the process that gives rise to sensory signals. For every stimulus, a random draw from a Bernoulli distribution determines whether or not a changepoint occurs. For a changepoint (right panel), the generative mean is drawn at random from a uniform distribution, whereas it remains the same as before for no changepoints (left panel). Finally, in both cases, the stimulus location is drawn at random from a normal distribution that is centred on the generative mean. See text in section 4.2 for details and generative parameter settings.

4.3 Bayesian inference

The task is to predict the location of the next (sound) stimulus, x_{t+1}, whenever the sequence stops. In order to do so accurately, an observer would be wise to continuously estimate the unknown generative mean μ_t, because the next stimulus is likely to be sampled at random from a normal distribution that is centred on μ_t. Hence, we will describe an algorithm that infers the location of the unknown μ_t from the observations $x_{1:t}$.

While algorithms have been developed to simultaneously estimate the hazard rate, H_{cp}, and experimental noise, σ_{exp}, from the observations during ongoing sequence presentations (Wilson et al., 2010; Piray & Daw, 2021), we here assume that participants have learned the values for these parameters and we treat their estimates as stable constants that we denote as $\hat{\sigma}_{exp}$ and $\hat{H}_{cp}$.

Bayesian inference for changepoint problems of the like that we face here was described by Adams & MacKay, 2007 (also see Fearnhead and Liu, 2007). The optimal solution requires an agent to have extensive memory and computational capacity because its posterior distribution at any timepoint t is a weighted mixture distribution that consists of t nodes (i.e., mixture components): a new node is added with every new observation. Since this would quickly exhaust human working memory limits and become computationally intractable for longer sequences, we will introduce a maximum memory capacity (M) for the number of nodes that can be memorized and subsequently utilized. In our implementation here, this means that the posterior belief about the former generative mean, μ_{t-1}, based on all preceding stimuli, $x_{1:(t-1)}$, is first simplified to comply with the memory constraint via the function f_{MC} (which will be discussed in more detail in section 4.5), before it is used as a prior distribution for the upcoming generative mean, μ_t, conditional on the assumption of no-changepoint (i.e., $\mu_t = \mu_{t-1}$). The memory constraint function f_{MC} ensures that the simplified conditional prior distribution consists of a weighted mixture distribution of maximally M nodes:

$$\tilde{p}(\mu_t | x_{1:(t-1)}, cp_t = 0) = \sum_{n=2}^{N_t} \tilde{w}_t^{(n)} \tilde{p}(\mu_t)^{(n)} = f_{MC}\left(\bar{\bar{p}}(\mu_{t-1} | x_{1:(t-1)})\right)$$

Please note that we will consistently refer to the agent's subjective prior probabilities, distributions and parameters by means of a tilde, while we use a double overbar for subjective posterior probabilities, distributions and parameters. These are likely to be approximations of the priors and posteriors of an ideal observer because of simplifications and estimations. We will index the prior nodes at timepoint t with $n = 1:N_t$, where N_t is defined by the sequence length (t) or by $M + 1$, whichever is smaller: $N_t = \min(t, M + 1)$. Node indices are superscripted within parentheses. The first prior node is reserved for the assumption of an upcoming changepoint: $\tilde{p}(\mu_t)^{(1)} = \tilde{p}(\mu_t | cp_t = 1)$. Note that given a changepoint, μ_t is

conditionally independent of $x_{1:(t-1)}$. The full prior distribution for μ_t is described as a weighted sum of the two options, either there was a changepoint or there was not:

$$\tilde{p}(\mu_t|x_{1:(t-1)}) = \tilde{p}(cp_t = 1)\tilde{p}(\mu_t|cp_t = 1) + \tilde{p}(cp_t = 0)\tilde{p}(\mu_t|x_{1:(t-1)}, cp_t = 0)$$

$$= \hat{H}_t\tilde{p}(\mu_t)^{(1)} + (1 - \hat{H}_t)\sum_{n=2}^{N_t}\widetilde{w}_t^{(n)}\tilde{p}(\mu_t)^{(n)}$$

where the estimate of the hazard rate $\hat{H}_t = 1$ for $t = 1$, and $\hat{H}_t = \hat{H}_{cp}$ otherwise.

Upon observing x_t, the posterior distribution for μ_t is computed via Bayes' rule by multiplication of the prior with the subjective likelihood function, $\ddot{p}(x_t|\mu_t)$, which is equal to $\ddot{p}(x_t|\mu_t, x_{1:(t-1)})$ due to conditional independence, and by division with a normalization constant, $c(x_t)$:

$$\bar{p}(\mu_t|x_{1:t}) = \frac{\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t|x_{1:(t-1)})}{\int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t|x_{1:(t-1)})d\mu_t}$$

$$= \frac{\ddot{p}(x_t|\mu_t)\left(\hat{H}_t\tilde{p}(\mu_t)^{(1)} + (1 - \hat{H}_t)\sum_{n=2}^{N_t}\widetilde{w}_t^{(n)}\tilde{p}(\mu_t)^{(n)}\right)}{c(x_t)}$$

$$= \frac{\hat{H}_t\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(1)}}{c(x_t)} + \sum_{n=2}^{N_t}\frac{(1 - \hat{H}_t)\widetilde{w}_t^{(n)}\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n)}}{c(x_t)}$$

$$= \frac{\hat{H}_t c(x_t)^{(1)}}{c(x_t)}\frac{\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(1)}}{c(x_t)^{(1)}} + \sum_{n=2}^{N_t}\frac{(1 - \hat{H}_t)\widetilde{w}_t^{(n)}c(x_t)^{(n)}}{c(x_t)}\frac{\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n)}}{c(x_t)^{(n)}}$$

$$= \bar{\bar{w}}_t^{(1)}\bar{p}(\mu_t|x_{1:t})^{(1)} + \sum_{n=2}^{N_t}\bar{\bar{w}}_t^{(n)}\bar{p}(\mu_t|x_{1:t})^{(n)} = \sum_{n=1}^{N_t}\bar{\bar{w}}_t^{(n)}\bar{p}(\mu_t|x_{1:t})^{(n)}$$

We thus find that the posterior is a weighted mixture distribution, where each of the posterior nodes is computed by multiplication of the likelihood function with the respective prior node, followed by normalization:

$$\bar{\bar{p}}(\mu_t|x_{1:t})^{(n)} = \frac{\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n)}}{c(x_t)^{(n)}}$$

where the node-specific normalization constants $c(x_t)^{(n)}$ ensure that the posterior nodes are themselves proper probability distributions:

$$c(x_t)^{(n)} = \int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n)}d\mu_t$$

Furthermore, we have seen that the posterior weights depend on the prior weights as:

$$\bar{\bar{w}}_t^{(1)} = \hat{H}_t\frac{c(x_t)^{(1)}}{c(x_t)}$$

$$\bar{\bar{w}}_t^{(2 \leq n \leq N_t)} = (1 - \hat{H}_t)\widetilde{w}_t^{(n)}\frac{c(x_t)^{(n)}}{c(x_t)}$$

where we note that the overall normalization constant $c(x_t)$ is a weighted sum of the node-specific normalization constants:

$$c(x_t) = \int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t|x_{1:(t-1)})d\mu_t$$

$$= \hat{H}_t \int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(1)}d\mu_t + \sum_{n=2}^{N_t}(1-\hat{H}_t)\tilde{w}_t^{(n)}\int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n)}d\mu_t$$

$$= \hat{H}_t c(x_t)^{(1)} + \sum_{n=2}^{N_t}(1-\hat{H}_t)\tilde{w}_t^{(n)}c(x_t)^{(n)}$$

Now, we will make this general approach for Bayesian inference more concrete by showing that it can be implemented via simple updating equations for the summary statistics (i.e., parameters) of each node's distribution.

We will start with a single observation, x_t. Since the agent has learned that the stimulus was sampled from a normal distribution that is centred at μ_t with variance $\hat{\sigma}_{exp}^2$, it is straightforward to construct the subjective likelihood function for μ_t using the symmetry of the normal distribution:

$$\ddot{p}(x_t|\mu_t) = N(x_t;\mu_t,\hat{\sigma}_{exp}^2) = N(\mu_t;x_t,\hat{\sigma}_{exp}^2) = \frac{1}{\hat{\sigma}_{exp}}\varphi\left(\frac{\mu_t - x_t}{\hat{\sigma}_{exp}}\right)$$

where φ represents the standard normal distribution.

In the case of a changepoint, μ_t is sampled from a uniform distribution on the interval [a, b]. Hence, the first node of the prior distribution equals:

$$\tilde{p}(\mu_t)^{(1)} = \tilde{p}(\mu_t|cp_t = 1) = U(\mu_t;a,b) = \frac{1}{b-a}[a \le \mu_t \le b]$$

where we have used the Iverson bracket notation.

It follows that the first posterior node is a truncated normal distribution:

$$\bar{\bar{p}}(\mu_t|x_{1:t})^{(1)} = \frac{\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(1)}}{c(x_t)^{(1)}} = \frac{N(\mu_t;x_t,\hat{\sigma}_{exp}^2)[a \le \mu_t \le b]}{(b-a)c(x_t)^{(1)}}$$

$$= TN\left(\mu_t;\bar{\bar{\mu}}_t^{(1)},\bar{\bar{\sigma}}_t^{(1)},a,b\right) = \frac{\frac{1}{\bar{\bar{\sigma}}_t^{(1)}}\varphi\left(\frac{\mu_t - \bar{\bar{\mu}}_t^{(1)}}{\bar{\bar{\sigma}}_t^{(1)}}\right)[a \le \mu_t \le b]}{\Phi\left(\frac{b - \bar{\bar{\mu}}_t^{(1)}}{\bar{\bar{\sigma}}_t^{(1)}}\right) - \Phi\left(\frac{a - \bar{\bar{\mu}}_t^{(1)}}{\bar{\bar{\sigma}}_t^{(1)}}\right)}$$

characterized by the following parameters (together with constants a and b):

$$\bar{\bar{\mu}}_t^{(1)} = x_t$$

$$\bar{\bar{\sigma}}_t^{(1)} = \hat{\sigma}_{exp}$$

where Φ represents the cumulative distribution function of the standard normal distribution.

Since the first posterior node becomes the second prior node (see section 4.5 for details), the second posterior node will also be a truncated normal distribution. In fact, this is the case for each posterior node with index $n > 1$:

$$\bar{\bar{p}}(\mu_t|x_{1:t})^{(n>1)} = \frac{\ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n)}}{c(x_t)^{(n)}} = \frac{N\big(\mu_t; x_t, \hat{\sigma}_{exp}^2\big)TN\big(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{(n)}, a, b\big)}{c(x_t)^{(n)}}$$

$$= \frac{N\big(\mu_t; x_t, \hat{\sigma}_{exp}^2\big)N\left(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{2\,(n)}\right)[a \leq \mu_t \leq b]}{\left(\Phi\left(\frac{b - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right) - \Phi\left(\frac{a - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right)\right)c(x_t)^{(n)}}$$

$$= \frac{N\left(\mu_t; \bar{\bar{\mu}}_t^{(n)}, \bar{\bar{\sigma}}_t^{2\,(n)}\right)[a \leq \mu_t \leq b]}{\frac{1}{N\left(x_t; \tilde{\mu}_t^{(n)}, \hat{\sigma}_{exp}^2 + \tilde{\sigma}_t^{2\,(n)}\right)}\left(\Phi\left(\frac{b - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right) - \Phi\left(\frac{a - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right)\right)c(x_t)^{(n)}}$$

$$= \frac{N\left(\mu_t; \bar{\bar{\mu}}_t^{(n)}, \bar{\bar{\sigma}}_t^{2\,(n)}\right)[a \leq \mu_t \leq b]}{\Phi\left(\frac{b - \bar{\bar{\mu}}_t^{(n)}}{\bar{\bar{\sigma}}_t^{(n)}}\right) - \Phi\left(\frac{a - \bar{\bar{\mu}}_t^{(n)}}{\bar{\bar{\sigma}}_t^{(n)}}\right)} = TN\left(\mu_t; \bar{\bar{\mu}}_t^{(n)}, \bar{\bar{\sigma}}_t^{(n)}, a, b\right)$$

where the posterior parameters result from the product of the two normal distributions in the numerator, which itself is a scaled normal distribution. The posterior parameters can be computed efficiently with the following update equations:

$$\bar{\bar{\mu}}_t^{(n>1)} = \tau_t^{(n)}\tilde{\mu}_t^{(n)} + \big(1 - \tau_t^{(n)}\big)x_t = x_t + \tau_t^{(n)}\big(\tilde{\mu}_t^{(n)} - x_t\big)$$

$$\bar{\bar{\sigma}}_t^{(n>1)} = \sqrt{\tau_t^{(n)}\tilde{\sigma}_t^{2\,(n)}}$$

where the "prior reliability" $\tau_t^{(n)}$ represents a normalized measure of precision (i.e., reciprocal of variance) of the untruncated prior node relative to the precision of a single observation with regards to the measure of interest μ_t:

$$\tau_t^{(n)} = \frac{\frac{1}{\tilde{\sigma}_t^{2\,(n)}}}{\frac{1}{\tilde{\sigma}_t^{2\,(n)}} + \frac{1}{\hat{\sigma}_{exp}^2}} = \frac{\hat{\sigma}_{exp}^2}{\hat{\sigma}_{exp}^2 + \tilde{\sigma}_t^{2\,(n)}}$$

Computation of the posterior node via the normalized product of likelihood and prior node can thus be viewed as an example of precision-weighted integration.

Finally, we still need to define the nodes' normalization constants, $c(x_t)^{(n)}$, which are required to compute the posterior weights $\bar{\bar{w}}_t^{(n)}$:

$$c(x_t)^{(1)} = \int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(1)}d\mu_t = \frac{1}{b - a}\int N(\mu_t; x_t, \hat{\sigma}_{exp}^2)[a \leq \mu_t \leq b]d\mu_t$$

$$= \frac{1}{b - a}\int_{\mu_t = a}^{b} N(\mu_t; x_t, \hat{\sigma}_{exp}^2)d\mu_t = \frac{1}{b - a}\left(\Phi\left(\frac{b - x_t}{\hat{\sigma}_{exp}}\right) - \Phi\left(\frac{a - x_t}{\hat{\sigma}_{exp}}\right)\right)$$

1   Likewise, we also integrate out the unknown μ_t for the nodes' constants with indices $n > 1$:

2
$$c(x_t)^{(n>1)} = \int \ddot{p}(x_t|\mu_t)\tilde{p}(\mu_t)^{(n>1)}d\mu_t = \int N(\mu_t; x_t, \hat{\sigma}_{exp}^2)TN(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{(n)}, a, b)d\mu_t$$

3
$$= \frac{N\left(x_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{2\,(n)} + \hat{\sigma}_{exp}^2\right)}{\Phi\left(\frac{b - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right) - \Phi\left(\frac{a - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right)} \int_{\mu_t=a}^{b} N\left(\mu_t; \bar{\bar{\mu}}_t^{(n)}, \bar{\bar{\sigma}}_t^{2\,(n)}\right)d\mu_t$$

4
$$= \frac{1}{\sqrt{\tilde{\sigma}_t^{2\,(n)} + \hat{\sigma}_{exp}^2}}\varphi\left(\frac{x_t - \tilde{\mu}_t^{(n)}}{\sqrt{\tilde{\sigma}_t^{2\,(n)} + \hat{\sigma}_{exp}^2}}\right)\frac{\Phi\left(\frac{b - \bar{\bar{\mu}}_t^{(n)}}{\bar{\bar{\sigma}}_t^{(n)}}\right) - \Phi\left(\frac{a - \bar{\bar{\mu}}_t^{(n)}}{\bar{\bar{\sigma}}_t^{(n)}}\right)}{\Phi\left(\frac{b - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right) - \Phi\left(\frac{a - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right)}$$

We note that these normalization constants, $c(x_t)^{(n)}$, can be interpreted as the likelihood of a
particular node, given the latest observation x_t. The likelihood of the first node is essentially a
scalar that depends on the spatial range of μ_t, multiplied by a term that depends on how near
the observation was to the space boundaries (a and b). The likelihood of all other nodes is given
by the probability density of the normal distribution that is centred on the node's prior location
parameter $\tilde{\mu}_t^{(n)}$, and with variance equal to the summed variances of prior and experimental
noise, multiplied by another complex term that depends on the proximity of observation x_t and
prior mean $\tilde{\mu}_t^{(n)}$ to the space boundaries.

<u>4.4 Prior relevance</u>

Since updating from prior to posterior happens on a per-node basis, and since the posterior
weights, $\bar{\bar{w}}_t^{(n)}$, collectively form a posterior probability distribution over the nodes, we can also
view these weights as a quantification of the adequacy of the respective prior nodes in terms of
having provided information about the latest generative mean μ_t. In other words, $\bar{\bar{w}}_t^{(n)}$ is a
posterior measure for the relevance of the n[th] prior node with regards to the latest observation
x_t, and relative to the other prior nodes.

Although the first prior node also exists, $\tilde{p}(\mu_t)^{(1)} = \tilde{p}(\mu_t|cp_t = 1) = U(\mu_t; a, b)$, we may prefer to
think of "the prior" as the collection of nodes that are based on the posterior over the previous
observations, conditional on no changepoint: $\tilde{p}(\mu_t|x_{1:(t-1)}, cp_t = 0)$. As such, we define "prior
relevance" Π_t as the sum of the posterior weights with indices $n > 1$ (Krishnamurthy et al.,
2017):

26
$$\Pi_t = \sum_{n=2}^{N_t} \bar{\bar{w}}_t^{(n)} = \bar{\bar{p}}(cp_t = 0|x_{1:t})$$

27   and the posterior probability of a changepoint at timepoint t is: $\bar{\bar{p}}(cp_t = 1|x_{1:t}) = 1 - \Pi_t =$
28     $\bar{\bar{w}}_t^{(1)}$.

29   Next, we will show that a logit transformation of the prior relevance, the unbounded quantity Q_t,
30   can be intuitively computed via the information-theoretic measure of surprisal:

$$1 \quad Q_t = logit(\Pi_t) = \log\left(\frac{\Pi_t}{1-\Pi_t}\right) = \log\left(\frac{\bar{\bar{p}}(cp_t = 0|x_{1:t})}{\bar{\bar{p}}(cp_t = 1|x_{1:t})}\right)$$

$$2 \quad = \log\left(\frac{1-\widehat{H}_t}{c(x_t)}\sum_{n=2}^{N_t}\widetilde{w}_t^{(n)}c(x_t)^{(n)}\right) - \log\left(\frac{\widehat{H}_t}{c(x_t)}c(x_t)^{(1)}\right)$$

$$3 \quad = \log\left(\frac{1-\widehat{H}_t}{\widehat{H}_t}\right) - \log\left(c(x_t)^{(1)}\right) + \log\left(\sum_{n=2}^{N_t}\widetilde{w}_t^{(n)}c(x_t)^{(n)}\right)$$

$$4 \quad = \log\left(\frac{\tilde{p}(cp_t = 0)}{\tilde{p}(cp_t = 1)}\right) + S(x_t|cp_t = 1) - S(x_t|cp_t = 0)$$

5 where we have defined surprisal conditional on the changepoint assumption:

$$6 \quad S(x_t|cp_t = 1) = -\log\left(c(x_t)^{(1)}\right) = \log(b-a) - \log\left(\Phi\left(\frac{b-x_t}{\widehat{\sigma}_{exp}}\right) - \Phi\left(\frac{a-x_t}{\widehat{\sigma}_{exp}}\right)\right)$$

$$7 \quad S(x_t|cp_t = 0) = -\log\left(\sum_{n=2}^{N_t}\widetilde{w}_t^{(n)}c(x_t)^{(n)}\right)$$

In other words, the posterior log-odds for the no changepoint hypothesis is equal to its prior log-
odds plus the difference in conditional surprisal (see also Liakoni et al., 2021; Modirshanechi et
al., 2022). N.b. this unbounded quantity can be transformed to a probability via the logistic
function: $\Pi_t = logistic(Q_t) = (1 + e^{-Q_t})^{-1}$.

Note that surprisal under the assumption of a changepoint is approximately constant,
especially when the stimulus x_t is located in the middle of space and far away from the
boundaries (a and b). Furthermore, when the prior conditional on no changepoint,
$\tilde{p}(\mu_t|x_{1:(t-1)}, cp_t = 0)$, consists of only one node ($N_t = 2$, e.g., when $M = 1$), then we find that
the associated conditional surprisal is dominated by the precision-weighted prediction error,
i.e., the ratio of the observed squared prediction error, $\left(\tilde{\mu}_t^{(2)} - x_t\right)^2$, to the expected squared
prediction error, $\tilde{\sigma}_t^{2^{(2)}} + \widehat{\sigma}_{exp}^2$:

$$19 \quad S(x_t|cp_t = 0, N_t = 2) = -\log\left(c(x)^{(2)}\right)$$

$$20 \quad = \frac{1}{2}\left(\frac{\left(\tilde{\mu}_t^{(2)} - x_t\right)^2}{\tilde{\sigma}_t^{2^{(2)}} + \widehat{\sigma}_{exp}^2} + \log\left(2\pi\left(\tilde{\sigma}_t^{2^{(2)}} + \widehat{\sigma}_{exp}^2\right)\right)\right) - \log\left(\frac{\Phi\left(\frac{b-\bar{\bar{\mu}}_t^{(2)}}{\bar{\bar{\sigma}}_t^{(2)}}\right) - \Phi\left(\frac{a-\bar{\bar{\mu}}_t^{(2)}}{\bar{\bar{\sigma}}_t^{(2)}}\right)}{\Phi\left(\frac{b-\tilde{\mu}_t^{(2)}}{\tilde{\sigma}_t^{(2)}}\right) - \Phi\left(\frac{a-\tilde{\mu}_t^{(2)}}{\tilde{\sigma}_t^{(2)}}\right)}\right)$$

21 Hence, for the limited memory model with $M = 1$, the transformed prior relevance Q_t is equal
22 to:

$$23 \quad Q_t = \log\left(\frac{1-\widehat{H}_t}{\widehat{H}_t}\right) + \log(b-a) - \log\left(\sqrt{2\pi\left(\tilde{\sigma}_t^{2^{(2)}} + \widehat{\sigma}_{exp}^2\right)}\right) - \frac{1}{2}\frac{\left(\tilde{\mu}_t^{(2)} - x_t\right)^2}{\tilde{\sigma}_t^{2^{(2)}} + \widehat{\sigma}_{exp}^2}$$

$$-\log\left(\varPhi\left(\frac{b - \tilde{\mu}_t^{(2)}}{\tilde{\sigma}_t^{(2)}}\right) - \varPhi\left(\frac{a - \tilde{\mu}_t^{(2)}}{\tilde{\sigma}_t^{(2)}}\right)\right) + \log\left(\frac{\varPhi\left(\frac{b - \bar{\bar{\mu}}_t^{(2)}}{\bar{\bar{\sigma}}_t^{(2)}}\right) - \varPhi\left(\frac{a - \bar{\bar{\mu}}_t^{(2)}}{\bar{\bar{\sigma}}_t^{(2)}}\right)}{\varPhi\left(\frac{b - x_t}{\hat{\sigma}_{exp}}\right) - \varPhi\left(\frac{a - x_t}{\hat{\sigma}_{exp}}\right)}\right)$$

So, under the minimal memory assumption ($M = 1$), we find that the prior relevance is larger
when 1) the a-priori probability for a changepoint is lower and when 2) the spatial range for the
generative mean is larger. Furthermore, 3) the prior relevance decreases a-priori when the
prior's uncertainty about the upcoming stimulus location x_t is larger, either due to a less reliable
prior on μ_t or due to larger experimental noise. Importantly, 4) the prior relevance decreases a-
posteriori when the squared prediction error is larger, and this dependence on prediction error
is stronger when the prior is more reliable and when there is less experimental noise. Finally, 5)
the prior relevance increases a-priori when the prior's location parameter is nearer to or even
outside the spatial boundary for the generative mean, and 6) it increases a-posteriori when the
observation x_t is more peripheral than the posterior's location parameter. In other words, the
prior is considered more relevant a-posteriori when it biases the percept towards the centre of
space, especially when the new observation is near or outside the spatial boundaries for the
generative mean.

<u>4.5 Pruning function</u>

In the above-described recursive Bayesian inference algorithm (section 4.3) we have mentioned
that the preceding posterior distribution becomes the next prior distribution, conditional on no
changepoint, and constrained by limited memory via the function f_{MC}, for all $t > 1$:

$$\tilde{p}\big(\mu_t | x_{1:(t-1)}, cp_t = 0\big) = f_{MC}\left(\bar{\bar{p}}\big(\mu_{t-1} | x_{1:(t-1)}\big)\right)$$

$$\sum_{n=2}^{N_t} \widetilde{w}_t^{(n)} TN\big(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{(n)}, a, b\big)^{(n)} = f_{MC}\left(\sum_{n=1}^{N_{t-1}} \bar{\bar{w}}_{t-1}^{(n)} TN\left(\mu_{t-1}; \bar{\bar{\mu}}_{t-1}^{(n)}, \bar{\bar{\sigma}}_{t-1}^{(n)}, a, b\right)\right)$$

where the total number of nodes (including the first changepoint node) is: $N_t = \min(t, M + 1)$.

A fully-Bayesian ideal observer would have no memory restrictions ($M = \infty$), such that the
number of nodes always increases by 1 per timestep: $N_t = N_{t-1} + 1$. However, this is unrealistic
for human working memory. So, we investigated modifications of the statistically optimal
algorithm.

To comply with memory constraints, it has been proposed to reduce the number of posterior
nodes that carry over into the subsequent prior. This has been termed "node pruning". Roughly
speaking, it can be done in two ways: 1) one can discard posterior nodes entirely or 2) one can
merge posterior nodes before prior formation. For example, 1a) Adams & MacKay, 2007
suggested to discard posterior nodes when their inferred relevance, $\bar{\bar{w}}_t$, is smaller than some
threshold. Instead, 1b) Skerritt-Davis & Elhilali, 2018 suggested to discard the oldest node, i.e.,
the one with the highest node index, whenever memory capacity is exceeded, because humans
likely first forget the contribution of stimuli that were presented the longest time ago. Besides,
those old stimuli are a-priori less likely to be informative for estimating the current generative
mean μ_t in an environment with changepoints. On the other hand, 2a) Wilson et al., 2010
suggested to merge nodes based on their similarity in terms of mean and variance. Their key

insight was that nodes with similar run lengths represent similar belief distributions. In our
description of the Bayesian algorithm, this translates to merging nodes that have adjacent node
indices. Finally, 2b) a rather extreme form of node merging was first suggested by Nassar et al.,
2010, in which they reduced the posterior to one node ($M = 1$) with weighted average mean and
variance, where the weights were naturally given by the nodes' relevance, $\bar{\bar{w}}_t$. This algorithm was
later refined by Nassar et al., 2012, such that the variance of the merged node was computed
based on the full variance of the weighted mixture distribution, which incorporates additional
uncertainty due to disparity between the means of the nodes.

Here, we incorporate some of the above insights and test which of three competitive ideas for
node pruning best fits the behavioral data for various settings of the memory capacity
parameter M: ranging from 1 to 4. In all three of the pruning methods, we make use of the
insights that the oldest two nodes are often most similar, and that the memory of the oldest
contributing stimuli may become hazy. So, we either merge the oldest two posterior nodes or we
simply discard one of them, but we always sum their weights, so that the oldest remaining
node, i.e., with the highest prior node index (N_t) represents the belief that a changepoint
occurred at least $N_t - 1$ timepoints ago. The pruning rule thus only affects the oldest pair of
posterior nodes, whenever the number of posterior nodes exceeds the memory capacity,
$N_{t-1} > M$. Hence, all other prior nodes are simply identical to the preceding posterior node with
one index lower:

For all three f_{MC} and all prior nodes with indices $2 \leq n \leq M$, and for prior node $n = N_t$ if $N_{t-1} \leq$
M:

$$\widetilde{w}_t^{(n)} = \bar{\bar{w}}_{t-1}^{(n-1)}$$

$$\tilde{\mu}_t^{(n)} = \bar{\bar{\mu}}_{t-1}^{(n-1)}$$

$$\tilde{\sigma}_t^{(n)} = \bar{\bar{\sigma}}_{t-1}^{(n-1)}$$

25 In the first pruning method we discard the oldest posterior node once the memory capacity is
26 exceeded, in accordance with the idea of simply forgetting stimuli that were presented a long
27 time ago (Skerritt-Davis & Elhilali, 2018). Since, we keep the most recent of the two oldest
28 nodes, we refer to this pruning method as *keep_RCNT*:

29 For f_{MC_RCNT} and prior node $n = N_t$ if $N_{t-1} > M$:

$$\widetilde{w}_t^{(n)} = \bar{\bar{w}}_{t-1}^{(n-1)} + \bar{\bar{w}}_{t-1}^{(n)}$$

$$\tilde{\mu}_t^{(n)} = \bar{\bar{\mu}}_{t-1}^{(n-1)}$$

$$\tilde{\sigma}_t^{(n)} = \bar{\bar{\sigma}}_{t-1}^{(n-1)}$$

f_{MC_RCNT} effectively puts a limit on the number of stimuli that can get integrated, even if there
are no changepoints for a long time. Hence, the variance parameter of the last prior node is
bound to a minimum: $\tilde{\sigma}_t^{2(n)} \geq \frac{1}{M} \hat{\sigma}_{exp}^2$, and its prior reliability is bound to a maximum: $\tau_t^{(n)} \leq$
$\frac{M}{M+1}$.

Furthermore, if the memory capacity is set to a minimum of one node, $M = 1$, this observer
would only remember the location of the latest stimulus, x_t. In this special case, f_{MC_RCNT} does
not allow for any integration of evidence over multiple stimuli. The prior belief about μ_t,

conditional on no changepoint, $\tilde{p}\left(\mu_t\middle|x_{1:(t-1)}, cp_t = 0\right)$ would be described by a single truncated normal distribution, $TN\left(\mu_t; \tilde{\mu}_t^{(2)}, \tilde{\sigma}_t^{(2)}, a, b\right)$, with parameters equal to: $\tilde{\mu}_t^{(2)} = x_{t-1}$ and $\tilde{\sigma}_t^{(2)} = \hat{\sigma}_{exp}$.

In the second pruning method we instead discard the least relevant of the two oldest posterior nodes, i.e., we keep the node with the maximum posterior probability, *keep_MAXP*:

For f_{MC_MAXP} and prior node $n = N_t$ if $N_{t-1} > M$:

$$\widetilde{w}_t^{(n)} = \bar{\bar{w}}_{t-1}^{(n-1)} + \bar{\bar{w}}_{t-1}^{(n)}$$

$$if\ \bar{\bar{w}}_{t-1}^{(n-1)} \geq \bar{\bar{w}}_{t-1}^{(n)}, then \begin{cases} \tilde{\mu}_t^{(n)} = \bar{\bar{\mu}}_{t-1}^{(n-1)} \\ \tilde{\sigma}_t^{(n)} = \bar{\bar{\sigma}}_{t-1}^{(n-1)} \end{cases}$$

$$if\ \bar{\bar{w}}_{t-1}^{(n-1)} < \bar{\bar{w}}_{t-1}^{(n)}, then \begin{cases} \tilde{\mu}_t^{(n)} = \bar{\bar{\mu}}_{t-1}^{(n)} \\ \tilde{\sigma}_t^{(n)} = \bar{\bar{\sigma}}_{t-1}^{(n)} \end{cases}$$

Potentially keeping the oldest but more relevant node allows one to make full use of evidence integration over many relevant stimuli (i.e., more than M stimuli can be integrated). In the special case with $M = 1$, an observer with the f_{MC_MAXP} pruning function would determine whether or not a changepoint has occurred after every stimulus (based on whether the prior relevance Π_t is smaller than 0.5). This observer would then keep the node that is associated with the inferred event (changepoint or not) and discard the other.

The third pruning function does not deterministically select one or the other node, but instead attempts to summarize the information from both nodes into a single one by computing a weighted average, *keep_WAVG*.

For f_{MC_WAVG} and prior node $n = N_t$ if $N_{t-1} > M$:

$$\widetilde{w}_t^{(n)} = \bar{\bar{w}}_{t-1}^{(n-1)} + \bar{\bar{w}}_{t-1}^{(n)}$$

$$\tilde{\mu}_t^{(n)} = (1 - \omega_t^{(n)})\bar{\bar{\mu}}_{t-1}^{(n-1)} + \omega_t^{(n)}\bar{\bar{\mu}}_{t-1}^{(n)}$$

$$\tilde{\sigma}_t^{(n)} = \sqrt{(1 - \omega_t^{(n)})\bar{\bar{\sigma}}_{t-1}^{2\,(n-1)} + \omega_t^{(n)}\bar{\bar{\sigma}}_{t-1}^{2\,(n)} + \omega_t^{(n)}(1 - \omega_t^{(n)})\left(\bar{\bar{\mu}}_{t-1}^{(n-1)} - \bar{\bar{\mu}}_{t-1}^{(n)}\right)^2}$$

where the weight is defined as:

$$\omega_t^{(n)} = \frac{\bar{\bar{w}}_{t-1}^{(n)}}{\bar{\bar{w}}_{t-1}^{(n-1)} + \bar{\bar{w}}_{t-1}^{(n)}}$$

The location parameter of the new prior node is thus a weighted average of the two posterior location parameters. The squared scale parameter of the prior node is formed by a weighted average of the posterior squared scale parameters, plus a term that depends on the squared distance between the nodes' mean parameters multiplied by a scalar that indicates the uncertainty about which of the two nodes is more relevant, $\omega_t^{(n)}(1 - \omega_t^{(n)})$, i.e., the variance of a Bernoulli distribution with parameter $\omega_t^{(n)}$.

In the special case where $M = 1$, the f_{MC_WAVG} pruning function forms the core belief updating algorithm of the reduced Bayesian inference model that was described by Nassar et al., 2012. Under those minimal memory conditions, the new prior node's parameters can be computed

directly from the preceding prior node parameters and the latest observation x_{t-1} (without explicitly computing the posterior parameters):

$$\tilde{\mu}_t{}^{(2)} = \left(1 - \omega_t{}^{(2)}\right)\bar{\bar{\mu}}_{t-1}{}^{(1)} + \omega_t{}^{(2)}\bar{\bar{\mu}}_{t-1}{}^{(2)}$$

$$= (1 - \Pi_{t-1})x_{t-1} + \Pi_{t-1}\left(\tau_{t-1}{}^{(2)}\tilde{\mu}_{t-1}{}^{(2)} + \left(1 - \tau_{t-1}{}^{(2)}\right)x_{t-1}\right)$$

$$= x_{t-1} + \Pi_{t-1}\tau_{t-1}{}^{(2)}\left(\tilde{\mu}_{t-1}{}^{(2)} - x_{t-1}\right)$$

$$\tilde{\sigma}_t{}^{(2)} = \sqrt{\left(1 - \omega_t{}^{(2)}\right)\bar{\bar{\sigma}}_{t-1}^2{}^{(1)} + \omega_t{}^{(2)}\bar{\bar{\sigma}}_{t-1}^2{}^{(2)} + \omega_t{}^{(2)}(1 - \omega_t{}^{(2)})\left(\bar{\bar{\mu}}_{t-1}{}^{(2)} - \bar{\bar{\mu}}_{t-1}{}^{(1)}\right)^2}$$

$$= \sqrt{(1 - \Pi_{t-1})\hat{\sigma}_{exp}^2 + \Pi_{t-1}\tau_{t-1}{}^{(2)}\tilde{\sigma}_{t-1}^2{}^{(2)} + \Pi_{t-1}(1 - \Pi_{t-1})\tau_{t-1}^2{}^{(2)}\left(\tilde{\mu}_{t-1}{}^{(2)} - x_{t-1}\right)^2}$$

We thus find that the new prior's location parameter is based on the latest observation plus a bias towards the preceding prior's location parameter. The product of prior relevance and prior reliability, $\Pi_{t-1}\tau_{t-1}$, here serves as a normalized bias measure from the latest stimulus location (x_{t-1} at 0 in normalized space) to the prior's location parameter ($\tilde{\mu}_{t-1}{}^{(2)}$ at 1 in normalized space).

4.6 Decision strategy

So far, we have shown how an observer can update beliefs about the generative mean μ_t after observing a new stimulus and how to reduce memory load by restrictive formation of a new prior. This prior distribution can then be used to predict the location of the upcoming stimulus when the observer is prompted to do so. It is straightforward to construct a predictive distribution for the unobserved stimulus x_t based on the prior on μ_t by additionally accounting for the experimental noise, $x_t \sim N\left(\mu_t, \hat{\sigma}_{exp}^2\right)$:

$$\tilde{p}\left(x_t | x_{1:(t-1)}\right) = \int \ddot{p}(x_t | \mu_t)\tilde{p}\left(\mu_t | x_{1:(t-1)}\right)d\mu_t$$

$$= \hat{H}_t \int \ddot{p}(x_t | \mu_t)\tilde{p}(\mu_t)^{(1)}d\mu_t + \sum_{n=2}^{N_t}(1 - \hat{H}_t)\tilde{w}_t{}^{(n)} \int \ddot{p}(x_t | \mu_t)\tilde{p}(\mu_t)^{(n)}d\mu_t$$

$$= \hat{H}_t \int N\left(x_t; \mu_t, \hat{\sigma}_{exp}^2\right)U(\mu_t; a, b)d\mu_t$$

$$+ \sum_{n=2}^{N_t}\left(1 - \hat{H}_t\right)\tilde{w}_t{}^{(n)} \int N\left(x_t; \mu_t, \hat{\sigma}_{exp}^2\right)TN\left(\mu_t; \tilde{\mu}_t{}^{(n)}, \tilde{\sigma}_t{}^{(n)}, a, b\right)^{(n)}d\mu_t$$

One may recognize that we have already evaluated these integrals for a particular value of x_t when we computed the normalization constants of the posterior nodes, $c(x_t)^{(1)}$ and $c(x_t)^{(n>1)}$. Fortunately, it is not necessary to evaluate the integrals for all possible values of the unknown upcoming observation x_t. Instead, in order to make the best possible prediction, an observer only needs to compute the expected values of the predictive distribution's nodes:

$$E\left[\tilde{p}\left(x_t | x_{1:(t-1)}\right)\right] = \hat{H}_t E[U(\mu_t; a, b)] + \sum_{n=2}^{N_t}\left(1 - \hat{H}_t\right)\tilde{w}_t{}^{(n)}E\left[TN\left(\mu_t; \tilde{\mu}_t{}^{(n)}, \tilde{\sigma}_t{}^{(n)}, a, b\right)^{(n)}\right]$$

where we have used the fact that the additional experimental noise, which is sampled at random from a normal distribution, does not change the expected values of the predictive distribution's components. These expected values are:

$$E[U(\mu_t; a, b)] = \frac{a + b}{2}$$

$$E\left[TN\left(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{(n)}, a, b\right)^{(n)}\right] = \tilde{\mu}_t^{(n)} + \tilde{\sigma}_t^{(n)} \frac{\varphi\left(\frac{a - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right) - \varphi\left(\frac{b - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right)}{\Phi\left(\frac{b - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right) - \Phi\left(\frac{a - \tilde{\mu}_t^{(n)}}{\tilde{\sigma}_t^{(n)}}\right)}$$

Note that the latter expectation is given by the location parameter of the prior node plus a truncation-dependent term that biases the expectation towards the centre of space, especially when the node's location parameter $\tilde{\mu}_t^{(n)}$ is near or outside the space boundaries for μ_t (a and b).

So, the statistically optimal prediction for the location of the upcoming stimulus, $\tilde{x}_t$, i.e., one that minimizes the squared error $(x_t - \tilde{x}_t)^2$ across many such predictions, is given by a weighted average of the prior nodes' distribution expectations. Such a strategy is called model averaging (Wozny et al., 2010); where the nodes here represent competing models of the world, i.e., hypotheses about the occurrence of the latest changepoint. Since the expectation of the first prior node, conditional on an upcoming changepoint, is equal to $0.5(a + b)$, the ideal Bayesian observer would bias all of their responses towards the centre of space with a weight equal to $\hat{H}_t$. However, in accordance with Nassar et al., 2010, we did not observe such central biases in the current dataset (Figure 2A). Therefore, we assume that participants made their predictions conditional on the assumption that there will not be a changepoint. Under the "model averaging" decision strategy this amounts to:

$$\tilde{x}_{t,AVG} = E\left[\tilde{p}\left(x_t | x_{1:(t-1)}, cp_t = 0\right)\right] = \sum_{n=2}^{N_t} \tilde{w}_t^{(n)} E\left[TN\left(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{(n)}, a, b\right)^{(n)}\right]$$

While the model averaging decision strategy is the one that a Bayesian observer would use under a squared error loss function, it is possible that participants relied on one of many other loss functions. For example, in multiple-choice tasks, the optimal strategy is to select the option with the maximum a-posteriori probability (MAP). Participants could have post-hoc applied this common strategy to determine which of the prior nodes contains the most relevant information about the generative mean μ_t. Under the so-called "model selection" decision strategy, participants would then single out the prior node with the highest weight $\tilde{w}_t^{(n)}$ as the basis for their prediction:

$$\tilde{x}_{t,MAP} = E\left[TN\left(\mu_t; \tilde{\mu}_t^{(n)}, \tilde{\sigma}_t^{(n)}, a, b\right)^{(n_{MAP})}\right]$$

$$n_{MAP} = argmax_{n=2:N_t} \tilde{w}_t^{(n)}$$

Note that both decision strategies lead to the same prediction, $\tilde{x}_{t,AVG} = \tilde{x}_{t,MAP}$, if the memory capacity is set to $M = 1$.

4.7 Late truncation simplification

The above near-Bayesian model computations can be simplified by ignoring the complex space truncation terms until a prediction response has to be made. In other words, during sequence presentation, sensory evidence may be accumulated (or not, in case of inferred changepoints) without considering the space boundaries for the generative mean. Under this assumption, the normalization constants (i.e., the likelihoods of the nodes) are approximated by:

$$c(x_t)^{(1)} \approx \frac{1}{b-a}$$

and

$$c(x_t)^{(n>1)} \approx \frac{1}{\sqrt{\tilde{\sigma}_t^{2\,(n)} + \hat{\sigma}_{exp}^2}} \varphi\left(\frac{x_t - \tilde{\mu}_t^{(n)}}{\sqrt{\tilde{\sigma}_t^{2\,(n)} + \hat{\sigma}_{exp}^2}}\right)$$

The simplification implies that any new observation x_t is not immediately compared against the spatial boundaries for the generative mean (a, b) when computing the prior relevance Π_t. The spatial range merely plays a role as an a-priori offset for the transformed prior relevance Q_t.

Nevertheless, we do assume that participants are aware of the spatial boundaries for the generative mean and that they take these into account when they make predictions for the upcoming stimulus. However, instead of computing the complex bias term for the expectation of the posterior truncated normal distributions, the prediction itself is simply truncated unto the interval of the generative mean. Hence, the predictions are first approximated:

$$\tilde{x}_{t,AVG} \approx \sum_{n=2}^{N_t} \tilde{w}_t^{(n)} \tilde{\mu}_t^{(n)}$$

$$\tilde{x}_{t,MAP} \approx \tilde{\mu}_t^{(n_{MAP})}$$

and subsequently truncated:

$$\tilde{x}_t \leftarrow \begin{cases} a & if\ \tilde{x}_t \leq a \\ \tilde{x}_t & if\ a < \tilde{x}_t < b \\ b & if\ \tilde{x}_t \geq b \end{cases}$$

4.8 Response distribution

We assume that a participant intends to direct the response to the location of their best guess for the upcoming stimulus, $\tilde{x}_t$, but that the response itself is inaccurate to some extent. Hence, we assume that the actual response is disturbed by random response noise according to:

$$r \sim N(\tilde{x}_t, \sigma_{resp}^2)$$

Furthermore, subjects' attention may occasionally lapse, or they may blink during the last stimulus presentation, such that they have no idea where the next stimulus is going to be presented. On such lapses ($\Lambda = 1$), we assume that their intended response location is randomly chosen from the uniform distribution of the generative mean, $\tilde{x}_t | \Lambda = 1 \sim U(a, b)$. The

predicted response distribution is a weighted sum of the conditional response distributions for a lapse and no lapse:

$$p\big(r|x_{1:(t-1)}\big) = \lambda p(r|\Lambda = 1) + (1-\lambda)p\big(r|\Lambda = 0, x_{1:(t-1)}\big)$$

where λ is the lapse rate.

Since responses are bound to the response interval $[c = -90°, d = 90°]$, we define the predicted response distribution, conditional on no lapse as a truncated normal distribution, where the location parameter is given by the model's prediction $\tilde{x}_t$:

$$p\big(r|\Lambda = 0, x_{1:(t-1)}\big) = TN\big(r; \tilde{x}_t, \sigma_{resp}, c, d\big)$$

The predicted response distribution conditional on a lapse is defined by the following convolution of a uniform and normal distribution, $\int N\big(r; \tilde{x}_t, \sigma_{resp}^2\big)U(\tilde{x}_t; a, b)d\tilde{x}_t$, truncated to the response interval $[c, d]$:

$$p(r|\Lambda = 1) = \frac{\Phi\left(\dfrac{b-r}{\sigma_{resp}}\right) - \Phi\left(\dfrac{a-r}{\sigma_{resp}}\right)}{\int_{r=c}^{d} \Phi\left(\dfrac{b-r}{\sigma_{resp}}\right)dr - \int_{r=c}^{d} \Phi\left(\dfrac{a-r}{\sigma_{resp}}\right)dr}[c \le r \le d]$$

where the integrals in the denominator can be computed analytically as:

$$\int_{r=c}^{d} \Phi\left(\frac{y-r}{\sigma_{resp}}\right)dr = -\sigma_{resp} \int_{z=\frac{y-c}{\sigma_{resp}}}^{\frac{y-d}{\sigma_{resp}}} \Phi(z)dz$$

$$= \sigma_{resp}\left(\left(\frac{y-c}{\sigma_{resp}}\Phi\left(\frac{y-c}{\sigma_{resp}}\right) + \varphi\left(\frac{y-c}{\sigma_{resp}}\right)\right) - \left(\frac{y-d}{\sigma_{resp}}\Phi\left(\frac{y-d}{\sigma_{resp}}\right) + \varphi\left(\frac{y-d}{\sigma_{resp}}\right)\right)\right)$$

and we note that the denominator is approximately equal to $d - c$, such that the probability, conditional on a lapse, for any response that is well away from and in-between the space boundaries, $a \ll r \ll b$, is approximately constant: $p(r|\Lambda = 1) \approx (d - c)^{-1}$.

4.9 Model fitting and model comparison

We utilize the method of maximum likelihood estimation to optimize the parameter values of a model, θ_m, to best predict the spatial prediction responses r_k of a participant, across all relevant trials $k = 1: N_k$.

$$\hat{\theta}_m = argmax_{\theta_m} L(\theta_m) = argmax_{\theta_m} \prod_{k=1}^{N_k} p(r_k|\theta_m)$$

where the likelihood across trials $L(\theta_m)$ for a particular set of parameter values is computed as a product of the likelihoods for each trial, and the likelihood for a single trial response is given as the probability density of the model-predicted response distribution, $p\big(r|x_{1:(t-1)}, \theta_m\big)$, evaluated at the participant's response location, r_k.

We fitted the models separately for both experimental noise conditions. For each fit, we optimized the following four parameters: subjective estimate of the changepoint hazard rate ($0 < \hat{H}_{cp} < 1$), subjective estimate of the experimental noise standard deviation ($0° < \hat{\sigma}_{exp} < 200°$), the standard deviation of the response noise ($0° < \sigma_{resp} < 200°$), and the lapse rate ($0 < \lambda < 1$):

$$\theta_m = \{\hat{H}_{cp}, \hat{\sigma}_{exp}, \sigma_{resp}, \lambda\}$$

The only exceptions to this were the models with limited memory capacity, $M = 1$, and the f_{MC_LAST} pruning method. These models essentially base their predicted response distributions on the last stimulus location only, and they do not make use of the hazard rate estimate $\hat{H}_{cp}$. Under the late truncation simplification assumption, the experimental noise estimate $\hat{\sigma}_{exp}$ is also not used (without the simplification assumption it is used to bias the prediction $\tilde{x}_t$ towards the centre of space via the expectation of the truncated normal). So, for these models we optimized either three ($\hat{\sigma}_{exp}, \sigma_{resp}, \lambda$) or two parameters ($\sigma_{resp}, \lambda$) only.

To find the parameter values that maximize the likelihood we used the Bayesian Adaptive Direct Search optimization algorithm (BADS; Acerbi & Ma, 2017; https://github.com/acerbilab/bads). For each model and dataset (responses from one participant for one experimental noise condition) we ran BADS four times, each from a different starting point, $\theta_{m,0}$. To obtain promising starting points for each dataset, we first selected 1000 sets of parameter values θ_m at random from within the following plausible bounds: $\hat{H}_{cp}$: 0.01 - 0.99, $\hat{\sigma}_{exp}$: 1° - 50°, σ_{resp}: 1° - 50°, and λ: 0.001 - 0.25. For each of the parameter sets we computed the likelihood $L(\theta_m)$, and we subsequently selected the four parameter sets with the highest likelihood as starting points for BADS.

Non-extensive parameter recovery analyses indicated good identifiability of the true model parameters. Each of the model variations was tested several times with various parameter combinations. Responses were generated for a hypothetical observer using the experimental trials (i.e., stimuli location sequences) of a random participant from the current study as model input. Model parameters were then fitted to the generated response data using the above-described method. Approximate correspondence of the fitted parameters with the parameter values that were used during generation was checked subjectively. Although minor differences existed (as expected due to random noise generation and limited number of trials), none of the parameter recovery results gave rise to doubt identifiability.

For comparison of the models' quality of fit to participants' data, we computed the Bayesian information criterion (BIC) for each fit and then obtained an estimate of the log model evidence (lme) per participant for each model by summing over the two experimental noise conditions according to:

$$BIC = -2\log\left(L(\hat{\theta}_m)\right) + \#(\theta_m)\log(N_k)$$

$$lme = -\frac{1}{2}\left(BIC_{\sigma_{exp}=10°} + BIC_{\sigma_{exp}=20°}\right)$$

where $\#(\theta_m)$ represents the number of fitted parameters for model m.

The log model evidence lme is used to compare the models' performances in predicting participants' responses. We make use of two different comparison methods. First, we assume that all subjects make prediction responses according to the same underlying inference

mechanism. The most likely mechanism, out of the ones tested here, is represented by the model where the summed *lme* across subjects is largest. This is known as a fixed effects model comparison. We used bootstrapping to obtain robust estimates of the summed *lme* differences between models, and their confidence intervals (Acerbi et al., 2018). Precisely, we repeatedly (N = 10,000) sampled 29 subjects with replacement and computed the summed *lme* differences for each sample, for all models relative to one reference model. Subsequently, we selected the 0.05, 0.5, and 0.95 quantiles for each model from the bootstrapped summed differences.

The second model comparison method we employed is based on the random effects method (Stephan et al., 2009). In general, this analysis accounts for heterogeneity within the subject population and estimates a probability distribution across models to indicate the likelihood of any one model to have generated the responses of a randomly selected subject. We here used the random effects method in a factorial model comparison, where probability distributions were estimated across competing model components based on the summed *lme* per subject over all models that incorporated that component (Acerbi et al., 2018): e.g., the factor 'pruning function' had three components: keep_*RCNT*, keep_*MAXP*, and keep_*WAVG*. For each factor, we could then compare the components' predictive performance relative to each other via the protected exceedance probability measure (Rigoux et al., 2014).

4.10 Experimental noise and changepoint hazard rate inference

In the previous section we have described how we fit the model's parameters to participants' responses, but how did participants obtain their estimates of the parameters of the generative model? A Bayesian observer would construct a joint distribution over the parameters and update it iteratively as evidence comes in. This evidence comes in the form of a likelihood, that expresses the probability of observing a certain stimulus location x_t given a particular set of parameter values, and conditional on all previous observations (and the model itself). Under a non-informative prior over the joint parameter space, the parameter combination that maximizes the likelihood product across all observations forms the best estimate of the parameters. This fully Bayesian inference process is rather complex, likely computationally intractable for human brains, and falls outside of the scope of this study (for related discussions and algorithms see Wilson et al., 2010 and Piray & Daw, 2021). However, we utilized the general idea of computing likelihoods for particular combinations of parameter values to obtain an insight into which parameter combinations are more or less probable to have given rise to the given stimuli locations. Hence, we can compare the fitted parameter estimates of the participants to these likelihoods, in an attempt to quantify the errors that participants made in estimating the parameter combinations.

An equivalent algorithm to maximizing the likelihood product is minimizing the summed surprisal (Friston, 2010), across all stimuli in the experimental condition (i.e., across all stimuli in all trials with the same experimental noise). Surprisal for a single stimulus is computed as:

$$S(x_t) = -\log\left(\widehat{H}_t c(x_t)^{(1)} + \sum_{n=2}^{N_t} (1 - \widehat{H}_t)\widetilde{w}_t^{(n)} c(x_t)^{(n)} \right)$$

In the limited memory model ($M = 1$) with late truncation simplification, single stimulus surprisal is approximated with:

$$S(x_t) \approx -\log\left(\frac{\widehat{H}_t}{b-a} + \frac{1-\widehat{H}_t}{\sqrt{\tilde{\sigma}_t^{2\,(2)} + \hat{\sigma}_{exp}^2}}\,\varphi\left(\frac{x_t - \tilde{\mu}_t^{(2)}}{\sqrt{\tilde{\sigma}_t^{2\,(2)} + \hat{\sigma}_{exp}^2}}\right)\right)$$

To compute the coloured background plane of Figure 4A, we computed the approximate
surprisal summed across all stimuli of each experimental condition (all trials and all subjects
were aggregated), for a grid of 625 parameter combinations: 25 values of $\hat{\sigma}_{exp}$ between 2.5° and
250° (logarithmically spaced) x 25 values of $\widehat{H}_{cp}$ between 0.02 and 0.98 (linearly spaced). The
summed surprisal values were subsequently scaled to the interval between 0 (the minimum
surprisal) and 1 (surprisal for the largest $\widehat{H}_{cp}$ and $\hat{\sigma}_{exp}$, i.e., top right corner in the plot), and
larger surprisal values (bottom left corner) were capped to a maximum of 1.5. Linear
interpolation was used during plotting to create a smooth surface.

4.11 Qualitative data analysis

The data shown in Figures 2 and 3 is the group median (Q1 – Q3 in shaded area, i.e., 25% and
75% quantiles at the group level) of the median at the individual level, per grid-point on the x-
axis. This robust visualization controlled for outlier responses at the individual level (e.g.,
lapses), and for possible outlier participants at the group level. Likewise, we employed non-
parametric rank-based statistics (sign tests and Wilcoxon signed rank tests) that are robust to
outliers and non-normality of the response data (which contained much intersubject
variability).
19
In Figures 2B and 2C the trials were first discretized per SAC level (stimuli after changepoint)
and the medians were computed for each bin. In Figures 2A, 3A and 3B the x-axis represented
continuous variables (omniscient mean or absolute prediction error), so we instead computed
rolling weighted medians for each grid point on the x-axis, where the weights were assigned to
the individual's responses by a Gaussian kernel that was centred on the grid-point (SD = 5° in
Figure 2A, SD = 0.1 in Figure 3A, and SD = 0.2 in Figure 3B, see below for further explanations).
To improve smoothness of the curves in the figures, the group-level medians (and Q1s, Q3s)
were computed via bootstrapping (N = 100 random samples of 29 subjects, with replacement):
the depicted values are the means across the bootstrapped group-level medians (and Q1s,
Q3s).
30
31   The normalized errors (Figure 2C) were computed for each trial as the ratio of the participant's
32   error (numerator) and the error of the naïve observer (denominator), with respect to the true
33   generative mean μ_t:
34
35
$$normalized\ error = \frac{r - \mu_t}{x_t - \mu_t}$$

36
37   As explained in the previous paragraph, these normalized errors were discretized per SAC level
38   and the individual's median was then computed for each bin. The group-level medians (Q1s,
39   Q3s) were subsequently computed via bootstrapping.
40
41   The normalized bias (Figure 3A) for each trial was computed as the ratio of the participant's bias
42   (numerator) and the prediction error of the omniscient observer (denominator):
43

$$normalized\ bias = \frac{r - x_t}{\tilde{\mu}_{t,omni} - x_t}$$

The signed bias (Figure 3B) of a trial was computed as:

$$signed\ bias = \frac{r - x_t}{sgn(\tilde{\mu}_{t,omni} - x_t)}$$

where the 'sgn(y)' function is -1 if y<0, and 1 otherwise.

To obtain unbiased estimates of an individual's average trace as a function of a continuous variable (Figures 2A, 3A, 3B) via the rolling median method it is essential that the trial density across the x-axis is approximately equal. This was naturally the case for the generative mean μ_t, because it was sampled from a uniform distribution between -90° and 90°, and so it was also approximately true for the omniscient observer's estimate of the generative mean (Figure 2A). However, to achieve a relatively constant density of trials over the (omniscient observer's) prediction errors for the normalized and signed bias plots (Figure 3), we used a non-linear transformation of the prediction errors when we computed the rolling medians. These transforms were based on the expected cumulative probability distributions of the prediction errors, as is explained in the following paragraphs.

The absolute distances between the generative means from before and after a changepoint are approximately distributed as a triangular distribution (across many trials):

$$p(|\mu_{t-1} - \mu_t|_{cp_t=1}) \approx \frac{2}{180} - \frac{2|\mu_{t-1} - \mu_t|}{180^2}$$

By extension, the absolute prediction errors of the omniscient observer for SAC 1 (Figure 3A) have nearly the same distribution. Hence, their cumulative distribution function (cdf) can be approximated as:

$$p\left(|\tilde{\mu}_{t,omni} - x_t|_{cp_t=1} \leq \varepsilon\right) = \int_0^\varepsilon p\left(|\tilde{\mu}_{t,omni} - x_t|_{cp_t=1}\right) d|\tilde{\mu}_{t,omni} - x_t|_{cp_t=1} \approx \frac{2\varepsilon}{180} - \frac{\varepsilon^2}{180^2}$$

for absolute prediction errors $\varepsilon \in [0°, 180°]$.

The cdf allowed us to assign a cumulative probability to every trial based on the omniscient observer's prediction errors. By definition, the trials of an individual now had a constant density over these cumulative probabilities. We could thus compute an individual's rolling median normalized bias over a grid of cumulative probabilities using a Gaussian weights kernel in the cdf-transformed space. The group-level medians (Q1s, Q3s) were subsequently obtained for each grid point via bootstrapping. Each of the grid points corresponds to a particular prediction error (of the omniscient observer), which we computed via the inverse cdf and utilized as x-axis labels in Figure 3A.

We used a similar cdf-based transformation for the prediction errors of the omniscient observer on no-changepoint stimuli (i.e., SAC 2 and SAC 3 in Figure 3B). The directional prediction errors are roughly distributed as a normal distribution:

$$p(\tilde{\mu}_{t,omni} - x_t|cp_t = 0) \approx N(0, \tilde{\sigma}^2_{t,omni} + \sigma^2_{exp})$$

Since the omniscient observer is fully aware of the changepoints, the a-priori uncertainty about the generative mean, $\tilde{\sigma}^2_{t,omni}$, is equal to the experimental noise variance divided by the number of stimuli that were observed since the last changepoint, e.g., N = 1 for SAC 2 and N = 2 for SAC 3. Hence, the cdf for the absolute prediction errors can be written as:

$$p\left(\left|\tilde{\mu}_{t,omni} - x_t\right|_{cp_t=0} \leq \varepsilon\right) \approx 2\Phi\left(\frac{\varepsilon}{\sigma_{exp}\sqrt{(1 + N^{-1})}}\right) - 1$$

For $\varepsilon \geq 0$, where N is defined by the SAC level, and Φ denotes the cdf of the standard normal distribution.

As before, the cdf was used to assign cumulative probabilities to trials (separately for both noise conditions in SAC 2 and SAC 3), which were then used as a basis to compute individuals' rolling weighted median biases on a regular grid in cdf-space. Subsequently, group-level medians (Q1s, Q3s) were computed via bootstrapping, and the corresponding absolute prediction errors of the grid points were computed via inverse cdfs. Finally, we plotted the curves of the two SAC levels on a common axis, where the axis-spacing was obtained via a cdf transformation with N = 1.5 (i.e., an average spacing for both SAC levels).

N.b. the depicted curves of the modelled observers were computed in the same way as for the human observers: i.e., we simulated their intended response locations ($\tilde{x}_t$, without response noise or lapses) for each individual's set of trials and we used them to compute rolling medians at the individual level (via the cdf-transformation method, if necessary) and group-level medians via bootstrapping, with the same methodological settings as for the human observers.

Acknowledgements

We thank Kamesh Krishnamurthy, Matthew Nassar, Shilpa Sarode, and Joshua Gold for making their experimental data available and for kindly answering our questions. We also thank Günther Koliander for helpful feedback on an earlier version of the methods section. This work was supported by the Austrian Science Fund (FWF; doi.org/10.55776/ZK66, Dynamates).

References

Acerbi, L., Dokka, K., Angelaki, D. E., & Ma, W. J. (2018). Bayesian comparison of explicit and implicit causal inference strategies in multisensory heading perception. *PLOS Computational Biology*, *14*(7), e1006110. https://doi.org/10.1371/journal.pcbi.1006110

Acerbi, L., & Ma, W. J. (2017). Practical Bayesian Optimization for Model Fitting with Bayesian Adaptive Direct Search. *Advances in Neural Information Processing Systems*, *30*.

Adams, R. P., & MacKay, D. J. C. (2007). *Bayesian Online Changepoint Detection* (No. arXiv:0710.3742). arXiv. http://arxiv.org/abs/0710.3742

Bakst, L., & McGuire, J. T. (2023). Experience-driven recalibration of learning from surprising events. *Cognition*, *232*, 105343. https://doi.org/10.1016/j.cognition.2022.105343

Bévalot, C., & Meyniel, F. (2023). *A dissociation between the use of implicit and explicit priors in perceptual inference*. bioRxiv. https://doi.org/10.1101/2023.08.18.553834

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of cognitive science. *Behavioral and Brain Sciences*, *36*(3), 181–204. https://doi.org/10.1017/S0140525X12000477

De Lange, F. P., Heilbron, M., & Kok, P. (2018). How Do Expectations Shape Perception? *Trends in Cognitive Sciences*, *22*(9), 764–779. https://doi.org/10.1016/j.tics.2018.06.002

Eissa, T. L., Gold, J. I., Josić, K., & Kilpatrick, Z. P. (2022). Suboptimal human inference can invert the bias-variance trade-off for decisions with asymmetric evidence. *PLOS Computational Biology*, *18*(7), e1010323. https://doi.org/10.1371/journal.pcbi.1010323

Faisal, A. A., Selen, L. P. J., & Wolpert, D. M. (2008). Noise in the nervous system. *Nature Reviews Neuroscience*, *9*(4), 292–303. https://doi.org/10.1038/nrn2258

Fearnhead, P., & Liu, Z. (2007). On-Line Inference for Multiple Changepoint Problems. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, *69*(4), 589–605. https://doi.org/10.1111/j.1467-9868.2007.00601.x

Friston, K. (2010). The free-energy principle: A unified brain theory? *Nature Reviews Neuroscience*, *11*(2), 127–138. https://doi.org/10.1038/nrn2787

Glaze, C. M., Filipowicz, A. L. S., Kable, J. W., Balasubramanian, V., & Gold, J. I. (2018). A bias–variance trade-off governs individual differences in on-line learning in an unpredictable environment. *Nature Human Behaviour*, *2*(3), 213–224. https://doi.org/10.1038/s41562-018-0297-4

Kang, P., Tobler, P. N., & Dayan, P. (2024). Bayesian reinforcement learning: A basic overview. *Neurobiology of Learning and Memory*, *211*, 107924. https://doi.org/10.1016/j.nlm.2024.107924

Kiyonaga, A., Scimeca, J. M., Bliss, D. P., & Whitney, D. (2017). Serial Dependence across Perception, Attention, and Memory. *Trends in Cognitive Sciences*, *21*(7), 493–497. https://doi.org/10.1016/j.tics.2017.04.011

Knill, D. C., & Pouget, A. (2004). The Bayesian brain: The role of uncertainty in neural coding and computation. *Trends in Neurosciences*, *27*(12), 712–719. https://doi.org/10.1016/j.tins.2004.10.007

Körding, K. P., Beierholm, U., Ma, W. J., Quartz, S., Tenenbaum, J. B., & Shams, L. (2007). Causal Inference in Multisensory Perception. *PLOS ONE*, *2*(9), e943. https://doi.org/10.1371/journal.pone.0000943

Krishnamurthy, K., Nassar, M. R., Sarode, S., & Gold, J. I. (2017). Arousal-related adjustments of perceptual biases optimize perception in dynamic environments. *Nature Human Behaviour*, *1*(6), 0107. https://doi.org/10.1038/s41562-017-0107

Lee, S., Gold, J. I., & Kable, J. W. (2020). The human as delta-rule learner. *Decision*, *7*(1), 55–66. https://doi.org/10.1037/dec0000112

Liakoni, V., Modirshanechi, A., Gerstner, W., & Brea, J. (2021). Learning in Volatile Environments With the Bayes Factor Surprise. *Neural Computation*, *33*(2), 269–340. https://doi.org/10.1162/neco_a_01352

Ma, W. J. (2012). Organizing probabilistic models of perception. *Trends in Cognitive Sciences*, *16*(10), 511–518. https://doi.org/10.1016/j.tics.2012.08.010

McGuire, J. T., Nassar, M. R., Gold, J. I., & Kable, J. W. (2014). Functionally Dissociable Influences on Learning Rate in a Dynamic Environment. *Neuron*, *84*(4), 870–881. https://doi.org/10.1016/j.neuron.2014.10.013

Meijer, D., & Noppeney, U. (2020). Chapter 5—Computational models of multisensory integration. In K. Sathian & V. S. Ramachandran (Eds.), *Multisensory Perception* (pp. 113–133). Academic Press. https://doi.org/10.1016/B978-0-12-812492-5.00005-X

Meijer, D., Veselič, S., Calafiore, C., & Noppeney, U. (2019). Integration of audiovisual spatial signals is not consistent with maximum likelihood estimation. *Cortex*, *119*, 74–88. https://doi.org/10.1016/j.cortex.2019.03.026

Modirshanechi, A., Brea, J., & Gerstner, W. (2022). A taxonomy of surprise definitions. *Journal of Mathematical Psychology*, *110*, 102712. https://doi.org/10.1016/j.jmp.2022.102712

Nassar, M. R., Bruckner, R., & Frank, M. J. (2019). Statistical context dictates the relationship between feedback-related EEG signals and learning. *eLife*, *8*, e46975. https://doi.org/10.7554/eLife.46975

Nassar, M. R., Rumsey, K. M., Wilson, R. C., Parikh, K., Heasly, B., & Gold, J. I. (2012). Rational regulation of learning dynamics by pupil-linked arousal systems. *Nature Neuroscience*, *15*(7), 1040–1046. https://doi.org/10.1038/nn.3130

Nassar, M. R., Waltz, J. A., Albrecht, M. A., Gold, J. M., & Frank, M. J. (2021). All or nothing belief updating in patients with schizophrenia reduces precision and flexibility of beliefs. *Brain*, *144*(3), 1013–1029. https://doi.org/10.1093/brain/awaa453

Nassar, M. R., Wilson, R. C., Heasly, B., & Gold, J. I. (2010). An Approximately Bayesian Delta-Rule Model Explains the Dynamics of Belief Updating in a Changing Environment. *The Journal of Neuroscience*, *30*(37), 12366–12378. https://doi.org/10.1523/JNEUROSCI.0822-10.2010

Norton, E. H., Acerbi, L., Ma, W. J., & Landy, M. S. (2019). Human online adaptation to changes in prior probability. *PLOS Computational Biology*, *15*(7), e1006681. https://doi.org/10.1371/journal.pcbi.1006681

O'Reilly, J. X. (2013). Making predictions in a changing world—Inference, uncertainty, and learning. *Frontiers in Neuroscience*, *7*. https://doi.org/10.3389/fnins.2013.00105

Payzan-LeNestour, E., & Bossaerts, P. (2011). Risk, Unexpected Uncertainty, and Estimation Uncertainty: Bayesian Learning in Unstable Settings. *PLoS Computational Biology*, *7*(1), e1001048. https://doi.org/10.1371/journal.pcbi.1001048

Pearce, J. M., & Hall, G. (1980). A model for Pavlovian learning: Variations in the effectiveness of conditioned but not of unconditioned stimuli. *Psychological Review*, *87*(6), 532–552.

Piasini, E., Liu, S., Chaudhari, P., Balasubramanian, V., & Gold, J. I. (2023). *How Occam's razor guides human decision-making*. https://doi.org/10.1101/2023.01.10.523479

Piray, P., & Daw, N. D. (2021). A model for learning based on the joint estimation of stochasticity and volatility. *Nature Communications*, *12*(1), 6587. https://doi.org/10.1038/s41467-021-26731-9

Pouget, A., Beck, J. M., Ma, W. J., & Latham, P. E. (2013). Probabilistic brains: Knowns and unknowns. *Nature Neuroscience*, *16*(9), 1170–1178. https://doi.org/10.1038/nn.3495

Quintero, S. I., Shams, L., & Kamal, K. (2022). Changing the Tendency to Integrate the Senses. *Brain Sciences*, *12*(10), 1384. https://doi.org/10.3390/brainsci12101384

Rahnev, D., & Denison, R. (2018). Suboptimality in Perceptual Decision Making. *Behavioral and Brain Sciences*, *41*, 1–107. https://doi.org/10.1017/S0140525X18000936

Razmi, N., & Nassar, M. R. (2022). Adaptive Learning through Temporal Dynamics of State Representation. *The Journal of Neuroscience*, *42*(12), 2524–2538. https://doi.org/10.1523/JNEUROSCI.0387-21.2022

Rescorla, R. A., & Wagner, A. R. (1972). A theory of Pavlovian conditioning: Variations in the effectiveness of reinforcement and nonreinforcement. In A. H. Black & W. F. Prokasy (Eds.), *Classical conditioning II: Current research and theory*. Appleton-Century-Crofts.

Rigoux, L., Stephan, K. E., Friston, K. J., & Daunizeau, J. (2014). Bayesian model selection for group studies—Revisited. *NeuroImage*, *84*, 971–985. https://doi.org/10.1016/j.neuroimage.2013.08.065

Ryali, C., Reddy, G., & Yu, A. J. (2018). Demystifying excessively volatile human learning: A Bayesian persistent prior and a neural approximation. *Advances in Neural Information Processing Systems*, *31*.

Shams, L., & Beierholm, U. (2022). Bayesian causal inference: A unifying neuroscience theory. *Neuroscience & Biobehavioral Reviews*, *137*, 104619. https://doi.org/10.1016/j.neubiorev.2022.104619

Shams, L., & Beierholm, U. R. (2010). Causal inference in perception. *Trends in Cognitive Sciences*, *14*(9), 425–432. https://doi.org/10.1016/j.tics.2010.07.001

Skerritt-Davis, B., & Elhilali, M. (2018). Detecting change in stochastic sound sequences. *PLOS Computational Biology*, *14*(5), e1006162. https://doi.org/10.1371/journal.pcbi.1006162

Skerritt-Davis, B., & Elhilali, M. (2021). Computational framework for investigating predictive processing in auditory perception. *Journal of Neuroscience Methods*, *360*, 109177. https://doi.org/10.1016/j.jneumeth.2021.109177

Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., & Friston, K. J. (2009). Bayesian model selection for group studies. *NeuroImage*, *46*(4), 1004–1017. https://doi.org/10.1016/j.neuroimage.2009.03.025

Talluri, B. C., Urai, A. E., Tsetsos, K., Usher, M., & Donner, T. H. (2018). Confirmation Bias through Selective Overweighting of Choice-Consistent Evidence. *Current Biology*, *28*(19), 3128-3135.e8. https://doi.org/10.1016/j.cub.2018.07.052

Tavoni, G., Doi, T., Pizzica, C., Balasubramanian, V., & Gold, J. I. (2022). Human inference reflects a normative balance of complexity and accuracy. *Nature Human Behaviour*, *6*(8), 1153–1168. https://doi.org/10.1038/s41562-022-01357-z

Trimmer, P. C., Houston, A. I., Marshall, J. A. R., Mendl, M. T., Paul, E. S., & McNamara, J. M. (2011). Decision-making under uncertainty: Biases and Bayesians. *Animal Cognition*, *14*(4), 465–476. https://doi.org/10.1007/s10071-011-0387-4

Verbeke, P., & Verguts, T. (2024). Humans adaptively select different computational strategies in different learning environments. *Psychological Review*, No Pagination Specified-No Pagination Specified. https://doi.org/10.1037/rev0000474

Wilson, R. C., Nassar, M. R., & Gold, J. I. (2010). Bayesian Online Learning of the Hazard Rate in Change-Point Problems. *Neural Computation*, *22*(9), 2452–2476. https://doi.org/10.1162/NECO_a_00007

Wilson, R. C., Nassar, M. R., & Gold, J. I. (2013). A Mixture of Delta-Rules Approximation to Bayesian Inference in Change-Point Problems. *PLoS Computational Biology*, *9*(7), e1003150. https://doi.org/10.1371/journal.pcbi.1003150

Wozny, D. R., Beierholm, U. R., & Shams, L. (2010). Probability Matching as a Computational Strategy Used in Perception. *PLoS Computational Biology*, *6*(8), e1000871. https://doi.org/10.1371/journal.pcbi.1000871

Yu, L. Q., Wilson, R. C., & Nassar, M. R. (2021). Adaptive learning is structure learning in time. *Neuroscience & Biobehavioral Reviews*, *128*, 270–281. https://doi.org/10.1016/j.neubiorev.2021.06.024