Differential destinations, dynamics, and functions of high- and low-order features in the feedback signal during object processing

Wenhao Hou[1,3], Sheng He[1,2,3,*], and Jiedong Zhang[1,3,*]

[1] State Key Laboratory of Brain and Cognitive Science, Institute of Biophysics, Chinese Academy of Sciences, Beijing 100101, China

[2] Institute of AI, Hefei Comprehensive National Science Center, Hefei 230088, China

[3] University of Chinese Academy of Sciences, Beijing 100049, China

[*] Correspondence: hes@ibp.ac.cn (S.H.) zhangjiedong@gmail.com (J.Z.)

Abstract

Brain is a hierarchical information processing system, in which the feedback signals from

high-level to low-level regions are critical. The feedback signals may convey complex high-

order features (e.g., category, identity) and simple low-order features (e.g., orientation, spatial

frequency) to sensory cortex to interact with the feedforward information, but how these

types of feedback information are represented and how they differ in facilitating visual

processing is unclear. The current study used the peripheral object discrimination task, 7T

fMRI, and MEG to isolate feedback from feedforward signals in human early visual cortex.

The results showed that feedback signals conveyed both low-order features natively encoded

in early visual cortex and high-order features generated in high-level regions, but with

different spatial and temporal properties. The high-order feedback information targeted both

superficial and deep layers, whereas the low-order feedback information reached only deep

layers in V1. In addition, MEG results revealed that the feedback information from occipito-

temporal to early visual cortex emerged around 200 ms after stimulus onset, and only the

representational strength of high-order feedback information was significantly correlated with

behavioral performance. These results indicate that the complex and simple components of

feedback information play different roles in predictive processing mechanisms to facilitate

sensory processing.

Introduction

As sensory information is processed in the primate brain, the neural system actively interprets the sensory input to generate a consistent and meaningful perception. This process relies on the interplay between feedforward and feedback processes in the neural processing hierarchy. Anatomically, feedback connections are widely distributed in the visual cortex[1]. Functionally, behavioral and neural evidence has shown that neural feedback to early visual cortex is critical for many visual functions, such as object recognition and visual awareness[2–4]. However, limited knowledge of the nature of the feedback information hinders our understanding of how neural feedback interacts with visual input.

Significant transformations of neural representations occur across the visual processing hierarchy. Compared to early visual cortex, where neurons encode low-order features like orientation and spatial frequency[5], neurons in higher-level cortex have larger receptive fields and more complex tuning of high-order features[6,7], such as category and identity. What kind of information is conveyed by feedback signals? Based on predictive coding theory[8,9], the feedback signal is compared to the input signal to generate prediction errors for further processing. However, the high-order representation is more abstract and invariant, and a feedback signal with such information may not be feasible for a direct "comparison". For an effective comparison, it is reasonable to assume that the feedback signal should be in the form of low-order predicted information. However, previous evidence suggests that object category information could be decoded in the feedback signals[10,11]. It is unclear whether this category decoding originated from high-order object category information, or was driven by low-order (i.e., object shape and orientation) information[12]. Therefore, it is crucial to dissociate these two types of features and investigate what kind of information is conveyed in feedback signals during object processing.

A notable feature of the primate brain is the presence of layered structures, with each layer serving a distinct function[1,13–15]. In the early visual cortex, feedforward signals are directed towards the middle layers, while both deep and superficial layers receive feedback signals. The output signals to downstream regions are generated in the superficial layer. The feedback information may originate from object processing areas in temporal cortex, but in the early visual cortex, the laminar profiles of the high- and low-order information in feedback signals are unknown. It is important to clarify where the different types of input and feedback information arrive in early visual cortex.

Plenty of evidence indicates that feedback signals can enhance visual processing efficiency, and further optimize behavioral performance[16,17]. However, the behavioral implications of high- and low-order feedback information remain unclear. It is important to examine whether and when each type of feedback information correlates with behavioral performance during visual processing.

Examining neural information in the feedback signal can be challenging due to the highly tangled distribution of the feedforward and feedback signals during visual processing in the cortex. To isolate the feedback signals, we took advantage of a peripheral object recognition paradigm. Previous studies have shown that when objects are presented in the visual periphery for identification, their information is fed back to foveal V1[10]. The spatial separation between the input signal and feedback signal in the retinotopic visual cortex enabled the extraction of various types of feature information in the feedback signal without interference from feedforward visual input. Additionally, the high spatial resolution of 7T MRI and high temporal resolution of MEG recording allowed for the evaluation of laminar profiles and temporal dynamics of feedback signals respectively, as well as information flow among different cortical regions. The results indicate that, in addition to the low-order features, feedback signals also transmit high-order category information to V1. Importantly, the high-order information cannot be observed in feedforward processing in V1. Interestingly, high- and low-order feedback information exhibit different laminar profiles. The quality of high-order information in feedback signal also shows a significant correlation with behavioral performance. The high-order information originates from object processing regions in the occipito-temporal cortex approximately 200 ms after visual input. Apparently, high-order feedback information from downstream regions and its interaction with locally encoded low-order information may be critical for efficient visual processing.

Results

Orientation and category information in the feedback signal to V1 during peripheral object processing

In Experiment 1, peripheral object task was used during the 7T fMRI scan. The stimuli were novel objects from two categories (smoothie and cubie) and two orientations (vertical and horizontal) (see Figure 1A). In each trial, two objects from the same category with the same orientation were briefly presented (100 ms) in the peripheral visual field (7 degrees from fixation) (see Figure 1B). Participants were asked to judge whether the two objects were identical while maintaining fixation. To optimize fMRI signal in the experimental runs, a block design was used, with each block consists of eight trials testing objects from the same category and orientation (see *Materials and Methods* for more details).

In addition to the twelve experimental runs, three localizer runs were included in the scan to identify regions of interest (ROIs) in each hemisphere. In one of the localizer runs, flashing checkerboards were presented either at the periphery where objects were presented during the task or at the fovea. ROIs of peripheral V1 and foveal V1 were identified using contrast maps between these two conditions (Figure S1). In the other two localizer runs, everyday objects and scrambled objects were presented in different blocks while participants performed a one-back task. These conditions were used to identify two high-level object processing regions: the lateral object complex (LOC)[18] in the ventral pathway and the posterior intraparietal sulcus (pIPS)[19] in the dorsal pathway.

The neural responses based on BOLD signal in the four ROIs were estimated. Univariate analysis shows significant fMRI responses in three ROIs (peripheral V1, LOC, pIPS) during the task, while no significant fMRI response was observed in foveal V1 (t(17)=-0.09, p=0.93) (Figure 1C) due to the absence of visual input in the fovea.

Figure 1. Feedback information to foveal V1 in the peripheral object task (n=18).

(**A**) Four types of objects (two orientations × two object categories) were used in the experiment. (**B**)

Two objects from the same type were presented in the periphery and participants had to discriminate

whether they were identical. (**C**) Strong fMRI responses were found in peripheral V1 corresponding

to the stimulus locations and high-level regions, but not in foveal V1. (**D**) Schematic representation of

feedforward and feedback connections in different cortical layers of V1. (**E**) High-order category

information from feedback signals could be decoded in foveal, but not peripheral, V1. (**F**) The

category information could be decoded in superficial and deep layers of foveal V1, but absent in all

layers of peripheral V1. (**G-H**) Low-order orientation information from feedback signals could be

decoded only in the deep layer of foveal V1 and across layers in peripheral V1. Error bars reflect ±1

SEM. * indicates paired t-test with significance of p< 0.05. ** indicates paired t-test with significance

of p< 0.01. † indicates marginal significance. The dashed line represents the chance level of decoding

performance. See also Figure S2.

Multivariate analysis (Linear support vector machine, SVM) was used to evaluate the

information encoded in each ROI by classifying the neural response patterns elicited by

objects from different conditions. The neural patterns were classified based on low-order

orientation information (horizontal or vertical) or high-order category information (cubie or

smoothie). The classification accuracy was used to indicate the existence of information in

each ROI.

Although the average fMRI responses in foveal V1 did not differ from the baseline, the

neural response patterns there supported significantly above chance decoding accuracies of

high-order categories (t(17)=3.14, p=0.003) (see Figure 1E). The object category information

was also examined in other cortical regions. The decoding performances were significantly

above chance in the LOC and pIPS (ts>1.94, ps<0.04), but not in the peripheral V1 (t(17)=-

1.19, p=0.87) (see Figure 1E).

Further, the 7T fMRI's sub-millimeter resolution enabled us to examine the laminar profiles

of cortical regions. Previous neurophysiology studies have shown that in V1, feedforward

and feedback signals differentially target different layers. Here, based on anatomical images

of each participant, the gray matter was segmented into deep, middle, and superficial layers

(Figure 1D). The neural responses in these layers from each ROI were extracted and analyzed

separately.

In foveal V1, the high-order category information could be decoded in the superficial and

deep layers (ts>2.37, ps<0.02), but not in the middle layer (t(17)=-0.62, p=0.73). In

peripheral V1, none of the layers showed significant decoding performance (ts<0.10,

ps>0.46)(Figure 1F). While the chance level decoding performance in peripheral V1 rejects

the possibility that the high-order information is laterally communicated from peripheral V1,

the laminar profile of information in foveal V1 more clearly demonstrates that high-order

category information was transmitted to the deep and superficial layers of foveal V1 via

feedback connections. In the two high-level regions LOC and pIPS, category information was

successfully decoded in the middle and superficial layers (ts>1.92, ps<0.04), suggesting that

the category information was present in the middle layer in these regions and further

processed and outputted to other cortical regions through the superficial layer.

For the low-order orientation information, the decoding performance was significant in

peripheral V1 and LOC (ts>2.32, ps<0.02), but not in pIPS (t(17)=0.00, p=0.50) (Figure 1G).

In foveal V1, the orientation decoding performances were marginally significant (t(17)=1.50,

p=0.08). Further layer analysis showed that in foveal V1, significant orientation decoding

was observed in the deep layer (t(17)=2.43, p=0.01), but not in the middle and superficial

layers (ts< 0.98, ps>0.17) (Figure 1H). The fine-scale laminar profiles of different types of

feedback information in foveal V1 supported this observation (Figure S2). In peripheral V1

where stimuli were presented, not surprisingly, significant orientation decoding performances

were observed in the middle and superficial layers (ts>3.06, ps<0.004). In the two high-level

visual regions, orientation information was only significant in the deep layer of LOC

(t(16)=2.26, p=0.02) . The results indicate the presence of orientation information in the

feedback signal in foveal V1, however the strength of the low-order orientation information

appears to be weaker and less extensive across cortical layers compared to the high-order

category information.

High-order category information in V1 not driven by low-level features

Is the successful decoding of category information observed in foveal V1 truly driven by

high-order information in the feedback signals, or could it be driven by some low-level

confounding features embedded in the stimuli that are natively encoded in V1? To address

this concern, Experiment 2 was conducted to examine the visual representation in foveal V1

with stimuli directly presented at the fovea, thus providing strong representation of low-level

features in the feedforward processing. In addition, during the scan, participants were asked

to perform a one-back task regarding the fixation color. This manipulation makes the object

stimuli task-irrelevant, minimizing the feedback signal during object processing (Figure 2A).

Figure 2. Object representation in foveal V1 during a fixation task (n=18).

(**A**) The object stimulus was presented at the fovea as a task-irrelevant stimulus and participants

performed a 1-back task to the fixation color. (**B-C**) Category information could not be decoded in

foveal V1. (**D-E**) Orientation information could be decoded in all layers of foveal V1. Error bars

reflect ±1 SEM. * indicates paired t-test with significance of p< 0.05. ** indicates paired t-test with significance of p< 0.01. The dashed line represents the chance level of decoding performance.

Decoding analysis revealed significant orientation information in foveal V1 ($t(17)=6.94$, $p<0.001$), but no category information could be detected there ($t(17)=0.38$, $p=0.35$). Not surprisingly, there is significant category information in the LOC ($t(16)=2.48$, $p=0.01$) (Figure 2B&D). Further layer analysis revealed that category information was significant in the middle and superficial layers of LOC ($ts>1.92$, $ps<0.04$), while orientation information was significant in all three layers of foveal V1 ($ts>5.35$, $ps<0.001$) (Figure 2C&E). No significant category information was observed in either layer of the foveal V1 ($ts<0.80$, $ps>0.21$), indicating that without task-driven feedback signals, feedforward processing alone was insufficient to generate category information in foveal V1. These observations support the interpretation that the category information in foveal V1 observed in the peripheral object discrimination task was coming from the feedback signals.

Temporal dynamics of feedback category and orientation information

The two 7T fMRI experiments revealed distinct neural representations conveyed in the feedback signal and their laminar profiles in V1. In Experiment 3, the temporal dynamics of high- and low-order feature representations in the feedback signal were examined using MEG. The MEG experiment included two tasks, the peripheral object task (as in Experiment 1) and the foveal object task (as in Experiment 2) (see *Materials and Methods* for more details). The order of the two task blocks was counterbalanced across participants.

Figure 3. Temporal dynamics of object representation in different cortical regions (n=15).

(**A**) In the MEG experiment, two objects of the same type were presented in the periphery. The locations of the objects changed across trials. (**B-C**) Using the source localization algorithm, the neural responses of three cortical regions were extracted. In all regions, both category and orientation information could be decoded either within the same location set (**B**) or across different location sets (**C**). (**D**) Same-location and cross-location decoding performances were normalized and plotted together to facilitate their comparison. The dynamics of decoding performance were significantly delayed for cross-location decoding in early visual cortex (solid red and blue lines). The dashed black line represents the chance level of decoding performance. The gray bar on the time axis indicates the presentation time of the object stimuli. Colored shaded areas reflect ±1 SEM. The colored bars below the time courses indicate the significance (p<0.01) of the decoding accuracy in a cluster permutation test. See also Figure S3.

In the peripheral object experiment (Figure 3A), to examine the neural representations of high- and low-order information, we trained and tested SVMs for them at each time point after the stimulus onset (see *Materials and Methods*). Source localization analysis was applied to map the MEG signals from the sensors to the cortex in each participant. Dynamic statistical parametric mapping (dSPM)[20] was used to extract neural response patterns in three cortical regions: the early visual cortex, the occipito-temporal cortex, and the posterior

parietal cortex. The limited spatial resolution of the source localization method made it difficult to separate the neural responses between foveal and peripheral regions in the early visual cortex. To estimate the strength of the neural representations in the foveal region in the early visual cortex, we applied cross-location decoding analysis to the data from the peripheral object task. During the task, two objects were presented in each trial, either at the upper-right and lower-left visual fields or at the upper-left and lower-right visual field, thus the visual information was sent to different retinotopic areas in the early visual cortex during feedforward processing. The neural representations elicited by feedforward processing from the two pairs of locations are spatially separated and could not be generalized across locations. However, during feedback processing, object information was fed back to the same foveal cortex, allowing for generalization of feedback neural representation across different peripheral locations. Here, when the decoders were trained and tested using data from objects presented at the same locations, the results showed that both category and orientation information could be decoded from all three cortical regions (Figure 3B). Next, the decoders were trained and tested using data from different locations, and the decoding performance generally decreased in all cortical regions (Figure 3C). To compare the temporal dynamics between same-location and cross-location decoding, we normalized the peak performances of the same-location decoding and cross-location decoding (Figure 3D). The results indicate that, for both category and orientation information in the early visual cortex, decoding performances were substantially delayed for cross-location data compared to the same-location data. This is consistent with the idea that feedback signals in the early visual cortex, which were slower than feedforward signals, supported the generalized cross-location decoding. In contrast, the dynamics of decoding performances showed location invariance in occipito-temporal cortex. In posterior parietal cortex, delayed performance was observed for cross-location decoding, possibly due to the extensive retinotopic representations in parietal cortex. Further latency analysis, which estimated the time from stimulus onset to 75% of peak decoding performance, showed consistent results that for both high- and low-order information, the latency was shortest in early visual cortex for same-location decoding, but was shortest in occipito-temporal cortex for cross-location decoding (Figure S3).

The transmission and behavioral relevance of high- and low-order feedback information

To evaluate the transmission of high- and low-order information between different cortical regions, Granger causality analysis was performed on the temporal dynamics of neural representation. First, the strength of neural representation at each time point in each ROI was estimated by calculating the distance from the neural response pattern to the decoding hyperplane in the high-dimensional space for each time point in each trial[21]. Then the Granger causality analysis tested whether the variation in neural representation strength at the current time in the target ROI could be explained by past neural representations in a source ROI, beyond the explanation provided by past representations in the target ROI itself (Figure 4A)[22,23].

Figure 4. Information transmission between cortical regions revealed by Granger causality analysis (n=15).

(**A**) The strength of representation was estimated by the distance from the neural response pattern to the decoding hyperplane. The dynamics of representation strength were used to estimate information transmission between cortical regions. (**B-C**) The Granger causality of feedforward (blue) and feedback (orange) category (**B**) and orientation (**C**) information between three cortical regions during peripheral object discrimination task. (**D-E**) The Granger causality of feedforward and feedback information of category (**D**) and orientation (**E**) during a fixation detection task with an object presented at the fovea. The directions and initial timings of information flow between cortical regions were also indicated by arrows and the onset times next to the arrows. The gray bar on the time axis indicates the presentation time of the object stimuli. The colored shaded areas reflect ±1 SEM. The colored bars below the time courses indicate the significance (p<0.01) of Granger causality in a cluster permutation test.

In the peripheral object task, significant Granger causality in the feedforward direction was found for high-order category information from early visual cortex to occipito-temporal

cortex (190 ms) and to posterior parietal cortex (100 ms). Notably, significant Granger causality was observed in the feedback direction from occipito-temporal cortex to early visual cortex emerging around 220 ms, and from posterior parietal cortex to early visual cortex emerging at 520 ms (Figure 4B). For low-order orientation information, significant Granger causality in the feedforward direction was found from early visual cortex to occipito-temporal cortex and posterior parietal cortex, both emerging around 140 ms. For the feedback direction, significant Granger causality was observed from occipito-temporal cortex to early visual cortex emerging around 250 ms (Figure 4C). These results further support that feedback signals from occipito-temporal cortex to early visual cortex contain both high- and low-order information. The broad temporal overlap between feedforward and feedback processes, especially for the high-order category information, is consistent with a recurrent processing for visual object recognition.

In the foveal object task, feedforward category information was observed from the early visual cortex to both occipito-temporal cortex (200 ms) and posterior parietal cortex (310 ms). Feedback category information to the early visual cortex was observed from the occipito-temporal cortex (160 ms) and posterior parietal cortex (360 ms) (Figure 4D). For orientation information in the feedforward direction, significant Granger causality was found from early visual cortex to occipito-temporal cortex (120 ms) and to posterior parietal cortex (110 ms). For the feedback orientation information, significant Granger causality was observed from occipito-temporal cortex to early visual cortex emerging at 290 ms (Figure 4E). These results suggest that, for foveally presented objects, the feedforward-feedback recurrent processes between occipito-temporal cortex and early visual cortex occur in a narrower time window.

After tracking the dynamic transmission of feedback signals, we also examined the behavioral relevance of different types of information in the feedback signal at each time point to uncover the contribution of feedback signals to behavioral performance. The reaction time was recorded for each trial during the MEG session, which allowed us to calculate its correlation with the strength of time-resolved high-order and low-order information in the feedback signal during the peripheral object discrimination task. Similar to Granger causality analysis, the distance from the neural response pattern to the decoding hyperplane was used to estimate the strength of neural representation (Figure 4A). To concentrate on the feedback signal in early visual cortex, we trained the hyperplane with data from trials in which objects

were presented at different locations from the current trial (i.e., cross-location decoding). For

each time point, the correlation between the reaction time and the neural representation

strength across different trials was calculated for each participant (Figure 5A). The positive

correlation indicated that better representation quality linked with faster reaction time. The

group-averaged results revealed significant behavioral correlations in the early visual cortex

for high-order category information, emerging around 210 ms after stimulus onset, which is

consistent with the results from Granger causality analysis. Additionally, significant

behavioral correlations were observed in the occipito-temporal cortex (190 ms) (Figure 5B).

However, no significant behavioral correlation was observed in the early visual cortex for

low-order orientation information. Apparently, neither high- nor low-order information in

the parietal cortex was correlated with behavioral response.

Figure 5. Behavioral relevance of feedback information in the visual cortex (n=15).

(**A**) The strength of information representation at each time point of each trial was estimated by cross-location decoding, its correlation with reaction time across trials was calculated to estimate its behavioral relevance. (**B**) Significant behavioral relevance was observed for category information in early visual cortex between 200 and 400 ms after stimulus onset, consistent with the time window of feedback signals. Colored shaded areas reflect ±1 SEM. The colored bars below the time courses indicate the significance (p<0.05) of the correlation in a cluster permutation test. (**C**) Schematic summary depiction of information flow among key cortical regions (top) and different types of feedback information from temporal cortex to different cortical layers of V1 (bottom).

Discussion

Understanding what types of information are conveyed by feedback signals is critical to the investigation of the computational mechanism of feedback processing. Our results demonstrate that the feedback signals to V1 convey both low-order and high-order information. The orientation information, which is considered natively encoded in V1, could be detected in the feedback signals. The observation supports the notion that the feedback process elicits comparable neural representations to those of the feedforward process[24,25], enhancing processing efficiency by predicting the input signals[8,9]. Notably, reliable representations of category information were also detected in the feedback signals to V1, while this information could not be observed in V1 in a feedforward dominated process. These results firmly establish that the category information in V1 originated from a high-level region in the visual hierarchy, rather than generated locally in V1. This suggests that during the recurrent processes for object identification, high-level regions communicate feedback signals to V1, and these feedback signals not only contain local V1-native features that enable predictive error encoding, but also communicates more complex and invariant neural information to constrain the predictive processing.

Moreover, the current study found that the laminar profile of high-order information differed from that of low-order information in the feedback signals (Figure 5C). Orientation representation was observed in the deep layer, while high-order category representation was found in both deep and superficial layers. The deep and superficial layers of V1 have different roles in visual processing. Both deep and superficial layers receive feedback signals from downstream high-level regions, but the superficial layer also generates output signals for further processing downstream. Specifically, within the superficial layer, output signals are generated in layers 2/3 and sent to the downstream regions targeting layer 4. Meanwhile, layer 1 receives feedback signals, that can modulate the output signals in layers 2/3[26,27]. Our study suggests that the orientation information in feedback signals may reflect the mechanisms predicting the input signal during object processing. The predicted orientation representation in deep layer of V1 was consistent with previous findings that the neural representations of expected orientation was only observed in the deep layer of V1[28]. This laminar profile was also observed in the V1 neural responses to subjective contours in illusory Kanizsa figures[29], supporting the predicting coding theory. The high-order category information, which was shown to be fed back to both the superficial and deep layers, may

support additional mechanisms during the feedback processing. The category information
observed in the superficial layer may arise from layer 1, and its function could be to modulate
the output signals in layers 2/3. The feedback information to the superficial layer may be
linked to task-driven top-down modulation, as similar laminar profiles have been observed
previously in top-down attention and working memory tasks[30–33]. Therefore, we hypothesize
that the high-order information in the feedback signal, especially in the superficial layer,
guides and constrains feedforward processing to enhance processing efficiency in the object
identification task. In other words, if the experimental design required participants to
discriminate orientation rather than object identity, we would expect stronger orientation
information in foveal V1 and significant decoding performance of orientation feedback
information in the superficial layer of foveal V1. Recent studies[34,35] have also highlighted the
relationship between feedback information and neural representations in V1 superficial layer.
The functional relevance of the feedback signals, especially the high-order information, was
also demonstrated in the MEG results, which consistently showed a significant trial-to-trial
correlation between the high-order feedback information and the behavioral performances.

The next question is how high-order information was encoded in the early visual cortex.
Recent two-photon imaging has revealed the existence of neurons in the superficial layer of
V1 that are selective to complex patterns and features[36–39]. Although the distribution of such
complex-feature selective neurons is very sparse, they likely play an important role in the
representation and utilization of high-order feedback information. Meanwhile, in accordance
with the sparse distribution of the complex feature selective neurons in V1, the feedback
signals did not significantly increase the general fMRI response amplitude in foveal V1.
Currently, the response dynamics and connectivity patterns of these V1 neurons are unclear,
future studies should compare high-order and low-order information dynamics across
different cortical layers to further advance our understanding of how high-order feedback
information interacts with feedforward visual processing to increase efficiency.

The Granger causality analysis from MEG results reveals that the backward information
transition of both high-order category information and low-order orientation information
from the occipito-temporal cortex to the early visual cortex, which emerged approximately
200 ms after the peripheral object onset. Consistently, the behavioral correlation results show
that high-order information in the early visual cortex began to correlate with behavioral
performance around 200 ms. These results suggest that functional-relevant high-order

information reached foveal V1 approximately 200 ms after stimulus onset in the peripheral

object identification task. The temporal dynamics of feedback information in this study is

consistent with previous observations[11,40,41]. However, it is important to note that the

temporal dynamics of the feedback process may vary depending on the visual inputs and task

demands. On one hand, low-quality visual input, such as low-contrast or occluded objects,

may delay the initial feedforward and model generating process[42–44], which in turn delays the

feedback signals. On the other hand, Previous research has shown that the foveal feedback

mechanism exhibits some degree of flexibility. For instance, increasing the high-level

operation of the peripheral task can delay the temporal dynamics of the foveal feedback[11].

Additionally, there is also evidence that feedback process operates differently for peripheral

vision compared with central vision, with the Central-peripheral Dichotomy theory proposing

a weaker feedback for peripheral vision[45]. Therefore there are multiple factors that may lead

to temporal variations of the feedback signal[16].

In the current study, fMRI signals from early visual cortex and two high-level brain regions

(LOC and pIPS) were recorded. Neural dynamics of these regions were extracted from MEG

signals. Decoding analyses based on fMRI and MEG signals consistently showed that object

category information could be decoded from both regions. These findings raise an important

question: further Granger causality analysis indicates that the feedback information in foveal

V1 was mainly driven by signals from the LOC. Layer-specific analysis showed that category

information could be decoded in the middle and superficial layers of the LOC. A reasonable

interpretation of this result is that feedforward information from the early visual cortex was

received by the LOC's middle layer, then the category information was generated and fed

back to foveal V1 through the LOC's superficial layer. A recent study found that, in object

selective regions in temporal cortex, the deep layer showed the strongest fMRI responses

during an imagery task[46]. Together, the results suggest that the deep and superficial layers

correspond to different feedback mechanisms. It is worth noting that other cortical regions

may also generate feedback signals to the early visual cortex. The current study did not have

simultaneously recorded fMRI signals from the prefrontal cortex, but it has been shown that

feedback signals can be traced back to the prefrontal cortex during complex cognitive tasks,

such as working memory[47,48]. Further fMRI studies with submillimeter resolution and whole-

brain coverage are needed to test other potential feedback pathways during object processing.

The peripheral object identification task required processing of both category and orientation

information, and the results showed that both kinds of information were fed back to early

visual cortex. Evidence has shown that the foveal feedback occurrence depends on the

requirement for distinguishing fine object details in the periphery[11,49]. Object category

feedback information was not observed in foveal V1 when participants were distinguishing

between colors instead of distinguishing between object identities[10]. It is apparent that the

feedback mechanism could flexibly select the information, especially the high-order

information, sent back to the early visual cortex depending on the task requirements.

However, it is unclear whether low-order information conveyed in the feedback signals is

more independent of the task demand. Supposing the function of the low-order feedback

information is to support the realization of predictive coding in early visual cortex, then the

low-order information could be more intrinsic and task-invariant in feedback signals.

The hierarchical structure and extensive feedback connections are key features of the human

neural system. Feedback signals are believed to be important for efficient neural processing,

but the algorithm of these signals in neural computation is largely unknown. Our findings

dissociated various types of information in the feedback signals, uncovered their laminar

profiles, and traced their temporal dynamics across the cortical hierarchy. These findings

reveal the multiple components in the feedback signals, and contribute to the comprehensive

understanding of the interactive feedforward and feedback computational mechanisms, a key

feature in human intelligence.

Materials and Methods

Participants

In the fMRI experiments, 22 participants were recruited, all of whom had normal or corrected-to-normal vision. In the data analysis, 4 participants were excluded due to excessive head movement. Therefore, data from 18 effective participants (10 females; aged 19-29) was included in the results. The MEG experiment recruited 15 participants (10 females; aged 19-29). Before the experiments, all participants gave written consent, and the institutional review board of the Institute of Biophysics, Chinese Academy of Sciences approved the protocols (#2017-IRB-004).

fMRI experiments
Stimuli and procedures

OpenGL was used to generate object stimuli. The stimuli consisted of two categories (cubie vs. smoothie) and two orientations (vertical vs. horizontal). For each category, 18 individual objects were created.

During the peripheral object task, objects from the same condition were presented in the upper left and lower right visual field, 7° away from the fixation. The object size was either 3° × 1.5° or 1.5° × 3° depending on the stimulus conditions. Objects were presented for 100 ms in each trial, followed by 1900 ms of blank screen. Participants were asked to judge whether the two objects were identical. To maximize the fMRI signals, block design was used, with each block containing 8 trials from the same condition. During each block, the fixation was presented for 200 ms repeatedly, with 300 ms interval between two fixations. The color of the fixation changed randomly, but this should be ignored in the peripheral task.

In the foveal task of the fMRI experiment, an object of the same size as in the peripheral task was presented at foveal for 100 ms, followed by a 1900 ms interval. All other parameters were the same as in the peripheral task. The participants completed a one-back task where they had to press a button when the fixation color was repeated between two adjacent presentations.

The fMRI experiment contained 12 task runs. Each run included 8 blocks, with 1 block from each condition in each task, interleaved with 12 second blank periods. The peripheral and

foveal task blocks were presented alternately, and the orders were counterbalanced across

runs. The orders of the object condition were pseudo-random across runs. The accuracy of

behavioral responses in the peripheral object task was 67.4%±4.4%.

In addition to the task runs, three localizer runs were included in the scan. In one of the runs,

flashing checkerboards with a size of 3° were presented in different blocks at either the foveal

or peripheral visual field, which was used to localize the ROIs of foveal and peripheral V1.

The locations of the checkerboards matched the object locations in the task runs. The other

two runs were used to localize LOC and pIPS. Everyday object images and phase-scrambled

images were presented in different blocks.

MRI scanning and preprocessing

MRI data were collected on a Siemens Magnetom 7 Tesla MRI system (passively shielded,

45mT/s slew rate) (Siemens, Erlangen, Germany), with a 32-channel receive 1-channel

transmit head coil (NOVA Medical, Inc, Wilmington, MA, USA), at the Beijing MRI Center

for Brain Research (BMCBR). High-resolution T1-weighted anatomical images (0.7 mm

isotropic voxel size) were acquired with a MPRAGE sequence (256 sagittal slices,

acquisition matrix = 320 × 320, Field of view (FOV) = 223 × 223 mm, GRAPPA factor = 3,

TR = 4000 ms, TE = 3.05 ms, TI = 0 ms, flip angle = 0°, pixel bandwidth = 240 Hz per

pixel). GE-EPI sequences were used to collect functional data in the main experiment (TR =

2000 ms, TE = 23 ms, 0.8 mm isotropic voxels, FOV = 128 × 128 mm, GRAPPA factor = 3,

partial Fourier 6/8, 31 slices of 0.8 mm thickness, flip angle is about 80, pixel bandwidth =

1157 Hz per pixel). During the scan, GE-EPI images with reversed phase encoding direction

from experiment functional scan were collected to correct the spatial distortion of EPI

images.

MRI image data were analyzed with FreeSurfer (CorTechs Inc, Charlestown, MA, USA)[50],

AFNI (http://afni.nimh.nih.gov)[51], and custom codes. For anatomical data, to reconstruct the

cortical surfaces, anatomical data were further processed by FreeSurfer, including gray and

white matter segmentation and identification of V1 region. SUMA and custom

Python/MATLAB codes were used to generate equi-volume surfaces

(https://github.com/herrlich10/mripy). For each voxel, its volume percentages of WM, CSF,

and different cortical layers (deep, middle, superficial) were calculated. For function data,

preprocessing included slice-timing correction, motion correction, distortion correction using

reversed-phase encoding EPI images, and intensity normalization. An additional spatial

smoothing with a 2 mm Gaussian kernel was applied to the localizer data. Beta values of

stimulus-evoked responses were estimated with GLM for each voxel.

Regions of interest

Foveal V1 and peripheral V1 were defined on the surface of each participant, with contrast

between the foveal and peripheral checkerboards (p<0.01, uncorrected). The anatomical

labeling of V1 was used to constrain the spatial locations of the ROIs. The LOC was defined

as regions responding more strongly to everyday objects than to scrambled objects in ventral

occipital-temporal cortex. The pIPS was located in the Intraparietal Sulcus, which responded

more strongly to real objects than to the rest conditions. All ROIs were defined on the gray

matter surface and then converted to volume. For the layer analysis, the voxels in the ROI

could be further classified into deep, middle, and superficial layers based on their dominant

volume percentages generated from the anatomical data analysis. Due to limited FOV size of

the EPI sequence, the LOC was not covered in one participant.

For each ROI, the number of voxels depended on the size of the activated region, as

estimated from the localizer data. The numbers are as follows: foveal V1, 2185 ± 389;

peripheral V1, 1294 ± 215; LOC, 3451 ± 863; and pIPS, 5154 ± 1517. To avoid the signals of

large vessels, a portion of voxels was removed based on the distribution of large vessels: V1

foveal, $22.5\% \pm 6.6\%$; V1 peripheral, $6.8\% \pm 3.9\%$; LOC, $16.1\% \pm 8.1\%$; and pIPS, $5.1\% \pm$

3.2%. For the decoding analysis, the top 500 responsive voxels in each ROI were selected to

balance the voxel numbers across different ROIs for training and testing the decoder.

Correcting the vasculature-related signals

Two analyses were performed to remove vasculature-related signals. The distribution of beta

values in each ROI was fitted by two Gaussian distributions. Voxels that fell into the higher

response Gaussian distribution were excluded from further analyses[52]. Second, the mean EPI

signal was calculated for each voxel and the spatial trend of EPI signal was removed in each

ROI. Similar to the beta values analysis, two Gaussian distributions were used to fit the

distribution of EPI signal in each ROI. Voxels falling into the lower response Gaussian

distribution were also excluded from further analyses[52].

Decoding analysis

For each ROI and each participant, a linear classifier (http://www.csie.ntu.edu.tw/~cjlin/libsvm)[53] was trained to classify the neural response patterns from different conditions. To estimate the decoding performances, supervised learning and a leave-one-run-out cross-validation approach were used. The neural response patterns of the same condition were averaged in each run. Before each training procedure for each ROI, the top 500 voxels were selected based on their t-value between two conditions. For the layer analysis in each ROI, the top 300 voxels were selected for each layer. If a layer had fewer than 300 voxels, then all the voxels were included in the training procedure.

MEG experiment

Stimuli and procedures

The MEG experiment used similar stimuli and tasks as the fMRI experiment. For the peripheral object task, two objects were presented in the peripheral visual fields (7 ° from fixation) for 100 ms in each trial. The object locations were either upper left and lower right or upper right and lower left, which was random across trials. Participants had to determine whether the two objects were identical within 2100 ms of stimulus onset. Each participant completed 104 trials for every condition at each location set. For the foveal task, each trial lasted between 900 ms and 1300 ms randomly, and the object was presented at the fixation for 100 ms. Participants were instructed to press a button when the fixation color turned white. Trials in which a key was pressed were excluded from later analyses. 104 valid trials were collected for each object condition for each participant.

Each participant completed four task runs, each consisting of one peripheral task block and one foveal task block. The order of the two tasks was counterbalanced within each participant. The accuracy of the peripheral object task was $67.3\% \pm 5.1\%$.

MEG data acquisition and preprocessing

The MEG experiment was conducted using a CTF system at the Beijing MRI Center for Brain Research (BMCBR). The data analysis was completed using the MNE Python toolbox[54] and custom codes. The raw data were sampled at 300 Hz and then down sampled to 100 Hz. A bandpass filter between 1 and 30 Hz was applied.

Independent Component Analysis was used to eliminate biological artifacts, including

heartbeat and ocular artifacts. For each trial, the MEG data were baseline-corrected using a

time window from 243 ms to 43 ms before stimulus onset. Trials with instantaneous

distortion were excluded from further analysis, along with their adjacent trials. One

participant did not complete all trials in the foveal task, resulting in approximately 92 trials

per condition.

Source reconstruction

The cortical surface was reconstructed for each individual participant based on the

anatomical T1 data acquired in MRI scan. A boundary element model (BEM) was set up

based on the inner skull boundary extracted via watershed algorithm[55]. To extract the source

space and calculate the forward solution, the coordinate frames were aligned based on

fiducials and digitizer points on the head surface. For each hemisphere, 4098 source points

were generated to build the source space. A regularized noise covariance matrix was

estimated using MEG data from 243 ms to 43 ms before stimulus onset. Source estimates

were obtained using dynamic statistical parametric mapping (dSPM)[20], a linear minimum-

norm inverse method. A Loose value of 0.2 was used when calculating the inverse operator.

The resulting source activations were projected onto the surface normal.

Three ROIs, early visual cortex, occipito-temporal cortex, and posterior-parietal cortex, were

identified using the anatomical labels in the surface reconstructed by Freesurfer (see Figure

3B). The data from the source points within each ROI were extracted for further analyses.

MEG decoding

The decoding analysis employed a neural decoding toolbox (http://www.readout.info)[56] and

custom Python/MATLAB codes. The trials from each condition were randomly divided into

eight splits, and were averaged within each split. Then a cross-validator were created with a

leave-one-split-out procedure, similar to decoding analysis in the fMRI data. The 100 most

informative channels or sources were selected based on the F value across all conditions, and

were further used to train and test decoders.

The above process was repeated 20 times at each time point to estimate the temporal

dynamics of high- and low-order information. In the peripheral task, in addition to training

and testing decoders with data from identical stimulus locations, the decoders were also

trained and tested across different stimulus locations to examine the location invariant visual

representation. The temporal dynamics of decoding performances were smoothed with a

Gaussian kernel with a half width of 100 ms.

Granger causality analysis

The Granger causality analysis was conducted with the Multivariate Granger Causality

(MVGC) toolbox [22,23] using the time courses of visual information represented in each ROI,

which were estimated by the distances from the neural response pattern to the decoding

hyperplane in the high-dimensional spaces of neural responses[21]. The similar training and

testing procedures were applied to the MEG time courses as in the decoding analysis, but the

distance of neural response pattern to the trained hyperplane was calculated at each time

point. A further distance in the correct direction indicated a higher quality of neural

representation at each time point. The distances were normalized by subtracting the mean and

dividing by the standard deviation of trials. Next, autoregressive model was used to examine

whether the quality of the neural representation in the current time in a target region could be

explained by the past representation quality in a source region, beyond the explanation

supplied by the past of the target region itself. The Granger causal influence was defined as

$\ln(U_{reduced}/U_{full})$, where U is the unexplained variance by the model. To create baselines for

statistical comparisons, the MEG data before the stimulus onset (-200 ms to 0 ms) were

extracted and the same autoregressive model was applied to estimate the increase of variance

explanation in the noise background[57]. For each pair of ROIs, we tested both directions of

Granger causality with the all other ROIs serving as regression factors. The analysis was

conducted for each time point using a 150 ms sliding time windows preceding this time point,

and a model order (i.e., the number of time-lags) of 5 (10, 20, 30, 40, 50 ms) was selected. To

enhance visibility, the time courses of the Granger causality influence were smoothed by a

Gaussian kernel with a half width of 50 ms.

Behavioral correlation of neural representation

For each time point in each trial, the distance from the neural response pattern to the

decoding hyperplane was calculated to estimate the quality of neural representation. The

decoding hyperplane was trained with the neural responses of objects presented at the

location set different from the current trial (cross-location decoding). Then for each condition

at each time point, the Pearson correlation coefficient was calculated between the decoding

distances and the behavioral reaction times across trials. Finally, the correlation coefficients

were averaged across all conditions to generate the time course of behavioral correlation of

neural representation for each participant. This procedure was repeated for each brain region.

The positive correlation coefficient meant that the better quality of neural representation

related to a faster reaction. Only the data from correct trials were used to estimate the

behavioral correlation. The trials with reaction time outside two SD were excluded from the

analysis. For correlation calculation in each time point, the neural response patterns that were

incorrected classified with high distance (outside two SD) were excluded. The time courses

of behavioral correlation were smoothed by a Gaussian kernel with a half width of 100 ms.

Significance testing

In the fMRI response analyses, two-tail t-test was used to assess whether the BOLD signal

change was different from baseline. In the decoding analysis, one-tail t-test was used to

examine whether the decoding accuracy exceeded the chance level. There is strong evidence

showing that feedback information is sent to the foveal V1 during a peripheral object task

[10,11,49], and anatomical and functional evidence shows that the superficial and deep layers of

V1 receive feedback information during visual processing. Therefore, we specifically

examined two types of feedback information in the superficial and deep layers of foveal V1,

and did not apply multiple-comparison correction to the decoding results.

For the MEG decoding, since we did not have a strong prior about when feedback

information would arrive in the foveal V1, we used the nonparametric cluster-based

permutation test [58,59] to correct multiple comparisons over time. For each time point, the sign

of the effect (i.e., decoding accuracy vs. chance, Granger causality influence vs. baseline,

behavioral correlation vs. zeros) was randomly flipped in each participant for 50000 times to

get the null hypothesis distribution. Then the cluster-based permutation test was performed,

where clusters were defined as continuous significant time points in the time-series. The

effects in each cluster were summed and the most significant of them in the time-series was

used to generated the corrected null hypotheses distribution.

Data availability statement

All preprocessed data and code in this study have been uploaded to figshare

https://doi.org/10.6084/m9.figshare.25991362.v1 .

Raw data has not been deposited in a public repository due to file size, but is available upon

request.

Acknowledgements

This work was supported by the National Key Research and Development Program of China

(Grant Nos. 2021ZD0204200, 2021ZD0203800 and 2022ZD0211900); Key Research

Program of Frontier Sciences, Chinese Academy of Sciences (Grant No. KJZD-SW-L08);

and CAS Project for Young Scientists in Basic Research (Grant No. YSBR-071). The authors

would like to thank Dr. Peng Zhang and Dr. Chencan Qian for their help during data

collection and analysis.

Author contributions

W.H., S.H., and J.Z. conceived the project and designed the experiments. W.H. and J.Z.

performed the experiments. W.H. and J.Z. developed the analysis pipeline and analyzed the

data. W.H., S.H., and J.Z. wrote the manuscript.

Declaration of interests

The authors declare no competing interests.

681
682

Reference:

1. Felleman, D.J., and Van Essen, D.C. (1991). Distributed hierarchical processing in the primate cerebral cortex. Cereb Cortex *1*, 1–47.

2. Lamme, V.A., Supèr, H., and Spekreijse, H. (1998). Feedforward, horizontal, and feedback processing in the visual cortex. Curr. Opin. Neurobiol. *8*, 529–535. https://doi.org/10.1016/s0959-4388(98)80042-1.

3. Kreiman, G., and Serre, T. (2020). Beyond the feedforward sweep: feedback computations in the visual cortex. Ann. N. Y. Acad. Sci. *1464*, 222–241. https://doi.org/10.1111/nyas.14320.

4. Kar, K., and DiCarlo, J. (2021). Fast Recurrent Processing via Ventrolateral Prefrontal Cortex Is Needed by the Primate Ventral Stream for Robust Core Visual Object Recognition. Neuron *109*, 164-176.e5. https://doi.org/10.1016/j.neuron.2020.09.035.

5. Hubel, D.H., and Wiesel, T.N. (1977). Ferrier lecture. Functional architecture of macaque monkey visual cortex. Proc. R. Soc. Lond. B Biol. Sci. *198*, 1–59. https://doi.org/10.1098/rspb.1977.0085.

6. Desimone, R., Albright, T.D., Gross, C.G., and Bruce, C. (1984). Stimulus-selective properties of inferior temporal neurons in the macaque. J Neurosci *4*, 2051–2062.

7. Bao, P., She, L., McGill, M., and Tsao, D.Y. (2020). A map of object space in primate inferotemporal cortex. Nature *583*, 103–108. https://doi.org/10.1038/s41586-020-2350-5.

8. Rao, R.P.N., and Ballard, D.H. (1999). Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. Nat. Neurosci. *2*, 79–87. https://doi.org/10.1038/4580.

9. Friston, K. (2005). A theory of cortical responses. Philos. Trans. R. Soc. Lond. B. Biol. Sci. *360*, 815–836. https://doi.org/10.1098/rstb.2005.1622.

10. Williams, M.A., Baker, C.I., Op De Beeck, H.P., Mok Shim, W., Dang, S., Triantafyllou, C., and Kanwisher, N. (2008). Feedback of visual object information to foveal retinotopic cortex. Nat. Neurosci. *11*, 1439–1445. https://doi.org/10.1038/nn.2218.

11. Fan, X., Wang, L., Shao, H., Kersten, D., and He, S. (2016). Temporally flexible feedback signal to foveal cortex for peripheral object recognition. Proc. Natl. Acad. Sci. *113*, 11627–11632. https://doi.org/10.1073/pnas.1606137113.

12. Morgan, A.T., Petro, L.S., and Muckli, L. (2019). Scene Representations Conveyed by Cortical Feedback to Early Visual Cortex Can Be Described by Line Drawings. J. Neurosci. *39*, 9410–9423. https://doi.org/10.1523/JNEUROSCI.0852-19.2019.

13. Harris, K.D., and Mrsic-Flogel, T.D. (2013). Cortical connectivity and sensory coding. Nature *503*, 51–58. https://doi.org/10.1038/nature12654.

14. Rockland, K.S., and Pandya, D.N. (1979). Laminar origins and terminations of cortical
connections of the occipital lobe in the rhesus monkey. Brain Res. *179*, 3–20.
https://doi.org/10.1016/0006-8993(79)90485-2.

15. Wong-Riley, M. (1978). Reciprocal connections between striate and prestriate cortex in
squirrel monkey as demonstrated by combined peroxidase histochemistry and
autoradiography. Brain Res. *147*, 159–164. https://doi.org/10.1016/0006-
8993(78)90781-3.

16. Wyatte, D., Jilk, D.J., and O'Reilly, R.C. (2014). Early recurrent feedback facilitates visual
object recognition under challenging conditions. Front. Psychol. *5*.
https://doi.org/10.3389/fpsyg.2014.00674.

17. Gilbert, C.D., and Li, W. (2013). Top-down influences on visual processing. Nat. Rev.
Neurosci. *14*, 350–363. https://doi.org/10.1038/nrn3476.

18. Grill-Spector, K., Kourtzi, Z., and Kanwisher, N. (2001). The lateral occipital complex and
its role in object recognition. Vision Res. *41*, 1409–1422. https://doi.org/10.1016/S0042-
6989(01)00073-6.

19. Kastner, S., Chen, Q., Jeong, S.K., and Mruczek, R.E.B. (2017). A brief comparative review
of primate posterior parietal cortex: A novel hypothesis on the human toolmaker.
Neuropsychologia *105*, 123–134.
https://doi.org/10.1016/j.neuropsychologia.2017.01.034.

20. Dale, A.M., Liu, A.K., Fischl, B.R., Buckner, R.L., Belliveau, J.W., Lewine, J.D., and Halgren,
E. (2000). Dynamic Statistical Parametric Mapping: Combining fMRI and MEG for High-
Resolution Imaging of Cortical Activity. Neuron *26*, 55–67.
https://doi.org/10.1016/S0896-6273(00)81138-1.

21. Jia, K., Zamboni, E., Kemper, V., Rua, C., Goncalves, N.R., Ng, A.K.T., Rodgers, C.T.,
Williams, G., Goebel, R., and Kourtzi, Z. (2020). Recurrent Processing Drives Perceptual
Plasticity. Curr. Biol. *30*, 4177-4187.e4. https://doi.org/10.1016/j.cub.2020.08.016.

22. Seth, A.K. (2010). A MATLAB toolbox for Granger causal connectivity analysis. J.
Neurosci. Methods *186*, 262–273. https://doi.org/10.1016/j.jneumeth.2009.11.020.

23. Barnett, L., and Seth, A.K. (2014). The MVGC multivariate Granger causality toolbox: A
new approach to Granger-causal inference. J. Neurosci. Methods *223*, 50–68.
https://doi.org/10.1016/j.jneumeth.2013.10.018.

24. Keller, A.J., Roth, M.M., and Scanziani, M. (2020). Feedback generates a second
receptive field in neurons of the visual cortex. Nature *582*, 545–549.
https://doi.org/10.1038/s41586-020-2319-4.

25. Kirchberger, L., Mukherjee, S., Self, M.W., and Roelfsema, P.R. (2023). Contextual drive
of neuronal responses in mouse V1 in the absence of feedforward input. Sci. Adv. *9*,
eadd2498. https://doi.org/10.1126/sciadv.add2498.

26. Shipp, S. (2007). Structure and function of the cerebral cortex. Curr. Biol. *17*, R443–
R449. https://doi.org/10.1016/j.cub.2007.03.044.

27. Schuman, B., Dellal, S., Prönneke, A., Machold, R., and Rudy, B. (2021). Neocortical Layer
1: An Elegant Solution to Top-Down and Bottom-Up Integration. Annu. Rev. Neurosci.
44, 221–252. https://doi.org/10.1146/annurev-neuro-100520-012117.

28. Aitken, F., Menelaou, G., Warrington, O., Koolschijn, R.S., Corbin, N., Callaghan, M.F.,
and Kok, P. (2020). Prior expectations evoke stimulus-specific activity in the deep layers
of the primary visual cortex. PLOS Biol. *18*, e3001023.
https://doi.org/10.1371/journal.pbio.3001023.

29. Kok, P., Bains, L.J., van Mourik, T., Norris, D.G., and de Lange, F.P. (2016). Selective
Activation of the Deep Layers of the Human Primary Visual Cortex by Top-Down
Feedback. Curr. Biol. *26*, 371–376. https://doi.org/10.1016/j.cub.2015.12.038.

30. Liu, C., Guo, F., Qian, C., Zhang, Z., Sun, K., Wang, D.J., He, S., and Zhang, P. (2021).
Layer-dependent multiplicative effects of spatial attention on contrast responses in
human early visual cortex. Prog. Neurobiol. *207*, 101897.
https://doi.org/10.1016/j.pneurobio.2020.101897.

31. van Kerkoerle, T., Self, M.W., and Roelfsema, P.R. (2017). Layer-specificity in the effects
of attention and working memory on activity in primary visual cortex. Nat. Commun. *8*,
13804. https://doi.org/10.1038/ncomms13804.

32. Lawrence, S.J., Norris, D.G., and de Lange, F.P. (2019). Dissociable laminar profiles of
concurrent bottom-up and top-down modulation in the human visual cortex. eLife *8*,
e44422. https://doi.org/10.7554/eLife.44422.

33. Lawrence, S.J.D., Van Mourik, T., Kok, P., Koopmans, P.J., Norris, D.G., and De Lange, F.P.
(2018). Laminar Organization of Working Memory Signals in Human Visual Cortex. Curr.
Biol. *28*, 3435-3440.e4. https://doi.org/10.1016/j.cub.2018.08.043.

34. Bergmann, J., Petro, L.S., Abbatecola, C., Li, M.S., Morgan, A.T., and Muckli, L. (2024).
Cortical depth profiles in primary visual cortex for illusory and imaginary experiences.
Nat. Commun. *15*, 1002. https://doi.org/10.1038/s41467-024-45065-w.

35. Iamshchinina, P., Kaiser, D., Yakupov, R., Haenelt, D., Sciarra, A., Mattern, H.,
Luesebrink, F., Duezel, E., Speck, O., Weiskopf, N., et al. (2021). Perceived and mentally
rotated contents are differentially represented in cortical depth of V1. Commun. Biol. *4*,
1069. https://doi.org/10.1038/s42003-021-02582-4.

36. Victor, J.D., Mechler, F., Repucci, M.A., Purpura, K.P., and Sharpee, T. (2006). Responses
of V1 neurons to two-dimensional hermite functions. J. Neurophysiol. *95*, 379–400.
https://doi.org/10.1152/jn.00498.2005.

37. Vinje, W.E., and Gallant, J.L. (2000). Sparse Coding and Decorrelation in Primary Visual
Cortex During Natural Vision. Science *287*, 1273–1276.
https://doi.org/10.1126/science.287.5456.1273.

38. Tang, S., Lee, T.S., Li, M., Zhang, Y., Xu, Y., Liu, F., Teo, B., and Jiang, H. (2018). Complex
Pattern Selectivity in Macaque Primary Visual Cortex Revealed by Large-Scale Two-
Photon Imaging. Curr. Biol. *28*, 38-48.e3. https://doi.org/10.1016/j.cub.2017.11.039.

39. Tang, S., Zhang, Y., Li, Z., Li, M., Liu, F., Jiang, H., and Lee, T.S. (2018). Large-scale two-
photon imaging revealed super-sparse population codes in the V1 superficial layer of
awake monkeys. eLife *7*, e33370. https://doi.org/10.7554/eLife.33370.

40. Ge, Y., Zhou, H., Qian, C., Zhang, P., Wang, L., and He, S. (2020). Adaptation to feedback
representation of illusory orientation produced from flash grab effect. Nat. Commun.
11, 3925. https://doi.org/10.1038/s41467-020-17786-1.

41. Chambers, C.D., Allen, C.P.G., Maizey, L., and Williams, M.A. (2013). Is delayed foveal
feedback critical for extra-foveal perception? Cortex *49*, 327–335.
https://doi.org/10.1016/j.cortex.2012.03.007.

42. VanRullen, R., and Thorpe, S.J. (2001). The time course of visual processing: from early
perception to decision-making. J. Cogn. Neurosci. *13*, 454–461.
https://doi.org/10.1162/08989290152001880.

43. Kovacs, G., Vogels, R., and Orban, G. (1995). Selectivity of macaque inferior temporal
neurons for partially occluded shapes. J. Neurosci. *15*, 1984–1997.
https://doi.org/10.1523/JNEUROSCI.15-03-01984.1995.

44. Nielsen, K.J., Logothetis, N.K., and Rainer, G. (2006). Dissociation Between Local Field
Potentials and Spiking Activity in Macaque Inferior Temporal Cortex Reveals
Diagnosticity-Based Encoding of Complex Objects. J. Neurosci. *26*, 9639–9645.
https://doi.org/10.1523/JNEUROSCI.2273-06.2006.

45. Zhaoping, L. (2024). Peripheral vision is mainly for looking rather than seeing. Neurosci.
Res. *201*, 18–26. https://doi.org/10.1016/j.neures.2023.11.006.

46. Carricarte, T., Iamshchinina, P., Trampel, R., Chaimow, D., Weiskopf, N., and Cichy, R.M.
(2024). Laminar dissociation of feedforward and feedback in high-level ventral visual
cortex during imagery and perception. iScience *27*, 110229.
https://doi.org/10.1016/j.isci.2024.110229.

47. Degutis, J.K., Chaimow, D., Haenelt, D., Assem, M., Duncan, J., Haynes, J.-D., Weiskopf,
N., and Lorenz, R. (2024). Dynamic layer-specific processing in the prefrontal cortex
during working memory. Commun. Biol. *7*, 1140. https://doi.org/10.1038/s42003-024-
06780-8.

48. Finn, E.S., Huber, L., Jangraw, D.C., Molfese, P.J., and Bandettini, P.A. (2019). Layer-
dependent activity in human prefrontal cortex during working memory. Nat. Neurosci.
22, 1687–1695. https://doi.org/10.1038/s41593-019-0487-z.

49. Yu, Q., and Shim, W.M. (2016). Modulating foveal representation can influence visual
discrimination in the periphery. J. Vis. *16*, 15. https://doi.org/10.1167/16.3.15.

50. Fischl, B. (2012). FreeSurfer. NeuroImage *62*, 774–781.
https://doi.org/10.1016/j.neuroimage.2012.01.021.

51. Cox, R.W. (1996). AFNI: Software for Analysis and Visualization of Functional Magnetic
Resonance Neuroimages. Comput. Biomed. Res. *29*, 162–173.
https://doi.org/10.1006/cbmr.1996.0014.

52. Kay, K., Jamison, K.W., Vizioli, L., Zhang, R., Margalit, E., and Ugurbil, K. (2019). A critical
assessment of data quality and venous effects in sub-millimeter fMRI. NeuroImage *189*,
847–869. https://doi.org/10.1016/j.neuroimage.2019.02.006.

53. Chang, C.-C., and Lin, C.-J. (2011). LIBSVM: A library for support vector machines. ACM
Trans. Intell. Syst. Technol. *2*, 1–27. https://doi.org/10.1145/1961189.1961199.

54. Gramfort, A. (2013). MEG and EEG data analysis with MNE-Python. Front. Neurosci. *7*.
https://doi.org/10.3389/fnins.2013.00267.

55. Ségonne, F., Dale, A.M., Busa, E., Glessner, M., Salat, D., Hahn, H.K., and Fischl, B.
(2004). A hybrid approach to the skull stripping problem in MRI. NeuroImage *22*, 1060–
1075. https://doi.org/10.1016/j.neuroimage.2004.03.032.

56. Meyers, E.M. (2013). The neural decoding toolbox. Front. Neuroinformatics *7*.
https://doi.org/10.3389/fninf.2013.00008.

57. Kietzmann, T.C., Spoerer, C.J., Sörensen, L.K.A., Cichy, R.M., Hauk, O., and Kriegeskorte,
N. (2019). Recurrence is required to capture the representational dynamics of the
human visual system. Proc. Natl. Acad. Sci. *116*, 21854–21863.
https://doi.org/10.1073/pnas.1905544116.

58. Maris, E., and Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-
data. J. Neurosci. Methods *164*, 177–190.
https://doi.org/10.1016/j.jneumeth.2007.03.024.

59. Spaak, E. (2024). Cluster Test: Simple cluster-based permutation testing in arbitrary
dimensions. https://doi.org/10.5281/zenodo.10877825
https://doi.org/10.5281/zenodo.10877825.

Supplementary:

Figure S1: Activation maps of the foveal stimulus and the sizes of the foveal V1 ROI in two example

participants. (A) Voxels showing stronger fMRI responses to the foveal checkerboard than to the

peripheral checkerboard. (B) Voxels showing stronger fMRI responses to foveal objects than to the

baseline. Blue solid lines indicate the spatial range of the foveal V1 ROI for each participant.

Figure S2: Fine-scale laminar profiles of orientation and category information in foveal V1 in

peripheral object task. Significant category information was found in the deep and superficial layers

(ts>1.94, ps<0.035), and significant orientation information was found in the deep layers (ts>2.26,

ps<0.019), but no significant difference was observed between two types of information (ts<0.61,

ps>0.55).

Figure S3. Latency for category (**A**) and orientation (**B**) information in three cortical regions during peripheral object recognition task. Time courses of decoding accuracy were smoothed with a Gaussian kernel with a half-width of 150 ms, and latency was estimated as the time from stimulus onset to 75% of peak decoding performance. When calculating the group mean of latency, data exceeding 2 SD were excluded. The latency of cross-location decoding for category information was significantly longer in early visual cortex than in occipito-temporal cortex ($t(11)=2.86$, $p=0.03$), and the effect was marginally significant for orientation information ($t(12)=2.52$, $p=0.06$), indicating the decoding performances were driven by feedback signals. In same-location decoding, the latency of category information was similar between early visual cortex and occipito-temporal cortex, and the latency of orientation information is much shorter in early visual cortex ($t(13)=4.01$, $p=0.001$). * indicates paired t-test with significance of $p< 0.05$. ** indicates paired t-test with significance of $p< 0.01$. † indicates marginal significance (Holm-Bonferroni corrected).