AnnSQL: A Python SQL-based package for large-scale single-cell genomics analysis on a laptop

Authors

Kenny Pavan[1,2] and Arpiar Saunders[1#]

Affiliations

1. Vollum Institute, Oregon Health & Science University, Portland, OR, 97239, USA
2. Biomedical Engineering Graduate Program, Oregon Health and Science University, Portland, OR, 97239, USA

[#] Correspondence: saundear@ohsu.edu

Abstract

As single-cell genomics technologies continue to accelerate biological discovery, software tools that use elegant syntax and minimal computational resources to analyze atlas-scale datasets are increasingly needed. Here we introduce AnnSQL, a Python package that constructs an AnnData-inspired database using the in-process DuckDb engine, enabling orders-of-magnitude performance enhancements for parsing single-cell genomics datasets with the ease of SQL. We highlight AnnSQL functionality and demonstrate transformative runtime improvements by comparing AnnData or AnnSQL operations on a 4.4 million cell single-nucleus RNA-seq dataset: AnnSQL-based operations were executed in minutes on a laptop for which equivalent AnnData operations largely failed (or were ~700x slower) on a high-performance computing cluster. AnnSQL lowers computational barriers for large-scale single-cell/nucleus RNA-seq analysis on a personal computer, while demonstrating a promising computational infrastructure extendable for complete single-cell workflows across various genome-wide measurements.

Availability and Implementation

AnnSQL is a pip installable package that can be accessed with usage documentation at: https://github.com/ArpiarSaundersLab/annsql.

1. Introduction

Single-cell genomics technologies have emerged as transformative tools for discovering genome-wide RNA and chromatin landscapes of complex tissue at single-cell resolution in health and disease (Wen et al., 2022; Nayak & Hasija, 2021; Heumos et al., 2023). Popular software tools have converged on data structures that facilitate storage, preprocessing and myriad downstream analyses by prioritizing organizational clarity at the cost of computational performance. For example, Scanpy (Wolf et al., 2018) and the Scverse ecosystem (Virshup et al., 2023) use AnnData, while Seurat (Butler et al., 2018), uses Seurat objects. Now routine, "atlas-scale" descriptions of millions of cells based on tens of thousands to millions of genomics features strain software tools that use hierarchical structures (like AnnData) and often require high-performance computing clusters to execute. We were inspired to create AnnSQL for simple analysis of large datasets because in other contexts, SQL databases are a popular storage choice due to high transactional speed of row-oriented storage formats (Plattner, 2009) and because no other SQL-based single-cell genomics analysis packages currently exist.

H5 hierarchical objects like AnnData have become standard storage for single-cell genomics software development in recent years (The HDF Group, 2020/2024). AnnData provides a convenient and compact structure for storing, organizing and analyzing high-dimensional datasets. Applications can load AnnData entirely into system memory or, for large datasets, stream AnnData from disk using the "backed mode" parameter. Although AnnData allows faster statistical operations than traditional row-oriented databases, the backed mode often lacks support for aggregate functions.

Advances in SQL databases present new opportunities for single-cell genomics applications. Traditional SQL databases are limited because they often require technical knowledge for configuring and running databases as a background system process that requires connection to the service via the application, adding complexity that restricts the ease of data exploration. As an alternative, SQLite (Gaffney et al., 2022) operates in-process by creating a file-based database capable of direct application access yet a reliance on row-oriented transactions can restrict performance on statistical operations. To enable high-performance statistical functions and in-process queries, DuckDb (Raasveldt & Mühleisen, 2019) was implemented as a column-based storage engine that operates using chunked vectors of column data. Strict in-process operation allows DuckDb data to be stored in a file and accessed in a memory-efficient manner using SQL via the Python API. These features nominate DuckDb as a powerful storage and processing engine for cell by genomic features matrices.

We developed AnnSQL to bridge the gap between AnnData objects and SQL databases for single-cell genomics analysis. AnnSQL converts each layer of the AnnData hierarchical object into an equivalent SQL table, using the Python DuckDb API. AnnSQL supports both in-memory and backed modes of AnnData, enabling larger than memory databases to be built with minimal computational resources. AnnSQL-instantiated datasets can be fluidly queried using SQL syntax, allowing aggregate and statistical functions to be performed on larger than memory datasets with exceptionally fast run times.

2. Results

2.1 Package Capabilities

The AnnSQL package enables SQL-based queries on AnnData objects, returning results as either an AnnData object, Pandas dataframe (McKinney, 2010), or Parquet file (Vohra, 2016), thus seamlessly supporting a variety of downstream analysis tools or pipelines. Functionally, AnnSQL captures the AnnData hierarchical H5 data structure and represents the data in a relational database using the in-process DuckDb engine (**Figure 1A**). AnnSQL supports in-memory and on-disk database representations, useful for smaller or larger datasets, respectively. AnnSQL databases are built using the *MakeDb* class that supports AnnData inputs from both backed and non-backed modes. Once a database has been created and instantiated using the AnnSQL class (**Figure 1B, 1C**), the AnnSQL package provides methods for querying, updating, and deleting cell or genome-feature data, as well as extended functionality to perform common single-cell manipulations or analyses, such as normalization, log transforms, determining library or gene counts and calculating feature variance.

Figure 1. A) AnnSQL workflow. AnnSQL converts AnnData objects using DuckDB to enable high-performance SQL queries. B) Basic usage example using the pbmc68k reduced dataset provided with Scanpy. C) The ERD of the database generated from the pbmc68k reduced dataset. D) Runtime comparisons of six queries and filters (**Figure S1A**) for AnnSQL and AnnData (backed and non-backed modes displayed as on-disk and in-memory, respectively).

2.2 Runtime Estimates

To systematically compare runtime differences across AnnData filters and AnnSQL queries, we generated six increasing complex queries of synthetic scRNA-seq data and stratified our analysis by in-memory or on-disk modes for each method (**Figure 1D** and **S1A**)(**Methods**). In-memory comparisons trials ranged from 1,000 to 100,000 cells before reaching system memory limits, while on-disk trials ranged from 1,000 to 250,000 cells. Critically, AnnSQL runtimes were essentially unchanged across the full range library sizes tested for both in-memory and on-disk.

On-disk AnnData outperformed on-disk AnnSQL only for libraries < 5,000 cells, while queries of
250,000 cells were on average ~400 times faster using AnnSQL (0.14 versus 57 seconds). In-
memory AnnData outperformed in-memory AnnSQL only for libraries with < 45,000 cells and both
methods achieved <0.01 second runtimes with <75,000 cell libraries. These comparative runtime
metrics illustrate the drastic speed improvements and size-scalability of AnnSQL processing of
large scRNA-seq datasets.
139
2.3 Use Case: Querying and processing 4.4 million cells on a laptop.
To illustrate AnnSQL runtime improvements, we analyzed a single nucleus RNA-seq atlas of the
mouse containing 4.4 million cells and annotations (Langlieb et al., 2023). First, we opened the
atlas AnnData object in backed mode and created an on-disk AnnSQL database using the
MakeDb class (**Methods**). Next, we performed routine procedures (cell filtering, summing library
feature counts, cell-count normalization and cell-count log transformation) using either the original
AnnData object (in-memory or on-disk/backed mode) or on-disk AnnSQL (using methods
provided in our package) on both a laptop and a High Performance Cluster (HPC) (**Table 1** and
Methods). For all procedures other than filtering, AnnData analysis failed on both the laptop or
HPC due to a lack of support for backed-mode or memory errors. Equivalent procedures using
AnnSQL completed between
~4.5-108 minutes on a laptop and
were 37-64% faster than on the
HPC. While backed-mode (but
not in-memory) filtering could be
accomplished on a laptop using
AnnData, this procedure was
~680x faster using AnnSQL. The
HPC did enable filtering using in-
memory AnnData, but was still
~18x faster on a laptop with
AnnSQL. These data illustrate
how AnnSQL performance
enhancements allow users to
access and manipulate atlas-
scale scRNA-seq data from their
personal computer with ease.

Procedure	Approach	Runtime Laptop (sec)	Runtime HPC (sec)
Filtering	AnnSQL	0.24	1.03
	AnnData (Backed)	163.17	391.97
	AnnData (Memory)	*Memory Error*	4.36
Total Library Counts	AnnSQL	270	470
	AnnData (Backed)	*Not Supported*	*Not Supported*
	AnnData (Memory)	*Memory Error*	*Memory Error*
Normalize Expression	AnnSQL	6480	10251
	AnnData (Backed)	*Not Supported*	*Not Supported*
	AnnData (Memory)	*Memory Error*	*Memory Error*
Log Transform	AnnSQL	3553	9878
	AnnData (Backed)	*Not Supported*	*Not Supported*
	AnnData (Memory)	*Memory Error*	*Memory Error*

Table 1: Runtimes of processing an AnnData object containing 4.4 million cells opened in backed mode and in-memory vs. on-disk AnnSQL. Scanpy preprocessing functions were used for AnnData, while AnnSQL extended functionality methods were used for the AnnSQL database.

167
3. Methods
3.1 Package Software Structure
AnnSQL was built as an object-oriented Python package that parses the layer structure of typical
AnnData objects into SQL tables (**Figure 1C**) and provides flexible parameters. All functionality
presented in AnnSQL, exists in 3 classes: (1) The *BuildDb* class is used to construct both in-
memory and on-disk databases using the DuckDb Python client API. (2) The *MakeDb* class can
be instantiated to create an on-disk database from a properly formatted AnnData object and
stored with the ".asql" file extension. (3) The class *AnnSQL* is the main access point to instantiate

and interrogate a dataset. The package has methods for queries, allows multiple return types,
and contains extended functionality to help with data preprocessing.
178
3.2 Database Construction
Each layer in a common single-cell AnnData object is a parameter in the AnnSQL and *MakeDb*
classes. Both classes make calls to the *BuildDb* class to construct a relational database with the
AnnData layers determined by the user (*X*, *obs*, *var*, *var_names*, *obsm*, *varm*, *obsp*, and *uns*). *X*
is created as a table where each gene is a column cast as a FLOAT with the addition of a "cell_id"
column to contain the cell barcode. The *obs* table structure is composed of columns for the
"cell_id" and each *obs* property. The *var* table contains the vertical layer associated with the
AnnData object where the auto incremented id represents the gene and each column represents
var layer properties. Each *obsm*, *varm*, and *obsp* layer property is composed of a different data
type or structure. To convert layers to SQL tables, we created a new table for each layer property.
For example, the X_pca property of the *obsm* layer is translated into the table, "obsm_X_pca"
containing the cell by PCA matrix. Lastly, the *uns* AnnData layer is serialized and inserted into
the "*uns_raw*" table. This table contains the property name defined by the key column, a serialized
data value column, and the original data_type column, such that the data can be reconstructed.
Lastly, a convenience view "*adata*" is created by joining the obs and X table. Developers can
optionally bypass the view creation by using the "*convenience_view*" boolean parameter. Lastly,
special characters in gene names or other table columns are stripped of non-sql safe characters
and replaced with underscores.
197
3.3 Database Query Wrapper
The AnnSQL class contains several methods for updates, deletes, and queries. The class
requires either a path to a previously built AnnSQL database or an AnnData object to load into
memory. After instantiation, the *query* method interfaces with the database to return a pandas
dataframe (default), AnnData, or Parquet file. The *query_raw* method opens a db connection and
executes a SQL statement. Additionally, the methods *show_settings* and *show_tables* exist for
convenience.
205
3.4 Extended Functionality
AnnSQL contains functionality for basic preprocessing as methods within the AnnSQL class which
include: Total counts per library, counts per gene, data normalization, log transformations, and
gene expression variance calculation. To accomplish data total counts per library,
calculate_total_counts iterates cells in chunks and adds the "total_counts" column to the *X*, then
obs table. Calculating total gene counts is accomplished in the **calculate_gene_counts** method
by adding a "total_gene_counts" column to the *var* table and using the internal SUM function. The
expression_normalize method updates the *X* table in chunks by dividing gene counts by
"total_counts" then multiplying by the normalized value (default: 10^4). The **expression_log**
method updates all values in the *X* table with the user defined ln, log2 or log10 parameter options.
Lastly, **calculate_variable_genes** uses the population variance function in DuckDb to calculate
gene-specific expression and stores the result in the "variance" column of the *var* table. In chunk
parameters, gene sample variance is calculated including Bessel's bias correction.
219

3.5 Runtime Analyses

Runtime tests were performed on simulated and Mouse Brain Atlas data (Langlieb et al., 2023). Simulated Anndata objects contained random expression values and saved as h5ad files and ranging from 1,000 to 250,000 cells. Each file contained 10,000 genes and an *obs* layer with random cell type assignments. File queries and filters were compared (**Figure S1A)** and generated the runtime results (**Figure 1D)**.

The Mouse Brain dataset was converted into an on-disk AnnSQL database using the *MakeDb* class, then queried and processed as described in **Table 1**. Filters are as follows:

AnnData

adata[adata[:, "ENSMUSG00000070880"].X > 0, "ENSMUSG00000070880"]

AnnSQL

adata.sql.query("SELECT ENSMUSG00000070880 FROM X WHERE ENSMUSG00000070880 > 0")

Runtime analyses were performed on an Ubuntu 24.04 laptop, containing 40Gb memory, 1Tb SSD Drive and a 12th Gen Intel® Core™ i7-1255U×12 CPU or a HPC single node containing 46 CPUS (Intel® Xeon® Gold 6542Y), 512Gb memory and high-performance storage. Runtime scripts are in the "examples/analyses" repository.

4. Discussion

Here, we introduce AnnSQL for analysis of single-cell genomics data using SQL syntax and showcase query and preprocessing performance using large datasets with minimal computational resources. AnnSQL uses the in-process DuckDb engine and provides extended functionality to showcase how vectorized queries of the column-based storage engine benefit single-cell genomics applications. In future releases, extended functionality methods can be further improved by utilizing DuckDb user-defined functions. Additionally, the DuckDb client API supports programming languages popular in genomics research and development (including Java, R, C++, Julia, and cmd libraries).

AnnSQL runtime comparisons highlight impressive performance improvements achieved that help democratize access to large-scale single-cell RNA-seq data, enabling laptop-based analysis of millions of cells datasets in minutes. The ease and clarity of SQL syntax, along with Python-based wrapper functions, further lowers the analysis barriers. We do note that for small-scale datasets (<30,000 cells), AnnData slightly outperforms AnnSQL operations, but minor differences in runtime might be tolerated if users prefer SQL-based data access.

In developing AnnSQL, we intentionally mirrored the AnnData layered structure for interpretability. While an ideal H5 based structure, AnnData is a non-optimal structure for a relational database (Codd, 1970). Future work converting AnnData objects into an optimized normal formed database may further decrease runtimes (Kent, 1983).

While the use of SQL for single-cell genomics data storage and analysis has yet to be extensively explored, our results indicate that SQL-based databases may be increasingly valuable as

datasets continue to grow. We suspect this lack of attention was due to either the technical knowledge necessary for database configuration or the resources necessary to process a cell by genomic feature matrix in a typical implementation (such as SQLite or MySql (*MySQL*, n.d.)). Our AnnSQL results suggest column-based SQL approaches for filtering or processing single-cell data should be considered when (1) fluid SQL syntax is preferred; (2) dataset size exceeds system memory; or (3) when minimal computational resources are desired for exploring large datasets without downsampling.

Conflict of Interests

Authors declare no conflicts of interest.

Author Contributions

Conceptualization (KP); Data Curation (KP); Formal Analysis (KP); Funding acquisition (AS); Investigation (KP); Methodology (KP, AS); Project Administration (AS); Resources (KP, AS); Software (KP); Supervision (AS); Validation (KP); Visualization (KP); Writing – original draft (KP); Writing – review & editing (KP, AS).

Acknowledgements

The authors thank Connor Frankston, Zach Goode, Dr. Guanming Wu, Dr. Lamya Ben Ameur in addition to the members of the Saunders lab, Andrew Adey lab, and Brian O'Roak lab for helpful advice and/or discussions, as well as Theresa Provitola for design assistance with the AnnSQL logo.

Funding

This work has been supported by the NIH Brain Initiative (R01 MH130464); Sloan Foundation, and Simons Foundation Autism Research Initiative.

References

Butler, A., Hoffman, P., Smibert, P., Papalexi, E., & Satija, R. (2018). Integrating single-cell transcriptomic data across different conditions, technologies, and species. *Nature Biotechnology*, *36*(5), 411–420. https://doi.org/10.1038/nbt.4096

Codd, E. F. (1970). A relational model of data for large shared data banks. *Communications of the ACM*, *13*(6), 377–387. https://doi.org/10.1145/362384.362685

Gaffney, K. P., Prammer, M., Brasfield, L., Hipp, D. R., Kennedy, D., & Patel, J. M. (2022). SQLite: Past, present, and future. *Proc. VLDB Endow.*, *15*(12), 3535–3547. https://doi.org/10.14778/3554821.3554842

Heumos, L., Schaar, A. C., Lance, C., Litinetskaya, A., Drost, F., Zappia, L., Lücken, M. D., Strobl, D. C., Henao, J., Curion, F., Schiller, H. B., & Theis, F. J. (2023). Best practices for single-cell analysis across modalities. *Nature Reviews Genetics*, 1–23. https://doi.org/10.1038/s41576-023-00586-w

Kent, W. (1983). A simple guide to five normal forms in relational database theory. *Communications of the ACM*, *26*(2), 120–125. https://doi.org/10.1145/358024.358054

Langlieb, J., Sachdev, N. S., Balderrama, K. S., Nadaf, N. M., Raj, M., Murray, E., Webber, J. T., Vanderburg, C., Gazestani, V., Tward, D., Mezias, C., Li, X., Flowers, K., Cable, D. M.,

Norton, T., Mitra, P., Chen, F., & Macosko, E. Z. (2023). The molecular cytoarchitecture of the adult mouse brain. *Nature*, *624*(7991), 333–342. https://doi.org/10.1038/s41586-023-06818-7

McKinney, W. (2010). *Data Structures for Statistical Computing in Python*. 56–61. https://doi.org/10.25080/Majora-92bf1922-00a

MySQL. (n.d.). MySQL. Oracle Corporation. Retrieved October 16, 2024, from https://www.mysql.com/

Nayak, R., & Hasija, Y. (2021). A hitchhiker's guide to single-cell transcriptomics and data analysis pipelines. *Genomics*, *113*(2), 606–619. https://doi.org/10.1016/j.ygeno.2021.01.007

Plattner, H. (2009). A common database approach for OLTP and OLAP using an in-memory column database. *Proceedings of the 2009 ACM SIGMOD International Conference on Management of Data*, 1–2. https://doi.org/10.1145/1559845.1559846

Raasveldt, M., & Mühleisen, H. (2019). DuckDB: An Embeddable Analytical Database. *Proceedings of the 2019 International Conference on Management of Data*, 1981–1984. https://doi.org/10.1145/3299869.3320212

The HDF Group. (2024). *Hierarchical Data Format, version 5* [C]. https://github.com/HDFGroup/hdf5 (Original work published 2020)

Virshup, I., Bredikhin, D., Heumos, L., Palla, G., Sturm, G., Gayoso, A., Kats, I., Koutrouli, M., Berger, B., Pe'er, D., Regev, A., Teichmann, S. A., Finotello, F., Wolf, F. A., Yosef, N., Stegle, O., & Theis, F. J. (2023). The scverse project provides a computational ecosystem for single-cell omics data analysis. *Nature Biotechnology*, *41*(5), 604–606. https://doi.org/10.1038/s41587-023-01733-8

Virshup, I., Rybakov, S., Theis, F. J., Angerer, P., & Wolf, F. A. (2024). anndata: Access and store annotated data matrices. *Journal of Open Source Software*, *9*(101), 4371. https://doi.org/10.21105/joss.04371

Vohra, D. (2016). Apache Parquet. In D. Vohra (Ed.), *Practical Hadoop Ecosystem: A Definitive Guide to Hadoop-Related Frameworks and Tools* (pp. 325–335). Apress. https://doi.org/10.1007/978-1-4842-2199-0_8

Wen, L., Li, G., Huang, T., Geng, W., Pei, H., Yang, J., Zhu, M., Zhang, P., Hou, R., Tian, G., Su, W., Chen, J., Zhang, D., Zhu, P., Zhang, W., Zhang, X., Zhang, N., Zhao, Y., Cao, X., … Chen, Z.-J. (2022). Single-cell technologies: From research to application. *The Innovation*, *3*(6). https://doi.org/10.1016/j.xinn.2022.100342

Wolf, F. A., Angerer, P., & Theis, F. J. (2018). SCANPY: Large-scale single-cell gene expression data analysis. *Genome Biology*, *19*(1), 15. https://doi.org/10.1186/s13059-017-1382-0

 Supplemental Figure

Supplemental Figure 1. Runtime comparisons for six equivalent operations (*rows*) performed using AnnData versus AnnSQL (summarized in **Figure 1D**). *Left*, operation-specific calls. *Right*, runtime comparisons for on-disk and in-memory modes.