PLM-interact: extending protein language models to predict protein-protein interactions

Dan Liu[1], Francesca Young[1], Kieran D. Lamb[1], Adalberto Claudio Quiros[2,4], Alexandrina Pancheva[3], Crispin Miller[2,3], Craig Macdonald[4], David L Robertson[1, #], Ke Yuan[2,3,4,#]

[1]MRC-University of Glasgow Centre for Virus Research, Glasgow, United Kingdom;

[2]School of Cancer Sciences, University of Glasgow, Glasgow, United Kingdom;

[3]Cancer Research UK Scotland Institute, Glasgow, United Kingdom;

[4]School of Computing Science, University of Glasgow, Glasgow, United Kingdom.

#Shared senior/corresponding authors: david.l.robertson@glasgow.ac.uk, ke.yuan@glasgow.ac.uk

Abstract

Computational prediction of protein structure from amino acid sequences alone has been achieved with unprecedented accuracy, yet the prediction of protein-protein interactions (PPIs) remains an outstanding challenge. Here we assess the ability of protein language models (PLMs), routinely applied to protein folding, to be retrained for PPI prediction. Existing PPI prediction models that exploit PLMs use a pre-trained PLM feature set, ignoring that the proteins are physically interacting. Our novel method, PLM-interact, goes beyond a single protein, jointly encoding protein pairs to learn their relationships, analogous to the next-sentence prediction task from natural language processing. This approach provides a significant improvement in performance: Trained on human-human PPIs, PLM-interact predicts mouse, fly, worm, *E. coli* and yeast PPIs, with 16-28% improvements in AUPR compared with state-of-the-art PPI models. Additionally, it can detect changes that disrupt or cause PPIs and be applied to virus-host PPI prediction. Our work demonstrates that large language models can be extended to learn the intricate relationships among biomolecules from their sequences alone.

Introduction

Proteins are the main structural components of cells and mediate biological processes by interacting with other proteins[1]. Disruption of these protein-protein interactions (PPIs), e.g., mediated by mutations can underlie human disease[2]. In virology PPIs are particularly important as viruses depend entirely on the host cell for replication, achieved mainly through specific interactions with host proteins. Understanding PPI mechanisms offers the potential

for developing novel therapy strategies for both human disease and pathogen infections[3].

Unfortunately, experimentally identifying PPIs is both costly and time-consuming, such that

interaction datasets remain sparse with only a few species having comprehensive coverage[4,5].

Computational algorithms offer an efficient alternative to the prediction of PPIs at scale.

Existing prediction approaches mainly leverage protein properties such as protein structures,

sequence composition and evolutionary information[6,7,8,9]. Applying these features to pairs

of proteins, classifiers have been trained using classical machine learning[10] and deep

learning approaches[11]. Recently, protein language models (PLMs) trained on large public

protein sequence databases have been used for encoding sequence composition,

evolutionary and structural features[12–14], becoming the method of choice for representing

proteins in state-of-the-art PPI predictors. A typical PPI prediction architecture uses a pre-

trained PLM to represent each protein in a pair separately, then a classification head is

trained for a binary task that discriminates interacting pairs from non-interacting pairs[13,15]

(**Figure 1a**). Despite this use of PLMs, identifying positive PPIs remains challenging.

The main issue is PLMs are primarily trained using single protein sequences, i.e., while they

learn to identify contact points within a single protein[16], they are not 'aware' of interaction

partners. In a conventional PLM-based PPI predictor architecture, a classification head is

used to extrapolate the signals of inter-protein interactions by grouping common patterns of

intra-protein contacts in interacting and non-interacting pairs, respectively (**Figure 1a**). This

strategy relies on the classification head being generalisable. Unfortunately, with a

feedforward neural network being the dominant option, these classifiers often don't

generalise well.

To address the lack of inter-protein context in training, we propose a novel PPI prediction

model, PLM-interact, that directly models PPIs by extending and fine-tuning a pre-trained

PLM, ESM-2[17]. PLM-interact (trained on human PPI data) achieves a significant

improvement compared to other predictors when applied to mouse, fly, worm, yeast and *E.*

coli datasets. We demonstrate that PLM-interact is capable at identifying mutations that

cause and disrupt interactions. We also show PLM-interact's performance in a virus-human

PPI prediction task.

PLM-interact

To directly model PPIs, two extensions to ESM-2 are introduced (**Figure 1b**): (1) longer permissible sequence lengths in paired masked-language training to accommodate amino acid residues from both proteins; (2) implementation of the "next sentence" prediction task[18] to fine-tune ESM-2 where the model is trained with a binary label indicating whether the protein pair is interacting or not (see Methods for more details). Our training task is, thus, a mixture of the next sentence prediction and the mask language modelling tasks. This architecture allows amino acids in a protein to be linked by amino acids from a different protein through transformer's attention mechanism.

Figure 1. A comparison of PLM-interact to the typical existing PPI prediction framework. a. PPI prediction models that use pre-trained protein language models to extract single protein embeddings. Then an interaction classifier is trained use these single protein embeddings. **b.** PLM-interact uses a protein language model with a longer context to handle a pair of protein sequences directly. Both the mask language modelling task and a binary classification task predicting interaction status are used to train the model. (see **Supplementary Figure 1**).

The training of PLM-interact begins with the pre-trained large language model ESM-2. We fine-tune it for PPIs, by showing it pairs of known interacting and non-interacting proteins. In contrast to similar training strategies in machine learning[18], we find the next sentence prediction and mask language modelling objectives need to be balanced. We therefore conducted comprehensive benchmarking for different weighting options, before selecting a 1:10 ratio between classification loss and mask loss, combined with initialisation using the

85 ESM-2 (with 650M parameters), as this achieved the best performance (see Methods and
86 **Supplementary Figure 1).**

PLM-interact improves prediction performance

To examine the performance of PLM-interact, we benchmark the model against five PPI
prediction approaches: TT3D[13], Topsy-Turvy[19], D-SCRIPT[15], PIPR[6] and DeepPPI[20]. We use
a multi-species dataset created by Sledzieski et al.[15]. Each model is trained on human protein
interaction data and tested on five other species. The human training dataset in this multi-
species dataset includes 421,792 protein pairs (38,344 positive interaction pairs and 383,448
negative pairs), human validation includes 52,725 protein pairs (4,794 positive interaction
pairs and 47,931 negative pairs) and the mouse, worm, fly and yeast test datasets each
includes 55,000 pairs (5,000 positives interaction pairs and 50,000 negative pairs), except
for the *E. coli* test dataset, which includes 22,000 pairs (2,000 positive interaction pairs and
20,000 negative pairs). The positive PPIs in these datasets are experimentally-derived
physical interactions, while the negative pairs are randomly paired proteins not reported to
interact.
100
PLM-interact achieves the highest AUPR (area under the precision-recall curve)[23] with the
next best performer, TT3D[13], although similar performance to Topsy-Turvy[19] (**Figure 2b**).
Tested on mouse, fly and worm test species datasets, PLM-interact has an improvement of
16%, 21% and 20% AUPR compared to TT3D[13], respectively. The predictions for yeast and
E. coli PPIs are more challenging because they are more evolutionarily divergent from the
human proteins used for training than the other species (see **Figure 2b**): Our model achieved
an AUPR of 0.706 on yeast, a 28% improvement over TT3D's AUPR of 0.553 and a 19%
improvement on *E. coli* with an AUPR of 0.722.
109
Importantly, the improvement in PLM-interact is due to its ability to correctly identify
positive PPIs: Comparing the prediction interaction probability of PLM-interact with the
second-best predictor TT3D, PLM-interact consistently assigned higher probabilities of
interaction to true positive PPIs. TT3D, in contrast, despite using a broader feature set,
produces a bimodal distribution for interaction probabilities in all held-out species (more
details see **Supplementary Figure 2**).

Figure 2. **PLM-interact achieves the highest PPI prediction performance**. The benchmarking
results of PLM-interact with state-of-the-art PPI prediction models. **a.** The data size of training,
validation and test PPIs. **b.** The taxonomic tree of the training and test species, precision-recall curves

of each test species and a bar plot of AUPR values on PPI prediction benchmarking. **c**. Violin plots
of predicted interaction probabilities of PLM-interact and TT3D on positive and negative pairs,
respectively. (see **Supplementary Figure 2** for more information).

Next, we showcase five positive PPI instances, one for each test species, for which our model
produces a correct prediction, but TT3D produces an incorrect prediction (**Figure 3**). These
PPIs are necessary for essential biology processes including ubiquinone biosynthesis, RNA
polymerisation, ATP catalysis, transcriptional activation and protein transportation. We use
Chai-1[21] and AlphaFold3[22] to predict and visualise these interacting protein structures
(**Figure 3** and **Supplementary Figure 3**). Notably, both Chai-1 and AlphaFold3 have only
1 out 5 structures with close to high-confidence prediction (ipTM close to 0.8). Both
methods give failed prediction scores (ipTM <0.6) for 4 out 5 structures. PLM-interact gives
correct predictions with high confidence in all cases.

132
Figure 3. PPI example for each species that was predicted correctly by PLM-interact but not
by TT3D. Protein-protein structures are predicted by Chai-1[21] and visualised with ChimeraX[23]. Both
models' prediction interaction probabilities range between 0 and 1. A predicted interaction
probability >0.5, is predicted as a positive PPI, while <0.5 is a negative pair. Interacting proteins are

shown from left (yellow) to right (green), respectively, for **mouse**: Q8K1Z0 (Ubiquinone

biosynthesis protein COQ9, mitochondrial) and Q8R1S0 (Ubiquinone biosynthesis monooxygenase

COQ6, mitochondrial); **Worm**: Q21955 (Mediator of RNA polymerase II transcription subunit 15)

and Q9N4F2 (Mediator of RNA polymerase II transcription subunit 19); **Fly**: Q9V3J1 (V-type

proton ATPase subunit H) and Q9V7D2 (V-type proton ATPase subunit D 1); **Yeast**: P22149 (Iron-

regulated transcriptional activator AFT1) and P53040 (Transcription initiation factor TFIID subunit

6); and ***E. coli***: A0A454A7G5 (ABC transporter permease protein) and A0A454A7H5 (Possible

ABC-transport protein, ATP-binding component). See **Supplementary Figure 3** for AlphaFold3[22]

predicted structures. The ipTMs for both Chai-1 and AlphaFold3 are shown for each structure, where

ipTM <0.6 indicates failed predictions and ipTM >0.8 indicates high confidence predictions.

147 PLM-interact can identify the impact of mutations on interactions

Here, we demonstrate examples of PLM-interact correctly predicting the consequences of

mutations on PPIs. Canonical protein sequences (ie proteins without mutations) are retrieved

from UniProt[24]. Amino acid substitutions associated with changes in PPIs are obtained from

InAct[25]. We obtained predicted interaction probabilities for canonical and mutants from

PLM-interact trained on human data (see Methods). For mutations associated with

interaction gain 'mutation-causing' interactions (see **Figure 4a**), PLM-interact predicted

interaction probabilities of the negative pair are below 0.5, whereas the interaction

probabilities of the mutant PPI exceed 0.5. For mutation-disrupting PPIs (**Figure 4b**), the

predicted interaction probabilities of the positive PPI exceed 0.5, whereas the interaction

probabilities of the mutant PPI are below 0.5. Examples are presented in **Figure 4**, where

complex structures are predicted by Chai-1[21].

We show two examples of mutations that cause PPIs in **Figure 4a,** the protein Ataxin-1 and

SOD1 (Superoxide dismutase [Cu-Zn]), which in humans are encoded by the ATXN1 and

SOD1 genes separately. Ataxin-1 interacts with many other proteins and the expansion of a

glutamine(Q)-encoding repeat can affect the function of PPIs and cause the genetic disease

spinocerebellar ataxia type1 (SCA1) and other polyglutamine diseases[26]. Predictions from

PLM-interact show that prior to mutation, this PPI has a predicted interaction probability of

0.411, correctly indicating non-interaction with E2s (Ubiquitin-conjugating enzyme E2 E3).

Following mutation, PLM-interact increases this score to 0.771, correctly predicting that the

mutation induces interaction. In the second example (**Figure 4a**), the SOD1 gene encodes

superoxide dismutase enzymes that break down human superoxide radicals. SOD1 is linked

to the nervous system disease amyotrophic lateral sclerosis (ALS)[27], with the A4V mutation

being the most common variant in North America[28]. PLM-interact predicts 0.465 and 0.851

before and after the mutation, correctly capturing the change in interaction with CDK4

(Cyclin-dependent kinase 4).

174
Figure 4. Demonstration of PLM-interact detecting changes in human PPIs associated with

mutations. **a** shows two mutation-causing interaction examples, while **b** shows two mutation-

disrupting PPI examples. These PPI structures are predicted using Chai-1[21] and visualised with

ChimeraX[23]; here, the mutated amino acids are highlighted in purple. Prediction interaction

probabilities exceeding 0.5 indicate the proteins interact, while below 0.5 indicate non-interact. Chai-
1's ipTM scores give the structure prediction confidence where <0.6 indicates failed predictions.
Interacting protein structures are shown from left (yellow) to right (green): **a.** Residue 225 Glutamine
(Q) of P54253 (Ataxin-1) is mutated to 50 Q, causing interaction with Q969T4 (Ubiquitin-
conjugating enzyme E2 E3)[29]; Residue 5 Alanine (A) of P00441 (Superoxide dismutase [Cu-Zn]) is
mutated to Valine (V), causing interaction with P11802 (Cyclin-dependent kinase 4)[30]. **b.** Residue
86 Arginine(R) of P62993 (Growth factor receptor-bound protein 2) is mutated to Lysine (K),
disrupting its interaction with Q5SXH7-1 (Pleckstrin homology domain-containing family S
member 1)[31]; Residue 732 Tyrosine (Y) of Q96PD2 (Discoidin, CUB and LCCL domain-containing
protein 2) is mutated to Phenylalanine (F), disrupting its interaction with P46109 (Crk-like protein)[32].
See **Supplementary Figure 4** for AlphaFold3[22] predicted structures.

Next, we show two examples of mutations that disrupt PPIs (**Figure 4b**). First, GRB2
(growth factor receptor bound protein 2) is associated with signal transduction. GRB2
mutations are associated with multiple cancers, including breast cancer[33] and leukaemia[34].
The canonical protein interacts with PLEKHS1 (Pleckstrin homology domain-containing
family S member 1). PLM-interact predicts that the missense mutation R86K reduces the
interaction probability from 0.503 to 0.477. Second, CLCP1 is a transmembrane protein that
regulates cell growth and this protein is identified as a cancer marker, exhibiting up-
regulated expression in lung cancer[35]. Again, PLM-interact predicts that the missense
mutation Y732F reduces the interaction probability from 0.873 to 0.425.

Improved virus-human PPI prediction

To study virus-host PPI prediction, we train PLM-interact on a virus-human PPIs dataset
from Tsukiyama et al.[11]. The dataset is derived from the Host-Pathogen Interaction Database
(HPIDB) 3.0[36], comprising a total of 22,383 PPIs, which include 5,882 human and 996 virus
proteins. We compare our model with three recent virus-human PPI models: PLM-based
approach STEP[14] and the protein embeddings-based approaches LSTM-PHV[11] and
InterSPPI[37]. STEP is similar to existing PPI models benchmarked previously in our study;
it leverages protein sequence embedding extracted by the pre-trained PLM ProtBERT[38]. The
results show that PLM-interact outperforms the other models. For the STEP comparison this
corresponds to improvements in AUPR, F1 and MCC scores of 5.7%, 10.9% and 11.9%,
respectively (**Figure 5a**). The length of virus, human proteins and the combined length of
virus-human PPIs are shown in **Figure 5b**. To further analyse our model's performance, we
select three pairs of virus-human PPIs from our test data, all with corresponding
experimental virus-human complex structures available in the HVIDB[39]. We then use

ChimeraX[23] to visualise these structures and present PLM-interact's predicted interaction

probability for each example (see **Figure 5c**).

Figure 5. a. Comparison of AUPR, F1 and MCC metrics of PLM-interact against recent virus-human
PPI models. **b**. The distribution of the length of virus proteins, human proteins and virus-human
protein pairs. **c**. The virus-human PPIs are correctly predicted by our model and the 3D complex
structures of virus-human PPIs are experimentally verified structures collected from the human-virus
PPI database (**HVIDB**[39]). From left (green) to right (yellow), these interacting protein structures are:
Tumour necrosis factor receptor superfamily member 14 (Human protein: Q92956) with Envelope
glycoprotein D (human herpes simplex virus 1: P57083), Ephrin-B2 (human protein: P52799) with
Glycoprotein G (Nipah virus protein: Q9IH62) and Retinoblastoma-associated protein (human
protein: P06400) with Large T antigen (Simian virus 40: P03070). Note: The metrics results of the
other three models in panel **a** are taken from STEP[14] paper.

Discussion

227 In this study we have developed a novel PPI prediction method, PLM-interact, that extends

228 single protein-focused PLMs to their interacting protein partner. We report significant

229 improvements in held-out species comparisons and highlight successful examples of

230 predicting mutational effects on protein interactions. We further demonstrate PLM-interact's

performance in a virus-human PPI prediction task, showing a significant improvement over state-of-the-art prediction approaches.

Underlying the benefit of PLM-interact is the improved capability of correctly predicting positive PPIs in the held-out species. However, positive PPIs are challenging to predict due to a lack of high-quality PPI data for training. Our improved performance relative to TT3D is particularly impressive given that we only use sequences. TT3D[13] includes explicit structural information, the per-residual structural alphabet in Foldseek[40], to improve its prediction over Topsy-Turvy, which incorporated network data.

Furthermore, our results show the potential of predicting mutational effects on PPIs from sequence alone. This could lead to a new generation of interaction aware in-silico variant effect predictors where methods rely on PLMs of the single proteins[41–43]. However, current training data remains limited. The number of high-quality structures of mutant proteins and their interaction partners are low. Algorithmically, models with long and multimodal context[44–46] that include multiple proteins, structures and nucleotides could be specialised for interaction tasks.

Finally, effective sequence-based virus-host PPI predictors could provide the much-needed molecular detail to conventional virus-host species prediction tools, which tend to rely on genome composition signals ignoring host molecules that are interacting physically with viral molecules[47–50]. In those approaches, the host species only act as labels. Recent progress within SARS-CoV-2 PPI studies mapped out a complex interaction landscape between the virus and human proteome[51,52]. Other viruses are likely to have similarly complex interactions with human and animal hosts. Leveraging these interactions could lead to tools that are better at predicting zoonotic events and the potential for emergence of novel viruses. While PLM-interact has demonstrated significant improvements there is much to do in terms of generating reliable predictions, in particular the need for high-quality virus-host experimental PPI data for training. What is clear is attention applied to longer-range sequence interactions is enhancing our understanding of protein interactions, the fundamental 'language' of molecules.

Methods

Datasets

The benchmarking human PPI dataset, from Sledzieski et al.[15], comprises human training and validation data and test data from five other species: mouse, *Mus musculus*; fly, *Drosophila melanogaster*; worm, *Caenorhabditis elegans*; yeast, *Saccharomyces cerevisia*e; and *E. coli*, *Escherichia coli*), all retrieved from STRING V11[53]. We train and validate our model on human PPIs and then conduct inference on PPIs from five other species. All training, validation and test datasets maintain a 1:10 ratio of positive to negative pairs, reflecting the fact that positive PPIs are significantly fewer than negative pairs in the actual host PPI networks. The length of protein sequences ranges from 50 to 800 and PPIs are clustered at 40% identity using CD-HIT[54] to remove the redundant PPIs. The human training dataset includes 38,344 positive PPIs, whereas the validation set includes 4,794 positive PPIs. Each of the five species includes 5,000 positive interactions, except for *E. coli,* which only has 2,000 positive interactions due to the fewer positive PPIs in the STRING dataset used[15].

The benchmarking dataset of 22,383 virus-human PPIs includes 5,882 human and 996 virus proteins. This dataset was obtained from Tsukiyama et al.[11], sourced from the HPIDB 3.0 database[36]; the ratio of positive to negative pairs is 1:10 and negative pairs are chosen based on sequence dissimilarities. The length of protein sequences ranges from 30 to 1,000 and the redundant PPIs are filtered based on a threshold of 95% identity using CD-HIT[54].

In addition, we provide models trained on human PPIs from STRING V12[55]. The positive PPIs are selected by collecting physical links with positive experimental scores, while excluding PPIs with positive homology scores and confidence scores below 400. Previous studies have typically limited the maximum length of protein sequences to 800 or 1000 due to GPU memory limitations. We process the length of protein sequences up to 2000, with a combined length threshold for PPIs of nearly 2500. This human dataset includes 60,308 positive PPIs for training and 15,124 positive PPIs for testing. Furthermore, protein sequences are clustered at 40% identity using MMSeq2[56] and only PPIs from the distinct clusters are chosen to eliminate redundant PPIs. Again, the positive-to-negative protein pair ratio is 1:10, consistent with the aforementioned two benchmarking datasets.

Model architecture

We use ESM-2 as the base model in PLM-interact. ESM-2 is an encoder transformer model with a parameter size range from 8 million to 15 billion. The results presented are PLM-interact based on ESM-2 with 650M parameters. We also provided PLM-interact models with ESM-2 35M on our GitHub repository to help with quick testing. The input representation contains amino acid token representations from two proteins. This setup is similar to the original BERT model[57], also known as the *cross-encoder* which simultaneously encodes a pair of query and answer sentences.

A standard input sequence of PLM-interact, x, can be shown as the following:

$$x = [CLS, P_1, EOS, P_2, EOS], \tag{1}$$

where CLS is the classification token, P_1 contains amino acid tokens of protein 1, P_2 contains amino acid tokens of protein 2, and EOS is the end-of-sentence token. The first EOS token marks the end of the amino acid sequence in protein 1. This setting allows us to use the original ESM-2 tokenizer to generate embedding vectors e, and pass them to the transformer encoder of the ESM-2:

$$h = f(e), \tag{2}$$

where f is ESM-2, e contains the token embeddings of x, and h contains the output embeddings of all input tokens. h can be presented as:

$$h = \{h_{cls}, h_{a_1}, \dots h_{EOS}, \dots h_{a_n}, \dots h_{EOS}\}, \tag{3}$$

where h_{a_1} and h_{a_n} represent amino acid tokens in proteins 1 and 2. Then, we use the CLS token embedding to aggregate the representation of the entire sequence pair and as the features for a linear classification function φ, and parameterised as a single feed forward layer with a ReLU activation function. The output of the FF layer is converted by the sigmoid function σ to obtain the predicted interaction probability g,

$$g = \sigma\big(\varphi(h_{cls})\big). \tag{4}$$

Model Training

PLM-interact is trained with two tasks: 1) a mask language modelling (MLM) task
predicting randomly masked amino acids and 2) a binary classification task predicting the
interaction label of a pair of proteins. PLM-interact is trained for 10 epochs using a batch
size of 128 on both benchmarking datasets of human PPIs and virus-human PPIs. For all
training runs, the input protein pairs are trained on both orders as the interaction between
protein 1 and protein 2 is the same as the protein 2 and protein 1, which leads to double the
size of the training set. The validation and testing sets are not subject to the same data
argumentation. The learning rate is 2e-5, weight decay is 0.01, warm up is 2000 steps, and
the schedular is WarmupLinear which linearly increasing the learning rate over the warmup
steps. During training, we evaluate the model's performance at every 2000 steps on the
validation set. For every evaluation, a set of 128 protein pairs are randomly sampled from
the validation set and the results are averaged over 100 times to ensure metric reliability.
Here, we use both masking and classification losses to optimize our model, the loss function
for each data point l can be represented as:

331
$$l = \alpha l_{mlm} + \beta l_{ce},\tag{5}$$

332 where l_{mlm} and l_{ce} are separately represent the MLM loss and classification (ie cross
333 entropy) loss. l can be written as:

334
$$l = -\frac{\alpha}{M}\sum_{i=1}^{M} \ln p(x_i|x_{-i}) - \beta(y\ln(g) + (1-y)\ln(1-g)),\tag{6}$$

where M is the number of the masked tokens, x_i is the true token at position i,
$p(x_i|x_{-i})$ is the probability of the true token x_i given the unmasked amino acid x_{-i}. y
is the label of the interaction and g is the predicted probability for $y = 1$, obtained from
equation 4. α and β are weights for the MLM and classification losses.

All of the models are trained on the DiRAC Extreme Scaling GPU cluster Tursa. A typical
10-epoch training run of the model with ESM-2 (650M) with human PPIs takes 31.1 hours
on 16 A100-80 GPUs. A typical 10-epoch training run of the model with ESM-2 (650M)
trained on virus-human PPIs takes 30.5 hours on 8 A100-80 GPUs. The model with ESM-
2 (650M) trained on STRING V12 human PPIs used 16 A100-80 GPUs for 86.4 hours. For

model training time with different ratios and model sizes, see the following section
optimisation experiment and **Supplementary Table 1**.

We provide model checkpoints that include human PPI models trained on Sledzieski et al.'s
benchmarking datasets retrieved from STRING V11[53], the virus-human PPIs model trained
on the benchmarking virus-human PPIs created by Tsukiyama et al.[11], sourced from HPIDB
3.0[36], as well as human PPIs collected by us from STRING V12[53].

PLM-interact optimisation experiments

To find the optimal value of α and β in equation (6), we benchmark a range of different
options between mask loss and classification loss on human benchmarking data. For each
ESM-2-35M and ESM-2-650M model, we train five models with different setting of ratios
$\alpha : \beta$ between mask loss and classification loss. The ratios are $\alpha : \beta$ = 1:1, 1:5, 1:10, 0:1
(with mask), and 0:1 (without mask, denoted as classification). (**Supplementary Figure 1**
b, c). We used the human validation set for each model to identify the optimal epoch
checkpoint achieving the best AUPR. Next, the final model is selected based on testing on
five other host PPIs.

For ESM-2-650M, the 1:10 ratio is the optimal choice (McNemar test, the greatest counts
of p-values less than 0.05) compared to other options (**Supplementary Figure 1 d**). The
model with a 1:5 ratio of mask to classification loss based on ESM-2-35M achieved the
highest number of significant improvements (McNemar test, the greatest counts of p-values
less than 0.05) compared to other models (**Supplementary Figure 1 e**). According to these
results, we select a loss ratio of 1:10 for ESM-2-650M and 1:5 for ESM-2-35M. The ratio
setting is implemented in both benchmarking of human PPI training and virus-human PPI
training, as well as human PPI training using the STRING V12 database.
367

Baselines

We compute the prediction interaction probabilities based on checkpoints of TT3D[13], Topsy-
Turvy[19] and D-SCRIPT[15] to generate precision-recall (PR) curves in **Figure 2b**. Due to the
absence of publicly available checkpoints for DeepPPI[20] and PIPR[6], these methods are
excluded from the PR curve comparison. The AUPR values for DeepPPI and Topsy-Turvy
are sourced from the Topsy-Turvy paper[19], those for D-SCRIPT and PIPR are from the D-

SCRIPT paper[15], and the AUPR value of TT3D is obtained through email communication.

A complete list of the main features, architectures, reference, and code link of each baseline

method can be found in **Supplementary Table 2**.

MMseq2

378   We used MMseq2 to obtain the protein sequence-based alignment results between each pair

379   of proteins; the parameters setting is:

380   --threads 128 --min-seq-id 0.4 --alignment-mode 3 --cov-mode 1.

Chai-1

382   Chai-1[21] is a state-of-the-art model for molecular structure prediction, available at

383   https://lab.chaidiscovery.com/. We use Chai-1 with the "specify restraints" option to predict

384   protein-protein structure complexes and visualise predicted PPI structures using the

385   molecular visualisation program ChimeraX[23].

AlphaFold3

387   AlphaFold3 is a tool to predict the biomolecular interactions including protein, DNA, small

388   molecules, ions and modified residues[22], available at https://alphafoldserver.com/. We use

389   AlphaFold3 in its PPI mode to predict protein structure complexes. The results are visualised

390   with the molecular visualisation program ChimeraX[23].

McNemar's test

392   McNemar's Chi-Square test[58] is a statistical test that determines if there are significant

393   differences between paired nominal data.

394
$$McNemar's\,test = \frac{(\frac{model1_{true}}{model2_{false}} - \frac{model1_{fasle}}{model2_{true}})^2}{\left(\frac{model1_{true}}{model2_{false}} + \frac{model1_{fasle}}{model2_{true}}\right)} \tag{7}$$

395   Here, $model1_{true}$ and $model2_{true}$ separately represent the count of correct prediction

396   obtained by $model1$ or $model2$, while $model1_{fasle}$ and $model2_{false}$ separately represent

397   the count of incorrect prediction obtained by $model1$ and $model2$.

To investigate if our models with varying ratios of mask-to-classification loss perform significant differences, we conducted a McNemar's test for any pairs of models in optimisation experiments. This test is based on the number of correct and incorrect between two models. Predicted interaction probabilities from each model are used to get predicted labels, which are used to obtain the counts of correct and incorrect predictions. A McNemar's test p-value ≤ 0.05 indicates a significant difference between the predictive performance of two models. The model with more correct predictions is considered superior to the other.

Data availability

Sledzieski et al.'s benchmarking PPI data is available at https://d-script.readthedocs.io/en/stable/data.html

Tsukiyama et al.'s virus-human benchmarking PPIs dataset is available at:

http://kurata35.bio.kyutech.ac.jp/LSTM-PHV/download_page

STRING V12 PPIs database: https://stringdb-downloads.org/download/protein.physical.links.v12.0.txt.gz

The mutations that cause or disrupt PPIs are from IntAct[25] Database; the link is

https://ftp.ebi.ac.uk/pub/databases/intact/current/various/mutations.tsv

UniProt: https://www.uniprot.org/

HVIDB: http://zzdlab.com/hvidb/download.php

Code availability

The code and trained models are available at https://github.com/liudan111/PLM-interact

Acknowledgements

The authors acknowledge funding from the European Union's Horizon 2020 research and innovation 562 program, under the Marie Sklodowska-Curie Actions Innovative Training Networks 563 grant agreement no. 955974 (VIROINF) for DL, a UK Medical Research Council (MRC) Doctoral Training Programme in Precision Medicine studentship (MR/N013166/1) for KDL and MRC grants: MC_UU_00034/5, MC_UU_00034/6 and MR/V01157X/1. KY acknowledges support from Cancer Research UK (EDDPGM-Nov21\100001 and DRCMDP-Nov23/100010), Biotechnology and Biological Sciences Research Council (BBSRC) BB/V016067/1, Prostate Cancer UK MA-TIA22-001 and EU

428 Horizon 2020 grant ID 101016851. This work used the DiRAC Extreme Scaling service
429 (Tursa) at the University of Edinburgh, managed by the Edinburgh Parallel Computing
430 Centre on behalf of the STFC DiRAC HPC Facility (www.dirac.ac.uk). The DiRAC service
431 at Edinburgh was funded by BEIS, UKRI and STFC capital funding and STFC operations
432 grants. DiRAC is part of the UKRI Digital Research Infrastructure.

Supplementary Figures

Supplementary Figure 1. The benchmarking of different ratios of mask to classification loss on five species PPI prediction. **a.** The bar plot to show the ratio between mask loss and classification loss. **b** and **c** respectively represent the performance of our model with the different ratios between mask and classification loss on 650M and 35M of ESM-2 models. The left is aligned with taxonomy tree of the hosts that are used for evaluating our human PPI model. **d** and **e** show the better model with significant improvements than the other, p-value < 0.05 with McNemar's Test.

442 **Supplementary Figure 2. The distribution of prediction scores of positive and negative protein**

443 **pairs of PLM-interact, TT3D, TT and D-SCRIPT.** PLM-interact outperforms other models by

444 identifying the most true positive pairs (predicted interaction probability > 0.5) and true negative

445 pairs (predicted interaction probability < 0.5), demonstrating that PLM-interact achieves the best

446 performance, except for negative pairs of *E. coli*.

447
Supplementary Figure 3. PPI example for each species that was predicted correctly by PLM-

interact but not by TT3D. Protein-protein structures are predicted by AlphaFold3[22]. and visualised

with ChimeraX[23]. Both models' prediction interaction probabilities range between 0 and 1. A

predicted interaction probability >0.5, is predicted as a positive PPI, while <0.5 is a negative pair.

Interacting proteins are shown from left (yellow) to right (green), respectively. For information about

these PPIs, see **Figure 3**.

a Mutation-causing PPI

Ataxin-1 and Ubiquitin-conjugating enzyme E2 E3

Canonical ●   Ins225 Qx50 →   Mutant ●

0.411   0.771

0   0.5   1

Predicted interaction probability

0.40   0.36

0   0.6   0.8   1

ipTM (AlphaFold3)

Superoxide dismutase [Cu-Zn]) and Cyclin-dependent kinase 4

A5V →

0.465   0.851

0   0.5   1

Predicted interaction probability

0.08   0.08

0   0.6   0.8   1

ipTM (AlphaFold3)

b Mutation-disrupting PPI

Growth factor receptor-bound protein 2 and Pleckstrin homology domain-containing family S member 1

Mutant ●   ← R86K   Canonical ●

0.503   0.477

0   0.5   1

Predicted interaction probability

0.49   0.23

0   0.6   0.8   1

ipTM (AlphaFold3)

Discoidin, CUB and LCCL domain-containing protein 2 and Crk-like protein

← Y732F

0.873   0.425

0   0.5   1

Predicted interaction probability

0.22   0.38

0   0.6   0.8   1

ipTM (AlphaFold3)

454
Supplementary Figure 4. Demonstration of PLM-interact detecting changes in human PPIs

associated with mutations. **a** shows two mutation-causing interaction examples, while **b** shows two

mutation-disrupting PPI examples. These PPI structures are predicted using AlphaFold3[22] and

visualised with ChimeraX[23]; here, the mutated amino acids are highlighted in purple. Prediction
interaction probabilities exceeding 0.5 indicate the proteins interact, while below 0.5 indicate non-
interact. AlphaFold3's ipTM scores give the structure prediction confidence where <0.6 indicates
failed predictions. Interacting protein structures are shown from left (yellow) to right (green). See
Figure 4 for information about these protein pairs.

Supplementary Tables

464 **Supplementary Table 1.** This table shows the GPU hours (GPUhs) of different models.
465 PLM-interact has the two kinds of training strategies: masking language modelling and
466 binary classification, binary classification only. The ratios in this table present the different
467 weights between mask loss and classification loss, binary indicates the binary classification
468 task.

Models/GPUhs	650M	35M
0:1	522.4	238.2
1:1	514.3	299.1
1:5	508.4	238.1
1:10	496.9	240.4
Binary	355.8	130.9

469
470 **Supplementary Table 2.** This table described the features of state-of-the-art models in this
471 paper.

	Protein features	Model architecture	Source	Tool
TT3D	Pre-trained Bepler & Berger PLM Embeddings and one-hot encoding of the Foldseek 3Di	Convolutional neural network	Sledzies ki, S. et al. 2023	https://github.com/samsledje/D-SCRIPT
D-SCRIPT	Pre-trained Bepler & Berger PLM embeddings	Convolutional neural network	Sledzies ki, S. et al. 2021	http://dscript.csail.mit.edu
Topsy-Turvy	Pre-trained Bepler & Berger PLM embeddings and network structure	Intergrade D-SCRIPT and a network-based model GLIDE	Singh, R. et al. 2022	https://topsyturvy.csail.mit.edu
PIPR	Pre-trained amino acid embeddings using Skip-Gram model	Siamese residual RCNN	Chen, M. et al. 2019	https://github.com/muhaochen/seq_ppi
DeepPPI	One hot encoding amino acids	Fully connected model architecture	Richoux et al., 2019	https://gitlab.univ-nantes.fr/rich

				oux-f/DeepPPI
STEP	Pre-trained PLM ProtBERT embeddings	Siamese neural network	Madan, S. et al. 2022	https://github.com/SCAI-BIO/STEP/tree/main
LSTM-PHV	word2vec	LSTM and Siamese model	Tsukiyama et al.2021	http://kurata35.bio.kyutech.ac.jp/LSTM-PHV.
InterSPPI	doc2vec	Random Forest classifier	Yang et al. 2020	http://zzdlab.com/InterSPPI/

References

1.   Berggård, T., Linse, S. & James, P. Methods for the detection and analysis of protein–

protein interactions. *PROTEOMICS* **7**, 2833–2842 (2007).

2.   David, A. & Sternberg, M. J. E. The Contribution of Missense Mutations in Core and

Rim Residues of Protein–Protein Interfaces to Human Disease. *Journal of Molecular*

Biology **427**, 2886–2898 (2015).

3.   Vassilev, L. T. *et al.* In Vivo Activation of the p53 Pathway by Small-Molecule

Antagonists of MDM2. *Science* **303**, 844–848 (2004).

4.   Kotlyar, M., Pastrello, C., Sheahan, N. & Jurisica, I. Integrated interactions database:

tissue-specific view of the human and model organism interactomes. (2015)

doi:10.1093/nar/gkv1115.

5.   Shin, W.-H., Kumazawa, K., Imai, K., Hirokawa, T. & Kihara, D. Current Challenges

and Opportunities in Designing Protein–Protein Interaction Targeted Drugs. (2020)

doi:10.2147/AABC.S235542.

6.   Chen, M. *et al.* Multifaceted protein–protein interaction prediction based on Siamese

residual RCNN. *Bioinformatics* **35**, i305–i314 (2019).

7.   Hashemifar, S., Neyshabur, B., Khan, A. A. & Xu, J. Predicting protein–protein

interactions through sequence-based deep learning. *Bioinformatics* **34**, i802–i810

(2018).

8.   Huang, Y., Wuchty, S., Zhou, Y. & Zhang, Z. SGPPI: structure-aware prediction of

protein–protein interactions in rigorous conditions with graph convolutional network.

Briefings in Bioinformatics **24**, bbad020 (2023).

9.   Yuan, Q., Chen, J., Zhao, H., Zhou, Y. & Yang, Y. Structure-aware protein–protein

interaction site prediction using deep graph convolutional network. *Bioinformatics* **38**,

125–132 (2021).

10. Shen, J. *et al.* Predicting protein–protein interactions based only on sequences

information. *Proceedings of the National Academy of Sciences* **104**, 4337–4341

(2007).

11. Tsukiyama, S., Hasan, M. M., Fujii, S. & Kurata, H. LSTM-PHV: prediction of

human-virus protein–protein interactions by LSTM with word2vec. *Briefings in*

Bioinformatics **22**, bbab228 (2021).

12. Hallee, L. & Gleghorn, J. P. Protein-Protein Interaction Prediction is Achievable with

Large Language Models. 2023.06.07.544109 Preprint at

https://doi.org/10.1101/2023.06.07.544109 (2023).

13. Sledzieski, S., Devkota, K., Singh, R., Cowen, L. & Berger, B. TT3D: Leveraging

precomputed protein 3D sequence models to predict protein–protein interactions.

Bioinformatics **39**, btad663 (2023).

14. Madan, S., Demina, V., Stapf, M., Ernst, O. & Fröhlich, H. Accurate prediction of

virus-host protein-protein interactions via a Siamese neural network using deep protein

sequence embeddings. *Patterns* **3**, 100551 (2022).

15. Sledzieski, S., Singh, R., Cowen, L. & Berger, B. D-SCRIPT translates genome to

phenome with sequence-based, structure-aware, genome-scale predictions of protein-

protein interactions. *Cell Systems* **12**, 969-982.e6 (2021).

16. Zhang, Z. *et al.* Protein language models learn evolutionary statistics of interacting

sequence motifs. 2024.01.30.577970 Preprint at

https://doi.org/10.1101/2024.01.30.577970 (2024).

17. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a

language model. *Science* **379**, 1123–1130 (2023).

18. Reimers, N. & Gurevych, I. Sentence-BERT: Sentence Embeddings using Siamese

BERT-Networks. Preprint at http://arxiv.org/abs/1908.10084 (2019).

19. Singh, R., Devkota, K., Sledzieski, S., Berger, B. & Cowen, L. Topsy-Turvy:

integrating a global view into sequence-based PPI prediction. *Bioinformatics* **38**, i264–

i272 (2022).

20. Richoux, F., Servantie, C., Borès, C. & Téletchéa, S. Comparing two deep learning

sequence-based models for protein-protein interaction prediction. Preprint at

https://doi.org/10.48550/arXiv.1901.06268 (2019).

21. Chai Discovery *et al.* Chai-1: Decoding the molecular interactions of life. Preprint at

https://doi.org/10.1101/2024.10.10.615955 (2024).

22. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with

AlphaFold 3. *Nature* **630**, 493–500 (2024).

23. Pettersen, E. F. *et al.* UCSF ChimeraX: Structure visualization for researchers,

educators, and developers. *Protein Science* **30**, 70–82 (2021).

24. UniProt Consortium. UniProt: a worldwide hub of protein knowledge. *Nucleic Acids*

Res **47**, D506–D515 (2019).

25. Kerrien, S. *et al.* The IntAct molecular interaction database in 2012. *Nucleic Acids*

Research **40**, D841–D846 (2012).

26. Lim, J. *et al.* Opposing effects of polyglutamine expansion on native protein

complexes contribute to SCA1. (2008) doi:10.1038/nature06731.

27. Rosen, D. R. *et al.* Mutations in Cu/Zn superoxide dismutase gene are associated with

familial amyotrophic lateral sclerosis. *Nature* **362**, 59–62 (1993).

28. Wj, B. *et al.* SOD1A4V-mediated ALS: absence of a closely linked modifier gene and

origination in Asia. *PubMed* (2008).

29. C, H. *et al.* Interactome Mapping Provides a Network of Neurodegenerative Disease

Proteins and Uncovers Widespread Protein Aggregation in Affected Brains. *PubMed*

(2020).

30. Kabuta, T. *et al.* Ubiquitin C-terminal Hydrolase L1 (UCH-L1) Acts as a Novel

Potentiator of Cyclin-dependent Kinases to Enhance Cell Proliferation Independently

of Its Hydrolase Activity*. *Journal of Biological Chemistry* **288**, 12615–12626 (2013).

31. Grossmann, A. *et al.* Phospho-tyrosine dependent protein–protein interaction network.

Molecular Systems Biology **11**, 794 (2015).

32. Aten, T. M. *et al.* Tyrosine phosphorylation of the orphan receptor ESDN/DCBLD2

serves as a scaffold for the signaling adaptor CrkL. *FEBS Lett* **587**, 2313–2318 (2013).

33. Daly, R. J., Binder, M. D. & Sutherland, R. L. Overexpression of the Grb2 gene in

human breast cancer cell lines. *Oncogene* **9**, 2723–2727 (1994).

34. Ohanian, M. *et al.* Liposomal Grb2 antisense oligodeoxynucleotide (BP1001) in

patients with refractory or relapsed haematological malignancies: a single-centre,

open-label, dose-escalation, phase 1/1b trial. (2018) doi:10.1016/S2352-

3026(18)30021-8.

35. Koshikawa, K. *et al.* Significant up-regulation of a novel gene, CLCP1, in a highly

metastatic lung cancer subline as well as in lung cancers in vivo. *Oncogene* **21**, 2822–

2828 (2002).

36. Ammari, M. G., Gresham, C. R., McCarthy, F. M. & Nanduri, B. HPIDB 2.0: a

curated database for host–pathogen interactions. *Database* **2016**, baw103 (2016).

37. Yang, X., Yang, S., Li, Q., Wuchty, S. & Zhang, Z. Prediction of human-virus protein-

protein interactions through a sequence embedding-based machine learning method.

Computational and Structural Biotechnology Journal **18**, 153–161 (2020).

38. Elnaggar, A. *et al.* ProtTrans: Towards Cracking the Language of Life's Code Through

Self-Supervised Learning. 2020.07.12.199554 Preprint at

https://doi.org/10.1101/2020.07.12.199554 (2021).

39. Yang, X. *et al.* HVIDB: a comprehensive database for human–virus protein–protein

interactions. *Briefings in Bioinformatics* **22**, 832–844 (2021).

40. van Kempen, M. *et al.* Fast and accurate protein structure search with Foldseek. *Nat*

Biotechnol (2023) doi:10.1038/s41587-023-01773-0.

41. Frazer, J. *et al.* Disease variant prediction with deep generative models of evolutionary

data. *Nature* **599**, 91–95 (2021).

42. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised

learning to 250 million protein sequences. *Proc Natl Acad Sci U S A* **118**,

e2016239118 (2021).

43. Cheng, J. *et al.* Accurate proteome-wide missense variant effect prediction with

AlphaMissense. *Science* **381**, eadg7492 (2023).

44. Hayes, T. *et al.* Simulating 500 million years of evolution with a language model.

Preprint at https://doi.org/10.1101/2024.07.01.600583 (2024).

45. Cornman, A. *et al.* The OMG dataset: An Open MetaGenomic corpus for mixed-

modality genomic language modeling. (2024) doi:10.1101/2024.08.14.607850.

46. Wang, Y. *et al.* LC-PLM: Long-context Protein Language Model. (2024)

doi:10.1101/2024.10.29.620988.

47. Babayan, S. A., Orton, R. J. & Streicker, D. G. Predicting reservoir hosts and

arthropod vectors from evolutionary signatures in RNA virus genomes. *Science* **362**,

577–580 (2018).

48. Young, F., Rogers, S. & Robertson, D. L. Predicting host taxonomic information from

viral genomes: A comparison of feature representations. (2022)

doi:10.1371/journal.pcbi.1007894.

49. Liu, D., Young, F., Robertson, D. L. & Yuan, K. Prediction of virus-host associations

using protein language models and multiple instance learning. (2023)

doi:10.1101/2023.04.07.536023.

50. Roux, S. *et al.* iPHoP: An integrated machine learning framework to maximize host

prediction for metagenome-derived viruses of archaea and bacteria. (2023)

doi:10.1371/journal.pbio.3002083.

51. Stukalov, A. *et al.* Multilevel proteomics reveals host perturbations by SARS-CoV-2

and SARS-CoV. *Nature* **594**, 246–252 (2021).

52. J, L. *et al.* Virus-Host Interactome and Proteomic Survey Reveal Potential Virulence

Factors Influencing SARS-CoV-2 Pathogenesis. *PubMed* (2021).

53. Szklarczyk, D. *et al.* STRING v11: protein–protein association networks with

increased coverage, supporting functional discovery in genome-wide experimental

datasets. *Nucleic Acids Research* **47**, D607–D613 (2019).

54. Fu, L., Niu, B., Zhu, Z., Wu, S. & Li, W. CD-HIT: accelerated for clustering the next-

generation sequencing data. *Bioinformatics* **28**, 3150–3152 (2012).

55. Szklarczyk, D. *et al.* The STRING database in 2023: protein–protein association

networks and functional enrichment analyses for any sequenced genome of interest.

Nucleic Acids Research **51**, D638–D646 (2023).

56. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching for

the analysis of massive data sets. *Nature Biotechnology* **35**, 1026–1028 (2017).

57. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep

Bidirectional Transformers for Language Understanding. Preprint at

http://arxiv.org/abs/1810.04805 (2019).

58. McNemar, Q. Note on the sampling error of the difference between correlated

proportions or percentages. *Psychometrika* **12**, 153–157 (1947).

620