Feature similarity: a sensitive method to capture the functional interaction of brain regions and

networks to support flexible behavior.

Xiuyi Wang[1,2,3]*, Baihan Lyu[1], Katya Krieger-Redwood[3], Nicholas E. Souter[3], Golia Shafiei[4],

Nan Lin[1,2], Jonathan Smallwood[5], Elizabeth Jefferies[3]*, Yi Du[1,2, 6]*

1. Institute of Psychology, Chinese Academy of Sciences, Beijing, 100101, China.

2. Department of Psychology, University of Chinese Academy of Sciences, Beijing 100049,

China.

3. Department of Psychology, University of York, Heslington, York, YO10 5DD, United Kingdom.

4. Department of Psychiatry, Perelman School of Medicine, University of Pennsylvania,

Philadelphia, PA 19104, USA.

5. Department of Psychology, Queens University, Kingston, Ontario, Canada.

6. Chinese Institute for Brain Research, Beijing 102206, China.

*Correspondence: wangxiuyi@psych.ac.cn, beth.jefferies@psych.ac.cn, duyi@psych.ac.cn

Abstract

The brain is a dynamic system where complex behaviours emerge from interactions across

distributed regions. Accurately linking brain function to cognition requires tools that are sensitive

to these dynamics. We introduce a novel technique - Feature Similarity (FS) - to capture

intricate interaction patterns between brain systems. Our results show that FS can capture

functional brain organisation: regions within the same functional network have greater FS

compared to those in different networks, and FS also identifies the principal gradient that spans

from unimodal to transmodal cortices. FS was found to be more sensitive to task modulation

than traditional functional connectivity (FC). Specifically, FS reveals interaction patterns missed

by FC, such as a double dissociation in Dorsal Attention Network (DAN): greater interaction

with Visual network during working memory tasks and greater interaction with default mode

network (DMN) during long-term memory tasks. This study highlights FS as a promising tool

for understanding flexibility in brain network dynamics.

Keywords: fMRI, functional interaction, feature similarity

1. Introduction

A central aim of cognitive neuroscience is to understand how brain regions interact to support human flexible behaviour. Currently, there is a great opportunity to address this question because datasets in which participants performed multiple cognitive tasks are rapidly increasing in size and scope. While various methods have been used to study functional interactions in specific contexts, it remains difficult to reliably and sensitively capture how these interactions change across tasks in a hypothesis-free manner. Thus, there is a critical need for new methods to address this gap.

Current neuroimaging methods measure functional interactions in specific contexts, but each has limitations that hinder widespread use. For example, within-subject functional connectivity (FC) does not distinguish stimulus-induced correlations from intrinsic or artificial correlations, making it less sensitive to task modulation (Simony et al., 2016). While inter-subject FC (ISFC) isolates stimulus-dependent correlations, it requires identical stimulus presentation across participants, limiting its use in varied datasets (Simony et al., 2016). Methods like psycho-physiological interactions (PPI) (O'Reilly et al., 2012) and dynamic causal model (DCM) (Friston, 2011) rely on predefined seed regions, restricting data-driven exploration. Additionally, methods like Granger causality (Seth et al., 2015) assume stationarity, which may not hold for non-stationary brain signals across tasks. Overall, these limitations necessitate a new approach for more flexible, data-driven analysis of functional interactions across tasks.

Recent studies have highlighted significant advances in the understanding of time-series features of neural activity, revealing that these features can vary across different cognitive tasks tasks (Golesorkhi et al., 2021; Wolff et al., 2022). For instance, timescale of neural responses has been shown to differ depending on the nature of the task being performed tasks (Golesorkhi et al., 2021; Wolff et al., 2022). These insights motivated us to utilise feature similarity (FS) to capture how interaction patterns vary across tasks. The core of this method involves extracting a wide range of interpretable features from time-series data, utilizing these features to calculate the FS between brain regions, and then computing how FS varies across tasks (see Fig. 1). The extracted features include distributional properties, entropy, and variability (i.e., the signal

variability), temporal autocorrelation, time-delay embeddings, and nonlinear properties of a given time-series, including nonlinear temporal autocorrelation (Fulcher, 2018; Fulcher et al., 2013).

The development of FS was inspired by observations that certain brain regions possess distinct features, which equip them to support different functions, while regions with similar features tend to support parallel functions, regardless of their FC. For instance, early visual areas and the default mode network (DMN) are situated at opposing ends of the timescale hierarchy — early visual areas have rapid autocorrelation decay, whereas DMN regions show gradual autocorrelation decay (Blank and Fedorenko, 2020; Honey et al., 2012; Ito et al., 2020; Raut et al., 2020; Simony et al., 2016). This timescale difference underlies their functional roles: neural representations in early visual areas are minimally influenced by prior knowledge, while the DMN is heavily shaped by it (González-García et al., 2018). Similarly, transmodal regions like frontoparietal control network (FPCN) and DMN, though often showing negative FC (Wang et al., 2024a), share long timescales(Raut et al., 2020) and process inputs over longer periods (i.e., maintaining task goals) (Wang et al., 2021). These observations suggest that FS can capture functional similarities beyond aspects revealed by FC.

Furthermore, features can differ depending on tasks (Golesorkhi et al., 2021; Wolff et al., 2022), indicating their potential to depict variations in network interactions. For example, auditory story comprehension shortens the autocorrelation window in transmodal regions, but maintains its duration in unimodal regions. In contrast, motor and working memory tasks exhibit the opposite effect (Golesorkhi et al., 2021). These shifts in features reflect brain's dynamic adaptation to task demands, as seen with domain-general control network, which exhibits greater FS with dorsal attention network (DAN) during working memory tasks and with memory control network during long-term memory tasks (Wang et al., 2024a). These observations led us to develop a hypothesis-free, data-driven FS analysis that extracts comprehensive features to objectively capture the complexity of time-series data. FS has the potential to uncover previously undetected relationships due to the limitations of existing methods. With no reliance on predefined regions of interest or task designs, FS can be applied across multiple datasets,

offering a versatile tool for studying functional interactions in cognitive neuroscience.

In this study, we demonstrate that FS effectively captures dynamic interaction patterns

across tasks. To assess whether FS provides greater sensitivity than FC, we focused on the

well-established anti-correlation between two large-scale networks: DAN typically shows strong

FC with Visual network and weak FC with DMN, indicating competition between external

attention and cognition guided by long-term memory (Fox et al., 2005; Shine et al., 2019).

However, recent evidence demonstrates that DAN is topographically positioned between the

visual network and DMN (Margulies et al., 2016; Wang et al., 2024a), allowing it to cooperate

with both networks in certain situations (Buckner and DiNicola, 2019; Buckner and Margulies,

2019; Margulies et al., 2016; Mesulam, 1998; Smallwood et al., 2021). Tasks that involve

working memory and long-term memory are expected to involve distinct interaction patterns

between these networks (Fig. 2; Wang et al., 2024a). Our results show that FS captures this

flexibility better than FC. DAN interacts more with visual system in working memory tasks and

with DMN in long-term memory tasks in FS, but this distinction is not detected by FC. This

underscores FS's ability to capture nuanced brain dynamics.

Fig. 1. The workflow of the FS and FC analysis. (I) Individual-specific parcellation divided the whole brain into 400 parcels across 17 networks (Kong et al., 2021). (II) Average time series of each parcel. (III) Extraction of features of time series for each parcel. (IV) Pearson correlation coefficients of the extracted features represent the pairwise feature similarity between all possible combinations of brain parcels. (V) Functional connectivity involved calculating Pearson correlation coefficients between the time-series of parcels. (Vis = Visual, Aud = Auditory, SM = Sensory-motor, DAN = Dorsal attention network, VAN = Ventral attention network, FPCN = Fronto-parietal control network, Lang = Language, DMN = Default mode network).

Fig. 2. The experimental design. To tap working memory, we included two tasks: a spatial working memory task required participants to keep track of sequentially presented locations, while math decisions involved maintaining and manipulating numbers which rely more on working memory. To tap long-term memory, we included two tasks that required controlled retrieval of knowledge; a semantic feature matching task required participants to match probe and target concepts according to a particular semantic feature (color or shape), while a semantic association task involved deciding if pairs of words were linked in meaning. Response periods are indicated by a red box.

2. Results

The results are divided into three sections. (i) First, we took an existing individualized parcellation of the cortex to identify the parcels of each network and examined whether FS is equally capable of capturing the network structure as FC does. As expected, regions belonging to the same intrinsic functional subnetworks had greater FS compared to regions in different subnetworks. (ii) Next, we examined whether FS could capture the organizational principles of the cortex as is seen in FC. We found FS captured the principal intrinsic connectivity gradient that separates sensory-motor regions from transmodal areas, as well as the second component that separates somatomotor and auditory from visual cortex, which have been previously described using decompositions of FC. (iii), Finally, we examined whether FS is more sensitive to task-induced changes in brain dynamics than FC by examining how these metrics characterise network interactions across working memory and long-term memory tasks. Specifically, we asked whether FS and FC are equal in their capacity to identify differences in the way that DAN interacts with Visual network and DMN during working memory and long-term memory tasks.

The FS method consists of the following steps (see Fig. 1):

Step 1: Extract a diverse set of interpretable features from the time-series data.

Step 2: Calculate FS between brain regions by calculating the Pearson correlation coefficients of the extracted features.

Step 3: Examine how FS varies across different tasks.

2.1. Regions belonging to the same intrinsic functional network have greater FS compared to regions in different networks

We first examined whether parcels within the same network exhibited similar features. We selectedKong et al. 's parcellation (2021a) as it allows for individual-specific parcellations with greater homogeneity (Wang et al., 2024a) while capturing the inherent heterogeneity of large-

scale networks like DAN and FPCN. To estimate FC, we computed Pearson correlation

coefficients between regional time-series, and for FS, we computed Pearson correlations

between regional feature vectors (Fig. 1). Regions were considered similar in terms of features

if most time-series features—such as entropy, stationarity, and linear correlation properties—

were significantly correlated (Fulcher, 2018). FS captures regions with similar dynamical

properties but not necessarily synchronous activity (Fig. 1). For example, while FPCN-A and

DMN both have longer timescales, they often exhibit negative FC (Wang et al., 2024a).

As expected, regions within the same functional network showed higher FC compared to

those between networks, both at rest (t = 136.09, p < 0.001) and during tasks (spatial working

memory, t = 26.33, p < 0.001; math, t = 26.36, p < 0.001; semantic feature matching, t = 70.02,

p < 0.001; semantic association, t = 57.60, p < 0.001) (Fig. 3). Similarly, FS was higher within

networks compared to between networks, both at rest (t = 91.24, p < 0.001) and across tasks

(spatial working memory, t = 18.35, p < 0.001; math, t = 14.51, p < 0.001; semantic feature

matching, t = 42.27, p < 0.001; semantic association, t = 38.04, p < 0.001) (Fig. 3). All p-values

were FDR-corrected. These findings suggest that FS can capture intrinsic network structure

traditionally measured by FC.

We also assessed the similarity between FC and FS by correlating the FC and FS matrices

at rest and during tasks. We observed weak but significant positive correlations between FC

and FS as indicated by arrows (Fig.3) at rest (r = 0.29, p = 0) and during tasks (spatial working

memory, r = 0.37, p = 0; math, r = 0.33, p = 0; semantic feature matching, r = 0.33, p = 0;

semantic association, r = 0.33, p = 0). All p-values were FWE-corrected using maximum r

values (Method 4.5.4). The positive correlations suggest that regions with similar time-series

features exhibited coherent spontaneous fluctuations. However, the largest correlation was

0.37, indicating that these measures also capture different information.

Fig. 3. The FC matrix and FS matrix at rest and for each task. Regions within the same intrinsic functional network exhibited greater FC and FS than regions in different networks at rest and for each task. FC and FS showed positive but weak correlations at rest and for each task. (***: p < 0.0001).

2.2. FS reveals unique organizational principles beyond FC

Next, we investigated whether FS and FC captured similar or different components of connectivity. Firstly, we performed dimension reduction analysis (diffusion embedding) (Margulies et al., 2016) on the resting state FC matrix for the HCP dataset (Fig. 3A). We focused on the three components with the largest eigenvalues, which explained 28.02% variance in total (see Fig. 4I for scree plot). Consistent with previous studies (Margulies et al., 2016; Wang et al., 2020, 2022, 2024a, 2024b), the first component explaining 12.75% of the variance corresponded to the principal gradient described by Margulies et al. (2016). This component separated sensory-motor regions (shown in purple-blue in Fig. 4A) from transmodal areas (shown in red-white in Fig. 4A). The second component explained 11.29% of the variance and separated somatomotor and auditory cortex (shown in purple-blue in Fig. 4B) from visual cortex (shown in red-white in Fig. 4B). The third component explained 3.98% of the variance and separated FPCN regions (shown in purple-blue in Fig. 4C) from DMN regions (shown in red-white in Fig. 4C).

Similarly, we performed dimension reduction analysis on the resting state FS matrix for the

HCP dataset (Fig. 3F), using the procedures above. The three components with the largest

eigenvalues explained 23.23% of the variance (see Fig. 4I for scree plot). FS captured two

components that were similar to the results for FC, and one not uncovered by FC (Fig. 4). The

first principal component of FS explained 12.19% of the variance and had a distinct spatial

distribution from the first three components of FC: it did not show significant correlations with

any of the components of FC (p > 0.05; Fig. 4D). The next two components of FS were seen in

FC data (Fig. 4). The second component of FS (explaining 7.11% of the variance; Fig. 4E)

aligned with the principal gradient of FC (Fig. 4A), separating sensory-motor from transmodal

cortex, with a strong correlation between components (r = 0.89, p = 0, spin permutation

corrected). The third component of FS (explaining the 3.94% variance; Fig. 4F) corresponded

to the second component of FC (Fig. 4B), separating somatomotor and auditory cortex from

visual cortex, with a strong correlation between components (r = 0.87, p = 0, spin permutation

corrected). These findings further confirm that FS captures meaningful information, i.e.,

organizational principle.

To gain insight into the first component of FS, we investigated its correlation with the map

of intrinsic timescale, which reflects the temporal duration of ongoing inputs that the brain can

process. The first component resembles the distribution of intrinsic timescale reported by Raut

et al. (2020) ,which is longest in transmodal regions (Wolff et al., 2022). We therefore estimated

intrinsic timescale for each parcel by measuring the decay of the temporal autocorrelation

function and quantifying the time taken for the autocorrelation function to reach a threshold of

r= 0.5, which is half of the full width at half maximum (see Murray et al., 2014; Raut et al., 2020

for similar implementation). Higher values indicate longer processing times for ongoing inputs.

Our results align with Raut et al. (2020), showing short timescales in the insula and cingulate

cortex, and long timescales in the angular gyrus, posterior cingulate cortex, and frontal pole.

(Fig. 4G). We found that the first principal component, which explained the most variance in FS,

was significantly correlated with the intrinsic timescale map (left hemisphere: r = 0.82, p = 0;

right hemisphere: r = 0.80, p = 0; Fig. 4H, corrected for spatial autocorrelation using spin

permutation), indicating that FS can capture meaningful information not captured by traditional

FC, such as the intrinsic timescale of the brain's response.

Fig. 4. The top three principal components of FC and FS. FC and FS captured two similar

principal components and one distinct component. The first principal component of FC (A)

corresponds to the second principal component of FS (E), as indicated by the arrows denoting

a strong correlation (r = 0.89, p = 0, corrected for spatial autocorrelation using spin permutation),

which separates sensory-motor regions from transmodal areas. Similarly, the second principal

component of FC (B) corresponds to the third principal component of FS (F), with a strong

correlation (r = 0.87, p = 0, corrected for spatial autocorrelation using spin permutation),

separating somatomotor and auditory cortex from visual cortex. These findings suggest that FS

captures similar organizational information to FC. However, the third principal component of FC

(C), which separates FPCN regions from DMN regions, was not captured by FS. The first

principal component of FS (D), which corresponds to the intrinsic timescale gradient (G), was

not captured by FC. (G) The intrinsic timescale map shows short timescales in the insula and

cingulate cortex, and long timescales in the angular gyrus, posterior cingulate cortex, and

frontal pole. (H) The first principal component of FS was significantly correlated with the intrinsic timescale gradient map in both the left (r = 0.82, p = 0) and right (r = 0.80, p = 0) hemispheres (corrected for spatial autocorrelation using spin permutation). The histograms illustrate the null model distributions. (I) Scree plots showing the eigenvalues for the top eight principal components of FS (orange) and FC (blue).

2.3. FS showed greater variation across tasks than FC

The above analyses showed that FS captured similar information to FC but also additional dimensions of cortical organisation. Next, we examined whether FS was more sensitive to task modulation than FC. FC measures the temporal correlation between time-series from different brain regions, focusing on the synchrony of neural activity. In contrast, FS extracts a comprehensive set of features from the time-series, such as entropy, stationarity, and autocorrelation, providing a multidimensional profile of the brain's activity. Given that tasks impose specific cognitive demands and engage distinct neural processes, the brain's functional organization undergoes modulation at multiple levels. Temporal correlation (as captured by FC) may remain stable under certain conditions, but the underlying features of the time-series, such as signal complexity, variability, and temporal autocorrelation, may exhibit more sensitivity to these changes. This multidimensional analysis may allow FS to detect subtle changes in brain dynamics during tasks that may be missed by FC.

We computed the Pearson correlation coefficients of the task mean FC matrices for every possible combination pair of tasks. For example, we calculated the Pearson correlation coefficients of the FC matrices of the spatial working memory task (Fig. 3B) and math task (Fig. 3C). Similarly, we calculated the Pearson correlation coefficients of the FS matrices of these two tasks (Fig. 3G and 3H). Then we directly compared these two r values. We found correlations for FC were consistently higher than those for FS for every task pair (Fig. 5A; p < 0.05; see Table 1 for statistics), suggesting that FS may be more sensitive to task differences than FC.

The task sensitivity of FS was further confirmed when we compared the correlations of FS

with those of FC between two non-semantic tasks for each participant. Since the same participants completed both the spatial working memory task and the math task, we calculated the Pearson correlation coefficients between the FC matrix of the spatial working memory task and that of math task for each participant and transformed the resulting r values to z values using Fisher's transformation. Similarly, we also calculated the Fisher's z values between the FS matrices of the two non-semantic tasks for each participant. Finally, we compared the z values of FC with those of FS by conducting paired t-tests. We found that the correlations of FC were greater than the correlations of FS for the non-semantic tasks (Fig. 5B; t = 26.58, p < 0.001). We then conducted the same analysis for the two semantic tasks, semantic feature matching and association, and observed the same pattern (i.e., stronger correlation across tasks for FC than for FS; Fig. 5C, t = 23.29, p < 0.001). The smaller correlation of FS is not because the data of FS are noisier. By contrast, FS carries meaningful task information, as FS matrices correctly classify task labels for non-semantic tasks (accuracy = 0.83, p = 0) and semantic tasks (accuracy = 0.78, p = 0), both significantly above chance level (0.5) (see SM 2.1 for detailed results). These findings suggest that FS is more sensitive to task modulation than FC, as FS takes into account multiple aspects of time-series similarity, whereas FC reflects only one.

Fig. 5. FS showed smaller correlations across tasks than FC. A – The group mean FC matrices

showed higher correlations across tasks compared to FS matrices. Each dot represents the

correlation coefficient between two tasks, with 10 possible combinations among the four tasks.

B – The correlations of FC matrices for spatial working memory and math task were greater

than the correlations of FS matrices. Each dot represents the correlation coefficient between

the two task-specific matrices of one participant. C – The correlations of FC matrices for

semantic feature matching and semantic association task were significantly greater than the

correlations of FS matrices for these two tasks. Each dot represents the correlation coefficient

between the two task-specific matrices of one participant.

Table 1. FS showed greater variation across tasks than FC.

Task 1	Task 2	r (FC)	r (FS)	z	p
Rest	Spatial working memory	0.68	0.33	96.31	0
Rest	Math	0.67	0.38	82.64	0
Rest	Feature matching	0.86	0.68	82.48	0
Rest	Association	0.88	0.68	110.49	0
Spatial working memory	Math	0.75	0.43	103.38	0
Spatial working memory	Feature matching	0.73	0.42	94.50	0
Spatial working memory	Association	0.71	0.42	88.63	0
Math	Feature matching	0.75	0.43	103.38	0
Math	Association	0.73	0.43	93.72	0
Feature matching	Association	0.98	0.94	86.35	0

291 2.4. FS captured network interaction patterns across tasks not captured by FC

292 　　After showing that FS was generally more sensitive to task modulation than FC, we

293 examined whether FS could capture the varying network interaction patterns across tasks that

294 missed by FC. We tested the interaction difference between DAN and Visual network versus

DAN and DMN, to test the hypothesis that DAN is more similar to Visual network in non-semantic tasks, which rely more on visual features and working memory, and more similar to DMN in semantic tasks, which rely more on long-term memory. We expected that this pattern would be seen more readily in FS, since this metric was more sensitive than FC to task demands above.

Since the tasks were presented visually in the current study, we selected DAN-A (Kong et al., 2021), which is typically engaged together with Visual network and showed greater feature similarity with Visual network than other attention networks (DAN-B, Ventral attention network) in a classification analysis (Fig. S1). We compared FC and FS between DAN-A and Visual network versus DAN-A and DMN across tasks, focusing on differences in the strength of these connections. For simplicity, we combined the three visual subnetworks into a single visual network and the three default mode subnetworks into a single DMN. While connectivity differences did not vary across tasks when assessed with FC (Fig. 6, $p > 0.05$, FWE corrected), there was a difference between non-semantic and semantic tasks for FS ($p < 0.001$; FWE corrected). DAN-A always showed greater FC with Visual network than with DMN at rest (Fig. 6, $t = 53.68$, $p < 0.001$) and for each task (Fig. 6, spatial working memory, $t = 16.19$, $p < 0.001$; math, $t = 11.73$, $p < 0.001$; semantic feature matching, $t = 17.19$, $p < 0.001$; semantic association, $t = 14.95$, $p < 0.001$), consistent with previous studies. However, DAN-A showed greater FS with Visual network than with DMN at rest (Fig. 5, $t = 10.58$, $p < 0.001$) and in non-semantic tasks (Fig. 5, spatial working memory, $t = 3.55$, $p = 0.004$; math, $t = 3.19$, $p = 0.003$), but showed the opposite pattern in semantic tasks (Fig. 5, semantic feature matching, $t = -2.86$, $p = 0.008$; semantic association, $t = -2.64$, $p = 0.01$). These findings suggest that FS is more sensitive to dynamic interaction patterns between networks that reflect differing cognitive demands.

Fig. 6. FS captured varying interaction patterns for DAN-A across tasks that missed by FC. Top panel: DAN-A always showed greater FC with Visual network than with DMN at rest and for each task and there was no difference across tasks. Bottom panel: The difference between DAN-A and Visual network versus DAN-A and DMN in the non-semantic tasks was greater than in semantic tasks. DAN-A showed greater FS with Visual network than with DMN at rest and for the non-semantic tasks, but showed the opposite pattern in the semantic tasks that relied on long-term memory supported by DMN.

The task sensitivity of FS was further confirmed when we examined the interaction differences between the domain general control network (FPCN-A) and Visual network versus FPCN-A and DMN. Interaction difference for FPCN-A across tasks were only captured by FS and not by FC (Fig. S2; See SM 2.3 for detailed information). There was no difference in FC across tasks for FPCN-A ($p > 0.05$, FWE corrected), with FPCN-A always showing greater FC with Visual network than with DMN at rest ($t = 2.39$, $p = 0.02$) and for each task (spatial working memory, $t = 11.36$, $p < 0.001$; math, $t = 11.44$, $p < 0.001$; semantic feature matching, $t = 6.50$, $p < 0.001$; semantic association, $t = 3.62$, $p = 0.001$). However, FS revealed different patterns across tasks, with a greater difference between FPCN-A and Visual network compared with FPCN-A and DMN for the non-semantic than semantic tasks ($p < 0.001$; FWE corrected).

Specifically, FPCN-A showed similar FS with Visual network and DMN at rest (t = 1.39, p = 0.17)

and in the math task (t = -0.73, p = 0.47) but showed greater FS with DMN than with Visual

network in the spatial working memory task (t = -4.97, p < 0.001) and semantic tasks (semantic

feature matching, t = -9.12, p < 0.001; semantic association, t = -8.25, p < 0.001). These findings

support that FS is more sensitive to task modulation than FC.

3. Discussion

In this study, we demonstrate that FS serves as a robust index for unveiling network

structures, brain topography, and task modulations. The validation of FS was supported by two

observations: (1) regions belonging to the same intrinsic functional network exhibited greater

FS compared to regions in distinct networks, and (2) FS captured the principal gradient that

organizes neural systems along a spectrum from unimodal to transmodal cortex, with sensory-

motor regions situated at one end and transmodal areas at the other. Furthermore, our study

expands upon prior research by demonstrating that FS exhibits greater sensitivity to task

modulation. Under specific conditions, FS reveals unique interaction patterns that remain

undetected by FC. For instance, DAN-A exhibits greater FC with Visual network than DMN

during both working memory and long-term memory tasks. However, DAN-A displays greater

FS with Visual network than DMN in working memory tasks and the opposite pattern in long-

term memory tasks, suggesting a shift in DAN-A features towards DMN in semantic tasks where

long-term memory supported by DMN is required. The discrepancies in interaction patterns

between FC and FS indicate that certain patterns can only be discerned through FS. The task

sensitivity of FS is further substantiated by examining the interaction patterns of the FPCN-A.

Collectively, these findings suggest that FS is a promising method for uncovering network

interaction patterns and functions.

Our findings suggest that FS is a more suitable approach for studying interaction patterns

across multiple cognitive domains than FC, given it is more sensitive to task effects. The brain

functions as an information processing and transfer system, wherein networks supporting

various functions must coordinate with one another to facilitate complex cognitive processes,

such as memory retrieval (Shine et al., 2019). Furthermore, investigating the interaction

patterns of brain networks can offer a more refined understanding of the brain's functional organization, which is not static. Nevertheless, interaction patterns have predominantly been investigated using FC, which may have limited our understanding of the flexible nature of network connectivity, given its limited sensitivity to task modulation. We propose it may be beneficial to reanalyse existing fMRI data using FS and re-evaluate previous findings drawn using FC, to generate novel insights, resolve inconsistencies, revise existing theories, and propose new theoretical frameworks.

While we advocate the use of FS for reanalysing existing data, this does not imply that FC is without merit. FS serves as a complementary measure to FC, which remains valuable for comprehending the general functional architecture of the brain, for example, as shaped by neuroanatomy. FC is particularly adept at revealing coupling patterns of intrinsic activity. For instance, DMN regions exhibit greater FC with each other at rest and during various conditions and this functional similarity is thought to be at least partly related to their anatomical location at a maximum distance from primary sensory-motor cortex (Margulies et al., 2016) and by the strong influence of spatial proximity on connectivity patterns. Yet these observations might underplay the dynamic nature of connectivity patterns and their sensitivity to changes in cognitive state. DMN regions display no ISFC at rest, nor when participants listen to scrambled words or individual words – although they do exhibit ISFC when participants listen to sentences and paragraphs (Simony et al., 2016). This observation suggests that FC is predominantly influenced by intrinsic activity, while ISFC is driven by stimulus-related activity during states of coherent semantic cognition. Since FC, ISFC and FS convey distinct information, combining these methods can offer a comprehensive understanding of the brain's functionality.

Although this study highlights the increased sensitivity of FS to task modulation, the specific features that change across tasks have yet to be determined. It is imperative for future research to identify and interpret features. For instance, we demonstrated that the DAN-A exhibits greater FS with Visual network than DMN in non-semantic tasks, wherein participants focus more on external visual information. Conversely, DAN-A displays greater FS with DMN than Visual network in semantic tasks, where participants rely on long-term memory. Given that

approximately 7,000 features were extracted and employed in calculating FS, future research

can pinpoint the specific features that vary across these tasks. While our results demonstrate

that FS can exhibit greater sensitivity to task modulation than FC in specific datasets and

networks, this finding does not imply that feature similarity is universally superior. Therefore,

our study should be viewed as an illustration of the potential advantages of FS, rather than a

definitive conclusion about its superiority in all contexts. Future investigations should

encompass a more extensive array of diverse tasks.

Conclusion

Our results demonstrate that Feature Similarity (FS) offers a significant methodological

advancement in understanding dynamic brain network interactions. While traditional functional

connectivity (FC) methods have provided valuable insights, FS is more sensitive and reliable

in capturing subtle changes in network interactions, particularly across different cognitive states.

Just as motion tracking software has revolutionized the study of animal behaviour by enabling

precise analysis of how animals interact in different social contexts, we argue that FS

represents a similar breakthrough in neuroimaging—enhancing our ability to assess brain

function and cognitive flexibility with greater precision. While experimental designs and

neuroimaging hardware continue to improve, FS provides a powerful tool for reanalysing

existing fMRI datasets, resolving inconsistencies, and advancing our theoretical understanding

of cognitive flexibility. Ultimately, FS could become an essential tool for exploring the adaptive

nature of brain network dynamics.

4. Materials and Methods

This study included three datasets, one publicly available dataset – the Human

Connectome Project (HCP), and two task fMRI datasets collected at the University of York, UK.

We analysed the resting state functional MRI (rsfMRI) data of 245 unrelated participants

who completed all four resting state scans from the S900 release of HCP dataset to investigate

the functional hierarchy, FC, and FS patterns. In addition, to compare whether FC and FS can

capture varying interaction patterns to the same extent, we used two types of tasks (tapping working memory and long-term memory retrieval) which are associated with distinct neurocognitive modes (Wang et al., 2020). To tap working memory, participants completed easy and hard spatial working memory and arithmetic tasks designed to localise domain general control regions (Blank et al., 2014; Fedorenko et al., 2013, 2011; Wang et al., 2020, 2021, 2022, 2024a), which required information to be maintained and manipulated. They also completed two semantic tasks tapping knowledge in long-term memory, a semantic feature matching task that involved linking probe and target concepts (presented as written words) based on colour or shape, and a semantic association task in which participants decided if pairs of words were semantically associated or not (Wang et al., 2024a, 2024b). These datasets have been previously analysed (Wang et al., 2024a, 2024b).

4.1. Participants

All participants were right-handed, native English speakers, had normal or corrected-to-normal vision, and had no history of psychiatric or neurological illness. For the HCP dataset, informed consent was obtained, and the study was approved by the Institutional Review Board of Washington University at St. Louis. For the York non-semantic and semantic dataset, the research was approved by the York Neuroimaging Centre and Department of Psychology ethics committees.

We analysed the data of 245 neurologically healthy volunteers (130 males, 115 females), aged 23 – 35 years (mean = 28.21, SD = 3.67), from the HCP dataset (Glasser et al., 2013).

31 neurologically healthy adults (26 females; age: mean ± SD = 20.60 ± 1.68, range: 18 – 25 years) performed spatial working memory and math tasks in York. One participant with incomplete data (only one of two sessions) was removed. A functional run was excluded if (i) mean relative root mean square (RMS) framewise displacement was higher than 0.2 mm, (ii) it had more than 15% percentage of total frames with motion exceeding 0.25 mm, or (iii) a participant's accuracy on the respective task was three standard deviations below the group mean. If only run of one task was left for a given participant after exclusion, the data from this

task were removed for this participant. These exclusion criteria resulted in a final sample of 27

participants for both the spatial working memory task and the math task.

We also analysed a semantic task dataset collected at the University of York, UK. 31

healthy adults were recruited from the University of York (25 females; age: mean ± SD = 21.26

± 2.93, range: 19 – 34 years). The same exclusion criteria for functional runs were applied as

above. For the feature matching task, this left 23 participants with 4 runs, 4 participants with 3

runs, and 1 participant with 2 runs. For the association task, there were 24 participants with 4

runs, 3 participants with 3 runs, and 3 participants with 2 runs. To select experimental materials,

we recruited 30 native English speakers who did not participate in the main fMRI experiment

as subjects (21 females; age range: 18 – 24 years). These individuals rated the color and shape

similarity as well as the semantic association strength for each word pair.

4.2. Tasks paradigms

4.2.1. Spatial working memory task

Participants were required to maintain four or eight sequentially presented locations in a

3×4 grid (Fedorenko et al., 2011), giving rise to easy and hard spatial working memory

conditions. Stimuli were presented at the center of the screen across four steps. Each of these

steps lasted for 1s and highlighted one location on the grid in the easy condition, and two

locations in the hard condition. This was followed by a decision phase, which showed two grids

side by side (i.e., two-alternative forced choice (2AFC) paradigm). One grid contained the

locations shown on the previous four steps, while the other contained one or two locations in

the wrong place. Participants indicated their response via a button press and feedback was

immediately provided within in 2.5s. Each run consisted of 12 experimental blocks (6 blocks

per condition and 4 trials in a 32 s block) and 4 fixation blocks (each 16 s long), resulting in a

total time of 448 s.

4.2.2. Math task

Participants were presented with an addition expression on the screen for 1.45s and,

subsequently made a 2AFC decision indicating their solution within 1s. The easy condition used

single-digit numbers while the hard condition used two-digit numbers. Each trial ended with a

blank screen lasting for 0.1s. Each run consisted of 12 experimental blocks (with 4 trials per

block) and 4 fixation blocks, resulting in a total time of 316s.

4.2.3. Semantic feature matching task

Participants were required to make a yes/no decision matching probe and target concepts

(presented as words) according to a particular semantic feature (colour or shape), specified at

the top of the screen during each trial. The feature prompt, probe word, and target words were

presented simultaneously. Half of the trials were matching trials in which participants would be

expected to identify shared features; while half of the trials were non-matching trials in which

participants would not be expected to identify shared features. For example, in a colour

matching trial participants would answer 'yes' to the word-pair DALMATIANS – COWS, due to

their colour similarity, whereas they would answer 'no' to COAL -TOOTH as they do not share

a similar colour.

This task included four runs and two conditions (two features: colour and shape),

presented in a mixed design. Each run consisted of four experimental blocks (two 150s blocks

per feature), resulting in a total time of 612s. In each block, 20 trials were presented in a rapid

event-related design. In order to maximize the statistical power of the rapid event-related fMRI

data analysis, the stimuli were presented with a temporal jitter randomized from trial to trial

(Dale, 1999). The inter-trial interval varied from 3 to 5 s. Each trial started with a fixation,

followed by the feature, probe word, and target word presented centrally on the screen,

triggering the onset of the decision-making period. The feature, probe word, and target word

remained visible until the participant responded, or for a maximum of 3 s. The condition order

was counterbalanced across runs and run order was counterbalanced across participants. Half

of the participants pressed a button with their right index finger to indicate a matching trial and

responded with their right middle finger to indicate a non-matching trial. Half of the participants

pressed the opposite buttons.

4.2.4. Semantic association task

Participants were asked to decide if pairs of words were semantically associated or not (i.e., yes/no decision as above) based on their own experience. Overall, there were roughly equal numbers of 'related' and 'unrelated' responses across participants. The same stimuli were used in the semantic feature matching task and semantic association task. For example, DALMATIANS and COWS are semantically related; COAL and TOOTH are not. The feature and association tasks were often separated by one week. This task included four runs, presented in a rapid event-related design. Each run consisted of 80 trials, with about half being related and half being unrelated trials. The procedure was the same as the feature matching task except only two words were presented on the screen.

4.3. Image acquisition

4.3.1. Image acquisition for HCP dataset

MRI acquisition protocols of the HCP dataset have been previously described by Barch et al., (2013) and Glasser et al., (2013). Images were acquired using a customized 3T Siemens Connectome scanner having a 100 mT/m SC72 gradient set and using a standard Siemens 32-channel radiofrequency receive head coil. Participants underwent the following scans: structural (at least one T1-weighted (T1w) MPRAGE and one 3D T2-weighted (T2w) SPACE scan at 0.7-mm isotropic resolution), rsfMRI (4 runs ×14 min and 33 s), and task fMRI (7 tasks, 46.6 min in total). Since not all participants completed all scans, we only included 339 unrelated participants from the S900 release. Whole-brain rsfMRI and task fMRI data were acquired using identical multi-band echo planar imaging (EPI) sequence parameters of 2-mm isotropic resolution with a TR = 720 ms. The dMRI data consisted of one 1.25 mm isotropic scan for each participant with 3 shell HARDI type acquisition, including b = 1000, 200, 3000 s/mm^2, total for 270 non-collinear directions. Spin echo phase reversed images were acquired during the fMRI scanning sessions to enable accurate cross-modal registrations of the T2w and fMRI images to the T1w image in each subject and standard dual gradient echo field maps were acquired to correct T1w and T2w images for readout distortion. Additionally, the spin echo field

maps acquired during the fMRI session (with matched geometry and echo spacing to the gradient echo fMRI data) were used to compute a more accurate fMRI bias field correction and to segment regions of gradient echo signal loss.

Subjects were considered for data exclusion based on the mean and mean absolute deviation of the relative root-mean-square motion across either four rsfMRI scans, resulting in four summary motion measures. If a subject exceeded 1.5 times the interquartile range (in the adverse direction) of the measurement distribution in two or more of these measures, the subject was excluded. In addition, functional runs were flagged for exclusion if more than 25% of frames exceeded 0.2 mm frame-wise displacement (FD_power). These above exclusion criteria were established before performing the analysis，(for similar implementation, see Faskowitz et al., 2020; Sporns et al., 2021). The data of 91 participants was excluded because of excessive head motion and the data of another 3 participants was excluded because their resting data did not have all the time points. In total, the data of 245 participants was analysed after exclusions.

4.3.2. Image acquisition for York non-semantic dataset

MRI acquisition protocols have been described previously (Wang et al., 2020; 2021; 2022; 2024a; 2024b). Structural and functional data were collected on a Siemens Prisma 3T MRI scanner at the York Neuroimaging Centre. The scanning protocols included a T1-weighted MPRAGE sequence with whole-brain coverage. The structural scan used: acquisition matrix of $176 \times 256 \times 256$ and voxel size $1 \times 1 \times 1$ mm^3, repetition time (TR) = 2300 ms, and echo time (TE) = 2.26 ms. Functional data were acquired using an EPI sequence with an 800 flip angle and using GRAPPA with an acceleration factor of 2 in 3 x 3 x 4 mm voxels in 64-axial slices. The functional scan used: 55 3-mm-thick slices acquired in an interleaved order (with 33% distance factor), TR = 3000 ms, TE = 15 ms, FoV = 192 mm.

4.3.3. Image acquisition for York semantic dataset

MRI acquisition protocols have been described previously (Wang et al., 2024a; 2024b).

Whole brain structural and functional MRI data were acquired using a 3T Siemens MRI scanner utilising a 64-channel head coil, tuned to 123 MHz at York Neuroimaging Centre, University of York. The functional runs were acquired using a multi-band multi-echo (MBME) EPI sequence, each 11.45 minutes long (TR=1.5 s; TEs = 12, 24.83, 37.66 ms; 48 interleaved slices per volume with slice thickness of 3 mm (no slice gap); FoV = 24 cm (resolution matrix = 3x3x3; 80x80); 75° flip angle; 455 volumes per run; 7/8 partial Fourier encoding and GRAPPA (acceleration factor = 3, 36 ref. lines); multi-band acceleration factor = 2). Structural T1-weighted images were acquired using an MPRAGE sequence (TR = 2.3 s, TE = 2.3 s; voxel size = 1x1x1 isotropic; 176 slices; flip angle = 8°; FoV= 256 mm; interleaved slice ordering). We also collected a high-resolution T2-weighted (T2w) scan using an echo-planar imaging sequence (TR = 3.2 s, TE = 56 ms, flip angle = 120°; 176 slices, voxel size = 1x1x1 isotropic; Fov = 256 mm).

4.4. Image pre-processing

4.4.1. Image pre-processing of HCP dataset

We used HCP's minimal pre-processing pipelines (Glasser et al., 2013). Briefly, for each subject, structural images (T1w and T2w) were corrected for spatial distortions. FreeSurfer v5.3 was used for accurate extraction of cortical surfaces and segmentation of subcortical structures (Dale et al., 1999; Fischl et al., 1999). To align subcortical structures across subjects, structural images were registered using non-linear volume registration to the Montreal Neurological Institute (MNI152) space. Functional images (rest and task) were corrected for spatial distortions, head motion, and mapped from volume to surface space using ribbon-constrained volume to surface mapping.

Subcortical data were also projected to the set of extracted subcortical structure voxels and combined with the surface data to form the standard CIFTI grayordinate space. Data were smoothed by a 2-mm FWHM kernel in the grayordinates space that avoids mixing data across gyral banks for surface data and avoids mixing areal borders for subcortical data. Rest and task fMRI data were additionally identically cleaned for spatially specific noise using spatial ICA+FIX

(Salimi-Khorshidi et al., 2014) and global structured noise using temporal ICA (Glasser et al.,

2018). For accurate cross-subject registration of cortical surfaces, a multimodal surface

matching (MSM) algorithm (Robinson et al., 2014) was used to optimize the alignment of

cortical areas based on features from different modalities. MSMSulc ("sulc": cortical folds

average convexity) was used to initialize MSMAll, which then utilized myelin, resting state

network, and rfMRI visuotopic maps. Myelin maps were computed using the ratio of T1w/T2w

images (Salimi-Khorshidi et al., 2014). The HCP's minimally preprocessed data include cortical

thickness maps (generated based on the standardized FreeSurfer pipeline with combined T1-

/T2-reconstruction). For this study, the standard-resolution cortical thickness maps (32k mesh)

were used.

4.4.2. Image pre-processing of York non-semantic and semantic dataset

The York datasets were preprocessed using fMRIPrep 20.2.1 [(Esteban et al., 2018),

RRID:SCR_016216], with detailed methods previously described in (Wang et al., 2024a,

2024b). In brief, anatomical preprocessing involved intensity non-uniformity correction, skull

stripping, segmentation, and surface reconstruction. Spatial normalization to MNI152 templates

was performed through nonlinear registration. For each BOLD run, functional data

preprocessing followed standard fMRIPrep procedures. This included generating a reference

volume, applying fieldmap correction, and co-registering the BOLD reference to anatomical

space. Motion correction and slice-time correction were performed. Resampling was done in

the surface space - fsaverage, and final data were output in CIFTI grayordinate space. Post-

processing of fMRIPrep outputs was performed using eXtensible Connectivity Pipeline (XCP)

(Ciric et al., 2018). Volumes with framewise displacement greater than 0.3 mm were excluded

before nuisance regression. A total of 36 nuisance regressors, including motion parameters,

global signal, white matter, and CSF signals, were regressed. Residual time-series were band-

pass filtered (0.01-0.08 Hz) and smoothed with a 6.0 mm FWHM Gaussian kernel. Detailed

information is provided in Supplementary Materials and Methods, Section 1.1.

4.5. Task fMRI analysis

4.5.1. Individual-specific parcellation

To account for anatomical and functional variability, we used a multi-session hierarchical Bayesian model to estimate individual-specific parcellations, following the methods in Kong et al., (2021, 2019). This approach defines 400 individualized parcels across 17 networks per participant and the individual-specific parcellation showed greater homogeneity than the parcellation using group atlas (Kong et al., 2021a; Wang et al., 2024a). All subsequent analyses were based on parcel-specific time-series. Detailed information is provided in Supplementary Materials and Methods, Section 1.2.1.

4.5.2. Constructing fMRI FC matrices

To investigate how FC varies across tasks, we computed task-based and resting state FC matrices. We opted not to use the traditional psychophysiological interaction (PPI) method for measuring task-state functional connectivity due to its potential to inflate activation-induced task-state functional connectivity, which may identify regions that are active rather than interacting during the task (Cole et al., 2019). Since task activations can spuriously inflate task-based functional connectivity estimates, it is necessary to correct for task-timing confounds by removing the first-order effect of task-evoked activations (i.e., mean evoked task-related activity, likely active during the task) prior to estimating task-state functional connectivity (likely interacting during the task) (Cole et al., 2019). Specifically, we fitted the task timing for each task using a finite impulse response (FIR) model, a method that has been shown to reduce both false positives and false negatives in FC estimation (Cocuzza et al., 2020; McCormick et al., 2022; Norman-Haignere et al., 2012). In semantic tasks, approximately 5 timepoints were modeled for each trial. For the non-semantic task, roughly 2.5 timepoints were modeled for each trial.

Following task regression, we demeaned the residual time series for each parcel and quantified the FC using Pearson correlation for each participant, task and run. The Pearson

correlation coefficients might be inflated due to the temporal autocorrelation in task fMRI time

series data (Allefeld et al., 2008). To address this, we corrected the Pearson correlation using

a correction approach, xDF, which accounts for both autocorrelation within each time series as

well as instantaneous and lagged cross-correlations between the time series (Afyouni et al.,

2019). This method provides an effective degrees of freedom estimator that addresses cross-

correlations, thereby preventing inflation of Pearson correlation coefficients. Our goal was not

to remove temporal autocorrelation, but to enhance the precision and reliability of correlation

estimates, reducing false functional connectivity between regions. We calculated xDF-adjusted

z-scored correlation coefficients to assess the interregional relationships in BOLD time series,

resulting in a 400 × 400 functional connectivity matrix for each participant, task, and run. Finally,

we averaged these functional connectivity estimates within networks, and between pairs of

networks, to construct a network-by-network functional connectivity matrix. The same method

was used to calculate the resting-state functional connectivity of the HCP dataset and construct

a corresponding network-by-network functional connectivity matrix, except without the task

regression step.

4.5.3. Feature extraction of the time-series data

To investigate how the FS patterns vary across tasks, we calculated task-based and

resting state FS using the extracted features. To extract the features of the time-series required

for this analysis, we used the time-series analysis toolbox (hctsa) (Fulcher et al., 2013; Fulcher

and Jones, 2017). With this tool, we transformed each time-series in the dataset into a set of

over 7,700 features, which include, but are not limited to, distributional properties, entropy and

variability, autocorrelation, time-delay embeddings, and nonlinear properties of a given time-

series (see Fig. 1; Fulcher, 2018; Fulcher et al., 2013). We extracted features from the

parcellated fMRI time-series of each participant, each task, and each run separately. After the

feature extraction procedure, we removed the outputs of the operations that produced errors

and normalized the remaining features (about 6900 features) across parcels using an outlier-

robust sigmoidal transform. The resulting normalized feature matrix (400 parcels × ~7000

features × 4 runs) was used to predict networks labels of parcels to identify the DAN subnetwork

with varying interaction patterns across tasks (Method 4.5.4) and to construct FS matrix for

further analysis (Method 4.5.4).

4.5.4. Constructing fMRI FS matrices

To investigate how FS patterns vary across tasks, we calculated task-based and resting

state FS matrices. Specifically, we calculated Pearson correlation coefficients of the extracted

features, which represented the pairwise FS between all possible combinations of brain parcels

(see Fig. 1). This resulted in a 400 by 400 FS matrix for each run each task for each participant.

Finally, to construct a network-by-network FS matrix, we averaged the estimates of FS within

networks and between pairs of networks for further analysis.

To investigate whether functionally connected regions display similar features, we

calculated Pearson correlations coefficients for FS within and between networks defined by

resting state FC. Then we tested whether the correlations for FS within networks were greater

than the correlations between networks.

Additionally, we estimated the similarity between FC and FS by calculating their

correlations at rest and for each task. To control for multiple comparison, we FWE-corrected

the p values using permutation-based maximum r values. Specifically, we created a null

distribution using permutation for each task and chose the maximum values among all the tasks.

We then compared the observed correlation value with the null distribution to examine whether

the correlation between FC and FS was significantly greater than that expected from null

distribution.

4.5.5. Dimension reduction analysis of FC and FS

To examine whether FC and FS captured similar principal components, we performed

dimension reduction analysis on both resting state FC matrix and FS matrix derived from the

HCP dataset. For the FC matrix, we first calculated resting state FC for each run of each

participant, as detailed in Method section 2.5.2. Subsequently, these individual connectivity

matrices were then averaged to calculate a group-level connectivity matrix. We extracted ten

group-level gradients from the group-level connectivity matrix (dimension reduction technique = diffusion embedding, kernel = None, sparsity = 0.9), in line with previous studies (Mckeown et al., 2020; Wang et al., 2020) using the Brainspace Toolbox (Vos de Wael et al., 2020). This analysis resulted in ten group-level gradients explaining maximal whole-brain connectivity variance in descending order. A parallel analysis was performed for the FS matrix, employing identical procedures except for the input, which consisted of the FS matrix as delineated in Method Section 2.5.4. This analysis resulted in ten group-level gradients explaining maximal whole-brain FS variance in descending order. We retained the components explaining the most variance by looking at the eigenvalues of each component in the scree plots shown in Fig 3.

Finally, we examined the similarities between the first three components captured by FC and FS, respectively via calculating the Pearson correlations between corresponding components. Due to the spatial autocorrelation present in each principal component, we created a null distribution using spin permutation implemented in BrainSMASH (Burt et al., 2020). This approach simulates brain maps, constrained by empirical data, that preserve the spatial autocorrelation of cortical parcellated brain maps. We then compared the observed correlation value with the null distribution for left hemisphere to examine whether the correlation between two components of parcels in the left hemisphere was significantly greater than that expected from spatial autocorrelation alone. Similarly, we examined the correlation between two components of parcels in the right hemisphere using the same methods. This analysis was performed for the two hemispheres separately because the geodesic distance between parcels was used to generate the spatial-autocorrelation-preserving surrogate maps when creating the null distribution. It was only possible to measure within-hemisphere geodesic distance between parcels because the left and right hemisphere surface maps were not on the same mesh.

4.5.6. Timescale analysis

The first component captured by FS matrix was similar to the timescale gradient map reported by (Raut et al.,2020), as determined by visual comparison. To further understand this component, we calculated its correlation with the intrinsic timescale gradient map, which represents the temporal duration of ongoing inputs that the brain can process. The intrinsic

timescale for each parcel was characterized by the decay of the temporal autocorrelation

function, as the time taken for the autocorrelation function to reach a threshold of $r = 0.5$ (i.e.,

half of the full width at half maximum), consistent with prior studies (Murray et al., 2014; Raut

et al., 2020). A higher value of the intrinsic timescale indicates longer ongoing inputs that the

parcel can process. Given the spatial autocorrelation present in this component and the

timescale gradient map, we created a null distribution using spin permutation implemented in

BrainSMASH (Burt et al., 2020). We subsequently compared the observed correlation value

with the null distribution for each hemisphere to determine whether the real correlations were

significantly greater than that expected by spatial autocorrelation alone.

4.5.7. Calculating the correlations across tasks in FC and in FS

To test whether FS was more sensitive to task modulation than FC, we calculated

correlations across tasks for both measures and compared their sensitivities by assessing if FS

showed weaker correlations than FC. We used two methods: (i) we first calculated Pearson

correlations (r1) for FC across tasks for each possible pair of tasks at the group level (for

instance, between the spatial working memory and math tasks) using the task mean FC

matrices. Then, we repeated the process for FS (r2), using the task mean FS matrices. Finally,

we then compared the resulting correlation values (r1 versus r2). (ii) We calculated the Pearson

correlation coefficients between the FC matrix of the spatial working memory task and the FC

matrix of math task at the individual level for each participant given that each participant

completed both spatial working memory task and math task. Then we repeated the process for

FS, using the FS matrix of each participant. Finally, we converted the r values to z values using

Fisher transformation and compared the z values of the FC with the ones of the FS by

conducting paired t-tests. The same procedures were applied to the two semantic tasks

(semantic feature matching versus association).

4.5.8. Classification analysis – decoding task labels using FS matrix

To determine whether feature similarity captures task information, we conducted

classification analyses to predict task labels (spatial working memory versus math) using FS

matrices of the non-semantic tasks of all the participants, respectively. We employed scikit-learn's (Pedregosa et al., 2011) linear support vector machine classifier (SVC) with 5-fold cross-validation to avoid overfitting and ensure reliable performance. To assess statistical significance, we performed permutation tests by shuffling task labels 1,000 times, creating a null distribution for comparison (Ojala and Garriga, 2010). The same approach was used for semantic tasks (semantic feature matching versus. semantic association) using feature similarity matrices of semantic tasks.

4.5.9. Comparing FC difference and FS difference between networks across tasks

To investigate whether FS captured varying interaction patterns across tasks that could not be captured by FC, we first calculated the average FC between DAN-A and Visual network and between DAN-A and DMN, across all runs per participant per task. Subsequently, we calculated the relative FC difference by subtracting the FC between DAN-A and DMN from the FC between DAN-A and Visual network. Finally, we conducted paired-t tests for each task to examine the significance of the FC difference between network pairs. We further investigated whether the task influenced the FC difference between network pairs using the maximum/minimum permutation test. We calculated the mean FC difference between DAN-A and Visual network versus DAN-A and DMN for each task and calculated the mean FC difference between each task pair. To access statistical significance, we permutated the task label 10000 times and then calculated the mean FC difference between these two tasks to build a null distribution for each task pair. To control the family-wise error (FWE) rate ($p = 0.05$, FWE-corrected) given the inclusion of multiple task pairs, we utilized the permutation-based maximum mean FC difference and minimum mean FC difference values in the null distribution for each task pair. To evaluate significance, if the observed mean difference value was positive, we counted the percentage of times that mean difference values in the maximum null distribution were greater than the observed 'true' mean difference values. Conversely, if the observed mean difference value was negative, we counted the percentage of times of mean difference values in the minimum null distribution were less than the observed 'true' mean

difference values.

We then examined whether task influences the FS differences between targeted network

pairs (DAN-A-Visual versus DAN-A-DMN) using the same procedures but applied to FS. Our

results showed that FS is more sensitive to task modulation than FC in the DAN-A-Visual and

DAN-A-DMN comparison. To assess whether this holds for other networks, we repeated the

analysis, comparing FPCN-A-Visual versus FPCN-A-DMN.

4.5.10. Classification analysis – decoding network labels of parcels

Given heterogeneity of DAN, we used a data-driven approach to identify the subnetwork

most likely to vary in interaction patterns during tasks using the extracted features. Specifically,

we conducted a classification analysis on a normalized feature matrix (400 parcels by about

7000 features by 4 runs) to decode parcel network labels. After confirming accurate

classification, we examined the confusion matrix to identify classification errors (Detailed

information is provided in Supplementary Materials and Methods, Section 1.2.3). This allowed

us to explore network similarity, as functionally similar networks are more likely to be

misclassified.

4.6. Data and code Accessibility

790   **Acknowledgements**

791   We are grateful to Pradeepa Ruwan and Antonia De Freitas for piloting the experiment. We

792   would like to thank Ben D Fulcher for providing codes and a guide to help us extract the features

using hctsa. X. W. discloses support for the research of this work from National Natural Science Foundation of China (Grant Number. 32300881). Y. D. discloses support for the publication of this work from the STI 2030—Major Projects (Grant Number. 2021ZD0201500), the National Natural Science Foundation of China (Grant No. 31822024), and Scientific Foundation of Institute of Psychology, Chinese Academy of Sciences (Grant Number. E2CX3625CX). E. J. discloses support for the research of this work from a European Research Council Consolidator grant (Project ID: 771863 - FLEXSEM). N. L. discloses support for the research of this work from National Natural Science Foundation of China (Grant Number. 32471111).

Declaration of interests

The authors declare no competing interests.

References

Afyouni S, Smith SM, Nichols TE. 2019. Effective degrees of freedom of the Pearson's correlation coefficient under autocorrelation. *Neuroimage* 199:609–625. doi:10.1016/j.neuroimage.2019.05.011

Allefeld C, Graben PB, Kurths J. 2008. Advanced Methods of Electrophysiological Signal Analysis and Symbol Grounding. *Nova* 276–296.

Barch DM, Burgess GC, Harms MP, Petersen SE, Schlaggar BL, Corbetta M, Glasser MF, Curtiss S, Dixit S, Feldt C, Nolan D, Bryant E, Hartley T, Footer O, Bjork JM, Poldrack R, Smith S, Johansen-Berg H, Snyder AZ, Van Essen DC. 2013. Function in the human connectome: Task-fMRI and individual differences in behavior. *Neuroimage* 80:169–189. doi:10.1016/j.neuroimage.2013.05.033

Blank I, Kanwisher N, Fedorenko E. 2014. A functional dissociation between language and multiple-demand systems revealed in patterns of BOLD signal fluctuations. *J Neurophysiol* 112:1105–1118. doi:10.1152/jn.00884.2013

Blank IA, Fedorenko E. 2020. No evidence for differences among language regions in their temporal receptive windows. *Neuroimage* 219. doi:10.1016/j.neuroimage.2020.116925

Buckner RL, DiNicola LM. 2019. The brain's default network: updated anatomy, physiology and evolving insights. *Nature Reviews Neuroscience 2019 20:10* 20:593–608. doi:10.1038/s41583-019-0212-7

Buckner RL, Margulies DS. 2019. Macroscale cortical organization and a default-like apex

transmodal network in the marmoset monkey. *Nat Commun* 10:1976.
doi:10.1038/s41467-019-09812-8

Burt JB, Helmer M, Shinn M, Anticevic A, Murray JD. 2020. Generative modeling of brain maps
with spatial autocorrelation. *Neuroimage* 220:117038.
doi:10.1016/j.neuroimage.2020.117038

Ciric R, Rosen AFG, Erus G, Cieslak M, Adebimpe A, Cook PA, Bassett DS, Davatzikos C, Wolf
DH, Satterthwaite TD. 2018. Mitigating head motion artifact in functional connectivity MRI.
Nature Protocols 2018 13:12 13:2801–2826. doi:10.1038/s41596-018-0065-y

Cocuzza C V., Ito T, Schultz D, Bassett DS, Cole MW. 2020. Flexible coordinator and switcher
hubs for adaptive task control. *Journal of Neuroscience* 40:6949–6968.
doi:10.1523/JNEUROSCI.2559-19.2020

Cole MW, Ito T, Schultz D, Mill R, Chen R, Cocuzza C. 2019. Task activations produce spurious
but systematic inflation of task functional connectivity estimates. *Neuroimage* 189:1.
doi:10.1016/J.NEUROIMAGE.2018.12.054

Dale AM. 1999. Optimal Experimental Design for Event-Related fMRI, Hum. Brain Mapping.

Dale AM, Fischl B, Sereno MI. 1999. Cortical Surface-Based Analysis. *Neuroimage* 9:179–194.
doi:10.1006/nimg.1998.0395

Esteban O, Markiewicz C, Blair RW, Moodie C, Isik AI, Erramuzpe Aliaga A, Kent J, Goncalves
M, DuPre E, Snyder M, Oya H, Ghosh S, Wright J, Durnez J, Poldrack R, Gorgolewski
KJ. 2018. {fMRIPrep}: a robust preprocessing pipeline for functional {MRI}. *Nat Methods*.
doi:10.1038/s41592-018-0235-4

Faskowitz J, Esfahlani FZ, Jo Y, Sporns O, Betzel RF. 2020. Edge-centric functional network
representations of human cerebral cortex reveal overlapping system-level architecture.
Nat Neurosci 23:1644–1654. doi:10.1038/s41593-020-00719-y

Fedorenko E, Behr MK, Kanwisher N. 2011. Functional specificity for high-level linguistic
processing in the human brain. *Proceedings of the National Academy of Sciences*
108:16428–16433. doi:10.1073/pnas.1112937108

Fedorenko E, Duncan J, Kanwisher N. 2013. Broad domain generality in focal regions of frontal
and parietal cortex. *Proceedings of the National Academy of Sciences* 110:16616–16621.
doi:10.1073/pnas.1315235110

Fischl B, Sereno MI, Dale AM. 1999. Cortical surface-based analysis: II. Inflation, flattening,
and a surface-based coordinate system. *Neuroimage*. doi:10.1006/nimg.1998.0396

Fox MD, Snyder AZ, Vincent JL, Corbetta M, Van Essen DC, Raichle ME. 2005. The human

brain is intrinsically organized into dynamic, anticorrelated functional networks, PNAS July.

Friston K. 2011. Dynamic causal modeling and Granger causality Comments on: the
identification of interacting networks in the brain using fMRI: model selection, causality
and   deconvolution.   *Neuroimage*   58:303–5;   author   reply   310-1.
doi:10.1016/j.neuroimage.2009.09.031

Fulcher BD. 2018. Feature-Based Time-Series AnalysisFeature Engineering for Machine
Learning and Data Analytics. CRC Press. pp. 87–116. doi:10.1201/9781315181080-4

Fulcher BD, Jones NS. 2017. hctsa: A Computational Framework for Automated Time-Series
Phenotyping   Using   Massive   Feature   Extraction.   *Cell   Syst*   5:527-531.e3.
doi:10.1016/j.cels.2017.10.001

Fulcher BD, Little MA, Jones NS. 2013. Highly comparative time-series analysis: the empirical
structure of time series and their methods. *J R Soc Interface* 10:20130048.
doi:10.1098/rsif.2013.0048

Glasser MF, Coalson TS, Bijsterbosch JD, Harrison SJ, Harms MP, Anticevic A, Van Essen DC,
Smith SM. 2018. Using temporal ICA to selectively remove global noise while preserving
global   signal   in   functional   MRI   data.   *Neuroimage*   181:692–717.
doi:10.1016/J.NEUROIMAGE.2018.04.076

Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S,
Webster M, Polimeni JR, Van Essen DC, Jenkinson M. 2013. The minimal preprocessing
pipelines   for   the   Human   Connectome   Project.   *Neuroimage*   80:105–124.
doi:10.1016/j.neuroimage.2013.04.127

Golesorkhi M, Gomez-Pilar J, Zilio F, Berberian N, Wolff A, Yagoub MCE, Northoff G. 2021. The
brain and its time: intrinsic neural timescales are key for input processing. *Commun Biol*.
doi:10.1038/s42003-021-02483-6

González-García C, Flounders MW, Chang R, Baria AT, He BJ. 2018. Content-specific activity
in frontoparietal and default-mode networks during prior-guided visual perception. *Elife* 7.
doi:10.7554/eLife.36068

Honey CJ, Thesen T, Donner TH, Silbert LJ, Carlson CE, Devinsky O, Doyle WK, Rubin N,
Heeger DJ, Hasson U. 2012. Slow Cortical Dynamics and the Accumulation of Information
over Long Timescales. *Neuron* 76:423–434. doi:10.1016/j.neuron.2012.08.011

Ito T, Hearne LJ, Cole MW. 2020. A cortical hierarchy of localized and distributed processes
revealed via dissociation of task activations, connectivity changes, and intrinsic
timescales. *Neuroimage* 221:117141. doi:10.1016/j.neuroimage.2020.117141

Kong R, Yang Q, Gordon E, Xue A, Yan X, Orban C, Zuo X-N, Spreng N, Ge T, Holmes A,

Eickhoff S, Yeo BTT. 2021. Individual-Specific Areal-Level Parcellations Improve Functional Connectivity Prediction of Behavior. *Cerebral Cortex* 31:4477–4500. doi:10.1093/cercor/bhab101

Margulies DS, Ghosh SS, Goulas A, Falkiewicz M, Huntenburg JM, Langs G, Bezgin G, Eickhoff SB, Castellanos FX, Petrides M, Jefferies E, Smallwood J. 2016. Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proceedings of the National Academy of Sciences* 113:12574–12579. doi:10.1073/pnas.1608282113

McCormick EM, Arnemann KL, Ito T, Hanson SJ, Cole MW. 2022. Latent functional connectivity underlying multiple brain states. *Network Neuroscience* 1–42. doi:10.1162/netn_a_00234

Mckeown B, Strawson WH, Wang H-T, Karapanagiotidis T, Vos de Wael R, Benkarim O, Turnbull A, Margulies D, Jefferies E, McCall C, Bernhardt B, Smallwood J. 2020. The relationship between individual variation in macroscale functional gradients and distinct aspects of ongoing thought. *Neuroimage* 220:117072. doi:10.1016/j.neuroimage.2020.117072

Mesulam M-M. 1998. From sensation to cognition, Brain.

Murray JD, Bernacchia A, Freedman DJ, Romo R, Wallis JD, Cai X, Padoa-Schioppa C, Pasternak T, Seo H, Lee D, Wang XJ. 2014. A hierarchy of intrinsic timescales across primate cortex. *Nat Neurosci* 17:1661–1663. doi:10.1038/nn.3862

Norman-Haignere S V., McCarthy G, Chun MM, Turk-Browne NB. 2012. Category-Selective Background Connectivity in Ventral Visual Cortex. *Cerebral Cortex* 22:391–402. doi:10.1093/cercor/bhr118

Ojala M, Garriga GC. 2010. Permutation tests for studying classifier performance, Journal of Machine Learning Research.

O'Reilly JX, Woolrich MW, Behrens TEJ, Smith SM, Johansen-Berg H. 2012. Tools of the trade: Psychophysiological interactions and functional connectivity. *Soc Cogn Affect Neurosci* 7:604–609. doi:10.1093/scan/nss055

Pedregosa FABIANPEDREGOSA F, Michel V, Grisel OLIVIERGRISEL O, Blondel M, Prettenhofer P, Weiss R, Vanderplas J, Cournapeau D, Pedregosa F, Varoquaux G, Gramfort A, Thirion B, Grisel O, Dubourg V, Passos A, Brucher M, Perrot andÉdouardand M, Duchesnay andÉdouard, Duchesnay EDOUARDDUCHESNAY Fré. 2011. Scikit-learn: Machine Learning in Python Gaël Varoquaux Bertrand Thirion Vincent Dubourg Alexandre Passos PEDREGOSA, VAROQUAUX, GRAMFORT ET AL. Matthieu Perrot. *Journal of Machine Learning Research* 12:2825–2830.

Raut R V., Snyder AZ, Raichle ME. 2020. Hierarchical dynamics as a macroscopic organizing

principle of the human brain. *Proc Natl Acad Sci U S A* 117:20890–20897.
doi:10.1073/pnas.2003383117

Robinson EC, Jbabdi S, Glasser MF, Andersson J, Burgess GC, Harms MP, Smith SM, Van
Essen DC, Jenkinson M. 2014. MSM: A new flexible framework for Multimodal Surface
Matching. *Neuroimage* 100:414–426. doi:10.1016/J.NEUROIMAGE.2014.05.069

Salimi-Khorshidi G, Douaud G, Beckmann CF, Glasser MF, Griffanti L, Smith SM. 2014.
Automatic denoising of functional MRI data: Combining independent component analysis
and hierarchical fusion of classifiers. *Neuroimage* 90:449–468.
doi:10.1016/J.NEUROIMAGE.2013.11.046

Seth AK, Barrett AB, Barnett L. 2015. Granger causality analysis in neuroscience and
neuroimaging. *Journal of Neuroscience* 35:3293–3297. doi:10.1523/JNEUROSCI.4399-
14.2015

Shine JM, Breakspear M, Bell PT, Ehgoetz Martens K, Shine R, Koyejo O, Sporns O, Poldrack
RA. 2019. Human cognition involves the dynamic integration of neural activity and
neuromodulatory systems. *Nat Neurosci* 22:289–296. doi:10.1038/s41593-018-0312-0

Simony E, Honey CJ, Chen J, Lositsky O, Yeshurun Y, Wiesel A, Hasson U. 2016. Dynamic
reconfiguration of the default mode network during narrative comprehension. *Nat
Commun* 7:12141. doi:10.1038/ncomms12141

Smallwood J, Bernhardt BC, Leech R, Bzdok D, Jefferies E, Margulies DS. 2021. The default
mode network in cognition: a topographical perspective. *Nat Rev Neurosci* 22:503–513.
doi:10.1038/s41583-021-00474-4

Sporns O, Faskowitz J, Teixeira AS, Cutts SA, Betzel RF. 2021. Dynamic expression of brain
functional systems disclosed by fine-scale analysis of edge time series. *Network
Neuroscience* 5:405–433. doi:10.1162/netn_a_00182

Vos de Wael R, Benkarim O, Paquola C, Lariviere S, Royer J, Tavakol S, Xu T, Hong SJ, Langs
G, Valk S, Misic B, Milham M, Margulies D, Smallwood J, Bernhardt BC. 2020. BrainSpace:
a toolbox for the analysis of macroscale gradients in neuroimaging and connectomics
datasets. *Commun Biol* 3:1–10. doi:10.1038/s42003-020-0794-7

Wang HT, Ho NSP, Bzdok D, Bernhardt BC, Margulies DS, Jefferies E, Smallwood J. 2020.
Neurocognitive patterns dissociating semantic processing from executive control are
linked to more detailed off-task mental time travel. *Sci Rep* 10. doi:10.1038/s41598-020-
67605-2

Wang X, Gao Z, Smallwood J. 2021. Both Default and Multiple-Demand Regions Represent
Semantic Goal Information. The *Journal of Neuroscience.* 41:3679–3691.

Wang Xiuyi, Krieger-Redwood K, Lyu B, Lowndes R, Wu G, Souter NE, Wang Xiaokang, Kong R, Shafiei G, Bernhardt BC, Cui Z, Smallwood J, Du Y, Jefferies E. 2024a. The brain's topographical organization shapes dynamic interaction patterns that support flexible behaviour based on rules and long term knowledge. *The Journal of Neuroscience* e2223232024. doi:10.1523/JNEUROSCI.2223-23.2024.

Wang X, Krieger-Redwood K, Cui Y, Smallwood J, Du Y, Jefferies E. 2024b. Macroscale brain states support the control of semantic cognition. *Commun Biol* 7. doi:10.1038/s42003-024-06630-7

Wang X., Margulies DS, Smallwood J, Jefferies E. 2020. A gradient from long-term memory to novel cognition: Transitions through default mode and executive cortex. *Neuroimage* 220. doi:10.1016/j.neuroimage.2020.117074

Wang Xiuyi, Krieger-Redwood K, Zhang M, Cui Z, Wang Xiaokang, Karapanagiotidis T, Du Y, Leech R, Bernhardt BC, Margulies DS, Smallwood J, Jefferies E. 2022. Physical distance to sensory-motor landmarks predicts language function. doi:10.1093/cercor/bhac344

Wolff A, Berberian N, Golesorkhi M, Gomez-Pilar J, Zilio F, Northoff G. 2022. Intrinsic neural timescales: temporal integration and segregation. *Trends Cogn Sci* 26:159–173. doi:10.1016/j.tics.2021.11.007