TMVisDB: Annotation and 3D-visualization of transmembrane proteins

Tobias Olenyi[*,1,♦], Celine Marquet[*,1], Anastasia Grekova[2], Leen Houri[3], Michael Heinzinger[1], Christian Dallago[1,4], Burkhard Rost[1,3]

1   School of Computation, Information, and Technology (CIT), Faculty of Informatics, Chair of Bioinformatics & Computational Biology, TUM (Technical University of Munich), 85748 Garching/Munich, Germany
2   Structural and Computational Biology Unit, European Molecular Biology Laboratory (EMBL), 69117 Heidelberg, Germany
3   TUM School of Life Sciences Weihenstephan (WZW), Alte Akademie 8, Freising, Germany
4   NVIDIA DE GmbH, Einsteinstraße 172, 81677 Munich, Germany

*   Authors contributed equally.
♦   Corresponding author: service+tmvisdb[at]rostlab.org,
    http://www.rostlab.org/, Tel: +49-289-17-811 (email rost: assistant@rostlab.org)

Abstract

Since the rise of cellular life, transmembrane proteins (TMPs) have been crucial to various cellular processes through their central role as gates and gatekeepers. Despite their importance, experimental high-resolution structures for TMPs remain underrepresented due to experimental challenges. Given its performance leap, structure predictions have begun to close the gap. However, identifying the membrane regions and topology in three-dimensional structure files on a large scale still requires additional *in silico* predictions. Here, we introduce *TMVisDB* to sieve through millions of predicted structures for TMPs. This resource enables both browsing through 46 million predicted TMPs and visualizing them along with their topological annotations without having to tap into costly predictions of the AlphaFold3-style. *TMVisDB* joins *AlphaFoldDB* structure predictions and transmembrane topology predictions from the protein language model (pLM) based method *TMbed*. We showcase the utility of TMVisDB for the analysis of proteins through two use cases, namely the B-lymphocyte antigen CD20 (*Homo sapiens*) and the cellulose synthase (*Novosphingobium sp. P6W*). We demonstrate the value of *TMVisDB* for large-scale analyses through findings pertaining to all TMPs predicted for the human proteome. TMVisDB is freely available at https://tmvisdb.rostlab.org

Keywords: Protein language models, AlphaFold, Transmembrane protein prediction, Transmembrane topology

Abbreviations: AFDB, AlphaFold DB; **AI**, artificial intelligence; **ASCII**, American Standard Code for Information Interchange; **GO**, Gene Ontology; **MIB,** mitochondrial intermembrane space bridging complex; **MICOS**, mitochondrial contact site and cristae junction organizing system; **PDB**, Protein Data Bank; **pLDDT**, predicted local distance difference test; **pLM**, protein language model; **SAM**, mitochondrial outer membrane sorting assembly machinery; **SOM**, supporting online material; **SP,** signal peptide; **TM**, transmembrane; **TMB**, transmembrane beta strand; **TMH**, transmembrane alpha helix; **TMP**, transmembrane protein; **TOPDB**, Topology Database of Transmembrane Proteins; **UA**, UniProt accession number; **3D**, three dimensional.

Introduction

Experimental structures for transmembrane proteins remain sparse. Despite many biological processes depending on proteins spanning cell membranes, only 5% of all high-resolution experimental three-dimensional (3D) structures in the Protein Data Bank (PDB) are transmembrane proteins (TMPs) [5]. Although structure-determination methods have advanced significantly [3, 6-10], TMPs continue to pose many technical challenges [11]. Therefore, today's databases often contain only small subsets of membrane proteins, and few focus solely on TMPs or add information on (predicted) membrane embeddings [12-16]. As of November 2024, *mpstruc*, a curated database, covers 1,736 unique TMPs with experimental 3D structures [17], constituting 1.2% of all PDB structures (132,007 unique sequences redundancy-reduced at 100% identity). Substantially below the estimate of 20-30% of proteins in any proteome being TMPs [1, 18], this imbalance becomes more striking, considering that TMPs make up almost 50% of all drug targets [19].

Novel resources may push novelty into the realm of TMPs. Few computational methods revolutionized a field as quickly and dramatically as AlphaFold2 [3]. Providing reliable 3D predictions, AlphaFold2, AlphaFoldDB (AFDB) [20], and AlphaFold3 [6] are extraordinary catalysts for research in artificial intelligence (AI) and the life sciences [2]. Along with the advance in structure prediction, methods quickly and reliably searching and clustering the exploding sequence have continuously improved [21-23]. An orthogonal approach to leverage the wealth of sequence data was introduced by protein language models (pLMs) [24-29]. Such pLMs learn from protein sequences without experimental annotations (dubbed 'unlabeled' in AI jargon) to extract meaningful numeric representations (embeddings) encoding sequences as vectors. The knowledge acquired during pre-training on raw sequences can readily be transferred to downstream predictions of per-residue [1, 30-33] and per-protein phenotypes [34-37].

The unparalleled number of available protein sequences, pLM embeddings, and experimental and predicted structures may help to overcome limitations for studying TMPs *in vitro* and *in vivo*. Combining *in silico* methods and resources enables the discovery of previously unknown TMPs and the exploration of known and unknown TMPs in exceptional detail. An example of TMP predictions' usefulness is the *TmAlphaFold database*, taking AlphaFold2 structures as input to provide membrane localization for almost 216k (215,844) predicted alpha-helical TMPs [38].

Here, we introduce TMVisDB, a collection of over 46 million (46M) predicted alpha-helical and beta-barrel TMPs with their AlphaFold2-predicted 3D structure as well as membrane topology and annotation predicted by the pLM-based method TMbed [1]. TMVisDB was created by applying TMbed for all proteins in AFDB [20] (>200M, 07/22). TMbed is *on par* with or outperforms all other TMP prediction methods in classifying residues as transmembrane alpha-helix (TMH) or transmembrane beta-strand (TMB). TMbed also predicts the orientation of TM-segments within the membrane (dubbed *topology*) and signal peptides (SP). The latter reaches the binary classification performance of SignalP6 without distinguishing different SP types [1, 39]. TMVisDB is the first resource to gather such a large number of per-residue transmembrane topology annotations and, compared to existing TMP databases [17, 38], expanding the exploration space of easily browsable TMPs by two to four orders of magnitude. Providing interactive visualizations of TMP annotations with their respective AlphaFold2 structures, the

91 intuitive interface of tmvisdb.rostlab.org enables all users to investigate small- and large-scale
92 hypotheses on TMPs.
93
94   **Results**

Over 46M predicted transmembrane proteins. TMVisDB is a relational database with
46,048,450 proteins (11/24, Table 1), comprising 23% of AlphaFold DB [20] (AFDB, >200M,
07/22) [2]. Transmembrane proteins (TMPs) and their topology were predicted for proteins in
AFDB using the pLM-based, state-of-the-art TMP prediction method TMbed [1]. About 95%
of the proteins in TMVisDB have predicted transmembrane alpha-helices (TMHs), 4.6% contain
predicted transmembrane beta-strands (TMBs), and 0.1% contain both, likely providing a
lower estimate for the error of our approach. At the same time, no convincing current evidence
supports or rules out the existence of such proteins. Signal peptides (SP) were predicted by
TMbed for 13.6% of all TMPs (archaea: 13.83%, bacteria: 14.5%, eukaryotes: 15.3%),
compared to 7.1% of all proteins in UniProt [40] with AlphaFold2 [3] structures and
transmembrane annotation.
106
107 **Table 1: Summary of proteins in TMVisDB*.**

TMbed prediction			Taxonomy (Domain)				
Transmembrane type	**Signal Peptide**	**All**	**Bacteria**	**Eukaryota**	**Archaea**	**Other**	
Alpha-helix (TMH)	no	39,391,449	28,020,596	9,944,469	991,477	434,907	
	yes	4,475,707	2,977,947	1,306,796	152,801	38,163	
Beta-stranded barrels (TMB)	no	323,017	269,126	43,215	1,401	9,275	
	yes	1,814,523	1,786,881	7,959	1,608	18,075	
Both	no	20,918	16,937	3,584	90	307	
	yes	22,836	21,731	771	52	282	
Total		**46,048,450**	**33,093,218**	**11,306,794**	**1,147,429**	**501,009**	

*Description: TMVisDB collects over 46M predicted transmembrane proteins (TMPs). Predictions were generated by applying TMbed on all proteins in AFDB (>200M, 07/22) [1, 2]. TMbed predicts alpha-helical and beta-barrel TMPs by per-residue assignments of one of four classes (transmembrane helix, transmembrane strand, signal peptide, and other). Proteins excluded from AFDB, such as viral proteins, are also missing in TMVisDB; proteins without known super-kingdom (Bacteria, Archaea, or Eukaryota) are classified as "Other".

Intuitive browsing and visualization. The website tmvisdb.rostlab.org enables interactive
access to browse and visualize all TMPs in TMVisDB. For large-scale analyses, the database
can be filtered by taxonomy (UniProt organism identifier, domain, kingdom), predicted TMP-
type (TMH, or TMB, or both), protein length, and presence/absence of predicted SP (Fig. 1a).
Each database record contains: UniProt name (ID), sequence length, organism domain and
kingdom, a link to the organism on UniProtKB, sequence classification based on TMbed
predictions, and cumulative TMbed predictions [1]. Results are downloadable in CSV format
(comma-separated columns in ASCII). Each row in the results is clickable to visualize the
prediction details, corresponding AlphaFold2 3D structure, and available annotations. In the

detail view, the structure of each protein can be colored by the (1) available annotations or (2)
AlphaFold2 per-residue confidence metric (pLDDT; Fig. 2, Supporting Online Material (SOM)
Fig. S1 for the interface, S2-S4). Protein sequence annotations are shown below the 3D
visualization, along with links for the respective sources; possible annotation resources are
UniProtKB [40], Membranome [12], TMAlphaFold [38], TopDB [41], and TMbed predictions [1].
Individual annotation regions are clickable and trigger highlighting of the respective region in
the 3D visualization.

Fig. 1: TMVisDB filter interface. The interface has two main components.

Panel (**a**) displays the primary filtering system with four distinct categories: (1) Taxonomy, allowing selection by UniProt Organism Identifier, Domain, and Kingdom; (2) Transmembrane topology, distinguishing between alpha-helix and beta-strand structures; (3) Signal Peptides (SP), enabling inclusion or exclusion of sequences with predicted SP; and (4) Sequence length parameters.

Panel (**b**): presents a partial output from a random TMVisDB selection without applied filters. Each record contains seven key features: (1) UniProtKB name (ID), (2) sequence length, (3) organism domain, (4) kingdom classification, (5) organism link to UniProtKB, (6) sequence classification based on TMbed predictions[1], and (7) cumulative TMbed predictions [1, 4].

Fig. 2: TMVisDB single protein use cases. Structural analysis of two proteins: (1) *B-lymphocyte antigen CD20* (P11836, Homo sapiens) and (2) *cellulose synthase protein* (A0A2Z5E6S1, Novosphingobium sp. P6W) using AlphaFold2 prediction [3]. Panels show CD20 in the upper section (**a, b**) and cellulose synthase protein in the lower section (c, d).

Left panels (**a, c**) visualize TMbed's predicted transmembrane topology using three distinct colors: (1) blue for alpha-helix, (2) gray for non-membrane regions, and (3) turquoise for signal peptide.

Right panels (**b, d**) display AlphaFold2's per-residue confidence metric (pLDDT) with four confidence levels: (1) very confident (pLDDT > 90, blue), (2) confident (70 < pLDDT ≤ 90, green), (3) low confidence (50 < pLDDT ≤ 70, yellow), and (4) very low confidence (pLDDT ≤ 50, red).

The predicted transmembrane regions show a strong colocation between topology predictions and structural confidence, exhibiting high pLDDT scores. Non-membrane regions, particularly those

Use case 1: B-lymphocyte antigen CD20 - expanding annotations. The B-lymphocyte antigen CD20 (UniProtKB-ID: P11836, Fig. 2a,b) is an ideal use case. Although, well-studied nature and an important drug target, there still is no high-resolution experimental structure available for CD20 in isolation.

TMVisDB revealed four transmembrane helices (TMHs, with 18-24 residues), supporting the high-confidence AlphaFold2 predictions (Fig. 2b). The predicted topology largely confirms the

membrane orientation observed in existing experimental structures [42] with minor deviations of up to five residues between TMVisDB and UniProtKB [43].

Our predictions also reinforce CD20's classification as a member of the MS4A family of TMPs. The structural features align with previous studies [44, 45], showing a non-glycosylated tetraspanin structure with one shorter and one longer extracellular loop and both C- and N-termini located in the cytosol (Fig. 2a). This case study demonstrates how TMVisDB can provide valuable structural insights for important therapeutic targets, even in the absence of complete experimental structures.

Use case 2: Cellulose synthase - exploring novel TMP annotation. TMVisDB's capability to analyze previously unstudied transmembrane proteins is exemplified by our examination of the *cellulose synthase protein* (UniProtKB-ID: A0A2Z5E6S1) from *Novosphingobium sp. P6W*, a gram-negative bacterium (Fig. 2c, d). Based on UniProtKB's automatic annotation of unreviewed records, this protein localizes to the prokaryotic outer membrane and functions in glycan metabolism and bacterial cellulose biosynthesis [46].

Our analysis revealed significant agreement between multiple prediction methods. While UniProtKB annotated a signal peptide spanning 29 residues, TMbed extended this prediction to 40 residues, confirmed by a high-confidence prediction from SignalP6.0 (cleavage site at position 40, probability 0.97) [39]. TMbed additionally identified twelve transmembrane beta-strands (TMBs), which correspond closely to the beta-barrel configuration predicted by AlphaFold2 (Fig. 2c). The high pLDDT scores of the transmembrane residues provide further validation for these previously unannotated TMBs (Fig. 2d).

We observed some minor discrepancies in the predictions, particularly where certain TMBs appeared shorter than their corresponding segments in the AlphaFold2 barrel structure (Fig. 2c, lower right). Several hypotheses could explain these differences: the natural membrane embedding might influence segment length, TMbed may have produced false negative predictions for some residues, or protein dynamics during binding events could have led AlphaFold2 to predict an alternative conformational state. However, current evidence remains insufficient to support any of these explanations conclusively.

Use case 3: *Homo sapiens* - combining large- and small-scale analyses. In addition to studies of individual proteins, TMVisDB enables large-scale analyses. TMVisDB contains 20.7% of the human proteins in AFDB (11/24), accessible via the human UniProtKB organism identifier (no. 9606). Out of these, we investigated the only proteins for which TMbed predicted both TMH and TMB: (1) *Deoxyribonuclease I fragment* (UniProtKB-ID: A0A192ZHB2; Fig. S2), (2) two sequence-similar *perforins* (UniProtKB-ID: B3KUT2, Q2M385; Fig. S3), (3) and three sequence-similar *DnaJ* homologs (B4DGD5, B4DPK2, Q9NVH1; Fig. S4).

TMbed predicted contradicting inside-to-outside TMH and outside-to-inside TMB topologies for the Deoxyribonuclease I fragment. While AlphaFold2 confirmed secondary structure elements in these regions, only the beta-strand was predicted at high plDDT (>80), and the prediction lacked an expected loop/bend between elements (Fig. S2). These inconsistencies suggest partial correctness of either prediction at best.

The perforin predictions showed mixed evidence for transmembrane topology. While the TMH prediction aligned with AlphaFold2 structure prediction (Fig. S3), UniProt annotation [47], and known membrane interactions [48], the short predicted TMB (5-6 residues) lacked such support. Although *MPEG1/Perforin-2* (UniProtKB-ID: Q2M385) forms homo-oligomeric beta-

barrel pores [49], comparative analysis of membrane-targeting perforin-like proteins from *Toxoplasma gondii* (UniProtKB-ID: G3G7T0) and *Plasmodium falciparum* (UniProtKB-ID: Q9U0J9) showed no similar TMB patterns, suggesting this prediction to be incorrect.

For *DnaJ* homologs, TMbed and AlphaFold2 predictions showed remarkable agreement in TMH and TMB membrane boundary predictions (Fig. S4). These predictions align with *DnaJ*'s known role in the mitochondrial intermembrane space bridging (MIB) complex and its association with the mitochondrial contact site and cristae junction organizing system (*MICOS*) [50, 51]. While direct experimental validation of these transmembrane domains remains pending, their presence could explain *DnaJ*'s function in *MICOS* assembly and cristae organization, presenting either a novel finding or a hypothesis for experimental verification.

Discussion

Organizing the growing number of available structures. The exponential growth of protein sequences and structures necessitates efficient organization and accessibility of specific protein groups. Protein language models (pLMs) have revolutionized this organization by enabling rapid functional scanning of large sequence databases independent of traditional sequence alignment methods [52, 53]. This capability enabled us to efficiently identify and extract transmembrane proteins (TMPs) from UniProt using the pLM-based TMbed method. While several structure prediction methods are now available [7-10], we chose AlphaFold2 [3] for TMVisDB due to its demonstrated accuracy in TMP structure prediction [54] and successful application in resources like the TMAlphaFold database [38]. The resulting TMVisDB combines these predictions with an intuitive search and visualization interface, making TMP structural data readily accessible to researchers.

Benefits and limitations often go hand in hand. TMVisDB enhances TMP analysis by combining per-residue transmembrane predictions with higher-resolution 3D structure predictions through complementary approaches: the pLM-based TMbed provides low-resolution protein-specific predictions while AlphaFold2 contributes high-resolution family-averaged predictions from multiple sequence alignments (MSAs). This double-stitching provides independent validation, as demonstrated by the cellulose synthase protein case, for which aligned predictions still leave questions about membrane embedding depth. The B-lymphocyte antigen CD20 case further illustrates TMVisDB's utility in confirming TM-regions and its current limitations with multimeric proteins, a constraint that will persist until tools like AlphaFold-Multimer [55] become more accessible.

TMbed, underlying TMVisDB, shines with a very low false positive rate (<1%). However, given thousands of predictions (e.g. 20k for human), this still implies many errors in our resource, as indicated by the likely incorrect prediction of proteins with both TMH and TMB segments. The database enables rapid comparative analyses to identify such potential false positives, as shown in our perforin analysis. However, TMVisDB faces scale-related challenges: it currently contains 38K human TMPs, far exceeding the estimated 20K total human proteins [56]. This inflation likely stems from AFDB including unreviewed proteins and fragments, creating redundancy that, while potentially useful, complicates database navigation.

Future developments of TMVisDB will address these challenges by implementing GO annotation- and binding-filters [31, 37], improved database performance, and regular AFDB

221 updates. These enhancements, guided by user feedback, will strengthen TMVisDB's role as a
222 comprehensive resource for TMP research.
223
224
225   **Materials and Methods**

TMbed transmembrane topology prediction. TMbed [1] performs residue-level classification
of transmembrane proteins (TMPs) into four categories: transmembrane alpha-helix (TMH),
transmembrane beta-strand (TMB), signal peptide (SP), and others. The method predicts
membrane orientation for TMH and TMB segments without the capability to identify re-entrant
regions. TMbed achieves state-of-the-art performance with 98±1% accuracy for alpha-helical
and 94±8% for beta-barrel TMPs while maintaining a false positive rate below 1%. Its
predictions locate 90% of TMHs and TMBs within five residues of their actual position. TMbed
can process the entire Swiss-Prot [40] (~567,000 proteins) in under 9 hours using only protein
Language Model (pLM) embeddings from single sequences, making it ideal for high-
throughput applications like TMVisDB [1].
236
Database and backend. TMVisDB is implemented as an SQLite (version 3) database with a
FastAPI-based Python backend. Each entry is uniquely identified by its UniProt accession (UA)
and contains protein sequence data, predictions, annotations, and taxonomic information. The
database incorporates, where available, experimentally derived topology data from TOPDB
[41] and single alpha-helix transmembrane annotations from Membranome [12]. TMVisDB
includes all transmembrane proteins from AlphaFold DB (AFDB) [2], as predicted by TMbed
[1]. AFDB's sequence coverage limitations apply to TMVisDB: sequences must be (i) between
16 and 2,700 amino acids for UniProtKB/Swiss-Prot entries (1,280 for others), (ii) contain only
standard amino acids, (iii) appear in UniProtKB's reference proteome "one sequence per gene"
FASTA file, (iv) remain unmodified in recent UniProt releases, and (v) be non-viral. The database
and its API are hosted at the Technical University of Munich (TUM); the code is available at
https://github.com/t03i/TMVisDB.
249
Web frontend. The TMVisDB web interface is implemented in Svelte 4, providing an interactive
environment for exploring transmembrane protein data. Users can filter the database by
transmembrane topology (TMH, TMB), signal peptide presence, taxonomy, and protein length
(Fig. 1). For individual proteins, the interface offers detailed visualization using the PDBe
Molstar component for 3D structure display and the Nightingale feature viewer from EBI for
sequence annotations (Fig. S2). The visualization system enables dynamic structures coloring
based on either transmembrane topology predictions or AlphaFold2's pLDDT scores (Fig. 2).
Additional annotations from UniProtKB [40] and TMAlphaFold [38] are loaded on demand. At
the same time, structural data is fetched directly from AlphaFoldDB. The web interface source
code is available at https://github.com/t03i/TMVisDB; the web interface is available at
tmvisdb.rostlab.org.
261

Accession Numbers

UniProt accessions: [A0A2Z5E6S1](#), [P11836](#), [A0A192ZHB2](#), [B3KUT2](#), [Q2M385](#), [B4DGD5](#), [B4DPK2](#), [Q9NVH1](#), [G3G7T0](#), [Q9U0J9](#)

UniProt organism identifier: 9606

Data Availability

The database and web interface presented in this study are freely accessible at tmvisdb.rostlab.org. A static version of the database (excluding sequence information and indices due to size constraints) has been deposited in the Zenodo repository (10.5281/zenodo.14186950). The complete source code for database implementation and web interface is available through GitHub (https://github.com/t03i/TMVisDB) under the Apache 2.0 license.

TMVisDB integrates data from the following established resources: AlphaFold DB (https://alphafold.ebi.ac.uk/), UniProtKB (https://www.uniprot.org/), TOPDB (http://topdb.enzim.hu/), Membranome (https://membranome.org/), and TMAlphaFold (http://tmalphafold.ttk.hu/). All data and source code are available without restrictions for academic and non-commercial use.

Acknowledgments

We gratefully acknowledge Dr. Luisa F. Jimenez-Soto for her critical analysis of our results and Dr. Michael Bernhofer for his invaluable guidance on the project direction and manuscript preparation. We extend our appreciation to Nikita Kugut for his continued support throughout this work, and to Prof. Arne Skerra (Technical University of Munich, WZW) for suggesting the CD20 system as a valuable use case.

We thank the Technical University of Munich for providing the infrastructure to host TMVisDB. Our work has been made possible by the groundbreaking development of AlphaFold2 by Dr. John Jumper and the DeepMind team, and we appreciate their commitment to open science through the public release of both code and predictions.

This work builds upon the contributions of numerous individuals and institutions committed to open science. We acknowledge the developers of the open-source programming libraries utilized in this study, the researchers who deposit their experimental data in public databases, the dedicated teams maintaining these databases, and the scientists who develop and share methods for enriching experimental data.

Funding

The Bavarian Ministry of Education supported this work by funding TUM. The authors declare no conflicts of interest.

Author contributions

Tobias Olenyi: Conceptualization, Data Curation, Methodology, Project Administration, Software, Validation, Visualization, Writing – Original Draft, Writing – Review & Editing

Céline Marquet: Conceptualization, Data Curation, Project Administration, Validation, Writing
– Original Draft, Writing – Review & Editing

Anastasia Grekova: Formal Analysis, Software, Writing – Original Draft

Leen Houri: Formal Analysis, Writing – Original Draft

Michael Heinzinger: Conceptualization, Writing – Original Draft

Christian Dallago: Conceptualization, Validation

Burkhard Rost: Supervision, Writing – Review & Editing

References

[1] Bernhofer M, Rost B. TMbed: transmembrane proteins predicted through language model embeddings. BMC Bioinformatics. 2022;23:326.

[2] Varadi M, Anyango S, Deshpande M, Nair S, Natassia C, Yordanova G, et al. AlphaFold Protein Structure Database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. Nucleic Acids Research. 2022;50:D439-D44.

[3] Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, et al. Highly accurate protein structure prediction with AlphaFold. Nature. 2021;596:583-9.

[4] Elofsson A. Progress at protein structure prediction, as seen in CASP15. Curr Opin Struct Biol. 2023;80:102594.

[5] Burley SK, Bhikadiya C, Bi C, Bittrich S, Chen L, Crichlow GV, et al. RCSB Protein Data Bank: powerful new tools for exploring 3D structures of biological macromolecules for basic and applied research and education in fundamental biology, biomedicine, biotechnology, bioengineering and energy sciences. Nucleic Acids Research. 2021;49:D437-D51.

[6] Abramson J, Adler J, Dunger J, Evans R, Green T, Pritzel A, et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3. Nature. 2024;630:493-500.

[7] Ahdritz G, Bouatta N, Kadyan S, Xia Q, Gerecke W, AlQuraishi M. OpenFold. 2021.

[8] Baek M, Baker D. Deep learning and protein structure modeling. Nat Methods. 2022;19:13-4.

[9] Lee JH, Yadollahpour P, Watkins A, Frey NC, Leaver-Fay A, Ra S, et al. EquiFold: Protein Structure Prediction with a Novel Coarse-Grained Structure Representation. bioRxiv; 2022.

[10] Mirdita M, Schütze K, Moriwaki Y, Heo L, Ovchinnikov S, Steinegger M. ColabFold: making protein folding accessible to all. Nat Methods. 2022;19:679-82.

[11] Li F, Egea PF, Vecchio AJ, Asial I, Gupta M, Paulino J, et al. Highlighting membrane protein structure and function: A celebration of the Protein Data Bank. Journal of Biological Chemistry. 2021;296.

[12] Lomize AL, Schnitzer KA, Todd SC, Cherepanov S, Outeiral C, Deane CM, et al. Membranome 3.0: Database of single-pass membrane proteins with AlphaFold models. Protein Science. 2022;31:e4318.

[13] Lomize MA, Pogozheva ID, Joo H, Mosberg HI, Lomize AL. OPM database and PPM web server: resources for positioning of proteins in membranes. Nucleic Acids Research. 2012;40:D370-6.

[14] Postic G, Ghouzam Y, Etchebest C, Gelly J-C. TMPL: a database of experimental and theoretical transmembrane protein models positioned in the lipid bilayer. Database. 2017;2017:bax022.

[15] Newport TD, Sansom MS P, Stansfeld PJ. The MemProtMD database: a resource for membrane-embedded protein structures and their lipid interactions. Nucleic Acids Research. 2019;47:D390-D7.

[16] Tordai H, Suhajda E, Sillitoe I, Nair S, Varadi M, Hegedus T. Comprehensive Collection and Prediction of ABC Transmembrane Protein Structures in the AI Era of Structural Biology. International Journal of Molecular Sciences. 2022;23:8877.

[17] White SH. mpstruc: Membrane Proteins of Known Structure. 1998.

[18] Fagerberg L, Jonasson K, von Heijne G, Uhlén M, Berglund L. Prediction of the human membrane proteome. Proteomics. 2010;10:1141-9.

[19] Santos R, Ursu O, Gaulton A, Bento AP, Donadi RS, Bologa CG, et al. A comprehensive map of molecular drug targets. Nat Rev Drug Discov. 2017;16:19-34.

[20] Tunyasuvunakool K, Adler J, Wu Z, Green T, Zielinski M, Zidek A, et al. Highly accurate protein structure prediction for the human proteome. Nature. 2021.

[21] Mirdita M, Steinegger M, Söding J. MMseqs2 desktop and local web server app for fast, interactive sequence searches. Bioinformatics. 2019;35:2856-8.

[22] Buchfink B, Reuter K, Drost H-G. Sensitive protein alignments at tree-of-life scale using DIAMOND. Nat Methods. 2021;18:366-8.

[23] Steinegger M, Mirdita M, Soding J. Protein-level assembly increases protein sequence recovery from metagenomic samples manyfold. Nat Methods. 2019;16:603-6.

[24] Alley EC, Khimulya G, Biswas S, AlQuraishi M, Church GM. Unified rational protein engineering with sequence-based deep representation learning. Nat Methods. 2019:1-8.

[25] Bepler T, Berger B. Learning protein sequence embeddings using information from structure. Seventh International Conference on Learning Representations. 2019/02/22 ed2019.

[26] Heinzinger M, Elnaggar A, Wang Y, Dallago C, Nechaev D, Matthes F, et al. Modeling aspects of the language of life through transfer-learning protein sequences. BMC Bioinformatics. 2019;20:723.

[27] Rives A, Meier J, Sercu T, Goyal S, Lin Z, Liu J, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. Proceedings of the National Academy of Sciences. 2021;118:e2016239118.

[28] Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Yu W, Jones L, et al. ProtTrans: Towards Cracking the Language of Lifes Code Through Self-Supervised Deep Learning and High Performance Computing. IEEE Trans Pattern Anal Mach Intell. 2021;44:7112-27.

[29] Heinzinger M, Rost B. Teaching AI to speak protein. Current Opinion Structural Biology. 2024.

[30] Marquet C, Heinzinger M, Olenyi T, Dallago C, Erckert K, Bernhofer M, et al. Embeddings from protein language models predict conservation and variant effects. Hum Genet. 2022;141:1629-47.

[31] Littmann M, Heinzinger M, Dallago C, Weissenow K, Rost B. Protein embeddings and deep learning predict binding residues for various ligand types. Scientific Reports. 2021;11:23916.

[32] Meier J, Rao R, Verkuil R, Liu J, Sercu T, Rives A. Language models enable zero-shot prediction of the effects of mutations on protein function. bioRxiv. 2021:2021.07.09.450648.

[33] Weissenow K, Rost B. Protein language models the new universal key? Current Opinion Structural Biology. 2024.

[34] Bileschi ML, Belanger D, Bryant DH, Sanderson T, Carter B, Sculley D, et al. Using deep learning to annotate the protein universe. Nat Biotechnol. 2022;40:932-7.

[35] Hamid M-N, Friedberg I. Identifying antimicrobial peptides using word embedding with deep recurrent neural networks. Bioinformatics. 2019;35:2009-16.

[36] Stärk H, Dallago C, Heinzinger M, Rost B. Light attention predicts protein location from the language of life. Bioinformatics Advances. 2021;1:vbab035.

[37] Littmann M, Heinzinger M, Dallago C, Olenyi T, Rost B. Embeddings from deep learning transfer GO annotations beyond homology. Scientific Reports. 2021;11:1160.

[38] Dobson L, Szekeres LI, Gerdán C, Langó T, Zeke A, Tusnády GE. TmAlphaFold database: membrane localization and evaluation of AlphaFold2 predicted alpha-helical transmembrane protein structures. Nucleic Acids Research. 2022:gkac928.

[39] Teufel F, Almagro Armenteros JJ, Johansen AR, Gíslason MH, Pihl SI, Tsirigos KD, et al. SignalP 6.0 predicts all five types of signal peptides using protein language models. Nat Biotechnol. 2022;40:1023-5.

[40] The UniProt C. UniProt: the universal protein knowledgebase in 2021. Nucleic Acids Research. 2021;49:D480-D9.

[41] Dobson L, Lango T, Remenyi I, Tusnady GE. Expediting topology data gathering for the TOPDB database. Nucleic Acids Res. 2015;43:D283-9.

[42] Rougé L, Chiang N, Steffek M, Kugel C, Croll TI, Tam C, et al. Structure of CD20 in complex with the therapeutic monoclonal antibody rituximab. Science. 2020;367:1224-30.

[43] UniProtKB. B-lymphocyte antigen CD20 - Homo sapiens | UniProtKB | UniProt. 2022.

[44] Oettgen HC, Bayard PJ, Van Ewijk W, Nadler LM, Terhorst CP. Further Biochemical Studies of the Human B-Cell Differentiation Antigens B1 and B2. Hybridoma. 1983;2:17-28.

[45] Bubien JK, Zhou LJ, Bell PD, Frizzell RA, Tedder TF. Transfection of the CD20 cell surface molecule into ectopic cell types generates a Ca2+ conductance found constitutively in B lymphocytes. Journal of Cell Biology. 1993;121:1121-32.

[46] UniProtKB. Cellulose synthase - Novosphingobium sp. P6W | UniProtKB | UniProt. 2022.

[47] UniProtKB. MPEG1 - Macrophage-expressed gene 1 protein - Homo sapiens (Human) | UniProtKB | UniProt. 2022.

[48] Osińska I, Popko K, Demkow U. Perforin: an important player in immune response. Cent Eur J Immunol. 2014;39:109-15.

[49] Pang SS, Bayly-Jones C, Radjainia M, Spicer BA, Law RHP, Hodel AW, et al. The cryo-EM structure of the acid activatable pore-forming immune effector Macrophage-expressed gene 1. Nat Commun. 2019;10:4288.

[50] Xie J, Marusich MF, Souda P, Whitelegge J, Capaldi RA. The mitochondrial inner membrane protein mitofilin exists as a complex with SAM50, metaxins 1 and 2, coiled-coil-helix coiled-coil-helix domain-containing protein 3 and 6 and DnaJC11. FEBS Lett. 2007;581:3545-9.

[51] Huynen MA, Mühlmeister M, Gotthardt K, Guerrero-Castillo S, Brandt U. Evolution and structural organization of the mitochondrial contact site (MICOS) complex and the mitochondrial intermembrane space bridging (MIB) complex. Biochimica et Biophysica Acta (BBA) - Molecular Cell Research. 2016;1863:91-101.

[52] Olenyi T, Marquet C, Heinzinger M, Kröger B, Nikolova T, Bernhofer M, et al. LambdaPP: Fast and accessible protein-specific phenotype predictions. bioRxiv; 2022.

[53] Kempen Mv, Kim SS, Tumescheit C, Mirdita M, Gilchrist CLM, Söding J, et al. Foldseek: fast and accurate protein structure search. bioRxiv; 2022.

[54] Hegedűs T, Geisler M, Lukács GL, Farkas B. Ins and outs of AlphaFold2 transmembrane protein structure predictions. Cell Mol Life Sci. 2022;79:73.

[55] Evans R, O'Neill M, Pritzel A, Antropova N, Senior A, Green T, et al. Protein complex prediction with AlphaFold-Multimer. bioRxiv; 2022.

[56] Wilhelm M, Schlegl J, Hahne H, Gholami AM, Lieberenz M, Savitski MM, et al. Mass-spectrometry-based draft of the human proteome. Nature. 2014;509:582-7.

TMVisDB

a

Filter By: **Taxonomy** Organism ID   Domain: Select Domain ⌄   Kingdom: All ⌄

Topology: **All** Both α-Helix β-Barrel   Signal Peptide: ⬤   Length: 16 ⌄ - 5500 ⌄

Apply Reset

b

Random Proteins

Search...

UniprotKB ID ↕	Sequence Length ↕	Domain ↕	Kingdom ↕	Organism ↕	Alpha ↕	Beta ↕	Signal ↕	#Alpha ↕	#Beta ↕	#Signal ↕
Filter	Filter	Filter	Filter	Filter	⌄	⌄	A ⌄	Filter	Filter	Filter
A0A536D911_9CHLR	107	Bacteria	Terrabacteria group	Chloroflexi bacterium	Yes	No	No	23	0	0
K5UL34_9VIBR	132	Bacteria	Proteobacteria	Vibrio sp. HENC-03	Yes	No	No	14	0	0
A0A397EZV9_9STRA	140	Eukaryota	Sar	Aphanomyces astaci	Yes	No	No	74	0	0
A0A662E771_9ACTN	153	Bacteria	Terrabacteria group	Actinobacteria bacterium	Yes	No	No	66	0	0