A Comparative Review of Deep Learning Methods for RNA Tertiary Structure Prediction

Ivona Martinović[1,2], Tin Vlašić[1], Yang Li[3], Bryan Hooi[2], Yang Zhang[2, 3, 4,*], Mile Šikić[1,5,*]

[1]Genome Institute of Singapore (GIS), Agency for Science, Technology and Research (A*STAR), 60 Biopolis Street, Genome, Singapore, 138672, Republic of Singapore.
[2]School of Computing, National University of Singapore, 13 Computing Drive, Singapore, 117417, Republic of Singapore.
[3]Cancer Science Institute of Singapore, National University of Singapore, 14 Medical Drive, Singapore, 117599, Republic of Singapore.
[4]Department of Biochemistry, Yong Loo Lin School of Medicine, National University of Singapore, 8 Medical Drive, Singapore, 117596, Republic of Singapore.
[5]Faculty of Electrical Engineering and Computing, University of Zagreb, 3 Unska Street, Zagreb, 10000, Croatia.

*Corresponding author(s). E-mail(s): zhang@nus.edu.sg; mile_sikic@gis.a-star.edu.sg; Contributing authors: ivona_martinovic@gis.a-star.edu.sg; tin_vlasic@gis.a-star.edu.sg; liyangum@nus.edu.sg; bhooi@comp.nus.edu.sg;

Abstract

Several deep learning-based tools for RNA 3D structure prediction have recently emerged, including DRfold, DeepFoldRNA, RhoFold, RoseTTAFoldNA, trRosettaRNA, and AlphaFold3. In this study, we systematically evaluate these six models on three datasets: RNA Puzzles, CASP15 RNA targets, and a newly generated large dataset of sequentially distinct RNAs, which serves as a benchmark for generalization capabilities. To ensure a robust evaluation, we also introduce a fourth, more stringent dataset that contains both sequentially and structurally distinct RNAs. We observed that each model predicts the best structure for certain RNAs, and evaluated whether commonly used scoring functions, Rosetta score and ARES, can reliably identify the most accurate structure from the predictions. Finally, since many RNA chains in the Protein Data Bank are part of complexes, we compare the performance of RoseTTAFoldNA and AlphaFold3 in predicting RNA structures within complexes versus isolated RNA chains extracted from these complexes. This comprehensive evaluation highlights the strengths and limitations of current deep learning-based tools and provides valuable insights for advancing RNA 3D structure prediction.

Keywords: benchmark, deep learning, RNA scoring, RNA single chain prediction, RNA tertiary structure prediction

1 Introduction

RNA molecules play key roles in various biological processes, ranging from gene regulation to catalysis [1]. Their functions are closely tied to their 3D structures, making accurate RNA structure prediction essential for understanding RNA biology and for applications in drug discovery and synthetic biology [2, 3, 4]. Experimental methods such as X-ray crystallography and cryo-electron microscopy are often costly and time-consuming, highlighting the need for computational approaches.

The field of protein structure prediction witnessed a paradigm shift with the introduction of AlphaFold2, which achieved remarkable success in predicting protein 3D structures with near-experimental accuracy. Inspired by AlphaFold2's success, similar approaches have been adapted to RNA 3D structure prediction. The models we examine in this study, DRfold [5], DeepFoldRNA [6], RhoFold [7], RoseTTAFoldNA [8], trRosettaRNA [9], and AlphaFold3 [10], build upon deep learning strategies originally developed for proteins and apply them to the unique challenges posed by RNA molecules.

While the adoption of deep learning has advanced the field, it is important to note that many machine learning-based tools for RNA structure prediction, such as those relying on probabilistic graphical models or feature-based methods, predate these advances. Given that each of these deep learning tools has been evaluated primarily against traditional methods, our work concentrates on comparing them directly against each other, with an additional focus on their ability to generalize to unseen, structurally novel RNA sequences.

The significant interest in RNA 3D structure prediction is evident from the growing number of recently published reviews [11, 12, 13, 14] and comparative studies [15, 16, 17, 18, 19]. However, while several studies have compared RNA 3D structure prediction tools, only a few include AlphaFold3 alongside the other tools, or fail to compare all state-of-the-art deep learning-based models on a consistent dataset. Additionally, these comparisons are often conducted on datasets that may overlap with the tools' training data. As a result, they do not effectively evaluate the ability of these tools to generalize to unseen data. Similarly, many benchmarks

rely on relatively small datasets, often with fewer than 50 RNAs, which limits the significance of the results. Furthermore, many studies fail to systematically assess sequence and especially structural similarity between the evaluation and training datasets, which is crucial for understanding true generalization performance.

In this study, we aim to address these limitations by comprehensively comparing six deep learning-based RNA 3D structure prediction tools across four datasets. Our key contributions are:

- **Comprehensive comparison**: We benchmark six tools across three datasets, including RNA Puzzles [20, 21, 22, 23], CASP15 RNA targets [24, 25], and a novel dataset of 190 RNAs published in the Protein Data Bank (PDB) [26] after April 2022, referred to as Dataset 3. This dataset, larger than those used in prior studies, ensures no overlap with the models' training data. Comprising RNAs that are sequentially distinct both among themselves and compared to all RNAs published prior to this cutoff date, Dataset 3 enables us to assess models' generalization capabilities.
- **Evaluation of generalization**: Beyond Dataset 3, we created a fourth, more stringent dataset by selecting RNAs from Dataset 3 that are both sequentially and structurally distinct from RNAs in the training datasets, allowing us to rigorously test the models' ability to generalize to highly dissimilar RNAs, presenting a more challenging and realistic test of their performance.
- **Evaluation of scoring function effectiveness**: We assess commonly used scoring functions, Rosetta score [27] and ARES [28], to determine their effectiveness in identifying the most accurate predicted structures. This approach is motivated by our observation that all models predicted the best structure for at least some RNAs. By incorporating scoring functions, we aim to explore what is the most we can get out of the benchmarked prediction tools.
- **Context-dependent performance comparison**: For RNAs from Dataset 3 that are a part of a complex in the PDB, we predict the entire complex using RoseTTAFoldNA and AlphaFold3. We then compare these predictions to the structures obtained by modeling the isolated RNA chains.

Since this study focuses on RNA tertiary or 3D structure prediction, any mention of structure prediction throughout refers specifically to RNA 3D structures unless otherwise specified.

2 Methods

This section briefly describes the benchmarked tools, datasets used, and metrics calculated for the evaluation.

2.1 Tools

This benchmark evaluates six deep learning-based RNA structure prediction models, each bringing certain unique approaches to the complex task of RNA tertiary structure modeling, which will be described in this subsection. The characteristics of these models are summarized in Table 1.

DRfold takes sequence and secondary structure as inputs and generates embeddings using RNA transformer blocks. Uniquely, DRfold is the only tool that relies solely on the sequence without requiring a multiple sequence alignment (MSA). These embeddings are then fed into a structure module and a geometric module. The structure module predicts nucleotide-wise frames to build full 3D structures in an end-to-end fashion, while the geometric module estimates pairwise nucleotide geometries. By combining outputs from both modules to define energy terms, DRfold gets its final prediction through energy minimization using the L-BFGS algorithm.

DeepFoldRNA processes MSA and secondary structure representations through self-attention layers and linear projections to generate embeddings. These embeddings are then passed to linear layers that predict distance and orientation restraints between nucleotide pairs. Using these restraints to define an energy function, DeepFoldRNA optimizes the structure through L-BFGS minimization to produce the final RNA conformation.

RhoFold (also called E2Efold-3D) first processes MSA using an RNA language model (RNA-FM [29]). These representations go through E2Eformer/Rhoformer, which is based on an attention mechanism, similar to the previous two models, where the key is communication between MSA representation and pair representations. This module is shallower compared to other modules for sequence embedding updates (eg. DRfold has 48 RNA transformer blocks, DeepFoldRNA 48 MSA Transformer blocks, while Rhofold has only 4 Rhoformer blocks). After obtaining these embeddings, they go into 8 layers of structure module, which produce full atom structure.

RoseTTAFoldNA is an adaptation of RoseTTAFold [30, 31], initially designed for protein modeling, extended to predict structures of nucleic acids. This tool can model not only isolated RNA molecules but also more complex structures that include various combinations of proteins, DNA, and RNA. Distinct from other RNA-focused tools, RoseTTAFoldNA uses a three-track architecture: a sequence track that processes MSA inputs, a 2D geometric track capturing base-pair and stacking interactions, and a 3D track that incorporates either structural templates or iteratively refined nucleic acid coordinates. Together, these tracks enable a multi-level representation of the nucleic acid, progressively building up spatial detail and structural accuracy. In the final stage, RoseTTAFoldNA employs a structure refinement module based on the SE(3)-Transformer [32], which leverages symmetry-aware transformations to refine the predicted 3D coordinates, ensuring more accurate and biologically relevant conformations.

Similarly, **trRosettaRNA** builds on the idea from trRosetta [33], a tool initially developed for protein folding through distance and orientation predictions between residue pairs. This adaptation extends those principles to RNA by predicting distances and angles between nucleotide pairs, thus capturing key geometric relationships within RNA structures. Deep learning is applied to derive pairwise nucleotide geometries from MSAs, which then inform energy terms. These energy terms are combined with those from the PyRosetta suite, and energy minimization is conducted to refine the RNA model and achieve the final conformation.

AlphaFold3 builds directly on the AlphaFold family [34, 35, 36], which transformed protein structure prediction with the breakthrough of AlphaFold2. AlphaFold3 extends this architecture and methodology to accommodate various molecules, including RNAs. One of the primary adjustments involves handling atoms directly rather than using frames to represent residues, allowing it to manage different residue types such as amino acids and nucleotides, as well as small molecules and ions. Additionally, AlphaFold3 incorporates a

Tool	Input SS	Input MSA	End-to-end	Post-processing	Uniqueness
DRfold	RNAfold [37], PETfold [38]	no	yes	optimization using end-to-end model + geometric restraints	predicts both end-to-end models and geometric restraints
DeepFoldRNA	PETfold (from MSA)	rMSA [39]	no	refinement using SimRNA [40]	×
RhoFold	no	rMSA, Infernal [41]	yes	relaxation	LM-based embeddings [29]
RoseTTAFoldNA	no	lite rMSA	yes	no	predicts RNA and complexes
trRosettaRNA	SPOT-RNA [42]	rMSA, Infernal	no	no	×
AlphaFold3	no	nhmmer & hmmalign	yes	no	diffusion-based architecture, works with atoms, predicts complexes

Table 1: Properties of deep learning-based RNA 3D structure prediction tools. *Abbreviations used: SS = secondary structure, MSA = multiple sequence alignment.*

diffusion-based structure module instead of the previous Structure module. It can predict RNA structures both as isolated chains and as part of larger RNA-protein complexes.

All of the models, except AlphaFold3, were installed and executed locally. At the moment when this research was conducted, AlphaFold3 was available only as a web server.

2.2 Datasets

In this benchmark, we used four datasets, all described in this section.

Dataset 1 consists of 37 RNA Puzzles from the RNA-Puzzles initiative, a widely-used benchmark. To prevent overlap with Dataset 2, Puzzles 35 and 36, which were CASP15 targets, were excluded. Since most of these Puzzles were published in the Protein Data Bank (PDB) [26], some of them may be part of the training datasets for some of the tools. Even though this dataset may not fully show the generalization capabilities of each model, we included it for its historical value and to demonstrate performance on typical tasks. This approach reflects practical scenarios where, for instance, a structural biologist seeking to predict the structure of a common RNA, such as tRNA, may prioritize reliable results over concerns about potential overlap with training data.

Dataset 2. Historically, CASP primarily focused on assessing the accuracy of protein structure prediction methods. However, the 15th edition marked a significant milestone by including RNAs for the first time [24, 25]. This integration highlights the growing importance of RNA structure prediction in molecular biology and biotechnology. CASP15 presented 12 RNA targets, containing both natural and synthetic RNAs. Our Dataset comprises all 12 of these RNAs. Table 2 shows the type, sequence length and number of sequences in the MSA generated for each RNA target. Notably, synthetic RNAs in this dataset are longer, have more complicated folds and exhibit fewer sequences in their MSAs than natural RNAs, thereby presenting more complex prediction challenges.

Type	Target ID	Type [43]	Length	#MSA seq.
Natural	R1107	RNA	69	2,265
	R1108	RNA	69	4,679
	R1116	RNA	157	2,011
	R1117	RNA/ligand	30	207
	R1149	RNA	124	663
	R1156	RNA	135	58
	R1189	RNA/protein	118	1,339
	R1190	RNA/protein	118	1,339
Synthetic	R1126	RNA	363	1
	R1128	RNA	238	105
	R1136	RNA	374	57
	R1138	RNA	720	0

Table 2: Properties of CASP15 RNA targets

Dataset 3. Our aim was to create a dataset that could effectively evaluate the generalization abilities of the models. Since not all tools explicitly disclose their training datasets, we could not rely on this information alone. Instead, given that all models except AlphaFold3 were developed for CASP15, we used the start of the CASP15 season in April 2022 as a training cutoff. This assumes that all tools were trained on all data available up to that point. To compile this dataset, we selected structures published in the PDB database after April 2022, ensuring that these RNAs were unseen during training. This approach enables a robust assessment of the

Fig. 1: **Process of creating Dataset 3.** The process begins with extracting RNA chains from all complexes available in the Protein Data Bank (PDB). Next, the chains are clustered using MMseqs2 based on a sequence identity threshold of 90% and a minimum coverage of 80%. Clusters are then filtered to include only those where all sequences were published after April 1, 2022, ensuring that the dataset contains RNAs distinct from those used in the training datasets. Furthermore, several filtering criteria are applied to RNA chains and only those that satisfy all criteria are kept. From the remaining clusters, one representative RNA is selected per cluster, and predictions are attempted for all six tools. The final dataset consists of 190 RNAs for which all six tools successfully generated predictions.

models' generalization ability to novel structures. Additionally, AlphaFold3 was trained on data published in the PDB up to the end of September 2021, and uses data published until January 2023 for its validation.

Starting with a download of all available RNA chains from PDB, which was 20,320 RNA chains, we applied sequence identity clustering using MMseqs2 [44, 45], filtering for a minimum sequence identity of 90% and coverage of at least 80%, resulting in 3,822 clusters. Clusters containing only RNAs published after April 2022 were retained, followed by further filtering to remove sequences shorter than 10 nucleotides, with resolution greater than 9 Å, those with fewer than 90% defined residues, and those consisting solely of unknown residues ('N' or 'X'). After these steps, 329 clusters remained, each uniquely represented by sequences with optimal resolution and maximal percentage of nucleotides with defined locations. This process is visualized in Figure 1.

For comparability, we only included sequences for which all models could produce final structures, yielding a final subset of 190 sequences. Notably, 34.2% of RNAs from the final dataset lacked MSA sequence coverage, and 70.5% had fewer than 100 MSA sequences, presenting more challenging tasks.

Dataset 4 is a subset of Dataset 3, designed to include RNAs that are not only sequentially distinct from those in the training datasets but also structurally distinct. To identify these RNAs, we employed the RNA3DB pipeline [46], which clusters RNA structures based on both sequence and structural similarity.

The RNA3DB pipeline comprises four main steps: parsing, filtering, clustering, and splitting the data into training and test sets. Since our goal was to evaluate pre-trained models, we did not perform the splitting step and instead focused on using the structural clusters. We use the same first step, parse all RNA chains from PDB. To align the pipeline with our specific filtering criteria, we modified the filtering step by adjusting the minimum RNA length to 10 nucleotides and including NMR solutions which were not originally included.

During the clustering step, RNAs are first grouped based on 99% sequence identity using MMseqs2. Each representative sequence is then mapped to an Rfam family using Infernal with an E-value cutoff of 1.0, to capture structural homology. The resulting clusters, called components, are formed using the maximally connected subgraphs algorithm. If a representative RNA cannot be mapped to any Rfam family, it is assigned to a special component_0, which is typically recommended as a test set because these RNAs are structurally unique and thus suitable for assessing a model's generalization ability.

After obtaining the clusters, we evaluated if each RNA from Dataset 3 was suitable for inclusion in Dataset 4. Specifically, we checked whether the RNA belonged to a cluster in which all member RNAs were published after April 2022. This criterion ensured that none of the RNA's structural relatives were part of the training datasets. Since Dataset 3 already enforced a sequence identity threshold of less than 90%, we retained the RNA3DB pipeline's default 99% sequence identity threshold. This decision was made to avoid introducing false or missing edges in the graph that is built during the clustering process, as RNA3DB only checks structural similarity for the cluster representative.

Most RNAs from Dataset 3 were assigned to component_0, reflecting their structural dissimilarity from other RNAs. Specifically, 137 out of 190 RNAs in Dataset 3 fell into component_0. An additional six RNAs belonged to other eligible clusters, though three of these were grouped within the same cluster. To avoid redundancy, we selected only one RNA from this group of three for inclusion in Dataset 4.

Dataset 4 comprises 140 RNAs in total, representing a highly stringent benchmark of structurally and sequentially distinct RNAs.

2.3 Metrics

While RMSD and TM-score [47] are widely recognized metrics, metrics like clash score [48] and local Distance Difference Test (lDDT) [49], and especially RNA-specific metrics such as Interaction Network Fidelity (INF) [50], add precision to our evaluation. These metrics offer supplementary insights into specific aspects of RNA structures, offering a well-rounded assessment.

To ensure accurate comparisons, we standardized both predicted and reference structures using RNA_normalizer from RNA-Puzzles Toolkit [51].

RMSD (Root Mean Square Deviation) is a fundamental and widely employed metric for comparing two structures. It calculates the average distance between corresponding atoms in aligned predicted and reference structures. Here, we computed all-atom RMSD using the RNA-Puzzles Toolkit. RMSD values are reported in angstroms (Å), where 1 Å equals 10^{-10} meters, and lower scores indicate closer structural resemblance. RMSD values below 2 Å usually suggest high accuracy, while values between $2-5$ Å are commonly acceptable for broader structural assessments.

TM-score (Template-modeling score) serves as a metric for assessing the overall similarity between two structures, offering a global perspective compared to the localized sensitivity of RMSD. It emphasizes smaller structural differences more than larger ones, making it ideal for capturing global structural alignment. TM-score values range from 0 to 1 where a score of 1 indicates a perfect structural match, while scores above 0.45 denote similar folds, and values below 0.2 suggest a minimal similarity. We utilized USalign [52] to compute the TM-score, employing the alignment option based on the residue index from the PDB files, a crucial step for handling gaps in reference structures without misalignment.

INF (Interaction Network Fidelity) evaluates the fidelity of predicted interactions relative to the interactions from the reference structure, an important factor in RNA structure where Watson-Crick, non-Watson-Crick, and stacking interactions play key roles. INF values range from 0 to 1, with 1 indicating all interactions in the reference structure are correctly predicted, and values close to 0 suggesting significant deviations. We calculated INF using the RNA Puzzles Toolkit, in which essential base interactions are detected by MC-Annotate [53]. Different variants of INF (e.g., INF_WC for Watson-Crick, INF_NWC for non-Watson-Crick, and INF_STACK for stacking interactions) allow us to assess models' performance in predicting specific types of RNA interactions. This specificity is essential, as RNA structural stability relies heavily on accurately capturing these interactions.

The **clash score**, computed with MolProbity [48], quantifies atomic overlaps by calculating the number of clashing atoms per 1,000 atoms with overlaps greater than 0.4 Å. Lower clash scores indicate fewer steric clashes and greater physical plausibility of the structure. While a low clash score supports structural accuracy, it does not guarantee that the model captures the native structure perfectly; instead, it helps ensure the predicted conformation is free from unphysical atomic overlaps.

Finally, **lDDT** (local Distance Difference Test) scores were calculated using OpenStructure [54] to evaluate how well local atomic environments in the model match those in the reference structure. lDDT measures the preservation of atomic distances within a given inclusion radius, capturing local structural fidelity over distances up to 4 Å. The lDDT score ranges from 0 to 1, where values closer to 1 represent higher agreement with the reference structure's local environment. This metric offers a residue-level assessment of structural accuracy, complementing the global orientation provided by RMSD and TM-score by highlighting the consistency of local atomic neighborhoods.

These metrics collectively provide a comprehensive view of RNA structure prediction quality, with each metric highlighting different structural characteristics and supporting a nuanced interpretation of each model's performance.

2.4 Experiments

RNA 3D structure prediction. Most of the tools evaluated in this study predict only single-chain RNAs, making this our primary focus. Since none of the models have published their training code and training them is resource- and time-intensive, we relied on the published weights. We also used the default parameters for all tools. When a model outputs multiple structures, we selected the first structure for comparison. Generating multiple sequence alignments (MSAs) can be time-consuming, so we generated the MSAs once using rMSA [39] and used them as input for all locally installed tools requiring MSAs, including DeepFoldRNA, RhoFold, RoseTTAFoldNA, and trRosettaRNA. For tools that use secondary structure as input, we followed their original pipelines without modifying the default secondary structure prediction model. When multiple structures are available in the PDB for the same RNA, we compare each predicted structure against all available references. For each prediction, we select the reference structure with the lowest all-atom RMSD and use this reference to report all other evaluation metrics. Additionally, we compared the performances of all of the tools on different length ranges and compared performances on single-chain RNAs, RNAs extracted from RNA-RNA complexes and from complexes with proteins.

Scoring functions. We aimed to determine whether the two most commonly used scoring functions, ARES and Rosetta score, could reliably identify the best prediction among the six. ARES is a deep learning-based scoring model for RNA structures, trained on 1000 FARFAR2-predicted structures [55] and their respective RMSDs across 18 RNAs. ARES is trained on RMSD values, meaning lower scores indicate better structural predictions. On the other hand, Rosetta score is an energy-based function from the Rosetta suite, designed to find the most energetically stable structure. Lower values are preferred here as well, although these scores are typically negative.

For our analysis, we first examined how well the scores from ARES and Rosetta correlate with RMSD. We also calculated the percentage of RNAs for which each scoring function selected the truly best prediction - the one with the lowest RMSD. Secondly, we incorporated ARES and Rosetta scores as additional "prediction tools" alongside the six RNA structure prediction models. For each RNA, we selected the prediction that received the

best score from either ARES or Rosetta, and used the corresponding RMSD or TM-score as the data point in our visualizations. This approach allowed us to evaluate if the scoring functions could improve the overall structure prediction, even though they did not directly generate RNA structure predictions.

Complex prediction. Finally, since many RNAs from our Dataset 3 are extracted from complexes, we wanted to check at least with AlphaFold3 and RoseTTAFoldNA, the only two tools that can predict complex structure, if the RNA chain predicted as part of the structure is better compared to when predicted as a single chain, without any context. Unfortunately, the webserver version of AlphaFold3 has a limit of $5,000$ tokens, meaning nucleotides and amino acids combined, and some of the RNA chains were extracted from some very large complexes, which have more than $5,000$ residues, so these could not be predicted as a full complex. In the end, there were 88 complexes, which covered 89 RNA chains from Dataset 3 that could be predicted using AlphaFold3. On the other hand, while we are not aware of such strict rules for RoseTTAFoldNA, we saw that generating a structure with over $1,000$ residues takes a couple of days, so we limited ourselves to predicting only complexes with up to $1,000$ residues. This resulted in 33 complexes and 33 RNA chains from Dataset 3.

3 Results and Discussion

3.1 RNA 3D structure prediction

Overall performance across the datasets. Figure 2 presents all-atom RMSD and TM-score metrics across Datasets 1, 2, and 3. In Figures 2A and 2B, evaluated on Dataset 1, which comprises RNA Puzzles, the models show their best performances, with low RMSD values and relatively high TM-scores. Overall, the tools perform similarly, with trRosettaRNA achieving the lowest mean RMSD of 6 Å, while RoseTTAFoldNA has the lowest median RMSD of 2.65 Å and the highest mean and median TM-score (0.601 and 0.688). These results suggest that Dataset 1 is the easiest for models to predict structures accurately, likely because it contains examples that may have been part of the training data. Interestingly, AlphaFold3 lags significantly behind the other tools, with the highest median RMSD of 6.25 Å and the second-lowest median TM-score of 0.418. For more detailed visualization of all-atom RMSD and TM-score per RNA puzzle, refer to Supplementary Figure S1.

In contrast, Figures 2C and 2D for Dataset 2, CASP15 RNA targets, reveal the poorest performances, with TM-scores approaching values seen in random folds. The high RMSD values, including an extreme case for R1138 (DeepFold's model has RMSD = 178.6 Å), underscore the complexity of Dataset 2 and raise questions about the models' capacity to model complex and large molecules. Supplementary Figure S2 provides additional detail, showing all-atom RMSD and TM-scores for individual RNA targets in Dataset 2. Notably, synthetic RNAs, which appear as outliers in Figure 2C, have the worst predicted structures. For synthetic RNAs, the median RMSD ranges from 28.18 Å for AlphaFold3 to 52.74 Å for DeepFoldRNA, whereas for natural RNAs, RMSDs are lower, from 14.4 Å (DeepFoldRNA) to 17.7 Å (DRfold). The discrepancy likely reflects the more common appearance of natural RNAs in the PDB and, consequently, in the training datasets, making synthetic RNAs more challenging for these models. Interestingly, AlphaFold3 performs relatively well on synthetic RNAs, suggesting a potential advantage in certain unseen cases. However, given that Dataset 2 contains only 12 examples, its small size limits definitive conclusions about the models' broader generalization abilities.

Finally, we specifically curated Dataset 3 to assess the models' generalization abilities. Figure 2E shows that all-atom RMSD values are centered around a median of 10 Å, ranging from 7.9 Å for DeepFoldRNA to 15 Å for AlphaFold3, indicating moderate prediction accuracy but still leaving room for improvement. On the other hand, Figure 2F shows generally low TM-scores across the tools, with median values spanning between 0.21 for RhoFold to 0.27 for DeepFoldRNA, with only a few instances per tool achieving TM-scores above 0.9. These results underscore the difficulty in achieving reliable generalization beyond training data for these tools. An example of predictions for one RNA from Dataset 3 is shown in Figure 3.

Performance based on other important metrics. It is important to note that while RMSD and TM-score offer some insight into structural accuracy, they can yield quite different results for the same predictions. To gain a more comprehensive understanding, we further evaluated these predictions using a range of metrics, including RNA-specific ones. Supplementary Figure S3 illustrates the correlations between various metrics for Dataset 3. For consistency in correlation direction, we inverted the values of RMSD and clash score, as lower values are preferred for these metrics. Interestingly, the only high correlation is between INF_ALL and INF_STACK. This is likely because stacking interactions are present in nearly all RNAs in the dataset, except for two, which also lack both Watson-Crick and non-Watson-Crick interactions. The lack of high correlations among the metrics suggests that each metric captures unique structural information, highlighting the value of using multiple metrics to evaluate predictions. This also implies that different tools may perform best depending on the specific structural aspect under consideration.

Figure 4 illustrates additional evaluation metrics for Dataset 3, including INF_ALL, INF_WC, INF_NWC, INF_STACK, clash score, and lDDT. Results using the same metrics for Datasets 1 and 2 are available in Supplementary Figures S4 and S5. When presenting the INF metrics, the RNA Puzzles toolkit assigns a value of -1 when neither the reference nor the predicted model contains a specific type of interaction. To ensure clarity and consistency in visualization, we excluded RNAs lacking certain interaction types. Additionally, if the reference model includes an interaction that the predicted model fails to capture, we assigned an INF value of 0, treating these instances as significant prediction failures.

For Dataset 3, all of the tools perform best for Watson-Crick interactions (see Figure 4B) and worst for non-Watson-Crick interactions (see Figure 4C). Median values for all interactions range from 0.56 for trRosettaRNA to 0.68 for DeepFoldRNA. DeepFoldRNA also performs the best for stacking interactions with a median of 0.70. AlphaFold3 outperforms other tools by a large margin for non-Watson-Crick interactions, with a median value of 0.26 compared to 0.10 to 0.13 for the rest of the tools. AlphaFold3 is also the best for Watson-Crick interactions, with a very high median of 0.86. In Figure 4E, a few outliers for RhoFold were removed from visualizations. While lower clash scores generally indicate better structural accuracy, DRfold consistently reports a clash score of 0, even though some native structures have a clash score larger than 0. For instance, more than 80% of references in Dataset 3 have clash scores greater than 0. RoseTTAFoldNA has the highest median clash

Fig. 2: **All-atom RMSD and TM-score for evaluated RNAs.** Boxplot representation of all-atom RMSDs and TM-scores for RNA structure predictions by six deep learning-based methods. ARES and Rosetta refer to scoring functions, and for each RNA, the structure presented is the one with the best score among the six predictions according to these functions. The "optimal" column represents a hypothetical perfect scoring approach, where for each RNA the structure with the minimal RMSD among the six predictions is selected. Note that the corresponding TM-score shown for "optimal" selections is not necessarily the highest, as structures were chosen solely based on RMSD. A. All-atom RMSD for Dataset 1 (RNA Puzzles). B. TM-score for Dataset 1 (RNA Puzzles). C. All-atom RMSD for Dataset 2 (CASP15 RNA targets). *DeepFoldRNA structure for R1138, which had an RMSD of 178.6 Å, was excluded from the visualization. D. TM-score for Dataset 2 (CASP15 RNA targets). E. All-atom RMSD for Dataset 3. F. TM-score for Dataset 3. *Abbreviations used: DFR = DeepFoldRNA, RF2NA = RoseTTAFoldNA, trRNA = trRosettaRNA, AF3 = AlphaFold3.*

score (31.54), and AlphaFold3 second-highest (12.93). In terms of the lDDT metric, shown in Figure 4F, DRfold performs the worst (median lDDT = 0.02), whereas DeepFoldRNA exhibits the best performance among the evaluated tools (median lDDT = 0.685).

Overall, DeepFoldRNA demonstrates the strongest performance across the majority of metrics for Dataset 3. Specifically, it achieves the best results for all-atom RMSD, TM-score, INF_all, INF_STACK, and lDDT, while also maintaining a respectable clash score (third best, with a median of 0.76). The only metrics where it falls short are INF_WC and INF_NWC, where AlphaFold3 outperforms it.

Similarly, Supplementary Figure S4 for Dataset 1 reveals that AlphaFold3 achieves the best results for INF_WC and particularly excels in INF_NWC. However, RoseTTAFoldNA slightly outperforms AlphaFold3 in INF_ALL and INF_STACK. For lDDT, trRosettaRNA achieves the highest score, while RoseTTAFoldNA stands out with a relatively high median clash score. Metrics for Dataset 2 are illustrated in Supplementary Figure S5, where AlphaFold3 demonstrates superiority across all evaluated metrics, except for clash score, where it has the second-highest value. Despite this exception, AlphaFold3 performs the best overall for the CASP15 RNA targets.

Fig. 3: **Predictions for RNA chain (PDB_ID: 7PWO_42).** The native structure is shown in green and the predicted structures in blue. All six predicted structures for this RNA chain exhibit relatively high RMSD and low TM-scores. Among these, DRfold and DeepFoldRNA produced the most accurate predictions, capturing a reasonable global fold. ARES selected AlphaFold3's prediction as the best, while Rosetta score favored trRosettaRNA's structure. However, DRfold's prediction had the lowest all-atom RMSD, and DeepFoldRNA's prediction ranked highest by TM-score. Visualizations of the structures were generated using PyMOL [56].

Assessing generalization abilities on Dataset 4. To highlight the impact of splitting datasets based solely on sequence similarity versus on both structural and sequence similarity, we compare all-atom RMSD (in Figure 5A) and TM-score (in Figure 5B) across Dataset 3 and its subset, Dataset 4. While median all-atom RMSD values remain consistent between the two datasets, indicating similar overall trends, TM-scores on Dataset 4 show a slight decrease, with DRfold emerging as the top performer, achieving a median of 0.239. This suggests that factoring in both structural and sequence similarity when creating subsets may be important for accurately assessing model performance, as it can reveal subtler distinctions in prediction quality that a sequence-only split might overlook. Other metrics for Dataset 4 are shown in Supplementary Figure S6. Given that Dataset 4 comprises over 70% of Dataset 3, it is unsurprising that the overall conclusions remain consistent. DeepFoldRNA continues to outperform other models across most metrics, confirming it generalizes better than the other models. However, the results still fall short of desirable levels, with median RMSD values around 10 Å and median TM-scores only slightly exceeding 0.2, which are comparable to random fold values. While some INF metrics, such as INF_WC, show promising median values above 0.9, there remains significant room for improvement, particularly in INF_NWC. Future efforts should focus on enhancing the models' ability to accurately predict stacking interactions and, most critically, complex non-Watson-Crick interactions, which are essential for capturing biologically accurate RNA conformations.

Performance per different RNA length groups. To assess the impact of RNA length on prediction accuracy, we divided RNAs from Dataset 3 into length-based groups: 0–50, 50–100, 100–150 nucleotides, and grouped all four longer RNAs together. Figure 6 presents all-atom RMSD (Figure 6A) and TM-score (Figure 6B) for each group. While the shortest group (0–50 nucleotides) includes some outliers, it generally shows the lowest median RMSD values, except for AlphaFold3, which performs slightly better on the next, longer group. The results indicate that all tools struggle most with the longest RNAs, where DeepFoldRNA shows the highest RMSD and DRfold the lowest.

Interestingly, TM-scores are lowest for the shortest RNAs, in contrast to RMSD results. This observation aligns with findings from other studies, which suggest that the TM-score is more stringent for very short RNAs (length < 30) [57]. Predictably, the longest RNAs also exhibit the poorest TM-scores, further questioning the predictive quality of these tools for larger structures.

Performance across different RNA types. To evaluate model performance across different RNA types, we examined single-chain RNAs, RNA chains from RNA-RNA complexes, and RNA chains from RNA-protein complexes, all from Dataset 3. Figure 7 presents the all-atom RMSD and TM-score results for each category. The dataset includes 17 single-chain RNAs, 7 RNA chains from RNA-RNA complexes, and 166 RNA chains from RNA-protein complexes.

For single-chain RNAs, AlphaFold3 stands out with the highest median TM-score of 0.38, significantly above the second-best, RoseTTAFoldNA with a median TM-score 0.29, while DeepFoldRNA achieves the best median RMSD of 4.57 Å. DRfold performs best for RNA-RNA complex chains, achieving the lowest median RMSD (2.03 Å), significantly outperforming other tools, while DeepFoldRNA achieves the highest median TM-score (0.33) for this category. RNA chains within RNA-protein complexes generally show the poorest results, with DeepFoldRNA performing the best in this category, achieving a median RMSD of 8.11 Å and a TM-score of 0.26.

Fig. 4: **Other important metrics for Dataset 3.** For INF metrics, all RNAs that do not have a certain type of interaction are excluded from visualizations. A. INF_ALL (excludes two RNAs without any interactions). B. INF_WC (excludes 119 RNAs without any Watson-Crick interactions). C. INF_NWC (excludes 135 RNAs without any non-Watson-Crick interactions). D. INF_STACK (excludes two RNAs without stacking interactions). E. Clash score. *RhoFold structures with very large clash scores were excluded from the visualization. F. lDDT. *Abbreviations used: DFR = DeepFoldRNA, RF2NA = RoseTTAFoldNA, trRNA = trRosettaRNA, AF3 = AlphaFold3.*

This aligns with expectations, as most tools, except RoseTTAFoldNA and AlphaFold3, were trained exclusively on single RNA chains without additional structural context, leading to better performance on single-chain RNAs. Interestingly, TM-scores are highest not for single-chain RNAs but for RNA-RNA complexes.

Overall, it is difficult to definitively say that one tool outperforms the others, as different tools excel for different datasets and metrics. Most tools perform similarly, and their results still fall short of the accuracy achieved in protein structure prediction, leaving substantial room for improvement. Given their comparable performance, we investigated which tool performs best for each RNA from Dataset 3 in terms of RMSD and TM-score, with the results shown in Figure 8. The figure illustrates that all six tools predict the best structure for some RNAs, and same as before, the results vary depending on the evaluation metric used. For instance, Figure 8B shows that while AlphaFold3 often achieves the highest TM-scores, its predictions do not consistently perform as well when evaluated by all-atom RMSD. The same analysis for Dataset 1 and Dataset 2 are shown in Supplementary Figures S7 and S8. These findings prompted us to explore the possibility of selecting the best prediction by combining tools and scoring the outcomes, potentially leading to higher-quality predictions.

3.2 Scoring functions

For scoring, we used ARES and Rosetta scores. In Figure 2, each panel (A–E) includes a gray dashed line, followed by boxes that represent RMSD and TM-score for the predictions scored as the best by these two

Fig. 5: **Comparison of all-atom RMSD and TM-score for Dataset 3 and its more stringent subset Dataset 4.** There are 190 RNA chains in Dataset 3 and 140 RNA chains in Dataset 4. A. RMSD for Datasets 3 and 4. B. TM-score for Datasets 3 and 4. *Abbreviations used: DFR = DeepFoldRNA, RF2NA = RoseTTAFoldNA, trRNA = trRosettaRNA, AF3 = AlphaFold3.*

scorers. These are followed by a box labeled "optimal", representing a hypothetical perfect scoring approach that selects the structure with the lowest RMSD among the six predictions for each RNA. This inclusion illustrates the potential improvement achievable with an optimal scoring method and highlights the best possible results attainable with the current prediction models.

Rosetta score predominantly selects trRosettaRNA's predictions, likely because trRosettaRNA's refinements are guided by Rosetta's own energy function. As a result, the Rosetta scoring column looks the same as trRosettaRNA's results in Datasets 1 and 3. For Dataset 2, Rosetta score chose DeepFoldRNA's prediction for R1138 as the best, despite this structure's exceptionally high RMSD of 178.6 Å, leading Rosetta score to select the best structure in only 12.52% of RNAs overall (13.51% for Dataset 1, 16.67% for Dataset 2 and 7.37% for Dataset 3). Spearman correlation between Rosetta score and RMSD is 0.0131 for Dataset 1, 0.1810 for Dataset 2 and -0.0208 for Dataset 3, with these low values indicating that predictions of structural accuracy are similar to a random choice.

ARES, commonly used by many groups in CASP competitions, was somewhat better. We noticed that it favored AlphaFold3's predictions in many cases, or to be precise, for all RNAs in Dataset 2, all but three RNAs in Dataset 1, and 85.79% RNAs in Dataset 3. Thus, it selected the best structure only for only 15.9% of all RNAs

Fig. 6: **RMSD and TM-score for Dataset 3 per length group**. There are 136 RNAs with lengths shorter than 50, 32 RNAs with lengths between 50 and 100, 18 RNAs with lengths between 100 and 150, and 4 RNAs with lengths between 200 and 350. In Dataset 3, there are no RNA chains with lengths between 150 and 200 nucleotides. A. All-atom RMSD. B. TM-score. *Abbreviations used: DFR = DeepFoldRNA, RF2NA = RoseTTAFoldNA, trRNA = trRosettaRNA, AF3 = AlphaFold3.*

(5.41% of Dataset 1, 33.33% in Dataset 2 and 8.95% in Dataset 3). Spearman correlation between ARES scores and RMSD is 0.0317 for Dataset 1, 0.2952 for Dataset 2, and -0.1856 for Dataset 3. These poor results may come from ARES being trained exclusively on structures generated using FARFAR2, suggesting that retraining it with structures predicted by tools benchmarked here could enhance its performance.

The optimal scoring function would significantly reduce the average RMSD and improve TM-scores across datasets. For Dataset 1, the average RMSD would decrease from 6.006 Å, achieved by trRosettaRNA, to 2.916 Å, while the average TM-score would increase from 0.601, achieved by RoseTTAFoldNA, to 0.718. On Dataset 2, the average RMSD would improve from 20.272 Å for AlphaFold3 to 17.579 Å. However, discrepancies between metrics become evident when comparing the TM-scores for Dataset 2; the average TM-score for structures selected based on minimum RMSD would drop slightly to 0.307 compared to AlphaFold3's 0.317. For Dataset 3, an optimal scorer would reduce the average RMSD from 11.697 Å for DeepFoldRNA to 9.146 Å, and the TM-score would improve from 0.296 (DeepFoldRNA) to 0.302. These results highlight the potential for improvement with a perfect scoring function and the challenges posed by conflicting metrics.

We conclude that the existing scoring methods do not significantly aid in consistently selecting the best structure among model predictions, and we believe that working on such scoring functions could benefit the field.

3.3 Complex prediction

Most tools predict only single RNA chains, yet the majority of RNA chains in the PDB come from complexes. This led us to investigate whether predictions for these chains improve when the entire complex is predicted, as opposed to predicting the RNA chain alone. This comparison was possible only for AlphaFold3 and RoseTTAFoldNA. As previously noted, AlphaFold3 enabled us to predict 88 complexes, from which we extracted 89 RNA chains, while RoseTTAFoldNA allowed for 33 complex predictions. Figure 9 compares the RMSD values for chains predicted within a complex versus as single RNA chains.

For AlphaFold3, predictions within the full complex are notably more accurate than those for isolated RNA chains. However, for RoseTTAFoldNA, this trend does not hold; in fact, single-chain predictions often yield better results than those from complex predictions. These unexpected differences may stem from the varying

Fig. 7: **All-atom RMSD and TM-score for different RNA types: single chain RNAs, RNA chains extracted from RNA-RNA complexes and extracted from RNA-protein complexes.** A. RMSD for single chain RNAs from Dataset 3 (17 RNA chains). B. TM-score for single chain RNAs from Dataset 3 (17 RNA chains). C. RMSD for RNA chains from RNA-RNA complexes from Dataset 3 (7 RNA chains). D. TM-score for RNA chains from RNA-RNA complexes from Dataset 3 (7 RNA chains). E. RMSD for RNA chains from protein-RNA complexes from Dataset 3 (166 RNA chains). F. TM-score for RNA chains from protein-RNA complexes from Dataset 3 (166 RNA chains). *Abbreviations used: DFR = DeepFoldRNA, RF2NA = RoseTTAFoldNA, trRNA = trRosettaRNA, AF3 = AlphaFold3.*

proportions of single-chain and complex examples in each model's training dataset, even though both models were trained on both complex and single-chain RNA structures.

To provide a broader comparison of complex prediction results, we present an overview of both AlphaFold3 and RoseTTAFoldNA performance in complex prediction mode in Figure 10. Figures 10A and 10B show the all-atom RMSD and TM-score, respectively, for the 89 RNA chains predicted using AlphaFold3. Figures 10C and 10D present the all-atom RMSD and TM-score for the 33 RNA chains predicted using RoseTTAFoldNA in complex mode.

The results show that AlphaFold3's complex predictions yield the best outcomes, achieving superior accuracy in both RMSD and TM-score. Supplementary Figures S9 and S10 further confirm this, showing additional metrics for these subsets. Notably, AlphaFold3 demonstrates strong performance in INF metrics, particularly for non-Watson-Crick interactions, highlighting its advantage in complex prediction accuracy.

3.4 Computation time

While performance is critical to assess, computational efficiency is equally important for practical applications, especially in scenarios where structure prediction occurs repeatedly within a training loop, as in models like gRNAde [58] for inverse folding. High execution times in such cases can pose significant challenges.

Fig. 8: **Percentage of RNA chains for which each tool predicted the best structures according to lowest RMSD and highest TM-score for Dataset 3.** A. The best structure for each RNA is determined according to all-atom RMSD. B. The best structure for each RNA is determined according to TM-score.

Fig. 9: **All-atom RMSD for structures of RNA chains predicted as a single chain and part of a complex.** There are 89 RNA chains predicted by AlphaFold3 and 33 RNA chains predicted by RoseTTAFoldNA, with fewer predictions due to resource constraints and time limitations. Data points below the diagonal line indicate that the prediction made as part of a complex has a lower RMSD and is thus more accurate, whereas points above the line signify that the single-chain prediction yields a better result.

Since generating MSAs can be time-consuming, we opted to compute them once and use the same MSAs across all tools that require them: DeepFoldRNA, RhoFold, RoseTTAFoldNA, and trRosettaRNA. This approach introduces some limitations in fair time comparisons, as DRfold does not require MSAs. Nonetheless, we believe that presenting an execution time overview is still informative. Supplementary Figure S11 shows execution times (in hours) for Dataset 3 RNAs for five tools that were run locally. AlphaFold3 is excluded because while this research was conducted, it was only available as an online server, where resource details were unavailable.

Among the other tools, DeepFoldRNA typically requires the longest runtime. Both DeepFoldRNA and DRfold demonstrate exponential growth in execution time with RNA length. For instance, the longest RNA in our dataset (under 350 nucleotides) took nearly 40 hours for both DeepFoldRNA and DRfold to process, while another slightly shorter RNA took DRfold almost 100 hours (over four days) to complete. For both tools, the time-intensive step is L-BFGS optimization: this step is essential for DeepFoldRNA, which only outputs geometrical restraints. In DRfold, however, frames are produced, but then DRfold combines these frames and a geometrically informed energy function that it then minimizes, adding substantial computation time.

While execution time is a critical factor in practical applications, its importance depends on the specific use case. Generating MSAs is particularly time-intensive, making pipelines that perform well with only single-sequence inputs highly desirable for tasks where rapid predictions are prioritized. For scenarios where accuracy is more critical than speed, the additional computational time required by methods like L-BFGS optimization or refinement may be justifiable. However, introducing flexibility into prediction pipelines, for example, an optional flag to toggle resource-intensive steps like MSA generation or optimization, could offer a balanced approach, allowing users to adapt the pipeline based on their specific requirements, whether for exploratory analysis or higher-precision predictions.

Fig. 10: **RMSD and TM-score for RNA chains from some complexes from Dataset 3.** The suffix "_complex" indicates predictions for the entire complex, not just the RNA chain within it. A. All-atom RMSD for 89 RNA chains from complexes that can be predicted by AlphaFold3 (complexes with fewer than 5000 residues). B. TM-score for the same 89 RNA chains from complexes predicted by AlphaFold3 (complexes with fewer than 5000 residues). C. All-atom RMSD for 33 RNA chains from complexes. D. TM-score for the same 33 RNA chains from complexes. *Abbreviations used: DFR = DeepFoldRNA, RF2NA = RoseTTAFoldNA, trRNA = trRosettaRNA, AF3 = AlphaFold3.*

4 Conclusion

This study benchmarked six state-of-the-art deep learning-based tools for RNA 3D structure prediction across four diverse datasets, employing a range of metrics such as all-atom RMSD, TM-score, INF metrics, clash score, and lDDT. The evaluation revealed varied performance among tools, influenced by dataset composition, RNA characteristics, and the choice of metric, highlighting the inherent challenges in comprehensive comparisons.

Dataset-specific analysis showed that tool performance can vary significantly. On Dataset 1, which comprises the RNA Puzzles, most tools perform similarly well, with AlphaFold3 slightly underperforming compared to others. The generally high performance on this dataset is likely due to overlaps between the RNA Puzzles and the tools' training datasets. On Dataset 2, consisting of CASP15 RNA targets, AlphaFold3 emerged as the top performer across most metrics, except for clash score. It excelled in predicting synthetic RNAs, but with RMSD values exceeding 20 Å and TM-scores below 0.5. For natural RNAs within Dataset 2, DeepFoldRNA achieved the best RMSD values, although AlphaFold3 retained an advantage in TM-scores. Evaluations on the proposed Dataset 3 highlighted DeepFoldRNA as the overall best-performing tool, excelling across most metrics except INF_WC and INF_NWC, where AlphaFold3 showed better results. Finally, Dataset 4, a subset of Dataset 3 emphasizing structural and sequence dissimilarity, confirmed DeepFoldRNA's best generalization capabilities among the tools, with performance trends consistent with those observed in Dataset 3.

Tool performance also depended on RNA chain context and length. For shorter RNAs, predictions generally achieved better RMSD values, while TM-scores were highest for RNAs between 50 and 100 nucleotides, reflecting the metric's stricter evaluation of very short RNAs. As RNA length increased even further, prediction accuracy steadily declined across all tools.

Single-stranded RNAs showed the best results overall, likely because all tools were primarily trained on this type of RNA. For RNA-RNA complexes, DRfold stood out as the best-performing tool. Interestingly, for RNA chains derived from RNA-protein complexes, DeepFoldRNA performed the best, an unexpected result given that AlphaFold3 and RoseTTAFoldNA were the only models trained on RNA-protein complexes.

Further experiments comparing predictions for RNA chains modeled as single entities versus as part of a complex revealed that AlphaFold3 performed significantly better when predicting full complexes. This suggests that incorporating structural context during model training could substantially improve predictions, especially for RNAs within complex environments.

Our evaluation of the ARES and Rosetta scoring functions showed limited success in reliably identifying the best predictions among the six tools. This underscores a critical area for improvement in RNA structure prediction: the development of robust scoring functions to aid in selecting the most accurate structures. Despite their limitations, each structure prediction tool demonstrated unique strengths, with all six occasionally producing the best predictions for specific RNAs. This diversity suggests that rather than striving to identify a universally superior tool, future efforts should focus on strategies to integrate or select the best predictions based on the specific context and available data.

Overall, while the evolution of deep learning-based tools for RNA structure prediction is promising, significant work remains to refine their performance and address existing limitations. Accurate RNA structure prediction is crucial not only for advancing our understanding of RNA biology but also for unlocking new possibilities in drug discovery, RNA-based therapeutics, and biotechnological innovations.

5 Data availability

We have made all sequences, MSAs and predicted structures for Datasets 1–3 publicly available, along with the extracted RNA chains from references for Dataset 3. Additionally, we provide the list of PDB IDs for RNAs included in Dataset 4 and the RNA chains extracted from complex predictions. All data can be accessed at https://zenodo.org/records/14219735.

The Protein Data Bank, from which we downloaded RNA structures and selected some for the creation of Dataset 3, is accessible at https://www.rcsb.org.

The AlphaFold3 web server can be accessed at https://alphafoldserver.com/welcome. Later, AlphaFold3's team made the inference code publicly available at https://github.com/google-deepmind/alphafold3.

DRfold was downloaded in May 2023 as a standalone program from https://zhanggroup.org/DRfold/. It is also available as a web server and on GitHub at https://github.com/leeyang/DRfold.

DeepFoldRNA was downloaded in May 2023 from https://github.com/robpearc/DeepFoldRNA. It is also accessible at https://zhanggroup.org/DeepFoldRNA/ as both a web server and a standalone program.

RhoFold was obtained in May 2023 from a GitHub repository that is no longer available (https://github.com/RFOLD/RhoFold.git). However, an alternative repository is accessible at https://github.com/Dharmogata/RhoFold. RhoFold is also available as a web server at https://proj.cse.cuhk.edu.hk/aihlab/rhofold/.

RoseTTAFold2NA was obtained in June 2023 from https://github.com/uw-ipd/RoseTTAFold2NA.

trRosettaRNA was downloaded in June 2023 from https://yanglab.qd.sdu.edu.cn/trRosettaRNA/download/. It is also accessible as a web server at https://yanglab.qd.sdu.edu.cn/trRosettaRNA/.

ARES was retrieved in July 2023 from https://zenodo.org/records/6893040.

The Rosetta suite, which provides Rosetta score, was downloaded in April 2024 from https://rosettacommons.org/software/download/.

USalign was acquired in May 2023 from https://zhanggroup.org/US-align/.

OpenStructure was utilized via a Docker container, which was downloaded in April 2024 from https://openstructure.org/download/.

For clash score calculations, we used the MolProbity package included in Phenix, downloaded in April 2024 from https://phenix-online.org/download/.

Supplementary information

The paper contains supplementary material.

Acknowledgements

The authors would like to thank Robin Pearce for the help with running DeepFoldRNA and valuable comments on this work, and Rafael Josip Penić on fruitful discussion on this work.

Funding. This work was supported in part by the National Research Foundation (NRF) Competitive Research Programme (CRP) under Project *Identifying Functional RNA Tertiary Structures in Dengue Virus* [NRF-CRP27-2021RS-0001 to M.Š.]; in part by Agency for Science, Technology and Research (A*STAR) Industry Alignment Fund - Pre-positioning Programme (IAF-PP) under Project *Drugging RNA: Our Goal for Oncology (DRAGON)* [H23J2a0094 to M.Š.].

The computational work for this article was partially performed on resources of the National Supercomputing Centre, Singapore (https://www.nscc.sg).

Author contributions

M.Š. and Y.Z. conceived the project and designed the experiments with the help of T.V. and Y.L. M.Š. and B.H. supervised the work. I.M. conducted the experiments, prepared data, and wrote the manuscript. T.V. participated in discussions and wrote the manuscript. All authors reviewed the manuscript and approved the final version.

Competing interests

The authors declare no competing interests.

References

[1] Run-Wen Yao, Yang Wang, and Ling-Ling Chen. Cellular functions of long noncoding RNAs. *Nature Cell Biology*, 21(5):542–551, May 2019.

[2] Katherine Deigan Warner, Christine E Hajdin, and Kevin M Weeks. Principles for targeting RNA with drug-like small molecules. *Nature Reviews Drug Discovery*, 17(8):547–558, August 2018.

[3] Cormac Sheridan. First small-molecule drug targeting RNA gains momentum. *Nature Biotechnology*, 39(1):6–8, January 2021.

[4] Peter B Dykstra, Matias Kaplan, and Christina D Smolke. Engineering synthetic RNA devices for cell control. *Nature Reviews Genetics*, 23(4):215–228, April 2022.

[5] Yang Li, Chengxin Zhang, Chenjie Feng, Robin Pearce, P. Lydia Freddolino, and Yang Zhang. Integrating end-to-end learning with deep geometrical potentials for ab initio RNA structure prediction. *Nature Communications*, 14(1):5745, Sep 2023.

[6] Robin Pearce, Gilbert S Omenn, and Yang Zhang. De novo RNA tertiary structure prediction at atomic resolution using geometric potentials from deep learning. *bioRxiv*, pages 2022–05, 2022.

[7] Tao Shen, Zhihang Hu, Zhangzhi Peng, Jiayang Chen, Peng Xiong, Liang Hong, Liangzhen Zheng, Yixuan Wang, Irwin King, Sheng Wang, et al. E2Efold-3D: end-to-end deep learning method for accurate de novo RNA 3D structure prediction. *arXiv preprint arXiv:2207.01586*, 2022.

[8] Minkyung Baek, Ryan McHugh, Ivan Anishchenko, Hanlun Jiang, David Baker, and Frank DiMaio. Accurate prediction of protein-nucleic acid complexes using RoseTTAFoldNA. *Nature Methods*, 21(1):117–121, Jan 2024.

[9] Wenkai Wang, Chenjie Feng, Renmin Han, Ziyi Wang, Lisha Ye, Zongyang Du, Hong Wei, Fa Zhang, Zhenling Peng, and Jianyi Yang. trRosettaRNA: automated prediction of RNA 3D structure with transformer network. *Nature Communications*, 14(1):7266, Nov 2023.

[10] Josh Abramson, Jonas Adler, Jack Dunger, Richard Evans, Tim Green, Alexander Pritzel, Olaf Ronneberger, Lindsay Willmore, Andrew J Ballard, Joshua Bambrick, et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature*, pages 1–3, 2024.

[11] Jinsong Zhang, Yuhan Fei, Lei Sun, and Qiangfeng Cliff Zhang. Advances and opportunities in RNA structure experimental determination and computational modeling. *Nature methods*, 19(10):1193–1207, 2022.

[12] Xunxun Wang, Shixiong Yu, En Lou, Ya-Lan Tan, and Zhi-Jie Tan. RNA 3D structure prediction: progress and perspective. *Molecules*, 28(14):5532, 2023.

[13] Jun Zhang, Mei Lang, Yaoqi Zhou, and Yang Zhang. Predicting RNA structures and functions by artificial intelligence. *Trends in Genetics*, 2024.

[14] Sunandan Mukherjee, S Naeim Moafinejad, Nagendar Goud Badepally, Katarzyna Merdas, and Janusz M Bujnicki. Advances in the field of RNA 3D structure prediction and modeling, with purely theoretical approaches, and with the use of experimental data. *Structure*, 2024.

[15] Akash Bahai, Chee Keong Kwoh, Yuguang Mu, and Yinghui Li. Systematic benchmarking of deep-learning methods for tertiary RNA structure prediction. *bioRxiv*, pages 2024–02, 2024.

[16] Clément Bernard, Guillaume Postic, Sahar Ghannay, and Fariza Tahi. State-of-the-RNArt: benchmarking current methods for RNA 3D structure prediction. *NAR Genomics and Bioinformatics*, 6(2):lqae048, 2024.

[17] Clément Bernard, Guillaume Postic, Sahar Ghannay, and Fariza Tahi. Has AlphaFold 3 reached its success for RNAs? *bioRxiv*, pages 2024–06, 2024.

[18] Chandran Nithin, Sebastian Kmiecik, Roman Błaszczyk, Julita Nowicka, and Irina Tuszyńska. Comparative analysis of RNA 3D structure prediction methods: towards enhanced modeling of RNA–ligand interactions. *Nucleic Acids Research*, 52(13):7465–7486, 2024.

[19] Sumit Tarafder, Rahmatullah Roche, and Debswapna Bhattacharya. The landscape of RNA 3D structure modeling with transformer networks. *Biology Methods and Protocols*, 9(1):bpae047, 2024.

[20] José A. Cruz, Marc-Frédérick Blanchet, Michal Boniecki, Janusz M. Bujnicki, Shi-Jie Chen, Song Cao, Rhiju Das, Feng Ding, Nikolay V. Dokholyan, Samuel C. Flores, et al. RNA-Puzzles: a CASP-like evaluation of RNA three-dimensional structure prediction. *RNA (Cambridge)*, 18(4):610–625, 2012.

[21] Zhichao Miao, Ryszard W. Adamiak, Marc-Frédérick Blanchet, Michal Boniecki, Janusz M. Bujnicki, Shi-Jie Chen, Clarence Cheng, Grzegorz Chojnowski, Fang-Chieh Chou, Pablo Cordero, et al. RNA-Puzzles Round II: assessment of RNA structure prediction programs applied to three large RNA structures. *RNA (Cambridge)*, 21(6):1066–1084, 2015.

[22] Zhichao Miao, Ryszard W. Adamiak, Maciej Antczak, Robert T. Batey, Alexander J. Becka, Marcin Biesiada, Michał J. Boniecki, Janusz M. Bujnicki, Shi-Jie Chen, Clarence Y. Cheng, et al. RNA-Puzzles Round III: 3D RNA structure prediction of five riboswitches and one ribozyme. *RNA (Cambridge)*, 23(5):655–672, 2017.

[23] Zhichao Miao, Ryszard W Adamiak, Maciej Antczak, Michał J Boniecki, Janusz Bujnicki, Shi-Jie Chen, Clarence Yu Cheng, Yi Cheng, Fang-Chieh Chou, Rhiju Das, et al. RNA-Puzzles Round IV: 3D structure predictions of four ribozymes and two aptamers. *RNA*, 26(8):982–995, 2020.

[24] Rhiju Das, Rachael C Kretsch, Adam J Simpkin, Thomas Mulvaney, Phillip Pham, Ramya Rangan, Fan Bu, Ronan M Keegan, Maya Topf, Daniel J Rigden, et al. Assessment of three-dimensional RNA structure prediction in CASP15. October 2023.

[25] Rachael C Kretsch, Ebbe S Andersen, Janusz M Bujnicki, Wah Chiu, Rhiju Das, Bingnan Luo, Benoît Masquida, Ewan KS McRae, Griffin M Schroeder, Zhaoming Su, et al. RNA target highlights in CASP15: Evaluation of predicted models by structure providers. *Proteins: Structure, Function, and Bioinformatics*, 91(12):1600–1615, 2023.

[26] Helen M. Berman, John Westbrook, Zukang Feng, Gary Gilliland, T. N. Bhat, Helge Weissig, Ilya N. Shindyalov, and Philip E. Bourne. The Protein Data Bank. *Nucleic Acids Research*, 28(1):235–242, January 2000.

[27] Rebecca F Alford, Andrew Leaver-Fay, Jeliazko R Jeliazkov, Matthew J O'Meara, Frank P DiMaio, Hahnbeom Park, Maxim V Shapovalov, P Douglas Renfrew, Vikram K Mulligan, Kalli Kappel, et al. The rosetta all-atom energy function for macromolecular modeling and design. *Journal of chemical theory and computation*, 13(6):3031–3048, 2017.

[28] Raphael JL Townshend, Stephan Eismann, Andrew M Watkins, Ramya Rangan, Masha Karelina, Rhiju Das, and Ron O Dror. Geometric deep learning of RNA structure. *Science*, 373(6558):1047–1051, 2021.

[29] Jiayang Chen, Zhihang Hu, Siqi Sun, Qingxiong Tan, Yixuan Wang, Qinze Yu, Licheng Zong, Liang Hong, Jin Xiao, Tao Shen, et al. Interpretable RNA foundation model from unannotated data for highly accurate RNA structure and function predictions. *bioRxiv*, pages 2022–08, 2022.

[30] Minkyung Baek, Frank DiMaio, Ivan Anishchenko, Justas Dauparas, Sergey Ovchinnikov, Gyu Rie Lee, Jue Wang, Qian Cong, Lisa N Kinch, R Dustin Schaeffer, et al. Accurate prediction of protein structures and interactions using a three-track neural network. *Science*, 373(6557):871–876, 2021.

[31] Minkyung Baek, Ivan Anishchenko, Ian Humphreys, Qian Cong, David Baker, and Frank DiMaio. Efficient and accurate prediction of protein structure using RoseTTAFold2. *bioRxiv*, pages 2023–05, 2023.

[32] Fabian Fuchs, Daniel Worrall, Volker Fischer, and Max Welling. SE(3)-Transformers: 3D roto-translation equivariant attention networks. *Advances in neural information processing systems*, 33:1970–1981, 2020.

[33] Zongyang Du, Hong Su, Wenkai Wang, Lisha Ye, Hong Wei, Zhenling Peng, Ivan Anishchenko, David Baker, and Jianyi Yang. The trRosetta server for fast and accurate protein structure prediction. *Nature protocols*, 16(12):5634–5651, 2021.

[34] Andrew W Senior, Richard Evans, John Jumper, James Kirkpatrick, Laurent Sifre, Tim Green, Chongli Qin, Augustin Žídek, Alexander WR Nelson, Alex Bridgland, et al. Improved protein structure prediction using potentials from deep learning. *Nature*, 577(7792):706–710, 2020.

[35] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596(7873):583–589, Aug 2021.

[36] Richard Evans, Michael O'Neill, Alexander Pritzel, Natasha Antropova, Andrew Senior, Tim Green, Augustin Žídek, Russ Bates, Sam Blackwell, Jason Yim, et al. Protein complex prediction with alphafold-multimer. *biorxiv*, pages 2021–10, 2021.

[37] Ronny Lorenz, Stephan H Bernhart, Christian Höner zu Siederdissen, Hakim Tafer, Christoph Flamm, Peter F Stadler, and Ivo L Hofacker. ViennaRNA Package 2.0. *Algorithms for molecular biology*, 6:1–14, 2011.

[38] Stefan E Seemann, Jan Gorodkin, and Rolf Backofen. Unifying evolutionary and thermodynamic information for RNA folding of multiple alignments. *Nucleic Acids Research*, 36(20):6355–6362, 2008.

[39] Chengxin Zhang, Yang Zhang, and Anna Marie Pyle. rMSA: a sequence search and alignment algorithm to improve RNA structure modeling. *Journal of Molecular Biology*, 435(14):167904, 2023.

[40] Michal J Boniecki, Grzegorz Lach, Wayne K Dawson, Konrad Tomala, Pawel Lukasz, Tomasz Soltysinski, Kristian M Rother, and Janusz M Bujnicki. SimRNA: a coarse-grained method for RNA folding simulations and 3D structure prediction. *Nucleic acids research*, 44(7):e63–e63, 2016.

[41] Eric P Nawrocki and Sean R Eddy. Infernal 1.1: 100-fold faster rna homology searches. *Bioinformatics*, 29(22):2933–2935, 2013.

[42] Jaswinder Singh, Jack Hanson, Kuldip Paliwal, and Yaoqi Zhou. RNA secondary structure prediction using an ensemble of two-dimensional deep neural networks and transfer learning. *Nature communications*, 10(1):5407, 2019.

[43] Rhiju Das, Rachael C Kretsch, Adam J Simpkin, Thomas Mulvaney, Phillip Pham, Ramya Rangan, Fan Bu, Ronan M Keegan, Maya Topf, Daniel J Rigden, et al. Assessment of three-dimensional RNA structure prediction in CASP15. *Proteins: Structure, Function, and Bioinformatics*, 91(12):1747–1770, 2023.

[44] Martin Steinegger and Johannes Söding. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nature Biotechnology*, 35(11):1026–1028, November 2017.

[45] Martin Steinegger and Johannes Söding. Clustering huge protein sequence sets in linear time. *Nature Communications*, 9(1):2542, June 2018.

[46] Marcell Szikszai, Marcin Magnus, Siddhant Sanghi, Sachin Kadyan, Nazim Bouatta, and Elena Rivas. RNA3DB: A structurally-dissimilar dataset split for training and benchmarking deep learning models for RNA structure prediction. *Journal of Molecular Biology*, page 168552, 2024.

[47] Yang Zhang and Jeffrey Skolnick. Scoring function for automated assessment of protein structure template quality. *Proteins: Structure, Function, and Bioinformatics*, 57(4):702–710, 2004.

[48] Vincent B Chen, W Bryan Arendall, Jeffrey J Headd, Daniel A Keedy, Robert M Immormino, Gary J Kapral, Laura W Murray, Jane S Richardson, and David C Richardson. MolProbity: all-atom structure validation for macromolecular crystallography. *Acta Crystallographica Section D: Biological Crystallography*, 66(1):12–21, 2010.

[49] Valerio Mariani, Marco Biasini, Alessandro Barbato, and Torsten Schwede. lddt: a local superposition-free score for comparing protein structures and models using distance difference tests. *Bioinformatics*, 29(21):2722–2728, 2013.

[50] Marc Parisien, José Almeida Cruz, Éric Westhof, and François Major. New metrics for comparing and assessing discrepancies between rna 3d structures and models. *Rna*, 15(10):1875–1885, 2009.

[51] Marcin Magnus, Maciej Antczak, Tomasz Zok, Jakub Wiedemann, Piotr Lukasiak, Yang Cao, Janusz M Bujnicki, Eric Westhof, Marta Szachniuk, and Zhichao Miao. RNA-Puzzles toolkit: a computational resource of RNA 3D structure benchmark datasets, structure manipulation, and evaluation tools. *Nucleic Acids Res*, 48(2):576–588, January 2020.

[52] Chengxin Zhang, Morgan Shine, Anna Marie Pyle, and Yang Zhang. US-align: universal structure alignments of proteins, nucleic acids, and macromolecular complexes. *Nature Methods*, 19(9):1109–1115, Sep 2022.

[53] Patrick Gendron, Sébastien Lemieux, and François Major. Quantitative analysis of nucleic acid three-dimensional structures. *Journal of molecular biology*, 308(5):919–936, 2001.

[54] Marco Biasini, Valerio Mariani, Jürgen Haas, Stefan Scheuber, Andreas D Schenk, Torsten Schwede, and Ansgar Philippsen. OpenStructure: a flexible software framework for computational structural biology. *Bioinformatics*, 26(20):2626–2628, 2010.

[55] Andrew Martin Watkins, Ramya Rangan, and Rhiju Das. FARFAR2: improved de novo rosetta prediction of complex global RNA folds. *Structure*, 28(8):963–976, 2020.

[56] Schrödinger, LLC. The PyMOL molecular graphics system, version 1.8. November 2015.

[57] Sha Gong, Chengxin Zhang, and Yang Zhang. RNA-align: quick and accurate alignment of RNA 3D structures based on size-independent TM-scoreRNA. *Bioinformatics*, 35(21):4459–4461, 2019.

[58] Chaitanya K Joshi and Pietro Lio. grnade: A geometric deep learning pipeline for 3d rna inverse design. *RNA Design*, page 121.