Direct high-throughput deconvolution of unnatural bases via nanopore sequencing and bootstrapped learning

Mauricio Lisboa Perez[1*], Michiko Kimoto[2*], Priscilla Rajakumar[1*], Chayaporn Suphavilai[1], Rafael Peres da Silva[1], Hui Pen Tan[2], Nicholas Ting Xun Ong[1], Hannah Nicholas[1], Ichiro Hirao[2#], Chew Wei Leong[1#], Niranjan Nagarajan[1,3#]

[1]*Genome Institute of Singapore (GIS), Agency for Science, Technology and Research (A*STAR), 60 Biopolis Street, Genome, Singapore 138672, Republic of Singapore*

[2]*Institute of Bioengineering and Bioimaging (IBB), Agency for Science, Technology and Research (A*STAR), Nanos, Singapore 138669, Republic of Singapore*

[3]*Yong Loo Lin School of Medicine, National University of Singapore, Singapore 117596, Republic of Singapore*

[*]*Co-first Authors*
[#]*Corresponding Authors*
Lead Contact: nagarajann@gis.a-star.edu.sg

Abstract

The discovery of synthetic xeno-nucleic acids (XNAs) that can basepair as unnatural bases (UBs) to expand the genetic alphabet has spawned interest in many applications, from synthetic biology to DNA storage. However, the inability to read XNAs in a direct, high-throughput manner has been a significant limitation for xenobiology. Here we demonstrate that XNA-containing templates can be directly and robustly sequenced (>2.3 million reads/flowcell, similar to DNA controls) on a MinION sequencer from Oxford Nanopore Technologies to obtain signal data that is significantly distinct from DNA controls (median fold-change >6×). To enable training of machine learning models that deconvolve these signals and basecall XNAs along with natural bases, we developed a framework to synthesize a complex pool of 1,024 UB-containing oligonucleotides with diverse 6-mer sequence contexts and high XNA purity (>90% UB-insertion on average). Bootstrapped models to enable data preparation, and data augmentation with spliced XNA reads to provide high context diversity, enabled learning of a generalizable model to call natural as well as unnatural bases with high accuracy (>80%) and specificity (99%). These results highlight the versatility of nanopore sequencing as a platform for interrogating nucleic acids for xenobiology applications, and the potential to transform the study of genetic material beyond those that use canonical bases.

Introduction

Synthetic xeno-nucleic acids (XNAs) consist of unnatural bases (UBs) beyond the canonical A, T, C, G, and U found in naturally occurring DNA and RNA. These UBs expand the information space of the genetic code, offer novel biochemical properties, and have opened up new fields in xenobiology, synthetic biology, and biotechnology. Exemplary XNAs include the bases P and Z developed at the Foundation for Applied Molecular Evolution[1,2], d5SICS and dNaM developed at the Scripps Research Institute[3,4], and Ds and Pa/Px developed at RIKEN[5,6]. The use of UBs to expand the genetic alphabet has several applications in synthetic biology, including the development of sensors, aptamers, nanostructures, and semi-synthetic organisms[7–9]. With the advent of DNA storage as a paradigm to develop low-energy, ultra-high-density systems[10,11], reading and writing UBs has another potential application, however current approaches are limited in speed, nucleotide-resolution, and throughput.

A common early approach to detect UBs was to use Sanger sequencing and decipher the UB positions through signal gaps stemming from the inability to sequence through these UBs[5,6,12,13]. An alternative approach has involved using PCR to replace UBs followed by sequencing and mutation analysis to detect them, but with the drawback of introducing unintended errors during amplification[1,14]. Both approaches suffer from the corresponding limitations of sample processing, which introduce sources of error and operational cost. Next-generation sequencing, while much less limited in throughput, largely faces similar challenges due to its inability to natively detect UBs[15,16]. In particular, the detection of UBs in specific sequence contexts or in the presence of multiple UBs can be challenging[14,16]. A potential alternative is direct single-molecule interrogation of nucleic acids with third-generation technologies, which have shown promise with canonical nucleic acid base modifications (e.g. methylated DNA[17–20]), although the ability to directly sequence XNAs, which contain a different nucleic acid backbone, has not been demonstrated[21].

In this study, we developed the technology enabling direct sequencing of XNAs using a widely available nanopore sequencing platform (Oxford Nanopore Technologies – ONT). Our results suggest that UB-containing XNA templates can be robustly

sequenced on an ONT MinION system, with yield similar to DNA controls (>2 million reads

per flowcell), without notable truncation of reads, and with raw signals that are significantly

different from natural bases (median fold-change >6×). To enable direct decoding of

XNAs from these raw nanopore signals, we developed an XNA design and synthesis

framework that generates a complex library of XNA oligonucleotides (n=1,024) containing

all possible single-UB, 6-mer sequences, which provides the critical materials to train a

basecaller model for XNAs. Via our bootstrapped training approach, which retrieves

additional accurate training data, and our read-splicing based data-augmentation

technique, responsible for generating reads with high sequence context diversity, we

show that a generalizable deep learning model based on convolutional neural networks

(CNNs) can be trained to call unnatural bases with high accuracy (>80%) and specificity

(99%). Our work provides the first example of direct high-throughput deconvolution of

unnatural bases using nanopore sequencing, enabling determination of nucleotide-level

identities in XNAs needed for synthetic biology applications, and opening up the

possibility that other classes of synthetic and natural nucleic acids may also be amenable

to a bootstrapped and data-augmented learning approach.

Results

Analysis of XNAs on a high-throughput nanopore sequencer retains high fidelity

As a proof-of-concept to study the sequencing of XNAs, we leveraged the Px-Ds (X-Y)

architecture, one of the three known classes of unnatural basepairs[6] (**Figure 1A**,

Supplementary Figure 1). The Px-Ds basepair system was designed taking into

consideration hydrophobicity, shape, and electrostatic complementarity properties that

enable the basepair to be efficiently amplified with PCR[6], facilitating synthesis of XNAs

with UBs in diverse sequence contexts. For the initial experiment, we designed 20

individual templates with either a single UB (XNA01-XNA12), multiple UBs at varying

distances (XNA13-XNA16), or four equidistant UBs (XNA17-XNA20), flanked by

stretches of natural bases in different combinations and tagged via unique 24-nucleotide

barcodes (**Supplementary Figure 2**, **Supplementary File 1**).

We then used a commercially available high-throughput nanopore sequencer

(ONT MinION) to analyze the XNA molecules and control DNA (UB replaced by natural

base), initially using standard sequencing protocols and basecalling pipelines (**Figure 1A**; **Methods**). The XNA sequencing process generated data continuously with no unexpected interruptions, with each flow cell yielding a total of >2 million raw reads (>5 Gbp of data), similar to yields from other sequencing runs with DNA templates[22] (**Supplementary Figure 3**). However, XNA containing libraries had lower throughput as a function of time relative to the DNA libraries (mean=81%, 95% CI=69-99%), potentially due to a higher number of pore blockage and saturation events (39% vs 27% for control DNA). Despite this, in libraries containing equal concentrations of DNA and XNA templates, no strong bias was observed against XNA templates, with similar numbers of XNA and DNA reads being sequenced and successfully aligned to reference templates (2.3 vs 2.4 million reads). Read lengths for XNAs and DNAs were also very similar (median length 2.7kbp), with a substantial fraction of XNA reads (>75%) providing near full-length (±5%) template sequences (**Figure 1B**). A slightly higher fraction of XNA reads were shorter (1.2kbp) than the DNA reads recovered, due to incomplete fusion PCR[13] in the XNA synthesis process (**Figure 1B**; **Methods**).

Alignment of reads to reference sequences provided similarly high coverage for XNA and DNA templates (median>97%; **Figure 1C**; **Methods**), though a higher fraction of XNA reads (33% vs 21%) exhibited incomplete coverage (<95%), potentially due to higher fragmentation rate or inability of conventional analytics to decode natural bases correctly (particularly around UBs). Demultiplexing successfully identified templates for a high proportion of both XNA and DNA reads (92.5% vs 93.1%, edit distance <5bp; **Figure 1D**), while the distribution of XNA and DNA reads also did not show a strong bias across the barcodes/templates where they were pooled together for sequencing (**Figure 1E**). In terms of basecalling accuracy, we noted that error rates were similar but slightly higher for natural bases in XNA libraries versus control libraries (5% vs 3%; **Supplementary Figure 4**), consistent with the expectation that the presence of UBs could induce basecalling errors in related signals. Taken together, these results highlight the ability to generate signal data for XNAs with high fidelity on a high-throughput nanopore sequencer, despite the system not being designed for it, and correspondingly the native basecaller's inability to appropriately analyze UB containing signals.

Nanopore sequencing generates distinct electrical signals and reproducible errors near UBs

After aligning reads to templates, we analyzed the corresponding raw electrical signal data measured by the nanopore sequencing device as a function of various sequence contexts (**Methods**). XNA signals showed UB-specific divergence in contexts containing a single UB (XNA01), as well as multiple UBs that were close together (XNA13) or more spaced out (XNA16), and this pattern was seen for Ds as well as Px bases (upper and lower panels; **Figure 2A**). However, the largest difference was not necessarily observed when the UB was in the middle of the kmer (**Figure 2A**), and specific patterns of divergence varied in different sequence contexts (**Supplementary Figure 5**-**7**). Overall, the average signal-level difference between XNA and DNA control sequences was observed to be greater near UB positions ($\pm$3bp) than away from it (mean signal difference of 5.3 vs 0.7, median fold-change >6×), and the impact of sequence context was also seen in the form of larger variance for the distribution (43 in UB context vs 0.4 in non-UB context, **Figure 2B**). These results verify that the raw electrical signals generated from nanopore sequencing in the presence of UB-containing XNAs can be notably distinct from those generated from an analogous DNA template.

Subsequently, we investigated if signal-level distributions for UB-containing kmers were distinguishable from reference distributions for kmers containing each of the natural bases, based on a nanopore signal model[19]. In general, we noted a pattern where XNA-containing kmers exhibited signal distributions with distinct modes compared to natural bases in several (but not all) kmers surrounding a UB (similar signals when UB is at end of the kmer and generally larger differences when UB is at the center, **Figure 2C**). The fold-change per template between the unnatural base and the mode for each natural base had median value >5% for both Px and Ds bases (**Figure 2D**). These observations indicate that UBs are associated with electrical signal traces potentially distinguishable from all four natural bases.

We next assessed the impact of signal-level differences on basecalling with the standard basecaller model and whether they introduced reproducible errors. In agreement with the signal-level comparisons (**Figure 2A**), XNA basecalling error rates

also diverged from control DNA basecalling error rates in contexts containing a UB
(**Figure 2E**). Several templates exhibited very high error rates (>60%; **Figure 2F**) in the
neighborhood of a single UB (XNA01) as well as when multiple UBs were present at
varying distances to each other (XNA13 and XNA16). Notably, in contexts where natural
bases are between UBs that are moderately spaced apart (>5 bp), we observed only a
marginal effect for basecalling of those bases (XNA16, <10% error rate; **Figure 2E**),
highlighting that the basecaller model can perform reasonably well even in regions
flanked by UBs.

Overall, in comparison to control sequences, the bases surrounding a UB (±5 bp)
showed substantially higher basecalling error rates (mean of 18% vs 3%; **Figure 2F**). The
observed error rates are particularly high for the closest neighbors but quickly decrease
with increasing distance away from the UB (from 1 to 3 bp distance, median of 30%, 18%
and 12%, respectively). In contrast, basecalling for positions far from the UB was not
impacted by its presence, obtaining error rates not significantly different from those for
the control DNA templates (>6 bp; **Figure 2F**). Finally, for most templates (>90%) the
native basecaller repeatedly miscalled the same natural base more than 40% of the time
(**Supplementary Figure 8**), emphasizing the consistency of the underlying signal data.
These observations demonstrate that the performance of the standard basecaller is
strongly and reproducibly impacted when deconvoluting UB signals (i.e., bases affected
by a UB), while it is not impacted at positions sufficiently distant from UBs, a feature that
is ideal for bootstrapping the preparation of training data for learning a basecaller that can
natively decode UBs.

Generation of a complex template library to enable training of XNA basecaller
models

To obtain a new basecaller for XNAs (i.e. capable of natively basecalling natural as well
as unnatural bases) we needed training data with enough reads and diversity of sequence
contexts containing UBs such that a neural network model with sufficient generalization
capability could be developed. Since nanopore signal levels are known to be affected by
the identity of at least the 6 adjacent bases in the pore during sequencing (**Figure 2A**),
we designed a complex library where a UB is flanked by 5-mers of the same sequence

identity on both sides (4^5=1,024 templates containing $N_1N_2N_3N_4N_5$-M-$N_1N_2N_3N_4N_5$
sequence, where: N_i = A, T, G, or C; M = Ds or Px; **Supplementary Figure 2**,
Supplementary File 2-3), such that a rolling 6-nt window places the UB in every position
within the 6-mer resulting in all possible 6,144 single-UB 6-mer sequence contexts being
represented. Synthesizing such a large library would have been infeasible by employing
the chemical synthesis approach that is typically used for obtaining high-fidelity XNAs,
which was used for the initial proof-of-concept library here (20 templates). We therefore
designed and developed a cost-effective enzymatic synthesis scheme to generate this
much larger complex library (>50× in size; **Figure 3A**; **Methods**).

The proposed scheme consists of enzymatically inserting the Ds base at the 3'-
end of a fixed DNA sequence. For this insertion, we explored two methods using different
templates (31-mer and 20-mer; **Figure 3B**). In the first method, we used 31-mer
templates containing the Pa nucleotide (more stable alternative to Px). However, only a
moderate yield for the Ds-inserted product could be obtained from the reaction mixture
(even after purification by denaturing gel electrophoresis; T-Temp31Pa; **Figure 3C**).
Subsequently, we designed a second method, using a 20-mer template with a mini-
hairpin DNA sequence to stabilize the structure at the insertion target site (20-mer; **Figure
3B**). This method resulted in higher Ds insertion efficiency (T-MH-Temp20; **Figure 3C**).

To assess the insertion efficiency of the proposed enzymatic synthesis scheme,
we estimated the purity of Ds insertion per pool of templates (**Figure 3D**; **Methods**),
where each pool was comprised of subsets of templates with the same first and fifth bases
in the target sequence (**N$_1$**$N_2N_3N_4$**N$_5$**, 16=4^2 pools with 64=4^3 fragments each;
Supplementary Figure 9). Considering the proportion of pools with high UB retention
rate (>85%), the 20-mer (mini-hairpin) method provided a substantial improvement over
the 31-mer (Pa) method (median of 94% *vs* 67%; **Figure 3D**). Overall, a great majority of
XNA templates (91%) synthesized via the mini-hairpin method were estimated to have
high-purity (>85%). These results emphasize how an enzymatic synthesis scheme with
the right design can still enable generation of a substantially more complex template
library reliably, and with purity high enough that it could enable effective training of a XNA
basecaller model.

Bootstrapping and data augmentation enables training of an accurate generalized XNA basecaller

The complex template library was sequenced on a MinION sequencer, generating >6 million reads, with similar level of success as the proof-of-concept library in terms of long read lengths, near full-length template coverage and successful barcode identification (**Supplementary Figure 10**). The distribution of reads across templates was found to be relatively similar, with hundreds of reads being available per template for most templates, after preprocessing and filtering of short reads (**Supplementary Figure 11**; **Methods**). XNA training data was prepared by pre-processing reads selected for training by splitting them into signal chunks and attributing ground-truth sequence based on the library reference template sequence, discarding chunks that matched poorly to the reference (**Methods**). A significant fraction of reads was discarded in this way in an initial round of training (29%), as the baseline DNA model is prone to high error rates within UB regions (**Figure 2E**-**F**, **Supplementary Table 1**). Nevertheless, the resulting model was able to substantially improve basecalling in bases adjacent to the UB (93.8%, Round 1) versus the baseline model (75.6%, Round 0; **Figure 4A**). The updated basecaller model was used to repeat the pre-processing of reads, resulting in much fewer reads being discarded (11%), and retraining of a basecaller model with improved accuracy for calling UBs and neighboring bases (>94% in Round 2; **Figure 4A**). Further rounds of train data preparation and basecaller fine-tuning had limited impact on the number of reads added (<1%) and improvement of model performance (Round 3, **Figure 4A**), indicating that one round of bootstrapping was sufficient to obtain an accurate model for the complex library.

Model training based directly on XNA reads from the complex library is expected to have low generalizability as the sequence context surrounding the UB containing kmers is fixed. Correspondingly, testing on reads from the proof-of-concept 20-member library demonstrated low accuracy for both UBs and natural bases (5% UB accuracy, 71% DNA accuracy; Complex Library, **Figure 4B**). To overcome this limitation, we supplemented model training with different data augmentation approaches, allowing us to generate artificial reads with raw signals corresponding to UB containing kmers placed in diverse sequence contexts. Initially, fully synthetic signals were simulated based on a signal-level model trained on real signal data from the complex library (**Methods**). This approach

notably improved UB and DNA accuracy (24% and 89% respectively) relative to the
model trained directly on the complex library, where the proportion of UBs was kept
constant (0.3%; Fully Synthetic, **Figure 4B**). However, as DNA accuracy was lower than
the baseline DNA model (94%), we investigated a hybrid approach containing a mixture
of real DNA signals with simulated XNA signals that were generated by replacing specific
positions in real DNA chunks with synthetic signals representing UB kmers (**Methods**).
This approach provided slightly lower UB accuracy relative to the fully synthetic version,
but higher DNA accuracy that matched the baseline model (14% and 94% respectively;
Hybrid, **Figure 4B**). The final strategy that was tested involved splicing real DNA and XNA
signals together to generate artificial XNA reads with high context diversity while retaining
the fidelity of real sequencing data (**Methods**). Training based on these spliced chunks
resulted in substantial improvement in UB accuracy without compromising DNA accuracy
(34% and 94% respectively), indicating that it provides the most robust and generalizable
approach for data augmentation and model training (Spliced, **Figure 4B**).

Leveraging the flexibility of this approach for data augmentation, we next explored
various ways to improve model performance. By increasing the proportion of UBs in each
generated read, in contrast to using a single UB per read, substantial gains in UB
accuracy were noted (~2× to 64% at 4% UB) with only a slight reduction in DNA accuracy
(~1%; **Figure 4B**). While UB accuracy can be further improved, this comes with
diminishing returns at higher UB proportions (66% UB accuracy and 90% DNA accuracy;
trained with 11% UB proportion, **Figure 4B**). As baseline models are well-adapted to call
DNA bases, we next explored a *domain adaptation* approach by preserving these pre-
trained weights for some layers during fine-tuning (**Methods**). Successively freezing
layers of the basecaller architecture up to layer 6 (out of 9; **Supplementary Figure 12**)
helped boost model accuracy without substantially altering DNA accuracy (70% UB
accuracy for XY model with 6 frozen layers; **Figure 4C**). Not surprisingly, models trained
separately for each of the UBs achieved even higher accuracy (77% for X and 81% for
Y), which could be leveraged for highly accurate joint basecalling when both strands of
the XNA are sequenced in duplex mode (**Figure 4C**).

Using the complex library to evaluate model performance across diverse sequence
contexts further confirmed that high UB accuracies are typically obtained by our model
across templates (median accuracy=86% and 82% for X and Y, and 73% for XY model;
Figure 4D). In addition, this comes with very high specificity (99%), and thus natural
bases are rarely miscalled as one of the UBs (**Figure 4E**). Instead, a significant proportion
of the errors involve UBs being missed (i.e. a base deletion), similar to what is seen in
nanopore basecalling models for natural bases as well (4-7%; **Figure 4E**). In addition,
UBs are more likely to be miscalled to a natural base, relative to the natural-base-to-
natural-base miscall rate (2-6% vs 0-2%; **Figure 4E**), suggesting that our models are
conservative. Finally, we did not observe a strong influence from the order of UBs in a
template, or the number of natural bases between consecutive UBs, in terms of X and Y
basecalling accuracy (**Figure 4F**). Moreover, model performance was also comparable
for templates containing multiple UBs (including a 6-mer with two UBs), despite these
configurations not being present in the training data (**Figure 4F**), highlighting the
generalization capability of the model. Overall, these results highlight the ability to learn
a high-accuracy generalized direct basecalling model for XNA sequences using
bootstrapping and data augmentation to increase data complexity.

Discussion

In this work, we provide the first demonstration of direct high-throughput sequencing and
deconvolution of xeno-nucleic acid bases (Ds-Px pair) that can be readily performed on
a commercial sequencer. This effectively expands the set of bases that can be natively
read by nanopore sequencers paving the way for in-depth exploration of other classes of
unnatural bases as well[23,24]. Our results highlight that ONT's nanopore sequencing device
can be applied out-of-the-box to XNAs containing multiple Ds-Px unnatural base pairs,
processing them to generate raw electrical signals without significant disruption, and with
only a slight reduction in throughput to produce >2 million reads and >5 Gbp of data in a
single MinION run (**Supplementary Figure 3**). The resulting read sets were frequently
near full-length (>75% within 5% of expected length) and showed no notable biases in
data generation efficiency compared to their DNA controls (**Figure 1B-E**). These results

bode well for the use of nanopore architectures as versatile systems for natively reading
and decoding diverse non-canonical bases.

The raw signal data, however, does not directly provide nucleotide base identities.
To assess if it could be used for training a basecaller that could directly deconvolve
signals into bases, we first systematically assessed the distinguishability, fidelity and
reproducibility of the signal data. We found that the native basecaller was robust enough
to produce DNA reads that were largely accurate, except in regions surrounding the UB
(**Figure 2F**). This enables accurate alignment of signal data to reference bases, and
consequently preparation of training data for machine learning with UB containing XNA
signals. Notably, signal data around a UB (±3 bp) is substantially different relatively to
control DNA reads (median fold-change >6×; **Figure 2A-B**), and these differences are
not apparent outside the UB region. We further noted that the native basecaller makes
reproducible errors in XNA containing reads indicating that the underlying signal patterns
could be reproducibly re-interpreted with an appropriately trained basecaller
(**Supplementary Figure 8**).

Training a basecaller that directly deconvolves UBs along with canonical bases
requires training data that contains signals from XNA reads with known sequences in a
sufficiently complex library. While chemical synthesis approaches have high efficiency,
they can be prohibitively expensive for generating large-scale libraries. Enzymatic
synthesis approaches are generally known to provide modest insertion efficiencies (7%-
73%)[24] at lower cost. Here we demonstrated that a complex XNA library (n=1,024
templates) can be generated with high insertion efficiency (>85%) by designing a custom
insertion template and a mini-hairpin to stabilize the UB at the target site (**Figure 3C-D**).
A similar strategy could be useful for designing complex libraries for other UBs as well.
We chose to design our library to capture signals generated by all 6,144 single-UB 6-
mers sequence contexts (**Figure 3A, Supplementary Figure 2**). This improves on
previous work based on 4-mers[24], and is expected to benefit model training by capturing
greater sequence context diversity in critical bases impacting signal data[25]. In principle,
generating data with 6-mers containing multiple and consecutive UBs would also benefit
model training. However, this is currently infeasible with even modest levels of efficiency[6]

and therefore a limitation of our work is that we are currently unable to assess the
capabilities of our model with such XNAs.

Despite the sequence diversity in the immediate neighborhood of the UB in our
complex library, the XNAs that we sequence still have a predictable sequence backbone
(**Supplementary Figure 2**). Not surprisingly therefore, using this read data directly
provides a high-accuracy model for reads from the library (94% for UBs; **Figure 4A**), but
does not generalize to other sequence contexts. Nevertheless, this initial model based on
bootstrapped learning allows us to align signal data from the complex library to its
corresponding reference bases accurately and thus enables further robust training. As
generalizability is a common problem for training XNA models with limited training data
complexity, we explored several strategies for data augmentation including generating
fully synthetic signals, as well as signals that splice combinations of real and synthetic
data. Our results suggest that retaining signals from real XNA reads while embedding
them in diverse DNA read contexts provides higher accuracy relative to synthetic data
(>80%) and robust generalizability for the model (**Figure 4B-F**). The models reported
here also exhibit very high-specificity (99%) relative to prior work[24] (80-93%), while
demonstrating the capability for the first time to directly deconvolve signals and read UBs
and natural bases in an XNA. Our strategy for data augmentation is versatile and can be
adjusted to different requirements. For example, lower UB proportions can be used when
prioritizing DNA accuracy over UB accuracy, while UBs that were not synthesized
together can be incorporated into the same artificial read, to improve model accuracy for
more densely packed UBs and different classes of UBs. Notably, data augmentation
might be even more important as we seek to expand the alphabet of bases that can be
directly read by nanopores [4,24], and the corresponding demands for library complexity go
up rapidly.

With ongoing advances in nanopore sequencing technology, there are several
opportunities to further enhance capabilities to sequence XNAs by directly optimizing the
design of motor enzymes, pores and signal modalities (e.g. variable-voltage[26]). Additional
measurements (e.g., duplex-basecalling, translocation time and backwards step) could
also substantially aid in closing the gap between UB and canonical basecalling accuracy.
High-throughput XNA sequencing can, in turn, pave the way for advances in various

fields. For example, DNA storage applications can greatly benefit from the much higher

information density that an expanded alphabet enables[11,23]. In synthetic biology, the

development of new UBs, new XNA synthesis methods, and the creation of synthetic

genomes that exploit UBs can be transformed by the ability to directly sequence XNAs.

Finally, the development of UB-containing aptamers[15,27] and other DNA therapeutics

would benefit from easier access to direct XNA sequencing. More broadly, we hope that

the proof-of-concept shown in this work further accelerates the use of nanopore

sequencing techniques to interrogate the role of non-canonical basepairs across various

domains of life[28].

Methods

Preparation of XNA fragments containing natural and unnatural bases

XNA fragments containing Ds or Diol-Pa were chemically synthesized with an automated DNA synthesizer (H-8 SE DNA/RNA synthesizer, K&A Laborgeraete) using Ds and Diol-Pa phosphoramidite prepared in-house[5,29] and commercially available natural base phosphoramidites (Glen Research), or purchased from Gene Design. In-house synthesized oligonucleotides were purified by denaturing gel electrophoresis, after deprotection with concentrated ammonia solution. The unnatural base substrates, dDsTP, dPxTP, and dPa'TP, were prepared in-house as described previously[5,30]. DNA fragments consisting of natural base sequences were purchased from Integrated DNA Technologies (IDT) and used to prepare short and long XNAs (**Supplementary File 4**).

Preparation of proof-of-concept 20-member XNA Library

Using chemically synthesized DNA fragment sets, we first prepared short XNAs with barcode sequences, through primer extension in the presence of dPxTP and then PCR amplification in the presence of dDsTP and dPxTP as additional unnatural base substrates, as described previously[13]. Combinations of Ds-containing templates and the barcode fragments are summarized in **Supplementary File 5**. The presence of unnatural bases at specific positions in the PCR-amplified short XNAs (~97% purity) was confirmed by an in-house Sanger gap sequencing method[13]. For nanopore sequencing analysis, we prepared long XNAs by fusion PCR as described previously[13], in the presence of dDsTP and dPxTP, using three DNA blocks: short XNAs prepared as described above, left-arm DNA fragments, and right-arm DNA fragments. The presence of unnatural bases at specific positions was confirmed by an in-house Sanger gap sequencing method[13]. The control long DNAs, where the unnatural bases were replaced by natural bases, were prepared by fusion PCR in the absence of unnatural substrates, using the short DNA blocks with chemically-synthesized templates comprising of natural base only (for XNA01–XNA16) or prepared by replacement PCR in the presence of dPa'TP[16] (for XNA17–XNA20).

Preparation of complex XNA library

Ds insertion: Synthetic 90-mer oligonucleotide pools (oPools™ Oligo Pool, **Supplementary File 2-3, Supplementary Figure 9**) were purchased from IDT, as mixtures of 50pmol fragments. DNA fragments with phosphorylation at 5'-end (ordered with phosphorylation or phosphorylated by T4 DNA polynucleotide kinase followed by denaturing-gel purification) were directly used for single-Ds nucleotide insertion by exonuclease deficient Klenow Fragment DNA polymerase (KFexo-, New England Biolabs).

In the initial trial, each 90-mer DNA pool was annealed with the corresponding 31-mer template (5'-TG(Diol-Pa)NNNNNTATGGCAGCTGTTTCATGTGTGA-3', N=A, G, C, or T), positioning Pa opposite the site intended for Ds insertion. The Ds insertion was performed through the incubation of the 90-mer DNA pool (2µM) with 31-mer template (20µM) in the presence of 100µM dDsTP and 0.2U/µl KFexo- in the reaction buffer (25mM Tris-HCl pH 7.5, 10mM MgCl$_2$, 1mM DTT, 50mM NaCl) for 60 min at room temperature. The inserted products were purified by denaturing PAGE. However, we found that Ds insertion rate was relatively low, so we designed a new type of template for Ds insertion using a 20-mer containing a mini-hairpin DNA sequence at 5' terminus, X-MH-temp20 (5'-GCGAAGCGTNNNNNTATGG(ddC)-3', N=A, G, C, or T, underlined: mini-hairpin sequence). The design was based on three points: (1) the mini-hairpin sequence at the 5'-terminus allowed specific and stabilized hybridization to the 3'-region of 90-mer pool, (2) the use of 2',3'-dideoxy C at the 3'-terminus prevents additional Ds insertion, and (3) Ds insertion opposite T is allowed since we add only dDsTP (**Figure 3A-B**). As expected, the Ds insertion in the presence of the 20-mer template was much improved compared with that in the presence of the 31-mer (**Figure 3C-D**). Finally, the Ds insertion to 90-mer pool was performed through the incubation of the 90-mer DNA pool with 20-mer template (75µM) in the presence of 100µM dDsTP and 0.5U/µl KFexo- in the reaction buffer for 30 min at 37°C.

Circligation: The prepared Ds-inserted DNA pools (around 1.5 to 2.5 pmol) were subjected to self-ligation (10µl) by 50 Units of Circligase II (Lucigen) in the circligation buffer supplemented with 2.5mM MnCl$_2$ and 1M Betain for 16 h at 60°C, followed by heat inactivation of the ligase at 80°C for 10 min. The unligated fragments were removed by

treatment with Exonuclease I (NEB) and Exonuclease III (NEB) at 37°C for 45 min,

followed by heat inactivation of the nucleases at 80°C for 20 min.

Preparation of short and long XNA pools: The reaction aliquots were subjected to 12-

cycle PCR amplification in the presence of dDsTP and dPxTP, using two primers,

pUC19rev-47 and pUC19fwd-42. The PCR-amplified products (short XNA pools)

corresponding to 135-bp (without Ds-Px) /136-bp (with Ds-Px) were purified by denaturing

PAGE, followed by fusion PCR to prepare long XNAs, as described above. The presence

of unnatural bases at specific positions in the PCR-amplified short/long XNA pools were

confirmed by an in-house Sanger sequencing method supplemented with ddPa'TP[13] or

Ion PGM deep sequencing after replacing the unnatural base pairs with natural bases[16].

Nanopore library preparation and sequencing

XNA library samples were sequenced on Oxford Nanopore Technologies (ONT) MinION

Mk1B or Mk1C devices using MinION R9.4.1 flowcells. These samples were prepared

using the ONT Ligation Sequencing Kit (SQK-LSK109 or SQK-LSK110) following

standard library preparation protocol instructions provided by the vendor. The nucleic acid

concentration of each sample was measured using the Qubit^{TM} dsDNA HS kit on a

Qubit^{TM} 3 Fluorometer (Invitrogen).

In total, we ran five different synthesis and sequencing batches: 1) XNA+DNA #01-16; 2)

XNA #17-20; 3) DNA #17-20; 4) Complex library; 5) Complex library subset

(**Supplementary Figure 2**, **Supplementary Figure 9**). Run #5 was needed to replenish

some of the templates (n=214) with low read counts in run #4.

Nanopore data pre-processing

To prepare XNA sequence reads for raw nanopore signal analysis and basecaller

training, we used Guppy (v4.0.14) with the dna_r9.4.1_450bps_hac profile for initial

basecalling. The output basecalled sequences were then aligned to template references

using Minimap2[31] (v2.17-r941; parameters -x map-ont -c -secondary=no -w 5). For

alignment we used only template-specific regions as references, i.e. the sequences

corresponding to the left and right arms were omitted from the reference targets, as this

helped to avoid misalignment to the wrong target. After alignment, the barcode region

was located and used to compute the number of mismatches with the reference barcode

to obtain edit distances. Reads with low template coverage (<85%), high barcode

distance (>5) or unexpected read length (<1k or >3k) were filtered out, before counting

the final number of reads per template (**Supplementary Figure 11**). Nanopolish[19]

(v0.13.0; parameters eventalign -samples -scale-events -print-read-names) was used to

obtain the mapping between read bases and raw signals.

XNA training data preparation

We randomly sampled 316k reads from the complex XNA library sequencing batches, of

which 297k reads were used for training and 19k reads for validation, with respective

medians of 170 and 10 reads per template and strand. We prepared the input for training

the basecaller by first dividing the raw signals into chunks with a chunk size of 3600 and

an overlap of 900 signal points. Each chunk was then basecalled and mapped to the

library reference to retrieve the ground-truth sequence. We retained only the chunks that

contained a UB and had at least 90% coverage and accuracy relative to the aligned

reference (**Supplementary Table 1**). Each chunk of signals $S = \{S_1, ..., S_{chunksize}\}$ was

normalized via SMAD (Scaled Median Absolute Deviation) normalization[32], as defined

below:

476
$$smad(S) = k * median(|S_i - median(S)|)$$

477
$$S_{norm} = \frac{S_{raw} - median(S_{raw})}{smad(S_{raw})}$$

where, for consistency with the Gaussian distribution, we used 1.4826 as the scale factor

k.

XNA basecaller architecture and training

We used Bonito[33] (v0.5.0) Super Accuracy (SUP) as the backbone architecture for our

XNA basecaller models. We made certain adaptations to Bonito's implementation and

basecaller architecture (**Supplementary Figure 12**) to enable training with data

containing a six-letter alphabet. The baseline model, trained solely on DNA data, was

used as the default set of initial weights for fine-tuning with the XNA data. After round 1,

rounds 2 and 3 of the bootstrapping strategy used the weights from the previous round to

extract training chunks and initialize the model for fine-tuning (**Figure 4A**). Unless

otherwise specified, we fine-tuned the weights from all layers. However, in some cases,

we partially froze the network and only fine-tuned the weights from the top layers (**Figure

4C**). We fine-tuned the network for 5 epochs with a learning rate of 5e-4, applying dropout

rates of 50% to the top layer and 5% to any remaining unfrozen layers.

Performance evaluation

To comprehensively evaluate our basecaller models, we assessed their performance on

both XNA libraries (proof-of-concept and complex). For performance evaluation over the

proof-of-concept XNA library we randomly sampled 10k reads, consisting of 250 reads

per UB and template (**Supplementary Figure 13**). For the complex library we randomly

sampled 40k reads (median of 20 reads per UB and template). Each model was used to

basecall the two test sets, and evaluation was conducted on the reads successfully

aligned to reference templates. To evaluate how well our models can basecall natural

bases (ACGT) and UBs (XY), we calculated base-level accuracy and reported the

average accuracy per template and strand for each group of bases (natural and

unnatural). We categorized natural bases within 5 bases of a UB into a separate group

(i.e. UB-adjacent bases) due to their susceptibility to the influence of the UB at the signal

level and, consequently, in terms of basecalling. We computed the specificity metric

considering UBs as positives (P) and natural bases as negatives (N).

Refined signal-to-sequence alignment

We used Nanopolish on the reads from the complex XNA library to obtain an initial signal-

to-sequence alignment, which was subsequently refined. In order to obtain an alignment

with higher quality, we used the sequences basecalled by the XNA model from round 2

of the bootstrapped training procedure and we substituted the UBs in the reference

sequences with the natural base that minimized the average standard deviation per kmer

(A for both X and Y). We filtered out reads with alignments that have coverage <75%, a

position with signal count >50, an average variance per position >20 or a signal match

score >2. We also computed an alternative score by matching the signals to a reference

sequence without the UB, representing the mis-insertion case, and discarded the reads

where the difference between the alternative and original scores was less than -0.25,

capping discarded reads at 15% of the total. The signal match score for a given sequence
of signals grouped by kmer is the average z-score based on kmer model mean and
standard-deviation and is defined as:

$$score = \frac{\sum_i^L \left| \frac{\hat{\mu}_{ki} - \mu_k}{\sigma_k} \right|}{L}$$

where L is the sequence length, $\hat{\mu}_{ki}$ is the observed mean signal level for kmer k at
position i of the sequence, μ_k is the model mean signal level for kmer k and σ_k the model
standard deviation. We used the kmer signal model parameters employed by Nanopolish.

Since Nanopolish was designed solely for natural bases, the output alignment is not very
accurate around unnatural bases, necessitating additional steps to improve it. After
filtering the reads, we employed dynamic time warping (DTW)[34] in two iterations to refine
the signal-to-sequence alignment in the region comprising the UB kmers and the 5 kmers
before and after. Initially, we substituted both the UBs with the natural base "A" and used
the model mean signal level as the reference signal for each kmer. Subsequently, we
updated the reference corresponding to the UB kmers with the observed mean signal
level, computed from the signals aggregated across all reads after the first iteration. We
ran the DTW algorithm with Euclidean distance and an asymmetric step pattern, which
ensures that every signal is always matched to a single kmer. Additionally, to enforce that
each kmer would be matched to at least three signals, we repeated each reference signal
three times.

Synthetic signal generation

We simulated nanopore signals using the modeled signal distribution (mean and standard
deviation) of each 6-mer. For DNA kmers, we used the model available with the
Nanopolish tool. However, for XNA kmers, we had to generate our own model covering
the UBs explored in this work (Px-Ds). We modeled the XNA kmers by first applying our
refined signal-to-sequence alignment on the sequenced reads from the complex XNA
library. We then grouped the observed XNA signals per 6-mer, removed outliers
($\pm 3 \times stdev$), and extracted the mean and standard deviation from the remaining samples
(**Supplementary File 6**).

Using the 6-mer signal model for DNA and XNA, we simulated the signals for a specific

kmer by sampling from a truncated normal distribution, with the kmer model mean and

standard deviation as parameters, and then adding Gaussian noise[35]. The generation of

a synthetic signal $\tilde{s}_k$ for kmer *k* is defined as follows:

$$\tilde{s}_k = \mu_k + \sigma_k \times truncnorm(-\omega + \Delta, \omega + \Delta) + noise$$

where ω and Δ are the window size and shift value, respectively, for defining the truncation

lower and upper bounds. We used a window size of 1.5 and a shift value randomly chosen

from -0.5, 0 and 0.5. The Gaussian noise was also sampled from a truncated normal

distribution, with a standard deviation scale randomly selected within the range of 0 to 1

and lower and upper bounds of ± 3. The random parameters (window shift and noise

standard deviation) vary between reads but are chosen once and fixed for each read.

Fully synthetic XNA chunks

We used the DNA training data from Bonito as the source for the reference sequences

for which we generated fully synthetic nanopore reads. Adhering to a target UB proportion

for the new XNA reads, we randomly selected multiple positions from the source

reference sequence to be replaced by X or Y, ensuring that no 6-mer contained more

than one UB by maintaining a minimum of 5 bases between selections. We also used

Bonito's data to determine the number of signal points each kmer instance should have.

To estimate this information, we segmented the chunk of raw signals corresponding to

the source sequence into kmers. Finally, we normalized the resulting chunk of signals

using SMAD normalization.

Hybrid XNA chunks

We created hybrid reads by replacing specific signals in DNA chunks from Bonito training

data with synthetically generated XNA signals. Given a DNA chunk and its reference

sequence, we selected multiple positions from the sequence to be replaced by UBs and

then substituted the signals corresponding to these positions with nanopore simulations

for the UB kmers resulting from the replacement. To determine which signals correspond

to the replaced positions, we segmented the DNA signal chunks into kmer instances

employing DTW with the model mean signal level serving as the reference signal for each

kmer. Similar to the final step of our refined signal-to-sequence alignment, we ran the DTW algorithm with Euclidean distance, an asymmetric step pattern, and repeating each reference signal three times.

Spliced XNA chunks

To achieve more diverse sequence contexts while maintaining high nanopore signal fidelity, we assembled spliced reads by replacing specific signals in DNA chunks from Bonito training data with XNA signal slices extracted from our nanopore XNA reads. We used the chunks from the complex XNA library, obtained with the basecaller model from round 2 of bootstrapped training, as the source for the signal slices for UB kmers. The refined signal-to-sequence alignment approach was used to identify XNA signal slices that likely contain a UB. To extract the XNA slices, we kmer-segmented the chunks employing DTW with our XNA kmer model. When selecting which XNA slices will be used to substitute the DNA signals, we randomly sampled five slices and then selected the one with the number of signals closest to the length of the insertion region. If the selected XNA slice was longer than the insertion region, we removed evenly spaced signal points as needed. Conversely, if the slice was shorter, we used linear interpolation to add evenly spaced signal points.

Code and data availability

Source code for scripts used to obtain the XNA basecaller and analyze the data are available in a GitHub project at https://github.com/CSB5/XNA_Basecaller. Nanopore sequencing data is available from the European Nucleotide Archive (ENA – https://www.ebi.ac.uk/ena/browser/home) under project accession number PRJEB82716.

Acknowledgements

This work was funded by the Advanced Manufacturing and Engineering (AME) Programmatic grant A18A9b0060. Additional funding supporting manpower came from Singapore Ministry of Health's National Medical Research Council under its Open Fund – Individual Research Grants (NMRC/OFIRG/MOH-000649-00), and the Programme for Research in Epidemic Preparedness and Response (PREPARE), under its Joint Strategic

603 Open Grant Call (Environmental Transmission & Mitigation and Diagnostics Co-604 operatives; PREPARE-OC-ETM-Dx-2023-006). Additional compute resources were 605 provided by the A*STAR Computational Resource Center through the use of its high-606 performance computing facilities.

Figure Legends

Figure 1. High throughput nanopore sequencing of XNAs. (A) Overview of workflow, showing the synthesis of XNA templates containing unnatural basepairs (details in **Supplementary Figure 2**), nanopore sequencing, signal-level analysis and direct deconvolution of natural and unnatural bases. (B) Histogram of read lengths for XNA and control DNA libraries (dotted lines indicate median values). (C) Histogram of template coverage of template-specific region for XNA and control DNA libraries (dotted lines indicate median values). (D) Bar chart with read counts as a function of barcode distance (computed as edit distance of sequenced barcode to the closest reference barcode). (E) Read proportion between XNA and DNA sequences for each template, sorted by XNA proportion.

Figure 2. Nanopore sequencing generates distinct electrical signals and reproducible basecalling errors for unnatural bases. (A) Average signal level comparison between XNA and control DNA reads for representative templates (other templates in **Supplementary Figure 5-7**). Vertical dashed lines indicate the location of the UB, and shaded areas indicate ±3bp windows around the UB. (B) Boxplots showing signal differences between XNA and DNA libraries for a template in the context of UBs (±3bp window) and in non-UB sequence contexts. (C) Signal level distributions based on read data for kmers containing UBs and corresponding Nanopolish model distributions for kmers where the UB is replaced by one of the natural bases. (D) Boxplots showing average signal fold-change per template between read data for UB kmers and corresponding Nanopolish model distributions for kmers where the UB is replaced by one of the natural bases. (E) Error rates per base position for selected templates with one or two UBs. The UB position is indicated by a vertical dashed line and shaded areas indicate 5bp windows around the UB. (F) Boxplots showing error rates as a function of distance from the unnatural base across all templates ("****": One-sided Wilcoxon p-value<0.0001, "*":p-value<0.05, "ns": p-value>0.05). Summary statistics were computed based on sub-sampling of 5k reads per template and strand.

Figure 3. Generation of a complex XNA template library. (A) Schematic overview of XNA synthesis process, where DNA fragments phosphorylated at the 5'-end and

containing the template and barcode sequences undergo enzymatic single-nucleotide

insertion of Ds at 3'-terminus. The resulting XNA fragments are then subjected to circular

self-ligation followed by PCR using natural and unnatural base substrates to obtain the

double-stranded XNA. (B) Figure depicting the two alternative strategies that were

explored for enzymatic single-nucleotide insertion, using a 31-mer (Pa) and a 20-mer

(mini-hairpin) template. (C) Gel electrophoresis results for single-nucleotide insertion

products using the two alternative strategies. (D) Boxplots depicting Ds insertion

efficiency per pool of templates for the two alternative strategies. Insertion efficiencies

were estimated via replacement PCR and Ion PGM sequencing.

Figure 4. Training of a high-accuracy XNA basecalling model. (A) Line plot depicting

base-level accuracy per round of training for unnatural bases, natural bases within 5bp of

an unnatural base and more distant natural bases. The baseline round of training depicts

results using the Bonito Super Accuracy DNA model. (B) Line plots depicting performance

on the proof-of-concept library using basecaller models trained with different sets of real

and artificial reads, with increasing proportion of UBs per read. The following figures are

based on models trained with spliced data and 9% UB proportion. (C) Line plots depicting

performance of models trained jointly for both UBs or separately, with increasing number

of layers frozen. Subsequent analyses are based on models with 6 frozen layers. (D)

Boxplots depicting performance of the final model, based on the complex library for

testing with diverse templates and held-out reads. (E) Basecalling confusion matrix for

UBs and natural bases. The last column represents deletion errors. (F) Barplots (error

bars represent 100% percentile interval) depicting performance analysis for reads with

multiple UBs. UB proximity, number and order did not seem to have a strong impact on

UB accuracy, indicating that the final trained basecaller is robust in handling reads with

multiple UBs.

References

1. Yang, Z., Chen, F., Alvarado, J. B. & Benner, S. A. Amplification, mutation, and sequencing of a six-letter synthetic genetic system. *J. Am. Chem. Soc.* **133**, 15105–15112 (2011).

2. Hoshika, S. *et al.* Hachimoji DNA and RNA: A genetic system with eight building blocks. *Science 363* 884–887 (2019) doi:10.1126/science.aat0971.

3. Malyshev, D. A., Seo, Y. J., Ordoukhanian, P. & Romesberg, F. E. PCR with an Expanded Genetic Alphabet. *J Am Chem Soc* **131**, 14620–14621 (2009).

4. Li, L. *et al.* Natural-like Replication of an Unnatural Base Pair for the Expansion of the Genetic Alphabet and Biotechnology Applications. *J Am Chem Soc* **136**, 826–829 (2014).

5. Hirao, I. *et al.* An unnatural hydrophobic base pair system: site-specific incorporation of nucleotide analogs into DNA and RNA. *Nat. Methods* **3**, 729–735 (2006).

6. Kimoto, M., Kawai, R., Mitsui, T., Yokoyama, S. & Hirao, I. An unnatural base pair system for efficient PCR amplification and functionalization of DNA molecules. *Nucleic Acids Res* **37**, e14–e14 (2009).

7. McKenzie, L. K., El-Khoury, R., Thorpe, J. D., Damha, M. J. & Hollenstein, M. Recent progress in non-native nucleic acid modifications. *Chem Soc Rev* **50**, 5126–5164 (2021).

8. Kimoto, M., Cox, R. S. & Hirao, I. Unnatural base pair systems for sensing and diagnostic applications. *Expert Rev Mol Diagn* **11**, 321–331 (2011).

9. Zhang, Y. *et al.* A semi-synthetic organism that stores and retrieves increased genetic information. *Nature* **551**, 644–647 (2017).

10. Goldman, N. *et al.* Towards practical, high-capacity, low-maintenance information storage in synthesized DNA. *Nature* **494**, 77–80 (2013).

11. Lim, C. K., Nirantar, S., Yew, W. S. & Poh, C. L. Novel Modalities in DNA Data Storage. *Trends Biotechnol* **39**, 990–1003 (2021).

12.   Malyshev, D. A. *et al.* A semi-synthetic organism with an expanded genetic
alphabet. *Nature* **509**, 385–388 (2014).

13.   Kimoto, M., Soh, S. H. G. & Hirao, I. Sanger Gap Sequencing for Genetic Alphabet
Expansion of DNA. *ChemBioChem* **21**, 2287–2296 (2020).

14.   Kimoto, M. & Hirao, I. Genetic alphabet expansion technology by creating unnatural
base pairs. *Chemical Society Reviewsa* **49**, 7602–7626 (2020).

15.   Kimoto, M., Yamashige, R., Matsunaga, K., Yokoyama, S. & Hirao, I. Generation
of high-affinity DNA aptamers using an expanded genetic alphabet. *Nat Biotechnol*
31, 453–457 (2013).

16.   Hamashima, K., Soong, Y. T., Matsunaga, K., Kimoto, M. & Hirao, I. DNA
Sequencing Method Including Unnatural Bases for DNA Aptamer Generation by
Genetic Alphabet Expansion. *ACS Synth Biol* **8**, 1401–1410 (2019).

17.   Liu, Y. *et al.* DNA methylation-calling tools for Oxford Nanopore sequencing: a
survey and human epigenome-wide evaluation. *Genome Biol* **22**, 295 (2021).

18.   Nguyen, T. A. *et al.* Direct identification of A-to-I editing sites with nanopore native
RNA sequencing. *Nat Methods* (2022) doi:10.1038/s41592-022-01513-3.

19.   Simpson, J. T. *et al.* Detecting DNA cytosine methylation using nanopore
sequencing. *Nat Methods* **14**, 407–410 (2017).

20.   Zhang, Y.-Z. *et al.* On the application of BERT models for nanopore methylation
detection. in *IEEE International Conference on Bioinformatics and Biomedicine*
(BIBM) 320–327 (IEEE, 2021). doi:10.1109/BIBM52615.2021.9669841.

21.   Ledbetter, M. P. *et al.* Nanopore Sequencing of an Expanded Genetic Alphabet
Reveals High-Fidelity Replication of a Predominantly Hydrophobic Unnatural Base
Pair. *J Am Chem Soc* **142**, 2110–2114 (2020).

22.   Wang, Y., Zhao, Y., Bollas, A., Wang, Y. & Au, K. F. Nanopore sequencing
technology, bioinformatics and applications. *Nat Biotechnol* **39**, 1348–1365 (2021).

23.   Tabatabaei, S. K. *et al.* Expanding the Molecular Alphabet of DNA-Based Data
Storage Systems with Neural Network Nanopore Readout Processing. *Nano Lett*
(2022) doi:10.1021/acs.nanolett.1c04203.

24.   Kawabe, H. *et al.* Enzymatic synthesis and nanopore sequencing of 12-letter
supernumerary DNA. *Nat Commun* **14**, 6820 (2023).

25.   Rang, F. J., Kloosterman, W. P. & de Ridder, J. From squiggle to basepair:
computational approaches for improving nanopore sequencing read accuracy.
Genome Biol **19**, 90 (2018).

26.   Noakes, M. T. *et al.* Increasing the accuracy of nanopore DNA sequencing using a
time-varying cross membrane voltage. *Nat Biotechnol* **37**, 651–656 (2019).

27.   Kimoto, M., Matsunaga, K. & Hirao, I. DNA Aptamer Generation by Genetic
Alphabet Expansion SELEX (ExSELEX) Using an Unnatural Base Pair System. in
Methods in Molecular Biology book series (MIMB,volume 1380) 47–60 (2016).
doi:10.1007/978-1-4939-3197-2_4.

28.   Zhou, Y. *et al.* A widespread pathway for substitution of adenine by diaminopurine
in phage genomes. *Science 372* 512–516 (2021) doi:10.1126/science.abe4882.

29.   Kimoto, M., Soh, S. H. G., Tan, H. P., Okamoto, I. & Hirao, I. Cognate base-pair
selectivity of hydrophobic unnatural bases in DNA ligation by T4 DNA ligase.
Biopolymers **112**, (2021).

30.   Yamashige, R. *et al.* Highly specific unnatural base pair systems as a third base
pair for PCR amplification. *Nucleic Acids Res* **40**, 2793–2806 (2012).

31.   Li, H. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**,
3094–3100 (2018).

32.   Stoiber, M. H. *et al.* De novo Identification of DNA Modifications Enabled by
Genome-Guided Nanopore Signal Processing. *bioRxiv* 1–28 (2016)
doi:10.1101/094672.

33.   Seymour, C. & Oxford Nanopore Technologies Ltd. Bonito: A PyTorch Basecaller
for Oxford Nanopore Reads. https://github.com/nanoporetech/bonito (2019).

34.   Giorgino, T. Computing and Visualizing Dynamic Time Warping Alignments in R :
The dtw Package. *J Stat Softw* **31**, 1–24 (2009).

35.   Gamaarachchi, H., Ferguson, J. M., Samarakoon, H., Liyanage, K. & Deveson, I.
W. Squigulator: simulation of nanopore sequencing signal data with tunable noise
parameters. *bioRxiv* (2023).

Figure 1

Figure 2

Figure 3

A

DNA Fragment → XNA Fragment

Enzymatic single-nucleotide insertion
dDsTP

Circular self-ligation

XNA

Px / Ds

PCR
dNTPs, dPxTP, dDsTP

B

Enzymatic single-nucleotide insertion methods

31-mer (Pa)

```
51merA: 5'-CGCGCATACCGCTACGCAAAAAACATCACACATGAAACAGCTGCCATANNNNA
        T-Temp31Pa: 3'-AGTGTGTACTTTGTCGACGGTATNNNNTPaGT-5'
```

dDsTP

20-mer (Mini-Hairpin)

```
51merA: 5'-CGCGCATACCGCTACGCAAAAAACATCACACATGAAACAGCTGCCATANNNNA
        T-MH-Temp20: 3'-ddCGGTATNNNNTTG-CG
```

Blocking   Blocking & Stabilization

dDsTP

Mini-Hairpin

C

Method: 20-mer (MH)   31-mer (Pa)
Substrate: dDsTP -   dDsTP -

75-mer

51-mer+Ds
(52-mer)

50-mer

51-mer

Denaturing 15%-PAGE (SYBR Gold staining)

D

Method 31-mer / 20-mer

0% 20% 40% 60% 80% 100%

% of templates w/
high insertion efficiency

Figure 4

Supplementary Figure 1. Chemical structures of natural and unnatural bases included in this study. The diagram shows how the natural (A with T, and G with C) and unnatural bases (Ds with Px) basepair. As can be seen here, the chemical structure of Ds and Px, and therefore of the corresponding XNAs containing them, can be quite distinct from natural DNA.

Supplementary Figure 2. Design overview for XNA templates. Circles indicate the location of UBs, Px in red and Ds in green respectively, on forward and reverse strands. All templates have the same left and right arm sequences. The primers (left, middle and right) are non-unique sequences surrounding the barcode and UB kmer regions that are leveraged during synthesis (**Supplementary File 1** and **4**; **Methods**).

Supplementary Figure 3. Proof-of-concept library sequencing throughput for XNA, DNA and mixed runs. The curves show cumulative sums for (A) number of reads and (B) bases sequenced as a function of time. XNA and DNA runs included templates 17-20, while the mixed run included XNA and DNA templates 1-16.

Supplementary Figure 4. Basecalling error rates for natural bases in XNA and DNA templates.

Supplementary Figure 5. Nanopore electrical signal levels for XNA and DNA libraries around UBs. Each curve shows average signal level based on a subsampling of 5,000 reads. Vertical dashed lines indicate the location of the UB, and shaded areas indicate a window of 3bp around the UB. All templates in this figure have a single unnatural base in the XNA.

Supplementary Figure 6. Nanopore electrical signal levels for XNA and DNA libraries around 2 consequent UBs. Similar to **Supplementary Figure 5**, except that all templates in this figure have two unnatural bases in the XNA.

Supplementary Figure 7. Nanopore electrical signal levels for XNA and DNA libraries around 4 consequent UBs. Similar to **Supplementary Figure 5**, except that all templates in this figure have four unnatural bases in the XNA.

Supplementary Figure 8. Native basecaller produces reproducible errors for unnatural bases. Distribution of basecalling frequency of the most frequently called natural base at a UB position across templates in the proof-of-concept library.

90-mer Pool (1024 different $N_1N_2N_3N_4N_5$ combinations corresponding to 30-mer barcode)

5′ p $N_1N_2N_3N_4N_5$ ATnnnnnnnnnnnnnnnnnnnnnnnnnnnnnnTACGCATACCGCTACGCAAAAAATGTCACACATGAAACAGCTGCCATA$N_1N_2N_3N_4N_5$

OligoDNA Pool (IDT)	$N_1N_2N_3N_4N_5$	Sequence
Pool_01	C $N_2N_3N_4$ G	64
Pool_02	C $N_2N_3N_4$ A	64
Pool_03	C $N_2N_3N_4$ C	64
Pool_04	C $N_2N_3N_4$ T	64
Pool_05	G $N_2N_3N_4$ G	64
Pool_06	G $N_2N_3N_4$ A	64
Pool_07	G $N_2N_3N_4$ C	64
Pool_08	G $N_2N_3N_4$ T	64
Pool_09	A $N_2N_3N_4$ G	64
Pool_10	A $N_2N_3N_4$ A	64
Pool_11	A $N_2N_3N_4$ C	64
Pool_12	A $N_2N_3N_4$ T	64
Pool_13	T $N_2N_3N_4$ G	64
Pool_14	T $N_2N_3N_4$ A	64
Pool_15	T $N_2N_3N_4$ C	64
Pool_16	T $N_2N_3N_4$ T	64

Supplementary Figure 9. Schematic for Ds insertion process and corresponding oligo DNA pools generated. 16 different oligo DNA library pools, each of which consists of 64 defined fragments (50 pmole each, 90-mer) were generated.

Supplementary Figure 10. Sequencing statistics for the complex library. (A) Histogram of read lengths for forward and reverse strand reads. (B) Histogram of template coverage for template-specific region. (C) Bar chart with read counts as a function of barcode distance (computed as edit distance of sequenced barcode to the closest reference barcode).

Supplementary Figure 11. Read distribution per template in the complex library. Read counts for each template and strand for the two sequencing runs of the complex library, after filtering of reads by barcode distance (≤8), template coverage (≥85%) and read length (between 1k and 3k).

Supplementary Figure 12. XNA basecaller architecture. The neural network architecture for the Bonito basecaller was suitably modified to enable basecalling of UBs. Firstly, the output alphabet was expanded from four to six bases. Secondly, as the number of parameters for the last layer (layer No. 9, Linear) is exponentially related to the length of the alphabet and the chosen number of states, we reduced the number of states from 5 to 3 so that the model could fit into GPU memory for efficient training. Finally, the last 3 layers were fine-tuned to enable native basecalling of XNAs.

Supplementary Figure 13. Read count per template for the proof-of-concept library. Reads were counted after selecting for those with appropriate barcode distance (≤5), template coverage (≥85%) and read length (between 1k and 3k).

Round	Total Chunks	Unique Reads
0 (Baseline)	256,133	225,511 (71.24%)
1	330,814	282,491 (89.25%)
2	334,472	284,708 (89.95%)
3	334,734	285,584 (90.22%)

Supplementary Table 1. XNA train data signal chunks summary. Summary of the number of signal chunks satisfying the filter criteria (>90% coverage and accuracy), obtained from basecalling train and validation set XNA reads with the bootstrapped model from different rounds of training.