Convolutional-LSTM Approach for Temporal Catch Hotspots (CATCH): An AI-Driven Model for Spatiotemporal Forecasting of Fisheries Catch Probability Densities

Altair Agmata[1], Svanur Guðmundsson[1]

[1]Bláa Hagkerfið ehf., Reykjavík, Iceland

December 8, 2024

Abstract

Efficient fisheries management is crucial for sustaining both marine ecosystems and the economies that heavily depend on them, such as Iceland, where the fishing industry contributes significantly to national export revenues. Current fishing practices involve decisions informed by a combination of personal experience, current data on environmental and oceanographic conditions, reports from other captains, and target species within the constraints of the quota of the ship. However, the intricate spatiotemporal dynamics of fish behaviour in marine environments make it difficult to predict fish stock distributions, despite technological breakthroughs in fishing vessel data collection. Much of the decision-making still relies heavily on subjective judgment, highlighting the need for more robust, data-driven predictive methods. In an attempt to address this gap, this paper presents CATCH, a Convolutional LSTM neural network model that forecasts fish stock probability densities over time and space in Icelandic waters. The framework represents the first utilization of large-scale Icelandic fishing fleet data in such an advanced and predictive manner. The AI model efficiently captures the complex patterns affecting fish populations by integrating multidimensional data on depth, bottom temperature, and catch per unit effort (CPUE) probability densities. It then produces a multivariate forecast of these features going forward in time. The CATCH model demonstrates high accuracy and robustness, with low error metrics and strong structural similarity to the observed testing data. It also exhibits promising generalization capabilities across multiple commercially significant species, including Atlantic cod, haddock, saithe, golden redfish, and Greenland halibut. These results suggest that deep learning models like CATCH can serve as powerful tools for optimizing fisheries operations, enhancing sustainability, and supporting data-driven decision-making in fisheries management. Further improvements might extend the applicability of the model, including integration with detailed biological context and generalizing across multiple species groups, refining its predictive capabilities for broader ecological insights.

1 Introduction

Efficient fishing practices are essential for maximizing the economic benefits derived from marine resources while environmental sustainability is safeguarded. This ensures the long-term preservation of both the ecosystem and economic livelihoods of nations heavily reliant on the fishing industry. Iceland, in particular, is a country where the fishing sector plays a pivotal role in its economy and is widely believed to be the country's single most important industry (Arnason, 1995). In fact, current statistics estimate that the industry contributes approximately 38% of the nation's total export revenues in 2023, with the total export from fisheries valued at 359 billion ISK in 2023 (Statistics Iceland, 2024b,a). The economic significance of the fisheries industry thus underscores the importance of accurate fish stock management strategies. Icelandic waters, influenced by the dynamic North Atlantic currents, are home to commercially significant species, including *Gadus morhua* (Atlantic cod), *Melanogrammus aeglefinus* (haddock), *Reinhardtius hippoglossoides* (Greenland halibut), *Sebastes marinus* (golden redfish), and *Pollachius virens* (saithe). These species, among others, are essential to the economy, with Atlantic cod being one of the most valuable due to its high demand globally and its indispensable role in the ecosystem (Christensen *et al.*, 2009; Þórðarson *et al.*, 2014; Statistics Iceland, 2024b).

In line with the significant role that fisheries play in the economy, the Icelandic fishing industry has evolved to become one of the most technologically advanced of its kind in the world. Over the years, technological innovations have enabled companies to optimize their operations significantly throughout the value chain. These advancements facilitated the collection of massive and diverse datasets that includes information on fishing time, location, sea temperature, depth, and even on catch volume and composition. Currently, skippers gain insights about where and when to fish by manually reviewing and sharing their ships' data, and combining it with their personal experiences, environmental and oceanographic conditions, and weather forecasts. However, inherent uncertainties in the fishing process limit skippers' predictive capabilities, which rely heavily on subjective judgment. As a result, the there is a pressing need for an accurate prediction method that guide fishermen toward most efficient and environmentally sustainable fishing at all times (Abbott *et al.*, 2015). Currently the data collected, although rich and extensive, is underutilized by current approaches, analytical power needed to extract its full potential for predictive insights is insufficient.

To address these challenges, artificial intelligence (AI) offers promising new technologies, particularly deep learning models, for optimizing operations of fishing fleets (Núñez *et al.*, 2018; Zhao *et al.*, 2020; Xu *et al.*, 2023). Neural networks, the foundation of deep learning, are models inspired by the biological brain's structure and can uncover complex, non-linear relationships within the data. They are composed of simple, non-linear modules (neurons) that perform level-wise transformations of increasing abstraction, allowing very complex functions to be learned given enough combinations of such transformations (Lecun *et al.*, 2015). It is in recent times that AI became the more appealing choice compared to conventional statistical and classical machine learning methods because it can automatically learn non-linear representations of complex-structured data without relying on hand-crafted features or prior domain knowledge (Lecun *et al.*, 2015; Pilario *et al.*, 2020). In contrast, conventional statistical and machine-learning techniques were

limited in their ability to process natural data in their raw form, requiring rigorous feature engineering along with considerable domain expertise. This advantage has driven the rise of AI applications like ChatGPT in the natural language processing domain, where the model learns directly from raw training data without needing rules in language such as grammar and syntax to be explicitly specified (Mikolov *et al.*, 2013; Vaswani *et al.*, 2017; Brown *et al.*, 2020; Song and Fujimura, 2021).

The spatiotemporal nature of fisheries data requires an architecture that handles both the patterns through time in various temporal scales and spatial relationships across multiple geographical areas. For each of these two tasks, long short-term memory networks (LSTM) and convolutional neural networks (CNN), respectively, are particularly well-suited. LSTM networks, a special type of recurrent neural networks (RNN), are designed to retain information over long sequences of data and thus highly effective for time-series forecasting use cases. The term "long short-term memory" refers to the short-term memory lasting thousands of timesteps that the LSTM architecture aims to provide for RNNs, giving it the ability to analyze long-term sequence dependencies (Hochreiter and Schmidhuber, 1997). It also addresses the common vanishing/exploding gradient problem common with RNN's by keeping track of a separate "cell state" that changes with each iteration (Graves, 2012; Katrompas and Metsis, 2022). Due to these advantages, LSTM networks are one of the most popular models of choice for sequence-type datasets and have been successfully applied in multiple domains such as finance (Cao *et al.*, 2019; Ferdiansyah *et al.*, 2019; Moghar and Hamiche, 2020), manufacturing (Essien and Giannetti, 2020; Bai *et al.*, 2021; Liu *et al.*, 2023), healthcare (Islam *et al.*, 2019; Awais *et al.*, 2021), meteorology (Fente and Singh, 2018; Salman *et al.*, 2018; Hossain and Mahmood, 2020; Karevan and Suykens, 2020), fisheries (Núñez *et al.*, 2018; Zhao *et al.*, 2020; Xu *et al.*, 2023). Meanwhile, CNN's excel at capturing spatial relationships within the data, making them ideal for analyzing geographical distributions of fish populations. As the name implies, most of the heavy lifting in the feature extraction process within a CNN comes from the convolution operation that happens within each convolutional layer. Within this layer, local conjunctions of features from preceding layers are detected through discrete convolution between learnable kernel filters and the input/intermediate data resulting to the extraction of invariant features such as edges, motifs, parts and objects in an image (Lecun *et al.*, 2015). These features are then used downstream for classification, typically through a shallow or deep dense neural network. The architecture has seen great success in numerous applications where images are the main input data format (Li *et al.*, 2014; Muhammad *et al.*, 2018; Khandokar *et al.*, 2021; Yu *et al.*, 2023) or when data can loosely be transformed into image-like representation (Hou *et al.*, 2018; Sharma *et al.*, 2019, 2021; Essien and Giannetti, 2020).

An AI architecture that combines the strengths of both CNN's and LSTM's thus makes the most sense when tackling the complexity of spatiotemporal fisheries data, particularly when applied to forecasting. Incidentally, such an architecture that literally combines both such frameworks, called Convolutional LSTM, exists and was first applied to precipitation forecasting applications Shi *et al.* (2015). It has also become an increasingly popular choice and proven effective in applications involving data with both temporal sequences and spatially organized two-dimensional arrays across a variety of fields Sønderby *et al.* (2015); Luo *et al.* (2017); Zhang *et al.* (2018); Behera *et al.* (2021).

This study introduces CATCH (Convolutional-LSTM Approach for Temporal Catch

Hotspots) which is an AI model with the goal of producing accurate and timely predictions of fish stock probability densities across space and time in the Icelandic waters. This paper is the first in literature to discuss the use of a deep learning model such as convolutional-LSTM to predict fish stock movement. This is also the very first time that the previously unexplored data collected directly from the Icelandic fishing fleet will be utilized at such a computing scale and level of sophistication to benefit the fishing industry and ensure environmental sustainability. In Icelandic waters, where environmental variability and fishing pressure can shift rapidly, these AI-driven models offer a powerful tool for skippers and fisheries operators giving them valuable insights for their operations. Our model incorporates multidimensional spatiotemporal temperature, depth and catch per unit effort (CPUE) probability densities data, the output facilitating optimization of fisheries operation in a way that ensures profitability and future sustainability of Iceland's fishing industry.

Figure 1: An illustration of the common implementation scheme of A) Long Short-Term Memory (LSTM) neural network (Hochreiter and Schmidhuber, 1997) and B) Convolutional Neural Network (CNN) (Lecun *et al.*, 2015; Krizhevsky *et al.*, 2017) along with their corresponding equations.

2 Methodology

2.1 Training Dataset

The raw data used in this study was a proprietary dataset obtained from various fishing vessels operated by multiple Icelandic fishing companies. These data, encompassing species information, fishing gear, geographical data, vessel information, and environmental parameters, were retrieved using SQL queries to an Amazon Web Services (AWS) Redshift database where it is stored. Due to the proprietary nature of the data, we are unable to disclose the full dataset or make it public.

Before the data was used for model training, the retrieved raw data was first filtered and preprocessed to reduce the complexity of the learning task and make it appropriate to produce the insights and predictions expected of the model. The series of filtering steps taken are enumerated as follows:

1. *Limiting to only bottom trawling (Botnvarpa) as fishing gear type.* Since the main metric used to gain prediction insights on fisheries population is CPUE, this filtering was done to standardize the effort parameter from all observations as different fishing gears have varying catching efficiencies. Bottom trawlers in the dataset had the most amount of observations and also has least efficiency variance within the dataset, thus making it the best choice for effort standardization among different fishing gear types.

2. *Filtering data to 2008 onwards.* The filtering was done to eliminate sampling bias from sparse observations through time as was observed in the data before 2008. Data quality before the cutoff was extremely low and may lead to skewed patterns when used in downstream training.

The filtering process resulted to a dataset with 274,521 spatiotemporal observations spanning across five species: *Gadus morhua* (Atlantic cod), *Melanogrammus aeglefinus* (haddock), *Reinhardtius hippoglossoides* (Greenland halibut), *Sebastes marinus* (golden redfish), and *Pollachius virens* (saithe). This dataset is then preprocessed to prepare it for the model training process:

1. *Feature selection.* Features used for training and prediction was limited to three variables: CPUE (kilograms per minute), bottom temperature (Celsius), and depth (meters). The temperature and depth were selected, because of their hypothesized impact and data quality. CPUE on the other hand, was obtained by dividing the weight of the catch (kg) with the tow duration (min) for each observation. This normalized the effect of tow duration per catch, thus showing a glimpse of the fish population density at a specific time and area of the catch record.

2. *Binning observations across space and time.* The granularity of the observations were reduced through binning and aggregation. Binning was done with respect to space and time, imposing the assumption of local similarity within each bins.

In this study, spatial binning was done by 0.5° and 0.25° increments of longitude and latitude, respectively. The binning ranged from -28.75° to -9.25° longitude and 61° to 68.25° latitude, resulting to a 30×40 pixel spatial snapshot for each time observation (Figure 2). Meanwhile, temporal binning was done per month. Binning was set as mentioned to avoid information loss from using excessively large bins and to prevent proliferation of numerous uninformative small bins. Aggregation per bin was done by getting the mean of each group.

3. *Converting features to probability distributions.* This was done by normalizing each binned spatiotemporal observation for each feature to fractions of unity. Mathematically, it can be expressed as:

$$\hat{X}_{s,h,w,c} = \frac{X_{s,h,w,c}}{\sum_h \sum_w X_{s,h,w,c}} \in \mathbb{R}^{S \times H \times W \times C} \tag{1}$$

where X and $\hat{X}$ represents the raw and probability value tensors, respectively, of size S×H×W×C for each sample observation s, latitude h, longitude, w, and feature c. Converting the raw feature values to probability distribution offers several advantages with respect to forecast modelling such as enforcing stationarity by normalizing temporal and spatial variability, focusing on relative distribution dynamics, and improving the interpretability of the results, among others.

4. *Expanding the input tensor to time-lag dimensions.* A common technique used for temporal forecasting predictions to teach the model temporal relationships is by expanding the input tensor to time-lagged version of itself. In this study, time-lag values (T) of 3, 6, 12, 16 and 24 months were tested representing various spans of temporal variabilities to be considered per prediction resulting to a final 5D input tensor $\hat{X} \in \mathbb{R}^{S \times T \times H \times W \times C}$.

Figure 2: Spatial aggregation of the training dataset showing the binning grid across the Icelandic waters used in the study (left) and the sample snapshot of aggregated CPUE probability distribution observation with cubic spline interpolation for Cod at November 2012 (Right).

Figure 3: Convolutional LSTM (ConvLSTM) neural network cell used in the study based on Shi *et al.* (2015)

Figure 4: CATCH forecasting model architecture

2.2 Model Architecture

The core component used in the CATCH model was a convolutional LSTM (Shi *et al.*, 2015) neural network cell designed to capture both spatial and temporal dependencies in fisheries data. The architecture of the model per layer is mathematically expressed as:

$$i_t = \sigma \left(U_i * x_t + V_i * h_{t-1} + W_i \circ C_{t-1} + b_i \right)$$
$$f_t = \sigma \left(U_f * x_t + V_f * h_{t-1} + W_f \circ C_{t-1} + b_f \right)$$
$$o_t = \sigma \left(U_o * x_t + V_o * h_{t-1} + W_o \circ C_{t-1} + b_o \right)$$
$$\hat{C}_t = \tanh \left(U_g * x_t + V_g * h_{t-1} + b_c \right) \tag{2}$$
$$C_t = f_t \circ C_{t-1} + i_t \circ \hat{C}_t$$
$$h_t = o_t \circ \tanh \left(C_t \right)$$

Where '$\circ$' represents the Hadamard product and '$*$' the convolutional operation between the trainable kernel weights and an input image described by equation (3) in the case of convolution on input image x. In this architecture, the convolution operator is applied in the hidden and input states of LSTM.

$$(U * x)_{h,w} = \mathrm{Conv}\left(U, x_{h,w} \right) = \sum_{c=1}^{C} \sum_{m=1}^{K_h} \sum_{n=1}^{K_w} U_{m,n,c} \circ x_{h+m-1,w+n-1,c}. \tag{3}$$

Using the core component as building blocks, a multi-layer model architecture is built representing different layers of data abstraction and expression. Figure 4 shows the implemented architecture for the study wherein each layer's hidden state is used successively as input towards succeeding ConvLSTM layers. In these layers, expressivity of the data is increased by expanding the feature dimensionality C with the use of F kernel filters of size K with $F > C$. At the last layer, the last hidden state is extracted and passes through the output convolutional layer with F 3×3 kernel filters, compressing the output back to its original dimension C. Finally, the convolution output passes through a ReLU activation function to zero out negative probability predictions and the resulting logit $\hat{y}$ is normalized in a similar way with equation (1):

$$y_{b,t,\ h,w,c} = \frac{\hat{y}_{b,t,h,w,c}/\tau}{\sum_H \sum_W \hat{y}_{b,t,h,w,c}/\tau} \in \mathbb{R}^{B \times T \times H \times W \times C}. \tag{4}$$

where τ is the temperature hyperparameter used to control the entropy of the output probability distributions.

2.3 Training and Hyperparameter Tuning

The model is trained through back-propagation through time (BPTT) (Mozer, 1989) by minimizing a weighted binary cross-entropy (BCE) loss which is used to prioritize the accuracy towards the CPUE probability prediction. For each feature c, the BCE loss for a single element is given by:

$$\mathrm{BCE}_c \left(y_{\mathrm{obs}}, y_{\mathrm{pred}} \right) = -\frac{1}{N} \sum \left[y_{c,\mathrm{obs}} \log y_{c,\mathrm{pred}} + (1 - y_{c,\mathrm{obs}}) \log \left(1 - y_{c,\mathrm{pred}} \right) \right]. \tag{5}$$

$$\text{Weighted BCE Loss} = \sum_c w_c \text{BCE}_c \tag{6}$$

In this study, the weights w_c for each feature used are 0.6, 0.2 and 0.2 corresponding to CPUE probability, bottom temperature, and depth, respectively.

The model was trained using data of varying lag size, and thus model context window, to gain prediction insights from variations attributed to short-term and long-term patterns. Specifically, context sizes of 3, 6, 12, 18, and 24 months backward were used in the study but only focusing on Cod (*G. morhua*) first as this is the species with the most number of observations within the dataset. The context length with the best results are then used to train and predict across all the five species. Each of the dataset was split to train, validation and test set, where the validation and test sets are set as 12-months-worth of data each covering 06-2022 to 05-2023 and 06-2023 to 05-2024, respectively. Hyperparameters for each of the training run were obtained automatically using Bayesian optimization through the Keras tuner library across 100 trials with the objective of minimizing the validation loss. The hyperparameter values/ranges used in the hypertuning process were summarized in Table 1. Decisions about the ranges and fixed values were made based on prior experiments, computational efficiency, and available compute resources.

Table 1: Hyperparameter values/ranges explored in the study.

Hyperparameter	Value / Range
Number of filters (F)	[4, 6]
Kernel size (K)	3×3
Number of ConvLSTM layers (L)	[2, 3]
Dropout in ConvLSTM layers	[0.1, 0.5]
Temperature (τ)	[0.2, 0.7]
Max epoch (E)	50
Batch size (B)	32
Learning rate (R)	[1×10^{-5}, 1×10^{-3}]

2.4 Model Evaluation

Predictions are evaluated based on performance with regard to the model's one-at-a-time (OAT) and recursive forecast. OAT prediction refers to predicting only one month at a time and that at every timestep, the model uses an input comprised purely of observed instances. In contrast, recursive forecast is done through generation of sequential predictions for a specified forecast length by iteratively using the model's previous predictions as inputs for subsequent predictions, creating a chain of forecasts over time while maintaining a consistent input size through slicing. Such predictions are evaluated against the testing data using metrics summarized in Table 2.

RMSE and MAE are both staple regression metrics and are metric analogues of each other with different outlier sensitivities. While the problem could be treated like a regression task, the data input and model output are both interpreted as probability distributions,

Table 2: List of metrics used to evaluate model performances and their corresponding mathematical formulations.

Metric	Formulation
Root mean squared error (RMSE)	$\frac{1}{T} \sum_{t=1}^{T} \sqrt{\frac{1}{N} \sum_{i=1}^{N} \left(y_{\text{obs},t,i} - y_{\text{pred},t,i} \right)^2}$
Mean absolute error (MAE)	$\frac{1}{T} \sum_{t=1}^{T} \frac{1}{N} \sum_{i=1}^{N} \left\| y_{\text{obs},t,i} - y_{\text{pred},t,i} \right\|$
Wasserstein distance (WD)	$\int_{-\infty}^{\infty} \left\| \text{CDF}_{\text{obs}}(x) - \text{CDF}_{\text{pred}}(x) \right\| dx$
Structural similarity index (SSI)	$\frac{\left(2\mu_{y_{\text{obs}}} \mu_{y_{\text{pred}}} + C_1 \right) \left(2\sigma_{y_{\text{obs}}, y_{\text{pred}}} + C_2 \right)}{\left(\mu_{y_{\text{obs}}}^2 + \mu_{y_{\text{pred}}}^2 + C_1 \right) \left(\sigma_{y_{\text{obs}}}^2 + \sigma_{y_{\text{pred}}}^2 + C_2 \right)}$

thus the use of Wasserstein distance (WD). It is the solution to the optimal transport plan for the amount of mass to be transported to transform a given distribution to the reference distribution (Arjovsky *et al.*, 2017). Structural similarity index (SSI), on the other hand, is a metric typically used in computer vision that gives importance on perceptual criteria by considering difference in intensities, contrast, and structural covariance between two images (Wang and Bovik, 2009).

3 Results

Figure 5: Metric values for one-at-a-time (OAT) and recursive predictions for *G. morhua* with respect to the observed values as functions of lag size (L, months) from 2023-06 to 2024-05 data.

Table 3: Specific metric values for OAT and recursive predictions for *G. morhua* with respect to observed values as functions of lag size (L) from 2023-06 to 2024-05 data. Arrows indicate direction of better scores, i.e. down means the lower the better and up means the higher the better. Standard deviation are reported in absolute unscaled units for easier comparison across varying orders of magnitudes.

Lag Size (L, months)	RMSE $\times 10^3$ ↓	MAE $\times 10^3$ ↓	WD $\times 10^3$ ↓	SSI $\times 10^1$ ↑
One-at-a-time (OAT)				
3	4.78	1.16	0.85	9.52
6	4.88	1.25	0.97	9.47
12	4.69	1.19	1.00	9.56
18	4.62	1.12	0.90	9.57
24	4.55	1.07	0.80	9.58
Std Dev	1.30×10^{-1}	6.70×10^{-2}	8.59×10^{-2}	4.51×10^{-2}
Recursive				
3	5.16	1.38	1.10	9.31
6	5.03	1.36	1.17	9.41
12	4.74	1.23	1.09	9.55
18	4.64	1.14	0.96	9.57
24	4.56	1.08	0.82	9.58
Std Dev	2.58×10^{-1}	1.32×10^{-1}	1.39×10^{-1}	1.19×10^{-1}

Table 4: Specific metric values for OAT with respect to observed values across various species (*P. virens*, *S. marinus*, *R. hippoglossoides*, and *M. aeglefinus*) from 2023-06 to 2024-05 data with lag size of 3 months. Arrows indicate direction of better scores, i.e. down means the lower the better and up means the higher the better.

Lag Size (L, months)	RMSE $\times 10^3$ ↓	MAE $\times 10^3$ ↓	WD $\times 10^3$ ↓	SSI $\times 10^1$ ↑
P. virens	5.69	1.31	1.11	9.41
S. marinus	5.23	1.11	0.83	9.58
R. hippoglossoides	8.11	1.24	0.96	9.70
M. aeglefinus	5.33	1.27	1.01	9.38

Table 3 and Figure 5 summarizes and illustrates the performance matrix on *G. morhua* test data across varying lag sizes (L). A close concurrence is observed between the model's predictions and the actual observed values as consistently low RMSE and MAE values were observed. Particularly for OAT predictions, the MAE varies from 1.07×10^{-3} to 1.25×10^{-3} across the different lag sizes, while the RMSE varies from $4.55 \times \times 10^{-3}$ to 4.88×10^{-3}. On the other hand, the RMSE and MAE values for recursive predictions range from 4.56×10^{-3} to 5.16×10^{-3} and 1.08×10^{-3} to 1.38×10^{-3}, respectively.

Low WD values, ranging from 0.80×10^{-3} to 1.00×10^{-3}, and high SSI values, ranging from 0.95 to 0.96, were also observed supporting the CATCH models robustness and accuracy. This is despite the striking difference between the nature of the observed and the predicted datasets (Figure 6 and Figure 7).

Figure 6: Metric values for one-at-a-time (OAT) and recursive predictions for *G. morhua* with respect to the observed values as functions of lag size (L, months) from 2023-06 to 2024-05 data.

Figure 7: Metric values for one-at-a-time (OAT) and recursive predictions for *G. morhua* with respect to the observed values as functions of lag size (L, months) from 2023-06 to 2024-05 data.

Figure 6 and Figure 7 shows the plotted observed catch (top row) and the predicted probability catch (bottom rows) in months for both OAT and recursive forecasts, respectively. These figures highlight the difference between the nature of the observed and predicted probability catches—with the observed datasets seen as highly discontinuous with multiple local clusters and the predicted datasets as smooth and continuous. The discontinuous nature of the observed dataset is due to the incomplete and uneven sampling from the fishing fleets. The figures also highlight the movements within the data across space and time and how different L values affect these movements in the predictions. While general concordance of the predicted with observed data on probability density distributions is apparent for all the lag sizes, movement is more obvious in models with lower L values and slowly diminishes as L increases.

Figure 8: Metric values for one-at-a-time (OAT) and recursive predictions for *G. morhua* with respect to the observed values as functions of lag size (L, months) from 2023-06 to 2024-05 data.

Table 4 summarizes performance metrics of test data from *P. virens*, *S. marinus*, *R. hippoglossoides*, and *M. aeglefinus* with a lag size of 3 months. Similar patterns of close concurrence are observed between the model's predictions and the actual observed values as consistently low RMSE and MAE values were observed in order of 10^{-3}. Low WD values, in the order of 10^{-3}, and high SSI values, close to unity, were also observed. Figure 8 illustrates the observed and predicted probability densities across time for all the four species. It also highlights how the alignment of predictions with the observed data, showcasing a strong correspondence and accurate reflection of overall spatiotemporal patterns despite varying dynamics across species.

4 Discussion

The results of the experiment imply that the CATCH model does a good job at capturing the data's underlying spatial and temporal patterns. This is exemplified by the favorable performance metrics for the one-at-a-time (OAT) and recursive forecast predictions as shown in Table 3 and Figure 5. Consistently low RMSE and MAE values, which are in the order of 10^3, implies that the model's predictions closely concur with the actual observations.

The CATCH model's low WD values, in the order of 10^{-3}, also imply that the predicted probability distributions closely match the observed distributions, which is crucial for accurate probabilistic forecasting. Despite the difference in nature of the observed and predicted datasets, low WD values shows that the model does not overfit and generalizes the patterns well, producing predictions that align with ecological intuition rather than overfitting to patches of data. This ensures the model's capability to extend predictions to unobserved regions, filling data gaps in a plausible manner while ensuring that the predicted distributions maintain structural coherence and environmental rele-

vance. Indeed, this is also supported by the high Structural Similarity Index (SSI) values approaching unity, demonstrating that the model maintains strong structural fidelity in its forecasts across time and signifies that the model preserves important spatial feature structures when compared to the observed data over time. Overall, these results highlight the model's robustness in capturing both spatial and temporal dynamics while generating predictions that are not only accurate but also ecologically meaningful, making it a valuable tool for potentially understanding and managing fisheries populations.

When comparing the metric values between OAT and recursive predictions, OAT forecasts consistently exhibits lower RMSE, MAE, and WD, along with higher SSI. This highlights the nature of compounding errors in recursive forecasting, as the model gradually uses its own synthetic predictions as input data over time. Additionally, examining the metrics for $L = 24$ reveals that both OAT and recursive predictions yield values that are close to each other with minimal differences. This trend suggests that as L becomes larger, the recursive metrics converge towards those of the OAT predictions. This thus implies that at least in the context of the training data used in the study, utilizing a context length of at least 24 is recommended in order for recursive forecasts to achieve reliability comparable to OAT predictions. Such observations align with literature findings (Bao et al., 2014; Yuan et al., 2019) suggesting that long-range recursive forecasting requires a larger context window.

The general trend observed on OAT predictions is that of improving performance as the number of lag size increases. This might indicate that a larger lag size, corresponding to a broader context window and input information, provides the model with wider context per prediction, enabling more accurate long-term forecasts. However, looking at the trend for the WD metric —which considers the evaluation as a comparison between probability distributions—it appears that higher model performance might also be obtained through smaller context windows. Indeed, the plot on recursive predictions (Figure 5) also shows a similar pattern, where the performance initially declines with increasing lag size and then starts to improve after $L = 12$. This suggests that two independent temporal patterns are at play, such that increasing or decreasing L leads to a trade-off between them. Such is a common scenario in time-series modeling where temporal dependencies are broadly classified into long-term and short-term impacts, typically reflected as trends and fluctuations, respectively (Bao et al., 2014). In this case, lower lag values might be more sensitive to short-term dynamics and thus captures them well, despite not reliably capturing long-term relationships. If such a trade-off pattern exists within the dataset used in the study, then the opposite should be true for a model with higher L. Results in Figure 6 provide visual affirmation of this reasoning. As L increases, spatial movement and intensity variations of the hotspots become less dynamic. In the observed test data, movement of the hotspots through time from north to south are seen to happen briefly from June to July 2023, and then slowly manifests again from January to May 2024. Such temporal dynamics is seen to be captured only by models with L of 3, 6 and 12 with movement diminishing as L increases. While increasing lag time improves the metrics and can be beneficial for capturing overarching patterns, it may lead to the attenuation of significant short-term events, which are critical in certain forecasting applications.

Building on the emphasis on short-term dynamics and considering that the observed data covers only 12 months—where such dynamics are more apparent—the model with $L = 3$ was chosen to predict across the remaining four species (P. virens, S. marinus, R. hip-

poglossoides, and *M. aeglefinus*). This decision was made because it demonstrated the best performance metrics and visual concordance with respect to capturing the movements within the test data, as evidenced by its performance with *G. morhua.* Figure 8 and Table 4 present the results of the CATCH model predictions for these species. From the figure, it is evident that the model effectively grasps the spatiotemporal movements shown by the observations, similar to the performance seen in *G. morhua.* The movement of hotspots and intensity variations over time are well-represented, indicating the model's proficiency in modeling essential spatial dynamics for each of the distinct datasets. Quantitatively, this is supported by metric performances in Table 4 where the values for RMSE, MAE, WD and SSI fall within similar orders of magnitude as those for *G. morhua.* These consistent metrics across multiple species demonstrate the robustness of the model in capturing the patterns even across varying training data distributions exhibited by different species.

The robustness of the model's framework suggests that the model potentially possesses the capability to generalize fish species behavior, at least for bottom-dwelling species that are being represented in this study. Having a single model that can effectively forecast multiple species behavior is particularly significant, as it implies that the model can capture underlying patterns and movements characteristic of the species as a group. Such generalization capability enhances the model's utility, potentially reducing the need for species-specific models and extensive amounts of training data for each species, as training can be done using only a handful of representative species to generalize patterns within a species group. This would make the model a valuable tool for predicting distributions of under-represented species in data-limited contexts. Moreover, the model's proficiency in capturing multi-species interactions could have important implications for ecosystem management and conservation efforts. By accurately modelling and subsequent extraction of model explainability insights on multi-species interactions, the CATCH model can provide valuable insights into species distribution patterns, habitat utilization, behavioral correlations, and potential areas of ecological significance. However, it is important to acknowledge potential limitations of the framework used within the study. While the model performs well with the species tested, further validation with additional species and longer observation periods would strengthen confidence in its generalization capabilities. Furthermore, the training and testing data used in the study was not validated in the context of known ecological dynamics from literature sources as the focus was solely the model's capability to produce accurate forecast given the observations in the data. Future work could thus involve generating and aligning insights with more context on the fish biology of these representative species, testing the model with other species group that exhibits completely different movement patterns, such as pelagic species, and training one general model from crafted features that capture multi-species interactions.

5   Conclusions and Recommendations

This study introduced the CATCH model, a deep learning framework utilizing Convolutional LSTM networks to forecast fish stock probability densities in Icelandic waters. This is the first in literature to discuss the utilization of this framework to the previously unexplored data collected by the Icelandic fishing fleet for the hope of aiding the Ice-

landic fishing industry and environmental sustainability. The model demonstrated high accuracy and robustness in predicting the spatial and temporal distributions of key commercial fish species, as evidenced by low RMSE, MAE, and WD, along with high SSI scores. These metrics show the generalization capability of the model without overfitting and how well it captures intricate spatiotemporal patterns. Interestingly, the model demonstrated potential to generalize across several species, accurately representing the distribution patterns of Greenland halibut, Atlantic cod, haddock, saithe, and golden redfish. This implies that the model might be applied to different species groups, which would eliminate the requirement for species-specific models and make it a useful tool for managing fisheries in situations when data is scarce.

Future recommendations for addressing the limitations and gaps identified within the study may include:

- *Testing Multi-Species Generalization.* Further validation of the model's generalization capabilities should be conducted by testing it on additional species, including those with different behavioral patterns, such as pelagic species. This will help determine the model's applicability across diverse species groups. Moreover, the training experiments performed in the current study involved independent CATCH models individually trained from different species and then subsequently used to predict across each of these species. A general model, while more computationally demanding and theoretically more complex, should be trained from a single dataset with crafted features that inherently highlights patterns for multi-species interactions. This could, in turn, forecast distributions even outside the representative species in the training data.

- *Incorporating Fish Biology Context* Aligning the model's insights with detailed fish biology (such as fish length and weight distributions) and ecological data can enhance its predictive power and interpretability. Integrating biological factors such as spawning cycles, feeding habits, and migration patterns could provide a more comprehensive understanding of species distributions.

- *Enhancing Model Inputs.* Exploring additional environmental variables, such as salinity, ocean currents, wind speed, and wind direction, among others, may improve the model's accuracy and provide deeper insights into the factors influencing fish stock movements.

- *Long-Term Forecasting*: Extending the model to perform long-term forecasts could be valuable for strategic planning in fisheries management. This would involve training the model with longer time-series data and testing its ability to predict future stock distributions over extended periods.

Enhancing the CATCH model in this way could significantly increase its value as a tool for operational research in the fishing industry by boosting potential profits and increasing the sustainability of fishing operations. Equally important, the model can provide deeper insights into the robustness of individual fish stocks, enabling better strategic measures to ensure sustainability and the preservation of newly spawned generations.

References

Abbott, J. K., Haynie, A. C., and Reimer, M. N. 2015. Hidden flexibility: Institutions, incentives, and the margins of selectivity in fishing.

Arjovsky, M., Chintala, S., and Bottou, L. 2017. Wasserstein gan.

Arnason, R. 1995. The Icelandic fisheries : evolution and management of a fishing industry. Fishing News Books Ltd., 1 edn.

Awais, M., Raza, M., Singh, N., Bashir, K., Manzoor, U., Islam, S. U., and Rodrigues, J. J. 2021. Lstm-based emotion detection using physiological signals: Iot framework for healthcare and distance learning in covid-19. IEEE Internet of Things Journal, 8: 16863–16871.

Bai, Y., Xie, J., Wang, D., Zhang, W., and Li, C. 2021. A manufacturing quality prediction model based on adaboost-lstm with rough knowledge. Computers & Industrial Engineering, 155: 107227.

Bao, Y., Xiong, T., and Hu, Z. 2014. Multi-step-ahead time series prediction using multiple-output support vector regression. Neurocomputing, 129: 482–493.

Behera, R. K., Jena, M., Rath, S. K., and Misra, S. 2021. Co-lstm: Convolutional lstm model for sentiment analysis in social big data. Information Processing & Management, 58: 102435.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., *et al.* 2020. Language models are few-shot learners. *In* Proceedings of the 34th International Conference on Neural Information Processing Systems. Curran Associates Inc.

Cao, J., Li, Z., and Li, J. 2019. Financial time series forecasting model based on ceemdan and lstm. Physica A: Statistical Mechanics and its Applications, 519: 127–139.

Christensen, A. S., Hegland, T. J., and Oddsson, G. 2009. The icelandic itq system. Comparative Evaluations of Innovative Fisheries Management: Global Experiences and European Prospects, pp. 97–118. URL https://link.springer.com/chapter/10.1007/978-90-481-2663-7_5.

Essien, A. and Giannetti, C. 2020. A deep learning model for smart manufacturing using convolutional lstm neural network autoencoders. IEEE Transactions on Industrial Informatics, 16: 6069–6078.

Fente, D. N. and Singh, D. K. 2018. Weather forecasting using artificial neural network. Proceedings of the International Conference on Inventive Communication and Computational Technologies, ICICCT 2018, pp. 1757–1761.

Ferdiansyah, Othman, S. H., Radzi, R. Z. R. M., Stiawan, D., Sazaki, Y., and Ependi, U. 2019. A lstm-method for bitcoin price prediction: A case study yahoo finance stock market. ICECOS 2019 - 3rd International Conference on Electrical Engineering and Computer Science, Proceeding, pp. 206–210.

Graves, A. 2012. Long short-term memory. pp. 37–45. URL `https://link.springer.com/chapter/10.1007/978-3-642-24797-2_4`.

Hochreiter, S. and Schmidhuber, J. 1997. Long short-term memory. Neural Computation, 9: 1735–1780. URL `https://direct.mit.edu/neco/article/9/8/1735-1780/6109`.

Hossain, M. S. and Mahmood, H. 2020. Short-term photovoltaic power forecasting using an lstm neural network and synthetic weather forecast. IEEE Access, 8: 172524–172533.

Hou, J., Adhikari, B., and Cheng, J. 2018. Deepsf: deep convolutional neural network for mapping protein sequences to folds. Bioinformatics, 34: 1295–1303. URL `https://dx.doi.org/10.1093/bioinformatics/btx780`.

Islam, M. S., Umran, H. M., Umran, S. M., and Karim, M. 2019. Intelligent healthcare platform: Cardiovascular disease risk factors prediction using attention module based lstm. 2019 2nd International Conference on Artificial Intelligence and Big Data, ICAIBD 2019, pp. 167–175.

Karevan, Z. and Suykens, J. A. 2020. Transductive lstm for time-series prediction: An application to weather forecasting. Neural Networks, 125: 1–9.

Katrompas, A. and Metsis, V. 2022. Enhancing lstm models with self-attention and stateful training. Lecture Notes in Networks and Systems, 294: 217–235.

Khandokar, I., Hasan, M., Ernawan, F., Islam, S., and Kabir, M. N. 2021. Handwritten character recognition using convolutional neural network. Journal of Physics: Conference Series, 1918: 042152. URL `https://iopscience.iop.org/article/10.1088/1742-6596/1918/4/042152https://iopscience.iop.org/article/10.1088/1742-6596/1918/4/042152/meta`.

Krizhevsky, A., Sutskever, I., and Hinton, G. E. 2017. Imagenet classification with deep convolutional neural networks. Communications of the ACM, 60: 84–90.

Lecun, Y., Bengio, Y., and Hinton, G. 2015. Deep learning.

Li, Q., Cai, W., Wang, X., Zhou, Y., Feng, D. D., and Chen, M. 2014. Medical image classification with convolutional neural network. 2014 13th International Conference on Control Automation Robotics and Vision, ICARCV 2014, pp. 844–848.

Liu, C., Zhu, H., Tang, D., Nie, Q., Li, S., Zhang, Y., and Liu, X. 2023. A transfer learning cnn-lstm network-based production progress prediction approach in iiot-enabled manufacturing. International Journal of Production Research, 61: 4045–4068. URL `https://www.tandfonline.com/doi/abs/10.1080/00207543.2022.2056860`.

Luo, W., Liu, W., and Gao, S. 2017. Remembering history with convolutional lstm for anomaly detection. *In* 2017 IEEE International Conference on Multimedia and Expo (ICME), pp. 439–444.

Mikolov, T., Sutskever, I., Chen, K., Corrado, G. S., and Dean, J. 2013. Distributed representations of words and phrases and their compositionality. *In* Advances in Neural Information Processing Systems, edited by C. J. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger, vol. 26. Curran Associates, Inc. URL `https://proceedings.neurips.cc/paper_files/paper/2013/file/9aa42b31882ec039965f3c4923ce901b-Paper.pdf`.

Moghar, A. and Hamiche, M. 2020. Stock market prediction using lstm recurrent neural network. Procedia Computer Science, 170: 1168–1173.

Mozer, M. 1989. A focused backpropagation algorithm for temporal pattern recognition. Complex Systems.

Muhammad, K., Ahmad, J., Mehmood, I., Rho, S., and Baik, S. W. 2018. Convolutional neural networks based fire detection in surveillance videos. IEEE Access, 6: 18174–18183.

Núñez, R. A. C., Ángel Ojeda Ruiz De La Peñã, M., Irigollen, A. F., Rodríguez, M. R., and Jardim, E. 2018. Deep learning models for the prediction of small-scale fisheries catches: finfish fishery in the region of "bahía magadalena-almejas". ICES Journal of Marine Science, 75: 2088–2096. URL https://dx.doi.org/10.1093/icesjms/fsy065.

Pilario, K. E., Shafiee, M., Cao, Y., Lao, L., and Yang, S. H. 2020. A review of kernel methods for feature extraction in nonlinear process monitoring. Processes, 8: 1–47.

Salman, A. G., Heryadi, Y., Abdurahman, E., and Suparta, W. 2018. Single layer & multi-layer long short-term memory (lstm) model with intermediate variables for weather forecasting. Procedia Computer Science, 135: 89–98.

Sharma, A., Lysenko, A., Boroevich, K. A., Vans, E., and Tsunoda, T. 2021. Deepfeature: feature selection in nonimage data using convolutional neural network. Briefings in Bioinformatics, 22: 1–12. URL https://dx.doi.org/10.1093/bib/bbab297.

Sharma, A., Vans, E., Shigemizu, D., Boroevich, K. A., and Tsunoda, T. 2019. Deepinsight: A methodology to transform a non-image data to an image for convolution neural network architecture. Scientific Reports 2019 9:1, 9: 1–7. URL https://www.nature.com/articles/s41598-019-47765-6.

Shi, X., Chen, Z., Wang, H., Yeung, D.-Y., kin Wong, W., and chun WOO, W. 2015. Convolutional lstm network: A machine learning approach for precipitation nowcasting. In Advances in Neural Information Processing Systems, edited by C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett, vol. 28. Curran Associates, Inc. URL https://proceedings.neurips.cc/paper_files/paper/2015/file/07563a3fe3bbe7e3ba84431ad9d055af-Paper.pdf.

Song, W. and Fujimura, S. 2021. Capturing combination patterns of long- and short-term dependencies in multivariate time series forecasting. Neurocomputing, 464: 72–82.

Statistics Iceland 2024a. Export value of icelandic fisheries in 2023 - statistics iceland. URL https://www.statice.is/publications/news-archive/fisheries/export-value-of-icelandic-fisheries-in-2023/#.

Statistics Iceland 2024b. Trade in goods in the year 2023 - final data - statistics iceland. URL https://www.statice.is/publications/news-archive/external-trade/trade-in-goods-in-the-year-2023-final-data/#.

Sønderby, S. K., Sønderby, C. K., Nielsen, H., and Winther, O. 2015. Convolutional LSTM Networks for Subcellular Localization of Proteins, pp. 68–80.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., *et al.* 2017. Attention is all you need. *In* Advances in Neural Information Processing Systems, edited by I. Guyon, U. von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, vol. 30. Curran Associates, Inc. URL `https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf`.

Wang, Z. and Bovik, A. 2009. Mean squared error: Love it or leave it? a new look at signal fidelity measures. IEEE Signal Processing Magazine, 26: 98–117.

Xu, H., Song, L., Zhang, T., Li, Y., Shen, J., Zhang, M., and Li, K. 2023. Effects of different spatial resolutions on prediction accuracy of thunnus alalunga fishing ground in waters near the cook islands based on long short-term memory (lstm) neural network model. Journal of Ocean University of China, 22: 1427–1438. URL `https://link.springer.com/article/10.1007/s11802-023-5525-5`.

Yu, F., Zhang, Q., Xiao, J., Ma, Y., Wang, M., Luan, R., Liu, X., *et al.* 2023. Progress in the application of cnn-based image classification and recognition in whole crop growth cycles. Remote Sensing 2023, Vol. 15, Page 2988, 15: 2988. URL `https://www.mdpi.com/2072-4292/15/12/2988/htmhttps://www.mdpi.com/2072-4292/15/12/2988`.

Yuan, S., Luo, X., Mu, B., Li, J., and Dai, G. 2019. Prediction of north atlantic oscillation index with convolutional lstm based on ensemble empirical mode decomposition. Atmosphere 2019, Vol. 10, Page 252, 10: 252. URL `https://www.mdpi.com/2073-4433/10/5/252/htmhttps://www.mdpi.com/2073-4433/10/5/252`.

Zhang, L., Zhu, G., Mei, L., Shen, P., Shah, S. A. A., and Bennamoun, M. 2018. Attention in convolutional lstm for gesture recognition. *In* Advances in Neural Information Processing Systems, edited by S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, vol. 31. Curran Associates, Inc. URL `https://proceedings.neurips.cc/paper_files/paper/2018/file/287e03db1d99e0ec2edb90d079e142f3-Paper.pdf`.

Zhao, Z., Tian, Y., Hong, F., Huang, H., and Zhou, S. 2020. Trawler fishing track interpolation using lstm for satellite-based vms traces. 2020 Global Oceans 2020: Singapore - U.S. Gulf Coast.

Þórðarson, G., Viðarsson, J. R., and Authors, H. . 2014. Coastal fisheries in iceland skýrsla matís 12-14 coastal fisheries in iceland / smábátaveiðar við Ísland.