Predicting human prediction error empowers reward learning task design

Jaehoon Shin[1], Jee Hang Lee[2,3], Sang Wan Lee[1,4,5,6,7*]

[1] *Department of Bio and Brain Engineering, Korea Advanced Institute of Science and Technology (KAIST) 34141 Daejeon, Republic of Korea*

[2] *Department of Human-Centered Artificial Intelligence, Sangmyung University 03016 Seoul, Republic of Korea*

[3] *Institute for Advanced Intelligence Study, Daejeon, Republic of Korea*

[4] *KAIST Center for Neuroscience-inspired Artificial, KAIST, Daejeon, 34141, Republic of Korea*

[5] *Department of Brain and Cognitive Sciences, Korea Advanced Institute of Science and Technology (KAIST)*

[6] *Graduate School of Data Science, Korea Advanced Institute of Science and Technology (KAIST)*

[7] *Kim Jaechul Graduate School of AI, Korea Advanced Institute of Science and Technology (KAIST)*

Summary

Environmental conditions affect human reward prediction. Stable environments foster accurate prediction but constrain learning opportunities, whereas uncertain environments diminish predictability. This stability-uncertainty dilemma complicates task design. We conceptualize this challenge as a task learning paradigm termed meta-prediction – predicting human prediction itself. The meta-prediction entwines two Bellman equations: one emulating human reward learning while the other generates new tasks by predicting the prediction error arising from the first. The meta-prediction with 82 subjects' data generated subject-independent tasks across four distinct scenarios. These tasks orchestrate foraging and uncertainty conditions, confirming our framework's task design ability. Moreover, their mechanistic interpretability provides insight into human reward learning. An independent fMRI study with 49 individuals validated that these tasks effectively modulated behavior and neural activities in prediction error encoding regions, including ventral striatum and lateral prefrontal

* Corresponding author. Email: sangwan@kaist.ac.kr

cortex. Lastly, we demonstrated its compositional capacity to generate complex tasks,
uncovering intrinsic biases in human reward learning.

Introduction

The environmental conditions exert a profound influence on human reward learning. Previous
research has yielded valuable insights into reward learning, including learning action values
for habit formation[1–4] and using internal models for goal-directed learning[5–8]. These
investigations have primarily relied on a stable environmental setting, which enables
confident predictions. While these investigations have predominantly occurred within stable
environmental contexts that foster accurate predictions, they inadvertently constrain the
breadth of experience and limit the predictive capabilities.

Recent studies have leveraged volatile and uncertain environments to examine the nuanced
dynamics of reward prediction[–12]. Such approaches accommodate the view that learning in
complex environments demands sophisticated predictive strategies wherein complementary
functions— habit, goal, memory, and intuition[13,14]— work in concert. However, the efficacy
of such strategies can be compromised in a highly uncertain and volatile environment,
making reliable predictions difficult. This tension reveals a key dilemma in task design: both
environmental stability and uncertainty impose constraints on our reward learning.

To address this, we conceptualize this challenge as a task learning problem (decoding), which
incorporates how environmental stability and uncertainty shape human reward prediction
processes (encoding). This perspective leads to a novel solution: learning a task control
policy that predicts human prediction, a paradigm we term *meta-prediction* (Fig. 1A). The
meta-prediction applies the reward prediction principle in machine learning, formulated as
Bellman updates[15], to human reward prediction, which can likewise be specified as Bellman
updates (Fig. 1B). Unlike conventional task design and optimization schemes[16,17], this setting
enables us to generate diverse learning tasks that guide the human reward prediction in
targeted ways (Fig. 1C: encoding-decoding framework).

Leveraging the fact that the prediction error—defined as the discrepancy between human
predictions and actual environmental outcomes—serves as a readout of the interaction
between the environmental structure and human predictions, we trained the meta-prediction
framework to generate tasks that either minimize or maximize human prediction error.
Extremizing this signal creates a dynamic space in which learners navigate the tradeoff
between environmental stability and uncertainty. For precise modulation of reward learning
strategies, the framework targets the two distinct forms of prediction error known to guide
habitual and goal-directed learning[2,6,10,18]: reward prediction error (RPE) and state prediction
error (SPE).

To demonstrate the feasibility of the meta-prediction framework, first, we obtained subject-
specific human prediction models by fitting the computational model of RL to behavioral
data from 82 subjects in a 2-stage goal-directed learning task[7,8,10]. Second, we trained the
meta-prediction module ("meta-prediction" of Fig. 1) to minimize or maximize SPE and/or

RPE of the pre-trained human prediction model. These generated tasks were verified in two independent fMRI studies with a total of 49 participants. The behavior analyses examined whether and how these interventions influence subjects' performance and learning speed. The model-based fMRI analyses demonstrated the intervention effects on the neural activities of brain areas known to guide predictions

Result

Meta-prediction theory

Our core challenge is to design tasks accommodating the ways in which environmental stability and uncertainty shape human reward prediction. The proposed framework, termed *meta-prediction*, addresses this problem by systematically generating tasks based on predictions of human prediction.

The meta-prediction consists of two steps. It learns to predict human predictions about future outcomes (*human prediction* in Fig. 1A) and then uses this prediction to generate a new task design (meta-prediction in Fig. 1A). Importantly, this design ensures that meta-prediction generates a task design that effectively influences *human prediction*, thereby enhancing environmental diversity without losing learnability. Our framework is generalizable in that one can generate various task designs by applying different task optimization schemes. For example, one can make a curriculum easier by having the meta-prediction minimize the human prediction error, or alternatively, make the existing task more challenging by maximizing it. Moreover, the meta-prediction allows us to diversify the dimensions of scenarios by incorporating into meta-prediction various factors, such as individual differences (e.g., varying the parameters of the human prediction model), type (e.g., state or reward), or the profile of prediction (e.g., reducing, maintaining, or increasing the amount of prediction error).

To illustrate the theoretical background, our framework was designed based on the Bellman equation, the basic mathematical framework of reward prediction. Weaved into a single learning framework are two Bellman equations, one for human prediction and the other for meta-prediction (Fig. 1B and Supplementary Table 4-6 for algorithm description). The Bellman equation for human prediction learns to predict rewards of the environment (task) while the Bellman equation for meta-prediction learns to predict the residual of human prediction (prediction error) by changing the task variables. The role of the former is to provide full observations about latent variable changes of the human prediction process, so that the latter can effectively translate them into the task design. This completes a learning cycle of "task - human prediction - meta-prediction - task updates".

The learning cycle begins with individually fitted human prediction models to encode individual variability of human prediction strategies (the *encoding* step in Fig. 1C). To preclude overfitting issues, these models should adopt theoretical principles from neuroscientific studies[6–8] rather than data-driven approaches using a generic class of neural networks. The model used in this study accommodates the prefrontal control of model-based and model-free reinforcement learning[8]. Then, we train another learning agent, called a meta-prediction model, to optimize the task design by predicting human prediction error, estimated

114   from the human prediction module (*decoding* step in Fig. 1C). The meta-prediction network
115   was implemented with a deep reinforcement learning model[19,20].

Fully parameterized task space with varying predictability

To furnish the meta-prediction framework with a broad and flexible task space, we
generalized a conventional two-step Markov decision task[7,8,10]. The task paradigm was
carefully parameterized to accommodate stable goal-directed learning and adaptive foraging
with different degrees of uncertainty (Fig. 2A). Unlike traditional reward learning regimes in
which reward functions remain fixed regardless of subjects' choices to impose rigid
constraints on the human learner's prediction, our task parameters were crafted to support a
wide spectrum of predictability (Fig. 2B). They include (1) state-transition probability, which
directly influences the learner's prediction about state-transition, (2) goals, which links the
learner's prediction to reward, and (3) reward foraging, in which the reward changes as a
function of the learner's action.

First, for the state-transition, we used a switching probability[8] instead of a drifting
probability[10] because the former exerts a more dramatic impact on state prediction. The
transition probability switches between 0.9 and 0.5, each simulating the condition of low and
high predictability about state-transition, respectively. Second, the goal conditions were
adapted from Lee et al.(2014)[8], in which the reward is redeemable only if the goal and the
color of the coin obtained at the outcome state match (goal-dependent devaluation). The goal
is assigned at the beginning of each trial to facilitate reward prediction and goal-directed
behavior. Lastly, we introduced reward foraging (Fig. 2C). It is our major modification to the
existing two-step task paradigm. Here, the learner's reward acquisition decreases reward by a
certain ratio while rewards in the unvisited outcome states are gradually restored,
accommodating foraging in nature. Note that this action-dependent reward function creates
complex dynamics of the learner's predictions about future reward.

Our meta-prediction model adjusted these task parameters, each designed to serve a distinct
purpose: (1) foraging environment (decreasing the reward in the exploited goal state), (2)
stable environment (preserving the current task structure, maintaining environmental
consistency), (3) naturalistic foraging environment (reducing the exploited goal state's reward
while replenishing rewards in previously unexploited goal states), (4) goal-directed learning
environment (explicitly assigning target goal states), (5) volatile environment (altering the
state-transition probability between 0.9 and 0.5, introducing different level of uncertainty)
(Also refer to the table of Fig. 2C). Importantly, each task parameter adjustment corresponds
to a discrete action of the meta-prediction model's control policy. For example, the model's
action sequence 2-1-3-3 represents a specific task design: the environment begins in a stable
state (Action 2), transitions into reward depletion through foraging (Action 1), and evolves
into a more naturalistic foraging pattern (Action 3s), where rewards shift adaptively between
exploited and unexploited goal states.

Our parameterized task space enables the meta-prediction model to strategically intervene in
human prediction processes by shaping the structure and dynamics of the learning
environment. For example, if the meta-prediction model predicted the moment the learner
predicts reward acquisition, it would determine when and how to intervene in its prediction

by changing the reward function. Likewise, the meta-prediction model predicting a human's
prediction about state-transition could engage in human prediction by changing the structure
of the state space.

Meta-prediction networks

We trained the *meta-prediction* framework on the task parameter space defined in the
preceding section. The training process comprised two stages (illustrated in Fig. 1A): In the
encoding stage, the *"human prediction"* model (termed as HP) was trained to predict the
human's choice behavior. In the decoding stage, the *"meta-prediction"* models (termed as MP)
were trained to generate new tasks, using the *human prediction* model as a reward function.

The HP was implemented using a reinforcement learning algorithm that combines model-
based and model-free reinforcement learning on a trial-by-trial basis, which is known to
explain goal-directed and habitual reward learning[8]. Importantly, the HP affords the MP the
leverage to predict human prediction error, the key variable guiding human prediction. The
HPs' parameters were optimized to maximally match their value function with the choice
behavior of 82 individual human subjects, collected using the two-step Markov decision
task[8,21]. Model comparison and parameter recoverability analysis in the prior studies[8,22,23]
ensured the model's reliability in predicting human reward learning.

We then trained the MP (the learning agent) to learn the HP's prediction (the reward function).
To make the MP fully compatible with the HP, the state space of the MP included the HP's
state and/or reward prediction error, which is the key variable for model-based and model-
free learning (see the 'Meta-prediction models' section in the Method). The MP's action
refers to changing the task parameters (Fig. 2B). Accordingly, a single learning cycle of the
MP is illustrated as follows. The MP's action is followed by the HP's prediction, which is
followed by the MP's observation about the HP's prediction error. The MP then computes the
discrepancy between predicted and actual prediction errors of the HP (*meta-prediction error*
in Fig. 1B), based on which the MP updates its value function. The MP was implemented
using a double deep Q network.[19,20]

The MP was trained in four training conditions: maximizing/minimizing x reward/state
prediction error of HPs (MaxR, MinR, MaxS, and MinS; see Fig. 3A). In MaxR/MinR, the
MP learns to predict the HP's current absolute reward prediction errors, whereas in
MaxS/MinS, the MP aims to predict the HP's state prediction errors. For MaxR/MaxS, the
reward function for the MP was defined as being directly proportional to the HP's prediction
error. Conversely, in MinR/MinS, the reward function was inversely proportional to the HP's
prediction error. Note that these training settings achieve the key challenge of our *meta-*
prediction problem: by manipulating environment stability and uncertainty (corresponding to
MP's policy), the MP can effectively ensure a wide spectrum of predictability of the HP
(quantified as MP's reward functions).

We conducted a total of 328 independent simulations, comprising 82 HPs' training across 4
conditions. To mitigate potential learning biases or local minima issues in the HPs during the
encoding step, we implemented a pre-training phase. This phase allowed the HPs to freely
explore the task environment, enabling them to fully develop internal representations of both

the task structure and reward functions. In the subsequent decoding step, MPs underwent full
training while the parameters of HPs remained fixed. Despite the complexity of the training
process, which involved intricate interactions between HP and MPs within each training
epoch, all simulations demonstrated stable learning patterns (see Fig. 3B-K; for detailed
explanation, see the 'Training the individual MPs' section in the Method.).

Mechanistic interpretability of meta-prediction

Task designs generated by the meta-prediction framework help us decipher how specific
environmental changes shape human prediction. Specifically, these designs serve as a direct
translation of the complex dynamics underlying human reward learning into the language of
environmental structure and variability. This approach enables task-level mechanistic
interpretability,

For this, we examined the policy of the fully-trained MPs. The MPs for MaxR and MinR
used the foraging actions only: actions 1, 2, and 3 (Fig. 2C). For maximal efficacy of the MP
in controlling reward prediction error, it would be desirable for human subjects to use a
model-free reinforcement learning strategy because it is the basic value learning strategy that
acts on reward prediction error. To ensure this, we fixed the state-transition probability at 0.5
(highly uncertain transition) and left the goal color blank all the time (flexible goal condition;
any types of rewards are achievable), the situations known to encourage model-free
learning[8,9,21,22,24–26].

The simple dimension reduction of the MP's actions showed that the MP developed distinctly
different policies to control reward prediction of the HP from a very early stage of training
(Fig. 3B-(i),(ii),(iii); Cohen's *d*-score in Fig. 3B-(iv),(v)). Moreover, the learned policies
reflect individual variability, as indicated by their variance increasing with training (PC
variance in Fig. 3B-(iv),(v)). The meta-prediction error of the MP converges quickly as early
as 300 training episodes (Fig. 3C), effectively guiding the HP's reward prediction error in a
desired manner (Fig. 3D; MaxR > MinR, two-sample two-tailed t-test at episode 20000, n=82,
p<0.0001).

A distinct pattern emerged in the MinR task (Fig. 3E; corresponding action sequence shown
in Extended Data Fig. 1A). In the early stage, the suboptimal task favored a fixed reward
function (Action 2) to stabilize the HP's learning process. Foraging (Action 1) accelerated the
reduction of the HP's reward prediction error by narrowing the gap between actual reward
values and the HP's predictions. This preference for foraging (Action 1) persisted throughout
training. Consequently, Action 1 serves to rapidly reduce the HP's reward prediction error
without compromising learnability. This strategy effectively deludes the HP into perceiving
its choices as correct when they were not.

The MaxR favors a fixed environment (Action 2) with the most uncertain and complex
reward distribution, in which state-transition is least predictable (*state-transition*
probability=0.5) and different reward values are assigned to different outcome states (Fig. 3F;
corresponding action sequence shown in Extended Data Fig. 1B). It is consistent with our
intuition that uncertain and complex task structures are hard to learn.

Unlike MinR and MaxR, the MPs for MinS and MaxS aim to control state prediction error, a
key variable for model-based learning. To meet this control requirement, the MPs employed
all the actions, including the ones capable of changing foraging patterns, goals, and state-
transition probabilities (Action 4 and 5 in Fig. 2C). For example, when goal changes, subjects
must replan their behavioral policies. When reducing uncertainty in state transitions, subjects
can learn about task structures rapidly. Both situations demand model-based learning
strategies. To further aid highly predictable predictions of model-based learning, the initial
state-transition probability was set to 0.9.

The MPs discovered distinctly different tasks for MinS and MaxS from the very early stage
of training (Fig. 3G), as indicated by the rapid convergence of meta-prediction error of the
MPs (Fig. 3H). As a result, it effectively guides HP's state prediction error (Fig. 3I; MaxS >
MinS, two-sample two-tailed t-test at episode 20000, n=82, $p<0.0001$). In the MinS (Fig. 3J;
corresponding action sequence shown in Extended Data Fig. 1C), the MP maintained its
state-transition probability to match the current predictions of the HP (avoiding Action5). In
the MaxS, on the other hand, the MP used most of the actions (Action1-4) almost equally to
create inconsistent reward situations (see Fig. 3K) except Action5. Here the MP changes state
transitions to the least predictable condition (by taking a one-time Action5 to change *state-*
transition probability from 0.9 to 0.5) in the beginning of trials and keeps it all times
(corresponding action sequence shown in Extended Data Fig. 1D). The ablation analyses also
confirmed the significant contribution of the MP's key actions (Action1 for MinR, Action 2
for MaxR, and Action5 for MinS and MaxS, see Extended Data Fig. 2).

Validation of meta-prediction through cross-subject shuffle test

To confirm that the MP effect generalizes to new human subjects who were not part of the
initial cohort used to develop the HP and MP, we first sought to identify the most
generalizable *meta-prediction* model (MP) from our simulation results (Fig. 3). We employed
a MP-HP shuffle test, inspired by cross-validation in machine learning (See Methods for
more details). This test evaluates each MP's average performance across all the other HPs not
used during training, estimating out-of-sample performance.

Notably, across all four training conditions (MinR, MaxR, MinS, MaxS), the shuffle test
identified subject-independent MPs that consistently performed well across all 82 HPs within
each condition (Fig. 4A). These MPs demonstrated performance comparable to subject-
specific MPs in all conditions (paired two-tailed t-test with Bonferroni correction for multiple
comparison, $p>0.999$ (MinR, n=82; MaxR, n=82; MaxS, n=82), p=0.9790 (MinS, n=82),
detailed subject-independent MP policies are provided in Extended Data Fig. 3). These
findings suggest that, for these four key conditions, a single representative MP policy may
generalize across individuals, without the need for individual-specific task adaption or
calibration.

Moreover, both subject-specific and subject-independent MPs outperformed previous
experimental designs in separating state and reward prediction errors - particularly those
intended to dissociate model-based and model-free learning systems[8,21,22]. In the MinR
condition, MPs tailored to minimize reward prediction error reduced the HPs' reward
prediction errors beyond those observed in prior experiments, while in the MaxR condition,

they increased reward prediction errors to a comparable degree (Fig. 4A-i; paired two-tailed
t-test with Bonferroni correction for multiple comparison, p<0.013 (MinR vs previous
experiments, n=82), $p>0.999$ (MaxR vs previous experiments, n=82)). Similarly, the MPs
designed to extremize state prediction error yielded better performance in both MinS and
MaxS compared to the prior experiments. (Fig. 4A-ii, paired two-tailed t-test with Bonferroni
correction for multiple comparison, p<0.001 (MinS vs previous experiments, n=82; MaxS vs
previous experiments, n=82)). These findings demonstrated the ability of our MP framework
to generate calibrated task environments that effectively modulate human prediction errors.

Behavioral and neural effects on human reward learning

Using the task generated by the subject-independent MP, we conducted two fMRI
experiments with 49 human subjects in total. In the first experiment, 26 participants
performed the reward prediction error tasks (MinR and MaxR), and in the second experiment,
23 participants completed the state prediction error tasks (MinS and MaxS). Subjects learned
the task well in all cases, as evidenced by the above-chance-level choice optimality (one-
sample two-tailed t-test, $p=0.022$ (MinR, n=26); $p=0.004$ (MaxR, n=26), $p<0.0001$ (MinS,
n=23; MaxS, n=23)). The choice optimality was defined as the proportion of a subject's
choice that matches those of an optimal model-based reinforcement learning algorithm with
complete task information, including reward function and state-transition probability.

As an initial validation, we tested whether the subject-independent MPs modulated subjects'
prediction errors. The reward and state prediction errors were quantified by fitting model-free
and model-based reinforcement learning algorithms to individual choice behavior,
respectively. In the first experiment (MinR and MaxR), we found that the MP effectively
extremized reward prediction errors (MaxR > MinR in Fig. 4B-(i), paired t-test, p<0.0001,
n=26). The second experiment (MinS and MaxS) also confirmed that the MP effectively
extremized state prediction errors (MaxS > MinS in Fig. 4B-(ii), paired t-test, p<0.0001,
n=23).

We then examined the influence of MPs on the reward-related behavior of human subjects.
The MPs for prediction error minimization and maximization resulted in statistically
significantly different choice behavior patterns. Choice optimality, a standard behavioral
index for goal-directed learning[23], was higher in the MaxR condition compared to the MinR
(Fig. 4C-(i); paired t-test, p=0.0145, n=23), while it was higher in the MinS than the MaxS
(Fig. 4C-(iii); paired t-test, p < 0.0001, n = 26). The win-stay ratio, a typical behavioral
metric for habitual learning[27], was higher in the prediction error maximization (MaxS and
MaxR) compared to the minimization (MinS and MinR) (Fig. 4C-(ii); paired t-test, p=0.0141,
n=26; Fig. 4C-(iv), paired t-test, p=0.004, n=23). This measure was defined as the proportion
of a subject's first-stage action choices that replicated those from the preceding trial,
conditional on that trial yielding a high-valued reward (for details, see the 'Win-stay ratio'
section in the Method).

Lastly, we evaluated the neural effect of MP on reward learning using model-based fMRI
analyses (see the fMRI acquisition and fMRI analysis section in Method). The whole-brain
analyses confirmed the previous findings[2,7,8] that the reward prediction error was reflected in
the activity patterns of the ventral striatum (Fig. 4D-(i)), while the state prediction error was

encoded in the neural activity of multiple cortical areas, including dorsolateral prefrontal
cortex, insula, and intraparietal sulcus (Fig. 4D-(ii),(iii),(iv)), fully consistent with the
previous studies[7,8]. We also examined specific effects of MP in the core area known to guide
reward learning. For this, the neural activity was extracted from the BOLD signals in the
identified cortical regions and the ventral striatum (for detailed ROI definitions, see the
'percent signal change' section in Methods). The neural effect of MP in these areas survived
after the most stringent Bonferroni correction for multiple comparisons. The neural activity
change was significantly greater in MaxR/MaxS compared to MinR/MinS (Percent signal
change plots in the bottom of Fig. 4D).

Decoding individual goal-habit bias through meta-prediction

The demonstrated efficacy of the meta-prediction framework in modulating human reward
learning, both behaviorally and neurally, motivated us to further investigate its potential for
quantifying innate reward learning biases, particularly the dynamic balance between goal-
directed and habitual learning strategies[3,11,28–33]. This goal–habit bias represents a critical
dimension of cognitive flexibility, whose dysregulation has been implicated in psychiatric
disorders such as addiction or obsessive compulsive disorder[34–40]. To assess whether our
meta-prediction framework could capture such bias, we trained MPs to modulate the key
variable known to guide transitions between goal-directed and habitual control[8,21,22,41,42]:
long-term prediction errors of the HPs (Fig. 5A). They are defined as the reward and state
prediction errors over multiple trials. For consistency, we used the same simulation settings
as before (Figs. 3 and 4). The HPs used in our simulation were previously fitted to data from
82 human subjects, thus serving as proxies for individual human reward learning.

To identify an optimal training regime, we trained MPs under four training conditions: long-
term MinR, MaxR, MinS, and MaxS. As predicted by the earlier study on the effect of long-
term prediction error on goal-habit bias[8], the MP trained under the long-term MinR condition
facilitated goal-to-habit transition by providing a stable and predictable environment
(Extended Data Fig. 5B. In contrast, the MP under the long-term MaxS condition effectively
disrupted the goal-habit bias by placing high demands on goal-directed learning (Fig.
5B, Extended Data Fig. 5C). Building on this insight, we introduced a combined training
regime, long-term MaxS + MinR, to accelerate the transition from goal-directed to habitual
control (Fig. 5C).

The trained MPs enabled rapid transitions from goal-directed to habitual control in a subject-
specific manner (Extended Data Fig. 6H). Consequently, any decline in MP performance on
different HPs is likely to reflect individual variation in goal–habit bias. To probe this, we
performed an MP-HP shuffle test, evaluating each MP's performance across all MP-HP
combinations based on the total reward accrued by the MP. This analysis revealed two
distinct MP-HP clusters, wherein one MP group effectively extremized the long-term
prediction errors of one subset of HPs, but not for the other (labeled c1 and c2 in Fig. 5B,C-
(i), detailed clustering results in Extended Data Fig. 7H). Notably, we identified a subject-
independent MP within each cluster, which exhibited the best average performance across all
HPs, surpassing both the subject-independent and subject-specific MPs from the earlier
simulations of Fig. 4 (Fig. 5B,C-(ii), Wilcoxon test, p<0.0001 (long-term MaxS, n=82; long-

363 term MaxS+MaxR, n=82)).

364 Interestingly, similar clustering patterns were found under more complex training regimes
365 such as long-term MaxS+MaxR and long-term MaxS+MinR (see Extended Data Fig. 7E,H),
366 with consistent grouping patterns (see Extended Data Fig. 8). We also found that these MPs
367 tend to favor action repetition policies consistent with those derived from simpler training
368 conditions, such as long-term MaxS, suggesting underlying structural inductive bias in task
369 design (see Extended Data Fig.9). This highlights an intriguing possibility for compositional
370 task design. For instance, complex tasks can be constructed by combining a small set of
371 primitive MPs trained under foundational conditions (MinR, MaxR, MinS, and MaxS).

372 Building on the above findings, we evaluated whether these clusters (c1 and c2) are
373 associated with HPs' goal-habit bias. This bias was defined as the extent to which a model-
374 based reinforcement learning algorithm better accounts for each subject's behavior compared
375 to a model-free approach, quantified using likelihood values. Interestingly, the HP's goal-
376 habit bias showed biomodal distributions that closely aligned with the two clusters identified
377 in the MP-HP shuffle test (Fig. 5D,E-(i)). Note that this cluster-level alignment was found
378 solely from MP performance, without access to any HP-specific information. This presents a
379 new possibility for decoding individual goal-habit bias. By either assessing MP performance
380 or simply aggregating the prediction error from a new human subject, it may be possible to
381 infer not only an individual's goal-habit bias (Fig. 5D,E-(ii)) but also a key parameter
382 underpinning this bias: state prediction error tolerance (Fig. 5D,E-(ii)).

Discussion

384 This study addresses a fundamental challenge in reward learning task design: overly stable
385 environments constrain learning opportunities, and highly uncertain ones render reward
386 learning intractable. To address this dilemma, we proposed a novel conceptual framework,
387 *meta-prediction*, which integrates two Bellman equations: one that emulates human reward
388 learning, while the other learns to generate task design by predicting the first. This approach
389 offers three key advantages. First, it enables optimal task design by navigating the tension
390 between simple and uncertain environments. Second, It provides mechanistic interpretability,
391 translating the complex nature of human reward learning into task design. Third, it supports
392 compositional task design, revealing how complex tasks can be assembled from primitive,
393 model-driven task components generated by our framework.

394 While traditional data-driven approaches for task optimization or task adaptation primarily
395 rely on observable behavior, our framework targets a latent variable underlying human
396 reward learning: prediction error. This approach enables a deeper understanding of how
397 internal expectations shape external behavior. Specifically, we demonstrated that modulating
398 two distinct types of prediction errors - reward-based and state-action-state transition-based -
399 yields distinctly diverse changes at the behavior and neural levels. Behaviorally, these
400 manipulations could influence motivation[44] and difficulty[45], and neurally, they engage distinct
401 pathways, including the basal ganglia[28,29,33] and prefrontal cortex[39,32].

402 Beyond observable choice behavior, our framework provides a window into the innate biases
403 underpinning human reward learning. Specifically, we demonstrated that the MP performance

profile, derived from the MP-HP shuffle test, revealed two latent dimensions: the degree of
goal-directed behavior ("goal-habit bias" in Fig. 5D,E-(ii)) and its key variable to guide the
behavioral transition from goal-directed to habitual learning[8,22] ("SPE tolerance" in Fig.
5D,E-(ii)). This allows for the readout of the individual bias of goal-directed learning without
model-fitting, which can be time-consuming and prone to interpretive pitfalls. Instead, our
meta-prediction offers a compositionally scalable, mechanistically interpretable, and
personalized means to optimizing task design (Extended Data Fig.9).

Previous researches have demonstrated the potential of using computational cognitive models
to generate tasks that influence human decision-making[16,17]. However, these approaches have
limited scalability and applicability due to their dependence on a narrow task
parameterization scheme (Single-step Markov decision task[16], Go-NoGo test[17]) and the
repeated use of near-identical task conditions (Multiround trust task[17]). Moreover, these
models primarily target explicit human behaviors (left/right choices[16,17], amount of
payback[17]), while overlooking the underlying learning strategies underpinning such behaviors.
Although these models are trained on observable human actions, they provide limited
guarantees regarding alignment between the decision-making processes of humans and
artificial neural networks (ANNs). A recent study[46] suggested a method for value alignment
between humans and ANNs using the hidden cognitive variables, such as causal uncertainty.
Nonetheless, it does not yet establish a direct correspondence with the underlying neural
substrates guiding human reward learning processes.

Our framework addresses this limitation through a novel approach: the Meta-Prediction
model (MP) generates or optimizes parameterized tasks, while the Human Prediction model
(HP) provides predictions within these tasks. We have demonstrated that MPs successfully
generate tasks across various training conditions, even when their task space differs from that
of the HPs. Future work could benefit from our HP-MP framework by generalizing it to an
encoder-decoder architecture, with HP serving as encoders and MP as decoders. This
architecture is interpretable, as the encoder provides a direct estimation of human prediction
error, while the decoder offers interpretation at the task level. This encoder, which can be
exchanged with diverse structures of HPs[47,48], also offers generalizability and unified insights
into human behavior prediction and associated task generation

Our meta-prediction framework has wide-ranging applications across various domains. One
key area is curriculum learning[49], where our framework enhances task sequencing by
streamlining a progression of learning experiences that promote goal-directed behavior
without compromising overall learnability. In decision neuroscience, it helps fine-tune
existing task structures for better dissociation between state and reward prediction errors. In
smart education, it can enhance learning efficiency while accommodating individual
variability[50]. Additionally, our framework can guide the diagnosis and treatment of mental
disorders associated with learning and prediction. By leveraging models of abnormal
behavior distributions in various conditions, the meta-prediction module could generate
tailored tasks to facilitate diagnosis or intervene in the latent processes for cognitive behavior
therapy. In summary, our meta-prediction theory offers a fundamental solution to value
alignment between humans and AI models. Training a meta-prediction module to minimize
prediction error can be evolved into the process of aligning the relevant value functions[51] of

human subjects with those of an arbitrary AI model, implying the AI model's learning of the
human learning process, or the 'meta-learning' AI model.

Materials and Methods

General Stimuli

We used fractal images to represent the initial state, four intermediate states following the player's first action, and four terminal states associated with rewards. Each subject observed nine fractal images randomly selected from a set of 126 images at the beginning of the task. A square box was displayed beneath the state image to indicate the target goal color (red, blue, yellow, or white). In the terminal state (i.e., the final phase of each trial), a state-associated coin (red, blue, yellow, or gray) and its value appeared below the target goal color image. Coin acquisition depended on matching the target goal color, which was displayed alongside the coin value. The gray coin consistently had a reward value of zero throughout the task, while the values of the other colored coins were determined at the start of each experiment. The ranking and cumulative scores were presented below the coin value to maintain participant engagement.

General Tasks

The experimental setup for fitting the human prediction model was adapted from previous two-stage Markov decision tasks[7,8]. We then modified this setup for meta-prediction model training and its application to novel human subjects. The basic structure of the experiment was the same for both simulation and real-human subject tasks. Participants pressed one of two buttons ('Right' or 'Left') based on the current state image and goal color. If no choice was made within 4 seconds of the state image presentation, the computer randomly selected an action to continue the task. The next state appeared between one and four seconds after the action. Following the final state and reward presentation, a new game began two seconds later, starting with the same initial state image.

Each action led participants to one of 2 possible next states based on state transition probabilities that the participants had to infer implicitly. The meta-prediction model set the state transition probabilities of either [0.5, 0.5] or [0.9, 0.1]. The state-action-reward mapping remained constant for each participant across all sessions. Participants learned this mapping and inferred the current state transition probabilities during a pre-training session, which was not included in the performance evaluation. The participants then applied their knowledge during five main sessions. Each session consisted of 80 game trials, organized into four blocks of 20 trials.

Prior to the pre-training session, participants were instructed about potential changes in state transition probabilities and the implications of the goal color image. However, they were not informed of the specific values of the colored coins or the exact state images they would encounter. The colored coins, except for gray, represented 'high,' 'medium,' and 'low' reward values – initialized at 40, 20, and 10 rewards, respectively – and these values remained fixed as upper boundaries throughout the task. During simulation, rewards for non-target goal coins were deactivated and hidden under specific goal conditions until reactivation by the meta-prediction models.

At the start of each game, participants could identify the current goal color from the displayed

goal color indicating images. In the flexible goal condition (white box), participants could
obtain coins at terminal states regardless of color. In the specific goal condition (red, yellow,
or blue), coin acquisition was restricted to the trials where the coin color matched the target
goal color. These rules were explained to the participants before the pre-training session.

We integrated foraging paradigms into the conventional two-stage Markov Decision Task to
incentivize explorative behaviors and mitigate habitual decision-making strategies. The initial
value of the coins was set as the upper boundary threshold, with reward values below two
decimal points systematically eliminated. To promote foraging behavior and discourage
habitual actions, the value of the acquired reward coin was devalued by 65%-85%.

Each block of tasks was administered according to either (i) the task environments generated
by the meta-prediction model or (ii) a pseudo-random policy where action selections
followed a stochastic distribution with controlled frequencies to maintain outcome
equilibrium. After completing each block, participants were asked to rate task difficulty on a
5-point scale. This subjective rating, however, was not incorporated into the meta-prediction
model.

Human prediction models (HPs)

We used the same arbitration model of reinforcement learning (RL) described in the previous
paper[8]. The model consisted of three primary components: a model-free learner, a model-
based learner, and an arbitrator.

The model-free learner utilized the SARSA algorithm[1], a standard approach in RL. The
model-based learner employed forward learning[7] for state transition updates and backward
planning to address predictable changes in task structures. Both learners generated distinct
prediction errors following each action: the model-free learner produced reward prediction
error (RPE), while the model-based learner generated state prediction error (SPE). The
arbitrator evaluated each learner's reliability based on the history of prediction errors and
modulated their relative contributions through a dynamic equilibrium mechanism[8].
Furthermore, the arbitrator computed the integrated Q-action values from both learners and
selected actions via the soft-max function[7,50]. For a detailed algorithm description, see the
supplementary data S5 (HP algorithm).

The HPs were trained on behavioral data collected from 82 participants across two
experiments: 22 adults (6 females, mean age 28, age range 19-40) from the USA and 60
adults (31 females, mean age 22.75, age range 19-35) from South Korea. The same two-stage
Markov decision task, excluding the foraging condition, was used for both experiments. Both
studies received ethical approval from their respective Institutional Review Boards – Caltech
for the U.S. experiment and KAIST for the South Korean experiment.

Meta-prediction model (MPs)

The MPs chose one from five distinct, pre-defined options (see Figure 2C). The first three
options were available to both SPE and RPE control, which focused on restoring or
maintaining the value of the devalued coins: (i) *Foraging* – kept the task structure unchanged

after reward devaluation, (ii) *Stable environment* – targeted previously devalued coins of the
same color, and (iii) *Naturalistic foraging* – targeted coins of the different colors other than
those previously devalued. These three options above increased the targeted coin values by
multipliers between 1.18 and 1.54, with values capped at a predetermined maximum. Next,
the additional two options were exclusive to SPE control: (4) *Goal-directed learning* –
alternated between specific goals (which randomly selected colors at the beginning of each
game) and flexible goals, and (5) *Volatile environment* – modified the state transition
probabilities between (0.9, 0.1) and (0.5, 0.5).

We implemented the MPs using the double-DQN algorithm[19,20]. The MPs featured a fully
connected architecture with a single hidden layer containing 64 neurons. The input vector
consisted of 20 dimensions: 16 dimensions for the rewards at terminal states, two dimensions
for transition probability, and two dimensions representing SPE and RPE values for the
current agent. The action selection of the MPs was guided by an epsilon-greedy policy
(epsilon = 0.1) to ensure a balance between exploration and exploitation. The models were
trained using the RMSprop algorithm[51] with mean squared error as a loss function. The
replay buffer had a capacity of 4500 samples. The training was conducted with a batch size of
32. Each MP was trained for 20,000 episodes, which included a pre-training phase.

The reward functions for the MPs varied depending on their training conditions. When an MP
was designed to maximize a single immediate or long-term prediction error, it received a
reward directly proportional to that target prediction error. Conversely, MPs designed to
minimize a single target received a reward inversely proportional to the corresponding
prediction error.

For models trained to control multiple target prediction errors, the reward function was
defined as a combination of the individual reward functions associated with each target. For
example, an MP trained to maximize long-term state prediction error while minimizing long-
term reward prediction error received a reward equal to the sum of two sub-rewards: one
directly proportional to the long-term state prediction error, and the other inversely
proportional to the long-term reward prediction error.

The MP's target prediction errors included the HP's absolute reward prediction error, state
prediction error, long-term reward prediction error, and long-term state prediction error.

Training the individual MPs

We implemented the pre-training stage for both the HP and MPs to replicate the experimental
setting of the original human subject experiments. During the first 100 episodes, the HPs
explored the default foraging task by performing random actions. For the MPs, we first
detached them from the task for the initial 25 episodes out of 100 episodes. Afterwards, we
had them perform random actions for the remaining 75 episodes to explore their action space.
For algorithm description, see the supplementary data S4 (HP pre-training) and S6 (MP
training).

Analysis of the behavioral dynamics of tasks generated by MPs during training

In relation to Figure 2B, we conducted a comprehensive analysis on the behavioral
characteristics of tasks generated by the MPs, focusing on their dynamics across the
initialization, early, and late training stages. We achieved it by systematically evaluating task
parameters at each stage of training.

First, we captured snapshots of the tasks generated by the MPs during each training episode.
Each snapshot consisted of a sequence of trials within the episode and the corresponding task
parameters – transition probability and coin reward values – manipulated by the MP.

Next, we categorized the collection of snapshots into two distinct groups after vectorizing the
tasks. Each task was encoded as a vector, with episodes comprising 20 trials represented by
80-dimensional vectors (20 trials $\times$ 4 features: one feature for transition probability and three
for coin rewards). These vectors were grouped into two categories based on the MP's target
prediction errors.

We then performed principal component analysis (PCA) on the tasks in each group,
extracting the two principal components with the highest variance. Finally, we calculated
Cohen's distance[52] between these components, aligning the measurement with the direction
of the MP's prediction error control.

Ablation study to evaluate the contribution of the MPs' key action

To highlight the significance of the MP's key action, we conducted a systematic ablation
study by strategically reducing the action space while preserving the consistent experimental
setup for the MPs' training. In these control tasks, MPs incorporating SPE were limited to
four actions (i.e., one action was removed from the original five). In contrast, those
employing RPE were restricted to two actions (i.e., one action was removed from the original
three). Importantly, all other experimental settings remained identical to the original MP
training framework, ensuring a controlled comparison. This approach enabled us to examine
the sensitivity of the models to changes in action space and to assess their controllability
across varying control task objectives (e.g., MinR, MaxR, MinS, MaxS).

Acquisition of the generalized MPs

We systematically collected subject-specific task environments generated by trained MPs,
each of which corresponded to a distinct HP. A comprehensive set of 82 task environments
was generated for each MP objective. These meticulously constructed task environments
were subsequently applied across all HPs, resulting in 82 $\times$ 82 sets of behavioral data,
wherein HPs responded to the task environments generated by the MPs. For each HP-MP pair,
we conducted a simulation of 100 episodes and computed the average reward achieved by the
MP across these episodes.

The MP that generated the task environment demonstrating the highest average reward across
all HPs was identified as the subject-independent MP. To rigorously assess performance, we
conducted a paired *t*-test to statistically compare the rewards obtained by the subject-
independent MP against those generated by individual HP-specific MPs.

Participants

A total of 26 right-handed volunteers (15 females, mean age 22.5, age range 19-35)
participated in the RPE control task, while 23 right-handed volunteers (9 females, mean age
24, age range 19-31) took part in the SPE control task, both of which included fMRI scanning.
Participants were pre-screened to exclude individuals with a history of neurological or
psychiatric illnesses. All participants provided informed consent, and the study was approved
by the KAIST Institutional Review Board.

Behavioral measures

Choice optimality: The choice optimality of individual participants evaluates whether they
had correctly learned the task structure and adapted their behavior across different task blocks.
It is defined as the proportion of optimal first-stage actions relative to the total number of
first-stage choices. An action is considered optimal if it has the highest expected value,
assuming full knowledge of both the coin reward values and the state transition probabilities.

Win-stay ratio: The win-stay ratio estimates individual habitual learning bias, which reflects
the tendency to persist with previous action choices that led to rewarding outcomes.
Rewarding outcomes are defined as coin rewards that exceed the average value of the current
coin set. For example, if the coin values were (Red: 35, Blue: 15, Yellow: 7, Gray: 0), the
rewarding outcomes would be the red and blue coins, as their values exceed the average
(14.25). The win-stay ratio is then calculated as the proportion of trials in which the first-
stage action is repeated following a trial that yielded a rewarding outcome.

Reaction time: We analyzed the effect of task control conditions on reaction time (RT) in
both RPE and SPE control tasks. In both conditions, there were no significant differences
between RT values. (RT MinR = 0.68s; RT MaxR = 0.71s, RT MinR vs MaxR paired t-test;
p=0.174; RT minS = 0.72s; RT maxR = 0.74s, RT MinR vs MaxR paired t-test; p=0.58, see
Extended Data Figure 4 for details.)

fMRI data acquisition

Functional imaging for the RPE task was conducted using a 3T Philips Achieva scanner
located at the Korea Basic Science Institute (KBSI). In comparison, the SPE task was
performed on a 3T Siemens Verio scanner located at the KAIST fMRI center. Both scanners
used 32-channel radio frequency coils. High-resolution structural images were acquired using
MPRAGE sequences, with a resolution of 1.2 mm $\times$ 1.2 mm $\times$ 1.2 mm for the RPE task and 1
mm $\times$ 1 mm $\times$ 1 mm for the SPE task.

Functional scans were acquired using a one-shot echo-planar imaging sequence (RPE: TR =
2500 ms; TE = 35 ms; FOV = 100 mm; flip angle = 79°; SPE: TR = 2500 ms; TE = 30 ms;
FOV = 100 mm; flip angle = 90°). Both tasks acquired 45 slices, with voxel resolutions of 3.5
mm $\times$ 3.5 mm $\times$ 3.5 mm for the RPE task and 3 mm $\times$ 3 mm $\times$ 3 mm for the SPE task.

fMRI Data analysis

We analyzed the fMRI data using the SPM12 software package (Wellcome Department of

Imaging Neuroscience, Institute of Neurology, London). Slice-timing correction was applied
to the functional images to address differences in acquisition times across individual slices
within each scan. The images were then motion-corrected, spatially normalized to a standard
echo-planar imaging (EPI) template to account for anatomical variability between
participants, and smoothed using a 3D Gaussian kernel with an 8 mm full width at half
maximum (FWHM). The processed dataset was subsequently subjected to statistical analysis.

GLM analysis

We employed a General Linear Model (GLM) to perform whole-brain analyses of human
decision-making processes. The model included regressors for stimulus onsets (R1),
parametric regressors encoding target prediction errors (R2-RPE or SPE) at the same time
points, and the movement-related regressors (R3-R8). For each GLM run at the single-subject
level, orthogonalization of the regressors was disabled to preserve the correlated information
between SPE and RPE. A whole-brain FWE correction ($p < 0.05$) was applied to account for
multiple comparisons. A high-pass filter (cutoff = 129 s) was used to remove low-frequency
noise from the data. All reported brain coordinates were based on MNI coordinates.

Percent signal change analyses

We selected spherical regions of interest (ROIs) based on the GLM results to examine
prediction errors. The SPE ROIs were defined as 20 mm radius spheres centered at (30, -56,
44), (48, 16, 46), and (34, 22, 0) for the intraparietal sulcus, dorsolateral prefrontal cortex,
and insular cortex, respectively. The RPE ROI was defined as a 5 mm radius sphere centered
at (-14, 8, -12) for the ventral striatum. All brain coordinates were based on MNI
coordinates. The difference in sphere radius was chosen based on the varying sizes of the
relevant brain regions.

We performed a percent signal change analysis using the rfxplot toolbox
(http://rfxplot.sourceforge.net/) to investigate prediction error onsets across different MP
objectives (minimizing, maximizing, and pseudo-random). Due to the relatively slow block
frequency (20 trials per block ≈ 15 minutes per block), we turned off high-pass filters during
the 1st level GLM analysis prior to conducting the percent signal change analysis.

HP-MP shuffle analysis

After acquisition of the HP-specific MPs for controlling long-term prediction errors, we
assessed the controller reward ranking for each MP within each HP. Each MP was assigned
an 82-length vector representing its ranking across specific HPs. We performed hierarchical
clustering based on the Euclidean distance between the controller reward ranking vectors.

Task environments that did not involve maximizing long-term state prediction errors showed
no clear separations (Extended Data Fig. 7-A,B,D,F,G). In contrast, three task conditions that
involved maximizing long-term state prediction errors exhibited similar cluster separations
(Extended Data Fig. 7-C,E,H), differing by only about 2-3 subjects (Extended Data Fig. 8).

For further cluster analysis, we selected clusters that maximized long-term state prediction

errors + minimized long-term reward prediction errors. The same method used for prediction
error analysis was applied to the principal component analysis of the task environments.

Data availability

The raw behavioral data and fMRI results are available for download at
https://github.com/brain-machine-intelligence/meta_prediction_2024.

Code availability

The simulation codes are also available for download at https://github.com/brain-machine-
intelligence/meta_prediction_2024.

Acknowledgements

This work was funded by the National Research Foundation of Korea(NRF) grant funded by
the Korea government(MSIT).(RS-2024-00341805), Institute of Information &
communications Technology Planning & Evaluation (IITP) grant funded by the Korea
government (MSIT) (No. RS-2023-00233251, System3 reinforcement learning with high-
level brain functions), the National Research Foundation of Korea(NRF) funded by the
Korean government (MSIT) (No. RS-2024-00439903), Institute for Information &
communications Technology Promotion(IITP) grant funded by the Korea
government(MSIT)(No.RS-2019-II190075 Artificial Intelligence Graduate School
Program(KAIST), Electronics and Telecommunications Research Institute(ETRI) grant
funded by the Korean government (25ZB1100, Core Technology Research for Self-
Improving Integrated Artificial Intelligence System), and Electronics and
Telecommunications Research Institute(ETRI) grant funded by the Korean government
[N01230878, Development of Beyond X-verse Core Technology for Hyper-realistic
interactions by Synchronizing the Real World and Virtual Space].

Author contributions

S.W.L., J.H.L and J.S. conceived and designed the study. J.S. implemented the behavioral
task and ran the fMRI study. J.H.L implemented the initial task controller and the simulation
framework. J.S. designed computational models and analyzed the data. S.W.L and J.S. wrote
the paper. S.W.L, J.H.L and J.S. reviewed, revised and edited the paper. All authors approved
the final version for submission.

Competing interests

The authors declare no competing interests.

Additional information

Supplementary information is available for this paper.

Correspondence and requests for materials should be addressed to S.W.L.

-References

1.   Schultz, W. Predictive reward signal of dopamine neurons. *J. Neurophysiol.* **80**, 1–27 (1998).

2.   Wunderlich, K., Dayan, P. & Dolan, R. J. Mapping value based planning and extensively trained
724   choice in the human brain. *Nat. Neurosci. 2012 155* **15**, 786–791 (2012).

725   3.   Tricomi, E., Balleine, B. W. & O'Doherty, J. P. A specific role for posterior dorsolateral striatum
726   in human habit learning. *Eur. J. Neurosci.* **29**, 2225–2232 (2009).

727   4.   Ikemoto, S. & Panksepp, J. The role of nucleus accumbens dopamine in motivated behavior: a
728   unifying interpretation with special reference to reward-seeking. *Brain Res. Rev.* **31**, 6–41
729   (1999).

730   5.   Tolman, E. C. Cognitive maps in rats and men. *Psychol. Rev.* **55**, 189–208 (1948).

731   6.   O'doherty, J. P., Dayan, P., Friston, K., Critchley, H. & Dolan, R. J. Temporal Difference Models
732   and Reward-Related Learning in the Human Brain V(t UCS) and V(t UCS 1) generates a
733   positive prediction error that, in the simplest form of TD learning, is used to increment the value
734   at time t UCS-1 (in proportion to. *Neuron* **28**, 329–337 (2003).

735   7.   Gläscher, J., Daw, N., Dayan, P. & O'Doherty, J. P. States versus rewards: Dissociable neural
736   prediction error signals underlying model-based and model-free reinforcement learning. *Neuron*
737   **66**, 585–595 (2010).

738   8.   Lee, S. W., Shimojo, S. & O'doherty, J. P. Neural Computations Underlying Arbitration between
739   Model-Based and Model-free Learning. (2014) doi:10.1016/j.neuron.2013.11.028.

740   9.   Daw, N. D., Niv, Y. & Dayan, P. Uncertainty-based competition between prefrontal and
741   dorsolateral striatal systems for behavioral control. **8**, (2005).

742   10.   Daw, N. D., Gershman, S. J., Seymour, B., Dayan, P. & Dolan, R. J. Model-based influences on
743   humans' choices and striatal prediction errors. *Neuron* **69**, 1204–1215 (2011).

744   11.   Balleine, B. W. & O'Doherty, J. P. Human and Rodent Homologies in Action Control:
745   Corticostriatal Determinants of Goal-Directed and Habitual Action. *Neuropsychopharmacol.*
746   *2010 351* **35**, 48–69 (2009).

747   12.   Dayan, P. & Daw, N. D. Decision theory, reinforcement learning, and the brain. *Cogn. Affect.*
748   *Behav. Neurosci.* **8**, 429–453 (2008).

749   13.   Momennejad, I. *et al.* The successor representation in human reinforcement learning. *Nat. Hum.*
750   *Behav. 2017 19* **1**, 680–692 (2017).

751   14.   Wang, J. X. *et al.* Prefrontal cortex as a meta-reinforcement learning system. *Nat. Neurosci.*
752   *2018 216* **21**, 860–868 (2018).

753   15.   Bellman, R. E. & Zadeh, L. A. Decision-Making in a Fuzzy Environment.
754   *https://doi.org/10.1287/mnsc.17.4.B141* **17**, B-141-B-164 (1970).

755   16.   Dezfouli, A. *et al.* Disentangled behavioural representations. *Adv. Neural Inf. Process. Syst.* **32**,
756   (2019).

757   17.   Dezfouli, A., Nock, R. & Dayan, P. Adversarial vulnerabilities of human decision-making. *Proc.*
758   *Natl. Acad. Sci. U. S. A.* **117**, 29221–29228 (2020).

18. Sutton, R. S. & Barto, A. G. *Introduction to reinforcement learning*. vol. 135 (MIT press Cambridge, 1998).

19. Van Hasselt, H., Guez, A. & Silver, D. Deep Reinforcement Learning with Double Q-Learning. *Proc. AAAI Conf. Artif. Intell.* **30**, 2094–2100 (2016).

20. Mnih, V. *et al.* Human-level control through deep reinforcement learning. *Nat. 2015 5187540* **518**, 529–533 (2015).

21. Kim, D., Jeong, J. & Lee, S. W. Prefrontal solution to the bias-variance tradeoff during reinforcement learning. *Cell Rep.* **37**, (2021).

22. Kim, D., Park, G. Y., O'Doherty, J. P. & Lee, S. W. Task complexity interacts with state-space uncertainty in the arbitration between model-based and model-free learning. *Nat. Commun. 2019 101* **10**, 1–14 (2019).

23. Heo, S., Sung, Y. & Lee, S. W. Effects of subclinical depression on prefrontal–striatal model-based and model-free learning. *PLOS Comput. Biol.* **17**, e1009003 (2021).

24. Kool, W., Cushman, F. A. & Gershman, S. J. When Does Model-Based Control Pay Off? *PLOS Comput. Biol.* **12**, e1005090 (2016).

25. Dolan, R. J. & Dayan, P. Goals and Habits in the Brain. *Neuron* **80**, 312–325 (2013).

26. Dayan, P. & Balleine, B. W. Reward, Motivation, and Reinforcement Learning. *Neuron* **36**, 285–298 (2002).

27. Lee, Julie J., and Mehdi Keramati. "Flexibility to contingency changes distinguishes habitual and goal-directed strategies in humans." PLOS Computational Biology 13.9 (2017): e1005753.

28. Balleine, B. W. & Dickinson, A. Goal-directed instrumental action: contingency and incentive learning and their cortical substrates. *Neuropharmacology* **37**, 407–419 (1998).

29. Graybiel, A. M. Habits, rituals, and the evaluative brain. *Annu. Rev. Neurosci.* **31**, 359–387 (2008).

30. Valentin, V. V., Dickinson, A. & O'Doherty, J. P. Determining the Neural Substrates of Goal-Directed Learning in the Human Brain. *J. Neurosci.* **27**, 4019–4026 (2007).

31. De Wit, S., Corlett, P. R., Aitken, M. R., Dickinson, A. & Fletcher, P. C. Differential Engagement of the Ventromedial Prefrontal Cortex by Goal-Directed and Habitual Behavior toward Food Pictures in Humans. *J. Neurosci.* **29**, 11330–11338 (2009).

32. Yin, H. H., Knowlton, B. J. & Balleine, B. W. Lesions of dorsolateral striatum preserve outcome expectancy but disrupt habit formation in instrumental learning. *Eur. J. Neurosci.* **19**, 181–189 (2004).

33. Yin, H. H., Ostlund, S. B., Knowlton, B. J. & Balleine, B. W. The role of the dorsomedial striatum in instrumental conditioning. *Eur. J. Neurosci.* **22**, 513–523 (2005).

34. Wyckmans, F. *et al.* Reduced model-based decision-making in gambling disorder. *Sci. Reports 2019 91* **9**, 1–10 (2019).

35. Voon, V. *et al.* Disorders of compulsivity: a common bias towards learning habits. *Mol. Psychiatry 2015 203* **20**, 345–352 (2014).

36. Robinson, T. E. & Berridge, K. C. The incentive sensitization theory of addiction: some current
issues. *Philos. Trans. R. Soc. B Biol. Sci.* **363**, 3137–3146 (2008).

37. Lee, R. S. C., Hoppenbrouwers, S. & Franken, I. A Systematic Meta-Review of Impulsivity and
Compulsivity in Addictive Behaviors. *Neuropsychol. Rev.* **29**, 14–26 (2019).

38. Abramovitch, A., Abramowitz, J. S. & Mittelman, A. The neuropsychology of adult obsessive–
compulsive disorder: A meta-analysis. *Clin. Psychol. Rev.* **33**, 1163–1171 (2013).

39. Kim, T. *et al.* Neurocomputational model of compulsivity: deviating from an uncertain goal-
directed system. *Brain* **147**, 2230–2244 (2024).

40. Ruan, Z., Liu, S., Liu, Y. an, Yang, Q. & Peng, Z. Disorders of compulsivity: Deficits in
arbitrating learning strategies. *Addict. Biol.* **29**, e13433 (2024).

41. Yoshida, W. & Seymour, B. Decisions about Decisions. *Neuron* **81**, 468–470 (2014).

42. O'Doherty, J. P., Lee, S. W. & McNamee, D. The structure of reinforcement-learning
mechanisms in the human brain. *Curr. Opin. Behav. Sci.* **1**, 94–100 (2015).

43. Da Silva, Carolina Feher, and Todd A. Hare. "Humans are primarily model-based learners in the
two-stage task." *BioRxiv* (2019): 682922..

44. Hamid, Arif A., et al. "Mesolimbic dopamine signals the value of work." *Nature neuroscience*
19.1 (2016): 117-126.

45. Behrens, Timothy EJ, et al. "Learning the value of information in an uncertain world." *Nature
neuroscience* 10.9 (2007): 1214-1221.

46. Lee, J. H., Heo, S. Y., & Lee, S. W. Controlling human causal inference through in silico task
design. *Cell Reports*, *43*(2) (2024).

47. Jaskir, Alana, and Michael J. Frank. "On the normative advantages of dopamine and striatal
opponency for learning and choice." Elife 12 (2023): e85107.

48. Bavard, Sophie, and Stefano Palminteri. "The functional form of value normalization in human
reinforcement learning." Elife 12 (2023): e83891.

49. Bengio, Y., Louradour, J., Collobert, R. & Weston, J. Curriculum learning. ACM Int. Conf.
Proceeding Ser. 382, (2009).

50. Matiisen, T., Oliver, A., Cohen, T. & Schulman, J. Teacher-Student Curriculum Learning. IEEE
Trans. Neural Networks Learn. Syst. 31, 3732–3740 (2017

51. Corlett, Philip R., Jessica A. Mollick, and Hedy Kober. "Meta-analysis of human prediction
error for incentives, perception, cognition, and action." Neuropsychopharmacology 47.7 (2022):
1339-1349.

52. Luce, R. D. INDIVIDUAL CHOICE BEHAVIOR * Theoretical Analysis.

53. Hinton, G., Srivastava, N. & Swersky, K. Neural Networks for Machine Learning Lecture 6a
Overview of mini---batch gradient descent.

54. Cohen, J. Statistical Power Analysis for the Behavioral Sciences. Stat. Power Anal. Behav. Sci.
(2013) doi:10.4324/9780203771587.

Fig 1. Meta-prediction. (A) Meta-prediction problem. (Left) In an uncertain value-learning environment, the
human prediction model (HP) aims to learn the probability distribution of the task's reward and structure by
minimizing the mismatch between the estimated and true distribution, called prediction error. (Middle) Meta-
prediction model (MP) aims to learn the distribution of individual HP errors from the HP-task interaction
(*encoding*). (Right) Once learning is completed, meta-prediction can generate the task by changing the task
parameters to guide HP (*decoding*). **(B)** Formulating the MP problem as a coupled Bellman equation. The
overall framework consists of the two-stage predictions, each specified as a separate Bellman equation. The red
and blue correspond to HP and MP, respectively. MP's reward function is defined as the prediction error of the
HP. The MP's state space is defined as the task variable and the HP's prediction error. The MP's actions are
defined as a set of changes of the task parameters. The MP's prediction error (i.e., "meta-prediction error") is
defined as the difference between the expected and the actual prediction error of the HP. The MP problem can be
solved using reinforcement learning (RL) algorithms. **(C)** The meta-prediction framework comprises three steps:
pre-task for data acquisition, HP fitting, and MP training. First, human choice behavior data were collected
using a reward learning task, such as a two-step goal-directed learning task[8,10]. Second, HPs were fitted to
imitate the individual subject's behavior ("encoding"). Third, another RL model (MP) was trained to change the
task parameters so as to guide the key variables of the individual HP. This training process yields an MP that
generates a task design to guide a single subject's behavior ("decoding"). Note that our framework is applicable
to any parameterized task.

Figure 2. Parameterized reward learning task. (A) Markov decision task[8,10] for goal-directed learning and foraging. This task accommodates goal-directed learning and foraging under environmental uncertainty. The learner, either a human subject or a human prediction model (HP), makes two consecutive choices in a single trial to collect coins of different colors. In each trial, subjects are presented with one of the three goals indicated by different colors. Subjects are asked to collect a coin available at the outcome state. Each outcome state contains a coin of a specific color, associated with a different reward amount. Coins are redeemable only when the current goal color matches the coin color, enforcing goal-directed learning. If the goal color is blank, all coins are redeemable, making the task equivalent to conventional reward learning. To reach the desired outcome state, subjects must learn to navigate the state-space whose structure is determined by state-transition probabilities. The fractal image and a box represent a state and a goal, respectively. **(B)** The structure of the task. The task parameters (θ_t) consist of the state transition probability (p_t) and the reward associated with different coin colors (r_t). The reward amount r_t may change over time by the associated Meta-prediction (MP) model's actions. **(C)** The MP's actions are defined on the task parameter space. Each action has a distinctive role: foraging (action #1, decreasing the reward in the visited goal state), stable environment (action #2, preserving the current task environment setting), naturalistic foraging (action #3, decreasing the visited goal state's reward while recovering other goal states' rewards), goal-directed learning (action #4, changing the target goal states), volatile environment (action #5, switching the state-transition probability between 0.9 and 0.5).

(A) Training conditions of meta-prediction models (MPs) and their rewards from human prediction models (HPs)

Training condition	Minimizing |Reward prediction error|	Maximizing |Reward prediction error|	Minimizing State prediction error	Maximizing State prediction error
Abbreviation	MinR	MaxR	MinS	MaxS
MP reward	∝ -1x HP's |reward prediction error|	∝ HP's |reward prediction error|	∝ -1 x HP's state prediction error	∝ HP's state prediction error

(B) Task generated by MPs at different training stages: MinR and MaxR

(C) Learning curve **(D) Learning curve** **(E) Action profile of MP models** **(F) Action profile of MP models**

(G) Task generated by MPs at different training stages: MinS and MaxS

(H) Learning curve **(I) Learning curve** **(J) Action profile of MP models** **(K) Action profile of MP models**

Fig 3. Mechanistic interpretation of meta-prediction. **(A)** Four training conditions of meta-prediction. The
meta-prediction models (MP) were trained to extremize prediction errors: MinR (minimizing reward prediction
error), MaxR (maximizing state prediction error), MinS (Minimizing state prediction error), MaxS (maximizing
state prediction error). **(B)** Tasks generated by MPs at the initialization, early, and late training stages in MinR
and MaxR. The dimension reduction analyses with PCA summarize how MPs learn to control each task
parameter in two opposite training conditions. Throughout training, tasks gradually accommodate not only
different training objectives (as indicated by the separability measure in (iv); Cohen's d) but also individual
variability (as indicated by the variance measure in (iv); variance). **(C)** Learning curve of the MP's meta-
prediction error. **(D)** Changes in the human prediction model (HP)'s reward prediction error during training. **(E-
F)** Action profile of MPs. Shown are the changes in the MP's action frequency, i.e., how many times the MP
changed task structures. **(E)** MaxR condition**, (F)** MinR condition. **(G-K)** The same analyses as (C-F), which
are for MinS and MaxS MP simulation data instead of MinR and MaxR MPs.

885
Fig 4. Behavioral and neural effects of meta-prediction. (A) Performance of meta-prediction models (MP)
was evaluated based on the prediction errors generated by human prediction models (HP). Performance
comparisons were made with the previous studies[8,21,22]. Prediction error was assessed under four training
conditions: MinR, MaxR, MinS, and MaxS (See Fig. 3A). S.S denotes subject-specific MP, trained individually
on each HP. S.I. denotes subject-independent MP, a single MP identified through the HP-MP shuffle test that
achieved the best average performance across all HPs. We validated the generalizability of S.I. by demonstrating
that its performance was comparable to that of its subject-specific counterparts, S.S. We then used S.I. for the
rest of the analyses. In addition to this direct performance, we also confirmed that the generated task designs
elicit greater variability in human prediction error (Fig. 4A-MP reward), compared to the prior two-step reward
learning tasks[8,21,22,] which relied on the hand-crafted environments. **(B)** Behavioral effects of the MPs in MinR
and MaxR. The effect was measured based on (i) the absolute reward prediction errors, estimated from the
model-free reinforcement learning (RL) fitted to individual subjects' behavior, (ii) the choice optimality, and (iii)
the win-stay ratio of individual subjects. **(C)** Behavioral effects of the MPs in MinS and MaxS. The state
prediction errors were estimated from the model-based RLs fitted to individual subjects' behavior. **(D)** Neural
evidence of MPs. Activities in the ventral striatum[2,7,8] correlated with reward prediction errors (i), while
activities in the lateral prefrontal cortex[7,8](ii), insula[8](iii), and intraparietal sulcus[7,8] (iv) correlated with state
prediction errors. The percent signal change analysis was performed on a 5mm radius. Error bars represented
SEM across subjects. Asterisks (*) indicate significance levels: * p<0.05, ** p<0.01, *** p<0.001 (two-tailed
paired t-test with n = 82 for (A), n=26 for (B)-i, (C)-i, (C)-iii, n=23 for (B)-ii, (C)-ii, (C)-iv). Clusters showing
significant effects at a threshold of p<0.001 (uncorrected) with a minimum cluster size of 100 voxels are
displayed in yellow in the brain images located in the upper row of the sub-figure (D).

Fig 5. Individual goal-habit bias classification with meta-prediction. (A) Effect of long-term prediction error (PE) on goal-directed reinforcement learning (RL) adopted from *Yoshida et al.(2014)*[41]. Earlier works showed that the reward/state PE (RPE/SPE) over multiple trials (long-term PE) is the key variable to explain bias towards two different reward learning strategies: goal-directed and habitual learning[8,21,41,42]. This view suggests that a meta-prediction model (MP) to control long-term PE could decode the goal-habit bias. **(B)** MPs trained for long-term SPE maximization. (i) MP-human prediction model (HP) shuffle test. We trained MPs for long-term SPE maximization (long-term MaxS). Shown are the MP rewards obtained from the frozen MPs applied to each HP. Two MP clusters were found, as indicated by c1 and c2. (ii) In terms of MP rewards, the cluster-based subject-independent MPs (C.B.) are better than a single subject-independent MP (S.I.) and multiple subject-specific MPs (S.S). (Wilcoxon test with Bonferroni test for multiple comparison; n=82, *p*<0.0001 for both S.S vs C.B and S.I vs C.B). **(C)** MPs were trained for long-term SPE maximization + long-term RPE minimization.

The same analyses as (B), except for MPs' target, which was the long-term SPE maximization + long-term RPE
minimization (dual objective long-term MaxS + MinR, Wilcoxon test with Bonferroni test for multiple
comparison; n=82, p<0.0001 for both S.S vs C.B and S.I vs C.B) **(D)** (i) MP-generated tasks for long-term SPE
maximization (dimension reduction analyses). Two different types of MP-generated tasks were indicated by red
(c1) and blue (c2) clusters. c1 and c2 were labeled from the (B). (ii) Distribution of goal-habit bias (left) and
SPE tolerance (right) of HPs was color-coded by the two clusters found in (C). The goal-habit bias was
measured as an innate preference to habitual RL (w in *Daw et al.(2011)*[10]; P_{mb} in *Lee et al.(2014)*[8]). The SPE
tolerance is the key parameter to reflect the sensitivity to its own PE[8]. **(E)** The same analyses as (D), except for
MPs for long-term SPE maximization + long-term RPE minimization. c1 and c2 were labeled from the (C).
Although (D) and (E) were based on independent experiments with independently performed clustering, the SPE
tolerance parameter histograms were identical, as both experiments resulted the same HP clusters (see Extended
Figure 8).

Extended Data Figure 1, Related to Figure 3. The action sequences of subject-specific meta-
prediction models (MPs) after training. The y-axis represented the frequency of actions across 82
MPs. In trial 1, all MPs were set to the 'Foraging' (action 1) action. **(A)** MPs minimizing reward
prediction error selected the 'Naturalistic foraging' action at trial 2, followed by consistent 'Foraging'
(action 1) actions, reducing reward discrepancies between optimal and suboptimal choices. **(B)** MPs
maximizing reward prediction error favored the 'Do nothing' (action 2) actions from trial two onward,
maintaining a steady reward discrepancy between optimal and suboptimal choices. **(C)** MPs
minimizing state prediction error maintained the initial low volatility (state transition probability = [0.9,
0.1]) by ignoring the 'Volatile environment' (action 5) action and frequently chose the 'Goal-directed
learning' (action 4) action to reinforce goal-directed behaviors in the HP. **(D)** MPs maximizing state
prediction error quickly shifted environmental volatility to a high stochastic level (state transition
probability = [0.5, 0.5]) and kept it by using the 'Volatile environment' (action 5) action only in trial 2.
Moreover, MPs used the 'Goal-directed learning' (action 4) action less than other actions, promoting a
shift in HPs from goal-directed to more habitual behaviors.

(A) Reward prediction error minimization

(B) Reward prediction error maximization

(C) State prediction error minimization

(D) State prediction error maximization

ns : non-significant, ** : p<0.01, **** : p<0.0001.
All statistics tests were paired t-tests with Bonferroni corrections for multiple comparisons.

Extended Data Figure 2, Related to Figure 3. The effect of action ablation in meta-prediction models
(MPs) on HP behavior. On the x-axis, 'None' represented fully intact MPs, while 'Action #' denoted
MPs with specific action removed. **(A)** MPs minimizing reward prediction error showed significantly
impaired performance in reward error control when the key action 'Foraging' (action 1) was ablated.
(B) Removing the 'Do nothing' action (action 2) in the MPs maximizing reward prediction error led to a
significant performance reduction. **(C)** The action ablation effects on the MPs minimizing state
prediction error were non-significant. **(D)** For state prediction error maximization, ablation of the
'Volatile environment' action (action 5) significantly impaired performance. Ablating 'Goal-directed
learning' (action 4) also reduced state prediction error control. Asterisks (*) indicate significance

levels: * p<0.05, ** p<0.01, *** p<0.001, **** p<0.0001 (two-tailed paired t-test with n = 82).

(A) Subject-independent MP's policy with reward prediction error minimization

Meta-prediction model (MP) action ■ : Action performed by the MP model

Action 1 (Foraging)
Action 2 (Do nothing)
Action 3 (Naturalistic foraging)

(B) Subject-independent MP's policy with reward prediction error maximization

Meta-prediction model action

Action 1 (Foraging)
Action 2 (Do nothing)
Action 3 (Naturalistic foraging)

(C) Subject-independent MP's policy with state prediction error minimization

Meta-prediction model action

Action 1 (Foraging)
Action 2 (Do nothing)
Action 3 (Naturalistic foraging)
Action 4 (Goal-directed learning)
Action 5 (Volatile environment)

(D) Subject-independent MP's policy with state prediction error maximization

Meta-prediction model action

Action 1 (Foraging)
Action 2 (Do nothing)
Action 3 (Naturalistic foraging)
Action 4 (Goal-directed learning)
Action 5 (Volatile environment)

961 **Extended Data Figure 3, Related to Figure 4.** Subject-independent meta-prediction (MP) policies
962 under four conditions: **(A)** MinR, **(B)** MaxR, **(C)** MinS and **(D)** MaxS. Black boxes mark the actions
963 taken by the MP model.

ns : non-significant, **** : p<0.0001.
All statistical tests were paired t-tests with Bonferroni corrections for multiple comparisons.

Extended Data Figure 4, Related to Figure 4. The meta-prediction models (MPs)' effect on the

reaction time of human subjects. **(i)** Subject-wise (n=26) averaged reaction time under MP conditions

for controlling reward prediction errors. The x-axis labels represent: 'MinR' = reward prediction error

minimization, 'Random' = pseudo-random actions, and 'MaxR' = reward prediction error

maximization. **(ii)** Subject-wise (n=23) averaged reaction time under MP conditions for controlling

state prediction errors. The x-axis labels represent: 'MinS' = state prediction error minimization,

'Random' = pseudo-random actions, and 'MaxS' = state prediction error maximization. The error bars

represent SEM, while dots represent the individual subject's data (n=26 for (i), n=23 for (ii)). Asterisks

(*) indicate significance levels: *** p<0.001 (two-tailed paired t-test with n = 26 for (i) and n = 23 for

(ii)).

(A) Long-term reward prediction error minimization

(B) Long-term reward prediction error maximization

(C) Long-term state prediction error minimization

(D) Long-term state prediction error maximization

(E) Long-term reward prediction error minimization
+ Long-term state prediction error minimization

(F) Long-term reward prediction error maximization
+ Long-term state prediction error maximization

(G) Long-term reward prediction error maximization
+ Long-term state prediction error minimization

(H) Long-term reward prediction error minimization
+ Long-term state prediction error maximization

Extended Data Figure 5, Related to Figure 5. The action sequences of subject-specific meta-
prediction models (MP) are trained for controlling long-term prediction errors. The y-axis represented
the frequency of actions across 82 MPs. In trial 1, all MPs were set to the 'Foraging' (action 1) action.
(A-D) MPs controlling a single type of prediction error displayed distinct action profiles: **(A)** a 'Do
nothing' (action 2) plateau; **(B)** a 'Goal-directed learning' (action 5) peak at trial 2; **(C)** 'Volatile
environment' (action 5) avoidance; and **(D)** a 'Volatile environment' (action 5) peak at trial 2. **(E-H)**
MPs controlling both prediction errors exhibited combined action profiles from relevant single-error
MPs. **(E)** showed a mix of (B) ''Goal-directed learning' (action 4) peaked at trial 2 and (D) 'Volatile
environment' (action 5) peaked at trial 3. **(F)** combined (A) 'Do nothing' (action 2) plateau and (C)
'Volatile environment' (action 5) avoidance. **(G)** combined partial (B) 'Do nothing' (action 2) plateau
with (D) 'Volatile environment' (action 5) peak at trial 2. **(H)** combined (B) 'Goal-directed learning'

(action 4) peak at trial 2 and (C) 'Volatile environment' (action 5) avoidance

(A) Long-term reward prediction error maximization

(B) Long-term reward prediction error minimization

(C) Long-term state prediction error maximization

(D) Long-term state prediction error maximization

(E) Long-term reward prediction error maximization
+ Long-term state prediction error maximization

(F) Long-term reward prediction error maximization
+ Long-term state prediction error minimization

(G) Long-term reward prediction error maximization
+ Long-term state prediction error minimization

(H) Long-term reward prediction error minimization
+ Long-term state prediction error maximization

Extended Data Figure 6, Related to Figure 5. The goal-habit bias of Human Prediction models (HPs)
with trained subject-specific Meta Prediction models (MPs) for long-term prediction error controls. **(A-**
D) The goal-habit bias of HPs with MPs controlling only one type of prediction error. Only the MPs
maximizing long-term state prediction error **(C)** stretched the goal-habit bias of HPs toward habitual
direction. **(E-H) The** goal-habit bias of HPs with MPs controlling both types of prediction errors. The
MPs that maximize the long-term prediction errors **(E, H)** showed the goal-habit bias separation

among HPs.

Extended Data Figure 7, Related to Figure 5. The distance between the Human Prediction model (HP)
's simulated behavior from the whole set of trained subject-specific Meta Prediction models(MPs). The
x-axis was automatically sorted for visualization. The HP behaviors under MPs with the long-term
state prediction error maximizations (**C, E, H**) showed two clusters in the dendrogram, while other
MPs (**A, B, D, F, G**) did not show the separations.

1003

(A) MaxS vs MinRMaxS Confusion Matrix **(D) MaxRMaxS vs MinRMaxS Confusion Matrix** **(C) MaxS vs MaxRMaxS Confusion Matrix**

※ MaxS : Long-term state prediction error maximization
MinRMaxS : Long-term reward prediction error minimization ÷ long-term state prediction error maximization
MaxRMaxS : Long-term reward prediction error maximization ÷ Long-term state prediction error maximization

Extended Data Figure 8, Related to Figure 5. The confusion matrices between Human Prediction model (HP) clusterings under 3 Meta Prediction models (MPs; The long-term state prediction error maximization only; MaxS, The long-term reward prediction error maximization + the long-term state prediction minimization; MaxRMaxS, The long-term reward prediction error minimization + the long-term state prediction minimization; MinRMaxS). The HP clusters were replicated in independent classifications with each MP.

(A) Long-term state prediction error maximization cluster 1

(B) Long-term state prediction error maximization cluster 2

(C) Long-term reward prediction error maximization + Long-term state prediction error maximization cluster 1

(D) Long-term reward prediction error maximization + Long-term state prediction error maximization cluster 2

(E) Long-term reward prediction error minimization + Long-term state prediction error maximization cluster 1

(F) Long-term reward prediction error minimization + Long-term state prediction error maximization cluster 2

1012

Extended Data Figure 9, Related to Figure 5. Optimized action sequences of subject-specific meta-
prediction models (MPs) controlling long-term prediction errors within each cluster. The y-axis
represented action frequency across 82 MPs in a specific trial. All MPs were set to 'Foraging' (action
1) in trial 1. (**A, B**) MPs maximizing only the long-term state prediction error. Both clusters exhibited a
prominent 'Volatile environment' (action 5) peak in trial 2. From trial three onward, clusters diverged:
cluster 1 MPs (**A**) favored 'Do nothing' (action 2) over other actions in most of the remaining trials,
while cluster 2 MPs (**B**) mostly selected 'Goal-directed learning' (action 4) in trial 3, then made
random actions, excluding 'Volatile environment' (action 5), after trial 3. (**C, D**) MPs maximizing both
long-term reward prediction error and long-term state prediction error. The MPs followed a mixed
policy, combining the behavior of long-term state prediction error MPs in the same cluster with the
policy of long-term reward prediction error maximization MPs (see Extended Data Fig. 5B). (**E, F**) MPs
minimizing long-term reward prediction error and maximizing long-term state prediction error. These
MPs followed a mixed policy, combining the behavior of long-term state prediction error MPs in the

same cluster with that of long-term reward prediction error minimization MPs (see Extended Data Fig.

5A).

Supplementary Data

Table S1. Parameter values of human prediction models in Meta-prediction training, Related to Figure

1C.

subject \ parameter	1	2	3	4	5	6
1	0.614434	0.077846	0.485981	6.358767	0.02833	0.199619
2	0.768861	0.303617	0.121948	9.841435	0.163633	0.079116
3	0.789506	0.348951	0.104459	7.674034	0.151593	0.069762
4	0.409728	0.106105	0.115738	3.459498	0.109123	0.100876
5	0.526636	0.289645	0.100623	9.439895	0.092528	0.141934
6	0.606038	0.342951	0.111231	9.076079	0.190424	0.131374
7	0.760805	0.257565	0.111405	8.585745	0.24738	0.049113
8	0.547765	0.097489	0.10841	3.83039	0.267223	0.023925
9	0.655238	0.348549	0.141602	8.84792	0.119685	0.097181
10	0.662204	0.035764	0.113472	9.770955	0.232971	0.176474
11	0.44467	0.047784	0.106051	0.493613	0.131951	0.198862
12	0.310721	0.051232	0.329584	0.133219	0.070455	0.191334
13	0.571157	0.322415	0.12557	9.499509	0.042897	0.07735
14	0.43934	0.095588	0.116781	0.145777	0.113934	0.187598
15	0.31271	0.010084	0.128219	6.354347	0.075998	0.199572
16	0.310466	0.015333	0.100762	0.100675	0.034124	0.178554
17	0.388709	0.023578	0.110374	0.874238	0.092507	0.090436
18	0.431981	0.01841	9.12556	5.438772	0.073431	0.198329
19	0.407993	0.048459	0.117829	0.176122	0.200654	0.086718
20	0.779709	0.341282	0.130899	9.993625	0.133518	0.086143
21	0.752672	0.346166	0.132993	7.2859	0.107888	0.01332
22	0.322062	0.024744	0.106951	0.124803	0.165586	0.068983
23	0.446239	0.246659	0.779179	6.856203	0.121264	0.091161
24	0.371982	0.228268	2.823635	5.559278	0.065565	0.199967
25	0.381629	0.111274	0.109168	6.159796	0.049914	0.128051
26	0.788474	0.340892	0.110013	8.002945	0.052318	0.100677
27	0.321857	0.017022	0.111729	1.000458	0.178763	0.014052
28	0.300924	0.029971	9.905311	6.714189	0.061418	0.034508

1031

parameter subject	1	2	3	4	5	6
29	0.324384	0.09861	9.9952	0.115685	0.126445	0.199985
30	0.537777	0.296909	0.11631	2.262599	0.088132	0.195528
31	0.592012	0.338338	0.110825	9.999963	0.148137	0.177133
32	0.301583	0.342705	9.146814	9.922909	0.010052	0.010093
33	0.755449	0.314772	0.170361	8.759698	0.081446	0.033905
34	0.776697	0.346732	9.997266	9.987646	0.059832	0.199926
35	0.605991	0.186202	0.432683	6.133691	0.010068	0.010406
36	0.302178	0.01087	0.134902	1.309548	0.045499	0.199933
37	0.531646	0.095563	0.111375	3.536236	0.092553	0.021334
38	0.637308	0.342439	0.109019	7.637068	0.221664	0.092096
39	0.59083	0.014004	0.111107	6.30222	0.172549	0.141236
40	0.362292	0.056831	1.003234	0.194567	0.065983	0.01008
41	0.300063	0.010425	0.109499	0.735191	0.249828	0.166104
42	0.39453	0.027757	0.290048	1.50953	0.057533	0.077469
43	0.415871	0.06227	0.13131	2.027751	0.046044	0.146878
44	0.786126	0.095856	0.109239	9.074241	0.15545	0.117417
45	0.303426	0.331936	0.513855	7.642088	0.046049	0.19903
46	0.712641	0.344217	4.342648	9.410404	0.135017	0.199966
47	0.302296	0.115472	9.737553	2.706059	0.09124	0.15917
48	0.403089	0.032476	0.110356	4.048887	0.021734	0.083046
49	0.788937	0.082713	0.166061	8.764681	0.094145	0.199098
50	0.635781	0.337506	0.113893	9.691597	0.184215	0.095825
51	0.627248	0.31874	0.112056	8.719899	0.115659	0.12472
52	0.690221	0.130822	0.111413	9.197222	0.137439	0.057715
53	0.761633	0.033442	0.273668	9.813905	0.032257	0.010046
54	0.315846	0.057795	0.112027	0.112444	0.370857	0.103709
55	0.329614	0.264606	0.183554	2.144173	0.062925	0.17437
56	0.485611	0.013314	0.15194	0.101912	0.30808	0.090112

1032

subject \ parameter	1	2	3	4	5	6
57	0.35893	0.329849	0.104179	9.616879	0.10953	0.112101
58	0.414693	0.33331	0.165218	9.657266	0.085795	0.199955
59	0.50646	0.118649	0.116518	2.924663	0.082591	0.179123
60	0.705979	0.33874	0.103961	9.991226	0.095651	0.126693
61	0.475085	0.108457	0.116342	3.730337	0.134566	0.113445
62	0.430969	0.347205	0.113076	9.993661	0.301218	0.13597
63	0.364989	0.335778	0.106356	9.525257	0.325967	0.160961
64	0.313824	0.066376	0.108005	0.746548	0.337433	0.152106
65	0.305608	0.023424	0.110639	0.100247	0.16997	0.095547
66	0.478126	0.015675	0.113917	0.104709	0.370248	0.012558
67	0.312882	0.265409	0.110839	6.826111	0.355819	0.022437
68	0.408621	0.34813	0.116268	9.545918	0.132775	0.102069
69	0.737792	0.349941	0.110716	9.088162	0.329604	0.109003
70	0.300125	0.328244	0.107688	9.979268	0.400769	0.077915
71	0.324178	0.020972	0.116942	1.075751	0.118785	0.032027
72	0.328015	0.012474	0.107297	2.428303	0.150773	0.199184
73	0.689799	0.144685	1.92092	2.926623	0.168029	0.159962
74	0.310902	0.056944	0.376634	3.406745	0.032164	0.067326
75	0.303094	0.058424	0.119711	0.482937	0.252542	0.010001
76	0.318385	0.0385	0.107431	9.728752	0.162256	0.110868
77	0.734543	0.349841	0.115792	9.647542	0.227691	0.140819
78	0.331594	0.014504	0.1101	0.10008	0.338421	0.191684
79	0.596621	0.32534	9.936829	9.266734	0.220292	0.010664
80	0.777138	0.349217	9.979405	8.676161	0.031022	0.197258
81	0.54892	0.308085	0.119453	7.895054	0.117192	0.197752
82	0.369014	0.013708	0.110438	3.257821	0.063261	0.141257

1033

1034 Parameter: 1- the threshold for defining zero state prediction error (SPE tolerance), 2- learning rate
1035 for the estimate of absolute reward prediction error, 3- rate of the habit-to-goal-directed transition, 4-
1036 rate of the goal-directed-to-habit transition, 5- inverse softmax temperature, and 6- learning rate of the
1037 goal-directed and the habitual learning systems, respectively.

 Table S2. Estimated parameter values of the prefrontal arbitration model, Related to Figure 4.

Reward prediction error control tasks

subject \ parameter	1	2	3	4	5	6
1	0.475129	0.244932	3.66343	3.02382	0.081958	0.047232
2	0.368079	0.487818	2.376709	9.898783	0.118322	0.310977
3	0.488006	0.488482	3.354468	9.92199	0.055769	0.049636
4	0.665453	0.197037	3.832987	3.856635	0.050004	0.010007
5	0.536118	0.414714	1.046106	1.191814	0.058217	0.49608
6	0.451306	0.412087	1.005015	2.671201	0.082689	0.421449
7	0.50993	0.306304	3.497932	5.415076	0.063202	0.010761
8	0.482246	0.114717	2.36597	4.052568	0.248365	0.123599
9	0.359004	0.492258	3.494057	9.872424	0.075655	0.499487
10	0.370926	0.486767	3	9.999978	0.1	0.479178
11	0.503838	0.201378	2.649779	3.627712	0.066899	0.161286
12	0.437984	0.155733	2.104488	2.651422	0.229046	0.088943
13	0.51512	0.241276	3.741184	1.757229	0.112595	0.116186
14	0.390985	0.498614	3.684519	9.610778	0.050109	0.499951
15	0.49285	0.052648	1.673708	1.00693	0.175449	0.495999
16	0.340496	0.194724	4.031402	1.98596	0.100013	0.320243
17	0.57028	0.252891	3.776668	3.968012	0.061544	0.018286
18	0.384995	0.499965	4.677387	9.982321	0.104433	0.235305
19	0.442284	0.323197	2.957537	3.083252	0.062703	0.422468
20	0.485335	0.092766	1.912168	5.453637	0.314769	0.010305
21	0.451767	0.499699	4.221357	9.999563	0.05025	0.367851
22	0.47545	0.489992	3.40096	9.935951	0.050412	0.456673
23	0.321378	0.489111	3.660831	9.824635	0.323079	0.17502
24	0.388085	0.430312	3.369189	9.662924	0.131554	0.180766
25	0.430411	0.083497	2.296856	3.430749	0.190055	0.292059
26	0.582313	0.161638	2.901955	2.576973	0.217325	0.052623

State prediction error control tasks

subject \ parameter	1	2	3	4	5	6
1	0.366403	0.899558	4.227148	9.858211	0.105907	0.101737
2	0.491226	0.197798	3.1235	2.959441	0.100011	0.100006
3	0.511405	0.210789	3.089085	2.880197	0.1	0.100105
4	0.264288	0.894963	3.366421	7.665539	0.109545	0.100476
5	0.448075	0.877808	4.455444	9.682624	0.100003	0.100014
6	0.312218	0.870475	4.200886	9.850393	0.106495	0.1009
7	0.542662	0.210569	3.332858	2.724288	0.100051	0.100005
8	0.440397	0.893482	3.866649	9.994524	0.1	0.101707
9	0.392674	0.890089	6.462891	9.938265	0.100013	0.100588
10	0.586275	0.216551	3.138944	2.998257	0.100031	0.100074
11	0.598884	0.203268	3.158897	3.048291	0.100001	0.100018
12	0.626025	0.89911	4.766795	9.93205	0.101802	0.215735
13	0.499932	0.238437	3.001558	2.997257	0.1	0.1
14	0.244288	0.899826	3.203043	9.983915	0.101463	0.6295
15	0.547448	0.22875	3.357933	1.919244	0.100001	0.100177
16	0.287579	0.753099	4.259656	9.912507	0.100303	0.100581
17	0.384664	0.832239	3.775143	9.952997	0.100023	0.100004
18	0.213488	0.892058	6.227573	9.999685	0.105125	0.100049
19	0.769316	0.487718	7.616646	6.59841	0.100007	0.100012
20	0.859277	0.437525	4.38729	7.214847	0.147334	0.100008
21	0.606601	0.635436	7.318267	4.538007	0.100004	0.100045
22	0.842506	0.567995	4.425778	3.372492	0.100479	0.218753
23	0.897395	0.161823	4.412243	7.593415	0.193518	0.1

1040

1041 Parameter: 1- the threshold for defining zero state prediction error (SPE tolerance), 2- learning rate

1042 for the estimate of absolute reward prediction error, 3- rate of the habit-to-goal-directed transition, 4-

1043 rate of the goal-directed-to-habit transition, 5- inverse softmax temperature, and 6- learning rate of the

1044 goal-directed and the habitual learning systems, respectively.

 Table S3. Neural signatures of the habitual and goal-directed systems, Related to Figure 4.

x	y	z	Peak in region	Hemi	p (FWE)	Z-score
Reward prediction error (RPE) in RPE control task						
-12	42	34	rACC	L	0.000	4.19[++]
-14	8	-12	Ventral Striatum (NAc)	L	0.074	3.88[+−]
12	8	-14	Ventral Striatum (NAc)	R	0.035	3.84[++]
Reward prediction error (RPE) in SPE control task						
-26	-4	20	Dorsal striatum (putamen)	L	0.027	4.24[++]
State prediction error (RPE) in SPE control task						
34	22	0	Insula	R	0.000	6.09*
4	32	50	dmPFC	R	0.000	5.73*
-26	-70	-10	Fusiform	L	0.000	5.61*
42	8	30	lPFC	R	0.000	5.50*
-38	6	34	lPFC	L	0.000	5.36*
-10	-74	-30	Cerebellum	L	0.002	5.31*
-26	-84	18	Cuneus	L	0.000	5.29*
48	16	46	dlPFC	R	0.002	5.11*
14	-66	36	Precuneus	R	0.002	5.10*
30	-56	44	IPS	R	0.000	5.07*
-30	22	0	Insula	L	0.003	5.04*
10	4	6	Ventral Striatum (NAc)	R	0.000	4.99*
-28	-58	44	IPS	L	0.007	4.82*
26	-70	-6	Fusiform	R	0.004	4.81*

1046

- rACC: rostral anterior cingulate cortex, NAc: nuclear accumbens, PCC: posterior cingulate cortex,

dmPFC: dorsomedial prefrontal cortex, lPFC: lateral prefrontal cortex, dlPFC: dorsolateral prefrontal

cortex, IPS: Intraparietal sulcus

- All the areas (marked with either "++", or "*") survived after the whole-brain correction for multiple

comparison at the cluster level (corresponding to "+"; height threshold t=3.53, extent>100 voxels),

except for the value signals.

- p (FWE): corresponds to peak-level if the z-score indicates *, and corresponds to cluster-level if the

zscore indicates ++/+.

*: thresholded p<0.05 FWE corrected at the peak-level, minimum 5 voxels extent.

++: survives whole-brain correction for multiple comparison at the cluster level (height threshold

t=3.53, extent>200 voxels).

 Table S4. Algorithm for Human-prediction (HP) pre-training, Related to method section

---

Algorithm 1: Human-Prediction (HP) pre-training

Input: Max training episode N, max trial T_{max}, Hyperparmeter set (prediction error memory buffer size M, learning rate λ, SPE tolerance θ, RPE learning rate Ω, rate of the habit-to-goal-directed transition $\mathcal{A}_{MB}$, rate of the goal-directed-to-habit transition $\mathcal{A}_{MF}$, inverse softmax temperature T) from paper [8]

Output: Pre-trained model-free tabular Q matrix Q_{MF}^*, pre-trained model-based tabular Q matrix Q_{MB}^*

Initialize model-free Q-table $Q_{MF} \leftarrow 0$;

Initialize model-based Q-table $Q_{MB} \leftarrow 0$;

for $episode = 1$ **to** N **do**

Reset SPE memory $\mathcal{D}_{SPE} \leftarrow \emptyset$ with capacity M;

Reset RPE memory $\mathcal{D}_{RPE} \leftarrow \emptyset$ with capacity M;

for $t = 1$ **to** T_{max} **do**

while $\neg$ *game terminate* **do**

8   Observe task state o_t *from* Task;

9   Observe task reward r_t^{HP} *from* Task;

             `// P_MB initialization by goal color from paper [8]`

10   Initialize Goal-habit bias P_{MB} from o_t;

             `// reward prediction error from paper [1]`

11           $\{RPE_t, Q_{MF}\} \leftarrow ModelFreeRL(o_t, r_t^{HP}; \lambda)$;

             `// state prediction error from paper [7]`

12           $\{SPE_t, Q_{MB}\} \leftarrow ModelBasedRL(o_t, r_t^{HP}; \lambda)$;

             `// long-term prediction error from paper [8]`

13   **append** RPE_t to $\mathcal{D}_{RPE}$ (drop oldest if $|\mathcal{D}_{RPE}| > M$);

14   **append** SPE_t to $\mathcal{D}_{RPE}$ (drop oldest if $|\mathcal{D}_{SPE}| > M$);

             `// P_MB from paper [8]`

15           $P_{MB} \leftarrow Arbitration(\mathcal{D}_{RPE}, \mathcal{D}_{SPE}, P_{MB}; \mathcal{A}_{MB}, \mathcal{A}_{MF})$;

16           $Q_{arb} \leftarrow Q_{MB} * P_{MB} + Q_{MF} * (1 - P_{MB})$;

17   HP action $a_t^{HP} \leftarrow softmax(Q_{arb}; T)$;

18   $\{Q_{MF}^*, Q_{MF}^*\} \leftarrow \{Q_{MF}, Q_{MB}\}$

 Table S5. Algorithm for Human-prediction (HP), Related to method section

---

Algorithm 2: Human-Prediction (HP)

Input: N, T_{max}, pre-trained model-free tabular Q matrix Q_{MF}^{pre}, pre-trained model-based tabular Q matrix Q_{MB}^{pre}, M, HP parameters $(M, \lambda, \theta, \Omega, \mathcal{A}_{MF}, \mathcal{A}_{MB}, T)$

Output: State prediction error SPE_t, Reward prediction error RPE_t, long-term SPE_t, long-term RPE_t

for $episode = 1$ **to** N **do**

Reset model-free Q-table $Q_{MF} \leftarrow Q_{MF}^{pre}$;

Reset model-based Q-table $Q_{MB} \leftarrow Q_{MB}^{pre}$;

Reset SPE memory $\mathcal{D}_{SPE} \leftarrow \emptyset$ with capacity M;

Reset RPE memory $\mathcal{D}_{RPE} \leftarrow \emptyset$ with capacity M;

for $t = 1$ **to** T_{max} **do**

while $\neg$ *game terminate* **do**

8   Observe task state o_t *from* Task;

9   Observe task reward r_t^{HP} *from* Task;

            `// `P_{MB}` initialization by goal color from paper [8]`

10   Initialize Goal-habit bias P_{MB} from o_t;

            `// reward prediction error from paper [1]`

11            $\{RPE_t, Q_{MF}\} \leftarrow ModelFreeRL(o_t, r_t^{HP}; \lambda)$;

            `// state prediction error from paper [7]`

12            $\{SPE_t, Q_{MB}\} \leftarrow ModelBasedRL(o_t, r_t^{HP}; \lambda)$;

            `// long-term prediction error from paper [8]`

13   **append** RPE_t to $\mathcal{D}_{RPE}$ (drop oldest if $|\mathcal{D}_{RPE}| > M$);

14   **append** SPE_t to $\mathcal{D}_{RPE}$ (drop oldest if $|\mathcal{D}_{SPE}| > M$);

15   long-term $RPE_t \leftarrow UncertaintyMF(\mathcal{D}_{RPE}; \Omega)$;

16   long-term $SPE_t \leftarrow UncertaintyMB(\mathcal{D}_{SPE}; \theta)$;

            `// `P_{MB}`s from paper [8]`

17            $P_{MB} \leftarrow Arbitration(\mathcal{D}_{RPE}, \mathcal{D}_{SPE}, P_{MB}; \mathcal{A}_{MB}, \mathcal{A}_{MF})$;

18            $Q_{arb} \leftarrow Q_{MB} * P_{MB} + Q_{MF} * (1 - P_{MB})$;

19   HP action $a_t^{HP} \leftarrow softmax(Q_{arb}; T)$;

Algorithm 3: Meta-Prediction (MP) algorithm

Input: HP hyperparameter set θ^{HP}, N, T_{max}, MP pre-training episode length N^{pre}, MP learning rate α; replay capacity L; minibatch size B; ε-greedy ε; discount γ; target update period C; initial task environment $\{\mathcal{R}_0, p_0\}$; goal-conditioned reward $\mathcal{R}_g(\cdot)$ (see Fig. 3A); MP action set $\{\mathcal{A}_1(\cdot), \ldots, \mathcal{A}_n(\cdot)\}$ (see Fig. 2C)

Output: Trained online parameters θ^*, MP action a_t^{MP}

Initialize online $Q(s, a; \theta)$ network with random θ;
Initialize target $Q^-(s, a; \theta^-)$ network with $\theta^- \leftarrow \theta$;
Initialize replay buffer $\mathcal{D} \leftarrow \emptyset$ with capacity L;
HP pre-training($\theta^{HP}, N^{pre}, T_{max}$) ;   // Algorithm 1
for *episode* $= 1$ **to** N **do**
Reset task environment $\{\mathcal{R}_{\text{task}}, p\} \leftarrow \{\mathcal{R}_0, p_0\}$;
for $t = 1$ **to** T_{max} **do**
while $\neg$ *game terminate* **do**
if $t = 1$ **then**
$a_t^{MP} = \mathcal{A}_1(\cdot)$
else
$s_t \leftarrow \text{concat}(\mathcal{R}_{\text{task}}, p, \text{SPE}_{t-1}, \text{RPE}_{t-1})$;
if *episode* $\leq N^{pre}$ **then**
14            $a_t^{MP} \sim \text{Uniform}(\{\mathcal{A}_1(\cdot), \ldots, \mathcal{A}_n(\cdot)\})$
15   **else**
16            $a_t^{MP} \leftarrow \varepsilon\text{-greedy}(\{\mathcal{A}_1(\cdot), \ldots, \mathcal{A}_n(\cdot)\}; s_t, \theta, \varepsilon)$
$(\mathcal{R}_{\text{task}}, p, d_t) \leftarrow a_t^{MP}(\mathcal{R}_{\text{task}}, p)$; // $d_t \in \{0, 1\}$ is terminal
$\{\text{SPE}_t, \text{RPE}_t\} \leftarrow HP(\theta^{HP})$;   // Algorithm 2
$r_t^{MP} \leftarrow \mathcal{R}_g(\text{SPE}_t, \text{RPE}_t)$;
$s_t' \leftarrow \text{concat}(\mathcal{R}_{\text{task}}, p, \text{SPE}_t, \text{RPE}_t)$;
if *episode* $> N^{pre}$ **then**
append $(s_t, a_t, r_t^{MP}, s_t', d_t)$ to $\mathcal{D}$ (drop oldest if $|\mathcal{D}| > L$);
if $|\mathcal{D}| \geq B$ **then**
sample $\{(s_i, a_i, r_i^{MP}, s_i', d_i)\}_{i=1}^{B} \sim \mathcal{D}$;
for $i = 1$ **to** B **do**
if $d_i = 1$ **then**
27            $y_i \leftarrow r_i^{MP}$;
28   **else**
           // selection by online
29            $a_i' \leftarrow \arg\max_a Q(s_i', a; \theta)$;
           // evaluation by target
30            $y_i \leftarrow r_i^{MP} + \gamma Q^-(s_i', a_i'; \theta^-)$;
31        $L(\theta) \leftarrow \frac{1}{B} \sum_{i=1}^{B} (y_i - Q(s_i, a_i; \theta))^2$;
32        $\theta \leftarrow \theta - \alpha \nabla_\theta L(\theta)$;
33   **if** $t \bmod C = 0$ **then** $\theta^- \leftarrow \theta$;

1063   Table S6. Algorithm for Meta-prediction (MP) pre-training, Related to method section