1 Depositing biological segmentation datasets FAIRly

2 Elaine ML Ho[1], Dimitrios Ladakis[1], Mark Basham[1], Michele C Darrow[1*]

3 [1]Artificial Intelligence and Informatics, The Rosalind Franklin Institute, Harwell Science and
4 Innovation Campus, Didcot, UK

5 *Corresponding author: Michele Darrow; michele.darrow@rfi.ac.uk

7 Abstract

Segmentation of biological images identifies regions of an image which correspond to
specific features of interest, which can be analysed quantitatively to answer biological
questions. This task has long been a barrier to conducting large-scale biological imaging
studies as it is time- and labour-intensive. Modern artificial intelligence segmentation tools
can automate this process, but require high quality segmentation data for training, which is
challenging to acquire. Biological segmentation data has been produced for many years, but
this data is not often reused to develop new tools as it is hard to find, access, and use.
Recent disparate efforts (Iudin, et al., 2023; Xu, et al., 2021; Vogelstein, et al., 2018; Ermel,
et al., 2024) have been made to facilitate deposition and re-use of these valuable datasets,
but more work is needed to increase re-usability. In this work, we review the current state of
publicly available annotation and segmentation datasets and make specific
recommendations to increase re-usability following FAIR (findable, accessible,
interoperable, re-usable) principles (Wilkinson, et al., 2016) for the future.

Keywords

Segmentation; annotation; volume electron microscopy; electron tomography; X-ray
tomography

Introduction

Segmentation is a required process for many volumetric biomedical imaging experiments. It is the step where scientists derive either illustrative examples or quantitative information which allows them to address the scientific question(s) at hand. For example, segmentation has been used to understand many aspects of biomedical health research and basic science research, from the cellular composition of the blood-nerve barrier (Malong, et al., 2023), the structure of the vascular network in equine placenta (Laundon, et al., 2024), the effects of SARS-CoV-2 viral infection (Mendonça, et al., 2021), and even as a tool for development of novel imaging techniques (Dumoux, et al., 2023). Across medical and basic science research, and imaging modalities from electrons (vEM, SEM, TEM) to X-rays (SXT, microCT), segmentation is a crucial step.

Until recently, segmentation was completed manually by tracing the outlines of the features of interest on all or many slices through a 3D dataset. With the advent of machine learning, this task can now be semi-automated using shallow (Luengo, et al., 2017) and deep learning approaches (Belevich, Joensuu, Kumar, Vihinen, & Jokitalo, 2016; Conrad & Narayan, 2023; Pennington, et al., 2022; Arganda-Carreras, et al., 2017; Berg, et al., 2019; Thermo Fisher Scientific) using foundational models (Conrad & Narayan, 2023; Narayan & Conrad, 2022). Even with these advances, segmentation still requires varying amounts of manual annotation to provide training data for machine learning approaches to learn from. In most cases, machine learning segmentations also require some level of manual correction to provide a high-quality output that can be used to derive meaning. Because of this level of manual intervention, high-quality segmentations are a scarce and valuable resource (Czymmek, et al., 2024). However, as with many scientific endeavours, the details associated with how the segmentations are produced are vital to downstream re-use.

There are a small number of options for public deposition of segmentations. The standard option in the vEM and X-ray imaging fields is EMPIAR (Electron Microscopy Public Image Archive) (Iudin, et al., 2023) which was created in 2013 to address the need for a raw/image data repository in the fields of cryo-electron microscopy and tomography (cryoEM and cryoET), though it has now expanded its remit to include vEM and X-ray imaging. As of writing, EMPIAR has released just shy of 5 PB of data across >1,800 entries. While it has the distinction of being the first community repository for segmentation data, its utility has been limited by the lack of standardised metadata collection during deposition and its broad purview. Prior to EMPIAR, the Electron Microscopy Data Bank (EMDB) (The wwPDB Consortium, 2024) acted as a repository for electron microscopy output maps, including in a small number of cases, segmentation maps uploaded as accompanying datasets. Smaller, more bespoke repositories have been created for specific purposes. For example,

OpenOrganelle (Xu, et al., 2021; Heinrich, et al., 2021) was created to host the vEM datasets
and accompanying segmentations specifically associated with the enhanced focused ion
beam SEM (eFIB-SEM) technology that was developed at HHMI Janelia (Xu, et al., 2017).
Similarly, some research groups with a novel technique (nanotomy.org; (Pirozzi,
Hoogenboom, & Giepmans, 2018)) have generated their own open repositories for storage
of data and associated metadata. Some segmentation data and metadata can also be found
on open generic repositories like Zenodo (European Organization For Nuclear Research &
OpenAIRE, 2013) or associated with public challenges such as on Kaggle (Kaggle, n.d.).
Finally, most recently, the Chan Zuckerberg Imaging Institute has entered this area with the
CryoET Data Portal (Ermel, et al., 2024), which at time of writing, contains ~300 entries
(datasets) mainly focused on cryoET data with annotated particle locations. 14 of these
depositions have "ground truth" annotations, nine of which are also found on EMPIAR.
Importantly, the depositions have a standardised metadata structure, naming conventions,
application programming interface (API), and detailed curation of metadata.

Here, we undertook a landscape review of the publicly available segmentation data and
associated metadata to understand and report on gaps and barriers within the current
system, as well as recommendations to address barriers to re-use.

Results

Datasets associated with electron and X-ray imaging segmentations (image, training, and label data) were searched for in common repositories (EMPIAR, EMDB, OpenOrganelle). Publications associated with segmentation were searched for using PubMed and a representative sub-sample was selected (see Methods). Searches were limited to entries from 2014 – 2024, and across all searches a total of 227 unique publications were selected. These entries were then assessed for various characteristics associated with segmentation datasets, metadata and re-use. These characteristics included:

- Type of study: biological (answering a biological question), method (sample preparation or image acquisition), software (software tool for processing the image data), dataset (describing a useful dataset for the community).
- Purpose of segmentation: Qualitative visualisation, quantitative morphology, proof-of-concept, benchmarking, single particle analysis (SPA) or sub-tomogram averaging (STA).
- Repository where data was deposited to, if at all. Here, we recorded the deposition location of four categories of data: the source data (microscopy images upon which segmentations are based), training data (microscopy images and their labels which were used to train artificial intelligence models), label data (segmentation masks), and code.
- Imaging modality
- File formats for source, training, and label data
- Origin of data, i.e. whether this publication generated new source/raw data or segmentations, and if they were generated elsewhere, where did this data come from
- Segmentation type: semantic or instance
- Segmentation method: manual, semi-automated, automated
- Biological scale and/or tissue

Based on this landscape analysis, we have identified both characteristics associated with data reuse and barriers preventing reuse of published segmentation data according to FAIR principles – scientific data should be findable, accessible, interoperable, and reusable (Wilkinson, et al., 2016).

Findability and accessibility of deposited data

Data cannot be reused unless the data and its associated metadata can be found and accessed. Of the 227 publications surveyed, 64.4% of source data, 76.3% of training data, 82.5% of label data, and 55.6% of code was either not deposited, available only on request, or not available anymore (Figure 1). In some cases, data was previously deposited in locations that were no longer available, e.g., at websites that no longer exist. Some data was deposited was in locations that were accessible, but difficult to find. For example, the reader would need to search through citation chains or using keywords online to find the correct dataset. Amongst the findable and accessible locations, the most common location for image data and label data to be deposited was in field-specific databases such as EMPIAR (Iudin, et al., 2023), EMDB (The wwPDB Consortium, 2024), or Neurodata (Vogelstein, et al., 2018). Another popular location is general databases such as Dryad (Dryad, n.d.) or Zenodo (European Organization For Nuclear Research & OpenAIRE, 2013); which also function similarly to field-specific databases, but due to their wide scope are much more difficult to search unless already aware of the existence of a specific entry.

Reproducibility of scientific studies is important to ensure the integrity of the biological conclusions that we draw from our research. This is especially important as we move towards artificial intelligence approaches which are not fully explainable – in these cases it is crucial that the data and procedures for training models are made available for scrutiny to avoid bias. Unfortunately, this was not the case for many of the publications that were surveyed. Of the 97 publications surveyed which required a model to be trained, training data was unavailable or inaccessible for 74 of them (76.3%). Code for generating semi- or fully automated segmentations was only available in 48.9% of publications surveyed.

Label data, i.e., the segmentation masks that were generated in the publication, was findable and accessible in only 25% of the publications surveyed which generated this data. Quantitative measurements are often taken from the label data to draw biological conclusions, but the label data was not made available in 74 of the 99 publications that did this.

Figure 1: Deposition locations of data from publications surveyed (n=227). Most publications did not deposit their data at all, or deposited in locations which were no longer available, e.g., at defunct institutional repositories. Some of the depositions were accessible but difficult to find, e.g., reader would be required to search for the data separately if the dataset was named but no direct working link was provided. Image data and label data was most likely to be deposited in field-specific databases such as EMPIAR or EMDB, whilst training data (where available) was most commonly available from public challenges. Code was most frequently available from self-maintained websites such as Github repositories. Note that some publications can be counted in multiple categories, e.g., if the publication had training data available online in a public challenge but required a separate search.

Interoperability of deposited data

Integrating data collected from different sources is also challenging due to the variability in file formats and metadata. Source, training, and label data was deposited in 26 different file formats (Figure 2). This variability makes tasks such as combining similar segmentation datasets together more difficult, as customised code is often needed to parse this data into a common format. While many image processing software packages do accept data in different open-source formats, and tools for parsing and converting bioimaging file formats such as Bioformats (Linkert, et al., 2010) exist, this would still be a daunting task. This indicates that the lack of standardisation in file formats still presents a barrier to interoperability of segmentation data.

Metadata was not standardised across the various repositories, creating conflicts when merging data across repositories. In its most extreme cases, the definitions of some types of segmentation data can vary between fields, which could cause datasets to be used inappropriately by researchers unfamiliar with the nuances of different fields (see Discussion). In many cases, metadata was simply missing, making re-use nearly impossible without extensive field-specific knowledge.

Chunked

Figure 2 File formats for source, training, and label data for the surveyed publications (n=227). Note that some publications used multiple file formats for each category and are counted multiple times in this instance. Source, training, and label data was deposited in 26 different file formats. Chunked or pyramidal file formats allow data to be accessed at different resolution levels or region-of-interest sizes easily. Data accessed via an API are typically stored in a chunked format on cloud providers for easy programmatic access. General data formats are often used, with tiff images being the most popular across all data types. Many datasets were also uploaded as zipped files, so the file formats of the actual data were not easily known before downloading the data. Microscopy-specific file formats were quite common, especially the mrc and map formats (which are the same mrcfile format) which together made up 22.3% of image data, 3.1% of training data, and 20%

174 *of label data. Proprietary and other more obscure file formats were more common in training and label datasets than in*
175 *source data.*

Rates of reuse

Rates of data reuse in biological segmentation studies are low. In all publications surveyed,
only 23.3% did not generate new data for their study (Figure 3). Software publications
collected new data for 57.7% of the studies, which is surprisingly high considering that most
software is developed for established use cases, for which segmentation data likely already
exists. Data reuse is more common in connectomics studies, with a slim majority of studies
reusing data rather than collecting new data (55% reused data).

Reused data was most often sourced from other studies, which may be less openly
accessible than data from public repositories as often these studies were conducted by the
same research group, which was the case for 20 of the 23 studies surveyed sourcing data
from other studies. Public data was also commonly used, but public challenges had the
most reuse per dataset. One notable example from the connectomics field is that 10 of the
40 total connectomics publications used data from the ISBI 2012 challenge (Arganda-
Carreras, et al., 2015). However, this data is no longer available at the original website (a
public challenge site), making it no longer findable (Note: it is still available at
https://imagej.net/events/isbi-2012-segmentation-challenge).

Figure 3 Sources of data used in all publications surveyed (n=227), only publications describing a software tool (n=97), and
publications in the connectomics field (n=40). The number of publications in each sub-category of data source is displayed
above the bar. Most publications collected their own data, including when the purpose of the publication was the
description of a software tool. The Connectomics field demonstrated the best rates of re-use with many publications
referencing the data from a public challenge. Note that some papers may be counted multiple times, e.g., a paper
describing a software tool used in connectomics would be counted as a software, connectomics, and in all papers.

Differences between imaging modalities

X-ray micro-computed tomography publications had the lowest rate (5.9%) of data re-use (Figure 4). Room-temperature EM (FIB-SEM, SBF-SEM, EM, ET, ssTEM, ATUM SEM, room-temperature ET, ssSEM) publications had the highest rate of reusing data collected elsewhere, with 35.8% of publications obtaining data from other studies, public data, or public challenges. This high rate of re-use is mainly due to the connectomics field. CryoEM (cryoEM, cryoET, cryoFIB-SEM) publications had a slightly lower rate of reusing data (31.4%).

Across all data types, cryoEM publications were most likely to deposit data in findable and accessible locations such as field-specific databases, general scientific databases or self-maintained websites (Table 1). Room-temperature and cryoEM studies most frequently deposited their image data (image training, and label) into field-specific databases such as EMDB or EMPIAR (Supplementary Figures 1-3). The X-ray publications with image data depositions were evenly spread across field-specific databases, general scientific databases, and self-maintained websites (Supplementary Figure 1).

Figure 4 Rates of data reuse in publications from X-ray (n=101), room-temperature EM (n=94) and cryo-EM (n=31). Note that some publications were counted in several categories if multiple modalities were used.

220
221 *Table 1 Percentage of publications in X-ray (n=101), room-temperature EM (n=94) and cryo-EM (n=31) depositing different types of data in each type of location.*

	Not findable or accessible	Not findable	Findable and accessible
Image			
X-ray	77.3	0.9	21.9
Room-temp EM	38.5	14.8	46.6
CryoEM	34.3	2.9	62.9
Training			
X-ray	82.1	0	17.8
Room-temp EM	62.3	9.1	28.6
CryoEM	66.7	0	33.3
Label			
X-ray	89.3	0	10.8
Room-temp EM	68.8	0.9	32.5
CryoEM	60	0	40
Code			
X-ray	60.9	0	39.1
Room-temp EM	51.9	1.3	46.8
CryoEM	37.5	0	62.5

Discussion

Ontological considerations

Many publications we reviewed were not findable or accessible as they were deposited at defunct URLs, were only available on request, or required researchers to search separately through citations or online to download the data. We found that data was deposited across at least 26 different file formats, and 32 different online repositories, limiting the interoperability of these datasets as significant effort would be required to parse these formats into a single unified database for training segmentation tools. Once found and accessed, we determined that there was considerable variation in the definitions of certain terms such as "reconstruction", "mask", "segmentation", and "ground truth". A consensus or clearer descriptions are required across the breadth of the bioimaging community to ensure that these datasets can be re-used appropriately without misinterpretation. Some recommendations on clearer descriptors of common bioimage data are included in Figure 5.

✓ Source data	✓ Annotation	✓ Segmentation	✓ Particle picks
✓ Image data	✓ Segmentation	✓ Prediction	✗ Segmentation
✗ Reconstruction	✓ Training data	✓ Labels	✗ Mask
	✓ Mask*	✓ Mask*	
	✗ Reconstruction	✗ Reconstruction	
	✗ Ground truth	✗ Ground truth	

* Only if described clearly, e.g., mask of manually annotated mitochondrial membranes

Figure 5 Different common types of bioimage data and recommendations on terms that should and should not be used for clear descriptions.

The term 'reconstruction' is used often in bioimage research. It is colloquially used to mean any of the following:

- A 3D volume created from 2D images
- An average of multiple 2D sub-images or 3D sub-volumes into a 3D representation of a feature of interest
- A segmentation from a 2D or 3D volume

These various uses of the term 'reconstruction' lead to confusion, and arguably none are
needed, as the better descriptions for the above examples would be tomogram/3D image
data, averaged feature and segmentation respectively.

The term 'mask' can similarly cause confusion as it is used to describe partial annotations
created as training data, predictions from semi- or automated approaches and proof-read
outputs. To a non-expert, each of these binary images may be present with little or no
associated description in a single repository entry. There may even be multiple labels
present in the same file with no associated metadata to describe the objects being labelled;
or when these descriptions are present, they are often shorthand or non-standardised
vocabulary (e.g., "mito" or "endo" to describe mitochondria or endosomes respectively).

The term 'segmentation' is canonically used to describe the pixel- or voxel-wise labelling of
features within an image, but recently in the cryoET field has also begun to be used to
describe the practice of re-inserting an object's average back into a 3D volume based on the
orientations and locations where individual objects were found prior to averaging. This new
practice is subtly different in a meaningful way, especially to non-experts, as the re-inserted
averaged object may not actually be present at that location, may not be found in the
orientation it is displayed in and may not represent the actual density present in the image(s).
A more appropriate term for this use-case would be averaged re-insertion annotation
(described by a set of coordinates and a vector) to distinguish between original particle
annotation. In this way, the object's locations and orientations can be provided alongside of
the single average that represents all members of the group, reducing the computational
storage burden. Importantly, we are not arguing that the practice of re-inserting averaged
objects be stopped, just that it is better described and differentiated from the canonical use
of the term 'segmentation'.

The issue of ground truth is more insidious; in the bioimaging field, it is often used to
describe expert annotation/segmentation. However, the term ground truth indicates that it
is infallibly accurate because the truth is known (e.g., from a simulation). When the term
"ground truth" is used to describe imperfect, biased, manual annotation/segmentation it
can lead to interpretation issues where experts disagree or where automated/semi-
automated strategies are erroneously discounted because they differ from the expert
annotation (Hecksel, et al., 2016). The best term to use here is either manual
annotation/segmentation or expert annotation/segmentation.

Volumetric imaging is often a long process of sample preparation, data collection and data
processing/analysis. Choosing to use careful language when describing this process in
publications, repositories and code gives the best chance of both shared understanding and
re-use, especially beyond the immediate research field.

The need for metadata

Segmentation specific metadata has lagged behind metadata associated with image acquisition, but it is crucially important to capture metadata from what is often the last step of the process, where the most energy has been expended, to reduce this burden in future. On a basic level, information as simplistic as what the feature of interest is (ideally linked to standard tissue and cellular ontologies) and whether it is described by zeros or ones (or something else) in the associated segmentation file would be a great place to start.

A secondary step would be to capture metadata associated with the purpose and quality of a segmentation and the process by which a segmentation was generated. There will likely be quality differences between segmentations generated for exclusively visualisation purposes versus those generated for quantitative analysis. And it is also likely that those segmentations which have undergone proofreading post-automated segmentation or by a second expert will be of higher quality than those which have not.

Beyond the basics, enhanced, automated metadata capture and search capabilities would help developers find suitable datasets for their use case and determine how much (if any) manual curation would be required to bring segmentation data to the required standard for their study. This metadata could include the number and size of the feature being segmented relative to the image, or whether the segmentation was verified by a correlative imaging approach (e.g., fluorescence to confirm location of a feature of interest in EM).

Specific recommendations

Action is needed at different levels to work towards FAIR deposition of segmentation data in the bioimaging community (Figure 6).

As an individual researcher please deposit your data, training data, label data and code. This includes segmentations that were done for visualisation purposes (e.g., show that subcellular organelles were visible in the images), and especially segmentations which formed the basis of quantitative conclusions (e.g., count and measure volume of mitochondria in images). Choose a field-specific database that provides a permanent DOI for your data; avoid institutional or personal repositories or those which are not permanent. When you are writing your manuscript and depositing your data, describe it clearly and unambiguously – consider the next researcher who will be tasked with attempting to reuse your data. When reviewing manuscripts, insist on the data, training data, label data and code being deposited in a field-specific database before acceptance.

As a community, we must standardise the data types and descriptions, file formats and metadata associated with our data, training data and label data. This is hard, but it is important. We must also move towards chunked file formats (e.g., OME-Zarr (Moore, et al.,

2023)) will allow for online viewing and processing of large data. Unsurprisingly, public
challenges play a large and unique role to move the field forward; they should be
encouraged and new performance metrics should be developed to understand the outputs.
We must work with our industry partners and software developers to ensure appropriate
metadata is generated instead of black-box tools and to automate the collation and
eventual deposition of this metadata. As a community we must also reward deposition of
data similarly to how we reward manuscript publication or funding acquisition.

As a repository, please provide tools for programmatic searching, access, uploading, and
processing of data, including the adoption of chunked file formats. This will enable
developers and researchers to understand the data before expending the effort and
resources to transfer a copy of it to local storage, or better yet, alleviate this need entirely.
And finally, we need to consider AI within the context of volumetric imaging and get our data
ready. We should ensure there is a place for standard samples and synthetic data alongside
of the "real" data. This includes understanding the quality of the data using quantitative
metrics and the deposition of data of variable quality – not just the best data.

 Individuals

1. Deposit segmentations in a database used in the field, with a permanent DOI
2. Describe data unambiguously (e.g., "mask of manually corrected predictions for cell membrane" vs "mask")
3. Avoid only uploading to personal or institutional repositories unless long-term storage plans are in place.

 Community

1. Work towards standardisation of:
   - Data types and descriptors
   - File formats, ideally chunked formats for modern online viewers and processing
   - Metadata structure
   - Performance metrics
2. Public challenges with clear scope and performance metrics
3. Work with industry partners and software developers towards automated collation and deposition of metadata.
4. Reward data deposition similarly to publications or funding acquisition.

 Repositories

1. Develop tools for programmatic searching, access, uploading, and processing.
2. Online viewers so data can be examined without downloading (requires use of chunked formats)
3. Databases need to be AI ready
   - Need quantitative quality metrics and data of varying quality – not just the best data
   - Real samples, standard samples, synthetic data
   - Structured metadata

334 *Figure 6 Specific recommendations for action at different levels to improve FAIR deposition of segmentation data in*
335 *bioimaging.*

Conclusion

Data deposition rates are disturbingly low, especially data from steps beyond the initial imaging data. Re-use of data is essential for many purposes, not least the development of segmentation software tools, particularly those using artificial intelligence techniques requiring large amounts of training data. Clear, unambiguous descriptions of data and metadata will democratise the development of solutions, broadening beyond the original field and scientists associated with large monetary investments in microscopes and associated kit. Changes are needed at all levels from individual researchers, the bioimaging community, and the repositories themselves; but together we can ensure precious data is captured for re-use and we are prepared to take advantage of future advancements in AI.

Methods

A collection of publicly available segmentation and annotation datasets for 3-D volumetric electron microscopy and associated metadata was assembled from searches in the EMDB, EMPIAR, and Open Organelle databases, and a literature search with Pubmed from 2012-2023. Characteristics about these datasets were collected and trends over time were investigated, e.g., the purpose of the segmentations, data formats, biological feature type and size scale, imaging modality, and others.

Literature searches

Searches were conducted on Pubmed and aggregated. Duplicates were removed and 100
publications were selected randomly from the remaining 2125 publications, in proportion to
the relative number of publications for each year from 2014-2024. This sampling strategy
meant that publication years with fewer overall publications matching the search terms had
fewer publications added to the final sample ensuring representation of overall trends in the
fields and across time were preserved. Selection was performed by assigning every
publication a random ID number, the search results were then filtered by year of publication,
and the publications were sorted in ascending order of the randomised ID. Before a paper
was added to the sample pool, it was reviewed more closely to determine if the paper was
relevant to the bioimaging community and questions at hand (i.e., delineation of biological
features of interest from an electron microscopy image). This was repeated until the total
number of publications for each year were added to the sample pool to reflect the proportion
of publications matching the search terms per year.

The specific searches used to represent the volume electron microscopy field were:

- "(("segmentation") OR ("annotation")) AND ((SBF SEM) OR (SBEM) OR (serial block
face scanning electron microscopy))"
- "(("segmentation") OR ("annotation")) AND ((FIB SEM) OR (FIB-SEM) OR (FIBSEM) OR
(focused ion beam scanning electron microscopy))"
- "((segmentation) OR (annotation)) AND ((electron microscopy) OR (EM))"
- "(("segmentation") OR ("annotation")) AND (electron tomography)"
- "(("segmentation") OR ("annotation")) AND ((ssTEM) OR (serial section TEM))"

The Pubmed search was repeated for the X-ray imaging field and 100 publications were
selected randomly from the 5651 publications, in proportion to the relative number of
publications for each year from 2014-2024 (as described above). The specific search used
to represent the X-ray imaging field was:

- "(("segmentation") OR ("annotation")) AND ((X-ray microscopy) OR (X-ray microCT)
OR (X-ray tomography) OR (X-ray micro-computed tomography))"

EMDB and EMPIAR were searched using the following query:

- "segmentation_filename:[* TO *] AND
structure_determination_method:tomography", "segmentation", "segmentations",
"annotation", and "annotations".

The OpenOrganelle database was manually searched for datasets that included image data
and an annotation or segmentation.

The resultant search results from EMPIAR, EMDB, and OpenOrganelle were added to those
results from the PubMed search and duplicates were again removed based on DOI. This
enriched the sample pool ensuring questions related to current trends/habits of data
deposition could be captured. The results were organised by publication, i.e. each
publication was a single record regardless of how many datasets were uploaded. The 231
publications were reviewed and information about the datasets generated from the
publications were recorded. These characteristics included:

• the study type (biological investigation, new imaging or sample preparation method,
dataset, or software paper)
• segmentation use (proof-of-concept, qualitative visualisation, quantitative
morphometry, single-particle analysis or sub-tomogram averaging)
• where the image data was deposited to (if at all)
• where training data was deposited to (if at all, or required)
• where label data was deposited to (if at all)
• where code for generating the segmentations was deposited to (if at all, or required)
• imaging modality
• file formats
• source of the datasets (collected for that publication, reused from elsewhere,
publicly available)
• Segmentation type (semantic or instance)
• Segmentation method (automated, semi-automated or manual)
• Biological scale (tissue, cellular, sub-cellular)

414 Data and Code Availability Statement:

419 Competing Interests Statement:

420 The authors declare that none of the authors have competing financial or non-financial
421 interests.

422 Author Contribution Statement:

423 MCD conceived of and supervised the project. EMLH and MCD defined the search strategy
424 and parameters. EMLH and DL collected the data. EMLH performed the analysis and
425 prepared the figures. EMLH and MCD wrote the manuscript. All authors reviewed the
426 manuscript prior to submission.

Acknowledgements:

429 The authors wish to acknowledge Wellcome Trust funding (Electrifying Life Sciences
430 220526/Z/20/Z)

References

Arganda-Carreras, I., Kaynig, V., Rueden, C., Eliceiri, K. W., Schindelin, J., Cardona, A., & Seung, H. S. (2017). Trainable Weka Segmentation: a machine learning tool for microscopy pixel classification. *Bioinformatics, 33*(15), 2424–2426. doi:10.1093/bioinformatics/btx180

Arganda-Carreras, I., Turaga, S. C., Berger, D. R., Cireşan, D., Giusti, A., Gambardella, L. M., . . . Seung, H. S. (2015). Crowdsourcing the creation of image segmentation algorithms for connectomics. *Frontiers in Neuroanatomy, 9*(142). doi:10.3389/fnana.2015.00142

Belevich, I., Joensuu, M., Kumar, D., Vihinen, H., & Jokitalo, E. (2016). Microscopy Image Browser: A Platform for Segmentation and Analysis of Multidimensional Datasets. *PLOS Biology, 14*(1), e1002340. doi:10.1371/journal.pbio.1002340

Berg, S., Kutra, D., Kroeger, T., Straehle, C. N., Kausler, B. X., Haubold, C., . . . Kreshuk, A. (2019). ilastik: interactive machine learning for (bio)image analysis. *Nature Methods, 16*, 1226–1232. doi:10.1038/s41592-019-0582-9

Chan Zuckerberg Imaging Institute. (n.d.). *CryoET Data Portal*. Retrieved from https://cryoetdataportal.czscience.com/

Conrad, R., & Narayan, K. (2023). Instance segmentation of mitochondria in electron microscopy images with a generalist deep learning model trained on a diverse dataset. *Cell Systems, 14*(1), 58-71. doi:10.1016/j.cels.2022.12.006

Czymmek, K. J., Belevich, I., Bischof, J., Mathur, A., Collinson, L., & Jokitalo, E. (2024). Accelerating data sharing and reuse in volume electron microscopy. *Nature Cell Biology, 26*, 498-503. doi:doi.org/10.1038/s41556-024-01381-3

Dryad. (n.d.). Retrieved from https://datadryad.org/stash

Ermel, U., Cheng, A., Ni, J., Gadling, J., Venkatakrishnan, M., Evans, K., . . . Carragher, B. (2024). A data portal for providing standardized annotations for cryo-electron tomography. *Nature Methods*. doi:https://doi.org/10.1038/s41592-024-02477-2

European Organization For Nuclear Research, & OpenAIRE. (2013). Zenodo. CERN. doi:10.25495/7GXK-RD71

Hecksel, C. W., Darrow, M. C., Dai, W., Galaz-Montoya, J. G., Chin, J. A., Mitchell, P. G., . . . Chiu, W. (2016). Quantifying Variability of Manual Annotation in Cryo-Electron

Tomograms. *Microscopy and Microanalysis, 22*(3), 487-496. doi:10.1017/S1431927616000799

Heinrich, L., Bennett, D., Ackerman, D., Park, W., Bogovic, J., Eckstein, N., . . . COSEM Project Team. (2021). Whole-cell organelle segmentation in volume electron microscopy. *Nature, 599*, 141-146. doi:10.1038/s41586-021-03977-3

Iudin, A., Korir, P. K., Somasundharam, S., Weyand, S., Cattavitello, C., Fonseca, N., . . . Patwardhan, A. (2023). EMPIAR: the Electron Microscopy Public Image Archive. *Nucleic Acids Research, 51*(D1), D1503-D1511. doi:doi.org/10.1093/nar/gkac1062

Kaggle. (n.d.). *Kaggle: Your Machine Learning and Data Science Community*. Retrieved from https://www.kaggle.com/

Linkert, M., Rueden, C. T., Allan, C., Burel, J.-M., Moore, W., Patterson , A., . . . Swedlow, J. R. (2010). Metadata matters: access to image data in the real world. *The Journal of Cell Biology, 189*(5), 777-782. doi:10.1083/jcb.201004104

Luengo, I., Darrow, M. C., Spink, M. C., Sun, Y., Dai, W., He, C. Y., . . . French, A. P. (2017). SuRVoS: Super-Region Volume Segmentation workbench. *Journal of Structural Biology, 198*(1), 43-53. doi:10.1016/j.jsb.2017.02.007

Moore, J., Basurto-Lozada, D., Besson, S., Bogovic, J., Bragantini, J., Brown, E. M., . . . Swedlow, J. R. (2023). OME-Zarr: a cloud-optimized bioimaging file format with international community support. *Histochem Cell Biol, 160*, 223-251. doi:10.1007/s00418-023-02209-1

Narayan, K., & Conrad, R. W. (2022). Seven benchmark datasets of instance segmentation of mitochondria: 6 diverse volume EM + 1 TEM (100 images) datasets. doi:10.6019/EMPIAR-10982

Pennington, A., King, O. N., Tun, W., Ho, E. M., Luengo, I., Darrow, M. C., & Basham, M. (2022). SuRVoS 2: Accelerating Annotation and Segmentation for Large Volumetric Bioimage Workflows Across Modalities and Scales. *Frontiers in Cell and Developmental Biology, 10*, 842342. doi:10.3389/fcell.2022.842342

Pirozzi, N. M., Hoogenboom, J. P., & Giepmans, B. N. (2018). ColorEM: analytical electron microscopy for element-guided identification and imaging of the building blocks of life. *Histochemistry and Cell Biology, 150*, 509-520. doi:10.1007/s00418-018-1707-4

The wwPDB Consortium. (2024). EMDB—the Electron Microscopy Data Bank. *Nucleic Acids Research, 52*(D1), D456-D465. doi:10.1093/nar/gkad1019

Thermo Fisher Scientific. (n.d.). Avizo.

Vogelstein, J. T., Perlman, E., Falk, B., Baden, A., Roncal, W. G., Chandrashekhar, V., . . .
Burns, R. (2018). A community-developed open-source computational ecosystem
for big neuro data. *Nature Methods, 15*, 846-847. doi:10.1038/s41592-018-0181-1

Wilkinson, M., Dumontier, M., Aalbersberg, I., Appleton, G., Axton, M., Baak, A., . . . Mons, B.
(2016). The FAIR Guiding Principles for scientific data management and stewardship.
Sci Data, 3(160018), Wilkinson, M., Dumontier, M., Aalbersberg, I. et al.
doi:https://doi.org/10.1038/sdata.2016.18

Xu, C. S., Hayworth, K. J., Lu, Z., Grob, P., Hassan, A. M., Garcia-Cerdán, J. G., . . . Hess, H.
F. (2017). Enhanced FIB-SEM systems for large-volume 3D imaging. *eLife, 6*, e25916.
doi:10.7554/eLife.25916

Xu, C. S., Pang, S., Shtengel, G., Müller, A., Ritter, A. T., Hoffman, H. K., . . . Hess, H. F. (2021).
An open-access volume electron microscopy atlas of whole cells and tissues. *Nature,*
599, 147-151. doi:10.1038/s41586-021-03992-4

Supplementary Information

513   *Supplemental Figure 1 Deposition locations of image training, label data and code for X-ray publications (n=101).*

Not findable or accessible

	Raw	Training	Label	Code
Not available anymore	2.2%, 3	1.3%, 1	1.8%, 2	3.8%, 3
Not deposited	36.3%, 49	61.0%, 47	67.0%, 75	48.1%, 38

Not findable

	Raw	Training	Label	Code
Requires separate search	12.6%, 17	7.8%, 6	0.9%, 1	
Commercial cloud	0.7%, 1	1.3%, 1		
References other paper	1.5%, 2			1.3%, 1

Findable and accessible

	Raw	Training	Label	Code
Field-specific database	20.7%, 28	6.5%, 5	16.1%, 18	
Public challenge	12.6%, 17	11.7%, 9	0.9%, 1	
General scientific database	5.9%, 8	3.9%, 3	4.5%, 5	3.8%, 3
Self-maintained website	7.4%, 10	6.5%, 5	5.4%, 6	39.2%, 31
DIY			2.7%, 3	
Supplementary Info			0.9%, 1	1.3%, 1
In other software				2.5%, 2

515 *Supplemental Figure 2 Deposition locations of image training, label data and code for room-temperature EM publications*
516 *(n=94).*

Not findable or accessible

Not findable

Findable and accessible

518 *Supplemental Figure 3 Deposition locations of image training, label data and code for cryo-EM publications (n=31).*

519