Highlights

Fast simulation of identity-by-descent segments

Seth D. Temple, Sharon R. Browning, Elizabeth A. Thompson

- We develop an efficient algorithm to simulate identity-by-descent segments around a locus. We measure that our algorithm can simulate long identity-by-descents for tens of thousands of individuals within one minute.

- We provide probabilistic arguments supporting an average runtime that scales approximately linearly for sample sizes smaller than ten thousand.

- We compare average runtimes to simulate identity-by-descent segments between our specialized algorithm versus more general coalescent frameworks.

Fast simulation of identity-by-descent segments

Seth D. Temple[a,b,c,*], Sharon R. Browning[d], Elizabeth A. Thompson[a]

[a]*Department of Statistics, University of Washington, Seattle, Washington, USA*
[b]*Department of Statistics, University of Michigan, Ann Arbor, Michigan, USA*
[c]*Michigan Institute for Data Science, University of Michigan, Ann Arbor, Michigan, USA*
[d]*Department of Biostatistics, University of Washington, Seattle, Washington, USA*

Abstract

The worst-case runtime complexity to simulate identity-by-descent segments is quadratic in sample size. We propose two main techniques to reduce the compute time, which are motivated by coalescent and recombination processes. We observe average runtimes to simulate detectable IBD segments around a locus that scale approximately linearly in sample size and take a couple of seconds for sample sizes less than ten thousand. In contrast, we find that existing methods to simulate IBD segments take minutes to hours for sample sizes exceeding a few thousand. When using IBD segments to study recent positive selection around a locus, our efficient algorithm makes feasible statistical inferences that would be otherwise intractable.

Keywords: identity-by-descent, coalescent, computational runtime

*Corresponding author
Email address:* sethtem@umich.edu (Seth D. Temple)

December 14, 2024

1. Introduction

Simulation is a powerful tool in population genetics to forecast the genetic impact of evolutionary scenarios, perform statistical inference on models and their parameters, and develop and evaluate new methods [29, 57]. There are two main frameworks for population genetics simulations, each having its own use cases, advantages, and disadvantages. Forward simulation models the dynamics of entire populations over time regarding individuals and their interactions [25]. This flexible approach can incorporate complex dynamics of selection, migration, and spatial context, among other features, at the cost of additional computation. Backward simulation models the genealogy of present-day samples strictly through their common ancestors and is less computationally intensive [29].

The speed of backward simulation is in large part due to coalescent theory [35, 36], which approximates the Wright-Fisher (WF) process [56] when the sample size is much smaller than the population size. The Kingman coalescent has been extended to address examples of migration [42], recombination [30, 32], selection [32, 33], and demography [28]. With recombination, the model becomes a sequence of correlated coalescent trees called the ancestral recombination graph (ARG). In recent years, numerous coalescent methods have been developed to simulate polymorphism data over large genomic regions efficiently [18, 31, 34], having randomly placed mutations on tree branches at a fixed genome-wide rate. The `msprime` software is a popular and robust option for backward simulation that scales to entire chromosomes and thousands of individuals [2]. Hybrid frameworks with forward simulations [26] and standards set for species-specific simulations [1, 38] have contributed to its widespread adoption.

Placing mutations on tree branches has linear complexity in sample size, which means analyses focusing on summary statistics of polymorphism data can be runtime inexpensive even in large samples. On the other hand, deriving the pairwise relationships between haplotypes is difficult for large sample sizes because the total number of computations scales quadratically in sample size. To be precise, two individuals share a haplotype segment identical-by-descent (IBD) if they inherit it from the same common ancestor. msprime has a feature to access IBD segments from the tree sequence, but its documentation warns that deriving and storing the IBD segments requires a lot of time and memory [2]. Another coalescent method ARGON simulates IBD segments as a feature within a much broader ARG-inference program [43]. These methods are the two current options to simulate IBD segments genome-wide in modestly sized samples. The runtime to simulate IBD segments with these programs has not been extensively benchmarked.

Long IBD segments can be informative about recent demographic changes [6, 10, 12, 44], recent positive selection [7, 52], population-specific recombination rates [58], mutation rates [53], allelic conversions [8], rare variant association studies [9, 14], and close familial relatedness [59], whereas summary statistics like the fixation index F_{ST} [55] and Tajima's D [49] or models like the sequentially Markovian coalescent (SMC) [39], and its extensions [45], concern population divergences and old selection events [49, 55], among other things. Methods using IBD segments thus serve as an important complementary approach to summary statistics and coalescent-based methods.

Distinguishing between alleles that are identical-by-state versus those that are identical-by-descent from a common ancestor can be challenging. Only those haplotypes extending over multiple centiMorgans, a unit of genetic distance to be de-

fined in Section 2, can be detected as IBD with high accuracy [20, 40, 41, 46, 60]. We refer to IBD segments longer than a fixed Morgans threshold as "detectable", where a user-defined threshold can depend on the dataset, the IBD segment detection method, and the tolerance to detection inaccuracies. Exceptionally long IBD segments are rare to observe outside of family studies, meaning that large sample sizes are required to observe enough for IBD-based analyses in outbred population studies.

Some methods require IBD data for the entire chromosomes [6, 44, 50, 58, 59], which simulators like `msprime` [2] and `ARGON` [43] are suited for. Other statistical inferences concern estimator consistency [52], uncertainty quantification [52], and convergence to an asymptotic distribution [51] around a single locus. Validating such theoretical results involves enormous simulations, for which `msprime` and `ARGON` are less suited.

In this work, we propose an algorithm to simulate IBD segments overlapping a focal location that is fast enough to validate asymptotic properties like consistency, confidence interval coverage, and weak convergence [13]. We modify a naive approach [52], and then we argue that our modified approach should drastically decrease runtime with high probability. We demonstrate in some simulation examples that the modified algorithm's average runtime scales approximately linearly with sample size, not quadratically.

2. Preliminary material

Backward simulation of IBD segment lengths overlapping a focal location involves two waiting time distributions: the time until a common ancestor and the genetic length until a crossover. Figure 1 illustrates the coalescent and recombi-

nation processes. Here, we formally define a parametric model for IBD segments overlapping a specific locus in terms of these processes.

2.1. The time until a common ancestor

Let n be the haploid sample size, $k \leq n$ the size of a subsample, $N(t)$ the population size t generations ago. Unless otherwise specified, time $t \geq 0$ always refers to time backward from the present day. For constant population size, note that $N = N(t)$ for all t. In the discrete-time Wright-Fisher (WF) process, each haploid has a haploid ancestor in the previous generation. If haploids have the same haploid ancestor, their lineages join.

Let the random variable T_k denote the time until a common ancestor is reached for any two of k haploids. The random variable $T_{n:k}^{+} := \sum_{l=k}^{n} T_l$ is the time until $n - k + 1$ coalescent events. The time to the most recent common ancestor (TMRCA) of the sample is $T_{n:2}^{+}$. The probability that the time until the most recent common ancestor of two specific haploids is

$$P(T_2 = t) = \prod_{\tau=1}^{t-1} \left(1 - \frac{1}{N(\tau)} \right) \frac{1}{N(t)}, \tag{1}$$

where $1/N(\tau)$ is the probability that a haploid has the same haploid parent as the other haploid at generation τ. The approximate probability that the time until a common ancestor is reached for any two of k haploids is

$$P(T_k = t \mid T_{n:k+1}^{+} = t_0) = \prod_{\tau=t_0+1}^{t-1} \left(1 - \frac{\binom{k}{2}}{N(\tau)} \right) \frac{\binom{k}{2}}{N(t)} \tag{2}$$

when k is much smaller than $\min_t N(t)$ [28]. The geometric model assumes that multiple coalescent events in a single generation are improbable. Its rate $\binom{k}{2}/N(\tau)$

is the probability that any two of k haploids have the same haploid parent at generation τ.

The Kingman coalescent [36, 35] comes from the continuous time limit of Equations 1 and 2 for large constant population size N. Specifically, T_k converges weakly to Exponential($\binom{k}{2}$) for $k \ll N$, $N \to \infty$, and time is scaled in units of N generations. Henceforth, we consider the positive real-valued T_k in units of N generations. Varying population sizes $N(t)$ are implemented by rescaling time *post-hoc* in a coalescent with constant population size N [28].

2.2. The distance until crossover recombination

The genetic distance between two points is the expected number of crossovers between them in an offspring gamete. This unit of haplotype segment length is the Morgan. Assuming no interference in double-stranded breaks and that crossovers occur randomly and independently, Haldane [22] derives that the genetic distance until crossover recombination is exponentially distributed, with the Poisson process modeling the crossover points along the genome. The number of crossovers between two points is then Poisson distributed with mean equal to the genetic distance between the two points, which leads to the Haldane map function connecting Morgans to the recombination frequency. (The Haldane map function is $\rho = 0.5(1 - \exp(-2d))$, where ρ is the recombination frequency and d is the genetic distance.)

From a fixed location, the Morgan distance until a crossover in one gamete offspring is distributed as Exponential(1). An important property of the exponential random variable is that the minimum of independent exponential random variables is an exponential random variable with a rate that is the sum of the

rates of the independent random variables. Since meioses are independent after t meioses the haplotype segment length to the right of a focal location is distributed as Exponential(t), where t is the rate parameter.

Let a and b be sample haplotypes in the current generation. Define $L_a, R_a \mid t \sim$ Exponential(t) to be sample haplotypes a's recombination endpoints to the left and right of a focal location. Since crossovers to the left and right are independent, the extant width derived from the ancestor at time t is $W_a := L_a + R_a \mid t \sim$ Gamma($2, t$). Because recombination events are independent in the t meioses descending to a and b from their common ancestor, the IBD segments that are shared by a and b are $L_{a,b}, R_{a,b} \mid t \sim$ Exponential($2t$) and $W_{a,b} \mid t \sim$ Gamma($2, 2t$). Under this model, the lengths of IBD segments are thus shorter, with a higher probability the more removed its common ancestor is from the present day. This fact is a key motivation for the fast algorithm we develop.

3. Theory and methods

Based on Sections 2.1 and 2.2, the blueprint to simulate IBD segment lengths around a locus is as follows: 1) simulate a coalescent tree for a sample from a population, 2) draw recombination endpoints to the left and right of a focal point at each coalescent event, and 3) derive from the recombination endpoints the haplotype segment lengths that are shared IBD. The third step involves calculating the minimum lengths to the right and left of a focal point for every pair of haplotypes, which is the computational bottleneck in simulating IBD segment lengths. Making fewer haplotype comparisons, without sacrificing the exactness of simulation, is the way to decrease compute times.

In Algorithm 1, we state the method to simulate long IBD segments around a

single locus. We make four modifications to the naive simulation algorithm, which are designed to reduce compute times when the primary goal is to generate IBD segments longer than some detection threshold. These implementations reduce compute times due to the mathematical properties of the coalescent time and recombination endpoint distributions.

First, whenever there is likely to be more than one coalescent event in a Wright-Fisher (WF) generation, we approximate the sampling of haploid parents as a binomial random variable (Section 3.1). Second, we exchange the Kingman coalescent for the discrete-time WF model once the number of non-coalesced haploids is much smaller than the population sizes. This implementation is similar to the hybrid simulation approach in Bhaskar et al. [4]. Third, we do not consider a sample haplotype for IBD segment calculation at future coalescent events once its haplotype segment length is less than the specified detection threshold, which we refer to as "pruning". In Section 3.2, we elaborate on the rare probability of long haplotype segments in large populations. Fourth, we combine two sample haplotypes for IBD segment calculation at future coalescent events if they share the same left and right recombination endpoints, which we refer to as "merging". In Section 3.3, we derive results concerning the probability of merging. We implement pruning and merging using object-oriented programming.

3.1. Approximating the Wright-Fisher process in large samples

Simulating the Kingman coalescent is much faster than simulating the discrete-time WF process. The accuracy of the Kingman coalescent requires that the sample size is much smaller than the population size. This requirement is so that the probability of there being more than one coalescent event in a generation is

---

Algorithm 1 Efficient simulation of IBD segment lengths

Input: sample size n, population sizes $N(t)$, Morgans threshold w
Output: Detectable IBD segment lengths $\ell_{a,b} \geq w$ for $a, b \in \{1, \ldots, n\}$ and the coalescent times of their common ancestors

1. Initialize recombination endpoints $l_a, r_a = \infty$ for all $a \in \{1, \ldots, n\}$, $k = n$, $t = 1$
2. **Simulate a coalescent tree**
   while $k > 2$
   (a) **if not** $k^3 \ll N(t)^3$ **then**
       i. Draw from Binomial($\binom{k}{2}, N(t)^{-1}$) (or Poisson in the limit)
       ii. Choose $a, b \in \{1, \ldots, n\}$ to coalesce
       iii. Iterate k down by 1
   (b) **else**
       i. Draw a common ancestor from $\{1, \ldots, N(t)\}$ for each $a \in \{1, \ldots, n\}$
       ii. **if** a, b have the same common ancestor, they coalesce, and iterate k down
   (c) Iterate t up by 1
3. **Simulate recombination endpoints**
   Initialize $\tau = 1$
   while $\tau <= t$
   (a) **for** coalescent event at time τ
       i. For each sample j under the subtree, draw $l'_j, r'_j \sim$ Exponential(v_j). **if** w_j is the time of its last interior node, **then** $v_j = \tau - w_j$
          • Update $l_j = \min(l_j, l'_j)$, $r_j = \min(r_j, r'_j)$, and $w_j = \tau$
          • **if** $l_j + r_j < c$, ignore all future updates for j
       ii. For each pair i, j, **if** $l_i = l_j$ and $r_i = r_j$, **then** merge nodes together
   (b) Iterate τ up by 1
   (**Option:** Use the Kingman coalescent if $k \ll N(t)$ for all remaining t.)

---

small. The assumption that the sample size is small relative to the population size can be violated in analyses of human biobanks. Under this violation, the coalescent approximation can deviate significantly from the exact discrete-time WF model [4, 43, 54].

In the following approximations for the sampling of haploid parents at each generation, we suppress the dependence on the generation time t. Let $k := k(t-1)$ be the number of lineages at generation $t-1$. Let $k' := k(t)$ and $N' := N(t)$ be the number of lineages and the population size in the previous generation t. The probability that a parent among $\{1, \ldots, N'\}$ has no children is $(1 - 1/N')^k$. The probability that a parent has at least one child is $1 - (1 - 1/N')^k$. The Taylor series expansion in $1/N'$ about zero is

$$1 - \left(1 - k/N' + \frac{k(k-1)}{2N'^2} - \frac{k(k-1)(k-2)}{6N'^3} \pm \ldots\right). \tag{3}$$

The second order approximation $k/N' - \binom{k}{2} \times N'^{-2}$ is accurate if $k^3 = o(N'^3)$. The expected number of parents in the previous generation t with a child in generation $t-1$ is then

$$\mathbb{E}[k'] \approx N'\left(k/N' - \binom{k}{2} \times N'^{-2}\right) = k - \binom{k}{2} \times N'^{-1}. \tag{4}$$

As an example, consider a sample of twenty thousand haploids whose ancestral population sizes in the recent ten generations are more than two hundred thousand haploids. The second order approximation is accurate for the first ten generations because $k^3 \cdot N^{-3} = 10^{-3}$ when the sample size $k = 2 \cdot 10^4$ is an order of magnitude smaller than the population size $N = 2 \cdot 10^5$. For this choice of k and N', the

expected number of coalescent events per generation is approximately five hundred.

Compared to drawing a parent for each child and then scanning a vector of size k for siblings, simulating the number of coalescent events in one generation from Binomial($\binom{k}{2}, N'^{-1}$) can be an efficient approximation. The last term being subtracted in Equation 4 is equal to the expected value of a Binomial random variable of $\binom{k}{2}$ trials with success probability N'^{-1}. Next, let A_1 and A_2 be the number of children from two specific haploid parents among the N' parents in the previous generation. If A_1 and A_2 are independent, then $P(A_1 = a_1, A_2 = a_2) = P(A_1 = a_1) \times P(A_2 = a_2)$. A_1 and A_2 are not independent, but the difference between the left term $P(A_1 = a_1, A_2 = a_2)$ and the right term $P(A_1 = a_1) \times P(A_2 = a_2)$ can be vanishingly small when N' is large. The probability $P(A_1 = a_1, A_2 = a_2)$ is derived by choosing a_1 among k samples to have the same parent and then choosing a_2 among $k - a_1$ samples to have a same parent distinct from the parent of the first a_1 samples.

$$
\begin{aligned}
& P(A_1 = a_1, A_2 = a_2) - P(A_1 = a_1) \times P(A_2 = a_2) \\
&= \binom{k}{a_1}(N')^{-a_1} \times \binom{k - a_1}{a_2}(N' - 1)^{-a_2} \\
&\quad - \binom{k}{a_1}(N')^{-a_1} \times \binom{k}{a_2}(N')^{-a_2} \\
&\leq \binom{k}{a_1}(N')^{-a_1} \times \binom{k}{a_2}(N')^{-a_2} \\
&= O(k^{a_1 + a_2} \cdot N'^{-(a_1 + a_2)}).
\end{aligned}
\tag{5}
$$

If both A_1 and A_2 have two or more children ($\min(a_1, a_2) \geq 2$), then Equation 5 is $o(1)$ when the second order approximation $k^3 = o(N'^3)$ is accurate.

In Algorithm 1, we assume that all simultaneous coalescent events are the result

₂₂₄ of only two children having the same parent. Bhaskar et al. [4] have shown that the

₂₂₅ majority of simultaneous coalescent events in a generation are of this type. Due

₂₂₆ to the coalescent and WF approximations, our method is not exact with respect

₂₂₇ to the time until a common ancestor.

₂₂₈ *3.2. The probability of detectable haplotype segment lengths*

₂₂₉ Within tens of generations, most haplotype segment lengths are shrunk by

₂₃₀ crossovers to a genetic length less than detection thresholds that are used in IBD-

₂₃₁ based analyses. A Morgans length threshold at least greater than 0.01 is typical

₂₃₂ in applied research [6, 7, 52, 53, 58]. The probabilities of a detectable haplotype

₂₃₃ segment to the right of and overlapping a focal location, R_a and W_a, respectively,

₂₃₄ conditional on coalescent time Nt (in generations), are

$$1 - F_{R_a|t}(w) = \exp(-Ntw), \tag{6}$$

₂₃₅

$$1 - F_{W_a|t}(w) = \exp(-Ntw) + Ntw \cdot \exp(-Ntw). \tag{7}$$

₂₃₆ Figure S1 shows that the upper tail probabilities of R_a and W_a are decreasing ex-

₂₃₇ ponentially over Nt generations. The probabilities of haplotype segment lengths

₂₃₈ greater than 0.01 can be far from zero when the haplotype is descendant from an

₂₃₉ ancestor within the last 100 generations. The probabilities of haplotype segments

₂₄₀ lengths greater than 0.02 are nearly zero when they are descendant from an an-

₂₄₁ cestor more than 300 generations ago. (But exponential random variables have

₂₄₂ heavy upper tail probabilities, so, in large samples, we may detect some long IBD

₂₄₃ segments descendant from ancestors older than 300 generations.)

₂₄₄ For large populations, the coalescent times of ancestral lineages can be much

greater than 500 generations. The expected time of the $(n - k + 1)^{\text{th}}$ coalescent event can be derived as:

$$
\begin{aligned}
\mathbb{E}[T_{n:k}^+] = \sum_{l=k}^{n} \mathbb{E}[T_l] &= \sum_{l=k}^{n} \binom{l}{2}^{-1} \\
&= 2 \times \sum_{l=k}^{n} \left(\frac{1}{l-1} - \frac{1}{l} \right) \\
&= 2 \times ((k-1)^{-1} - n^{-1}),
\end{aligned}
\tag{8}
$$

where $\binom{l}{2}$ is the rate parameter for the time until a common ancestor is reached for any two of l haploids. For $N = 10{,}000$ and $n \to \infty$, the expected coalescent time $\mathbb{E}[T_{n:40}^+]$ is 512.82 generations. For $N = 100{,}000$ and $n \to \infty$, the expected coalescent time $\mathbb{E}[T_{n:400}]$ is 501.25. If many recombination endpoint comparisons happen at the coalescence of common ancestors older than five hundred generations ago, many haplotypes can be pruned ahead of time. The pruning technique does not compromise the exactness of simulating IBD segment detectable beyond a length threshold.

3.3. The probability that recombination endpoints are shared between haplotypes

At some point in the past, two sample haplotypes may share the same recombination endpoints to the left and right of a fixed location. Without loss of generality, let haplotypes a and b coalesce to their common ancestor c at time u, and let haplotypes c and d coalesce to their common ancestor e at time $u + v$. Figures S2 and S3 illustrate the coalescent tree in this scenario. Observe that the recombination endpoints to the right $R_{a,c}, R_{b,c} \sim \text{Exponential}(u)$ and $R_{c,e} \sim \text{Exponential}(v)$.

The merging step in Algorithm 1 serves to avoid comparing both the endpoints of a and b with d when a and b have the same endpoints at time $u + v$. Specifically,

if a and b's shared recombination endpoint $R_{c,e}$ is smaller than their separate endpoints $R_{a,c}$ and $R_{b,c}$, we can henceforth treat them as the same haplotype without loss of information (Figure S2). If either of the individual lengths $R_{a,c}$ or $R_{b,c}$ are smaller than the common length $R_{c,e}$, we cannot merge the haplotypes without losing information (Figure S3).

The probability that haplotypes a and b have the same recombination endpoint at time $u + v$ is $v(2u + v)^{-1}$. We derive a result that replaces arbitrary coalescent times u and $u + v$ with double the expected times after the $(n - k)^{\text{th}}$ and $(n - j)^{\text{th}}$ coalescent events, respectively.

Proposition 3.1. *Let* $u/2 = \mathbb{E}[T^+_{n:(k+1)}] = 1/k - 1/n$ *and* $v/2 = \mathbb{E}[T^+_{n:(j+1)}] - \mathbb{E}[T^+_{n:(k+1)}] = 1/j - 1/k$ *(Equation 8). For* $j = o(k)$,

$$P(\min(R_{a,c}, R_{c,d}, R_{c,e}) = R_{c,e} \,|\, u, v) \to 1.$$

Proof. Note that $j = o(n)$ as well because $k \leq n$.

$$
\begin{aligned}
P(\min(R_{a,c}, R_{b,c}, R_{c,e}) = R_{c,e} \,|\, u, v) &= \frac{1/j - 1/k}{1/j + 1/k - 2/n} \\
&= \frac{(k - j)n}{(nk + nj - 2kj)} \\
&= \frac{1 - j/k}{(1 + j/k - 2j/n)} \\
&\to 1.
\end{aligned}
$$

$\square$

The implication of Proposition 3.1 is that haplotypes that share a recent common ancestor should have the same endpoints at the most distant common ancestors.

Since recombinations to the right and left of a focal location are independent, the result of Proposition 3.1 extends to simulating IBD segments overlapping a focal location. Figures S2 and S3 illustrate that merging occurs when the minimum recombination endpoints to the left and right of the focal location are drawn for the common ancestor c ($\min(R_{a,c}, R_{b,c}, R_{c,e}) = R_{c,e}$ and $\min(L_{a,c}, L_{b,c}, L_{c,e}) = L_{c,e}$).

3.4. The number of identity-by-descent comparisons

Pruning and merging should be most effective at reducing runtime if the majority of recombination endpoint comparisons happen at the oldest coalescent events. For these oldest coalescent events, we show that without pruning nor merging the expected number of IBD comparisons is of the same order as the worst-case number of IBD comparisons, which is asymptotically equivalent to the sample size squared.

Consider a random bifurcating tree. Here, and nowhere else, we work downward from the root of the tree. Throughout, we assume that n equals a power of 2 to simplify the floor and ceiling functions $\lfloor n/2^j \rfloor = \lceil n/2^j \rceil$ for $j \in \mathbb{N}$. At the coalescent event T_2, the tree bifurcates into two subtrees. At the coalescent event T_3, the scenario with the worst case number of comparisons is subtrees of size $n/2, n/4$, and $n/4$. In general, at each coalescent event, the worst case is to split in half the largest subtree, depicted in Figure S4A.

Let B_j be the size of one subtree randomly bifurcated from a subtree of size B_{j-1}. Figure S4 illustrates these subtree sizes in the context of a random bifurcating tree. The number of recombination endpoint comparisons is $B_j(B_{j-1} - B_j)$. In Theorem 3.2, we relate the expected value and covariance of $B_j(B_{j-1} - B_j)$ to the worst-case $n/2^{2j}$ computations. The result concerns a bounded number of

standard deviations from the expected value, which is a stronger notion than the expected number of computations $\Theta(\cdot)$. The intuition is that a $Binomial(m, 1/2)$ random variable's coefficient of variation $m^{-1/2}$ converges to 0 as m gets large. The general proof strategy is to recursively apply the law of total covariance and identify the exponents in the dominating terms.

Theorem 3.2. *Let $B_j \sim Binomial(B_{j-1}, 1/2)$ for bounded index $j \geq 1$ and $B_0 = n$.*

$$\lim_{n \to \infty} \frac{\mathbb{E}[B_j(B_{j-1} - B_j)] + O(1) \cdot Cov^{1/2}(B_j(B_{j-1} - B_j))}{n^2/2^{2j}} = 1. \tag{9}$$

Proof. We must calculate the expected value and the covariance in the numerator. Let $B \sim Binomial(m, 1/2)$.

$$
\begin{aligned}
\mathbb{E}[B(B-1)] &= \mathbb{E}[B^2] - \mathbb{E}[B] \\
&= m/4 + m^2/4 - m/2 \\
&= m(m-1)/4 \\
&= m(m-1) \cdot 2^{-2 \cdot 1}.
\end{aligned}
\tag{10}
$$

Using the law of total expectation, we solve the expected value for $j = 2$.

$$
\begin{aligned}
\mathbb{E}[B_2(B_1 - B_2)] &= \mathbb{E}[\mathbb{E}[B_2(B_1 - B_2)|B_1]] \\
&= \mathbb{E}[B_1(B_1 - 1) \cdot 2^{-2 \cdot 1}] \\
&= n(n-1) \cdot 2^{-2 \cdot 1} \cdot 2^{-2 \cdot 1} = n(n-1) \times 2^{-2 \cdot 2}.
\end{aligned}
\tag{11}
$$

Applying Equation 10 recursively, we derive the general formula

$$\mathbb{E}[B_j(B_{j-1} - B_j)] = n(n-1) \cdot 2^{-2j}. \tag{12}$$

The limit of Equation 12 divided by $n^2 \cdot 2^{-2j}$ is one. Next, we require that the standard deviation is of order less than n^2. Using the law of total covariance, we derive in Lemma A.1 that $\mathrm{Cov}(B_j(B_{j-1} - B_j)) \sim n^3$, where $\sim$ means asymptotically equivalent. Consequently,

$$\lim_{n \to \infty} n^{-2} \cdot \mathrm{Cov}^{1/2}(B_j(B_{j-1} - B_j)) = 0.$$

311   □

We remark that our marginal calculations along one branching path are not
the same as deriving the expected number of comparisons at the final j coalescent
events, the latter of which depends on the tree topology. Harding [27] discusses
the intractability of calculating probability masses for a tree topology with many
leaves, which is a limiting factor in deriving the expected number of comparisons
at the final j coalescent events. In Appendix A, we give moment calculations from
Dahmer and Kersting [16] that offer a complementary perspective on the number
of IBD comparisons, reiterating that a number of computations $\sim n^2$ should occur
at and near the root of the coalescent tree.

4. Results

Temple et al. [52] and Temple and Thompson [51] use our algorithm to con-
duct enormous simulation studies involving sample sizes as large as ten thousand
individuals and tens of millions of runs. (Individuals are "diploids", which we
implement as a haploid model with the number of haploids equal to the number
of individuals times 2.) Their empirical studies are feasible because of the pruning
and merging techniques, whose effects on runtime we benchmark in this section.

We also benchmark runtimes for `msprime` and `ARGON`, showing that these existing methods to simulate IBD can take more than an hour to complete one run when sample size exceeds five thousand.

4.1. Experimental setup

4.1.1. Demographic scenarios

We consider two complex demographic scenarios and constant population sizes. Figure S5 shows the demographic scenarios graphically. These demographic scenarios are the same as those used in Temple et al. [52], Temple and Thompson [51], and Temple [50]. We refer to the complex demographic scenarios as examples of three phases of exponential growth and a population bottleneck. The three phases of exponential growth scenario involves an ancestral population of five thousand individuals that grew exponentially at different rates in three different time periods. This demographic model is similar to the "UK-like" model in Cai et al. [12]. The population bottleneck scenario involves an ancestral population of ten thousand individuals that grew exponentially at a fixed rate but experienced an instantaneous reduction in size twenty generations before the present day.

4.1.2. Hard selective sweeps

We also consider a genetic model for positive selection [19, 23, 24] that is described in Crow and Kimura [15], Temple et al. [52], and Temple [50] as well as in many other articles. Briefly, the allele frequency $p_s(t)$ decreases backward in time as a function of a nonnegative selection coefficient s. The selection coefficient reflects the advantage the allele has relative to alternative alleles. The larger the selection coefficient is, the faster the allele frequency increased. Also, the larger the selection coefficient is, the more detectable IBD segments there are on average.

Positive selection around a locus is implemented via a coalescent with two subpopulations: one subpopulation has the sweeping allele, and one subpopulation does not have the sweeping allele. The population sizes are $N_e(t) \cdot p(t)$ and $N_e(t) \cdot (1 - p(t))$. Until the coalescent reaches the sweeping allele's time of *de novo* mutation, IBD segments are not possible between individuals in separate subpopulations.

4.2. Compute times

4.2.1. Simulating identity-by-descent segment lengths around a locus

To assess the effect of the pruning and merging rules, we evaluate four implementation strategies: merging and pruning (Algorithm 1), pruning only, merging only, and neither pruning nor merging (the naive approach). For each implementation, we run five simulations for sample sizes increasing by a factor of 2, recording the average wall clock compute time. The upper bound on sample size that we consider is 128,000 individiuals, which is of the same order as the UK Biobank data [11].

Figure 2 shows the average runtime per sample size between the implementations. Simulating IBD segment lengths without pruning nor merging takes more than one minute on average for eight thousand samples. Simulating IBD segment lengths with either pruning or merging can take less than one minute for sixty-four samples. Pruning appears to give a larger reduction in compute time than merging. Merging can further reduce runtime for sample sizes greater than one hundred thousand. The difference in five to ten seconds can be important when the number of simulations is enormous, as is the case in the Temple et al. [52] and Temple and Thompson [51] studies.

One important influence on runtime is the detection threshold. Figure S7 shows the algorithm's average runtime per sample size for different detection thresholds on segment length. With the 0.0025 Morgans cutoff, the quadratic behavior of runtime is visually apparent when more than twenty thousand samples are simulated, whereas the trend is less obvious for detection thresholds greater than 0.0050 Morgans. The algorithm is at least twice as fast on average for detection thresholds ≥ 0.02 Morgans versus those ≤ 0.0050 Morgans.

Another important influence on runtime is the population size. Figure S6 shows the algorithm's average runtime per sample size for different constant population sizes. The algorithm is at least twice as fast on average for population sizes $N \geq 10,000$ versus $N \leq 1,000$. Population sizes are estimated to be at least ten thousand for many model organisms [1, 38].

Figure S8 shows the algorithm's average runtime per sample size for different demographic scenarios and varying selection coefficients. Simulating IBD segment lengths takes more time for the population bottleneck and three phases of exponential growth scenarios compared to constant-size population scenarios. Runtime increases with the selection coefficient. The highest average measurement is more than four minutes for sixty-four thousand samples, the population bottleneck scenario, and $s = 0.04$.

Now, we perform twenty simulations each for sample sizes $2 \cdot 10^4, 4 \cdot 10^4, 8 \cdot 10^4, 16 \cdot 10^4$, and $32 \cdot 10^4$ and regress on runtime. The linear models in runtimes $\mathbf{Y} \in \mathbb{R}$, sample sizes $\mathbf{X} \in \mathbb{R}$, and regression coefficients $\boldsymbol{\beta}$ be:

$$\mathbf{Y} = \beta_0 \mathbf{X}; \tag{13}$$

$$\mathbf{Y} = \beta_1 \mathbf{X} + \beta_2 \mathbf{X}^2. \tag{14}$$

399 We measure the proportion of a fitted value explained by the linear effect as

$$\text{Percentage of prediction from linear component} = \frac{\hat{\beta}_1 x}{\hat{\beta}_1 x + \hat{\beta}_2 \cdot x^2}, \tag{15}$$

where x is a sample size. Figure S9 shows that the linear component in Equation 14

explains more than fifty percent of predictions for sample size $\leq 16 \cdot 10^4$, which we

say demonstrates approximately linear computational complexity in this domain.

Next, we estimate $\hat{\beta}_0$ equal to 0.0913 and 0.0707 in Equation 13 for population

sizes $N = 10,000$ and $N = 100,000$. We interpret this to mean that the expected

runtime increases by 0.0913 and 0.0707 seconds for each one unit increase to sample

size (in thousands), at least up to $n \leq 16 \cdot 10^4$.

Overall, we benchmark that our simulation algorithm can be run tens of thou-

sands of times within a day on one core processing unit of an Intel 2.2 GHz com-

pute node. Despite performance savings, we observe that our simulation algorithm

maintains quadratic behavior in sample size (Figure 2 and Figure S8). One ex-

planation for this finding is that a sizeable fraction of all lineages coalesce at least

once in the first few generations when the sample size exceeds ten thousand [4].

4.2.2. Simulating identity-by-descent segment lengths from the ancestral recombi-

nation graph

We measure the times it takes `ARGON` [43] and `msprime` [2] with `tskibd` [21]

to simulate detectable IBD segments around a locus. The `tskibd` program con-

catenates short IBD segments from `msprime` tree sequences into detectable IBD

segment lengths. To measure the computing time of these approaches, we do not include the time to simulate an ARG.

We simulate IBD segments ≥ 0.02 Morgans in a 0.07 Morgans region, which is a large enough region to contain all IBD segments ≥ 0.02 Morgans around its central location. Both programs visit nodes in the ARG in small, non-overlapping sliding windows. We consider window sizes of 0.0001 and 0.00001 Morgans in benchmarking runtimes. We compare compute times to those of Algorithm 1 with the 0.02 Morgans detection threshold.

Table 1 reports the average runtimes of each method for increasing sample size in the population bottleneck demographic scenario. `ARGON` takes nearly an hour to simulate the detectable IBD segment lengths of two thousand diploids. We do not run it for more than two thousand diploids due to concerns surrounding quadratic runtimes. With 0.0001 Morgans windows, `tskibd` takes less than twenty minutes to simulate the detectable IBD segment lengths of four thousand diploids and a little over an hour to simulate the IBD length distribution of eight thousand diploids. To get more precise IBD segment endpoints with `tskibd`, we use 0.00001 Morgans windows, which increases runtime eightfold or more. Some true IBD segments will not be detected if the window size is too large, but decreasing the window size increases runtime.

In comparison, for eight thousand diploids, our improved approach simulates IBD segments ≥ 0.01 Morgans around a locus in less than two seconds (Figure 2). Even our naive approach completes the same scope of simulations in less than two minutes. Our method is exact for a single locus, whereas `tskibd` may be inexact due to its windowing heuristic. Moreover, our method provides the full locus-specific length distribution whereas `ARGON` and `tskibd` provide a length

distribution truncated by the size of the genomic region. Conversely, our method relies on a mathematical construct without regard to finite chromosome sizes, which can result in detectable IBD lengths exceeding the chromosome size.

5. Discussion

To efficiently simulate IBD segment lengths overlapping a focal location, we exploit the fact that small values occur with high probability in Gamma random variables. Fast simulation in population genetics is important for statistical methods like approximate Bayesian computation [3], importance sampling [5, 48], and neural network learning [37]. Our method was developed with the evaluation of statistical consistency [13], parametric bootstrapping [17], and asymptotic distributions [51] in mind.

Existing methods `ARGON` [43] and `tskibd` [21] simulate IBD segment lengths for genomic region sizes less than 0.10 Morgans and thousands of samples within hours to days. These runtime performances are insufficient for the aforementioned methods and analyses, in particular parametric bootstrapping [52, 17]. We benchmark that our average runtime scales approximately linear as the number of haplotype pairs scales quadratically in sample size, taking as little as a couple of seconds or tens of seconds for sample sizes of order 10^4 or 10^5, respectively. The pruning and merging techniques presented here for a single locus could motivate changes to `ARGON` and `tskibd` that improve the runtime of genome-wide IBD simulations.

Related studies have already used our algorithm to these ends. Running our algorithm tens of millions of times with samples sizes ≥ 5000, Temple and Thompson [51] show simulation results that are consistent with the conditions of their central limit theorems. Running our algorithm millions of times with a sample

size of five thouand diploids, Temple et al. [52] show that ninety-five percent para-metric bootstrap intervals for a selection coefficient estimator contain the true parameter in ninety percent of simulations. They also show that exploring the effects of sample size and detection threshold on selection coefficient estimation is feasible on a laptop. Temple [50] assesses the tradeoffs between standard normal and percentile-based confidence intervals for the Temple et al. [52] selection coef-ficient estimator. Temple [50] also shows how to calculate the statistical power in an excess IBD rate scan as the magnitude of directional selection increases. These studies would otherwise have been computationally intractable using the existing methods `ARGON` and `tskibd`. Indeed, the scope of the Temple and Thompson [51] simulations amounts to hundreds of days of computing time even with our efficient algorithm.

The algorithm may assist in developing IBD clustering methods as well. A previously published method to simulate IBD cluster sizes comparable to those observed in human data is based solely on heuristics [47], whereas our method is an exact simulation of the process. Temple et al. [52] developed their method to find abnormally large IBD clusters by experimenting with our simulations. Generating IBD clusters, which are qualitatively different from Erdos-Renyi networks [51], could be fruitful in IBD network analyses [47]. The distribution of IBD cluster sizes could also help benchmark multi-way IBD segment detection [8].

Data and code availability

The algorithm is in a Python package (https://github.com/sdtemple/isweep), which is available under the CC0 1.0 Universal License.

Acknowledgments

S.D.T. acknowledges funding support from the US Department of Defense National Defense Science and Engineering Graduate Fellowship, the US National Institutes of Health T32 GM081062 Predoctoral Training Grant in Statistical Genetics, and Schmidt Sciences LLC. This research was supported in part by the US National Human Genome Research Institute of the National Institutes of Health under award number HG005701. We also acknowledge the Departments of Statistics and Biostatistics at the University of Washington for their support and maintenance of computing resources

Author contributions

S.D.T. proposed the study, planned the study, wrote the software, conducted the analysis, and wrote the manuscript. S.D.T. and S.R.B. developed the algorithm. S.D.T. and E.A.T. derived the theoretical results. All authors contributed to editing the manuscript.

Declaration of interests

The authors declare no competing interests.

 ## A. The number of identity-by-descent comparisons

 A.1. Computations near the root of the coalescent tree

 Lemma A.1. *Recall that $B_j \sim Binomial(B_{j-1}, 1/2)$ for $j \geq 1$ and $B_0 = n$. Then,*

$$Cov(B_j(B_{j-1} - B_j)) \sim n^3. \tag{A.1}$$

 Proof. We apply the laws of total covariance and expectation in a recursive fashion.
 Overall, we must control three terms:

$$\begin{aligned}
\mathrm{Cov}(B_j(B_{j-1} - B_j)) = \mathrm{Cov}(B_j^2, B_j^2) \\
+ \mathrm{Cov}(B_j B_{j-1}, B_j B_{j-1}) \\
- 2 \cdot \mathrm{Cov}(B_j B_{j-1}, B_j^2).
\end{aligned} \tag{A.2}$$

 The first four moments of the conditional binomial random variable are useful:

$$\begin{aligned}
\mathbb{E}[B_j | B_{j-1}] &= 0.5 \cdot B_{j-1}; \\
\mathbb{E}[B_j^2 | B_{j-1}] &= 0.5^2 (B_{j-1} + B_{j-1}^2); \\
\mathbb{E}[B_j^3 | B_{j-1}] &= 1 \cdot 0.5 \cdot B_{j-1} \\
&\quad + 3 \cdot 0.5^2 \cdot B_{j-1}(B_{j-1} - 1) \\
&\quad + 1 \cdot 0.5^3 \cdot B_{j-1}(B_{j-1} - 1)(B_{j-1} - 2); \\
\mathbb{E}[B_j^4 | B_{j-1}] &= 1 \cdot 0.5 \cdot B_{j-1} \\
&\quad + 7 \cdot 0.5^2 \cdot B_{j-1}(B_{j-1} - 1) \\
&\quad + 6 \cdot 0.5^3 \cdot B_{j-1}(B_{j-1} - 1)(B_{j-1} - 2) \\
&\quad + 1 \cdot 0.5^4 \cdot B_{j-1}(B_{j-1} - 1)(B_{j-1} - 2)(B_{j-1} - 3).
\end{aligned} \tag{A.3}$$

512 The following conditional covariances are also useful.

$$\text{Cov}(B_j, B_j | B_{j-1}) = 0.5^2 \cdot B_{j-1}^1 = O(B_{j-1}^1). \tag{A.4}$$

$$
\begin{aligned}
\text{Cov}(B_j, B_j^2 | B_{j-1}) &= \mathbb{E}[B_j^3 | B_{j-1}] - \mathbb{E}[B_j | B_{j-1}] \cdot \mathbb{E}[B_j^2 | B_{j-1}] \\
&= 1 \cdot 0.5 \cdot B_{j-1} \\
&\quad + 3 \cdot 0.5^2 \cdot B_{j-1}(B_{j-1} - 1) \\
&\quad + 1 \cdot 0.5^3 \cdot B_{j-1}(B_{j-1} - 1)(B_{j-1} - 2) \\
&\quad - 0.5^3 \cdot B_{j-1}(B_{j-1} + B_{j-1}^2) \\
&= 0.5^2 \cdot B_{j-1}^2 \\
&= O(B_{j-1}^2).
\end{aligned} \tag{A.5}
$$

$$
\begin{aligned}
\text{Cov}(B_j^2, B_j^2 | B_{j-1}) &= \mathbb{E}[B_j^4 | B_{j-1}] - \mathbb{E}[B_j^2 | B_{j-1}] \cdot \mathbb{E}[B_j^2 | B_{j-1}] \\
&= 1 \cdot 0.5 \cdot B_{j-1} \\
&\quad + 7 \cdot 0.5^2 \cdot B_{j-1}(B_{j-1} - 1) \\
&\quad + 6 \cdot 0.5^3 \cdot B_{j-1}(B_{j-1} - 1)(B_{j-1} - 2) \\
&\quad + 1 \cdot 0.5^4 \cdot B_{j-1}(B_{j-1} - 1)(B_{j-1} - 2)(B_{j-1} - 3) \\
&\quad - 0.5^4(B_{j-1}^2 + 2 \cdot B_{j-1}^3 + B_{j-1}^4) \\
&= -0.5^3 \cdot B_{j-1} - 0.5^3 \cdot B_{j-1}^2 + 0.5 \cdot B_{j-1}^3 \\
&= O(B_{j-1}^3).
\end{aligned} \tag{A.6}
$$

515 Notice that all of the conditional covariances are of an order of three or less. By
516 recursively applying the law of total expectation, we derive $\mathbb{E}[B_j^3] \sim n^3$. Another

important unconditional covariance term is

$$
\begin{aligned}
\mathrm{Cov}(B_j, B_j^2) &= \mathbb{E}[\mathrm{Cov}(B_j, B_j^2|B_{j-1})] + \mathrm{Cov}(\mathbb{E}[B_j|B_{j-1}], \mathbb{E}[B_j^2|B_{j-1}]) \\
&= \mathbb{E}[O(B_{j-1}^2)] + \mathrm{Cov}(O(B_{j-1}), O(B_{j-1}^2)),
\end{aligned}
\tag{A.7}
$$

which is asymptotically equivalent to n^2 when the total laws of expectation and covariance are applied recursively. Finally, we evaluate the asymptotic behavior of the three unconditional covariances in Equation A.2.

$$
\begin{aligned}
\mathrm{Cov}(B_j^2, B_j^2) &= \mathbb{E}[\mathrm{Cov}(B_j^2, B_j^2|B_{j-1})] + \mathrm{Cov}(\mathbb{E}[B_j^2|B_{j-1}], \mathbb{E}[B_j^2|B_{j-1}]) \\
&= \mathbb{E}[O(B_{j-1}^3)] + 0.5^4 \cdot \mathrm{Cov}(B_{j-1} + B_{j-1}^2, B_{j-1} + B_{j-1}^2)
\end{aligned}
\tag{A.8}
$$

$$
\begin{aligned}
\mathrm{Cov}(B_{j-1}B_j, B_{j-1}B_j) &= \mathbb{E}[B_{j-1}^2 \mathrm{Cov}(B_j, B_j|B_{j-1})] \\
&\quad + \mathrm{Cov}(B_{j-1} \cdot \mathbb{E}[B_j|B_{j-1}], B_{j-1} \cdot \mathbb{E}[B_j|B_{j-1}]) \\
&= 0.5^2 \cdot (\mathbb{E}[B_{j-1}^3] + \mathrm{Cov}(B_{j-1}^2, B_{j-1}^2))
\end{aligned}
\tag{A.9}
$$

$$
\begin{aligned}
\mathrm{Cov}(B_{j-1}B_j, B_j^2) &= \mathbb{E}[B_{j-1} \cdot \mathrm{Cov}(B_j, B_j^2|B_{j-1})] \\
&\quad + \mathrm{Cov}(B_{j-1} \cdot \mathbb{E}[B_j|B_{j-1}], \mathbb{E}[B_j^2|B_{j-1}]) \\
&= \mathbb{E}[O(B_{j-1}^3)] + 0.5^3 \cdot \mathrm{Cov}(B_{j-1}^2, B_{j-1} + B_{j-1}^2)
\end{aligned}
\tag{A.10}
$$

By recursively applying the total laws of expectation and covariance, we conclude that Equations A.8, A.9, and A.10 are asymptotically equivalent to n^3. $\qquad\square$

A.2. Computations near the leaves of the coalescent tree

A complementary perspective on joint subtree sizes we take from Dahmer and Kersting [16]. Now, we work upward from the leaves to the root. Dahmer and Kersting [16] provide a lemma for the expected number of subtrees containing r

sample haplotypes at the $(n-k)^{\text{th}}$ coalescent event. We can use their moment calculations together with the expected value of the hypoexponential random variable $T_{n:k}^+$ to build intuition for the average subtree sizes at a specified generation. In a toy example, Figure S10 shows the average number of sample haplotypes under subtrees of a given size at generations $N \cdot \mathbb{E}[T_{n:k}^+]$. Our main observation is that before the final coalescent events, which occur at expected times proportional to population size N, most sample haplotypes are expected to be under a subtree of size an order of magnitude smaller than the sample size.

References

[1] J. R. Adrion, C. B. Cole, N. Dukler, J. G. Galloway, A. L. Gladstein, G. Gower, C. C. Kyriazis, A. P. Ragsdale, G. Tsambos, F. Baumdicker, J. Carlson, R. A. Cartwright, A. Durvasula, I. Gronau, B. Y. Kim, P. McKenzie, P. W. Messer, E. Noskova, D. Ortega-Del Vecchyo, F. Racimo, T. J. Struck, S. Gravel, R. N. Gutenkunst, K. E. Lohmueller, P. L. Ralph, D. R. Schrider, A. Siepel, J. Kelleher, and A. D. Kern. A community-maintained standard library of population genetic models. *Elife*, 9, June 2020.

[2] F. Baumdicker, G. Bisschop, D. Goldstein, G. Gower, A. P. Ragsdale, G. Tsambos, S. Zhu, B. Eldon, E. Castedo Ellerman, J. G. Galloway, A. L. Gladstein, G. Gorjanc, B. Guo, B. Jeffery, W. W. Kretzschmar, K. Lohse, M. Matschiner, D. Nelson, N. S. Pope, C. D. Quinto-Cortés, M. F. Rodrigues, K. Saunack, T. Sellinger, K. R. Thornton, H. van Kemenade, A. Wohns, H. Y. Wong, S. Gravel, A. Kern, J. Koskela, P. L. Ralph, and J. Kelleher. Efficient ancestry and mutation simulation with msprime 1.0. *Genetics*, 220, Sept. 2021.

[3] M. A. Beaumont, W. Zhang, and D. J. Balding. Approximate Bayesian computation in population genetics. *Genetics*, 162(4):2025–2035, Dec. 2002.

[4] A. Bhaskar, A. G. Clark, and Y. S. Song. Distortion of genealogical properties when the sample is very large. *Proc. Natl. Acad. Sci. U. S. A.*, 111(6):2385–2390, Feb. 2014.

[5] S. Browning. A Monte Carlo approach to calculating probabilities for continuous identity by descent data. *J. Appl. Probab.*, 37(3):850–864, Sept. 2000.

[6] S. R. Browning and B. L. Browning. Accurate non-parametric estimation of recent effective population size from segments of identity by descent. *Am. J. Hum. Genet.*, 97(3):404–418, Sept. 2015.

[7] S. R. Browning and B. L. Browning. Probabilistic estimation of identity by descent segment endpoints and detection of recent selection. *Am. J. Hum. Genet.*, 107(5):895–910, Nov. 2020.

[8] S. R. Browning and B. L. Browning. Biobank-scale inference of multi-individual identity by descent and gene conversion. *Am. J. Hum. Genet.*, 111(4):691–700, Apr. 2024.

[9] S. R. Browning and E. A. Thompson. Detecting rare variant associations by identity-by-descent mapping in case-control studies. *Genetics*, 190(4):1521–1531, Apr. 2012.

[10] S. R. Browning, B. L. Browning, M. L. Daviglus, R. A. Durazo-Arvizu, N. Schneiderman, R. C. Kaplan, and C. C. Laurie. Ancestry-specific recent effective population size in the americas. *PLoS Genet.*, 14(5):e1007385, May 2018.

[11] C. Bycroft, C. Freeman, D. Petkova, G. Band, L. T. Elliott, K. Sharp, A. Motyer, D. Vukcevic, O. Delaneau, J. O'Connell, et al. The UK Biobank resource with deep phenotyping and genomic data. *Nature*, 562(7726):203–209, 2018.

[12] R. Cai, B. L. Browning, and S. R. Browning. Identity-by-descent-based estimation of the X chromosome effective population size with application to sex-specific demographic history. *G3 (Bethesda)*, 13(10):jkad165, Sept. 2023.

[13] G. Casella and R. L. Berger. *Statistical Inference.* Thomson Learning, 2002.

[14] H. Chen, A. Naseri, and D. Zhi. FiMAP: A fast identity-by-descent mapping test for biobank-scale cohorts. *PLoS Genet.*, 19(12):e1011057, Dec. 2023.

[15] J. F. Crow and M. Kimura. *An introduction to population genetics theory.* Harper & Row, New York, NY, 1970.

[16] I. Dahmer and G. Kersting. The internal branch lengths of the Kingman coalescent. *Ann. Appl. Probab.*, 25(3):1325–1348, 2015.

[17] B. Efron. Better bootstrap confidence intervals. *J. Am. Stat. Assoc.*, 82(397): 171–185, Mar. 1987.

[18] G. Ewing and J. Hermisson. MSMS: a coalescent simulation program including recombination, demographic structure and selection at a single locus. *Bioinformatics*, 2010.

[19] R. A. Fisher. XXI.—on the dominance ratio. *Proc. R. Soc. Edinb.*, 42:321–341, Jan. 1923.

[20] W. A. Freyman, K. F. McManus, S. S. Shringarpure, E. M. Jewett, K. Bryc, 23 and Me Research Team, and A. Auton. Fast and robust identity-by-descent inference with the templated positional Burrows-Wheeler transform. *Mol. Biol. Evol.*, 38(5):2131–2151, May 2021.

[21] B. Guo, V. Borda, R. Laboulaye, M. D. Spring, M. Wojnarski, B. A. Vesely, J. C. Silva, N. C. Waters, T. D. O'Connor, and S. Takala-Harrison. Strong positive selection biases identity-by-descent-based inferences of recent demog-

603 raphy and population structure in plasmodium falciparum. *Nat Commun*, 15
604 (1), Mar. 2024.

[22] J. B. S. Haldane. The combination of linkage values and the calculation of
606 distances between the loci of linked factors. *J. Genet.*, 8(29):299–309, 1919.

[23] J. B. S. Haldane. A mathematical theory of natural and artificial selection.
608 Part I. *Math. Proc. Cambridge Philos. Soc.*, 23:19–41, 1924.

[24] J. B. S. Haldane. *The causes of evolution.* Harper & Row, New York, NY,
610 1932.

[25] B. C. Haller and P. W. Messer. SLiM 3: forward genetic simulations beyond
612 the Wright–Fisher model. *Mol. Biol. Evol.*, 2019.

[26] B. C. Haller, J. Galloway, J. Kelleher, P. W. Messer, and P. L. Ralph. Tree-
614 sequence recording in SLiM opens new horizons for forward-time simulation
615 of whole genomes. *Mol. Ecol. Resour.*, 19(2):552–566, Mar. 2019.

[27] E. F. Harding. The probabilities of rooted tree-shapes generated by random
617 bifurcation. *Adv. Appl. Probab.*, 3(1):44–77, Apr. 1971.

[28] J. Hein, M. Schierup, and C. Wiuf. *Gene Genealogies, Variation and Evolu-
619 tion: A primer in coalescent theory.* Oxford University Press, New York, NY,
620 USA, 2005.

[29] S. Hoban, G. Bertorelle, and O. E. Gaggiotti. Computer simulations: tools
622 for population and evolutionary genetics. *Nat. Rev. Genet.*, 13(2):110–122,
623 Jan. 2012.

[30] R. R. Hudson. Properties of a neutral allele model with intragenic recombination. *Theor. Popul. Biol.*, 23(2):183–201, Apr. 1983.

[31] R. R. Hudson. ms a program for generating samples under neutral models. *Bioinformatics*, 18(2):337–338, 2002.

[32] R. R. Hudson and N. L. Kaplan. The coalescent process in models with selection and recombination. *Genetics*, 120(3):831–840, Nov. 1988.

[33] N. L. Kaplan, T. Darden, and R. R. Hudson. The coalescent process in models with selection. *Genetics*, 120(3):819–829, Nov. 1988.

[34] A. D. Kern and D. R. Schrider. Discoal: flexible coalescent simulations with selection. *Bioinformatics*, 2016.

[35] J. F. C. Kingman. The coalescent. *Stoch. Process. Their Appl.*, 13(3):235–248, Sept. 1982.

[36] J. F. C. Kingman. On the genealogy of large populations. *J. Appl. Probab.*, 19:27–43, 1982.

[37] K. Korfmann, O. E. Gaggiotti, and M. Fumagalli. Deep learning in population genetics. *Genome Biol. Evol.*, 15(2):evad008, Feb. 2023.

[38] E. M. Lauterbur, M. I. A. Cavassim, A. L. Gladstein, G. Gower, N. S. Pope, G. Tsambos, J. Adrion, S. Belsare, A. Biddanda, V. Caudill, J. Cury, I. Echevarria, B. C. Haller, A. R. Hasan, X. Huang, L. N. M. Iasi, E. Noskova, J. Obšteter, V. A. C. Pavinato, A. Pearson, D. Peede, M. F. Perez, M. F. Rodrigues, C. C. R. Smith, J. P. Spence, A. Teterina, S. Tittes, P. Unneberg, J. M. Vazquez, R. K. Waples, A. W. Wohns, Y. Wong, F. Baumdicker, R. A.

Cartwright, G. Gorjanc, R. N. Gutenkunst, J. Kelleher, A. D. Kern, A. P. Ragsdale, P. L. Ralph, D. R. Schrider, and I. Gronau. Expanding the stdpopsim species catalog, and lessons learned for realistic genome simulations. *Elife*, page RP84874, May 2023.

[39] H. Li and R. Durbin. Inference of human population history from individual whole-genome sequences. *Nature*, 475(7357):493–496, 2011.

[40] J. Nait Saada, G. Kalantzis, D. Shyr, F. Cooper, M. Robinson, A. Gusev, and P. F. Palamara. Identity-by-descent detection across 487,409 British samples reveals fine scale population structure and ultra-rare variant associations. *Nat. Commun.*, 11(1):6130, Nov. 2020.

[41] A. Naseri, X. Liu, K. Tang, S. Zhang, and D. Zhi. RaPID: ultra-fast, powerful, and accurate detection of segments identical by descent (IBD) in biobank-scale cohorts. *Genome Biol.*, 20(1):143, July 2019.

[42] H. B. Nath and R. C. Griffiths. The coalescent in two colonies with symmetric migration. *J. Math. Biol.*, 31(8):841–851, Oct. 1993.

[43] P. F. Palamara. ARGON: Fast, whole-genome simulation of the discrete time Wright-Fisher process. *Bioinformatics*, 32(19), Oct. 2016.

[44] P. F. Palamara, T. Lencz, A. Darvasi, and I. Pe'er. Length distributions of identity by descent reveal fine-scale demographic history. *Am. J. Hum. Genet.*, 91(5):809–822, Nov. 2012.

[45] S. Schiffels and R. Durbin. Inferring human population size and separation history from multiple genome sequences. *Nature genetics*, 46(8):919–925, 2014.

[46] R. Shemirani, G. M. Belbin, C. L. Avery, E. E. Kenny, C. R. Gignoux, and J. L. Ambite. Rapid detection of identity-by-descent tracts for mega-scale datasets. *Nat. Commun.*, 12(1):3546, June 2021.

[47] R. Shemirani, G. M. Belbin, K. Burghardt, K. Lerman, C. L. Avery, E. E. Kenny, C. R. Gignoux, and J. L. Ambite. Selecting clustering algorithms for identity-by-descent mapping. In *Pacific Symposium on Biocomputing 2023*, Jan. 2023.

[48] A. J. Stern, P. R. Wilton, and R. Nielsen. An approximate full-likelihood method for inferring selection and allele frequency trajectories from DNA sequence data. *PLoS Genet.*, 15(9):e1008384, Sept. 2019.

[49] F. Tajima. Statistical method for testing the neutral mutation hypothesis by DNA polymorphism. *Genetics*, 123(3):585–595, 1989.

[50] S. D. Temple. *Statistical Inference Using Identity-by-Descent Segments: Perspectives on Recent Positive Selection*. PhD thesis, University of Washington, 2024.

[51] S. D. Temple and E. A. Thompson. Identity-by-descent segments in large samples. *bioRxiv.org*, page 2024.06.05.597656, June 2024.

[52] S. D. Temple, R. K. Waples, and S. R. Browning. Modeling recent positive selection using identity-by-descent segments. *Am. J. Hum. Genet.*, 0(0), Oct. 2024.

[53] X. Tian, B. L. Browning, and S. R. Browning. Estimating the genome-wide

mutation rate with three-way identity by descent. *Am. J. Hum. Genet.*, 105 (5):883–893, Nov. 2019.

[54] J. Wakeley and T. Takahashi. Gene genealogies when the sample size exceeds the effective size of the population. *Mol. Biol. Evol.*, 2003.

[55] B. S. Weir and C. C. Cockerham. Estimating F-statistics for the analysis of population structure. *Evolution*, 38(6):1358, Nov. 1984.

[56] S. Wright. Evolution in mendelian populations. *Genetics*, 16(2):97–159, 1931.

[57] X. Yuan, D. J. Miller, J. Zhang, D. Herrington, and Y. Wang. An overview of population genetic data simulation. *J. Comput. Biol.*, 19(1):42–54, Jan. 2012.

[58] Y. Zhou, B. L. Browning, and S. R. Browning. Population-specific recombination maps from segments of identity by descent. *Am. J. Hum. Genet.*, 107 (1):137–148, July 2020.

[59] Y. Zhou, S. R. Browning, and B. L. Browning. IBDkin: fast estimation of kinship coefficients from identity by descent segments. *Bioinformatics*, 36 (16):4519–4520, Aug. 2020.

[60] Y. Zhou, S. R. Browning, and B. L. Browning. A fast and simple method for detecting identity-by-descent segments in large-scale data. *Am. J. Hum. Genet.*, 106(4):426–437, Apr. 2020.

 # Figures

Figure 1: Conceptual framework for IBD segment lengths. (Left) Sample haplotypes a, b, c, d trace their lineages back to common ancestors at times $t_4, t_4 + t_3, t_4 + t_3 + t_2$. (Right) Relative to a focal point, the haplotype segments lengths R_a, R_b, L_a, L_b are independent, identically distributed Exponential(t_4). The lengths shared IBD are $R_{a,b} := \min(R_a, R_b)$ and $L_{a,b} := \min(L_a, L_b)$. The IBD segment length $W_{a,b} := L_{a,b} + R_{a,b} \sim \text{Gamma}(2, 2 \cdot t_4)$ exceeds the detection threshold w Morgans.

Figure 2: Compute time to simulate IBD segment lengths around a locus depending on algorithm implementation. Compute time (y-axis) in seconds by sample size (x-axis) in thousands is averaged over five simulations. The legend denotes colored line styles for implementations using Algorithm 1 as is (blue), merging only (orange), pruning only (green), and neither pruning nor merging (red). The main text describes "merging" and "pruning" techniques. The demography is the population bottleneck. The Morgans length threshold is 0.01.

 Tables

Method	Samples	Compute Time (s)
ARGON	500	211.80
	1000	652.70 ($\approx$ 11 min)
	2000	3292.90 ($\approx$ 55 min)
tskibd	500	6.80
	1000	28.80
	2000	151.78
	4000	921.60 ($\approx$ 15 min)
	8000	4409.40 ($\approx$ 73 min)

Table 1: Average runtime to simulate detectable IBD segments with ARGON and tskibd. Using ARGON or tskibd, we report the mean number of hours, minutes, and seconds to simulate IBD segments $\geq$ 0.02 Morgans in a 0.07 Morgans region. Sample sizes range from 500 to 8000 diploids. Sliding non-overlapping windows are of size 0.0001 Morgans. Average runtimes are taken over ten simulations. Runtimes to simulate ARGs are not included in the results, which are small to negligible percentages of total runtimes.

 Supplementary figures

A)

B)

Figure S1: The upper tail probabilities of Gamma random variables. Subplots A) and B) show the survival probabilities for shape parameters 1 and 2, respectively. The rate of the random variables is the coalescent time in generations (x-axis). The survival probability (y-axis) comes from Equations 6 and 7. The length thresholds are denoted by different colors and line styles, defined in the legend.

A)

B)

Figure S2: Illustration of merging haplotypes. A) We draw recombination endpoints to the left and right of the focal location from Exponential(u) for both sample haplotypes a and b at coalescent time u. We draw recombination endpoints to the left and right of the focal location from Exponential(v) for the common ancestor c of a and b at coalescent time $u+v$. Colors denote branch lengths and recombination endpoints corresponding to a given haplotype. $l_{a,c}$ and $r_{a,c}$ denote the endpoints for a drawn to the left and right of the focal location at time u (lowercase denotes observation of random variables). B) We compute minimums of lengths drawn for c and a and c and b, respectively. We merge the sample haplotypes a and b in future calculations because the minimum lengths are both the recombination endpoints drawn from the common ancestor c. When comparing recombination endpoints at time $u+v$ with those of the haplotype d, we make one comparisons. The haplotypes remain longer than the detection threshold w Morgans.

A)

B)

Figure S3: Illustration of **not** merging haplotypes. A) We draw recombination endpoints to the left and right of the focal location from Exponential(u) for both sample haplotypes a and b at coalescent time u. We draw recombination endpoints to the left and right of the focal location from Exponential(v) for the common ancestor c of a and b at coalescent time $u + v$. Colors denote branch lengths and recombination endpoints corresponding to a given haplotype. $l_{a,c}$ and $r_{a,c}$ denote the endpoints for a drawn to the left and right of the focal location at time u (lowercase denotes observation of random variables). B) We compute minimums of lengths drawn for c and a and c and b, respectively. We **do not** merge the sample haplotypes a and b in future calculations because the minimum lengths are **not** both the recombination endpoints drawn from the common ancestor c. When comparing recombination endpoints at time $u + v$ with those of the haplotype d, we make **two** comparisons. The haplotypes remain longer than the detection threshold w Morgans.

Figure S4: Illustration of worst-case subtree sizes in random bifurcating tree. A) The worst-case subtree sizes of ancestors (dots) are when each bifurcation is an even split. B) The model $\{B_j\}$ of subtree sizes down one branching path is defined as random variables. The sample size is denoted as n.

A) **B)**

Figure S5: Demographic scenarios we consider in simulation studies: A) coalescent time in generations ago by the log 10 population size, and B) the most recent fifty generations by population size for examples of exponential growth. The legends specify the color and line style for each scenario. As opposed to coalescent time used in the main text, we describe the scenarios moving forward in time here. The three phases of exponential growth model is as follows: a population of ancestral size five thousand diploids increases exponentially each generation at rates one, seven, and fifteen percent starting three hundred, sixty, and ten generations ago. This demographic model is similar to the "UK-like" model in Cai et al. [12]. The population bottleneck model is as follows: a population of ancestral size ten thousand diploids increases exponentially each generation at a rate of two percent starting three hundred generations ago, but twenty generations before the present day, the population experiences an instantaneous reduction in size to one million diploids. Otherwise, the demographic scenarios we explore here are populations of constant size twenty-five and one hundred thousand diploids.

Figure S6: Compute time to simulate IBD segment lengths around a locus depending on population. Compute time (y-axis) in seconds by sample size (x-axis) in thousands is averaged over five simulations. The legends denote colored line styles for different constant population sizes $N \equiv N_e$ (in thousands). The Morgans length threshold is 0.02.

Figure S7: Compute time to simulate IBD segment lengths around a locus depending on the detection threshold. Compute time (y-axis) in seconds by sample size (x-axis) in thousands is averaged over five simulations. The legends denote colored line styles for different detection thresholds (in Morgans). The constant population size $N \equiv N_e$ is one hundred thousand diploid individuals.

Figure S8: Compute time to simulate IBD segment lengths around a locus depending on demography and selection. Compute time (y-axis) in seconds by sample size (x-axis) in thousands is averaged over five simulations. The legends denote colored line styles for different selection coefficients. A), B), C), and D) show results for demographic scenarios of three phases of exponential growth, a population bottleneck, and constant population sizes of twenty-five and one hundred thousand diploids, respectively. The Morgans length threshold is 0.01.

Figure S9: Percentage of regression model predictions explained by linear and quadratic effects. The percentage of predicted compute time (y-axis) in seconds by sample size (x-axis) in thousands with respect to linear and quadratic effects. Plots show results for A) the constant population size $N \equiv N_e = 10,000$ versus B) $N \equiv N_e = 100,000$. The detectable IBD segments are simulated with a 0.02 Morgans threshold.

Figure S10: The expected cardinality of subtree sizes at different coalescent times. Using Lemma 1 in Dahmer and Kersting [16], we compute the expected number of subtrees containing r samples (x-axis) at the $(n-k)^{\text{th}}$ coalescent event. We multiply these moments by r to get the expected number of leaves under such subtrees (y-axis). There are two thousand samples. Dark blue, orange, and green lines correspond to $k =$50, 95, and 180. We compute the expected time of the $(n-k)^{\text{th}}$ coalescent event [28] and multiply by a population size of ten thousand to get generations (legend). The vertical line is logarithm 10 of sample size.