How bats exit a crowded colony when relying on echolocation only -

a modeling approach

Omer Mazar[1], Yossi Yovel[1,2]

[1]Tel Aviv University, Sagol School of Neuroscience, Tel-Aviv 6997801, Israel.

[2]Tel Aviv University, Faculty of Life Sciences, School of Zoology, Tel-Aviv 6997801, Israel.

Author Contributions: **O.M** - Software, Formal analysis, Data acquisition, Validation,
Visualization, Methodology, Writing - original draft, Writing - review and editing. **Y.Y** -
Conceptualization, Resources, Supervision, Funding acquisition, Validation, Investigation,
Methodology, Project administration, Writing - review and editing

11
12

Abstract

Bats face a complex navigation challenge when emerging from densely populated roosts, where
vast numbers take off at once in dark, confined spaces. Each bat must avoid collisions with walls
and conspecifics while locating the exit, all amidst overlapping acoustic signals. This crowded
environment creates the risk of acoustic jamming, in which the calls of neighboring bats interfere
with echo detection, potentially obscuring vital information. Despite these challenges, bats
navigate these conditions with remarkable success. Although bats have access to multiple sensory
cues, here we focused on whether echolocation alone could provide sufficient information for
orientation under such high-interference conditions. To explore whether and how they manage this
challenge, we developed a sensorimotor model that mimics the bats' echolocation behavior under
high-density conditions. Our model suggests that the problem of acoustic jamming may be less
severe than previously assumed. Frequent calls with short inter-pulse intervals (IPI) increase the
sensory input flow, allowing integration of echoic information across multiple calls. When
combined with simple movement-guidance strategies—such as following walls and avoiding
nearby obstacles—this accumulated information enables effective navigation in dense acoustic
environments. Together, these findings demonstrate a plausible mechanism by which bats may
overcome acoustic interference and underscore the role of signal redundancy in supporting robust
echolocation-based navigation. Beyond advancing our understanding of bat behavior, they also
offer valuable insights for swarm robotics and collective movement in complex environments.

Introduction

In many bat species individuals dwell together in caves (or similar roosts), forming large colonies with tens to several millions of individuals[1,2] . Each evening, at approximately the same time, the bats take off from their roost, navigating through its passages toward the exit. The high density of bats flying simultaneously in great proximity poses many challenges for orientation in such a crowded and noisy environment. Flying while avoiding collisions, often in a pitch-black cave, demands the continuous detection and localization of both obstacles and nearby bats[3,4]. Employing echolocation, bats emit strong ultrasonic signals and interpret the reflected echoes to perceive their surroundings[5]. The reception of neighbors' loud calls, which share similar acoustic features with their own calls, can potentially hinder the bats' ability to detect the faint echoes reflected off the walls and the surrounding bats[5,6]. We examined whether bats could rely solely on echolocation to exit the roost even during such a chaotic 'rush hour'.

The question of how bats cope with acoustic interference — i.e., the masking of potential echoes by conspecific signals — has been extensively researched using playback experiments, field observations, on-body tags, and computational simulations[7–17]. However, much of this research has focused on foraging bats in small groups[5,6,9,16,18–20]. The challenges bats encounter during roost exits (e.g., cave exits) differ markedly from those encountered during group foraging. Bat density during roost exits is significantly higher, and bats need to detect and follow static walls or obstacles, which produce loud echoes, rather than small, sporadic prey items that generate faint echoes[21]. Their flight during exits is also more directional and involves avoiding collisions with conspecifics, in contrast to the erratic hunting maneuvers typically observed while foraging. Echolocation studies during dense collective movement are scarce[4,6,22–25], likely due to the complexities in recording separate echolocation calls and tracking individual flights within the swarm.

While collective movement has been extensively studied in various species, such as insect swarming, fish schooling, and bird murmuration[26–32], as well as in swarm robotics, where agents perform tasks such as coordinated navigation and maze-solving[33–35], most studies have focused on movement algorithms that assume full detection of neighbors[36–43]. Some models have incorporated limited interaction rules where individuals respond to only one or a few neighbors

due to sensory constraints[44,45] However, fewer studies have explicitly examined how sensory

interference, occlusion, and noise influence decision-making and affect collective movement[46].

The present study addresses these gaps by introducing an agent-based sensorimotor model based

on the well-documented echolocation capabilities of bats, simulating multiple bats pathfinding

their way out of a cave-like structure. We modeled the echolocation behavior of two insectivorous

bat species: *Pipistrellus kuhlii (*PK*)*, which roosts in abandoned buildings and frequently navigates

through conspecific-dense, cluttered corridors and the cave dwelling *Rhinopoma microphyllum*

(RM) which emerges from its roosts with thousands of individuals simultaneously. These two

species differ in their echolocation signals - PK echolocation signals are characterized by a wider

bandwidth and a higher terminal frequency than RM calls. We quantified the performance of an

individual bat flying among conspecifics, demonstrating that even a relatively simple sensorimotor

algorithm can facilitate successful orientation in such complex environments. The modeling

approach enabled us to explore how various biological and ecological factors influence

successful navigation under such challenging conditions.

Results

Our model was designed with conservative assumptions regarding bats' sensing, movement, and

sensorimotor integration, aiming to underestimate their capabilities and thereby establish a lower

bound on their actual performance. Real bats likely outperform the model's predictions. In our 2D

simulations[7], each bat emits sound signals and receives echoes reflected from the roost walls and

other bats, while also encountering masking signals caused by calls from conspecifics. These

masking signals can interfere and completely eliminate echo detection (which we refer to as

jamming) or cause echo localization errors. After estimating the distance and direction of each

detected reflector, the bat adjusts its echolocation parameters and maneuvers to find the exit while

simultaneously avoiding collisions. The bats dynamically adjust their echolocation parameters—

including call rate, duration, and frequency range—based on the estimated distance to obstacles,

following the well-documented transition between search, approach, and buzz phases observed in

echolocating bats (see[7] and Methods). Their reception was modeled using a biologically inspired

filter-bank receiver comprising 80 gammatone channels[7,47,48]. Each bat adjusted its flight following

a simple pathfinding algorithm based solely on the estimated locations of the detected reflectors

(see Methods, Supplementary Figure 1, and Supplementary Movie 1 for additional details). The
bats had to exit a roost designed as a corridor (14.5 m long x 2.5 m wide), with a right-angle turn
located 5.5 m before the exit (Figure 1A). Additionally, an obstacle (1.25 m wide) was situated
2.25 m in front of the opening. The simulated bats initiated their flight from the far end of the
corridor, within a randomly selected 1.5×2 m² area, taking off in the general direction of the exit
(±30 degrees), without prior knowledge of the roost's structure.

The sensory model accounted for six types of acoustic signals: (1) the bat's own calls, (2) echoes
from conspecifics, (3) echoes from walls in response to the bat's own calls (i.e., desired wall
echoes), (4) echoes from conspecific calls reflected off other bats, (5) echoes from conspecific
calls reflected off walls, and (6) the conspecific calls themselves. In the baseline model, bats were
assumed to reliably distinguish between all these signal types. In contrast, the confusion model
described below specifically tested the impact of failing to distinguish between desired wall echoes
(3) and wall echoes generated by conspecific calls (5), while preserving the bat's ability to identify
all other signal types. In brief, the bat responded to echoes as follows (see Methods and
Supplementary Figure 1 for details): If an obstacle or a conspecific was detected in front of the bat
and was too close, the bat would maneuver to avoid a collision. Otherwise, for exit-seeking, the
bat would follow the contour of the walls by steering toward the farthest detected obstacle ahead.
If a gap greater than 0.5 m was identified between adjacent reflectors, the bat directed its trajectory
toward the center of the gap.

The ability of the bats to exit the roost within 15 sec was evaluated for different group sizes, from
a single bat and up to 100 individuals. For simplicity, we will refer to the initial density at the
cave's far end as the number of bats per $3m^2$ (i.e., for groups of 100 bats, the density is 100
bats/$3m^2$, or 33.3 bats/m²). The bat densities we tested were chosen to reflect the typical range of
bat densities observed in natural caves during emergence events[25,49,50]. Key model parameters,
such as the sensory integration window, object target strength, echolocation parameters, and flight
velocity (see Table 1), were manipulated and their impact on the exit performance was analyzed.
To explicitly quantify the effect of sensory masking vs. the effect of collision avoidance (i.e.,
spatial interference) only, we turned the acoustic interference on and off to measure its impact.
Each scenario was repeated as follows: 1 bat: 240; 2 bats: 120; 5 bats: 48; 10 bats: 24; 20 bats: 12;
40 bats: 12; 100 bats: 6 (see Table 1), while misidentification rate, multi-call clustering, and
wall/conspecific target strength were tested only up to 40 bats (see Table 1).

Figure 1: The sensorimotor model. (A) Top view of the cave with three bats' trajectories. The focal bat is shown in black. All bats' flight trajectories are displayed while the bats' moment-to-moment decisions are represented by the colored lines: blue - random flight, yellow – collision avoidance, light green – wall-following, turquoise – movement toward a wall gap (see panel D for details). Green squares depict reflectors detected by the focal bat along its route. **(B)** A zoomed-in view of the marked rectangular area in Panel A, where the focal bat (black) emitted one echolocation call (black) and received echoes from the cave walls (green) and from two other bats (blue). It also received conspecifics' calls (red) and their reflection from the cave walls (orange), as well as the reflections from other bats (pink). Green squares indicate points that were detected by the focal bat from this call and red x's indicate missed points due to acoustic masking (i.e., jammed reflectors). The locations of the detected reflectors (green squares) are marked according to their localization by the bat (with simulated errors). The lines near the bats depict their flight direction. **(C)** The acoustic scene received by the focal bat is as depicted in B, including the emitted call and all received signals (colors as in panel B). **(C1)** The time-domain plot displays the envelope of signals, encompassing the emitted call and the received signals: the desired echoes from the walls and conspecifics; the calls of other bats; the echoes returning from conspecific calls and reflected off the walls and off other bats. Notably, in this example, some of the desired wall-echoes are jammed by stronger self-echoes reflected from nearby conspecifics. **(C2)**

The spectrogram of all the received signals presented in C1; for clarity, the emitted call is not depicted. **(C3)**
The responses of the active channels of the cochlear filter bank (FB channel) after de-chirping. Each channel
is represented by its central frequency on the y-axis. Each black dot represents the timing of a reaction that
was above the detection threshold in each channel. Note that early reactions in low-frequency channels
(marked by a yellow arrow) result from the stimulation of those channels caused by the higher frequencies
of the downward FM chirp. However, most of these stimulations do not reach the detection threshold and are
therefore not detected (see Methods). **(C4)** The detections of each channel are convolved with a Gaussian
kernel, summed, and compared with the detection threshold (dotted red line). Colored asterisks mark peaks
that were classified as **successful detections**—those identified in both the interference-free and full detection
conditions (see Methods for details). Other peaks may originate from masking signals or overlapping echoes
that did not meet the detection criteria (colors of the sources are as defined above). **Panel D** depicts the
pathfinding algorithm used by the bat. The algorithm involves a correlated-random flight during the search
phase (blue), collision avoidance (yellow), flying along the wall at a constant distance (green), and flying
toward the center of a gap between obstacles as an indicator of a possible exit (cyan). After each echolocation
call, the bat awaits an IPI (Inter Pulse Interval) period before processing the detections, adjusting flight and
echolocation parameters, and emitting the next call. Based on the received signals, it then modifies its next
call design and adjusts its direction and speed accordingly. For a detailed diagram of the complete
sensorimotor process see Supplementary Figure 1.

Bats find their way out of the cave even at high conspecific densities:

We first examined how bat density affects bats' ability to exit the cave, both alone and in a group.

The probability of exiting the cave within 15 seconds—defined as the proportion of bats that

successfully exited within this time frame—was significantly reduced at higher densities (Figure

2A, see Supplementary Movie 1 for a view of the bats' movement, $p<10^{-10}$, t =-23, DF=4077,

GLM, see details in Table 1). In trials in which a single bat was flying alone, it successfully exited

the cave in 100% of the cases. Even without sensory interference, the probability of exiting

decreased significantly from 100% to 86%±1.4% and 91%±1.7% at densities of 100 PKs/3m^2 and

100 RMs/3m^2, respectively (mean ± s.e.). When acoustic interference was added, the exit

probability further decreased to 63%±1.4% and 67%±1.4% for 100 PKs and RMs, respectively

(see Figure 2A).

The difference in exit probability between the two species was not significant (p=0.08, t =1.74,

DF=4077, GLM as above, Figure 2A). Similarly, the difference in echolocation parameters

between the two species did not affect the collision rate with the walls (with a maximum of 0.29

and 0.3 collisions per bat per second for PK and RM, respectively, with 100 bats (p=0.63, t =-0.48,

DF=4077, GLM, Figure 2C, see details in Table 1). To quantify sensory interference, we defined

a jammed echo as an echo entirely missed due to masking. The jamming probability, which was

calculated as the number of jammed echoes divided by the total number of self-echoes, was

significantly higher for RM compared to PK. The maximum difference between the two models

was 14.3% at a density of 10 bats, with a smaller difference of 9.8% observed at 100 bats (p<10^{-10},

t =6.56, DF=4077, GLM, Figure 2D, see details in Table 1). Accordingly, PK demonstrated a

minor but significant advantage in detecting the cave walls (p=0.024, t =-2.25, DF=4077, GLM,

Figure 2E, see details in Table 1). With 100 bats flying together, the probability of detecting a wall

echo at a distance of 1 m in a single call was around 50% and 46% for PK and RM, respectively.

Despite this minor disadvantage in detection, RM bats exhibited a better time-to-exit average than

PK bats, being 0.5 seconds faster to exit (p=0.0005, t =-4.06, DF=3533, for n=40 bats, Figure 2B).

Additionally, RM bats experienced a significantly higher probability of their self-generated

echoes, reflected off conspecifics, being jammed (p = 0.00016, t = 3.8, DF = 3593, GLM; see

details in Table 1).

Figure 2: Exit performance of *P. Kuhlii* (PK) and *R. Microphyllus* (RM). **(A)** Sensory interference
significantly impaired the probability of exiting the cave (compare dashed lines with continuous lines). The
probability of a successful exit also declined as the number of bats increased, with no significant difference
observed between the species when masking interference was applied. The insert shows the spectrograms of the
echolocation calls of PK (top) and RM (bottom). **(B)** The time-to-exit, which was calculated for successful trials

only, and **(C)** the collision rate with the walls both increased as a function of the number of bats. **(D)** The
probability of jamming significantly increased to about 55% and 63% with 100 bats for PK and RM, respectively.
(E) The detection probability of a wall reflector at one meter or less in front of a bat decreased as a function of
the number of bats. In panels (A-E), circles represent means and bars represent standard errors (see details in
Table 1). Asterisks indicate significant differences between the lines in each panel.

Multi-call integration improves exit performance: We next examined whether bats improve their

performance when integrating information from several consecutive calls. The integration window

determines the number of previous calls the bat uses at each step to guide its next movement

decision (see Methods and Supplementary Figure 2A). In the basic multi-call integration model,

detections from the previous calls — by default the last five — were stored in an allocentric (x-y)

reference frame, with each detection treated independently as a potential obstacle without

clustering or filtering. At each decision, the bat takes all of these detections into account when

guiding its movement and echolocation. The probability of exiting the roost significantly increased

when increasing the size of the integration window for all bat densities ($p < 10^{-10}$, t =28.5,

DF=10197, GLM, Figure 3A, see details in Table 1). For example, at a density of 40 bats/3m^2, the

exit probability improved from 20%, to 75%, and to 87% as the window size increased from one,

to three, and to 10 previous calls, respectively. In addition, increasing the window size resulted in

a significant improvement in the time-to-exit and the avoidance of wall collisions ($p < 10^{-10}$, t =-

12.8, DF=7661; $p < 10^{-10}$, t =-46.5, DF=10197, respectively, GLM, see details in Table 1). With

100 bats, the collision rate decreased by a factor of 2 from 0.53 to 0.25 collisions per second as the

window increased from 1 to 10 calls. The size of the integration window had no significant effect

on the jamming probability (p=0.37, t =0.9, DF=10197, GLM, see details in Table 1).

Exit probability was maximal at an intermediate flight-speed: We observed a significant and non-

linear effect of the flight speed of the bats on the performance, as shown in **Figure 1**Figure 3B

($p < 10^{-10}$, t =-29.9, DF=10196, GLM, see details in Table 1). The exit probability increased with

flight speed until it reached a maximum at 6-8 m/s and then declined rapidly. This was the case

for all bat densities, with the maximal exit probability ranging between 65% to 99%. At the optimal

velocity, the time-to-exit was also minimal. However, the collision rate increased monotonically

with speed, with a steep incline above the optimal speed.

Figure 3: Exit performance as a function of key sensorimotor parameters. (A) The effect of the integration window on the probability of exiting the roost, the time-to exit, the rate of collisions with the walls, and the probability of jamming (from left to right, respectively). Each colored line shows the trend as a function of the window-size for different bat densities, with each color representing a specific density. Note that a window size of 0 indicates that only the most recent call is used in the bat's decision-making, without integrating detections from previous calls. **(B)** The effect of the nominal flight speed of the bats, with panels and line-colors as in panel A. An optimal speed of approximately 6 to 8 m/sec can be observed for all densities above one bat. **(C)** The effect of call intensity on exit performance, panels as in (A). In all panels, circles represent means and bars represent standard errors. Error bars depicting standard errors are presented but are very small due to the large number of simulation repetitions. See Table 1 for the number of simulated bats.

Call intensity had only a minor effect on exit performance and only at high bat densities: For low bat densities (<40 bats), call intensity did not have a significant impact on either exit probability or collision rate (Figure 3C, p=0.89, t =0.13, DF=5757; p=82, t -0.21, DF=5757, respectively, GLM, see details in Table 1). Call intensity affected exit performance only when the

intensity dropped to 100 dB-SPL (@ 0.1m) and only at a high bat density of 100 bats/3m^2 (Figure

3**Figure 3** C). In this scenario, the exit probability declined from approximately 60% to 49.5%

(p=0.003, F = 8.45, DF = 2396, One-way ANOVA with 'hsd' post hoc test), and the collision rate

increased from 0.3 to 0.35 collisions per second (p<3·10^{-6}, F = 22.18, DF = 2396). Notably, this

low intensity is below the typical search-call intensity of most echolocating bats. At the same bat

density (100 bats/3m^2), further increasing the call intensity to above 100dB-SPL had no significant

effect on either exit probability (p=0.6) or collision rate (p=0.07). Calling louder also slightly, but

significantly, decreased the jamming probability at all bat densities, with a decrease of 3.5%±8%

to 5.5%±5% (mean ± s.e.) (p=0.02, t =-2.26, DF=8157, GLM, see Table 1).

While confusion between the desired echoes and those from conspecific calls may significantly

impair exit performance, multi-call clustering helps to mitigate this. We next addressed the

challenge of echo classification, assuming that a bat can differentiate an echo resulting from its

own calls from echoes resulting from the calls of other bats. To examine this assumption, we tested

another model, referred to as the **confusion model**, in which bats responded similarly both to wall

echoes returning from their own emissions and to those from conspecific emissions, treating all as

their own echoes. This confusion significantly decreased exit performance for all bat densities

(above one bat). The probability of a successful exit for a density of 40 bats/3m^2 dropped from

83.3±2.4% to 14.6±2.3% (p<<10^{-10}, t =-20.7, DF=2877, GLM, see details in Table 1), the exit time

increased from 7.6±0.18 to 9.3±0.2 seconds (p<<10^{-10}, t =15.5, DF=2157, GLM), and the collision

rate increased significantly from 0.2±0.007 to 0.8±0.013 collisions per second (p<<10^{-10}, t =-30,

DF=28777, GLM, see Figure 4, red and yellow lines).

To further examine whether this substantial decrease in performance could be mitigated even

without improving echo identification, we tested an enhanced integration model that, in addition

to extending the number of calls integrated, clustered spatially close detections, removed outliers,

and estimated wall directions based on grouped reflectors (see Methods and Supplementary Figure

2B). This **'multi-call clustering'** significantly improved performance, but exit probability and

time-to-exit still remained significantly lower than without echo-confusion: exit probability =

58±3% in comparison to 83.3±2.4% without echo confusion (p<<10^{-10}, t =18.3, DF=28777, GLM),

time-to-exit =9.3±0.2 seconds (p<<10^{-10}, t =-13.7, DF=1996, GLM), see Figure 4, yellow line. The

results above are reported for a density of 40 bats/3m^2. Interestingly, the multi-call clustering

restored the collision rate to the levels observed under the "No Confusion" condition (p=0.68, t =-

0.42, DF= 2877, GLM, see Figure 4C, dark-purple and red lines).

Figure 4: The impact of confusion on performance. The figure illustrates the impact of classification
confusion on roost-exit performance under various conditions. Blue lines depict trials with masking, while
assuming that bats can distinguish between echoes from their own calls and those of conspecifics (referred
to as "No Confusion"). Red lines depict performance where confusion between echoes is assumed. Yellow
lines depict performance under the confusion condition, with the added capability of   multi-call clustering
in a short-term working memory (referred to as "confusion with mitigation", see text for further details). In
all panels, circles represent means and bars indicate standard errors. **(A)** The probability of exiting the roost
significantly decreased with masking and confusion. In conditions with confusion and no aggregation
process, only 15% of bats successfully exited the roost, at a density of 40 bats/3m^2. Multi-call clustering
partially mitigated the confusion effect but did not eliminate it. **(B)** Bats with the ability to distinguish
between echoes demonstrated significantly shorter exit times than those experiencing confusion. Note that
time-to-exit refers only to successful attempts. **(C)** The collision rate with walls was highest for bats
experiencing both masking and confusion but decreased significantly when without confusion. Multi-call
clustering restored performance to the "No Confusion" condition, reducing collision rates accordingly, at
densities between 1 to 40 bats/3m^2.

Effect of Wall and Conspecific Target Strengths on Exit Performance: Increasing the wall

target strength significantly enhanced navigation performance (Supplementary Figure 3, Table 1),

improving exit probability by up to 64% and reducing time-to-exit by up to 2.8 seconds (p <<

10^{-10}). Stronger wall echoes improved environmental awareness but also slightly increased

masking of desired conspecific signals.

In contrast, changes in conspecific target strength had a much smaller effect (Supplementary Figure 4, Table 1), with only minor improvements in detection and collision rates, and no significant impact on exit probability. This likely reflects the fact that both desired and masking signals scale similarly with conspecific reflectivity. Overall, the model showed low sensitivity to variations in conspecific target strength.

Key parameter	Tested range	Default value	Effect Size on Explained Variable				GLM
			Exit prob. (%)	Time-to-exit (sec)	Jamming-prob. (%)	Obs. Collision (sec⁻¹)	Explaining factors
Number Of Bats$^\Omega$	[1, 2, 5, 10, 20, 40, 100]	**All Values**	-0.37/bat* [63:100]	0.044/bat * [4.6:8.9]	0.54/bat* [0:54]	0.25/bat* [0.05:0.3]	Number of bats
Bat species	[PK, RM]	**PK**	4.5 [63:67]	-0.4* [8.5:8.9]	9* [54:63]	0.01 [0.29:03].	Number of bats, bat species
Integration Window (#)	[0,1,3,5,10]	**5**	0.41/call* [29:70]	-0.16/call* [9.2:7.6]	0.01/call [54:55]	0.27/call [0.25:0.53]	Number of bats, integration window size
Nominal flight speed (m/s)	[2,4,6,8,10]	**6**	6/(1m/s), -12/(1m/s)* [15:63]	-1/(1m/s), 1/(1m/s)* [6:9.6]	1.4/(1m/s)* [55:65]	0.18/(1m/s)* [0.07:1.3]	Number of bats, flight speed, square of flight speed
Call level (dB-SPL, @ 0.1m)	[100,110,120, 130]	**120**	13$^\Psi$ [50:63]	-0.5 [7.9:8.4]	0.5/10dB* [53:58]	0.07 $^\Psi$ [0.29:0.36]	Number of bats, call level
Misidentification $^\Omega$	[Yes/No]	**N**	-69* [14:83]	1.3* [7.6:8.9]	30* [50:80]	0.6* [0.2:0.8]	Number of bats, With and without confusion
Misidentification and multi-call clustering $^\Omega$	[Yes/No]	**N**	-23* [58:83]	1.7* [7.6:9.3]	29* [50:79]	-0.02* [0.18:0.2]	Number of bats, With and without multi-call clustering
Masking	[Yes/No]	**Y**	23* [63:86]	0.8* [8.0:8.8]	54* [0:54]	0.03 [0.26:0.29]	Number of bats, With and without masking
Wall target strength (dB) $^{\alpha, \Omega}$	[-33, -23, -13, -3]	**-23**	16/10dB * [23:87]	0.7/10dB * [6.6:9.5]	-8.5/10dB * [34:68]	0.07/10dB * [0.19:0.47]	Number of bats, wall target strength
Conspecific target strength (dB) $^{\beta, \Omega}$	[-49, -43, -33, -23]	**-23**	-1.5/10dB [85:91]	0.25/10dB* [7.2:8.15]	-0.5/10dB [48:50]	0.1/10dB [0.16:0.2]	Number of bats, conspecific target strength

Table 1: Key model parameters and their effects on performance metrics. The table presents the key parameters tested, their ranges, default values, and effect sizes on various performance metrics: exit probability, time-to-exit, jamming probability, and collision rate with obstacles. The parameters comprised the number of bats, bat species (PK-*Pipistrellus kuhlii*, RM –*Rhinopoma microphyllum*), integration window,

nominal flight speed, call level, echo mis-identification with multi-call clustering (yes/no), masking (yes/no), wall target strength, and conspecific target strength. In each scenario, all parameters except the tested one were set to the default value. Call levels are reported in dB-SPL, referenced at 0.1 m from the source. Effect sizes for each parameter are explicitly listed for all four-performance metrics, expressed as the change per unit of the tested parameter (e.g., per bat or per 10 dB). For flight speed, a non-monotonic relationship was observed, and values are reported both before and after the peak performance (see Results, Fig. 3B). Values in square brackets indicate the minimum and maximum of the metric across the tested range. . Asterisk (*) indicates a significant impact. Each scenario was tested using Generalized Linear Models (GLMs) with number-of-bats and the tested parameters set as fixed explaining variables. Exit probability and jamming probability were treated as binomially distributed, collision rate was treated as a Poisson distributed, and all other variables were considered normally distributed. Explaining variables were set as fixed factors. The number of repetitions for each scenario was as follows: 1 bat: 240; 2 bats: 120, 5 bats: 48; 10 bats: 24; 20 bats: 12; 40 bats: 12; 100 bats: 6. $^{\Omega}$ Misidentification rate, multi-call clustering, wall target strength, and conspecific target strength were simulated only up to 40 bats due to significantly longer run-times. $^{\Psi}$ A significant difference in call intensity was found only for a bat density of 100 bats/3m^2, and between the group with a level of 100dB-SPL and all other groups. $^{\alpha}$ see Supplementary Figure 3. $^{\beta}$ see Supplementary Figure 4.

Discussion

We present a model-based approach that suggests how echolocating bats might find their way out of a crowded roost while contending with severe sensory interference caused by numerous nearby conspecifics. Our results demonstrate that a single bat, lacking prior knowledge of the roost's structure, successfully found the exit in all simulated trials using echolocation alone. As bat density increases, the bats face increased collision risks and more substantial acoustic interference, both of which reduce the probability of efficiently finding the exit. Nevertheless, even at densities of 100 bats/3m^2, most bats (63%) successfully exited the roost within a short timeframe. These results are based on a 2D simulation with up to 33 bats/m², under the assumption that bats can distinguish their own echoes from those of conspecifics. We demonstrate how a simple sensorimotor approach can solve this supposedly challenging task. This approach encompasses the following principles: (1) emission of echolocation calls; (2) reception of reflected echoes and masking signals; (3) detection of reflectors (including walls and conspecifics) using a gammatone filter bank biological receiver; (4) localization of the detected objects; (5) employment of multi-call integration of acoustic detections; (6) adjustment of flight and echolocation behavior based on the distance and angle to the reflectors; and (7) application of simple pathfinding rules to follow walls and gaps while avoiding collisions. Notably, despite the jamming of a substantial percentage of the echoes

— particularly, with 100 bats, 50% of the echoes from nearby obstacles at ~1 m distance — the

bats managed to maneuver correctly even with this simple approach and partial data.

A key component of this success was the multi-call integration: increasing the number of stored

calls from one to ten markedly improved performance, raising the exit probability from 20% to

87% and halving the collision rate. Real bats likely use a much more sophisticated approach that

also includes memorizing the roost's structure[51], using landmarks inside the roost[52], reliance on

the movement of nearby conspecifics[43,49], and exploitation of other sensory modalities. We thus

expect their actual performance to surpass that of our modeled bats.

Our model suggests that acoustic jamming might be less problematic than has been generally

assumed[5,11,53], and that movement under severe acoustic masking could be mitigated by increasing

the call-rate, creating a redundancy across several calls- similar to how real bats behave in a

complex environment[6]. In our model, the Inter-Pulse Interval (IPI) naturally varied according to

established echolocation behavior, decreasing from 100 msec in the search phase to 35 msec (~28

calls per second) in the approach phase, and further to 5 msec (200 calls per second) during the

final buzz (Table 2). The results indicate that this redundancy, combined with simple sensorimotor

heuristics, enhances successful navigation. This is consistent with several recent studies that have

pointed in this direction[7,24,25].

While echolocation phases—search, approach, and buzz—are traditionally associated with prey

capture, similar patterns have been documented in non-foraging tasks such as landing, obstacle

avoidance, clutter navigation, and drinking[54–64]. In these contexts, bats modulate call duration and

inter-pulse intervals according to object proximity, generating phase-like transitions even without

prey. This supports the interpretation of phase structure as a general proximity-sensing strategy

rather than a foraging-specific behavior. In our simulations, bats operated predominantly in the

approach phase due to the cluttered cave environment—consistent with natural emergence

behavior, where navigation dominates over open-space search. Accordingly, our use of

echolocation phases in the model is biologically plausible across a range of sensory-guided tasks.

The bat densities we simulated, ranging from 1 to 100 bats per 3m^2, reflect a wide range reported

in field studies. Although bat colonies can be much larger than 100 bats, the maximal simulated

density in our model (100 bats per 3 m²) resulted in bats flying in very close proximity, with an

average nearest-neighbor distance of 0.27 meters. This density is higher than some of the most-

dense reported bat aggregations, including studies on *Miniopterus fuliginosus*[49], *Myotis*
grisescens[65], and *Tadarida brasiliensis*[4,50,66], where bats emerge from the roost at rates of 15 to
500 bats per second, but fly with an average distance of 0.5 meters between individual bats.

We compared the performance of two FM echolocating insectivorous bat species: *Pipistrellus*
*kuhlii (*PK*)* and *Rhinopoma microphyllum (*RM*)*. PK bats emit wideband echolocation signals that
are less prone to jamming than RM bats' narrowband signal[15,67], as wideband signals distribute
energy across a broader frequency range and are thus more robust against interference[9,68] . Our
findings show that PK signals slightly reduce jamming probability (by 9%) and improve wall
detection. However, no significant differences in exit probabilities were noted between the two
species.

Using a simulation allowed us to separate the effects of **acoustic interference (masking)** and
spatial interference (collision avoidance) and revealed new insights into the sensorimotor
strategy that could plausibly be used by real bats. The spatial interference reduced the probability
of exiting the roost from 100% to 87%, while the acoustic masking further decreased it to 63%.
Increasing call intensity had little effect on exit performance, although slightly improving it at high
bat densities. When all bats increased their calling intensity, both desired echoes and masking
signals intensified equally, resulting in only a marginal effect. This was tested by varying call
intensity levels (100-130 dB SPL) in our simulations (Table 1), demonstrating that beyond a
certain level (~110 dB SPL), there is no further benefit in improving obstacle detection. These
results align with previous studies that have drawn similar conclusions[7,24].

Bats constantly adjust their flight speed to their surroundings[69–72] and specifically when
conspecifics are nearby[73]. Our study suggests that the optimal velocity for flying through a
crowded roost ranges from 6 m/sec to 8 m/sec for densities of 2-100 bats/3m^2. Exceeding this
velocity-range led to a significant drop in exit probability due to a significant increase in wall
collisions. We found that this speed did not depend on bat density in accordance with the
observations of Theriault et al.[50]. Notably, the reported velocities of RM when exiting a cave[25] and
PK emergence velocity near the cave[74] are close to the speed that appears optimal, based on our
simulations.

We also tested the effects of wall and conspecific target strengths on navigation. Stronger wall
echoes substantially improved exit probability and reduced obstacle collisions, despite slightly

increasing masking of conspecific echoes (Supplementary Figure 3). In contrast, changes in
conspecific reflectivity had minimal impact, likely because both desired and masking signals
scaled similarly (Supplementary Figure 4). This result may also stem from our model's assumption
that bats slow down, but continue flying at the same direction following a collision with a
conspecific.

Our basic model assumed that bats can distinguish between wall echoes and conspecific echoes,
as demonstrated in previous studies [75–77]. We suggest that this is a feasible assumption because
echoes from cave walls are longer and exhibit distinct spectro-temporal patterns, whereas echoes
from smaller objects, such as conspecifics, are shorter[47,78,79]. However, wall echoes reflected from
conspecific calls might resemble those from the bat's own calls in their amplitude and time-
frequency characteristics [20,73,80]. This led us to question how the misidentification of such echoes
as obstacles might affect navigation. When unable to distinguish between these echoes, the
simulated bats responded to all as if they were their own and thus mis-localized conspecific wall
echoes. The confusion led to a substantial drop in exit performance, with only 15% of the bats
successfully exiting compared to 82% under no-confusion conditions, at a density of 40 bats/3m^2.
At the same time, the collision rate increased markedly from 0.2 to 0.85 collisions per second.
These results demonstrate the vital importance of echo discrimination for successful navigation,
highlighting both the necessity of distinguishing between self and conspecific echoes and the
classic challenge of detecting desired signals in noisy environments. There is a substantial
evidence in the literature supporting the assumption that bats can recognize their own echoes and
reliably distinguish them from those of conspecifics[68,75–77,81].

Previous studies have also demonstrated that bats can aggregate acoustic information received
sequentially over several echolocation calls, effectively constructing an auditory scene in complex
environments[5,82–86]. Bats are also known to emit call sequences in groups, particularly when
spatiotemporal localization demands are high. Studies have recorded sequences of 2-15 grouped
calls, supporting the idea that grouping facilitates echo aggregation[83,87]. Accordingly, we tested
how multi-call clustering process—which included grouping nearby reflectors, removing outliers,
and estimating wall orientation based on these clusters—could assist bats in pathfinding, even
under the assumption of full confusion. At bat densities of 1 to 40 bats/3m^2 with masking, the
multi-call clustering completely restored the collision rate with walls from 0.85 back to 0.2
collisions per second, and significantly improved the exit probability, raising it to 58%, although

it did not entirely eliminate the impact of confusion. Our assumption of total confusion between

echoes from a bat's own calls and those from conspecifics, as well as our relatively simple

clustering model, likely underestimates the true capabilities of real bats when flying in complex

environments.

Navigation in bats involves processing complex sensory inputs and applying effective decision-

making, often requiring an ability to switch strategies[88–94]. Bats possess a highly accurate spatial

memory[82,90,94–96], which is essential for tasks like long-distance migration[51], homing[97], and

maneuvering in cluttered environments[95]. Additionally, they utilize acoustic landmarks to orient

in total darkness[52], occasionally rely on vision[91,92], particularly at the cave edge where light is

available, can passively detect echolocating peers, and perhaps eavesdrop on conspecifics'

echoes[23]. In this study we focused on whether echolocation alone is sufficient for one of the most

difficult orientation tasks that bats perform – exiting a roost at high densities without prior

knowledge of the roost's shape, aside from the initial flight direction. Thus, our echolocation-only

model, which was based on a five-call integration window during most simulations, probably

underestimates real bats' actual performance which also benefits from additional sensory input and

can employ addition navigation strategies by sharing information between each other to coordinate

and optimize the routes, such as manifested by swarming intelligence[33,98,99].

Our model highlights the importance of considering sensory interference in animal behavior

research and illuminates the impressive capabilities of echolocating bats. Additionally, the model

showcases the value of simulations and establishes a framework for future studies on collective

movement and swarming animals, and on robotics in complex environments.

Methods

The simulated bats rely solely on echolocation to detect and locate obstacles and other bats by

analyzing the sound waves they receive. They emit directional echolocation calls and receive the

echoes reflected by roost walls and conspecifics, as well as the calls of conspecifics and the echoes

returning from their calls. The bats adjust their flight trajectory and echolocation behavior based

on the estimated location of the detected objects (range and angle), which deteriorates upon

acoustic interference. The detection of the received signals is based on the mammalian gammatone

filter bank receiver, under the assumption that bats can differentiate between the desired detected

obstacles, conspecifics' echoes, and masking signals. We conducted 2D simulations with varying

number of bats (from 1 to 100) to analyze the flight trajectories with and without masking

interference by conspecifics. In the trials without masking interference the bats successfully

detected walls and conspecifics without any hindrance. While real-world bat navigation occurs in

3D space, the 2D framework represents a worst-case scenario for echolocation-based navigation,

as it increases effective bat density and limits maneuverability compared to a full 3D environment.

This approach provides a conservative test of jamming and collision avoidance while maintaining

computational tractability, allowing for extensive simulation runs to explore different variables

systematically. For a detailed description of the MATLAB simulation see Mazar & Yovel 2020[7].

The simulation arena was designed to mimic a roost with a corridor-like layout, measuring 14.5

meters in length and 2.5 meters in width, featuring a right-angle turn located 5.5 meters before the

exit (see Figure 1A for a top-down view). All bats started at a random position within a 2×1.5 m

area at the far end of the cave, each initiating flight within a 0.1-second window in a random

direction between -30° and +30° relative to the exit (see Figure 1). They employ a simple

navigation algorithm that dynamically adjusts flight direction based on the detected obstacles or

conspecifics (Supplementary Figure 1 and Figure 1D). If no obstacles or conspecifics are detected,

they continue in a correlated random walk with a maximal turning rate of approximately 30

deg/sec. When obstacles are detected, they are first localized with an error (see below and[7]). Then,

if an opening (i.e., a gap of at least 0.5 m between obstacles) is detected, the bats fly through it, if

not, they follow the walls while maintaining a 0.8 m distance from them. When approaching an

obstacle too closely (<1.5 m and at an angle <60º), they execute an obstacle avoidance maneuver.

Close proximity to another bat (<0.4 m) triggers an avoidance maneuver away from the nearest

conspecific. To evaluate the choice of these distances (1.5 m from walls and 0.4 m from other

bats), we tested the sensitivity of the model to conspecific avoidance distances ranging from 0.2

to 1.6 meters across bat densities of 2 to 40 bats/3m². We observed only a modest effect on exit

probability at the highest density, where exit probability increased slightly from 82% to 88% (p =

0.024, t = 2.25, DF = 958). No significant changes were observed in exit time, collision rate, or

jamming probability across other densities or conditions (GLM, with the number of bats and

avoidance distance set as fixed explanatory variables, and the outcome variable being one of: exit

probability, time-to-exit, collision rate, or jamming probability). These findings confirm that the

modeled behavior is largely insensitive to this parameter range.

If the bat collides with a wall, it immediately turns so that its new flight direction is at a 90° angle

to the wall. Collisions between conspecifics, which are common in nature and generally not

disruptive in low velocities, are not explicitly modeled. Instead, during the collision event the bat

keeps decreasing its velocity and changing its flight direction until the distance between bats is

above the threshold (0.4 m). We assume that the primary cost of such interactions arises from the

effort required to avoid collisions resulting in forced changes in flight's direction and speed, rather

than from the collision itself. Each decision relies on a multi-call integration window that records

the estimated locations of detected reflectors from recent echolocation calls (see Supplementary

Figure 2A). By default, this window includes the last five calls, and we systematically tested the

effect of using between 1 and 10 calls. This algorithm functions without any prior knowledge of

the bats' location or the roost's structure. To assess performance, we measured the probability of

successfully exiting the roost within a 15-second window. The time-based exit limit was chosen

because it is approximately twice the average exit time for 40 bats under acoustic interference in

our model, allowing bats sufficient time to correct their trajectory and circle back if they missed

the exit on the first attempt. This threshold keeps simulation times reasonable while still capturing

the key aspects of exit dynamics.

Echolocation behavior and flight speed follow the phases widely reported in insectivorous bats,

categorized as "search," "approach," and "buzz"[55,100–104] with specific echolocation parameters for

Pipistrellus kuhlii (Kuhl's pipistrelle)[70] and *Rhinopoma microphyllum* (greater mouse-tailed bat)[25].

The transition distances between these phases were identical for both species (see Table 2) and are

based on empirical studies documenting hunting and obstacle avoidance behavior[55,56,69,103–105]. In

nature, call parameters (Inter Pulse Interval (IPI), call duration, and start and stop frequencies) are

primarily shaped by the target distance and echo strength. Accordingly, there is little difference in

echolocation between prey capture and obstacles-related maneuvers, aside from intensity

adjustments based on target strength [56,57,87,106]. In our study, due to the dense cave environment,

the bats are found to operate in the approach phase nearly all of the time, which is consistent with

natural cave emergence behavior, where they are navigating through a cluttered environment rather

than engaging in open-space search. Our model was designed to remain as simple as possible while

relying on conservative assumptions that may underestimate bat performance. If, in reality, bats

fine-tune their echolocation calls even earlier or more precisely during navigation than assumed,

our model would still conservatively reflect their actual capabilities.

The simulated echolocation call consists of the dominant harmony of the bat's FM Chirp (1st

harmony of the PK and 2nd harmony of the RM). The echolocation signals used in our simulation

were modeled as logarithmic FM chirps, implemented using the MATLAB built-in function (e.g.,

chirp(t, f0, t1, f1, 'logarithmic')). This approach aligns with the known nonlinear frequency

modulation characteristics of *Pipistrellus kuhlii* (PK) and *Rhinopoma microphyllum* (RM). Table

2 provides the specific echolocation parameters used in the model, based on Kalko 1995[69], and

Goldshtein 2025 [25]. During the search phase, the bats fly at a nominal velocity of 6 m/sec, reducing

it by half during the approach phase and continuously adjusting their speed according to the

relative direction of the target, using a delayed linear adaptive law[7,103,107]. The maneuverability of

the bats is constrained to a maximum of 4 m/sec², limiting both angular and linear accelerations.

Additionally, our model includes random individual variations in terminal frequencies, assuming

a normal distribution with a standard deviation of 1 kHz across the bats.

Pipistrellus kuhlii (Kuhl's pipistrelle)						
Flight phase	Search	Approach		Buzz		
Parameter		Start	End	Terminal 1 start	Terminal 1 end	Terminal 2
Inter Pulse Interval [ms]	100	70	35	18	6	5
Call duration [ms]	7	5	2	2	1	0.3
Terminal frequency [kHz]	39	39	39	39	39	39
Chirp bandwidth [kHz]	8	35	30	30	20	20
Call intensity [dB-SPL]	120	120	90	90	80	80
Distance to target [m]	>1.2	1.2	0.4	0.4	0.2	<0.2
Rhinopoma microphyllum (greater mouse-tailed bat)						
Flight phase	Search	Approach		Buzz		
Parameter		Start	End	Terminal 1 start	Terminal 1 end	Terminal 2
Inter Pulse Interval [ms]	100	80	20	18	10	9
Call duration [ms]	12	7	2	2	1.5	0.75
Terminal frequency [kHz]	26	26	26	26	26	23.5
Chirp bandwidth [kHz]	3	4	5	3	3	3
Call intensity [dB-SPL, @0.1m]	120	120	90	90	80	80
Distance to target [m]	>1.2	1.2	0.4	0.4	0.2	<0.2

The sound intensity of the echoes generated by the bat's own calls and those of its conspecifics
are calculated using the sonar equation[7,108] (pp. 196-198), as shown in Equation 1, geometrical
relations are according to Supplementary Figure 5. The received levels of the masking calls are
determined by using the Friis transmission equation[109], as shown in Equation 2. All signal levels
were simulated and reported in dB-SPL, referenced to 0.1 meters from the emitting bat. Bats are
modeled acoustically as spherical reflectors with a fixed target strength of -23dB assuming
reference distance 1 meter, reflecting sound isotropically. This approximates a sphere with a radius
of 0.15 m, corresponding to the approximate wingspan of *Rhinopoma microphyllum* (RM) [25,110].
While target strength can vary with wing posture and body geometry, we chose a representative
value within the reported biological range for simplicity and model consistency. Our own
measurement of a 3D-printed RM bat yielded a target strength of –32 dB, and a sensitivity analysis
(Supplementary Figure 4) showed that model performance was only mildly affected across a wide
range of target strengths (see Supplementary Figure 4). This supports the robustness of our
approach to different sized bats. Walls are modeled as composites of individual reflectors placed
20 cm apart; each treated as a sphere with a 20 cm radius and a target strength of -22.5dB. For
simplicity, in our model, the head is aligned with the body, therefore the direction of the
echolocation beam is the same as the direction of the flight. The directivity of the calls and the
received echoes is defined by the piston model[7,102] with radii of 3 mm for the mouth-gap and 7
mm for the ear. The directivity is not directly influenced by velocity but follows behavioral
dependent frequency changes. As the bat transitions from search to approach to buzz phases, it
emits higher-frequency calls, leading to increased directivity. This shift coincides with a natural
reduction in speed during the approach phase. Echo delays are calculated as the two-way travel
time of the signals from the emitter to the target.

Equation 1: $P_r = P_t \cdot \dfrac{G_t(\phi_{target},f) \cdot G_r(\phi_{target},f)\lambda^2}{(4\pi)^3 D^4} \cdot 10^{-2\alpha_{att}(f)/10 \cdot (D-0.1)} \cdot \sigma(f)$

Equation 2: $P_{mask} = P_t G_t(\phi_{t_x r_x}, f) G_r(\phi_{r_x t_x}, f) \cdot \left(\dfrac{\lambda}{4\pi D_{txrx}}\right)^2 10^{-\alpha_{att} \cdot (D-0.1)}$

Equation 3: $P_{echoesFromMasking} = P_t \cdot \frac{G_t(\phi_{t_x}, f) \cdot G_r(\phi_{r_x}, f) \lambda^2}{(4\pi)^3 D_{t_x}{}^2 D_{r_x}{}^2} 10^{-\alpha_{att} \cdot (D_{t_x} + D_{r_x} - 0.2)} \cdot \sigma(f)$

where,

P_r: level of the received signal [SPL]

P_t : level of the transmitted call [SPL]

P_{mask} : level of the masking signal as received by the bat [SPL]

$P_{echoesFromMasking}$: level of the echoes reflected by conspecifics and received by the bat [SPL]

$G_t(\phi, f)$: gain of the transmitter (mouth of the bat, piston model), as a function of azimuth and frequency (*f*) [numeric]

$G_r(\phi, f)$: gain of the receiver (ears of the bat, piston model) [numeric]

ϕ_{target} : the angle between the bat and the reflected object [rad]

D: distance between the bat and the target [m]

$\phi_{t_x r_x}, D_{t_x r_x}$: the angle [rad], and the distance [m] between the transmitting conspecific and the receiving focal bat (from the transmitter's perspective)

$\phi_{r_x t_x}, D_{r_x t_x}$: the angle [rad], and the distance [m] between the receiving bat and the transmitting bat (from the receiver's perspective)

ϕ_{t_x} : the angle [rad], between the masking bat and target (from the transmitter's perspective)

$\alpha_{att}(f)$: atmospheric absorption coefficient for sound [dB/m]

$\sigma(f)$: SONAR cross-section of the target [m^2]

λ: The wavelength of the signal [m]

To maintain model simplicity, we did not incorporate Doppler effects in the echolocation model.
While Doppler shifts can affect frequency perception, their impact on jamming and navigation
performance is minimal in this context[111]. Moreover, the inter-individual random signals
frequencies were larger than the expected Dopplers. In addition, the model does not assign echoes
to earlier calls if their delays exceed the bat's own Inter-Pulse Interval (IPI), and thus does not
simulate pulse-echo ambiguity.

To model the detection process in the bat's cochlea, we employed a monoaural filter bank
receiver[47,112,113] consisting of 80 channels, each with three components: (i) a gammatone filter of
order 8, acting as a bandpass filter with center frequencies logarithmically scaled between 10kHz
and 80kHz[7]; (ii) a half-wave rectifier; and (iii) a lowpass filter (Butterworth, fc=8kHz, order=6).
Object detection and distance estimation are conducted using Saillant's method[7,47,114], based on
the sum of detections in the active channels, see Figure 1C, D. Initially, a de-chirping process
calculates the reference frequency-delay by detecting the peak in the response of each channel to
the emitted call in a noise-free environment. Subsequently, the received signal, containing both
desired echoes and masking sounds, passes through the filter bank. In each channel, all peaks
above a threshold level are detected and time-shifted by the de-chirp reference. The detection
threshold in each channel was set to the higher of two values: either 7 dB above the noise floor (0
dB-SPL) or the maximum received signal level minus 70 dB, thereby enforcing a dynamic range
of 70dB. Peaks from all channels are aggregated in 5 µs windows and convolved with a Gaussian
kernel with σ=5 µs. Output peaks that exceed the threshold level, set at 10% of the number of
active channels, and fall within a time window of 100µs around the expected delay, are considered
successful detections.

To evaluate the impact of acoustic interference, we conducted the detection procedure twice. The
first, termed "interference-free detection", comprised only the desired echoes, with white Gaussian
noise at a level of 0 dB-SPL and without masking signals. The second, termed "full detection"
comprised the desired echoes, Gaussian noise, and the masking signals. Detected echoes in the full
detection were defined by the strongest peak within a four-millisecond window (three milliseconds
before and one millisecond after, accounting for forward and backward masking [24,115–117]) detected
above the threshold within 100µs of the interference-free detections. If the detected peak in the
full detection condition was delayed by more than 100 µs compared to the interference-free case,
it was defined as a miss-detection. Peaks with smaller timing shifts were considered **detection**
with timing errors. Jammed echoes were defined as echoes that were detected under the
interference-free condition but not detected under the full detection condition. The **jamming**
probability was calculated as the ratio of jammed echoes in the full detection condition to the
detected echoes in the interference-free condition.

After detection, the bat estimates the range and the Direction of Arrival (DOA) of the reflecting
objects. The range is determined by the delay of the detected echo, including any errors derived

from the filter-bank process in the "full detection" process (i.e., including all masking
signals).[7,110,113]. The direction is not explicitly estimated through binaural processing. Instead,
based on previous studies [115,118], we assumed that bats can estimate the direction of arrival with an
angular error that depends on the Signal-to-Noise Ratio (SNR) and the angle. The inputs to this
process include the peak level of the desired echo, the noise level, and the level of acoustic
interference. The output is the estimated direction of arrival with a random error applied based on
the SNR. At an angle of 0º and an SNR of 10 dB, the standard deviation of the error is 1.5º [119] and
[7] (Equation 4), with the error capped at a maximum of 3º in our model.

Equation 4: $DOA_{error} = \sqrt{(k_2/_{SNR})^2 + (k_3 + k_4 \cdot sin(\phi))^2}$

where, k_2, k_3, and k_4 are constants chosen to produce a DOA error consistent with the range
described above.

To evaluate the impact of the assumption that bats can distinguish between echoes caused by their
own calls and those caused by other bats (i.e., conspecifics' reflectors), we tested an alternative
model in which the simulated bats treat all echoes reflected from walls as if they have originated
from their own calls The distance to reflectors of conspecifics' calls is estimated based on the time
difference between the echo and the bat's last call. The direction of arrival is estimated by the
angle between the bat and the physical reflector, with an added random error (the same process
used for their own echoes).

In real bats, spatial processing in the brain involves integrating auditory and spatial information
over time to construct a coherent map of the environment [5,68]. This neural computation is crucial
for navigation and prey detection in complex environments. To examine whether spatial
integration mitigates the confusion problem, we added a 'multi-call clustering' module that was
based on the sensory information obtained within a one-second memory window. The clustering
comprised the following steps: (i) clustering all detections in memory into groups with a maximum
internal distance of 10 cm; (ii) reconstructing the estimated walls positions and directions based
on the average of clusters that include at least two detections (rather than relying on single
reflections); and (iii) identifying openings between reconstructed wall edges ranging from 0.5 to
2.25 meters in width, see Supplementary Figure 1 and Supplementary Figure 2B. The model

assumes that bats store echo locations in an allocentric x-y coordinate system, transforming detections from a local to a global spatial framework. Collision avoidance is based not only on the integrated spatial representation but also on immediate echoes from the last call (prior to clustering), including potential uncorrected false detections and localization errors, which are independently processed for real-time evasive maneuvers.

Statistical analysis

Statistical analysis and the roost-exit model were conducted using MATLAB© 2023a.

Tests were performed with a significance level of 0.05. For each simulated scenario, we examined the effect of the various parameters on exit probability, time-to-exit, collision rate, and the jamming probability, using Generalized Linear Models (GLMs). The GLM tests were executed with MATLAB built-in function **'fitglm()'**. Probability variables (such as exit and jamming probabilities) were treated as binomially distributed; rate variables (such as collision rate) were treated as Poisson distributed, and all other variables were considered normally distributed. Unless otherwise stated, all explaining variables were set as fixed factors. All statistical analyses, including the statistical test and the corresponding sample sizes, are described throughout the text and summarized in Table 1. Standard errors are calculated across all individuals within each scenario, without distinguishing between different simulation trials.

Data availability

All data and codes generated during this study are included in the manuscript and supporting files. Source code files have been uploaded with a Graphical User Interface and a readme file for explanation. Data are available at zenodo and github:

https://zenodo.org/records/16992617 (link)

https://github.com/omermazar/Colony-Exit-Bat-Simulation/tree/main (link)

Supplementary

Supplementary Movie 1

link

Supplementary Figure 1: Decision-making in echolocation-based pathfinding

This diagram illustrates the sensorimotor decision-making process based solely on echolocation.

The process starts with the emission of an echolocation call (1) and the reception of echoes and

interfering signals (2), followed by sensory processing for detection, range estimation, and

direction of arrival (DOA) (3). After integrating detections over a 1–10 call window (4), the bat

engages in **crash avoidance** (5) by evaluating the proximity of conspecifics and obstacles directly

ahead. If either is too close, the bat turns in the opposite direction of the detected obstacle, by

applying maximum angular velocity away from it (e.g., if the obstacle is on the right, the bat turns

left). If no immediate threat is detected, the bat proceeds to **pathfinding** (6). During pathfinding,

it checks for obstacles and, if an opening is detected, flies toward the gap's center. Without the

optional **multi-call clustering process** (green), the bat simply integrates detections and flies

toward the farthest detected obstacle, interpreting it as a wall edge. If the multi-call clustering is

included (9), a one-second short memory aids in clustering detections, estimating wall edges, and

identifying openings, while also allowing the bat to follow walls at a constant distance.

Throughout, the bat continuously adjusts echolocation parameters (8) and controls flight direction

and velocity (7) based on ongoing sensory information and decision-making.

This figure demonstrates the effect of multi-call integration under non-confusing conditions. The upper-right panel shows the position of the focal bat (black) and nine conspecifics (red) within the roost corridor, with a zoomed-in view of the gray rectangle provided in Panels A–C. **(A)** When the integration window is set to zero calls (no memory), the bat relies solely on the latest call. Green circles and squares represent detected reflectors, while red Xs indicate missed (jammed) detections. Notably, the left wall of the corridor remains undetected due to jamming. **(B, C)** Increasing the integration window to five calls (magenta squares) and ten calls (black squares) accumulates detections from prior calls, improving coverage of the environment. In this basic integration model, each detection is treated independently, without clustering.

(D1, D2) Magnified views of the grey regions indicated in Panel C, comparing detections across

0, 5, and 10-call windows (green, magenta, and black, respectively), illustrating how extended

memory improves detection robustness. Note that the X-Y aspect ratios in D1 and D2 differ from

the main panels to enhance visibility of spatial distributions.

Supplementary Figure 2B: Multi-Call Clustering Example

This figure illustrates the multi-call clustering algorithm under full-confusion conditions. (A) A
focal bat (black) and four conspecifics (red) are shown in the lower corridor. (B) A zoom-in of the
gray rectangle in (A). Black ovals represent detections from the last call; red X's indicate jammed
echoes; black squares represent all detections stored across the integration window (before
clustering), each subject to localization error. When not applying multi-call clustering – the bat
would rely on all of these dots as reflectors. Under full confusion, the bat cannot distinguish self-
echoes from conspecific echoes, leading to false detections (red diamonds). Detections are
clustered when a reflector is detected twice or more within a 10 cm radius (green squares). The
clustered reflectors are used to estimate wall directions (blue dashed line) and detect possible gaps
(not shown). As a result of to the multi-call clustering algorithm, most false detections are removed
as outliers, except for one erroneous cluster (Panel A). Collision avoidance maneuvers are based
on both the clustered obstacles and the raw detections from the latest call (empty black ovals).

 Supplementary Figure 3: Sensitivity of exit performance to obstacle target strength

This figure shows how changes in the acoustic target strength of the cave walls affect navigation performance across five bat densities (1, 5, 10, 40, and 100 bats/3 m²). Target strength values ranged from –33 dB to –3 dB, corresponding to spherical reflectors with approximate radii from 0.05 m to 1.5 m. Overall, increasing obstacle target strength significantly influenced exit performance, primarily by reducing the probability of obstacle jamming and thereby improving detection. **(A) Exit Probability** increased with obstacle target strength across all densities, with a maximal increase of 64% for a density of 100 bats (p $\ll 10^{-10}$, t = 28.5, DF = 8157, GLM)**. (B) Time to Exit** decreased significantlywith increasing obstacle target strength, with a maximal reduction of approximately 2.8 seconds at a density of 10 bats (p $\ll 10^{-10}$, t = –22.2, DF = 6920,

GLM) . **(C) Conspecific Collision Rate** increased slightly with stronger obstacle echoes (p $\ll$

10^{-10}, t = 27.6, DF = 8157, GLM). **(D) Obstacle Collision Rate** decreased significantly with

increasing target strength (p $\ll 10^{-10}$, t = -10.7, DF = 8157, GLM), reflecting better detection of

walls and structures. **(E) Obstacle Jamming Probability** decreased consistently (p $\ll 10^{-10}$, t =

-19.8, DF = 8157, GLM). **(F) Conspecific Jamming Probability** increased with obstacle target

strength (p $\ll 10^{-10}$, t = 27.6, DF = 8157, GLM).

These results suggest that stronger wall echoes improve environmental awareness at the cost of

slightly increased masking of conspecific echoes. Despite this, the overall performance—

particularly exit probability and reduced obstacle collisions—improves significantly.

In all panels, circles represent means and bars represent standard errors. The error bars are

present but very small due to the large number of simulation repetitions, and thus may not be

visually noticeable at the plotted scale. See Table 1 for the number of simulated bats.

 Supplementary Figure 4: Sensitivity of exit performance to conspecific's target strength

This figure shows how changes in the acoustic target strength of conspecifics affect navigation performance across four bat densities (1, 5, 10, and 40 bats/3 m²). Overall, our results indicate that target strength has a relatively minor impact on performance, likely because it affects both desired echo signals and masking signals equally. Interestingly, this analysis also suggests that our model is more sensitive to the bat's response to nearby conspecifics than to the physical collision impact itself. **(A)** Exit probability was not significantly affected by conspecific target strength (p=0.28, t=-1.09, DF=5757, GLM, see details in Table 1). Note that the performance curves for densities of 1 and 5 bats overlap almost completely. **(B)** Time-to-exit increased with target strength at high density, with a maximal effect size of ~1 second at 40 bats (p = 0.003, t = 3.02, DF = 5578). **(C, D)** Collision rates with conspecifics decreased significantly with stronger target strength (p =

0.0002, t = –3.7, DF = 5757), while collisions with obstacles remained statistically unchanged (p

= 0.23, t = 1.18, DF = 5757). **(E, F)** Jamming probability was not significantly affected for either

conspecific or obstacle echoes (p = 0.6, t = –0.51, DF = 4762; p = 0.19, t = 1.31, DF = 5757,

respectively). This aligns with the notion that both useful and interfering signals scale similarly

with target strength. Importantly, the probability of detecting a conspecific located within 1 meter

increased substantially with higher target strength, improving from 25% to 43% at 40 bats (p <

10^{-10}, t = 6.45, DF = 4162).

In all panels, circles represent means and bars represent standard errors. The error bars are present

but very small due to the large number of simulation repetitions, and thus may not be visually

noticeable at the plotted scale. See Table 1 for the number of simulated bats.

Supplementary Figure 5: Angles and distances for two bats and two reflecting objects.

Bat1 receives a reflected echo from Prey1 or a stationary obstacle located at a distance of D from

it, with an angle ϕ_{target} relative to its flight direction (red arrow 1). Prey1 is also within the

detection range of Bat1, depicted by the green shaded piston area. Bat1 also receives masking sounds from Bat2. The echolocation signals emitted by Bat2 arrive at the ear of Bat1 at an angle $\phi_{t_x r_x}$ relative to its flight direction and from a distance of $D_{t_x r_x}$ (red arrow 2). Additionally, the echolocation signals of Bat2 are reflected by Prey2, before being received by Bat 1. These reflected signals act as masking signals at a relative angle of angle ϕ_{r_x}, and from a distance of D_{r_x} from Bat1.

References

1. Glover, A. M. & Altringham, J. D. Cave selection and use by swarming bat species. *Biol Conserv* **141**, 1493–1504 (2008).

2. Hristov, N. I., Betke, M., Theriault, D. E. H., Bagchi, A. & Kunz, T. H. Seasonal variation in colony size of brazilian free-tailed bats at Carlsbad cavern based on thermal imaging. *J Mammal* **91**, 183–192 (2010).

3. Vanderelst, D., Holderied, M. W. & Peremans, H. Sensorimotor Model of Obstacle Avoidance in Echolocating Bats. *PLoS Comput Biol* **11**, e1004484 (2015).

4. Gillam, E. H., Hristov, N. I., Kunz, T. H. & McCracken, G. F. Echolocation behavior of Brazilian free-tailed bats during dense emergence flights. *J Mammal* **91**, 967–975 (2010).

5. Ulanovsky, N. & Moss, C. F. What the bat's voice tells the bat's brain. *Proc Natl Acad Sci U S A* **105**, 8491–8498 (2008).

6. Lin, Y., Abaid, N. & Müller, R. Bats adjust their pulse emission rates with swarm size in the field. *Citation: The Journal of the Acoustical Society of America* **140**, 4318 (2016).

7. Mazar, O. & Yovel, Y. A sensorimotor model shows why a spectral jamming avoidance response does not help bats deal with jamming. *Elife* **9**, 1–23 (2020).

8. Takahashi, E., Hyomoto, K., Riquimaroux, H., Watanabe, Y. & Ohta, T. Adaptive changes in echolocation sounds by Pipistrellus abramus in response to artificial jamming sounds. *Journal of Experimental Biology* **217**, 2885–2891 (2014).

9. Ulanovsky, N., Fenton, M. B., Tsoar, A. & Korine, C. Dynamics of jamming avoidance in echolocating bats. *Proceedings of the Royal Society B: Biological Sciences* **271**, 1467–1475 (2004).

10. Gillam, E. H. & Montero, B. K. Influence of call structure on the jamming avoidance response of echolocating bats. *J Mammal* **97**, 14–22 (2016).

11. Bates, M. E., Stamper, S. A. & Simmons, J. A. Jamming avoidance response of big brown
bats in target detection. *Journal of Experimental Biology* **211**, 106–113 (2008).

12. Luo, J. & Moss, C. F. Echolocating bats rely on audiovocal feedback to adapt sonar signal
design. *Proceedings of the National Academy of Sciences* **114**, 10978–10983 (2017).

13. Corcoran, A. J. & Conner, W. E. Bats jamming bats: Food competition through sonar
interference. *Science (1979)* (2014).

14. Cvikel, N. *et al.* Bats aggregate to improve prey search but might be impaired when their
density becomes too high. *Current Biology* **25**, 206–211 (2015).

15. Cvikel, N. *et al.* On-board recordings reveal no jamming avoidance in wild bats. *Proceedings
of the Royal Society B: Biological Sciences* **282**, 20142274 (2015).

16. Götze, S., Koblitz, J. C., Denzinger, A. & Schnitzler, H. U. No evidence for spectral jamming
avoidance in echolocation behavior of foraging pipistrelle bats. *Sci Rep* **6**, 1–13 (2016).

17. Fawcett, K., Jacobs, D. S., Surlykke, A. & Ratcliffe, J. M. Echolocation in the bat,
Rhinolophus capensis: the influence of clutter, conspecifics and prey on call design and
intensity. *Biol Open* **4**, 693–701 (2015).

18. Gillam, E. H., Ulanovsky, N. & McCracken, G. F. Rapid jamming avoidance in biosonar.
Proceedings of the Royal Society B: Biological Sciences **274**, 651–660 (2007).

19. Giuggioli, L., McKetterick, T. J. & Holderied, M. Delayed Response and Biosonar
Perception Explain Movement Coordination in Trawling Bats. *PLoS Comput Biol* **11**,
1004089 (2015).

20. Obrist, M. K. Flexible bat echolocation: the influence of individual, habitat and conspecifics
on sonar signal design. *Behav Ecol Sociobiol* **36**, 207–219 (1995).

21. Krivoruchko, K. *et al.* A social foraging trade-off in echolocating bats reveals that they
benefit from some conspecifics but are impaired when many are around. *Proc Natl Acad Sci
U S A* **121**, e2321724121 (2024).

22. Hristov, N. I., Betke, M. & Kunz, T. H. Applications of thermal infrared imaging for research
in aeroecology. *Integr Comp Biol* **48**, 50–59 (2008).

23. Lin, Y. & Abaid, N. Modeling perspectives on echolocation strategies inspired by bats flying
in groups. *J Theor Biol* **387**, 46–53 (2015).

24. Beleyur, T. & Goerlitz, H. R. Modeling active sensing reveals echo detection even in large
groups of bats. *Proc Natl Acad Sci U S A* **116**, 26662–26668 (2019).

25. Goldshtein, A. *et al.* Onboard recordings reveal how bats maneuver under severe acoustic
interference. *Proceedings of the National Academy of Sciences* **122**, e2407810122 (2025).

26. Pearce, D. J. G., Miller, A. M., Rowlands, G. & Turner, M. S. Role of projection in the
control of bird flocks. *Proc Natl Acad Sci U S A* **111**, 10422–10426 (2014).

27.   Bastien, R. & Romanczuk, P. A model of collective behavior based purely on vision. *Sci*
832   *Adv* **6**, eaay0792 (2020).

833   28.   Davidson, J. D. *et al.* Collective detection based on visual information in animal groups.
834   *Journal of the Royal Society* **18**, 2021.02.18.431380 (2021).

835   29.   Aidan, Y., Bleichman, I. & Ayali, A. Pausing to swarm: locust intermittent motion is
836   instrumental for swarming-related visual processing. *Biol Lett* **20**, 20230468 (2024).

837   30.   Pitcher, T. J., Partridge, B. L. & Wardle, C. S. A blind fish can school. *Science (1979)* **194**,
838   963–965 (1976).

839   31.   Partridge, B. L. The Structure and Function of Fish Schools. **246**, 114–123 (1982).

840   32.   Strandburg-Peshkin, A. *et al.* Visual sensory networks and effective information transfer in
841   animal groups. *Current Biology* **23**, R709–R711 (2013).

842   33.   Youssefi, K. A. R. & Rouhani, M. Swarm intelligence based robotic search in unknown
843   maze-like environments. *Expert Syst Appl* **178**, (2021).

844   34.   Cheraghi, A. R., Shahzad, S. & Graffi, K. Past, Present, and Future of Swarm Robotics. in
845   *Proceedings of SAI Intelligent Systems Conference* vol. 296 190–233 (Springer, 2021).

846   35.   Faria Dias, P. G. *et al.* Swarm robotics: A perspective on the latest reviewed concepts and
847   applications. *Sensors* **21**, 2062 (2021).

848   36.   Couzin, I. D., Krause, J., James, R., Ruxton, G. D. & Franks, N. R. Collective Memory and
849   Spatial Sorting in Animal Groups. *J Theor Biol* **218**, 1–11 (2002).

850   37.   Attanasi, A. *et al.* Collective Behaviour without Collective Order in Wild Swarms of Midges.
851   *PLoS Comput Biol* **10**, (2014).

852   38.   Gautrais, J. *et al.* Deciphering Interactions in Moving Animal Groups. *PLoS Comput Biol* **8**,
853   e1002678 (2012).

854   39.   Nagy, M., Ákos, Z., Biro, D. & Vicsek, T. Hierarchical group dynamics in pigeon flocks.
855   *Nature 2010 464:7290* **464**, 890–893 (2010).

856   40.   Parrish, J. K. & Edelstein-Keshet, L. Complexity, Pattern, and Evolutionary Trade-Offs in
857   Animal Aggregation. *Science (1979)* **284**, 99–101 (1999).

858   41.   Sumpter, D. J. T., Krause, J., James, R., Couzin, I. D. & Ward, A. J. W. Consensus Decision
859   Making by Fish. *Current Biology* **18**, 1773–1777 (2008).

860   42.   Bialek, W. *et al.* Statistical mechanics for natural flocks of birds. *Proceedings of the National*
861   *Academy of Sciences* **109**, 4786–4791 (2012).

862   43.   Couzin, I. D., Krause, J., Franks, N. R. & Levin, S. A. Effective leadership and decision-
863   making in animal groups on the move. *Nature* **433**, 513–516 (2005).

864   44.   Bode, N. W. F., Franks, D. W. & Wood, A. J. Limited interactions in flocks: Relating model
865   simulations to empirical data. *J R Soc Interface* **8**, 301–304 (2011).

866   45.   Jhawar, J. *et al.* Noise-induced schooling of fish. *Nature Physics 2020 16:4* **16**, 488–493
867   (2020).

868   46.   Rosenthal, S. B., Twomey, C. R., Hartnett, A. T., Wu, H. S. & Couzin, I. D. Revealing the
869   hidden networks of interaction in mobile animal groups allows prediction of complex
870   behavioral contagion. *Proc Natl Acad Sci U S A* **112**, 4690–4695 (2015).

871   47.   Sanderson, M. I., Neretti, N., Intrator, N. & Simmons, J. A. Evaluation of an auditory model
872   for echo delay accuracy in wideband biosonar. *J Acoust Soc Am* **114**, 1648–1659 (2003).

873   48.   Neretti, N., Sanderson, M. I., Intrator, N. & Simmons, J. A. Time-frequency model for echo-
874   delay resolution in wideband biosonar. *J Acoust Soc Am* **113**, 2137–2145 (2003).

875   49.   Fujioka, E. *et al.* Three-Dimensional Trajectory Construction and Observation of Group
876   Behavior of Wild Bats During Cave Emergence. *Journal of Robotics and Mechatronics* **33**,
877   556–563 (2021).

878   50.   Theriault, D. *et al.* Reconstruction and Analysis of 3D Trajectories of Brazilian Free-Tailed
879   Bats in Flight. *CS Department, Boston University* (2010).

880   51.   Tsoar, A. *et al.* Large-scale navigational map in a mammal. *Proc Natl Acad Sci U S A* **108**,
881   E718–E724 (2011).

882   52.   Jensen, M. E., Moss, C. F. & Surlykke, A. Echolocating bats can use acoustic landmarks for
883   spatial orientation. *Journal of Experimental Biology* **208**, 4399–4410 (2005).

884   53.   Jones, T. K. & Conner, W. E. The jamming avoidance response in echolocating bats.
885   *Commun Integr Biol* **12**, 10–13 (2019).

886   54.   Sabol, B. M. & Hudson, M. K. Technique using thermal infrared-imaging for estimating
887   populations of gray bats. *J Mammal* **76**, (1995).

888   55.   Betke, M. *et al.* Thermal Imaging Reveals Significantly Smaller Brazilian Free-Tailed Bat
889   Colonies Than Previously Estimated. *J Mammal* **89**, 18–24 (2008).

890   56.   Tressler, J. & Smotherman, M. S. Context-dependent effects of noise on echolocation pulse
891   characteristics in free-tailed bats. *J Comp Physiol A Neuroethol Sens Neural Behav Physiol*
892   **195**, 923–934 (2009).

893   57.   Schnitzler, H.-U. & Kalko, E. K. V. Echolocation by Insect-Eating Bats: We define four
894   distinct functional groups of bats and find differences in signal structure that correlate with
895   the typical echolocation tasks faced by each group. *Bioscience* **51**, 557–569 (2001).

896   58.   Kalko, E. K. V. Insect pursuit, prey capture and echolocation in pipistrelle bats
897   (Microchirptera). *Anim Behav* **50**, 861–880 (1995).

59. Schnitzler, H., Kalko, E. & Miller, L. How the Bat, Pipistrellus Kuhli, Hunts for Insects.
Animal Sonar 619–623 (1988).

60. Taub, M. & Yovel, Y. Segregating signal from noise through movement in echolocating
bats. *Sci Rep* **10**, 1–10 (2020).

61. Taub, M., Mazar, O. & Yovel, Y. Pregnancy-related sensory deficits might impair foraging
in echolocating bats. *BMC Biology 2023 21:1* **21**, 1–9 (2023).

62. Fawcett, K. & Ratcliffe, J. M. Clutter and conspecifics: a comparison of their influence on
echolocation and flight behaviour in Daubenton's bat, Myotis daubentonii. *J Comp Physiol*
A Neuroethol Sens Neural Behav Physiol **201**, 295–304 (2015).

63. Grodzinski, U., Spiegel, O., Korine, C. & Holderied, M. W. Context-dependent flight speed:
Evidence for energetically optimal flight speed in the bat Pipistrellus kuhlii? *Journal of*
Animal Ecology **78**, 540–548 (2009).

64. Yovel, Y., Melcon, M. L., Franz, M. O., Denzinger, A. & Schnitzler, H. U. The voice of
bats: How greater mouse-eared bats recognize individuals based on their echolocation calls.
PLoS Comput Biol **5**, e1000400 (2009).

65. Kazial, K. A., Burnett, S. C. & Masters, W. M. Individual and Group Variation in
Echolocation Calls of Big Brown Bats, Eptesicus Fuscus (Chiroptera: Vespertilionidae) . *J*
Mammal **82**, 339–351 (2001).

66. Kazial, K. A., Kenny, T. L. & Burnett, S. C. Little brown bats (Myotis lucifugus) recognize
individual identity of conspecifics using sonar calls. *Ethology* **114**, 469–478 (2008).

67. Yovel, Y., Franz, M. O., Stilz, P. & Schnitzler, H. U. Complex echo classification by echo-
locating bats: a review. *Journal of Comparative Physiology A* **197**, 475–490 (2010).

68. Schnitzler, H. U., Moss, C. F. & Denzinger, A. From spatial orientation to food acquisition
in echolocating bats. *Trends Ecol Evol,* 386-394 (2003).

69. Ratcliffe, J. M. *et al.* Conspecifics influence call design in the Brazilian free-tailed bat,
Tadarida brasiliensis. *Can J Zool* **82**, 966–971 (2004).

70. Beetz, M. J. & Hechavarría, J. C. Neural Processing of Naturalistic Echolocation Signals in
Bats. *Front Neural Circuits* **16**, 899370 (2022).

71. Yovel, Y. & Ulanovsky, N. Bat Navigation. *The Curated Reference Collection in*
Neuroscience and Biobehavioral Psychology 333–345 (2017).

72. Moss, C. F. & Surlykke, A. Probing the natural scene by echolocation in bats. *Front Behav*
Neurosci **4**, 33 (2010).

73. Moss, C. F. & Surlykke, A. Auditory scene analysis by echolocation in bats. *Citation: The*
Journal of the Acoustical Society of America **110**, 2207 (2001).

74. Chili, C., Xian, W. & Moss, C. F. Adaptive echolocation behavior in bats for the analysis of
auditory scenes. *Journal of Experimental Biology* **212**, 1392–1404 (2009).

75. Salles, A., Diebold, C. A. & Moss, C. F. Echolocating bats accumulate information from
acoustic snapshots to predict auditory object motion. *Proc Natl Acad Sci U S A* **117**, 29229–
29238 (2020).

76. Kothari, N. B., Wohlgemuth, M. J., Hulgard, K., Surlykke, A. & Moss, C. F. Timing matters:
Sonar call groups facilitate target localization in bats. *Front Physiol* **6**, 168 (2014).

77. Corcoran, A. J. & Moss, C. F. Sensing in a noisy world: lessons from auditory specialists,
echolocating bats. *Journal of Experimental Biology* **220**, 4554–4566 (2017).

78. Munoz, N. E. & Blumstein, D. T. Multisensory perception in uncertain environments.
Behavioral Ecology **23**, 457–462 (2012).

79. Daria Genzel, Yossi Yovel & Michael M. Yartsev. Neuroethology of bat navigation. *Current
Biology* **28**, R997–R1004 (2018).

80. Boonman, A., Bar-On, Y., Cvikel, N. & Yovel, Y. It's not black or white-on the range of
vision and echolocation in echolocating bats. *Front Physiol* **4**, 248 (2013).

81. Danilovich, S. & Yovel, Y. Integrating vision and echolocation for navigation and perception
in bats. *Sci Adv* **5**, eaaw6503 (2019).

82. Harten, L., Katz, A., Goldshtein, A., Handel, M. & Yovel, Y. The ontogeny of a mammalian
cognitive map in the real world. *Science (1979)* **369**, 194–197 (2020).

83. Prat, Y. & Yovel, Y. Decision making in foraging bats. *Curr Opin Neurobiol* **60**, 169–175
(2020).

84. Barchi, J. R., Knowles, J. M. & Simmons, J. A. Spatial memory and stereotypy of flight
paths by big brown bats in cluttered surroundings. *Journal of Experimental Biology* **216**,
1053–1063 (2013).

85. Geva-Sagiv, M., Las, L., Yovel, Y. & Ulanovsky, N. Spatial cognition in bats and rats: from
sensory acquisition to multiscale maps and navigation. *Nature Reviews Neuroscience 2015
16:2* **16**, 94–108 (2015).

86. Gunier, W. J. & Elder, W. H. Experimental Homing of Gray Bats to a Maternity Colony in
a Missouri Barn. *American Midland Naturalist* **86**, 502 (1971).

87. Garnier, S., Gautrais, J. & Theraulaz, G. The biological principles of swarm intelligence.
Swarm Intelligence **1**, 3–31 (2007).

88. Fischer, D., Mostaghim, S. & Albantakis, L. How swarm size during evolution impacts the
behavior, generalizability, and brain complexity of animats performing a spatial navigation
task. in *Proceedings of the Genetic and Evolutionary Computation Conference* 77–84
(2018).

89. Schnitzler, H.-U., Kalko, E., Miller, L. & Surlykke, A. The echolocation and hunting behavior of the bat,Pipistrellus kuhli. *Journal of Comparative Physiology A* **161**, 267–274 (1987).

90. Wilson, W. W. & Moss, C. F. Sensory-motor behavior of free-flying FM bats during target capture. *Advances in the study of echolocation in bats and dolphins* 22–27 (2004).

91. Schnitzler, H. U. & Kober, R. Information in sonar echoes of fluttering insects available for echolocating bats. *Journal of the Acoustical Society of America* **87**, 882–896 (1990).

92. Kuc, R. Sensorimotor model of bat echolocation and prey capture. *J Acoust Soc Am* **96**, 1965–1978 (1994).

93. Vanderelst, D. & Peremans, H. Modeling bat prey capture in echolocating bats : The feasibility of reactive pursuit. *J Theor Biol* **456**, 305–314 (2018).

94. Simmons, J. A. & Kick, S. A. Interception of Flying Insects by Bats. *Neuroethology and Behavioral Physiology* 267–279 (1983).

95. Griffin, D. R., Webster, F. A. & Michael, C. R. The echolocation of flying insects by bats. *Anim Behav* **8**, 141–154 (1960).

96. Hiryu, S., Hagino, T., Fujioka, E., Riquimaroux, H. & Watanabe, Y. Adaptive echolocation sounds of insectivorous bats, Pipistrellus abramus, during foraging flights in the field. *J Acoust Soc Am* **124**, EL51–EL56 (2008).

97. Hagino, T., Hiryu, S., Fujioka, S., Riquimaroux, H. & Watanabe, Y. Adaptive SONAR sounds by echolocating bats. in *2007 Symposium on Underwater Technology and Workshop on Scientific Use of Submarine Cables and Related Technologies* 647–651 (2007).

98. Surlykke, A., Ghose, K. & Moss, C. F. Acoustic scanning of natural scenes by echolocation in the big brown bat, Eptesicus fuscus. *Journal of Experimental Biology* **212**, 1011–1020 (2009).

99. Ghose, K., Horiuchi, T. K., Krishnaprasad, P. S. & Moss, C. F. Echolocating bats use a nearly time-optimal strategy to intercept prey. *PLoS Biol* **4**, 865–873 (2006).

100. Mazar, H. *Radio Spectrum Management: Policies, Regulations, Standards and Techniques*. (John Wiley & Sons, Ltd, 2016).

101. H. T. Friis. A Note on a Simple Transmission Formula. *Proceedings of the IRE* **34**, 254–256 (1946).

102. Rahman, F. U. *et al.* Occurrence of Rhinopoma microphyllum (Brunnich, 1782) in Khyber Pakhtoonkhawa, Pakistan. *J Anim Plant Sci* **25**, 450–453 (2015).

103. Boonman, A. M., Parsons, S. & Jones, G. The influence of flight speed on the ranging performance of bats using frequency modulated echolocation pulses. *J Acoust Soc Am* **113**, 617 (2003).

104. Boonman, A. & Ostwald, J. A modeling approach to explain pulse design in bats. *Biol*
Cybern **97**, 159–172 (2007).

105. Weißenbacher, P. & Wiegrebe, L. Classification of virtual objects in the echolocating bat,
Megaderma lyra. *Behavioral Neuroscience* **117**, 833–839 (2003).

106. Saillant, P. A., Simmons, J. A. & Dear, S. P. A computational model of echo processing and
acoustic imaging in frequency-modulated echolocating bats: The spectrogram correlation
and transformation receiver. *Citation: The Journal of the Acoustical Society of America* **94**,
2691 (1993).

107. Popper, A. N. & Fay, R. R. *Hearing by Bats*. (Springer-Verlag, 1995).

108. Blauert, J. *Spatial Hearing: The Psychophysics of Human Sound Localization (Rev. Ed.)*.
(MIT press, 1997).

109. Mohl, B. & Surlykke, A. Detection of sonar signals in the presence of pulses of masking
noise by the echolocating bat , Eptesicus fuscus. *Journal of Comparative Physiology A* 119–
124 (1989).

110. Simmons, J. A. *et al.* Acuity of horizontal angle discrimination by the echolocating bat ,
Eptesicus fuscus. *J Comp Physiol* **153**, 321–330 (1983).

111. Fay, R. R. *Hearing by Bats*. *Journal of Chemical Information and Modeling* vol. 5 (Springer,
New York, NY, New York, 1995).

1020

1021

1022

1023

1024

1025