1

How bats exit a crowded colony when relying on echolocation only - a modeling approach

Omer Mazar[1], Yossi Yovel[1,2]

[1]Tel Aviv University, Sagol School of Neuroscience, Tel-Aviv 6997801, Israel.

[2]Tel Aviv University, Faculty of Life Sciences, School of Zoology, Tel-Aviv 6997801, Israel.

Author Contributions: **O.M** - Software, Formal analysis, Data acquisition, Validation,
Visualization, Methodology, Writing - original draft, Writing - review and editing. **Y.Y** -
Conceptualization, Resources, Supervision, Funding acquisition, Validation, Investigation,
Methodology, Project administration, Writing - review and editing

Abstract

Bats face a complex navigation challenge when emerging from densely populated roosts, where
vast numbers take off at once in dark, confined spaces. Each bat must avoid collisions with walls
and conspecifics while locating the exit, all amidst overlapping acoustic signals. This crowded
environment creates the risk of acoustic jamming, in which the calls of neighboring bats interfere
with echo detection, potentially obscuring vital information. Despite these challenges, bats
navigate these conditions with remarkable success. Although bats have access to multiple sensory
cues, here we focused on whether echolocation alone could provide sufficient information for
orientation under such high-interference conditions. To explore whether they manage this
challenge, we developed a sensorimotor model that mimics the bats' echolocation behavior under
high-density conditions. Our findings suggest that the problem of acoustic jamming may be less
severe than previously thought. Bats can compensate for potential interference by emitting
frequent calls with short inter-pulse intervals (IPI), creating a redundancy in the sensory
information that allows them to aggregate echoes over multiple calls. This redundancy, combined
with simple pathfinding strategies, such as following walls and avoiding nearby obstacles, enables
bats to exit the roost effectively, even when faced with significant sensory interference. Our model
indicates that bats' echolocation strategies are robust enough to mitigate the effects of jamming

and demonstrates the critical role of signal redundancy in successful navigation. These insights

not only enhance our understanding of bat behavior but also offer implications for swarm robotics

and collective movement in complex environments.

Introduction

In many bat species individuals dwell together in caves (or similar roosts), forming large colonies

with tens to tens of thousands of individuals[1] . Each evening, at approximately the same time, the

bats take off from their roost, navigating through its passages toward the exit. The high density of

bats flying simultaneously in great proximity poses many challenges for orientation in such a

crowded and noisy environment. Flying while avoiding collisions, often in a pitch-black cave,

demands the constant detection and localization of both obstacles and nearby bats[2,3]. Employing

echolocation, bats emit strong ultrasonic signals and interpret the reflected echoes to perceive their

surroundings[4]. The reception of neighbors' loud calls, which may share similar acoustic features

with their own calls, can potentially hinder the bats' ability to detect the faint echoes reflected off

the walls and the surrounding bats[4,5]. We examined whether bats could rely solely on echolocation

to exit the roost even during such a chaotic 'rush hour'.

The question of how bats cope with acoustic interference has been extensively researched using

playback experiments, field observations, on-body tags, and computational simulations[6–15].

However, much of this research has focused on foraging bats in small groups[4,5,8,15–18]. The

challenges bats encounter during roost exits (e.g., cave exits), however, differ markedly from those

encountered during group foraging. First, during roost exits the bat density is significantly higher,

and they need to detect and follow static walls or obstacles, which produce loud echoes, rather

than small, sporadic prey items that generate faint echoes[19]. Finally, their flight maneuvers involve

flying directionally and avoiding collisions with conspecifics, unlike the hunting maneuvers

typically observed while foraging. Echolocation studies during dense collective movement are

scarce[3,5,20–23], likely due to the complexities in recording separate echolocation calls and tracking

individual flights within the swarm. While collective movement has been extensively studied in

various species, including insect swarming, fish schooling, and bird murmuration[24–31], as well as

in swarm robotics agents performing tasks such as coordinated navigation and maze-solving[32–34],

most studies have focused on movement algorithms while overlooking the sensory challenges
involved[35–42].

The present study addresses these gaps by introducing an agent-based sensorimotor model based
on the well-documented echolocation capabilities of bats, simulating multiple bats pathfinding
their way out of a cave-like structure. We modeled the echolocation behavior of two insectivorous
bat species: *Pipistrellus kuhli (*PK*)*, which roosts in abandoned buildings and frequently navigates
through conspecific-dense, cluttered corridors and the cave dwelling *Rhinopoma microphyllum*
(RM) which emerges from its roosts with thousands of individuals simultaneously. These two
species differ in their echolocation signals. In brief, PK echolocation signals are characterized by
a wider band width than RM calls. We quantified the performance of an individual bat flying
among conspecifics, demonstrating that even a relatively simple sensorimotor algorithm can
facilitate successful orientation in such complex environments. The modeling approach enabled
us to explore how various biological and ecological factors influence successful navigation under
such challenging conditions.

Results

In our 2D simulations[6], each bat emits sound signals and receives the echoes reflected from roost
walls and other bats which are often masked by the calls emitted by conspecifics. The bat then
estimates the distance and direction of each reflector, adjusts its echolocation accordingly, and
maneuvers in search of an exit while also avoiding collisions. The bats dynamic echolocation
responses were modeled following the vast literature (see[6] and Methods). Their reception was
modeled using a biologically inspired filter-bank receiver comprising 80 gammatone
channels[6,43,44]. Each bat adjusted its flight following a simple pathfinding algorithm based solely
on the estimated locations of the detected reflectors (see Methods, Supplementary Figure 1, and
Supplementary Movie 1 for additional details). The bats had to exit a roost designed as a corridor
(14.5 m long x 2.5 m wide), with a right-angle turn located 5.5 m before the exit (Figure 1A).
Additionally, an obstacle (1.25 m wide) was situated 2.25 m in front of the opening. The simulated
bats initiated their flight from the far end of the corridor taking off in the general direction of the
exit (±30 degrees), without prior knowledge of the roost's structure. The basic sensory model took
all interference signals into account, while assuming that the bat can distinguish between echoes

from the walls and echoes from conspecifics. In brief, the bat responded to echoes as follows (see
detailed description in the Methods): If a static reflector or a conspecific was detected in front of
the bat and was too close (less than 0.4 m), the bat would maneuver to avoid a collision. Otherwise,
to find the exit, the bat would follow the direction of the walls by flying toward the farthest static
reflector ahead. Finally, if a gap greater than 0.5 m was detected between adjacent reflecting points,
the bat directed its flight toward the center of the gap.

The ability of the bats to exit the roost within 15 sec was evaluated for different group sizes, from
a single bat and up to 100 individuals. For simplicity, we will refer to the initial density at the
cave's far end as the number of bats per $3m^2$ (i.e., for groups of 100 bats, the density is 100
bats/$3m^2$, or 33.3 bats/m^2). The bat densities we tested were chosen to reflect the typical range of
bat densities observed in natural caves during emergence events[22,45,46]. Key model parameters,
such as the sensory integration window, object target strength, echolocation parameters, and flight
velocity (see **Table 1**), were manipulated and their impact on the exit performance was analyzed.
To explicitly quantify the effect of sensory masking vs. the effect of collision avoidance only, we
turned the acoustic interference on and off to measure its impact.

Figure 1: The sensorimotor model. (A) Top view of the cave with three bats. Data are presented for the
focal bat (black bat, and wide yellow trajectory). The flight trajectories are shown in thick lines, while the
bat's moment-to-moment decisions are indicated by the inner colored lines (see panel D). Green squares
depict reflectors detected by the focal bat along its route. **(B)** A zoomed-in view of the dashed rectangular
area in Panel A, where the focal bat (black) emitted one echolocation call (black filled) and received echoes
from the cave walls (green hollow) and from two other bats (blue hollow). It also received conspecifics' calls
(red filled) and their reflection from the cave walls (orange hollow), as well as the reflections from other bats
(red hollow). Green squares indicate points that were detected by the focal bat from this call and red x's
indicate missed points due to acoustic masking. The locations of the detected reflectors (green squares) are
marked according to their localization by the bat (with simulated errors). The lines near the bats depict their
flight direction. **(C)** The acoustic scene received by the focal bat is as depicted in B, including the emitted

call and all received signals (colors as in panel B). **(C1)** The time-domain plot displays the envelope of signals, encompassing the emitted call and the received signals: the desired echoes from the walls and conspecifics; the calls of other bats; the echoes returning from conspecific calls and reflected off the walls and off other bats. Notably, in this example, some of the desired wall-echoes are jammed by the stronger echoes reflected off conspecifics. **(C2)** The spectrogram of all the received signals presented in C1; for clarity, the emitted call is not depicted. **(C3)** The responses of the active channels of the cochlear filter bank after de-chirping. Each channel is represented by its central frequency on the y-axis. Each black dot represents the timing of a reaction that was above the detection threshold in each channel. Note that early reactions in low-frequency channels (marked by yellow arrows) result from the stimulation of those channels caused by the higher frequencies of the downward FM chirp. However, most of these stimulations do not reach the detection threshold and are therefore not detected (see Methods). **(C4)** The detections of each channel are convoluted with a Gaussian kernel, summed, and compared with the detection threshold (dotted red line). The colored asterisks illustrate detections of the received signals (colors of the sources are as defined above). Panel D depicts the navigation algorithm used by the bat. The algorithm involves a correlated-random flight during the search phase (blue), collision avoidance (yellow), flying along the wall at a constant distance (green), and flying toward the center of a gap between obstacles as an indicator of a possible exit (cyan). After each echolocation call, the bat awaits an IPI (Inter Pulse Interval) period before emitting the next call. Based on the received signals, it then modifies its next call design and adjusts its direction and speed accordingly.

Bats find their way out of the cave even at high conspecific densities:

We first examine how bat density affects bats' ability to exit the cave, alone and in a group. Higher bat densities significantly reduced the probability of exiting the cave in 15 seconds (**Figure 2** A, see Supplementary Movie 1 for a view of the bats' movement, $p<10^{-10}$, tStat=-23, DF=4077, GLM, see details in **Table 1**). In trials in which a single bat was flying alone, it successfully exited the cave in 100% of the cases. Even without sensory interference, the probability of exiting decreased significantly from 100% to 86%±1.4% and 91%±1.7% at densities of 100 PKs/3m^2 and 100 RMs/3m^2, respectively (mean ± s.e.). When acoustic interference was added, the exit probability further decreased to 63%±1.4% and 67%±1.4% for 100 PKs and RMs, respectively (see **Figure 2** A).

The difference in exit probability between the two species was not significant (p=0.08, tStat=1.74, DF=4077, GLM as above, **Figure 2**A). Similarly, the difference in echolocation parameters between the two species did not affect the collision rate with the walls (with a maximum of 0.29 and 0.3 collisions per bat per second for PK and RM, respectively, with 100 bats (p=0.63, tStat=-0.48, DF=4077, GLM, **Figure 2**C, see details in **Table 1**). To quantify sensory interference, we defined a jammed echo as an echo entirely missed due to masking. The jamming probability, which was calculated as the number of jammed echoes divided by the total number of reflected echoes, was significantly higher for RM compared to PK with a maximum difference of 14.3% for 10 bats,

and 9.8% for 100 bats (p<10^{-10}, tStat=6.56, DF=4077, GLM, **Figure 2**D, see details in **Table 1**).

Accordingly, PK demonstrated a minor but significant advantage in detecting the cave walls

(p=0.024, tStat=-2.25, DF=4077, GLM, **Figure 2**E, see details in **Table 1**). With 100 bats flying

together, the probability of detecting a wall echo at a distance of 1 m in a single call was around

50% and 46% for PK and RM, respectively. Despite this minor disadvantage in detection, RM bats

exhibited a better time-to-exit average than PK bats, being 0.5 seconds faster to exit (p=0.0005,

tStat=-4.06, DF=3533, for n=40 bats, **Figure 2**B). It should be noted that the time-to-exit was

calculated only for successfully exiting bats. RM bats also suffered from a significantly higher

probability of the desired conspecific's echoes being jammed (p=0.00016, tStat=3.8, DF=3593,

GLM, see details in **Table 1**).

Figure 2: Exit performance of P. Kuhli (PK) and R. Microphyllus (RM). **(A)** Sensory interference
significantly impaired the probability of exiting the cave (compare dashed black line with continuous black line).
The probability of a successful exit also declined as the number of bats increased, with no significant difference
observed between the species when masking interference was applied. The insert shows the spectrograms of the
echolocation calls of PK (top) and RM (bottom). **(B)** The time-to-exit, which was calculated for successful trials
only, and **(C)** the collision rate with the walls both increased as a function of the number of bats. **(D)** The
probability of jamming significantly increased to about 55% and 63% with 100 bats for PK and RM, respectively.
(E) The detection probability of a wall reflector at one meter or less in front of a bat decreased as a function of

the number of bats. In panels (A-E), circles represent means and bars represent standard errors (see details in
Table 1). Asterisks indicate significant differences between the lines in each panel.

A longer integration window improves exit performance: We next examined whether bats improve their performance when integrating information from several consecutive calls. The integration window determines the number of previous calls the bat uses at each step to guide its next movement decision (see Methods). The basic model used five calls. The probability of exiting the roost significantly increased when increasing the size of the integration window for all bat densities ($p<10^{-10}$, tStat=28.5, DF=10197, GLM, Figure 3A, see details in **Table 1**). For example, at a density of 40 bats/3m^2, the exit probability improved from 20%, to 75%, and to 87% as the window size increased from one, to three, and to 10 previous calls, respectively. In addition, increasing the window size resulted in a significant improvement in the time-to-exit and the avoidance of wall collisions ($p<10^{-10}$, tStat=-12.8, DF=7661; $p<10^{-10}$, tStat=-46.5, DF=10197, respectively, GLM, see details in **Table 1**). With 100 bats, the collision rate decreased by a factor of 2 from 0.53 to 0.25 collisions per second as the window increased from 1 to 10 calls. The size of the integration window had no significant effect on the jamming probability ($p=0.37$, tStat=0.9, DF=10197, GLM, see details in **Table 1**).

Exit probability was maximal at an intermediate flight-speed: We observed a significant and non-linear effect of the flight speed of the bats on the performance, as shown in Figure 3B ($p<10^{-10}$, tStat=-29.9, DF=10196, GLM, see details in **Table 1**). The exit probability increased with flight speed until it reached a maximum at 6-8 m/s and then declined rapidly. This was the case for all bat densities, with the maximal exit probability ranging between 65% to 99%. At the optimal velocity, the time-to-exit was also minimal. However, the collision rate increased monotonically with speed, with a steep incline above the optimal speed.

Figure 3: Exit performance as a function of key sensorimotor parameters. **(A)** The effect of the integration window on the probability of exiting the roost, the time-to exit, the rate of collisions with the walls, and the probability of jamming (from left to right, respectively). Each colored line shows the trend as a function of the window-size for different bat densities, with each color representing a specific density. **(B)** The effect of the nominal flight speed of the bats, with panels and line-colors as in panel A. An optimal speed of approximately 6 to 8 m/sec can be observed for all densities above one bat. **(C)** The effect of call intensity on exit performance, panels as in (A). In all panels, circles represent means and bars represent standard errors. See Table 1 for the number of simulated bats.

Call intensity had only a minor effect on exit performance and only at high bat densities: For low bat densities (<40 bats), call intensity did not have a significant impact on either exit probability or collision rate (Figure 3C, p=0.89, tStat=0.13, DF=5757; p=82, tStat-0.21, DF=5757, respectively, GLM, see details in **Table 1**). Call intensity affected exit performance only when the intensity dropped to 100 dB-SPL and only at a high bat density of 100 bats/3m^2 (Figure 3 C). In this scenario, the exit probability declined from approximately 60% to 49.5% (p=0.003, F = 8.45,

DF = 2396, One-way ANOVA with 'hsd' post hoc test), and the collision rate increased from 0.3

to 0.35 collisions per second (p<$3 \cdot 10^{-6}$, F = 22.18, DF = 2396). Notably, this low intensity is below

the typical search-call intensity of most echolocating bats. At the same bat density (100 bats/$3m^2$),

further increasing the call intensity to above 100dB-SPL had no significant effect on either exit

probability (p=0.6) or collision rate (p=0.07). Calling louder also slightly, but significantly,

decreased the jamming probability at all bat densities, with a decrease of 3.5%±8% to 5.5%±5%

(mean ± s.e.) (p=0.02, tStat=-2.26, DF=8157, GLM, see **Table 1**).

While confusion between the desired echoes and those from conspecific calls may significantly

impair exit performance, temporal aggregation helps to mitigate this. We next addressed the

challenge of echo classification, assuming that a bat can differentiate an echo resulting from its

own calls from echoes resulting from the calls of other bats. To examine this assumption, we tested

another model in which bats responded similarly both to wall echoes returning from their own

emissions and to those from conspecific emissions, treating all as their own echoes. This confusion

significantly decreased exit performance for all bat densities (above one bat). The probability of a

successful exit for a density of 40 bats/$3m^2$ dropped from 83.3±2.4% to 14.6±2.3% (p<<10^{-10},

tStat=-20.7, DF=2877, GLM, see details in **Table 1**), the exit time increased from 7.6±0.18 to

9.3±0.2 seconds (p<<10^{-10}, tStat=15.5, DF=2157, GLM), and the collision rate increased

significantly from 0.2±0.007 to 0.8±0.013 collisions per second (p<<10^{-10}, tStat=-30, DF=28777,

GLM, see Figure 4, red and yellow lines).

To further examine whether this decrease in performance could be mitigated by integrating

detections from successive calls, we tested a slightly improved aggregation model that clustered

detected reflectors over one second periods (see Methods). This temporal aggregation process

significantly improved performance, but exit probability and time-to-exit still remained

significantly lower than without echo-confusion: exit probability = 58±3% in comparison to

83.3±2.4% without echo confusion (p<<10^{-10}, tStat=18.3, DF=28777, GLM), time-to-exit

=9.3±0.2 seconds (p<<10^{-10}, tStat=-13.7, DF=1996, GLM), see Figure 4, yellow line. The results

above are reported for a density of 40 bats/$3m^2$. Interestingly, the aggregation process restored the

collision rate to the levels observed under the "No Confusion" condition (p=0.68, tStat=-0.42, DF=

2877, GLM, see Figure 4C, dark-purple and red lines).

Figure 4: The impact of confusion on performance. The figure illustrates the impact of classification confusion on roost-exit performance under various conditions. Blue lines depict trials with masking, while assuming that bats can distinguish between echoes from their own calls and those of conspecifics (referred to as "No Confusion"). Red lines depict performance where confusion between echoes is assumed. Yellow lines depict performance under the confusion condition, with the added capability of temporal aggregation process in a short-term working memory (referred to as "confusion with mitigation", see text for further details). In all panels, circles represent means and bars indicate standard errors. **(A)** The probability of exiting the roost significantly decreased with masking and confusion. In conditions with confusion and no aggregation process, only 15% of bats successfully exited the roost, at a density of 40 bats/3m^2. Temporal aggregation partially mitigated the confusion effect but did not eliminate it. **(B)** Bats with the ability to distinguish between echoes demonstrated significantly shorter exit times than those experiencing confusion. Note that time-to-exit refers only to successful attempts. **(C)** The collision rate with walls was highest for bats experiencing both masking and confusion but decreased significantly when without confusion. Temporal aggregation process restores performance to the "No Confusion" condition, reducing collision rates accordingly, at densities between 1 to 40 bats/3m^2.

Key parameter	Tested range	Default value	Effect size			Statistical Test
			Exit-probability (%)	Jamming-probability (%)	Collision rate (sec^{-1})	GLM's explaining factors
Number Of Bats	[1, 2, 5, 10, 20, 40, 100]	**All Values**	-0.37/bat* [63:100]	0.54/bat* [0:54]	0.25/bat* [0.05:0.3]	Number of bats
Bat species	[PK, RM]	**PK**	4.5 [63:67]	9* [54:63]	0.01 [0.29:03].	Number of bats, bat species
Integration Window (#)	[0,1,3,5,10]	**5**	0.41/call* [29:70]	0.01/call [54:55]	0.27/call [0.25:0.53]	Number of bats, integration window size
Nominal flight speed (m/s)	[2,4,6,8,10]	**6**	6/(1m/s), -12/(1m/s)* [15:63]	1.4/(1m/s)* [55:65]	0.18/(1m/s)* [0.07:1.3]	Number of bats, square of number of bats, flight speed
Call level (db-spl)	[100,110,120,130]	**120**	13$^\psi$ [50:63]	0.5/10dB* [53:58]	0.07 $^\psi$ [0.29:0.36]	Number of bats, call level
Misidentification	[Yes/No]	**N**	69* [14:83]	1.7* [7.6:9.3]	0.6* [0.2:0.8]	Number of bats, confusion flag
Misidentification and temporal aggregation process	[Yes/No]	**N**	23* [58:83]	1.7* [7.6:9.3]	-0.02* [0.18:0.2]	Number of bats, process flag
Masking	[Yes/No]	**Y**	23* [63:86]	54* [0:54]	0.03 [0.26:0.29]	Number of bats, masking
Wall target strength (db)	[-33, -23, -13, -3]	**-23**	2.13/dB [23:87]	1.16/dB [34:68]	0.01/DB [0.19:0.47]	Number of bats, wall target strength

Table 1: Key model parameters and their effects on performance metrics. The table presents the key parameters tested, their ranges, default values, and effect sizes on various performance metrics: exit probability, jamming probability, and collision rate. The parameters comprised the number of bats, bat species (PK-Pipistrellus kuhli, RM –Rhinopoma microphyllum), integration window, nominal flight speed, call level, echo mis-identification with temporal aggregation (yes/no), masking (yes/no), and wall target strength. In each scenario, all parameters except the tested one were set to the default value. The effect sizes for each parameter on exit probability, jamming probability, and collision rate are provided (per bat). Square brackets present the minimum and maximum values of the metric across the tested range. Asterisk (*) indicates a significant impact. Each scenario was tested using Generalized Linear Models (GLMs) with number-of-bats and the tested parameters set as fixed explaining variables. Exit probability and jamming probability were treated as binomially distributed, collision rate was treated as a Poisson distributed, and all other variables were considered normally distributed. Explaining variables were set as fixed factors. The number of repetitions for each scenario was as follows: 1 bat: 240; 2 bats: 120, 5 bats: 48; 10 bats: 24; 20 bats: 12; 40 bats: 12; 100 bats: 6. $^\psi$ A significant difference in call intensity was found only for a bat density of 100 bats/3m^2, and between the group with a level of 100dB-SPL and all other groups.

Discussion

We present a model-based approach that suggests how echolocating bats might find their way out of a crowded roost while contending with severe sensory interference caused by numerous nearby conspecifics. Our results demonstrate that a single bat, lacking prior knowledge of its location and of the roost's structure, can reliably find the exit using echolocation alone. As bat density increases, the bats face increased collision risks and more substantial acoustic interference, both of which reduce the probability of efficiently finding the exit. Nevertheless, even at densities of 100 bats/3m^2, most bats (63%) successfully exited the roost within a short timeframe. In brief, we demonstrate how a simple sensorimotor approach can solve this supposedly challenging task. This approach encompasses the following principles: (1) emission of echolocation calls; (2) reception of reflected echoes and interference signals; (3) detection of reflectors (including walls and conspecifics) using a gammatone filter bank biological receiver; (4) localization of the detected objects; (5) employment of short-term integration of acoustic detections; (6) adjustment of flight and echolocation behavior based on the distance and angle to the reflectors; and (7) application of simple pathfinding rules to follow walls and gaps while avoiding collisions. Notably, despite the jamming of a substantial percentage of the echoes (up to approximately 50% of the echoes from a 1 m distance), the bats managed to maneuver correctly even with this simple approach and partial data. Real bats likely use a much more sophisticated approach that also includes memorizing the roost's structure[47], using landmarks inside the roost[48], reliance on the movement of nearby conspecifics[42,45], and exploitation of other sensory modalities. We thus expect their actual performance to surpass that of our modeled bats.

Our model suggests that acoustic jamming might be less problematic than has been generally assumed[4,10,49] and that movement under severe acoustic masking could be mitigated by increasing the call-rate, creating a redundancy in information across several calls- similar to how real bats react in a complex environment[5], and using simple sensorimotor heuristics. This is consistent with several relatively recent studies that have hinted in this direction[6,22,23].

The bat densities we simulated (ranging from 1 to 100 bats per 3m^2) reflect a wide range of observed bat densities. Although bat colonies can be much larger than 100 bats, the density that we simulated resulted in bats moving very close to each other, with an average distance of 0.27 m to the nearest bat. This density is higher than some of the most-dense reported bat aggregations,

including studies on *Miniopterus fuliginosus*[45], *Myotis grisescens*[50], and *Tadarida*

brasiliensis[3,46,51], where bats emerge from the roost at rates of 15 to 500 bats per second, but fly

with an average distance of 0.5 meters between individual bats.

We compared the performance of two FM echolocating insectivorous bat species: *Pipistrellus*

*kuhli (*PK*)* and *Rhinopoma microphyllum (*RM*)*. PK bats emit wideband echolocation signals that

are less prone to jamming than RM bats' narrowband signal[14,52]. Our findings show that PK signals

slightly reduce jamming probability (by 9%) and improve wall detection. However, no significant

differences in exit probabilities were noted between the two species.

Using a simulation allowed us to separate the effects of sensory and spatial interferences (i.e.,

avoiding other bats) and revealed new insights into the sensorimotor strategy that is probably

applied by real bats. The spatial interference reduced the probability of exiting the roost from 100%

to 87%, while the sensory interference further decreased it to 63%. Increasing call intensity had

little effect on exit performance, although slightly improving it at high bat densities. When all bats

increased their calling intensity, both desired echoes and masking signals intensified equally,

resulting in only a marginal effect. There is, thus, no benefit beyond a certain level of calling

intensity that is needed to ensure proper obstacle detection (ca. 110dB-SPl, which is in accordance

with actual call intensities used by bats). These results align with previous studies that have drawn

similar conclusions[6,23].

Bats constantly adjust their flight speed to their surroundings[53–56] and specifically when

conspecifics are nearby[57]. Our study suggests that the optimal velocity for flying through a

crowded roost ranges from 6 m/sec to 8 m/sec for densities of 2-100 bats/3m^2. Exceeding this

velocity-range led to a significant drop in exit probability due to a significant increase in wall

collisions. We found that this speed did not depend on bat density in accordance with the

observations of Theriault et al.[46]. Notably, the reported velocities of RM when exiting a cave[22] and

PK emergence velocity near the cave[58] are close to the speed that appears optimal, based on our

simulations.

Our basic model assumed that bats can distinguish between wall echoes and conspecific echoes,

as demonstrated in previous studies [59]. We suggest that this is a feasible assumption because echoes

from cave walls are longer and exhibit distinct spectro-temporal patterns, whereas echoes from

smaller objects, such as conspecifics, are shorter[43,60,61]. However, wall echoes reflected from

conspecific calls might resemble those from the bat's own calls in their amplitude and time-frequency characteristics [18,57,62]. This led us to question how the misidentification of such echoes as obstacles might affect navigation. When unable to distinguish between these echoes, the simulated bats responded to all as if they were their own and thus mis-localized conspecific wall echoes. The confusion led to a significant drop in exit performance, in which only 15% of the bats successfully exited (compared to 82% without confusion), and the collision rate rose from 0.2 to 0.85 collisions per second, at a 40 bats/3m^2 density.

Previous studies have demonstrated that bats can aggregate acoustic information received sequentially over several echolocation calls, effectively constructing an auditory scene in complex environments[4,63–66]. Accordingly, we tested how temporal aggregation process, which also included clustering of nearby reflectors and estimating wall orientation based on integration, rather than processing single detections, might assist bats in pathfinding even under the assumption of full confusion. At bat densities of 1 to 40 bats/3m^2, the temporal aggregation process completely restored the collision rate with walls from 0.85 back to 0.2 collisions per second, and significantly improved the exit probability, raising it to 58%, although it did not entirely eliminate the impact of confusion. Our assumption of total confusion between echoes from a bat's own calls and those from conspecifics, as well as our relatively simple integration model, likely underestimates the true capabilities of real bats when flying in complex environments.

Navigation in bats involves processing complex sensory inputs and applying effective decision-making, often requiring an ability to switch strategies[67–73]. Bats possess a highly accurate spatial memory[63,69,73–75], which is essential for tasks like long-distance migration[47], homing[76], and maneuvering in cluttered environments[74]. Additionally, they utilize acoustic landmarks to orient in total darkness[48], occasionally rely on vision[70,71], particularly at the cave edge where light is available, can passively detect echolocating peers, and perhaps eavesdrop on conspecifics' echoes[21]. In this study we focused on whether echolocation alone is sufficient for one of the most difficult orientation tasks that bats perform – exiting a roost at high densities without prior knowledge of the roost's shape, aside from the initial flight direction. Thus, our echolocation-only model, which was based on a five-call integration window during most simulations, probably underestimates real bats' actual performance which also benefits from additional sensory input and can employ addition navigation strategies by sharing information between each other to coordinate and optimize the routes, such as manifested by swarming intelligence[32,77,78].

370   Our model highlights the importance of considering sensory interference in animal behavior
371   research and illuminates the impressive capabilities of echolocating bats. Additionally, the model
372   showcases the value of simulations and establishes a framework for future studies on collective
373   movement and swarming animals, and on robotics in complex environments.

Methods
375

The simulated bats rely solely on echolocation to detect and locate obstacles and other bats by
analyzing the sound waves they receive. They emit directional echolocation calls and receive the
echoes reflected by roost walls and conspecifics, as well as the calls of conspecifics and the echoes
returning from their calls. The bats adjust their flight trajectory and echolocation behavior based
on the estimated location of the detected objects (range and angle), which deteriorates upon
acoustic interference. The detection of the received signals is based on the mammalian gammatone
filter bank receiver, under the assumption that bats can differentiate between the desired detected
obstacles, conspecifics' echoes, and masking signals. We conducted simulations with varying
number of bats (from 1 to 100) to analyze the flight trajectories with and without masking
interference by conspecifics. In the trials without masking interference the bats successfully
detected walls and conspecifics without any hindrance. For a detailed description of the MATLAB
simulation see Mazar & Yovel 2020[6].

All bats in our model start their flight simultaneously within a 0.1 sec window from a random point
at the cave's end over a 2 x 1.5 m^2 area, heading in a random direction between -30 and 30 degrees
relative to exit direction (see **Figure 1**). They employ a simple navigation algorithm that
dynamically adjusts flight direction based on the detected obstacles or conspecifics
(Supplementary Figure 1 and Figure 1D). If no obstacles or conspecifics are detected, they
continue in a correlated random walk with a maximal turning rate of approximately 30 deg/sec.
When obstacles are detected, they are first localized with an error (see below and[6]). Then, if an
opening(i.e., a gap of at least 0.5 m between obstacles) is detected, the bats fly through it, if not,
they follow the walls while maintaining a 0.8 m distance from them. When approaching a
stationary obstacle too closely (<1.5 m and at an angle <60º), they execute an obstacle avoidance
maneuver. High proximity to another bat (<0.4 m) triggers an avoidance maneuver away from the
nearest conspecific. If the bat collides with a wall, it immediately turns so that its new flight

direction is at a 90° angle to the wall. Each decision relies on an integration window that records
the estimated locations of detected reflectors from the last five echolocation calls, with the
parameter being tested between 1 and 10 calls. This algorithm functions without any prior
knowledge of the bats' location or the roost's structure. To assess performance, we measured the
probability of successfully exiting the roost within a 15-second window, chosen because it is
approximately twice the average exit time for 40 bats and allows for a second corrective maneuver
if needed..

Echolocation behavior and flight speed follow the phases widely reported in insectivorous bats,
categorized as "search," "approach," and "buzz"[79–82] with specific echolocation parameters for
Pipistrellus khulli (Kuhl's pipistrelle)[54] and *Rhinopoma microphyllum* (greater mouse-tailed bat)[22].
The distance to the detected object defines the phase and accordingly determines the following
parameters: Inter Pulse Interval (IPI), call duration, and start and stop frequencies. The simulated
echolocation call consists of the dominant harmony of the bat's FM Chirp (1st harmony of the PK
and 2nd harmony of the RM). Table 2 provides the specific echolocation parameters used in the
model. During the search phase, the bats fly at a nominal velocity of 6 m/sec, reducing it by half
during the approach phase and continuously adjusting their speed according to the relative
direction of the target, using a delayed linear adaptive law[6,83,84]. The maneuverability of the bats
is constrained to a maximum of 4 m/sec², limiting both angular and linear accelerations.

Pipistrellus khulli (Kuhl's pipistrelle)						
Flight phase	Search	Approach		Buzz		
Parameter		Start	End	Terminal 1 start	Terminal 1 end	Terminal 2
Inter Pulse Interval [ms]	100	70	35	18	6	5
Call duration [ms]	7	5	2	2	1	0.3
Terminal frequency [kHz]	39	39	39	39	39	39
Chirp bandwidth [kHz]	8	35	30	30	20	20
Call intensity [dB-SPL]	120	120	90	90	80	80
Distance to target [m]	>1.2	1.2	0.4	0.4	0.2	<0.2
Rhinopoma microphyllum (greater mouse-tailed bat)						
Flight phase	Search	Approach		Buzz		

Pipistrellus khulli (Kuhl's pipistrelle)						
Flight phase	Search	Approach		Buzz		
Parameter		Start	End	Terminal 1 start	Terminal 1 end	Terminal 2
Inter Pulse Interval [ms]	100	80	20	18	10	9
Call duration [ms]	12	7	2	2	1.5	0.75
Terminal frequency [kHz]	26	26	26	26	26	23.5
Chirp bandwidth [kHz]	3	4	5	3	3	3
Call intensity [dB-SPL]	120	120	90	90	80	80
Distance to target [m]	>1.2	1.2	0.4	0.4	0.2	<0.2

Table 2: Echolocation parameters. The table presents the echolocation parameters of the two bat species
we simulated during the specified flight phases (i.e., search, approach, buzz, and final buzz). In each phase,
except for the search phase, in which the parameters remain constant, the parameters for each call are
determined by the distance to the closest detected object.

The sound intensity of the echoes generated by the bat's own calls and those of its conspecifics

are calculated using the sonar equation[6,85] (pp. 196-198), as shown in Equation 1. The received

levels of the masking calls are determined by using the Friis transmission equation[86], as shown in

Equation 2. Bats are modeled acoustically as spherical reflectors with a uniform target strength of

-23dB, reflecting sound isotropically. This acoustic characterization approximates a sphere with a

radius of 0.15 m, corresponding to the approximate wingspan of *Rhinopoma microphyllum* (RM)

[22,87]. Walls are modeled as composites of individual reflectors placed 20 cm apart; each treated as

a sphere with a 20 cm radius and a target strength of -20dB. The directivity of the calls and the

received echoes is defined by the piston model[6,82] with radii of 3 mm for the mouth-gap and 7 mm

for the ear. Echo delays are calculated as the two-way travel time of the signals from the emitter

to the target.

$$\text{Equation 1: } \boldsymbol{P_r} = \boldsymbol{P_t} \cdot \frac{G_t(\phi_{target}, f) \cdot G_r(\phi_{target}, f) \lambda^2}{(4\pi)^3 D^4} \cdot \boldsymbol{10}^{-2\alpha_{att}(f)/10 \cdot (D-0.1)} \cdot \boldsymbol{\sigma(f)}$$

$$\text{Equation 2: } \boldsymbol{P_{mask}} = \boldsymbol{P_t} G_t\big(\phi_{t_x r_x}\big) G_r\big(\phi_{r_x t_x}\big) \cdot \left(\frac{\lambda}{4\pi D_{txrx}}\right)^2 \boldsymbol{10}^{-\alpha_{att} \cdot (D-0.1)}$$

$$\text{Equation 3: } \boldsymbol{P_{echoesFromMasking}} = \boldsymbol{P_t} \cdot \frac{G_t(\phi_{t_x}) \cdot G_r(\phi_{r_x}) \lambda^2}{(4\pi)^3 D_{t_x}{}^2 D_{r_x}{}^2} \boldsymbol{10}^{-\alpha_{att} \cdot (D_{t_x}+D_{r_x}-0.2)} \cdot \boldsymbol{\sigma(f)}$$

where,

P_r: level of the received signal [SPL]

P_t : level of the transmitted call [SPL]

P_{mask} : level of the masking signal as received by the bat [SPL]

$P_{echoesFromMasking}$: level of the echoes reflected by conspecifics and received by the bat [SPL]

$G_t(\phi, f)$: gain of the transmitter (mouth of the bat, piston model), as a function of azimuth and frequency (f) [numeric]

$G_r(\phi, f)$: gain of the receiver (ears of the bat, piston model) [numeric]

ϕ_{target} : angle between the bat's direction and the target [rad]

D: distance between the bat and the target [m]

ϕ_{ii}, D_{ii} : angles[rad] and distances[m] between the emitting bat or receiving bat (tx and rx, respectively) and the target

$\alpha_{att}(f)$: atmospheric absorption coefficient for sound [dB/m]

$\sigma(f)$: SONAR cross-section of the target [m^2]

λ: The wavelength of the signal [m]

To model the bat's cochlea, we employed a filter bank receiver[43,88,89] consisting of 80 channels,
each with three components: (i) a gammatone filter of order 8, acting as a bandpass filter with
center frequencies logarithmically scaled between 10kHz and 80kHz[6]; (ii) a half-wave rectifier;
and (iii) a lowpass filter (Butterworth, fc=8kHz, order=6). Object detection and distance estimation
are conducted using Saillant's method[6,43,90], based on the sum of detections in the active channels,
see Figure 1C, D. Initially, a de-chirping process calculates the reference frequency-delay by
detecting the peak in the response of each channel to the emitted call in a noise-free environment.
Subsequently, the received signal, containing both desired echoes and masking sounds, passes
through the filter bank. In each channel, all peaks above a threshold level are detected and time-
shifted by the de-chirp reference. Peaks from all channels are aggregated in 5 µs windows and
convolved with a Gaussian kernel with σ=5 µs. Output peaks that exceed the threshold level, set
at 10% of the number of active channels, and fall within a time window of 100µs around the
expected delay, are considered successful detections.

To evaluate the impact of acoustic interference, we conducted the detection procedure twice. The
first, termed "interference-free detection", comprised only the desired echoes, with Gaussian noise
at a level of 0 dB-SPL and without masking signals. The second, termed "full detection" comprised
the desired echoes, Gaussian noise, and the masking signals. Detected echoes in the full detection
were defined by the strongest peak within a four-millisecond window (three milliseconds before
and one millisecond after, accounting for forward and backward masking) detected within 100µs
of the interference-free detections. Jammed echoes were those detected in the interference-free
condition and not in the full detection condition. The jamming probability was defined as the ratio
of jammed echoes in the full detection condition to the detected echoes in the interference-free
condition.

After detection, the bat estimates the range and the Direction of Arrival (DOA) of the reflecting
objects. The range is determined by the delay of the detected echo, including any errors derived
from the filter-bank process in the "full detection" process (i.e., including all masking signals).
The direction is estimated by adding directional errors to the calculated angle between the bat and
the target[6]. These errors are normally distributed with a zero mean and a standard deviation that
depends on the Signal-to-Noise Ratio (SNR) and the angle. At an angle of 0º and an SNR of 10dB,
the standard deviation of the error is $1.5º$[91,92].

To evaluate the impact of the assumption that bats can distinguish between echoes caused by their
own calls and those caused by other bats (i.e., conspecifics' reflectors), we tested an alternative
model in which the simulated bats treat all echoes reflected from walls as if they have originated
from their own calls. The distance to the conspecifics' reflectors is estimated based on the time
difference between the echo and the bat's last call. The direction of arrival is estimated by the
angle between the bat and the physical reflector, with an added random error (the same process
used for their own echoes).

In real bats, spatial processing in the brain involves aggregating auditory information over time to
construct a coherent map of the environment [4,93]. This neural computation is crucial for navigation
and prey detection in complex environments. Therefore, we also examined how the inclusion of
temporal aggregation process in the environment perception procedure helps bats mitigate the
confusion problem. The integration comprised the following steps, which were executed within a
one-second working memory (or integration window): (i) clustering all detections in memory into

groups with a maximum internal distance of 10 cm; (ii) reconstructing the estimated walls
positions and directions based on the average of clusters that include at least two detections (and
not based on single reflectors); and (iii) looking for openings between wall edges ranging from 0.5
to 2.25 meters in width, see Supplementary Figure 1. Note that detections from the last calls, even
if not clustered, are still used for obstacle avoidance maneuvers.

Statistical analysis

Statistical analysis and the roost-exit model were conducted using MATLAB© 2023a.

Tests were performed with a significance level of 0.05. For each simulated scenario, we examined
the effect of the various parameters on exit probability, time-to-exit, collision rate, and the
jamming probability, using Generalized Linear Models (GLMs). The GLM tests were executed
with MATLAB built-in function **'fitglm()'**. Probability variables (such as exit and jamming
probabilities) were treated as binomially distributed; rate variables (such as collision rate) were
treated as Poisson distributed, and all other variables were considered normally distributed. Unless
otherwise stated, all explaining variables were set as fixed factors. All statistical analyses,
including the statistical test and the corresponding sample sizes, are described throughout the text
and summarized in **Table 1.**

Data availability

All data and codes generated during this study are included in the manuscript and supporting files.
Source code files have been uploaded with a Graphical User Interface and a readme file for
explanation. Data are available at: link

https://drive.google.com/drive/folders/1hxnxbd37I2qVOLTWUob7cGhqXaQakEXs

504   Supplementary

505   Supplementary Movie 1 – link

507   Supplementary Figure 1: Decision-making in echolocation-based pathfinding

The diagram illustrates the sequential steps in a bat's pathfinding process based on echolocation. This process starts with the emission of an echolocation call (1) and the reception of echoes and interfering signals (2), followed by sensory processing for detection, range estimation, and direction of arrival (DOA) (3). After integrating detections over a 1–10 call window (4), the bat engages in **crash avoidance** (5) by evaluating the proximity of conspecifics and obstacles directly ahead. If either is too close, the bat turns to the opposite direction. If no immediate threat is detected, the bat proceeds to **pathfinding** (6). During pathfinding, it checks for obstacles and, if an opening is detected, flies toward the gap's center. Without the optional **temporal aggregation process** (green), the bat simply integrates detections and flies toward the farthest detected obstacle, interpreting it as a wall edge. If the temporal aggregation is included (9), a one-second short memory aids in clustering detections, estimating wall edges, and identifying openings, while also allowing the bat to follow walls at a constant distance. Throughout, the bat continuously adjusts echolocation parameters (8) and controls flight direction and velocity (7) based on ongoing sensory information and decision-making.

References

1. Glover, A. M. & Altringham, J. D. Cave selection and use by swarming bat species. *Biol Conserv* **141**, (2008).

2. Vanderelst, D., Holderied, M. W. & Peremans, H. Sensorimotor Model of Obstacle Avoidance in Echolocating Bats. *PLoS Comput Biol* **11**, e1004484 (2015).

3. Gillam, E. H., Hristov, N. I., Kunz, T. H. & McCracken, G. F. Echolocation behavior of Brazilian free-tailed bats during dense emergence flights. *J Mammal* **91**, 967–975 (2010).

4. Ulanovsky, N. & Moss, C. F. What the bat's voice tells the bat's brain. *Proc Natl Acad Sci U S A* **105**, 8491–8498 (2008).

5. Lin, Y., Abaid, N. & Müller, R. Bats adjust their pulse emission rates with swarm size in the field. *Citation: The Journal of the Acoustical Society of America* **140**, 4318 (2016).

6. Mazar, O. & Yovel, Y. A sensorimotor model shows why a spectral jamming avoidance response does not help bats deal with jamming. *Elife* **9**, 1–23 (2020).

7.   Takahashi, E., Hyomoto, K., Riquimaroux, H., Watanabe, Y. & Ohta, T. Adaptive changes
in echolocation sounds by Pipistrellus abramus in response to artificial jamming sounds.
2885–2891 (2014) doi:10.1242/jeb.101139.

8.   Ulanovsky, N., Fenton, M. B., Tsoar, A. & Korine, C. Dynamics of jamming avoidance in
echolocating bats. *Proceedings of the Royal Society B: Biological Sciences* **271**, 1467–1475
(2004).

9.   Gillam, E. H. & Montero, B. K. Influence of call structure on the jamming avoidance
response of echolocating bats. *J Mammal* **97**, 14–22 (2016).

10.   Bates, M. E., Stamper, S. A. & Simmons, J. A. Jamming avoidance response of big brown
bats in target detection. *Journal of Experimental Biology* **211**, 106–113 (2008).

11.   Luo, J. & Moss, C. F. Echolocating bats rely on audiovocal feedback to adapt sonar signal
design. *Proceedings of the National Academy of Sciences* **114**, 10978–10983 (2017).

12.   Corcoran, A. J. & Conner, W. E. Bats jamming bats: Food competition through sonar
interference. *Science (1979)* (2014) doi:10.1126/science.1259512.

13.   Cvikel, N. *et al.* Bats aggregate to improve prey search but might be impaired when their
density becomes too high. *Current Biology* **25**, 206–211 (2015).

14.   Cvikel, N. *et al.* On-board recordings reveal no jamming avoidance in wild bats.
Proceedings of the Royal Society B: Biological Sciences **282**, (2015).

15.   Götze, S., Koblitz, J. C., Denzinger, A. & Schnitzler, H. U. No evidence for spectral
jamming avoidance in echolocation behavior of foraging pipistrelle bats. *Sci Rep* **6**, 1–13
(2016).

16.   Gillam, E. H., Ulanovsky, N. & McCracken, G. F. Rapid jamming avoidance in biosonar.
Proceedings of the Royal Society B: Biological Sciences **274**, 651–660 (2007).

17.   Giuggioli, L., McKetterick, T. J. & Holderied, M. Delayed Response and Biosonar
Perception Explain Movement Coordination in Trawling Bats. *PLoS Comput Biol* **11**,
1004089 (2015).

18.   Obrist, M. K. Flexible bat echolocation: the influence of individual, habitat and conspecifics
on sonar signal design. *Behav Ecol Sociobiol* **36**, 207–219 (1995).

19.   Krivoruchko, K. *et al.* A social foraging trade-off in echolocating bats reveals that they
benefit from some conspecifics but are impaired when many are around. *Proc Natl Acad*
Sci U S A **121**, e2321724121 (2024).

20.   Hristov, N. I., Betke, M. & Kunz, T. H. Applications of thermal infrared imaging for
research in aeroecology. *Integr Comp Biol* **48**, 50–59 (2008).

21.   Lin, Y. & Abaid, N. Modeling perspectives on echolocation strategies inspired by bats
flying in groups. *J Theor Biol* **387**, 46–53 (2015).

22.   Goldstein, A. *et al.* Collective Sensing – On-Board Recordings Reveal How Bats Maneuver
Under Severe 4 Acoustic Interference. *Under Review* 1–25 (2024).

23.   Beleyur, T. & Goerlitz, H. R. Modeling active sensing reveals echo detection even in large
groups of bats. *Proc Natl Acad Sci U S A* **116**, 26662–26668 (2019).

24.   Strandburg-Peshkin, A. *et al.* Visual sensory networks and effective information transfer in
animal   groups.   *Current   Biology*   vol.   23   Preprint   at
https://doi.org/10.1016/j.cub.2013.07.059 (2013).

25.   Pearce, D. J. G., Miller, A. M., Rowlands, G. & Turner, M. S. Role of projection in the
control of bird flocks. *Proc Natl Acad Sci U S A* **111**, 10422–10426 (2014).

26.   Rosenthal, S. B. *et al.* Revealing the hidden networks of interaction in mobile animal groups
allows prediction of complex behavioral contagion. *Proc Natl Acad Sci U S A* **112**, 4690–
4695 (2015).

27.   Bastien, R. & Romanczuk, P. A model of collective behavior based purely on vision. *Sci*
Adv **6**, (2020).

28.   Davidson, J. D. *et al.* Collective detection based on visual information in animal groups.
Journal of the Royal Society **18**, 2021.02.18.431380 (2021).

29.   Aidan, Y., Bleichman, I. & Ayali, A. Pausing to swarm: locust intermittent motion is
instrumental for swarming-related visual processing. *Biol Lett* **20**, 20230468 (2024).

30.   Pitcher, T. J., Partridge, B. L. & Wardle, C. S. A blind fish can school. *Science (1979)* **194**,
963–965 (1976).

31.   Partridge, B. L. The Structure and Function of Fish Schools. **246**, 114–123 (1982).

32. Youssefi, K. A. R. & Rouhani, M. Swarm intelligence based robotic search in unknown maze-like environments. *Expert Syst Appl* **178**, (2021).

33. Cheraghi, A. R., Shahzad, S. & Graffi, K. Past, Present, and Future of Swarm Robotics. in *Lecture Notes in Networks and Systems* vol. 296 (2022).

34. Faria Dias, P. G. *et al.* Swarm robotics: A perspective on the latest reviewed concepts and applications. *Sensors* vol. 21 Preprint at https://doi.org/10.3390/s21062062 (2021).

35. Couzin, I. D., Krause, J., James, R., Ruxton, G. D. & Franks, N. R. Collective Memory and Spatial Sorting in Animal Groups. *J Theor Biol* **218**, 1–11 (2002).

36. Attanasi, A. *et al.* Collective Behaviour without Collective Order in Wild Swarms of Midges. **10**, (2014).

37. Gautrais, J. *et al.* Deciphering Interactions in Moving Animal Groups. *PLoS Comput Biol* **8**, e1002678 (2012).

38. Nagy, M., Ákos, Z., Biro, D. & Vicsek, T. Hierarchical group dynamics in pigeon flocks. *Nature 2010 464:7290* **464**, 890–893 (2010).

39. Parrish, J. K. & Edelstein-Keshet, L. Complexity, Pattern, and Evolutionary Trade-Offs in Animal Aggregation. *Science (1979)* **284**, 99–101 (1999).

40. Sumpter, D. J. T., Krause, J., James, R., Couzin, I. D. & Ward, A. J. W. Consensus Decision Making by Fish. *Current Biology* **18**, 1773–1777 (2008).

41. Bialek, W. *et al.* Statistical mechanics for natural flocks of birds. *Proceedings of the National Academy of Sciences* **109**, 4786–4791 (2012).

42. Couzin, I. D., Krause, J., Franks, N. R. & Levin, S. A. Effective leadership and decision-making in animal groups on the move. *Nature* **433**, 513–516 (2005).

43. Sanderson, M. I., Neretti, N., Intrator, N. & Simmons, J. A. Evaluation of an auditory model for echo delay accuracy in wideband biosonar. *J Acoust Soc Am* **114**, 1648–1659 (2003).

44. Neretti, N., Sanderson, M. I., Intrator, N. & Simmons, J. A. Time-frequency model for echo-delay resolution in wideband biosonar. *J Acoust Soc Am* **113**, 2137–2145 (2003).

45. Fujioka, E. *et al.* Three-Dimensional Trajectory Construction and Observation of Group
Behavior of Wild Bats During Cave Emergence. *Journal of Robotics and Mechatronics* **33**,
556–563 (2021).

46. Theriault, D. H. *et al.* Reconstruction and analysis of 3D trajectories of Brazilian free-tailed
bats in flight. *cs-web.bu.edu*.

47. Tsoar, A. *et al.* Large-scale navigational map in a mammal. *Proc Natl Acad Sci U S A* **108**,
E718–E724 (2011).

48. Jensen, M. E., Moss, C. F. & Surlykke, A. Echolocating bats can use acoustic landmarks
for spatial orientation. *Journal of Experimental Biology* **208**, 4399–4410 (2005).

49. Jones, T. K. & Conner, W. E. The jamming avoidance response in echolocating bats.
Commun Integr Biol **12**, 10–13 (2019).

50. Sabol, B. M. & Hudson, M. K. Technique using thermal infrared-imaging for estimating
populations of gray bats. *J Mammal* **76**, (1995).

51. Betke, M. *et al.* Thermal Imaging Reveals Significantly Smaller Brazilian Free-Tailed Bat
Colonies Than Previously Estimated. *J Mammal* **89**, 18–24 (2008).

52. Tressler, J. & Smotherman, M. S. Context-dependent effects of noise on echolocation pulse
characteristics in free-tailed bats. *J Comp Physiol A Neuroethol Sens Neural Behav Physiol*
195, 923–934 (2009).

53. Kalko, E. K. V. Insect pursuit, prey capture and echolocation in pipistrelle bats
(Microchirptera). *Anim Behav* **50**, 861–880 (1995).

54. Schnitzler, H., Kalko, E. & Miller, L. How the Bat, Pipistrellus Kuhli, Hunts for Insects.
Animal Sonar 619–623 (1988).

55. Taub, M. & Yovel, Y. Segregating signal from noise through movement in echolocating
bats. *Sci Rep* **10**, 1–10 (2020).

56. Taub, M., Mazar, O. & Yovel, Y. Pregnancy-related sensory deficits might impair foraging
in echolocating bats. *BMC Biology 2023 21:1* **21**, 1–9 (2023).

57.   Fawcett, K. & Ratcliffe, J. M. Clutter and conspecifics: a comparison of their influence on
645   echolocation and flight behaviour in Daubenton's bat, Myotis daubentonii. *J Comp Physiol*
646   *A Neuroethol Sens Neural Behav Physiol* **201**, 295–304 (2015).

647   58.   Grodzinski, U., Spiegel, O., Korine, C. & Holderied, M. W. Context-dependent flight speed:
648   Evidence for energetically optimal flight speed in the bat Pipistrellus kuhlii? *Journal of*
649   *Animal Ecology* **78**, (2009).

650   59.   Yovel, Y., Melcon, M. L., Franz, M. O., Denzinger, A. & Schnitzler, H. U. The voice of
651   bats: How greater mouse-eared bats recognize individuals based on their echolocation calls.
652   *PLoS Comput Biol* **5**, (2009).

653   60.   Yovel, Y., Franz, M. O., Stilz, P. & Schnitzler, H. U. Complex echo classification by echo-
654   locating bats: a review. *Journal of Comparative Physiology A* **197**, 475–490 (2010).

655   61.   Schnitzler, H. U., Moss, C. F. & Denzinger, A. From spatial orientation to food acquisition
656   in echolocating bats. *Trends Ecol Evol* (2003) doi:10.1016/S0169-5347(03)00185-X.

657   62.   Ratcliffe, J. M. *et al.* Conspecifics influence call design in the Brazilian free-tailed bat,
658   Tadarida brasiliensis. *cdnsciencepub.comJM Ratcliffe, HM Hofstede, R Avila-Flores, MB*
659   *Fenton, GF McCracken, S Biscardi, J BlaskoCanadian Journal of Zoology,*
660   *2004•cdnsciencepub.com* **82**, 966–971 (2004).

661   63.   Yovel, Y. & Ulanovsky, N. Bat Navigation. *The Curated Reference Collection in*
662   *Neuroscience and Biobehavioral Psychology* 333–345 (2017) doi:10.1016/B978-0-12-
663   809324-5.21031-6.

664   64.   Moss, C. F. & Surlykke, A. Probing the natural scene by echolocation in bats. *Frontiers in*
665   *Behavioral Neuroscience* vol. 4 Preprint at https://doi.org/10.3389/fnbeh.2010.00033
666   (2010).

667   65.   Moss, C. F. & Surlykke, A. Auditory scene analysis by echolocation in bats. *Citation: The*
668   *Journal of the Acoustical Society of America* **110**, 2207 (2001).

669   66.   Chili, C., Xian, W. & Moss, C. F. Adaptive echolocation behavior in bats for the analysis
670   of auditory scenes. *Journal of Experimental Biology* **212**, 1392–1404 (2009).

67. Corcoran, A. J. & Moss, C. F. Sensing in a noisy world: lessons from auditory specialists,
echolocating bats. *Journal of Experimental Biology* **220**, 4554–4566 (2017).

68. Munoz, N. E. & Blumstein, D. T. Multisensory perception in uncertain environments.
Behavioral Ecology **23**, 457–462 (2012).

69. Daria Genzel, Yossi Yovel & Michael M. Yartsev. Neuroethology of bat navigation.
Current Biology R997–R1004 (2018).

70. Boonman, A., Bar-On, Y., Cvikel, N. & Yovel, Y. It's not black or white-on the range of
vision and echolocation in echolocating bats. *Front Physiol* **4 SEP**, 1–12 (2013).

71. Danilovich, S. & Yovel, Y. Integrating vision and echolocation for navigation and
perception in bats. *Sci Adv* **5**, (2019).

72. Harten, L., Katz, A., Goldshtein, A., Handel, M. & Yovel, Y. The ontogeny of a mammalian
cognitive map in the real world. *Science (1979)* **369**, 194–197 (2020).

73. Prat, Y. & Yovel, Y. Decision making in foraging bats. *Curr Opin Neurobiol* **60**, 169–175
(2020).

74. Barchi, J. R., Knowles, J. M. & Simmons, J. A. Spatial memory and stereotypy of flight
paths by big brown bats in cluttered surroundings. *Journal of Experimental Biology* **216**,
1053–1063 (2013).

75. Geva-Sagiv, M., Las, L., Yovel, Y. & Ulanovsky, N. Spatial cognition in bats and rats: from
sensory acquisition to multiscale maps and navigation. *Nature Reviews Neuroscience 2015*
16:2 **16**, 94–108 (2015).

76. Gunier, W. J. & Elder, W. H. Experimental Homing of Gray Bats to a Maternity Colony in
a Missouri Barn. *American Midland Naturalist* **86**, 502 (1971).

77. Garnier, S., Gautrais, J. & Theraulaz, G. The biological principles of swarm intelligence.
Swarm Intelligence **1**, (2007).

78. Fischer, D., Mostaghim, S. & Albantakis, L. How swarm size during evolution impacts the
behavior, generalizability, and brain complexity of animats performing a spatial navigation
task. in *GECCO 2018 - Proceedings of the 2018 Genetic and Evolutionary Computation*
Conference (2018). doi:10.1145/3205455.3205646.

79. Schnitzler, H.-U., Kalko, E., Miller, L. & Surlykke, A. The echolocation and hunting behavior of the bat,Pipistrellus kuhli. *Journal of Comparative Physiology A* **161**, 267–274 (1987).

80. Wilson, W. W. & Moss, C. F. Sensory-motor behavior of free-flying FM bats during target capture. *Advances in the study of echolocation in bats and dolphins* 22–27 Preprint at (2004).

81. Schnitzler, H. U. & Kober, R. Information in sonar echoes of fluttering insects available for echolocating bats. *Journal of the Acoustical Society of America* **87**, 882–896 (1990).

82. Kuc, R. Sensorimotor model of bat echolocation and prey capture. *J Acoust Soc Am* **96**, 1965–1978 (1994).

83. Vanderelst, D. & Peremans, H. Modeling bat prey capture in echolocating bats : The feasibility of reactive pursuit. *J Theor Biol* **456**, 305–314 (2018).

84. Ghose, K., Horiuchi, T. K., Krishnaprasad, P. S. & Moss, C. F. Echolocating bats use a nearly time-optimal strategy to intercept prey. *PLoS Biol* **4**, 865–873 (2006).

85. Mazar, H. *Radio Spectrum Management: Policies, Regulations, Standards and Techniques*. (John Wiley & Sons, Ltd, 2016).

86. H. T. Friis. A Note on a Simple Transmission Formula. *Proceedings of the IRE* **34**, 254–256 (1946).

87. Rahman, F. U. *et al.* Occurrence of Rhinopoma microphyllum (Brunnich, 1782) in Khyber Pakhtoonkhawa, Pakistan. *J Anim Plant Sci* **25**, (2015).

88. Boonman, A. & Ostwald, J. A modeling approach to explain pulse design in bats. *Biol Cybern* **97**, 159–172 (2007).

89. Weißenbacher, P. & Wiegrebe, L. Classification of virtual objects in the echolocating bat, Megaderma lyra. *Behavioral Neuroscience* **117**, 833–839 (2003).

90. Saillant, P. A., Simmons, J. A. & Dear, S. P. A computational model of echo processing and acoustic imaging in frequency-modulated echolocating bats: The spectrogram correlation and transformation receiver. *Citation: The Journal of the Acoustical Society of America* **94**, 2691 (1993).

91.   Popper, A. N. & Fay, R. R. *Hearing by Bats*. (Springer-Verlag, 1995).

92.   Simmons, J. A. *et al.* Acuity of horizontal angle discrimination by the echolocating bat ,
Eptesicus fuscus. (1983).

93.   Hans-Ulrich Schnitzler & Elisabeth K. V. Kalko. echolocation by insect-eating bats.
Bioscience **51**, 557–569 (2001).