Fitness translocation: improving variant effect prediction with biologically-grounded data augmentation

Adrien Mialland
Artificial Intelligence Research Center, AIST [1]
mialland.a@gmail.com ⦿

Shuzo Fukunaga
University of Toronto
sfukunaga.academia@gmail.com

Riku Katsuki
The University of Electro-Communications
k2343004@gl.cc.uec.ac.jp

Yunfei Dong
The University of Tokyo
dong_yunfei_23@stu-cbms.k.u-tokyo.ac.jp

Hideki Yamaguchi
The University of Tokyo
yamaguchi.h.et.al@gmail.com

Yutaka Saito
Artificial Intelligence Research Center, AIST [1]
The University of Tokyo
School of Frontier Engineering, Kitasato University
saito.yutaka@kitasato-u.ac.jp ⦿

Abstract

Predicting the functional effects of protein variants (variant effect prediction) is essential in protein engineering but remains challenging due to the scarcity of fitness data for training prediction models. To address this limitation, we introduce a data augmentation strategy called fitness translocation, which leverages variant fitness data from homologous proteins to enhance prediction models for a target protein. Using embeddings from protein language models, our method computes the differences between the homologs wild type and its variants, which are applied to the target wild type to generate its synthetic variants in the embedding space. We evaluate this approach on three protein families: IGPS, GFP, and SARS-CoV-2 spike proteins, under various prediction models and training data sizes. Fitness translocation consistently improves prediction accuracy, especially under limited training data. Moreover, accuracy improvement is observed even between remote homologs with sequence identity as low as 35%. These results highlight the potential of data-efficient protein engineering by reusing fitness data previously accumulated in homologs. The code is available at https://github.com/adrienmialland/ProtFitTrans.

Keywords— machine learning, protein engineering, directed evolution, library design, training data, sequence space exploration

---

[1]National Institute of Advanced Industrial Science and Technology

1   Introduction

Understanding the relationship between protein sequence and function is central to protein engineering. Mapping this relationship accurately enables the rational design of proteins with novel or enhanced functions and supports the interpretation of mutations in both natural and engineered contexts [1]. In this setting, fitness refers to a quantitative measure of how well a protein performs a desired function such as enzymatic activity, binding affinity, or fluorescence. The fitness landscape describes the conceptual mapping from sequences to their corresponding fitness values, illustrating how sequence variations influence functional performance [2].

Exploring the fitness landscape experimentally is inherently limited by the vastness of sequence space. Even mutating a modest number of amino acid sites results in a combinatorial explosion of possible variants, 20^k for k sites, making comprehensive measurements infeasible. While modern technologies such as deep mutational scanning and high-throughput screening allow for the generation of large protein variant libraries [3–5], measuring fitness for each sequence remains costly and often less scalable than library construction [4]. Consequently, most experimentally characterized fitness landscapes are sparsely sampled, limiting our ability to generalize from observed variants to unseen ones.

To address this problem, machine learning models have been widely applied to learn the mapping from sequence to fitness using available experimental data [1, 6–9]. These models aim to generalize to unmeasured variants, enabling in silico prediction of fitness across unexplored regions of sequence space. This task, known as variant effect prediction, is essential in data-driven protein engineering, where the goal is to prioritize functionally promising variants for further testing. However, model performance is strongly influenced by the size and diversity of training data. Limited training data often lead to overfitting or poor generalization, particularly when the the data cover only a narrow region of sequence space.

One promising strategy to overcome this limitation is data augmentation, which involves generating synthetic training data by modifying existing data. In fields such as computer vision and natural language processing, data augmentation techniques such as image transformations or sentence paraphrasing are widely used to improve model generalization by increasing dataset diversity without requiring new labeled data [10, 11]. In protein variant effect prediction, however, direct analogs of these techniques are less straightforward, and effective augmentation strategies remain underexplored. A biologically motivated approach is to leverage information from homologous proteins, which often share structural and functional features due to common ancestry. Recent studies suggest that fitness landscapes may be partially conserved across homologs [12], indicating that variant fitness information in one homolog could help predictions in another if such information can be transferred appropriately.

Here, we introduce a data augmentation strategy called *fitness translocation*, which enables the transfer of variant fitness information across homologs. Given variant fitness data from a homolog, we use embeddings derived from protein language models (pLMs) [13, 14] to compute the difference between each variant and its wild type, capturing the mutational change as a vector offset. These offsets are then applied to the embedding of the target wild type to generate synthetic variants in the embedding space, effectively augmenting training data for the target protein. We evaluate fitness translocation on three protein families with diverse biological functions and experimental fitness assays: IGPS homologs [12], GFP homologs [15], and SARS-CoV-2 spike proteins [16], covering enzymatic activity, fluorescence intensity, and cell entry or receptor binding, respectively. We assess predictive performance using various prediction models and a range of training data sizes. We demonstrate that fitness translocation consistently improves variant effect prediction, particularly in low-data regimes. We also present algorithms to identify which homolog datasets are most beneficial for augmentation, allowing to adaptively utilize available datasets. These results highlight the potential of biologically grounded data augmentation to enable data-efficient protein engineering.

2   Methods

2.1   Problem Setting and Overview

Variants effect prediction is a task to estimate the fitness of variants relative to its wild type using experimental fitness measurements as training data. In typical protein engineering settings, only a small fraction of possible variants is measured due to practical constraints. The objective is to build prediction models that can generalize from these observed variants to unmeasured ones. To improve model performance in such low-data scenarios, we propose to augment available training data using fitness-labeled variants from homologous proteins with related sequences and functions. While homologs differ from the target protein in sequence, we assume that they often share similar fitness landscape due to their common ancestry. This creates an opportunity for transferring variant fitness information from homologs to the target.

Our proposed method, named fitness translocation, uses pLMs to represent sequences in an embedding space (Figure 1). In this space, we analyze how mutations shift the embedding of a homolog's wild-type sequence. These shifts, referred to as mutation offsets, are then applied to the target wild type to generate synthetic variants

in the embedding space. These synthetic variants are integrated with real variants to expand training data for prediction models.

Figure 1: Concept of Fitness Translocation. WT: Wild-Type. (a) The embeddings of the homologs variants shift the wild-type embedding. (b) When fitness translocation is applied, these shifts, or mutation offsets, are applied to the target wild-type to generate synthetic variants.

2.2   Protein Language Model Embeddings

To represent protein sequences in a form suitable for machine learning and data augmentation, we use pLMs, deep learning models pretrained on large corpora of natural protein sequences. pLMs are used to calculate a sequence embedding, fixed-length numerical vector representing sequence information. Because pLMs are pretrained on diverse protein families, they enable meaningful comparisons between sequences even across homologs, providing the foundation for fitness translocation. We used ESM-2 [14] or ESM-1v [17] pLMs (esm2_t33_650M_UR50D and esm1v_t33_650M_UR90S_1 respectively), but other existing pLMs can be used (e.g. [18, 19]).

2.3   Fitness Translocation

Fitness translocation is a data augmentation method that generates synthetic training data for a target protein by transferring variant fitness data obtained in a homologous protein. Given a homolog, we first compute embeddings for both its wild-type and variants using pLM. For each variant, we calculate a mutation offset, defined as the difference between the variant embedding and the wild-type embedding (Figure 1). This offset captures how the mutation shifts the representation of the homolog in the embedding space. To generate a synthetic variant for the target protein, we add the mutation offset from each homolog variant to the target wild-type embedding. The resulting synthetic embedding simulates how an analogous mutation might affect the target protein, under the assumption that the fitness landscape is at least partially conserved between the homolog and the target. We associate the synthetic variant with the same fitness value as the original homologous variant, normalized by the corresponding wild-type fitness value. While this may not reflect the true fitness of the unmeasured target variant, it provides a training signal grounded in evolutionarily related data. The set of synthetic variants, each represented as an embedding paired with a fitness label, is combined with (added to) the original training data for the target protein. By augmenting the target dataset in this way, fitness translocation increases the diversity of training data without requiring new experimental measurements. This approach is expected to be beneficial in low-data regimes where variant effect prediction models struggle to generalize from limited training data.

2.4   Prediction Models and Training Setup

To evaluate the effect of data augmentation by fitness translocation, we trained supervised regression models to predict the variant fitness from a sequence embedding. Each training sample consists of a sequence embedding, either from a real variant or a synthetic variant generated via fitness translocation, and the corresponding fitness label. When training with augmented data, synthetic variants were added to training data alongside the measured variants from the target protein. We tested three types of regression models: support vector regression (SVR), random forest regression (RF), and linear regression with L1 regularization (Lasso). Hyperparameters were selected through nested cross-validation (CV) [20] on training data.

For each target protein, we trained models under multiple training sizes to simulate low to moderate data scenarios. We used held-out test data from the same protein to evaluate prediction with and without augmentation. In all settings, test data contained only real variants that were never seen during training, ensuring a fair comparison between augmentation and baseline conditions.

2.5 Dataset

We evaluated fitness translocation using three protein families with experimentally measured variant fitness data: IGPS homologs, GFP homologs, and SARS-CoV-2 spike proteins. Each family includes multiple related proteins, allowing us to examine augmentation across homologs with varying levels of sequence similarity and biological context (Table 1).

Table 1: Summary of the dataset. The pairwise sequence identities and similarities are computed using EMBOSS Needle and EMBOSS Water [21], respectively for global and local alignment.

Protein Family	Homologs	Number of Variants	EMBOSS Needle		EMBOSS Water	
			Identity	Similarity	Identity	Similarity
IGPS	SsIGPS	1497	TmIGPS: 35.5% TtIGPS: 39.6%	TmIGPS: 56.7% TtIGPS: 55.8%	TmIGPS: 37.1% TtIGPS: 42.9%	TmIGPS: 58.8% TtIGPS: 60.1%
	TmIGPS	1502	SsIGPS: 35.5% TtIGPS: 35%	SsIGPS: 56.7% TtIGPS: 49.1%	SsIGPS: 37.1% TtIGPS: 36.4%	SsIGPS: 58.8% TtIGPS: 51.2%
	TtIGPS	1489	SsIGPS: 39.5% TmIGPS: 35%	SsIGPS: 55.8% TmIGPS: 49.1%	SsIGPS: 42.9% TmIGPS: 36.4%	SsIGPS: 60.1% TmIGPS: 51.2%
GFP	amacGFP	35500	cgreGFP: 42.7% ppluGFP: 17.9%	cgreGFP: 62.6% ppluGFP: 29.9%	cgreGFP: 45.1% ppluGFP: 25.2%	cgreGFP: 65.9% ppluGFP: 41.5%
	cgreGFP	26165	amacGFP: 42.7% ppluGFP: 18.5%	amacGFP: 62.6% ppluGFP: 32.3%	amacGFP: 45.1% ppluGFP: 23.2%	amacGFP: 65.9% ppluGFP: 38.4%
	ppluGFP	32260	amacGFP: 17.9% cgreGFP: 18.5%	amacGFP: 29.9% cgreGFP: 32.3%	amacGFP: 25.2% cgreGFP: 23.2%	amacGFP: 41.5% cgreGFP: 38.4%
SARS-CoV-2	XBB.1.5	7029	BA.2: 98.9%	BA.2: 98.8%	BA.2: 98.9%	BA.2: 98.9%
	BA.2	7129	XBB.1.5: 98.9%	XBB.1.5: 98.8%	XBB.1.5: 98.9%	XBB.1.5: 98.9%

IGPS homologs [12]: This set includes three homologs of imidazole glycerol phosphate synthase (IGPS) originated from *Thermogama maritima* (TmIPGS), *Sulfolobus Solfataricus* (SsIGPS), *Streptococus thermopjilus* (TtIGPS). Variant fitness data are measured for single-point mutants of each IGPS homolog based on growth rate under histidine-limited conditions, which represents the enzymatic activity of IGPS.

GFP homologs [15]: This family includes green fluorescent protein (GFP) originated from *Aequorea macrodactyla, Hydrozoa* (amacGFP), *Clytia gregaria, Hydrozoa* (cgreGFP), *Pontellina plumata, Copepoda* (ppluGFP). The fitness is defined by fluorescence intensity, measured for variants of each GFP homolog.

SARS-CoV-2 spike proteins [16]: This dataset includes spike protein variants from the two SARS-CoV-2 omicron strains: *XBB.1.5* and *BA.2* Variant fitness is quantified by ACE2 binding affinity or cell entry efficiency.

For each family, we designated one protein as the target for variant effect prediction and used one or more homologs as augmentation sources for fitness translocation. Variant fitness values were normalized by the wild-type fitness of the respective protein.

2.6 Homolog Selection Algorithms

When multiple homologs are available for a given protein family, not all are necessarily beneficial for data augmentation. So, we developed the homolog selection algorithms to identify which homologs are most informative for fitness translocation to a given target. The basic idea is to evaluate, across multiple train/validation splits, which homologs consistently improve model performance when added to the target dataset. Given a target protein, a set of homologs, a number N of data split, and a significance threshold α, the first selection stage measures the average change in predictive accuracy (denoted Δ_μ) when each individual homolog is translocated into the target data (Figure 1). We then compute whether this change is statistically significant across the data splits, retaining only the homologs that yield a significant positive effect. In the second stage, these selected homologs are further evaluated in combination, translocating one homolog after another from the highest to the lowest scoring. Each translocated homolog is kept only if it improves the performance of the previous combination, in order to identify the optimal set for fitness translocation. The formal description of our algorithm is shown in Algorithm S1 (Supplementary Data).

3 Results

Our fitness translocation method was evaluated on 60 configurations: (4 SARS-CoV-2 + 3 IGPS + 3 GFP) targets × 2 pLMs × 3 predictors. For a given configuration (associated with a target protein), 26 target training sizes from 45 up to 1125 variants were considered to undergo fitness translocation. For a given target training size, the homolog selection algorithm was applied to identify the optimal set of homologs, followed by the translocation of all possible set of homologs for comparisons. The performances of the variant effect prediction tasks were evaluated using Spearmans correlation between true and predicted fitness values over train/validation splits, and a number of $N = 50$ splits were considered to extract the corresponding sample of Spearmans correlation. Two sample of Spearmans correlation were then statistically compared using a one-sided paired t-test to evaluate whether the mean difference indicated an increase in performances, and a significant threshold of $\alpha = 0.05$ was used. Therefore, the corresponding minimal value that a paired t-test can reliably detect depends on the distribution of the samples, and is given by the following formula [22]:

$$\Delta_{\min} = t_{\alpha, N-1} \cdot \frac{s_d}{\sqrt{N}} \tag{1}$$

Where α is the significance threshold, N is the number of train/validation splits, $t_{\alpha, N-1}$ is the critical value of the Student-distribution for $N - 1$ degrees of freedom at the significance level α, and s_d is the standard deviation of the paired differences. Consequently, the minimum detectable improvement $\Delta_{\min}$ decreases as N increases and depends on the ability of a predictor to provide stable performances over multiple splits.

3.1 Fitness Translocation Evaluation

Figure 2, 3, and 4 respectively show representative results of IGPS, GFP, and SARS-CoV-2 spike protein cell entry (ACE2 binding available in the Supplementals Figure S15.2, as it shows similar behaviour to cell entry) for all possible set of translocated homologs, using the ESM2 pLM and the SVM classifier. The optimal set of homologs selected through the homolog selection algorithm, are then highlighted with a red line over all target training sizes. The additional results are reported in the Supplementary Data.

Figure 2: **Top:** Results for IGPS, ESM2 pLM, and SVR predictor. All combination of homologs yielded significant improvement, especially for smaller target training sizes. The optimal set of homolog selected by our method is highlighted with the red line, which shows its effectiveness for maximizing the improvement. **Bottom:** minimum average paired difference in performances $\Delta_{\min}$ that can be detected (Equation 1). It is inversely proportional to the training size and depends also on N.

These results reveal that incorporating additional protein data in a target protein dataset can substantially improve the performances of a variant effect prediction task. The effect was particularly visible for smaller sizes and was the biggest for SARS-CoV-2 cell entry (Figure S2, S6), followed by SARS-CoV-2 ACE2 binding (Figure S3, S7), IGPS (Figure S4, S8) and GFP (Figure S5, S9) families. Significant and consistent improvement could be achieved with IGPS and SARS-CoV-2 spike proteins, with the lowest sequence identity being 35% between TmIGPS and TtIGPS (Table 1). Improvement on GFP family was limited and occurred for smaller target training sizes in most cases, although some configurations yielded substantial improvements (Figure S17.2). Besides, the homolog selection algorithm was able to reliably select among the best performing set of homologs, that achieves a significant increase in performances on the target protein variants effect prediction

Figure 3: **Top:** Results for GFP, ESM2 pLM, and SVR predictor. Limited improvement could be achieved, and only for small target training size, but few other configurations still yielded substantial increase in performances (e.g Figure S17.2). The optimal set of homolog selected by the homolog selection algorithm is highlighted with the red line, and when no improvement was achieved, the original dataset was consistently selected as the best one. **Bottom:** minimum average paired difference in performances $\Delta_{\min}$ that can be detected (Equation 1). It is inversely proportional to the training size and depends also on N. The red line fluctuations arise from statistical instability, where increasing N would reduce the uncertainty and allow for smaller $\Delta_{\min}$ detection.

Figure 4: **Top:** Results for SARS-CoV-2 spike protein cell entry, ESM2 pLM, and SVR predictor. It achieved the highest increase in performances among all protein family, which allowed the homolog selection algorithm to easily select the translocated homolog, as highlighted with the red line. **Bottom:** minimum average paired difference in performances $\Delta_{\min}$ that can be detected (Equation 1). It is inversely proportional to the training size and depends also on N.

task. Especially, when the relative improvement between different homologs combinations were small, the lowest scoring combinations were systematically excluded (e.g Figure 2, S12.1). Also, in the case where no improvement could be achieved, the original target dataset was selected as the best one (e.g Figure 3, S13.3).

This behaviour stem from the use to the one-sided version of the paired t-test. It naturally establishes an upper threshold and minimizes the influences of the statistical fluctuations from non-effective combinations, which could otherwise be selected accidentally. Therefore, the initial selection of homologs in the homolog selection algorithm is improved. Besides, in cases where the improvement was too small to reach statistical significance,

increasing N may benefit the selection process, to decrease the minimum detectable improvement Δ_{min}. In particular, the variations in selection observed for smaller target training sizes in GFP family (Figure S13, S17), arised from the limited improvements it provided, which could not consistently reach statistical significance, while still showcasing reduced but noticeable improvements. In other words, statistical fluctuations could make the average (over N) improvement appear inconsistent, preventing detection when the true average is close to Δ_{min}, whereas a larger N would smooth out these fluctuations and decrease Δ_{min}. In addition, for all configuration that we evaluated (Figure S10, S11, S12, S13, S14, S15, S16, S17), the minimum detectable improvement Δ_{min} followed the expected trend expressed by Equation 1. For the smallest target training size, the sample size $N = 50$ resulted in Δ_{min} between 0.1 and 0.07, which then rapidly decreased as the target training size increased, to reach between 0.017 and 0.005 for the biggest target training sizes. In other words, the fitness translocation method naturally allows to detect smaller improvements as the target training size increases.

3.2 Ablation Experiment on Homolog Selection Algorithm

We conducted an ablation study to assess the contribution of individual components in the homolog selection procedure. In the first ablation scenario, we removed the statistical testing in the first selection stage and used the cross-validation performance within the target protein training data as a selection threshold. The second stage was kept unchanged to allow for sorting out the initial selection of homologs. So, in situation where the translocation of each individual homologs yielded substantial improvements in the first stage, this ablation scenario and the original selection method led to similar final set, as the second stage operated on similar sets (e.g. Figure S24, S36). However, when an individual homolog achieved poor performances in the first stage, the lack of paired t-test did not allow to effectively manage the statistical fluctuations (e.g. Figure S28.2, S39.2, S26.2), often resulting in suboptimal selections with poorer generalization capability.

The second ablation scenario starts with the same configuration as the first scenario – removing the statistical testing in the first selection stage. However, we also removed the second selection stage that sorts out the initial selected set, which results in all homologs from the first stage being selected as the final set. this approach led to similar consideration as the first ablations scenario, with the additional downside that the lack of sorting could not allow for the initial selection of homologs to be refined (e.g Figure S25.3, S36.3, S39.3), resulting in the worst results.

3.3 Performance Trends Across Homolog Combinations

The assessment of all possible combination showed that the results were dependent on the type of predictor and the combination being translocated, with consistency across various configurations.

Absolute Amplitudes Trend. In all family $-$ target $-$ pLM $-$ predictor configurations, the effect of the translocation eventually reached a saturation point as the target training sizes increased (Figure S4, S5, S8, S9), or indicated a trend toward saturation (Figure S2, S3, S6, S7). In other words, the performance difference between with and without fitness translocation becomes small as the target training size increases. The SARS-COV-2 spike proteins for cell entry had 12 configurations tested (2 targets $\times$ 2 pLMs $\times$ 3 predictors, Figure S2, S6) and had the biggest improvement, followed by SARS-CoV-2 spike proteins for ACE2 bindings that also had 12 configurations tested (Figure S3, S7). These results were consistent across all configurations and were substantial for all 26 target training sizes. The IGPS family had 18 configurations tested (3 targets $\times$ 2 pLMs $\times$ 3 predictors, Figure S4, S8) and had the second biggest improvement. It was consistent across target $-$ pLM configurations, and reaches saturation toward the higher target training sizes, but was dependent on the predictor. Specifically, the RF predictor resulted in decreased performances for the higher target training sizes (Figure S4.3, S8.3). The GFP family had 18 configurations tested (Figure S6, S9) and had the lowest performances. It was consistent across pLMs models, but showed varying trend over the target training sizes, and was dependent on both the target and the predictor. However, some configurations still provided substantial improvement for all 26 target training sizes (Figure S5.2, S9.2). Besides, as an overall trend, the final performances were mainly dependent on the content of the translocated combination and the type of predictor, where specific combinations could either increase or decrease the original performances. The effects of the pLMs were mostly marginal and mostly acted on the overall magnitude of the results, rather than the inherent capabilities of the additional datasets. However, the GFP family did not exhibit a clear pattern and had varying performances depending of the choice of species used as the target (Figure S5, S9).

Relative Amplitudes Trend. We assessed the relative amplitude between pairs of translocated combinations for IGPS and GFP families. For a given target, the relative amplitude between each pair showed a repeatable trend over each pLMs and each predictor. In other word, the translocated combinations could reliably be classified from the highest to the lowest performing. This was especially visible when the relative amplitude was more pronounced, and a representative example can be seen with IGPS family and SsIGPS species used as the target (Figure 2). The best improvement over both ESM model and all 3 predictors was

consistently observed with the translocation of TtIGPS, followed by TmIGPS + TtIGPS together, and then by TmIGPS alone (Figure S4, S8). Even for the RF classifier, that performed poorer than the SVR and Lasso classifier, no significant disruption of the overall trend could be noticed. Also, it should be specified that when the relative amplitude between pairs of combinations is not substantial (e.g. Figure S4.3, S8.3), the overall trend can probably be assessed as a whole as any impact on the trend, over different configurations, may be considered as statistical variations. Besides, and more interestingly, the relative amplitudes tended to be conserved over different targets. For instance, in IGPS family the translocation of TmIGPS consistently performed the worst over all targets that used it, and over all ESM and predictor configurations (Figure S4, S8). Finally, despite the reduced improvement that fitness translocation provided on GFP family, it still exhibited similar trends in relative amplitude between the translocated combinations (Figure S5, S9).

4 Discussion

This study demonstrates the potential of fitness translocation to address challenges in protein variant effect prediction tasks when available data is limited. By leveraging fitness landscapes from related proteins, this method enables the construction of augmented datasets that improve the prediction performance of a target protein. These findings highlight the benefit of fitness translocation as an effective approach to expand sequence-function annotations based on prior engineering efforts, and to improve the predictive performances for proteins with limited experimental data.

Comparison with Traditional Methods. Traditional data augmentation methods have been commonly used in various modern machine learning approaches, demonstrating their effectiveness in fields such as computer vision [23, 11] or natural language processing (NLP) [24, 25]. These methods range from basic manipulations, such as rotation or cropping, to the generation of synthetic data using advanced methods. However, these approaches are difficult to apply on protein data due to their unique characteristics. Proteins are subject to complex sequence-function relationships, where even a single residue mutation can significantly alter the properties of a given protein and must be carefully considered [26]. Moreover, recent investigations explored the advantages of multiple image and text related data augmentation methods for protein sequence prediction [27]. The authors suggest that while improvement can be achieved, the performance gains may be suboptimal and that innovative methods tailored to protein data are required. In that regard, our proposed fitness translocation method provides a simple framework for protein variant effect prediction that enables the use of protein data and fitness landscapes from past experiments. It allows to augment a given dataset without relying on synthetic data and with no alteration of the sequence-function pairs.

Fitness Translocation Evaluation. The generalizability of the fitness translocation method across multiple configurations, as shown by our results, makes it a reliable and easy to apply data augmentation approach for enhancing target protein datasets. Even for the GFP protein family, where improvements were not consistent across all configurations, significant gains were observed under specific conditions (Figure S5.2, S9.2). This later point suggests that certain protein species may only benefit from the translocation of a subsets of homologs, highlighting the potential advantage of increasing the number of homolog's datasets considered for fitness translocation. However, this may result in a significant increase in processing time if all possible combinations are evaluated. With a number of m homologs, each one of them being either included or not in the final augmented dataset, this would require a number of 2^m combinations to be evaluated. The introduction of the homolog selection algorithm in our method allows to effectively address this issue, by prioritizing the most promising combinations and reducing the number of evaluations to a maximum of $2m$. This upper limit is only maximized if all homologs are selected during the first selection stage. The use of a one-sided paired t-test can further improve both the processing times and the final performances, by reducing the impact of statistical variations and only considering the meaningful improvements. In that regard, Equation 1 provides a simple solution to set a relevant minimum detectable improvement $\Delta_{\min}$, with the downside that increasing N does not scale linearly with $\Delta_{\min}$, as it is proportional to $1/\sqrt{N}$. However, the use of $N = 50$ in this study was sufficient to achieve a $\Delta_{\min}$ below 0.1 for the smallest target training size, with $\Delta_{\min}$ rapidly decreasing as the training size increased (Figures 2, 3, 4). In addition, $\Delta_{\min}$ also depends on s_d, which is fixed by a given configuration. So, for a specific configuration, using the one-sided paired t-test with our homolog selection algorithm and a reasonably high number N can both provide reliable and meaningful results in a reduced processing time.

Biological Validity of Fitness Translocation. Recent investigations into phylogenetically divergent IGPS proteins with the TIM barrel fold, showing only 35-39.6% sequence identity (Table 1), have explored the evolutionary constraints imposed by sequence and structural requirements [12]. The study revealed unexpected long-range allosteric pathways linking distal residues to the active site, which likely play a critical role in maintaining function. Also, a significant correlation was observed between the fitness landscapes of the distant orthologs. The authors suggested that amino-acid preferences at a given position in the structure are mostly conserved during evolution. These findings propose a general mechanism by which evolutionary pressures contribute to the conservation of fitness landscapes, where such pressures maintain critical biophys-

ical and functional features of the protein, despite sequence divergence. Additionally, previous studies on closely related homologs (influenza virus nucleoproteins), with 94% sequence identity, reported similar results on amino-acid preferences at specific positions [28], further supporting the notion that fitness landscapes are shaped by conserved structural and functional properties, even for low sequence identity. So, the results from the study on IGPS led the authors to interpret landscapes conservation as the translocation of fitness landscapes in the sequence space.

Building on these findings, our study employed pre-trained pLMs to generate latent representations of protein sequences, leveraging their ability to capture intricate structural and functional features encoded in amino acids [13]. These models are pre-trained on large-scale protein sequence datasets containing billions of amino acids and learn internal representations by predicting masked amino acids. This allows the model to infer context-dependent features in a self-supervised manner, producing embeddings that represent the biological properties of protein sequences, while preserving the sequence-function relationship [29]. Our findings show that the translocation of the fitness landscape effectively take advantage of the conserved properties between protein species, with the possibility to generalize beyond the particular TIM barrel fold.

Implications for Protein Engineering. By introducing sequence diversity in datasets for machine learning models, fitness translocation has the potential to improve model generalization capabilities across diverse contexts, facilitating applications such as enzyme engineering or therapeutic development. In the case of directed evolution, the properties of a protein sequence are iteratively improved by mimicking the process of natural selection. It involves several rounds of mutagenesis, expression, and selection, where each round builds upon the previous one to construct a library of sequences that contains high quality variants. Its effectiveness is therefore dependent on the selection process, where a machine learning model should predict the best set of sequences to include in subsequent round [8]. The cost and time required for directed evolution make the fitness translocation method particularly suited to increase the model capabilities, select high quality variants, and limit the number of rounds. More generally, many applications that rely on sequence-function mappings of protein variants would likely benefit from fitness translocation. As an example, modern methods for designing artificial proteins with specific functions, or *de novo* protein design, often involves generative models trained on embeddings from a pLM [30]. These methods may therefore benefit from an augmented dataset with fitness translocation.

5 Conclusion

In this study, we introduced *fitness translocation*, a data augmentation technique for protein variant effect prediction which leverages evolutionary conservation of fitness landscapes. This method enables the translocation of sequence space embedding features from homologs protein datasets to a target protein, enriching its training data with biologically relevant variations from previous protein engineering efforts. We also presented a systematic selection framework that identifies the most beneficial set of homologs for data augmentation. This approach significantly improved the target protein variant effect prediction and demonstrates the utility of fitness translocation, particularly in scenarios with limited data. The implementation of the method is available at `https://github.com/adrienmialland/ProtFitTrans`.

6 Data Availability

The data underlying this article are available in the article and in its online supplementary material. The code is available at `https://github.com/adrienmialland/ProtFitTrans`

7 Supporting Information

Algorithm S1 and Figure S2.1-S41.3 (PDF)

8 Competing interests

The authors declare that they have no competing interests.

9 Author contributions statement

AM and YS developed the method and wrote the paper. AM wrote the code and performed the computational experiments. SF, RK, HY, and YD participated in the preliminary data analysis. All authors read and approved the final version of the manuscript.

10 Acknowledgments

This work was supported by JSPS KAKENHI (22H03691), AMED grant (JP19ak0101122), NEDO grant (JPNP14004), JACI Prize for Encouraging Young Researcher. The computations were partially performed on the NIG supercomputer at ROIS National Institute of Genetics, the ABCI supercomputer at AIST, and the SQUID supercomputer at Cybermedia Center, Osaka University through the HPCI System Research Project (hp230057, hp240075).

References

[1] Notin Pascal, Kollasch Aaron, Ritter Daniel et al. Proteingym: Large-scale benchmarks for protein fitness prediction and design. In *Advances in Neural Information Processing Systems*, 2024.

[2] Romero Philip A et Arnold Frances H. Exploring protein fitness landscapes by directed evolution. In *Nature reviews Molecular cell biology*, 2022. 10.1038/nrm2805.

[3] Gantz Maximilian, Neun Stefanie, Medcalf Elliot J et al. Ultrahigh-throughput enzyme engineering and discovery in in vitro compartments. In *Chemical Reviews*, 2023. 10.1021/acs.chemrev.2c0091.

[4] Vanella Rosario, Kovacevic Gordana, Doffini Vanni et al. High-throughput screening, next generation sequencing and machine learning: advanced methods in enzyme engineering. In *Chemical Communications*, 2022. 10.1039/D1CC04635G.

[5] Markel Ulrich, Essani Khalil D, Besirlioglu Volkan et al Advances in ultrahigh-throughput screening for directed enzyme evolution. In *Chemical Society Reviews*, 2020. 10.1039/C8CS00981C.

[6] Freschlin Chase R, Fahlberg Sarah A et ROMERO Philip A. Machine learning to navigate fitness landscapes for protein engineering. In *Current opinion in biotechnology*, 2022. 10.1016/j.copbio.2022.102713.

[7] Horne Jesse et Shuhla Diwakar. Recent advances in machine learning variant effect prediction tools for protein engineering. In *Industrial & engineering chemistry research*, 2022. 10.1021/acs.iecr.1c04943.

[8] Wittmann Bruce J, Johnston Kadina E, Wu Zachary et al. Advances in machine learning for directed evolution. In *Current opinion in structural biology*, 2021. 10.1016/j.sbi.2021.01.008.

[9] Yang Kevin K, Wu Zachary et Arnold Frances H. Machine-learning-guided directed evolution for protein engineering. In *Nature methods*, 2019. 10.1038/s41592-019-0496-6

[10] Iglesias Guillermo, Talavera Edgar, Gonzalez-Prieto Ángel et al. Data augmentation techniques in time series domain: a survey and taxonomy. In *Neural Computing and Applications*, 2023. 10.1007/s00521-023-08459-3.

[11] Shorten Connor et Khoshgoftaar Taghi M A survey on image data augmentation for deep learning. In *Journal of big data*, 2019. 10.1186/s40537-019-0197-0.

[12] Chan Yvonne H, Venev Sergey V, Zeldovich Konstantin B et al. Correlation of fitness landscapes from three orthologous TIM barrels originates from sequence and structure constraints. In *Nature communications*, 2017. 10.1038/ncomms14614.

[13] Rives Alexander, Meier Joshua, Sercu Tom et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. In *Proceedings of the National Academy of Sciences*, 2021. 10.1073/pnas.2016239118.

[14] Lin Zeming, Akin Halil, Rao Roshan et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. In *Science*, 2023. 10.1126/science.ade2574

[15] Somermeyer Louisa Gonzalez, Fleiss Aubin, Mishin Alexander et al. Heterogeneity of the GFP fitness landscape and data-driven protein design. In *Elife*, 2022. 10.7554/eLife.75842.

[16] Dadonaite Bernadeta, Brown Jack, Mcmahon Teagan E et al. Spike deep mutational scanning helps predict success of SARS-CoV-2 clades. In *Nature*, 2024. 10.1038/s41586-024-07636-1.

[17] Meier Joshua, Rao Roshan, Verkuil Robert et al. Language models enable zero-shot prediction of the effects of mutations on protein function. In *Advances in neural information processing systems*, 2022. 10.1101/2021.07.09.450648

[18] Brandes Nadav, OFer Dan, Rappoport Nadav et al. ProteinBERT: a universal deep-learning model of protein sequence and function. In *Bioinformatics*, 2022. 10.1093/bioinformatics/btac020

[19] Elnaggar Ahmed, Heinzinger Michael, Dallago Christian et al. Prottrans: Toward understanding the language of life through self-supervised learning. In *IEEE transactions on pattern analysis and machine intelligence*, 2021. 10.1109/TPAMI.2021.3095381

[20] Vabalas Andrius, Gowen Emma, Poliakoff Ellen et al. Machine learning algorithm validation with a limited sample size. In *Plos one*, 2019. 10.1371/journal.pone.0224365.

[21] Madeira Fabio, Madhusoodanan Nandana, Lee Joonheung et al. The EMBL-EBI Job Dispatcher sequence analysis tools framework in 2024. In *Nucleic acids research*, 2024. 10.1093/nar/gkae241.

[22] Hsu Henry et Lachenbruch Peter A. Paired t test. In *Wiley StatsRef: statistics reference*, 2014. 10.1002/9781118445112.stat05929.

[23] Takahashi, Ryo, Matsubara Takashi et Uehara Kuniaki. Data augmentation using random image cropping and patching for deep CNNs. In *IEEE Transactions on Circuits and Systems for Video Technology*, 2019. 10.1109/TCSVT.2019.2935128.

[24] Li Bohan, Hou Yutai et Che Wanxiang. Data augmentation approaches in natural language processing: A survey. In *Ai Open*, 2022. 10.1016/j.aiopen.2022.03.001.

[25] Feng Steven Y, Gangal Varun, Wei Jason et al. A survey of data augmentation approaches for NLP. In *arxiv preprint*, 2021. 10.48550/arXiv.2105.03075

[26] Le Hyunjung, Ozbulak Utku, Park Homin et al. Assessing the reliability of point mutation as data augmentation for deep learning with genomic data. In *BMC bioinformatics*, 2024. 10.1186/s12859-024-05787-6.

[27] Sun Rui, Wu Lirong, Lin Haitao et al. Enhancing Protein Predictive Models via Proteins Data Augmentation: A Benchmark and New Directions. In *arXiv preprint*, 2024. 10.48550/arXiv.2403.00875.

[28] Doud Michael B, Ashenberg Orr, et Bloom Jesse D. Site-specific amino acid preferences are mostly conserved in two closely related protein homologs. Molecular biology and evolution. In *Molecular biology and evolution*, 2021. 10.1093/molbev/msv167

[29] Alley Ethan C, Khimulya Grigory, Biswas Surojit et al. Unified rational protein engineering with sequence-based deep representation learning. In *Nature methods*, 2019. 10.1038/s41592-019-0598-1

[30] Tang Xiangru, Dai Howard, Knight Elizabeth et al. A survey of generative ai for de novo drug design: new frontiers in molecule and protein generation. In *Briefings in Bioinformatics*, 2024. 10.1093/bib/bbae338