Accurate and fast segmentation of filaments and membranes in micrographs and tomograms with TARDIS

Robert Kiewisz[1,2], Gunar Fabig[3], Will Conway[2,4], Jake Johnston[2,5], Victor A. Kostyuchenko[6,7], Cyril Bařinka[8], Oliver Clarke[5,9], Magdalena Magaj[10,11,12], Hossein Yazdkhasti[10,11], Francesca Vallese[5,13,14], Shee-Mei Lok[6,7], Stefanie Redemann[10,11,12], Thomas Müller-Reichert[3,15], Tristan Bepler[1,2*]

[1] Simons Machine Learning Center, New York Structural Biology Center, New York, United States

[2] Simons Electron Microscopy Center, New York Structural Biology Center, New York, United States

[3] Experimental Center, Faculty of Medicine Carl Gustav Carus, Technische Universität Dresden, Dresden, Germany

[4] Center for Computational Biology, Flatiron Institute, New York, United State

[5] Department of Physiology and Cellular Biophysics, Columbia University Irving Medical Center, New York, United States

[6] Programme in Emerging Infectious Diseases, Duke-National University of Singapore Medical School, Singapore, Singapore

[7] Centre for Bioimaging Sciences, Department of Biological Sciences, National University of Singapore, Singapore, Singapore

[8] Institute of Biotechnology of the Czech Academy of Sciences, BIOCEV, Vestec, Czech Republic

[9] Department of Anesthesiology, Columbia University Irving Medical Center, New York, United States

[10] Department of Cell Biology, University of Virginia School of Medicine, Charlottesville, United States

[11] Department of Molecular Physiology and Biological Physics, University of Virginia, School of Medicine, Charlottesville, United States

[12] Center for Membrane and Cell Physiology, University of Virginia School of Medicine, Charlottesville, United States

[13] Structural Biology Initiative, CUNY Advanced Science Research Center, New York, United States

[14] Department of Chemistry and Biochemistry, City College of New York, United States

[15] Core Facility Cellular Imaging, Faculty of Medicine Carl Gustav Carus, Technische Universität Dresden, Dresden, Germany

*Corresponding author(s). E-mail(s): tbepler@nysbc.org
Contributing authors: rkiewisz@nysbc.org; gunar.fabig@tu-dresden.de; wconway@nysbc.org; jjohnston@nysbc.org; victor.kostyuchenko@duke-nus.edu.sg; cyril.barinka@ibt.cas.cz; oc2188@cumc.columbia.edu; mmm6fd@virginia.edu; fv2215@cumc.columbia.edu; sheemei.lok@duke-nus.edu.sg; sz5j@virginia.edu; mueller-reichert@tu-dresden.de

Abstract

It is now possible to generate large volumes of high-quality images of biomolecules at near-atomic resolution and in near-native states using cryogenic electron microscopy/electron tomography (Cryo-EM/ET). However, the precise annotation of structures like filaments and membranes remains a major barrier towards applying these methods in high-throughput. To address this, we present TARDIS (**T**ransformer-b**a**sed **R**apid **D**imensionless **I**nstance **S**egmentation), a machine-learning framework for fast and accurate annotation of micrographs and tomograms. TARDIS combines deep learning for semantic segmentation with a novel geometric model for precise instance segmentation of various macromolecules. We develop pre-trained models within TARDIS for segmenting microtubules and membranes, demonstrating high accuracy across multiple modalities and resolutions, enabling segmentation of over 13,000 tomograms from the CZI Cryo-Electron Tomography data portal. As a modular framework, TARDIS can be extended to new structures and imaging modalities with minimal modification. TARDIS is open-source and freely available at https://github.com/SMLC-NYSBC/TARDIS, and accelerates analysis of high-resolution biomolecular structural imaging data.

Keywords: Cryo-EM/ET, TEM EM/ET, Segmentation, TARDIS, CNN, DIST, Semantic Segmentation, Instance Segmentation, Filaments, Microtubules, Membranes, Point Cloud

Introduction

Electron microscopy[1,2] (EM) and electron tomography[3–6] (ET) are leading a revolution in structural biology by enabling high-resolution[7–12] visualization of complex cellular and macromolecular structures[13–15]. Advancements in EM technology[16], such as improved microscope optics, detectors, sample preparation techniques, and data collection automation, have significantly increased acquisition speed and quality. As a result, researchers can now collect tomograms rapidly, leading to the accumulation of tens of thousands of tomograms in databases like EMPIAR[17] and the CZI data portal[18,19]. However, the analysis of these tomograms, especially the annotation of biological structures of interest, is now the primary barrier to unlocking the full potential of this data for studying biological systems. As an example, up to ~300 tomograms can be collected in a single day, but researchers currently spend months painstakingly annotating their biomolecules of interest for downstream analysis[20,21]. Large-scale imaging efforts across the scientific community are now generating thousands of tomograms annually. Notably, the Electron Microscopy Data Bank (EMDB) alone has recorded 8,640 tomogram deposits this year[22]. This surge in data generation requires rapid, automatic annotation methods to identify the position, volume, and quantity of cellular macromolecules[21] to extract biological insights from these rich data sources.

In order to quantitatively study biomolecules, such as microtubules[10,23], membranes[14], ribosomes[24,25], or viral particles[13,26], thousands of tomograms must be analyzed to gain insights into structural dynamics and interactions[10,11,27–30]. Yet, studies remain limited to only a handful of datasets that can feasibly be annotated[7,21,31–33]. Large-scale statistical analyses and comparative studies across different conditions or time points, require tens to hundreds of annotated tomograms to unlock new insights in biophysical analysis. This is not possible with

current annotation approaches. Therefore, faster and more efficient annotation methods are

required to realize the promise of tomography for large scale biological studies.

Several tools have been developed to assist, simplify, or automate the annotation of

membranes and microtubules in EM data, but they often fall short of meeting researchers

needs. Traditional, general-purpose software like Fiji[34], Napari[35], and IMOD[36] focus on manual

annotation which is time consuming. Specialized tools such as TomoSegMemTV[37] and

MemBrain-seg V2[38] for membrane segmentation, or Amira[39] for microtubule segmentation,

depend on high-quality tomograms and require extensive parameter tuning to achieve

acceptable results. Moreover, these tools are designed for the annotation of a single type of

macromolecule or work with one type of EM method. There are also tools such as Dragonfly[40]

which have been developed as general-purpose deep learning workflows that allow automatic

annotation of any macromolecule. However, Dragonfly requires training on a case-by-case

basis using labels manually provided by the user, necessitating significant labeling and

correction effort, and is limited to the prediction of structures from the background at the voxel

level. Dragonfly cannot be applied to problems where individual instances are required, which is

usually the case for biomolecule analysis. Thus, fast, accurate, out-of-the-box algorithms that

can be applied across diverse datasets for common biomolecules are critical.

Here, we present TARDIS (**Tra**nsformer-based **R**apid **D**imensionless **I**nstance **S**egmentation)[41],

a modular framework for annotating biomolecular structures both in EM micrographs and

tomograms. TARDIS includes state-of-the-art pre-trained networks for membrane and

microtubule annotation. To develop these pre-trained models, we created an extensively

manually annotated dataset of membranes and microtubules across tomograms and

micrographs obtained from plastic sections and cryo-EM/ET. In total, this dataset contains 382

images with 71,747 objects, the largest manually labeled dataset of its kind to date (**Suppl.**

Table 1). As a flexible framework, TARDIS is straightforward to extend with semantic

segmentation networks for new macromolecules. These integrate seamlessly with our pre-

trained instance segmentation network to automatically identify object instances from the

semantic maps, enabled by our novel point cloud-based instance segmentation model

architecture, **D**imensionless **I**nstance **S**egmentation **T**ransformer (DIST)[42], an SO(n) equivariant

transformer.

We demonstrate that TARDIS accurately annotates filaments and membranes. TARDIS

improves annotation accuracy by 42% and 55% over existing tools for microtubules and

membranes respectively. TARDIS is also fast, annotating a single tomogram in a matter of

minutes, orders of magnitude faster than manual annotation, and on average 2x faster than

other algorithms for membrane and 5x faster for microtubule segmentation. As a pluggable

framework, TARDIS integrates seamlessly with other tools for semantic segmentation to provide

instance predictions and is adaptable to new macromolecules and data types. We demonstrate

that TARDIS can be applied without any re-training to segmentation of tobacco mosaic virus

(TMV)[43,44] in cryo-ET. We also build and plugin a new semantic segmentation network for actin

in cryo-ET and deploy a semantic segmentation network for microtubules in fluorescent

microscopy images all within the TARDIS framework. Using TARDIS, we generated the largest,

high-quality annotation of microtubules and membranes across 13,000 tomograms - a task that

would have taken an experienced human annotator approximately 35 years to complete

manually. These annotations are available to the community in the CZI Cryo-ET data portal[18,19].

TARDIS is open-source and freely available at https://github.com/SMLC-NYSBC/TARDIS, and

we also provide an optional Napari plugin-based GUI for TARDIS at https://github.com/SMLC-

NYSBC/napari-tardis_em.

Results

TARDIS is a modular framework for any macromolecular segmentation

TARDIS is a framework for fully automated semantic and instance segmentation of cellular macromolecules across diverse resolutions and imaging modalities (**Fig. 1A**). It surpasses existing tools by offering broad applicability without requiring extensive manual parameter tuning. Optimized for accuracy and speed, TARDIS enables rapid annotation of large datasets. Its modular architecture supports seamless extensions to incorporate new macromolecular types (**Fig. 1B**).

The framework leverages pre-trained networks for 2D and 3D segmentation tasks and currently includes specialized semantic segmentation models for the following sub-cellular features:

- Microtubules in 3D electron tomograms (including cryo and plastic section)
- Microtubules in 2D total internal reflection fluorescence (TIRF) images
- Membranes in 2D cryo-electron micrographs
- Membranes in 3D cryo-electron tomograms
- Actin filaments in 3D cryo-electron tomograms

By combining these networks with our novel pre-trained point cloud-based instance segmentation model (DIST), TARDIS accurately distinguishes individual structures, enabling quantitative analyses across thousands of tomograms. We provide pre-trained DIST models for two general structures: linear structures (DIST-linear), e.g., filaments or membranes in 2D, and surfaces (DIST-surface), e.g., membranes in 3D. We refer to these collectively as the pre-trained instance segmentation models but apply DIST-linear to filaments and other linear objects and DIST-surface to 3D surfaces when applicable.

High-Accuracy Semantic Segmentation with FNet

This framework is anchored by our custom-designed FNet, a CNN model for semantic segmentation (**Suppl. Fig. 1**; *Methods*). FNet, a variant of the UNet architecture, provides improved semantic segmentation performance by combining a single UNet-style encoder with two concurrent decoders. One with conventional skip-connections and another with fully connected skip-connections. This architecture improves the precision of cellular structure segmentation, generating probability maps that are converted to binary masks and processed into point clouds (**Suppl. Fig. 2A-B**).

Geometry-aware instance segmentation with DIST

Point clouds are extracted from voxel-level probability maps through skeletonization, which retrieves the skeletons of segmented structures (**Suppl. Fig. 2A**; *Methods*). The DIST model predicts graph edges between points to delineate individual object instances. Operating on point clouds of any dimensionality, the model utilizes an SO(n) equivariant representation and integrates geometry-aware operations within a transformer network (**Suppl. Fig. 3**; *Methods*). Instances are identified by applying a graph-cut to the edge probability outputs, isolating the most likely connected components as distinct instances.

TARDIS accurately segments microtubule and membrane instances in tomograms

TARDIS aims to alleviate the bottleneck in annotating large tomographic data. To validate its performance, we benchmarked TARDIS against existing tools, such as Amira, MemBrain-seg

V2 and TomoSegMemTV, focusing on microtubule and membrane segmentation across

datasets of varying quality and resolution (**Suppl. Table 1**). Due to the lack of suitable public

data, we created a benchmark dataset comprising hand-curated microtubules and membranes.

Specifically, we fully instance-labeled membranes in 120 micrographs and 53 tomograms and

microtubules in 91 tomograms and 112 TIRF images (*Methods*).

Semantic segmentation is evaluated using F1 score, precision, recall, average precision (AP),

and precision at 90% recall (P90). We evaluated instance segmentation using the mean

coverage (mCov) score, which quantifies the overlap between ground truth and predicted point

clouds. These metrics range from 0 to 1, with higher values indicating better performance

(*Methods*).

3D microtubules segmentation

We evaluated TARDIS on microtubule segmentation task using dataset from both Cryo-ET and

plastic ET, with resolutions ranging from 16.00 to 25.72 Å per pixel (**Fig. 2A** and **Suppl. Table**

1). Validation results confirmed that the DIST-linear model significantly improves instance

segmentation of structures using point clouds, achieving near-perfect scores (**Suppl. Table 2**).

Benchmarking on curated datasets further demonstrated TARDIS improvements over Amira,

with TARDIS achieving an mCov score of 0.72 compared to Amira 0.42 (**Fig. 2B**). These results

underscore TARDIS higher segmentation accuracy, particularly in high-resolution tomograms

(≤18 Å), where Amira performance declined (**Fig. 2C** and **Suppl. Fig. 4A**).

For semantic segmentation, TARDIS consistently achieved a higher F1 score (0.61 vs. 0.17 for

Amira), indicating better retrieval of microtubules with significantly fewer false positives. At high

recall levels, TARDIS maintained a precision of 0.33, while Amira precision dropped to 0.01 at

90% recall (**Fig. 2D**). Although the Amira template-matching algorithm was previously applied

on the plastic ET dataset, its lower accuracy necessitated substantial manual corrections[10,11,27].

In contrast, TARDIS consistently segmented more microtubules with significantly less manual

adjustment (**Fig. 2A**, **Suppl. Fig. 4A** and **Table 1**).

3D membrane segmentation

We assessed TARDIS for membrane segmentation across varying tomogram resolutions and

membrane origins (**Fig. 3A and Suppl. Table 1**). For membrane instance segmentation, we

compared TARDIS exclusively with MemBrain-seg V2, which uses a connected component

algorithm. TomoSegMemTV was excluded from this analysis due to its frequent generation of

single-instance segmentations, making it unsuitable for detailed analyses.

We validated that the DIST-surface model improved instance segmentation of surface-like

structures using point clouds achieving an almost perfect mCov score of 0.91 (**Suppl. Table 2**).

Benchmarking on tomographic datasets further demonstrated TARDIS performance, achieving

an mCov score of 0.73, more than doubling the performance of MemBrain-seg V2, which scored

0.33 (**Fig. 3B**). This underscores TARDIS ability to accurately segment membrane instances.

Notably, applying the DIST model to membranes initially segmented with MemBrain-seg V2

significantly improved the mCov score from 0.33 to 0.68 (**Suppl. Fig. 6 A-B**).

Beyond instance segmentation, TARDIS significantly improves semantic segmentation through

the incorporation of the FNet architecture. We evaluated all methods on semantic segmentation

tasks, where TARDIS consistently achieved the highest F1 scores (**Table 2**). Although TARDIS

had a lower recall rate of 0.65 compared to 0.72 from MemBrain-seg V2, it demonstrated

superior precision-recall trade-offs across various decision thresholds (**Fig. 3C**, **Suppl. Fig. 4B**,

and **Table 2**). To further enhance membrane segmentation, we implemented a pixel size

normalization strategy. Scaling tomograms to an optimal resolution of 15 Å and micrographs to

4 Å yielded substantial improvements (**Suppl. Results**). Specifically, the FNet model scaled to 4

Å achieved the best results for high-resolution micrographs (<10 Å), while scaling to 8 Å

provided the highest accuracy for low-resolution micrographs. Based on these findings, we

integrated the optimal pixel size normalization into the automated workflow and publicly

released the enhanced model, providing the community with immediate access to this improved

tool.

Extending TARDIS to new biological structures and imaging modalities

TARDIS demonstrates high accuracy and efficiency in segmenting microtubules and

membranes in electron microscopy datasets, but its versatility extends well beyond these

applications. Designed as a modular segmentation tool, TARDIS handles diverse

macromolecular structures. To assess this, we evaluated TARDIS on various biological

structures and imaging modalities, showing its capacity to generalize across different datasets

with minimal or no retraining. We assessed TARDIS ability to accurately segment 2D

membranes, actin filaments, and the Tobacco Mosaic Virus (TMV). Given the lack of alternative

tools capable of performing instance segmentation for these structures, we identified a distance-

based grouping method as a comparison. This method is analogous to the connected

component algorithm used by MemBrain-seg V2. All methods were benchmarked using a

dataset annotated by an experienced user to assess their effectiveness.

2D membrane segmentation

We evaluate TARDIS performance on 2D membrane segmentation by training the FNet model

for semantic segmentation on a manually annotated dataset. We also incorporated ~60 nm thick

tomogram slices projected into 2D, which we observed to improve model performance (**Suppl.**

Table 3). For instance segmentation, we applied the pre-trained DIST-linear model. This

approach allowed TARDIS to accurately identify individual membrane instances, achieving the

highest mCov score among all tested methods (**Fig. 4A-B**).

We tested the pre-trained TARDIS FNet model for semantic segmentation, where it

outperformed a similarly deep UNet model, achieving superior F1 scores, particularly in high-

resolution micrographs (≤10 Å). TARDIS achieved a precision of 0.74 for membrane structure

recovery (**Suppl. Fig. 5A-B; Table 3**). Further analysis demonstrated that the TARDIS FNet

model performed well across both high-resolution (≤10 Å) and low-resolution (>10 Å) datasets,

achieving an F1 score of 0.41 on lower-resolution images while maintaining high precision

(**Suppl. Fig. 5C; Table 3**).

In summary, the TARDIS FNet model has established a new benchmark for 2D membrane

segmentation, demonstrating superior performance across various micrograph resolutions.

Moreover, we demonstrated that the TARDIS instance segmentation pipeline can be easily

reused. This achievement underscores TARDIS as the first open-source tool capable of reliably

segmenting membranes from micrographs and accurately retrieving instances.

Segmenting TMV in Cryo-ET without TARDIS re-training

To evaluate TARDIS adaptability to different filamentous structures, we applied it to segment

the TMV in Cryo-ET datasets[45]. For this task, we did not retrain any models. Instead, we

employed the pre-trained FNet model, originally developed for 3D microtubule segmentation,

alongside the pre-trained DIST-linear model. Despite structural differences between

microtubules and TMV, TARDIS successfully segmented TMV filaments without any fine-tuning

(**Fig. 4C**). This demonstrates the framework ability to handle diverse filamentous entities with

minimal manual intervention.

TARDIS can segment actin filament trained in limited data scenarios

In many biological studies, limited availability of training data presents a significant challenge for

deep learning-based models. To evaluate TARDIS performance under such constraints, we

tested it on actin filament segmentation using three annotated tomograms. For comparison,

both the TARDIS FNet and a standard UNet model were trained on this small dataset. Despite

the limited data, TARDIS outperformed UNet across all metrics (**Suppl. Table 4**) and achieved

superior instance recovery, with an mCov score of 0.12 compared to UNet 0.10. These results

demonstrate TARDIS robustness and adaptability for novel segmentation tasks, even when

training data are scarce.

Fluorescence microscopy microtubule segmentation

While TARDIS demonstrates effectiveness on EM data, it is designed as a modular tool capable

of addressing tasks beyond electron microscopy. To showcase its broader applicability, we

tested TARDIS on non-EM images by training the FNet network on TIRF microscopy images of

taxol-stabilized microtubules. Utilizing the pre-trained DIST-linear, TARDIS successfully

segmented and recovered nearly all microtubule instances from the benchmark dataset (**Fig.**

4D). These highlight TARDIS modular design and its effectiveness in adapting to various

imaging modalities while maintaining high performance in instance recovery and segmentation.

TARDIS Enables Large-Scale Annotation for Biophysical Analysis

In electron microscopy, a significant challenge is the publication of thousands of tomograms

without accompanying segmentation data. This gap often stems from researchers either lacking

effective tools for semantic and instance segmentation or choosing not to perform

segmentation. As a result, vast repositories of valuable datasets remain underutilized, with only

a few research groups possessing the resources required for segmentation, limiting broader

accessibility and analysis. TARDIS can fill this gap by enabling fast and accurate segmentation

of biomolecules in these datasets.

To demonstrate this, we segmented over 13,000 tomograms from the CZI Cryo-ET data portal

enabling comparative biophysical analyses of membranes across various cell types (**Fig. 5A-B**),

with pixel resolutions ranging from 0.867 to 56.12 Å. TARDIS autonomously processed these

datasets in an average of 3.75 ±3.38 (mean ± standard deviation) minutes per tomogram,

reducing the total segmentation time from an estimated 35 years (assuming one day per

tomogram) to just one month.

This efficiency opens new avenues for analyzing cellular architecture. For example, automated

segmentation revealed that 8.51% of tomograms lacked membrane structures or were of poor

quality (**Fig. 5A-B**). The remaining tomograms contained an average of 5.59 ±7.26 (mean ±

standard deviation) membranes per tomogram, with volumes of 0.009 ±0.017 µm³ (mean ±

standard deviation). These large-scale quantitative insights, previously unattainable, now enable

deeper exploration of cellular morphology and organization.

To further demonstrate TARDIS capabilities, we segmented 75 tomograms from the DS-10160

and DS-10161 CZI datasets[18] of the bacterium *Hylemonella gracilis* under varying conditions,

completing the task in ~5 hours on a single A100 GPU. This analysis revealed inner and outer

membrane curvatures of 0.026 and 0.019, respectively. Exposure to *Bdellovibrio* shifted these

values to 0.023 and 0.021, suggesting membrane softening or remodeling in response to the

predator[46] (**Fig. 5C-D**).

Additionally, we applied TARDIS to 30 tomograms from the EMPIAR-10815 dataset[47], focusing

on axons from mouse dorsal root ganglia. In ~2 hours, we segmented both membranes and

microtubules, identifying an average of 4.8 ±2.5 (mean ± standard deviation) microtubules per

field of view (**Fig. 5E**). Notably, 3 microtubules per field were consistently located within 50 nm

of a membrane, with an average length of 173 nm, indicating potential microtubule-membrane

interactions that may support anchoring and transport functions.

In conclusion, TARDIS streamlines segmentation and enhances comparative biophysical

analyses, enabling researchers to investigate structural variations across diverse biological

contexts. These analyses provide deeper insights into cellular adaptations, broadening our

understanding of structure-function relationships across biological systems.

Discussion

Structural biology has advanced significantly with innovations in imaging techniques and computational tools. However, accurately and efficiently segmenting tomograms remains a challenge due to the intricate and variable nature of biological structures. Traditional tools, such as Amira and MemBrain-seg V2, have been instrumental but often lack the precision and adaptability needed for diverse data types and varying quality levels.

A key feature of TARDIS is its robust instance segmentation capability, essential for analyzing complex biological structures where identical or similar macromolecules coexist in close proximity. TARDIS demonstrates state-of-the-art performance in instance segmentation tasks for both microtubules and membranes. Furthermore, its unique generalization capability allows TARDIS to extend to other instance segmentation problems without requiring retraining or fine-tuning. This flexibility positions TARDIS as a versatile tool for researchers working with diverse and complex cellular architectures. Its adaptability also facilitates rapid integration of new workflows for additional macromolecules, ensuring continued relevance in evolving research contexts.

Central to TARDIS is the incorporation of FNet, a specialized convolutional neural network architecture that enhances the accuracy of the semantic segmentation. Our results demonstrate that TARDIS, leveraging the FNet architecture, achieves higher precision in semantic segmentation compared to other methods. Specifically, the TARDIS FNet outperforms the standard UNet by producing sharper probability masks and capturing finer structural details (**Suppl. Fig. 9A-C**). Our DIST model further refines macromolecule segmentations by identifying individual object instances within the semantic masks output by FNet, effectively addressing issues of over-segmentation and under-segmentation commonly observed in other

tools. DIST demonstrates a remarkable ability to generalize across different filamentous/linear

and surface-like structures allowing it to be integrated seamlessly with new semantic

segmentation methods. We show this by applying our pre-trained DIST model to various cellular

macromolecules. Additionally, DIST can be extended to other point cloud data, including those

derived from LiDAR scans, showcasing its broad applicability (**Suppl. Results** and **Suppl. Fig.**

9D).

A major advantage of TARDIS is its fully automated approach. It operates effectively across

various dataset modalities, resolutions, and quality levels without requiring hyperparameter

tuning or model retraining. This versatility streamlines the segmentation process and minimizes

the need for manual intervention, making TARDIS an invaluable tool for structural biologists. To

further enhance user interaction, our Napari plugin enables real-time observation of

segmentation results and facilitates a more intuitive user experience.

TARDIS is quickly being adopted by the community and early versions of TARDIS have already

been applied successfully to multiple biological studies, confirming its practical utility[26,48]. These

early adopters have demonstrated TARDIS's ability to deliver high-quality segmentations across

diverse and complex biological structures, establishing it as a key resource in the field.

TARDIS represents a significant advancement in the field of structural biology by offering a

highly precise, flexible, and automated solution for tomogram segmentation. The FNet

architecture and integrated DIST model enable superior performance in both semantic and

instance segmentation tasks, allowing pre-trained networks in TARDIS to outperform existing

tools like UNet and MemBrain-Seg V2. The ability to operate across diverse datasets without

the need for retraining and user-friendly tools such as the Napari plugin make TARDIS

accessible and easy to use.

By making our datasets and code publicly available, we hope to encourage an open science

environment that will drive further innovations and discoveries in understanding the complex

architecture of cellular macromolecules. By incorporating additional segmentation networks for

new macromolecules over time, we anticipate that TARDIS will grow into a comprehensive

framework capable of annotating all cellular structures. We expect TARDIS will become an

integral part of the study of large biomolecules.

Acknowledgments

We thank Huihui Kuang (NYU Langone Health, New York) for acquiring membrane micrographs and Fred Heberle (University of Tennessee, Knoxville) for providing membrane micrographs and testing the early version of TARDIS. We thank Aygul Ishemgulova (NYSBC, New York) for providing tomogram in Figure 4C containing TMV structures. We thank Alex Noble (NYSBC, New York) for providing a membrane Cryo-ET dataset, Misha Kopylov (NYSBC, New York) for acquiring Cryo-ET microtubule dataset and Daija Bobe for (NYSBC, New York) preparing grids. We would also like to thank Neal Waxham (McGovern Medical School, Houston) for providing feedback and beta-testing the software. Special thanks to Utz Ermel, Bridget Carragher, and Clint Potter (CZI for Advanced Biological Imaging, Redwood City) for their help with depositing the segmentation dataset on the CZI Cryo-ET data portal. We thank the SEMC IT team for technical support.

This work was performed in part at the Simons Electron Microscopy Center located at the New York Structural Biology Center and was supported by grants from the Simons Foundation (SF349247) and Chan Zuckerberg Initiative (2023-331615 (5022) GB-1597298). Research in Oliver Clarke lab is supported by grant from National Institutes of Health (1R01HL168178). Research in the Müller-Reichert lab is supported by grants from the Deutsche Forschungsgemeinschaft (DFG; MU1423/8-3, grant number 258577783 and MU1423/10-3, grant number 282354882). The Müller-Reichert lab also acknowledges support from the CCBx program of the Center for Computational Biology of the Flatiron Institute (NY, USA). The research in the Shee-Mei Lok group was supported by the Ministry of Education, Singapore (MOET32023-002). Research in the Redemann lab was supported by Human Frontiers in Science HFSP (RGY0070/2019), National Institutes of Health Grant (NIH) R01GM144668 and by the CCBx program of the Center for Computational Biology of the Flatiron Institute (NY, USA,

427   SF1157393). Magdalena Magaj was supported by the Wagner Fellowship at UVA. The work in

428   the Bařinka lab was in part funded by the CAS (RVO: 86652036) and the Czech Science

429   Foundation (GA23-07149S).

Bibliography

1. Steere, R. L. Electron microscopy of structural detail in frozen biological specimens. *J. Biophys. Biochem. Cytol.* **3**, 45–60 (1957).

2. Milne, J. L. S. *et al.* Cryo-electron microscopy--a primer for the non-microscopist. *FEBS J.* **280**, 28–45 (2013).

3. Mastronarde, D. N. Dual-Axis Tomography: An Approach with Alignment Methods That Preserve Resolution. *Journal of Structural Biology* **120**, 343–352 (12 1997).

4. McEwen, B. F. & Marko, M. Chapter 5 Three-Dimensional Transmission Electron Microscopy and Its Application to Mitosis Research. in 81–111 (1998). doi:10.1016/S0091-679X(08)61976-7.

5. Peddie, C. J. *et al.* Volume electron microscopy. *Nat. Rev. Methods Primers* **2**, 51 (2022).

6. Doerr, A. Cryo-electron tomography. *Nat. Methods* **14**, 34–34 (2017).

7. Nogales, E. & Mahamid, J. Bridging structural and cell biology with cryo-electron microscopy. *Nature* **628**, 47–56 (2024).

8. Tollervey, F., Rios, M. U., Zagoriy, E., Woodruff, J. B. & Mahamid, J. Native molecular architectures of centrosomes in C. elegans embryos. *bioRxivorg* (2024) doi:10.1101/2024.04.03.587742.

9. Berger, C. *et al.* Cryo-electron tomography on focused ion beam lamellae transforms structural cell biology. *Nat. Methods* **20**, 499–511 (2023).

10. Kiewisz, R. *et al.* Three-dimensional structure of kinetochore-fibers in human mitotic spindles. *Elife* **11**, (7 2022).

11. Redemann, S. *et al.* C. elegans chromosomes connect to centrosomes by anchoring into the spindle network. *Nat. Commun.* **8**, 15288 (8 2017).

12. Yu, C.-H. *et al.* Central-spindle microtubules are strongly coupled to chromosomes during both anaphase A and anaphase B. *Molecular Biology of the Cell* **30**, 2503–2514 (9 2019).

13. Xu, C., Han, W. & Cong, Y. Cryo-EM and cryo-ET of the spike, virion, and antibody

neutralization of SARS-CoV-2 and VOCs. *Curr. Opin. Struct. Biol.* **82**, 102664 (2023).

14. van Hoorn, C. & Carter, A. P. A cryo-ET study of ciliary rootlet organization. (2024)

doi:10.7554/elife.91642.

15. Creekmore, B. C., Kixmoeller, K., Black, B. E., Lee, E. B. & Chang, Y.-W. Ultrastructure of

human brain tissue vitrified from autopsy revealed by cryo-ET with cryo-plasma FIB milling.

Nat. Commun. **15**, 2660 (2024).

16. Guaita, M., Watters, S. C. & Loerch, S. Recent advances and current trends in cryo-

electron microscopy. *Curr. Opin. Struct. Biol.* **77**, 102484 (2022).

17. Iudin, A. *et al.* EMPIAR: The electron microscopy public image archive. *Nucleic Acids Res.*

51, D1503–D1511 (2023).

18. The Chan Zuckerberg Institute. Cryo-ET Data Portal. Preprint at (2023).

19. Ermel, U. *et al.* A data portal for providing standardized annotations for cryo-electron

tomography. *Nat. Methods* (2024) doi:10.1038/s41592-024-02477-2.

20. Eisenstein, F. *et al.* Parallel cryo electron tomography on in situ lamellae. *Nat. Methods* **20**,

131–138 (2023).

21. Kiewisz, R., Baum, D., Müller-Reichert, T. & Fabig, G. Serial-section Electron Tomography

and Quantitative Analysis of Microtubule Organization in 3D-reconstructed Mitotic Spindles.

Bio Protoc. **13**, (2023).

22. wwPDB Consortium. EMDB-the Electron Microscopy Data Bank. *Nucleic Acids Res.* **52**,

D456–D465 (2024).

23. Gudimchuk, N. B. *et al.* Mechanisms of microtubule dynamics and force generation

examined with computational modeling and electron cryotomography. *Nat. Commun.* **11**, 1–

15 (7 2020).

24. McLaren, M. *et al.* CryoEM reveals that ribosomes in microsporidian spores are locked in a

dimeric hibernating state. *Nat. Microbiol.* **8**, 1834–1845 (2023).

25. Franken, L. E. *et al.* A general mechanism of ribosome dimerization revealed by single-

particle cryo-electron microscopy. *Nat. Commun.* **8**, (2017).

26. Bepler, T. *et al.* Antiviral activity of the host defense peptide piscidin 1: investigating a

membrane-mediated mode of action. *Front. Chem.* **12**, 1379192 (2024).

27. Fabig, G. *et al.* Male meiotic spindle features that efficiently segregate paired and lagging

chromosomes. *eLife* **9**, (3 2020).

28. Redemann, S. & Nazockdast, E. Integrated 3D Tomography and Computational Modeling

to Study Forces in Metaphase Spindles. *FASEB J.* **34**, 1–1 (4 2020).

29. Mendonça, L. *et al.* Correlative multi-scale cryo-imaging unveils SARS-CoV-2 assembly

and egress. *Nat. Commun.* **12**, 4629 (2021).

30. Rast, A. *et al.* Biogenic regions of cyanobacterial thylakoids form contact sites with the

plasma membrane. *Nat. Plants* **5**, 436–446 (2019).

31. Hylton, R. K. & Swulius, M. T. Challenges and triumphs in cryo-electron tomography.

iScience **24**, 102959 (2021).

32. Zimyanin, V. *et al.* Using 3D large scale tomography to study force generation in the mitotic

spindle. *Microsc. Microanal.* **30**, (2024).

33. Heinrich, L. *et al.* Whole-cell organelle segmentation in volume electron microscopy. *Nature*

599, 141–146 (2021).

34. Schindelin, J. *et al.* Fiji: an open-source platform for biological-image analysis. *Nature*

Methods **9**, 676–682 (7 2012).

35. Contributors, N. napari: a multi-dimensional image viewer for python. *Zenodo* Preprint at

(2019).

36. Kremer, J. R., Mastronarde, D. N. & McIntosh, J. R. Computer Visualization of Three-

Dimensional Image Data Using IMOD. *Journal of Structural Biology* **116**, 71–76 (1 1996).

37. Martinez-Sanchez, A., Garcia, I., Asano, S., Lucic, V. & Fernandez, J.-J. Robust membrane

detection based on tensor voting for electron tomography. *J. Struct. Biol.* **186**, 49–61

(2014).

38. Lorenz, L. *et al.* MemBrain v2: an end-to-end tool for the analysis of membranes in cryo-

electron tomography. *bioRxivorg* (2023).

39. Stalling, D., Westerhoff, M. & Hege, H.-C. Amira: a Highly Interactive System for Visual

Data Analysis. in (eds. Hansen, C. D. & Johnson, C. R.) 749–767 (Elsevier, 2005).

40. Inc., C. T. C. Dragonfly. Preprint at (2022).

41. Kiewisz, R., Fabig, G., Müller-Reichert, T. & Bepler, T. Automated Segmentation of 3D

Cytoskeletal Filaments from Electron Micrographs with TARDIS. *Microsc. Microanal.* **29**,

970–972 (7 2023).

42. Kiewisz, R. & Bepler, T. Membrane and microtubule rapid instance segmentation with

dimensionless instance segmentation by learning graph representations of point clouds.

NeurIPS Machine Learning in Structural Biology Workshop Preprint at (2022).

43. Lomonossoff, G. P. & Wege, C. TMV particles: The journey from fundamental studies to

bionanotechnology applications. *Adv. Virus Res.* **102**, 149–176 (2018).

44. Franklin, R. E. Structure of tobacco mosaic virus: Location of the ribonucleic acid in the

tobacco mosaic virus particle. *Nature* **177**, 928–930 (1956).

45. NeurIPS Preparation Of Labeled Cryo-ET Datasets For Training And Evaluation Of

Machine Learning Models. https://neurips.cc/virtual/2023/77456.

46. Banks, E. J. *et al.* Asymmetric peptidoglycan editing generates cell curvature in Bdellovibrio

predatory bacteria. *Nat. Commun.* **13**, 1509 (2022).

47. Foster, H. E., Ventura Santos, C. & Carter, A. P. A cryo-ET survey of microtubules and

intracellular compartments in mammalian axons. *J. Cell Biol.* **221**, (2022).

48. Ooi, J. S. G. *et al.* Tomography studies of the dengue fusion process. *Acta Crystallogr. A*

Found. Adv. **79**, C566–C566 (8 2023).

49. Redemann, S. *et al.* The Segmentation of Microtubules in Electron Tomograms Using

Amira. in (ed. Sharp, D. J.) vol. 1136 261–278 (Springer Science+ Business Media, 2014).

50. Nogales, E. & Downing, K. H. Tubulin and Microtubule Structures. in 211–225 (Humana

Press, 1 2009). doi:10.1007/978-1-59745-336-3_9.

51. Jiang, T. & Cheng, J. Target recognition based on CNN with LeakyReLU and PReLU

activation functions. in *2019 International Conference on Sensing, Diagnostics,*

Prognostics, and Control (SDPC) (IEEE, 2019). doi:10.1109/sdpc.2019.00136.

52. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**,

583–589 (8 2021).

Methods

Datasets

Microtubule tomographic and TIRF datasets

To develop microtubule dataset, we assembled a comprehensive collection of tomograms obtained under both room and cryogenic temperatures (**Supp. Table 1**). This dataset includes 93 tomograms with resolutions ranging from 1.16 to 3.64 nm. We divided the dataset into training, testing, and validation subsets using a 70/20/10 split. The collection encompasses three different imaging techniques, and seven specimen preservation methods and includes samples from eight distinct species, enhancing its diversity.

Microtubule segmentation was initially performed automatically using the AmiraZIBEdition software[39], and subsequently refined manually according to established protocols[49]. The segmentation results were saved in Amira proprietary ASCII format, detailing each microtubule instance as a set of points. For semantic segmentation, we created binary masks from point sets by drawing splines along each instance with a diameter of 25 nm[50]. This approach effectively transforms the detailed instance data into a format suitable for training and evaluating our semantic segmentation model.

We also collected a dataset from interference reflection microscopy (IRM)/TIRF microscopy. The dataset includes TIRF images and movies acquired with Nikon Ti-E microscope equipped with an H-TIRF System (Nikon, Japan), a 60x oil immersion 1.49 NA TIRF objective and an Andor iXon Ultra EMCCD camera (Andor Technology, Belfast, UK). Double-stabilized porcine microtubules were visualized using the IRM channel, while Janelia 549 labeled microtubule-binding proteins were visualized with a 561 nm excitation laser. Segmentation was performed

manually in Fiji and the annotations were converted to comma-separated values (CSV) file

format.

Membrane tomographic dataset

For our membrane dataset, we face a similar challenge to the microtubule scenario, a lack of

existing datasets for tomographic reconstructions or micrographs. To address this, we assemble

a diverse dataset of membranes based on expert curation. We also included tomograms

featuring membrane structures from the EMPIAR and CZI Cryo-ET data portals to further

broaden the dataset.

This effort results in a dataset of 53 tomograms with resolutions ranging from 0.55 to 2.40 nm.

We divide the dataset into training, testing, and validation segments with a 70/20/10 split.

Segmentation was carried out in two stages. First, we hand-segment 10 tomograms to train our

initial FNet model, after which we use this pre-trained model to perform all following

segmentation. We employed Napari with a custom interpolation plugin to curate all membranes

segmentation.

Using our segmentations, we extract instances from binary masks through a connected

component algorithm. Point clouds were generated via skeletonization and voxelization,

ensuring a consistent and accurate representation of membrane structures in our dataset.

Membrane micrograph dataset

In addition to assembling a membrane dataset from tomographic reconstructions, we enhance

our training and validation resources for CNN models by incorporating micrographs. This

expansion involves not only using micrographs provided by collaborators but also simulating

micrographs through tomogram projections. We achieve this by selecting tomographic volumes

approximately 60 nm thick and applying z-max projections to replicate the appearance of

micrographs. This approach significantly diversifies our dataset, allowing us to include a broader

range of data types. The methods for semantic and instance segmentation of these simulated

micrographs adhere to the same procedures previously outlined.

Actin tomographic dataset

We assemble tomograms of actin obtained under cryogenic temperatures (**Supp. Table 1**). In

total we fully annotated actin in 3 tomograms with resolution 1.38 nm and 1.81 nm. We divide

the dataset into training, testing, and validation segments with a 70/20/10 split.

Point Cloud synthetic dataset

To train the DIST model, we construct a dataset combining actual and simulated data. Real

images of membranes and microtubules were hand-segmented to create ground truth masks,

which are then skeletonized and voxelized. Simulated point clouds are also generated for

filaments and membranes, and processed using the same methods as the real data. This

approach ensures consistency between simulated and real datasets. To further augment

simulated dataset, each generated point is jiggled in random direction and amplitude to imitate

image noise. Additionally, simulated datasets were further augmented with random noise set-up

to 10% of the number of points and random drop of points within instances of microtubules and

membranes. Each point cloud is annotated with the correct instance IDs based on known

ground truth positions. The dataset is divided into 80% for training and 20% for validation, with

the simulated data included solely in the training set, comprising 50% of the total training

dataset.

Data preprocessing for CNN

Data preprocessing and augmentation are crucial for optimizing model performance. Initially,

each micrograph and tomogram underwent intensity normalization, where the mean intensity is

subtracted and divided by the standard deviation, followed by scaling all values to a range

between -1 and 1. To manage large images, we cut them into overlapping patches - 256x256

pixels for micrographs and 96x96x96 voxels for tomograms. The datasets are then divided into

training, testing, and validation (**Supplementary Table 1**).

FNet CNN model for accurate semantic segmentation

The TARDIS semantic segmentation workflow relies on the FNet model, illustrated in

Supplementary Figure 1, which features an encoder-decoder architecture with dual decoder

branches, giving the network an F-like shape. The first decoder adheres to a traditional UNet

design, employing skip connections to maintain spatial detail, while the secondary decoder

incorporates hierarchical skip connections from all encoder levels, enhancing the model ability

to capture features at multiple scales. This dual-decoder setup is finalized with a single

convolution and sigmoid function for binary segmentation. Both FNet and UNet architectures

include five layers each for encoding and decoding. Each layer is composed of group

normalization, a dual-convolution block followed by a LeakyReLu[51] activation function. The

training was conducted using the NAdam optimizer with a learning rate of 0.0001 and binary

cross-entropy (BCE) as the loss function. To standardize training between different modules

and avoid overfitting, an early stopping criterion was applied, halting training if no validation loss

improvement was observed over 250 epochs.

Post-processing of semantic binary masks to point clouds

The initial segmentation produces binary masks for filaments and membranes, which include

both false-positives and false-negatives (**Supp. Fig. 2A**). These inaccuracies affect the

precision of subsequent instance segmentation tasks, such as those using connected

component algorithms. To improve this, we convert the binary masks into point clouds through a

series of steps.

First, we perform skeletonization of the binary masks to capture the core structure, followed by

voxel down-sampling. The skeletonization process starts with a Euclidean distance

transformation, which computes the shortest distance from each foreground pixel to the nearest

background pixel, creating a distance map of the mask. We then apply thresholding based on

specific feature sizes - 12.5 nm for microtubules and 2 nm for membranes - to reduce noise and

separate closely packed structures (**Supp. Fig. 2A**).

Next, we generate point clouds by recording the coordinates of each pixel in the skeleton. Given

that these point clouds can become very dense, sometimes exceeding one million points, we

use voxel down-sampling to reduce the point count by a factor of ten without losing spatial and

geometric detail. This down-sampling yields a simplified yet accurate representation of the

original structures (**Supp. Fig. 2B**), enhancing computational efficiency and manageability.

DIST model for point cloud instance segmentation

Instance segmentation with DIST is divided into three parts: 1) Transformation of the raw point

cloud into a pairwise representation based on the distances between points to capture the initial

edge features. 2) Processing through the DIST model to output a matrix representing the

probability of connection between each point pair, as shown in **Supplementary Figure 3C**. This

matrix predicts potential edges in the instance graph, forming the basis for distinguishing

individual instances. 3) Application of a graph cut algorithm on the maximum likelihood graph to

segment instances based on the predicted edges.

Training of the DIST model focuses on predicting these edges by learning vector

representations for each point pair within the cloud, termed pairwise or edge embeddings. To

achieve translation and rotation invariance, initial edge features are based on the Euclidean

distances between point pairs, employing a scaled exponential function of the negative squared

distance to prioritize proximity. Formally, for a point cloud comprising points $p_i (i = 1, \ldots, n)$, we

construct a graph G with nodes for each p_i and edges $e_{i,j}$ connecting all pairs, where the weight

$e_{i,j}$ is calculated as $exp(-d^2_{i,j} / (2 \times s^2))$, with $d_{i,j}$ denoting the Euclidean distance between p_i and p_j,

and s representing a predetermined scale factor. This weighting approach allows us to embed

geometrical information about all points directly from the Euclidean distance. This allowed us to

ensure the SO(n) invariance for translation and rotation and embed all geometrical information

about nodes geometrical relationship and position in the space. This approach effectively

addresses the challenges posed by the complex nature of objects in point clouds, especially in

bioimaging domains where these objects can be large and may intersect or overlap.

Training DIST model for instance segmentation

We train two general DIST models (**Supp. Fig 3B**). The first segments chain-like structures, for

example microtubule filaments or 2D membranes derived from cryo-EM micrographs. The

second segments 3D surfaces, like membranes, mitochondria, etc. Similarly, as described

before DIST was trained using the NAdam optimizer with a 0.00001 learning rate. An early stop

mechanism was employed to halt training when there was no improvement in the moving

average of validation loss over 100 consecutive epochs. Regarding the loss function, binary

cross-entropy (BCE) was used to train the DIST model.

Training and evaluating the DIST model required building an instance graph representation for

each point cloud. The graph is represented as a 2D matrix (**Supp. Fig 3A**) with nodes p

represented by coordinates in n-dimensional space, and the edge represents spatial

connectivity between two nodes p_i and p_j, where *i* is shown in the matrix row, and *j* in the matrix

column. The graph representation for linear-like structures (membranes in 2D and microtubules)

is constructed from ground truth annotations in which each instance is an ordered list of nodes.

Knowing the order, the edge matrix is defined as 1 for each neighboring $p_{i,j}$. This approach

imposes restrictions where each *i* can have only up to two edges. In the case of 3D structures

like membranes, we build this 2D matrix by establishing for each p_i edge connection to its eight

nearest neighbor p_j within the same instance.

Graph cut from the predicted adjacency matrix

The output of the DIST model is a probability adjacency matrix (**Supp. Fig. 3A**), which contains

the probability of an edge existing between a set of two points. For the segmentation of filament

and membrane structures, which are known to have a linear chain we know the prior that each

node (points) has at most two neighbors. We can use this information to search for the graph

chain of nodes, where each node is connected to two other nodes with the highest probability.

In this case, we adopt a greedy algorithm for graph inference. First, we build a hash map for

each node in the point cloud containing node ID, and edge probability $p_{i,j}$. Next, for each new

instance, we searched the hash map for the initial node. This allows us in the final step to

iteratively find up to two edges with the highest probability for all connected nodes. This process

is continued until no new edges can be recognized for a given instance. We use this approach

when segmenting membranes and microtubules that follow this chain structure. In the case of

3D structures like membrane volumes, we do not have such priors, therefore we use a greedy

graph cut algorithm that connects nodes with all other nodes if their probability of connection is

higher than 0.5. This process continues until no new edges can be identified for a given

instance. The output of this approach is a list of coordinates belonging to the same instance

which can be output in any format suitable for the user.

Benchmark experiments

Semantic Segmentation.

In the evaluation of the semantic segmentation capabilities of the TARDIS framework, we

employed a comprehensive set of metrics, including F1 score, precision, and recall (**Eq.1-3**),

alongside more nuanced measures such as average precision (AP; **Eq. 4**) and average

precision at a recall threshold of 90% (AP90; **Eq. 4**). These metrics collectively offer a robust

assessment of the segmentation accuracy, effectively capturing the performance of TARDIS in

prioritizing true positives over false positives and negatives. The AP and AP90 scores provide

insights into the model efficacy across varying thresholds of detection confidence, reflecting the

area under the precision-recall curve and thus offering a detailed picture of model performance

in semantic segmentation tasks.

Instance Segmentation

For the instance segmentation evaluation, TARDIS was assessed using the mean coverage

(mCov; **Eq. 5**) metric. The mCov metric is designed to accurately quantify the overlap between

the ground-truth instances and the predicted instances within the point cloud, using intersection

over union (IoU) as the basis of measurement. This approach ensures an accurate evaluation of

instance segmentation.

Naïve Distance Grouping

In the absence of a pre-existing baseline benchmark for evaluating the performance of similar

point cloud data derived from filaments and membranes, we devised our benchmarking

standard, rooted in the principle of naive distance grouping. This approach entailed computing

the average distance between neighboring points within each point cloud dataset. This average

distance served as a critical distance threshold for each node (point) in the dataset. To delineate

instances within the data, we grouped points based on the premise that any given node could

be connected to a maximum of either two other nodes or an indefinite number (infinity) of nodes,

provided these connections did not exceed the established threshold distance. This method

allowed us to programmatically retrieve instances from complex point cloud datasets by

leveraging spatial proximity.

Figures

Figure 1: Overview of the TARDIS framework for semantic and instance segmentation

A) Example illustrating the distinction between semantic and instance segmentation. **B)**

Segmentation of micrographs or tomograms begins with a CNN. TARDIS uses custom pre-

trained CNN models to predict actin, membrane or microtubules from tomograms, micrographs

and TIRF images. Predicted semantic masks provide the initial segmentation of structures.

These masks are then skeletonized to produce a point cloud representing the core structure of

each object. Instance segmentation is finalized using the DIST model, which predicts

connection probabilities between points in the point cloud. The final instance prediction is

obtained through a greedy graph cut.

Figure 2: Microtubule segmentation examples and comparison with other state-of-the-art methods

A) Instance segmentation examples from TARDIS and Amira, with green lines indicating renders of the core of microtubule filament instances. **B)** mCov metric comparing instance segmentation results from Amira and TARDIS on an entire benchmark dataset. **C)** mCov metric showing instance segmentation results for microtubules using TARDIS and Amira on benchmark datasets from Cryo-ET and plastic ET reconstructed volumes. **D)** Precision-recall curves illustrating the quality of semantic segmentation between Amira and TARDIS.

Figure 3: Membrane segmentation from tomographic data examples and comparison with other state-of-the-art methods

A) Instance segmentation examples from TARDIS, MemBrain-seg V2, and TomoSegMemTV, with multicolor renderings indicating individual membrane instances. **C)** mCov metric showing a comparison of instance segmentation results between TARDIS and MemBrain-seg V2. TomoSegMemTV was excluded from the comparison as it achieved results close to 0 due to many datasets segmented only as a single instance. **C)** Precision-recall curves illustrating the quality of semantic segmentation between TARDIS, MemBrain-seg V2, and TomoSegMemTV.

Figure 4: Example of TARDIS applications where one of the models was reused, showcasing TARDIS generalizability

A) TARDIS benchmark results on instance segmentation task compared to distance grouping method. **B)** Example of TARDIS instance segmentation of membranes in 2D using the pre-train 2D membrane semantic segmentation model and DIST-linear. **C)** Examples of TARDIS instance and semantic segmentation of Tobacco Mosaic Virus (TMV) filaments, achieved by fully reusing the TARDIS microtubule segmentation workflow. **D)** Examples of TARDIS instance and semantic segmentation of stabilized microtubules from IRM images using TARDIS pre-train FNet model and re-used DIST-linear model.

Figure 5: Gallery of example datasets predicted with TARDIS

A) Examples of TARDIS predictions on randomly selected datasets from the CZI Cryo-ET data portal, with indicated pixel sizes and segmentation times. Colors represent individual instances. **B)** Example of a TARDIS prediction on a randomly selected dataset identified by TARDIS as containing no membrane structures. **C)** Example of tomographic slice and 3D view of segmented membraned from *Hylemonella gracilis*. **D)** Example of tomographic slice and 3D view of segmented membraned from *Hylemonella gracilis* in a presence of *Bdellovibrio*. **E)** Example of TARDIS segmentation of microtubules and membrane from EMPIAR-10815 dataset.

Tables

Table 1: Semantic segmentation metrics for microtubule filaments segmented from tomographic dataset. Precision, recall, and F1 scores are calculated using a probability threshold of 0.5 for TARDIS and Amira.

	Model	F1	Precision	Recall	AP	AP90
All Datasets	**TARDIS**	**0.61**	**0.70**	**0.55**	**0.69**	0.33
	Amira	0.17	0.11	0.51	0.25	0.01
Cryo-ET dataset	**TARDIS**	**0.58**	**0.72**	0.48	**0.71**	0.20
	Amira	0.03	0.04	0.06	0.02	0.02
TEM dataset	**TARDIS**	0.61	0.70	**0.56**	**0.67**	0.35
	Amira	0.20	0.12	0.61	0.48	0.01

802 **Table 2: Semantic segmentation metrics for membranes segmented from cryo-ET**

Type	F1	Precision	Recall	AP	AP90
TARDIS	**0.66**	0.68	0.65	0.58	**0.31**
MemBrain-seg V2	0.40	0.27	**0.72**	0.24	0.18
TomoSegMemTV	0.21	0.17	0.42	-	-

804 **Table 3: Semantic segmentation metrics for membranes segmented from cryo-EM**

	Type	F1	Precision	Recall	AP	AP90
All dataset	**TARDIS**	**0.56**	0.62	**0.55**	**0.61**	**0.37**
	UNet	0.54	**0.64**	0.51	0.61	0.37
Dataset with high-resolution* membrane	**TARDIS**	**0.64**	0.73	**0.62**	**0.71**	**0.52**
	UNet	0.62	**0.74**	0.58	0.71	0.52
Dataset with low-resolution** membrane	**TARDIS**	**0.41**	0.44	**0.42**	0.44	**0.12**
	UNet	0.40	**0.47**	0.37	**0.45**	0.10

805   * high-resolution - Micrograph of resolution smaller or equal to 10 Å

806   ** low-resolution - Micrograph of resolution greater than 10 Å

Supplement

Ablation study

TARDIS improves semantic segmentation performance due to the FNet architecture

TARDIS incorporates a novel CNN architecture called FNet into its workflow. We evaluated FNet on semantic segmentation tasks involving microtubules and membranes and found that the TARDIS FNet model significantly outperforms current state-of-the-art tools (**Table 1-3**). To compare TARDIS FNet efficiency also against other CNN architecture, we trained both FNet and a similarly deep UNet model within TARDIS, ensuring identical training parameters for a fair comparison. As expected, the TARDIS FNet model achieved superior results compared to the TARDIS UNet model across both microtubule and membrane benchmarks (**Suppl. Fig. 7A-C**). Specifically, the FNet model attained better metrics for microtubule segmentation from both Cryo-ET and plastic ET datasets (**Suppl. Fig. 7A, Supp. Fig 8A** and **Suppl. Table 5**). Additionally, TARDIS FNet demonstrated significant performance improvements in membrane segmentation tasks using data from both Cryo-ET (**Suppl. Fig. 7B, Supp. Fig 8B** and **Suppl. Table 6**) and micrographs datasets (**Suppl. Fig. 7C, Supp. Fig 8C** and **Suppl. Table 7**). Overall, the TARDIS FNet model demonstrated greater performance compared to a similarly deep UNet model. This improvement was achieved through our dual-decoder strategy, which enabled the generation of sharper probability maps (**Suppl. Fig 9**)

To further increase the reliability of TARDIS semantic segmentation, we implemented a pixel size normalization strategy. This approach ensures that various objects segmented by our TARDIS semantic segmentation module maintain at a consistent scale. We determined the optimal pixel size scaling for membrane segmentation tasks in both tomograms and micrographs by training the TARDIS FNet and UNet models with pixel normalization set to 15 Å,

8 Å, and 4 Å using micrograph datasets. Our results indicated that for tomographic datasets, the

TARDIS FNet model performed best when tomograms were scaled to a resolution of 15Å

(**Suppl. Fig. 8D** and **Suppl. Table 6**). In the case of micrographs, optimal performance was

achieved when the models were trained on data normalized to a resolution of 4Å (**Suppl. Fig.**

8C and **Suppl. Table 7**). Additionally, we observed that the TARDIS FNet model set to 4Å

yielded the best results particularly for high-resolution micrographs (<10 Å), while for low-

resolution micrographs, scaling to 8 Å provided the most accurate segmentation. Based on

these findings, we have integrated the optimal pixel size normalization into our automated

workflow and publicly released the enhanced model.

DIST can segment other point cloud data

DIST was initially developed for cryo-electron microscopy data, but it can be also effectively

applied to point cloud segmentation in domains like LiDAR from the ScanNetV2 dataset or the

PartNet dataset. To test this, we applied the DIST model, specifically pre-trained on the LiDAR

dataset, to segment point clouds from the ScanNetV2 and PartNet datasets. Our results

demonstrate that DIST performs well on this task, effectively segmenting objects and parts

(**Suppl. Fig 9D**). This shows that the DIST model generalizes well across datasets and adapt

for diverse point cloud segmentation challenges, further validating its potential for tasks beyond

its original bioimaging application.

Supplementary Figure 1: FNet CNN model architecture

The figure illustrates a CNN encoder-decoder framework dedicated to semantic segmentation in

images with low signal-to-noise ratios.

A

Binary Semantic Segmentation
- False Negative
- False Positive

Feature size based
Euclidian distance transformation

2D/3D Skeletonization

B

Binary Semantic Segmentation [sum z-projection]

Generate point cloud

Supplementary Figure 2: Illustration of pre-processing steps after the semantic

segmentation

A) Illustration of converting binary semantic masks to a point cloud. Green highlights false
negatives and red indicates false positives. The process begins with applying Euclidean
distance transformation based on feature size to minimize segmentation errors. This is followed
by skeletonization to extract the core features of the mask, which are then represented as a
point cloud. **B)** Example of TARDIS binary semantic segmentation mask and the corresponding
point cloud. The gray color represents a z-sum projection of the semantic mask, while the red
color denotes individual points within the generated point cloud.

Supplementary Figure 3: The DIST model architecture

A) Adjacency graphs illustrating edge connectivity in point clouds. The first graph displays the

ground truth adjacency matrix with each node connected to its two nearest neighbors. The

second graph shows the adjacency matrix derived from node distances and predicted

probabilities using DIST. **B)** Detailed workflow of DIST starts with edge representations

initialization based on distances between points in the input point cloud, resulting in an SO(n)

invariant representation. DIST layers then refine edge features through triangular multiplicative

updates and axial attention modules[52], ultimately decoding these into edge probabilities. Arrows

indicate the flow of information throughout the process. **C)** A cartoon depicting the distinction

between initial distance embeddings and DIST predictions. Initially, each node connects to all

other nodes, whereas DIST predictions retain only the relevant edges. **D)** Illustration of a

triangular multiplicative update. Pairs of nodes are connected as edges on the graph, with the

update process demonstrated by a triangle multiplicative update. Circles represent nodes, and

arrows indicate the edges involved in the update.

Supplementary Figure 4: Comparison of semantic segmentations using pre-trained FNet and UNet

A) Predicted semantic segmentation results for tomograms containing microtubules. **B)** Predicted semantic segmentation results for tomograms containing membranes, with the gray color representing a sum z-projection of the semantic mask.

Supplementary Figure 5: Comparison of semantic segmentations of membranes from EM micrographs

A) Predicted semantic membrane segmentation results for micrographs containing enveloped virus and liposome particles using TARDIS FNet and UNet pre-trained models. **B)** Precision/Recall curves for microtubule segmentation benchmark datasets, comparing predictions made by Amira, the pre-trained UNet, and TARDIS. **C)** Predicted semantic segmentation results for micrographs containing virus and liposomal membranes, on high- and low-resolution.

Supplementary Figure 6: Comparison of results combining TARDIS workflow MemBrain-seg V2

A) Sum z-projections of predicted instance segmentations from each tomogram, with randomly assigned colors representing individual instances. **B)** Plot displaying mCov scores for instance segmentation predictions.

Supplementary Figure 7: Comparison of semantic segmentations between TARDIS FNet CNN model and UNet

A) Predicted semantic segmentation results for tomograms containing microtubules using TARDIS FNet and UNet pre-trained models. **B)** Predicted semantic segmentation results for tomograms containing membranes. **C)** Predicted semantic membrane segmentation results for micrographs containing enveloped virus and liposomes particles.

Supplementary Figure 8: Precision/Recall curves comparing semantic segmentation
performance

A) Precision/Recall curves for microtubule segmentation benchmark datasets, comparing
predictions made by Amira, the pre-trained UNet, and TARDIS. **B)** Precision/Recall curves for
membrane segmentation benchmark datasets using the pre-trained FNet and UNet model on
tomographic data. **C)** Precision/Recall curves for membrane segmentation benchmark datasets
using TARDIS and the pre-trained UNet model on micrograph data. **D)** Precision and recall
curves for membrane datasets benchmarked using the FNet and UNet model. Different lines
represent UNet models trained with specific normalized pixel size resolutions. **E)** Precision and
recall curves for high-resolution membrane dataset benchmarks using the FNet and UNet
model. Different lines represent UNet models trained with various normalized pixel size
resolutions. **F)** Precision and recall curves for low-resolution membrane dataset benchmarks
using the FNet and UNet model. Different lines represent UNet models trained with various
normalized pixel size resolutions.

Supplementary Figure 9: Example of Unet and Fnet prediction on micrograph with membranes at various resolutions

A) Cropped micrographs showing selected areas containing membranes. **B)** Probability map generated by TARDIS semantic segmentation for the area depicted in A. **C)** Probability maps of the same areas shown in A, as predicted by the UNet model. **D)** Example of point clouds segmented with TARDIS using pre-trained model on LiDAR ScanNet V2 dataset. Read circles highlight areas of discrepancy between ground truth labels and DIST predictions.

 Supplementary Table 1: List of datasets with indicated train/validation/evaluation split

Dataset	Origin	Sample acquired by	Imagin technique	Specimen	Content	Pixel size (ang/pix)	Total number of images	Number of objects	Publish
Actin	EMPIAR-10989	-	Cryo-ET	RPE-1 cells	actin filament	13.8	3	-	Yes
	J. Johnston	J. Johnston		-	actin filament	18.1	3	-	No
Microtubules - TIRF	Bařinka lab	L. Motlová	IRM/TIRF	*In-vitro* microtubules	Double-stabilized porcine microtubules	750	112	1656	Yes
Microtubules – ET/Cryo-ET	Müller-Reichert lab	R. Kiewisz	ET	HeLa Kyoto cells	Microtubules	23.2	27	17466	Yes
				U2OS cells	Microtubules	25.7	9	10223	Yes
				RPE-1 cells	Microtubules	25.7	1	472	No
				C. elegans worm	Microtubules	23.2	1	441	Yes
		G. Fabig	ET	*C. elegans* worm	Microtubules	23.2 - 25.7	27	20223	No
				U2OS cells	Microtubules	25.7	5	4681	No
	Redeman n lab	M. Magaj	ET	*C. elegans* worm	Microtubules	21.2	2	1199	Yes
		H. Yazdkhati	ET	*Drosophila* embryo	Microtubules	21.43	4	7001	Yes

		S. Redemann	ET	*C. elegans* worm	Microtubules	11.8 & 23.2	2	1784	Yes
	O. Clarke	W. Conway	Cryo-ET	*In-vitro* microtubules	Microtubules	36.27	2	189	Yes
	W. Conway	W. Conway	Cryo-ET	*In-vitro* microtubules	Microtubules	16	11	578	No
Membranes - 3D	CryoTomoSim	-	Simulated Cryo-ET	-	Membranes	13.3	2	11	Yes
	J. Johnston	J. Johnston	Cryo-ET	-	Membrane	13.6	4	80	No
	Shee-Mei lab	V. Kostyuchenko	Cryo-ET	-	Membrane/ Viruses	6.8 – 13.5	8	89	No
	O. Clarke	A. Nobel & J. Johnston	Cryo-ET	-	Membrane	8 – 16.56	6	172	Yes
	CZI Data-Portal	-	Cryo-ET	-	Membrane/Liposomes	6.4 – 24.7	16	337	Yes
	EMPIAR	-	Cryo-ET	-	Membrane/Liposomes	5.5 – 17.6	17	260	Yes
Membrane – 2D	T. Bepler	H. Hui	Cryo-EM	-	Liposomes	1.3	45	1187	Yes
	F. Heberle	F. Heberle	Cryo-EM	-	Liposomes	2.5	5	326	Yes
	Shee-Mei lab	V. Kostyuchenko	Cryo-EM	-	Membrane/ Viruses	4.7	5	2041	Yes
	-	-	Cryo-ET	Projected Cryo-ET tomograms	Membrane/ Viruses/Liposomes	1.7 – 16.6	65	1331	Yes

934 **Supplementary Table 2: Validation of a point cloud segmentation on ground truth data**
935 **using DIST**

	Filament-like object	Surface structures
DIST (linear / surface)	**0.96**	**0.91**
Distance grouping	0.21	0.25

937 **Supplementary Table 3: Validation of an influence of cryo-ET projection on improving**
938 **semantic segmentation of Cryo-EM data**

	Scaling	Type	F1	Precision	Recall	AP	AP90
All Dataset	**8A**	**TARDIS**	**0.51**	**0.71**	0.44	**0.68**	**0.37**
	8A [Only Cryo-EM]	TARDIS	0.46	0.61	0.47	0.56	0.25
Dataset with high-resolution membrane	8A	TARDIS	0.54	**0.76**	0.48	0.72	**0.48**
	8A [Only Cryo-EM]	**TARDIS**	**0.70**	0.68	**0.74**	**0.77**	0.38
Dataset with low-resolution membrane	**8A**	**TARDIS**	**0.46**	**0.61**	**0.37**	**0.61**	**0.18**
	8A [Only Cryo-EM]	TARDIS	0.06	0.48	0.04	0.22	0.03

939 * high-resolution - Micrograph of resolution smaller or equal to 10 Å

940 ** low-resolution - Micrograph of resolution greater than 10 Å

941 **Supplementary Table 4: Validation of semantic and instance segmentation prediction of**

942 **actin from cryo-ET tomograms**

Type	F1	Precision	Recall	AP	AP90	mCov
FNet	**0.07**	**0.58**	**0.04**	**0.54**	**0.06**	**0.12**
UNet	0.06	0.55	0.04	0.50	0.02	0.10

944 **Supplementary Table 5: Validation of semantic segmentation prediction of microtubule**
945 **filaments segmented from tomographic dataset.** Precision, recall, and F1 scores are
946 calculated using a probability threshold of 0.5 for TARDIS and Amira.

	Model	F1	Precision	Recall	AP	AP90
All Datasets	**TARDIS [FNet]**	**0.61**	**0.70**	**0.55**	**0.69**	**0.33**
	TARDIS [UNet]	0.60	0.69	0.55	0.27	0.31
Cryo-ET dataset	**TARDIS [FNet]**	**0.58**	**0.72**	0.48	**0.71**	0.20
	TARDIS [UNet]	0.54	0.58	**0.50**	0.70	**0.30**
TEM dataset	**TARDIS [FNet]**	**0.61**	**0.70**	**0.56**	**0.67**	0.35
	TARDIS [UNet]	0.61	0.70	0.55	0.65	**0.37**

948 **Supplementary Table 6: Validation of pixel size normalization on semantic segmentation**

949 **prediction of membranes from cryo-ET tomograms**

Scaling	Type	F1	Precision	Recall	AP	AP90
8A	FNet	0.45	0.78	0.32	**0.69**	0.19
	UNet	0.43	**0.80**	0.29	0.69	0.19
15A	**FNet**	**0.66**	0.68	**0.65**	0.58	**0.31**
	UNet	0.66	0.66	0.65	0.57	0.28

951 Supplementary Table 7: Validation of pixel size normalization on semantic segmentation

952 prediction of membranes from cryo-EM micrographs

	Scaling	Type	F1	Precision	Recall	AP	AP90
	4A	**FNet**	**0.56**	0.62	**0.55**	0.61	**0.37**
		UNet	0.54	0.64	0.51	0.61	0.37
All Dataset	8A	FNet	0.51	**0.71**	0.44	**0.68**	0.37
		UNet	0.49	0.67	0.43	0.64	0.34
	15A	FNet	0.46	0.68	0.41	0.66	0.33
		UNet	0.38	0.63	0.31	0.61	0.26
	4A	**FNet**	**0.64**	0.73	**0.62**	0.71	**0.52**
		UNet	0.62	0.74	0.58	0.71	0.52
Dataset with high-resolution membrane	8A	FNet	0.54	**0.76**	0.48	**0.72**	0.48
		UNet	0.52	0.70	0.48	0.67	0.48
	15A	FNet	0.47	0.73	0.44	0.69	0.44
		UNet	0.35	0.62	0.28	0.59	0.30
	4A	FNet	0.41	0.44	**0.42**	0.44	0.11
		UNet	0.40	0.47	0.37	0.45	0.10
Dataset with low-resolution membrane	**8A**	**FNet**	**0.46**	0.61	0.37	0.61	0.18
		UNet	0.44	0.60	0.35	0.59	0.14
	15A	FNet	0.44	0.60	0.35	0.59	0.14
		UNet	0.44	**0.64**	0.35	**0.63**	**0.20**

953 * high-resolution - Micrograph of resolution smaller or equal to 10 Å

954 ** low-resolution - Micrograph of resolution greater than 10 Å

Algorithms, Program Codes, and Listings

956   **Equation 1. F1 score**

$$F1 = 2 * \frac{Precision \ * \ Recall}{Precision \ + \ Recall}$$

958   **Equation 2. Precision score**

$$Precision = \frac{Precision \ * \ Recall}{Precision \ + \ Recall}$$

960   **Equation 3. Recall score**

$$Recall = \frac{TP}{TP \ + \ FN}$$

961   Where TP denotes the number of true positive predictions, and FN denotes false negatives.

963   **Equation 4. AP score and AP90**

$$AP = \sum_{k=1}^{n} Precision_k \ * \Delta \ Recall_k$$

964   Where n is the number of thresholds, and k is the threshold value between 0 and 1. The

965     $Precision_k$ denotes precision at threshold k and $\Delta Recall_k$ denotes a change in recall between k

966   and k-1.

$$AP90 = Precision_k \ * \Delta \ Recall_k$$

968   Where k denotes Precision at the threshold where recall is equal to 90%, and $\Delta Recall_k$ denotes

969   a change in recall between k and k-1.

971　**Equation 5. mCov score**

$$mCov(I, P) = \frac{1}{|I|} \sum_{m=1}^{|I|} max_n IoU(I_m, P_n)$$

972　Where I_m denotes the number of projected spline or volume for the m-th ground truth instance.

973　P_m represents the n-th predicted instance, and |I| is the number of all ground truth instances.