Precise and scalable metagenomic profiling with sample-tailored minimizer libraries

Johan Nyström-Persson,[1],* Nishad Bapatdhar[2] and Samik Ghosh[2]

[1]JNP Solutions, Yokoami 2-9-5-407, Sumida-ku, 130-0015, Tokyo, Japan and [2]The Systems Biology Institute, Saisei Ikedayama Bldg., 5-10-25, Higashi Gotanda, Shinagawa-ku, 141-0022, Tokyo, Japan

*Corresponding author. johan@jnpsolutions.io

Abstract

Reference-based metagenomic profiling requires large genome libraries to maximize detection and minimize false positives. However, as libraries grow, classification accuracy suffers, particularly in k-mer-based tools, as the growing overlap in genomic regions among organisms results in more high-level taxonomic assignments, blunting precision. To address this, we propose sample-tailored minimizer libraries, which improve on the minimizer-LCA (lowest common ancestor) classification algorithm from the widely used Kraken 2. In this method, an initial filtering step using a large library removes non-resemblance genomes, followed by a refined classification step using a dynamically built smaller minimizer library. This 2-step classification method shows significant performance improvements compared to the state of the art. We develop a new computational tool called Slacken, a distributed and highly scalable platform based on Apache Spark, to implement the 2-step classification method, which improves speed while keeping the cost per sample comparable to Kraken 2. Specifically, in the CAMI2 "strain madness" samples, the fraction of reads classified at species level increased by 3.5x, while for *in silico* samples it increased by 2.2x. The 2-step method achieves the sensitivity of large genomic libraries and the specificity of smaller ones, unlocking the true potential of large reference libraries for metagenomic read profiling.

Key words: metagenomics, next generation sequencing, sequence analysis

Introduction

Metagenomics and increasing library sizes

Next-generation sequencing (NGS) has revolutionized our understanding of the underlying code of living systems, offering unprecedented insights into the structure and function of genomes of different species. Reference-based metagenomics tools rely on assembled libraries of annotated genomes to classify and characterise the taxa present in a sample. While sequence alignment can be complex, k-mer based tools offer an attractive cost/performance tradeoff based on exact matching of subsequences. Kraken (1) introduced the concept of metagenomic classification based on a database of k-mers and lowest common ancestor (LCA) taxa of these. This allows for very rapid classification of reads. Kraken 2 (2), now widely used, refined this concept to store only minimizers - minimal subsequences by some ordering - of k-mers together with their LCA taxa, yielding similar performance with much smaller databases. By using Bracken (3) together with Kraken 2, database bias stemming from the selection of reference genomes can also be removed, which also allows the

user to estimate the true read abundance for each taxon (read profiling).

The accuracy of reference-based metagenomics relies on the comprehensiveness of the reference libraries. Ideally, the reference library should include all the true genomes present in the sample to ensure accurate and reliable classifications. In recent decades, significant efforts have expanded many publicly available, high-quality annotated genome libraries. Since its first release in 2003, the NCBI RefSeq genome repository has grown rapidly, with the number of bacterial genomes doubling every 1.5 years (4) .

Larger and more comprehensive reference libraries are essential for accurate classification, as current research emphasises their role in reducing erroneous classifications (5; 6; 7). Even when focusing on a specific taxonomic group (e.g., fungi, viruses, bacteria), false positive rates can remain high if the reference database is limited to only that group (6) . Moreover, genome libraries are often noisy, plagued by sequence contamination and taxonomic misannotations (5). Contaminants from kits or lab processes can also lead to misclassifications, particularly when using highly specific or incomplete libraries that do not account for sequencing

Fig. 1: Excluding genomes when the minimizer database is built produces different classifications for reads from other genomes. In this toy example, a genus G1 contains three genomes S1, S2, and S3. These genomes contain the regions $A..F$ which contain the minimizers $a..f$. Some regions are conserved across genomes. Database 1 contains all three genomes which leads to six minimizer records, two of which are on genus level and four on species level. In database 2, the genome S2 has been removed, which pushes minimizer b down to species level. Read classification is by majority vote as in Kraken 2: the highest weighted path from leaf taxon to root is the final classification of a read. Database 1 classifies two reads as G1 and one read as S1, whereas database 2 pushes read 2 down to species level.

artefacts or unrepresented genomes (8). In general, the selection and curation of reference genomes is an essential step, which the Kraken 2 and Bracken authors also highlight (9).

2-step classification

Unfortunately, increasing library size can reduce classification specificity. As libraries expand, each read has more possible genome matches, complicating precise classification. This issue is pronounced with tools like Kraken 2, which assigns shared k-mers to the lowest common ancestor (LCA) of matching taxa. With larger libraries, LCAs tend to shift up the taxonomic tree, resulting in more classifications at higher taxonomic ranks (4). This makes classifications more *vague*, impacting species-level accuracy (*specificity*), as shown in fig. 1. Notably, the number of species in the NCBI RefSeq library has been doubling faster than the number of genera (4), suggesting that larger libraries disproportionately hinder species-level classification.

Some tools alleviate problems arising from large reference libraries by removing non-resemblance genomes from the library in an intermediate step (10). However, to the best of our knowledge, this method has not yet been applied in the context of k-mer based read binning.

We propose a novel *2-step classification method* that tailors the reference library to each sample. First, a preliminary classification with a large library filters out genomes not present in the sample. This step provides a conservative estimate of the genomes present in the sample. Next, a dynamic LCA-minimizer database containing only those genomes detected is built, and a second, more precise classification is performed. This approach leverages

knowledge of the entire sample metagenome to improve per-read classification specificity. Using a maximally large library for the first step reduces the risk of missing a genome, which could lead to false negatives and even false positives, while using a small but highly specific library, *built specifically for the samples being classified*, for the second step alleviates the vagueness problem.

Slacken

Directly implementing the 2-step method with Kraken 2 is computationally costly due to the time required to dynamically build sample-tailored databases. Additionally, Kraken 2 can require highly specialised computing resources with terabytes of RAM, and running it on large genome libraries—currently considered best practice for most reliable and accurate results (7) —is already challenging. Instead, to study the 2-step method, we developed a new implementation of the Kraken 2 algorithm designed to run on modern scalable infrastructure, called Slacken. Slacken implements the original Kraken 2 algorithm as faithfully as possible (1-step method), while also building large databases more efficiently. Slacken also implements the 2-step classification method efficiently, allowing us to study this method in a variety of settings.

Slacken is built using Apache Spark[1] (11) , a highly scalable distributed computing framework, and runs both on single machines and on clusters. It is compatible with Kraken 2, in the sense that it accepts the same input file formats and produces compatible output file formats. The Fastdoop (12) library is used

---

[1] https://spark.apache.org

Fig. 2: Kraken 2 + Bracken (top) compared with Slacken 2-step + Bracken (bottom) internal data flow. Coloured boxes are equivalent between the two systems in the sense that they compute the same results. Slacken and Kraken 2 both build a reusable minimizer-LCA taxon library which is the basis for classification. However, Slacken optionally pools all samples together for the first step. Pooled classification results in a taxon set sketch, which is the basis for a second minimizer-LCA library that is built on the fly (dynamic). Samples are then classified again using this second library. Bracken weights are also computed on the fly from the dynamic library, which means that Bracken may be run directly on the outputs from Slacken.

for efficient sequence input. Unlike Kraken 2, Slacken does not need to keep the entire database in memory, which allows for scaling to databases larger than the total RAM. Crucially, Slacken can classify multiple metagenomic samples at the same time, creating a large multisample read pool prior to classification and grouping back reads by sample after. This helps reduce the per-sample cost of classification, especially when using large genomic libraries.

In 2-step classification, multisample classification is a performance benefit, as in the 1-step method, but also influences the contents of the second library: including additional samples may cause additional taxa to be detected in the first step, which lets their genomes be included as possible classification targets in the second step. Thus, every sample can influence the classification results of every other sample. For this reason we classify related samples together.

Figure 2 contrasts the dataflow in 2-step Slacken (described below) with regular (1-step) Kraken 2 classification. Kraken 2 relies on a pre-built static LCA-minimizer database for classifications. Slacken uses an identical static database for the initial classification (the first step) only. In the second step, a heuristic is used to select taxa from the results and a new, smaller (in our experiments, typically around 10% or less of the initial size by minimizer count) LCA-minimizer database is built, containing only genomes from the detected taxa. This is equivalent to building a second Kraken 2 database on the fly with `kraken2-build`. The reads are now classified again using this second database, which produces the final result. Slacken's operations are thus equivalent to `kraken2` (classify), `kraken2-build`, and `bracken-build`, with the important difference that multiple samples can be classified simultaneously. As with Kraken 2, the final output is a read binning and a read profile (report), and Bracken may be used

to remove database bias from the latter, accurately estimating the true read abundance for each taxon in the sample.

Table 1 breaks down the runtime cost of running Slacken 1-step and 2-step classification on 50 samples from the CAMI2 strain madness dataset. Experiments were run using a commercial cloud computing provider. Slacken generally runs faster than Kraken 2 (wall clock time) since it can be distributed on a large number of machines that run in parallel. This does not mean that the number of CPU hours required by Slacken is always smaller. However, because Kraken 2 requires an expensive machine type for large databases (with sufficient RAM), the dollar cost per sample was sometimes lower for Slacken even when the CPUh requirement was larger.

Slacken 1-step classification implements the Kraken 2 read classification algorithm as faithfully as possible with very minor differences. We discuss these differences in section 2.4.

Materials & Methods

We evaluate the taxonomic read-binning performance of Slacken against Kraken 2, as well as the downstream taxonomic profiling results of Slacken + Bracken against Kraken 2 + Bracken.

Experiments were run on Amazon Web Services EC2 instances. Slacken was run on AWS Elastic MapReduce (EMR), on instances from the `m6gd` and `m7gd` families, which have 4 GB of RAM per CPU and physical NVMe drives. We used the `4xlarge` (16 CPU) and `8xlarge` (32 CPU) instance sizes. Genomes, samples, and built minimizer databases were stored on Amazon S3. AWS EMR release 7.1.0 was used, which includes Spark 3.5.1 and Java 17.

Kraken 2 version 2.1.3 and Bracken version 2.9 were used. These were run on instances of the type `x2gd.metal`. Kraken 2

Table 1. Cost of classify tasks for Slacken and Kraken 2

Tool	Task	Library	Samples	Time (h)	CPUh	Cost/sample ($)
Slacken	2-step classify	rspc	50	1.2	614	0.29
Kraken 2 & Bracken[1]	2-step classify	nt	50	7.45	522	0.87
Slacken	1-step classify	rspc	50	0.58	280	0.13
Kraken 2	1-step classify	nt	50	0.9	57.3	0.09
Slacken	1-step classify	rspc	1	0.03	14.9	0.35
Kraken 2	1-step classify	nt	1	0.02	1.07	0.09

Time and cost measurements for Kraken 2 and Slacken in a cloud environment. The average size of each sample was 4 GB as uncompressed fastq files. Slacken was run on a 50/50 mix of regular and interruptible (spot) instances with 4 GB RAM per CPU, with a total of 512 CPUs. Kraken 2 was run on a single machine with 64 vCPUs and 1 TB RAM in memory-mapped mode. Due to the high cost of building a large database with Kraken 2, we are comparing rspc performance with that of a pre-built nt database, which is of comparable size (1.5 TB of sequence data for nt, vs 1.8 TB for rspc).

[1] We estimated the cost of a 2-step method by using `kraken2` to first classify once, then using `kraken2-build` to build a custom database based on the results, classifying again, and then finally running `bracken-build` on the result.

was run in memory-mapped mode with the databases pre-copied to `/dev/shm` (shared memory) for best performance.

For all experiments, the default Kraken 2 parameters of $k = 35$, $m = 31$, $s = 7$, as well as the default spaced seed mask and XOR mask were used for both Kraken 2 and Slacken.

Two-step classification

We investigated the impact of applying a read based cutoff (R) filter for genome inclusion into the 2-step library. More specifically, given a read cutoff of N reads, we include in the dynamic library the genome of a species level taxon T and the genomes of all its taxonomic children if the total number of reads assigned to T and its children is at least N in the first classification. In all of our experiments we used multi-sample classification, which means that the number of reads for a given taxon needed to be at least N in total across all the samples in a group pooled together. We compare results for $R \in \{1, 10, 100\}$.

Details on the taxon set discovered by each heuristic for the various genomic libraries and sample families are available in supplementary table S3[2].

Genomic libraries

Two different genome libraries were used to build databases for this study. Both libraries are subsets of RefSeq release 224.

We used the Kraken 2 build scripts to obtain and preprocess genomes. The same low-complexity masking as for Kraken 2 was used (`k2mask`).

- **Standard (std)**: The selection of genomes included in the Kraken 2 standard library. This includes complete genomes and chromosomes from archaea, viruses, bacteria, plasmids, and human, as well as adapter sequences (UniVec_core). This was used to build databases with both Slacken and Kraken 2.
- **RefSeq prefer complete (rspc)**: The NCBI Reference Sequence genome library with only complete genome sequences/chromosomes for those taxa that have them, and draft genomes/scaffolds otherwise, as well as adapter sequences (UniVec_core). This allowed us to cover as many taxa in

Table 2. Comparison of minimizer-LCA libraries

Library	Taxa	FASTA sequences (GB)	Distinct minimizers
rspc	91822	1843	2.14×10^{11}
std	31390	198	1.46×10^{10}

RefSeq as possible, while avoiding contamination and noise from incomplete genomes for those taxa that had a complete genome. This was used to build databases with Slacken only.

Here, the std library is a strict subset of the rspc library. Both libraries include genomes from archaea, bacteria, human, viruses, plasmids, as well as adapter sequences. In addition, rspc contains fungi and other eukaryotic genomes.

These two libraries are compared in table 2. The number of taxa here denotes taxa with associated genomic sequences; the number of nodes in the complete tree when parent taxa are included is larger.

Classification experiments

Slacken and Kraken 2 were used to classify a total of 160 samples (see below). A total of 7040 sample classifications were compared against the ground truth reference at both the species and genus levels, for a total of 14080 experiments. Detailed results for each experiment are available in supplementary table S1[3] and visualizations are available in the supplementary materials.

We evaluated both Kraken 2 and Slacken classifiers at classification confidence levels of 0, 0.05, 0.1 and 0.15. An exhaustive analysis of Kraken2's parameter space by (7) identifies 0.15 as an optimal confidence threshold, which we primarily used to measure classifier performance although similar trends hold at other confidence levels. We used Kraken 2 and 10 Slacken-based classifiers for performance comparison and to investigate the impact of different values for the read based cutoff filter:

- **rspc_R100/std_R100**: Slacken with 2-step classification and a preliminary classification with a rspc/std database, 1-step

[2] https://github.com/JNP-Solutions/Slacken/blob/master/metrics/heuristicTaxa.tsv

[3] https://github.com/JNP-Solutions/Slacken/blob/master/metrics/All_metrics.tsv

confidence (c) at 0.15 and 2-step taxon filter at ≥ 100 reads per taxon.

- **rspc_R10/std_R10**: Slacken with 2-step classification and a preliminary classification with a rspc/std database, 1-step confidence (c) at 0.15 and 2-step taxon filter at ≥ 10 reads per taxon.

- **rspc_R1/std_R1**: Slacken with 2-step classification and preliminary classification with a rspc/std database (c) at 0.15 and 2-step taxon filter at ≥ 1 reads per taxon.

- **rspc_gold/std_gold**: Slacken with 2-step classification where the 2-step database is built using genomes from ground truth taxa and their descendants in rspc/std.

- **rspc_1-step/std_1-step**: Slacken 1-step classification with rspc/std database.

- **kraken2**: Kraken 2 classification with the std database.

For gold set classifiers, the gold set was computed as the union of ground truth taxa assigned to all reads of all samples in the corresponding sample family.

Differences between Slacken 1-step and Kraken 2

Given the same values of k (k-mer width), m (minimizer width) and s (spaced seed mask spaces), and given the same genomic library and taxonomy, Slacken classifies reads identically to Kraken 2. However, there are two sources of potential divergence between the two.

First, we have found that Kraken 2 during the build process stores spurious minimizers immediately after ambiguous regions in genomes, seemingly incorrectly. While this is not harmful, it means that the true value of k, for Kraken 2, lies between k and $k-1$. Such extra minimizers give Kraken 2 a slightly larger minimizer database for the same parameters. For the Kraken 2 standard library, we found that the difference is about 1% of the total minimizer count. Slacken classifications may thus be based on slightly less information, as we have opted to implement an ideal version of Kraken 2 rather than imitate the current software exactly.

Second, Kraken 2 uses a probabilistic data structure called a compact hash table (CHT) which sometimes can lose information when unrelated minimizers are merged into a single record. Slacken does not have this and instead stores each minimizer-LCA record in full. This means that Slacken databases, particularly when the library contains a very large number of taxa, may be more precise than in Kraken 2.

To quantify these differences, for each sample studied in the present work, we measured the L1 distance between the classification report (fraction of reads assigned per taxon) generated by 1-step Slacken and the one generated by Kraken 2, using the std library. The distance was never larger than 0.005, corresponding to 0.5% of reads.

Statistical analyses

All simulated and mock datasets contained per-read taxon labels. For each classified read, we assessed it as

- **True positive (TP)**: If the true label is identical to, or an ancestor of the classified label. For example, if a the true label is *Streptococcus agalactiae* and the classified label is the descendant strain *Streptococcus agalactiae 18RS21*.

- **Vague positive (VP)**: If the true label is a descendant of the classified label. For example, if the true label is *Bacteroides fragilis* and the classified label is *Bacteroides*.

- **False positive (FP)**: If the true label is neither a descendant nor an ancestor of the classified label. For example, if the true label is *Bacteroides fragilis* and the classified label is *Streptococcus*.

- **False Negative (FN)**: If the classifier failed to assign a label to the read.

We also computed the following metrics:

- **PPV**: positive predictive value, precision of read classifications: $\frac{|\text{TP}|}{|\text{TP}|+|\text{FP}|}$

- **Sensitivity**: sensitivity of read classifications: $\frac{|\text{TP}|}{|\text{Sample}|}$

- **Recall**: recall of read classifications: $\frac{|\text{TP}|}{|\text{TP}|+|\text{FN}|}$

where TP is the set of true positive reads classified in a sample, FP the set of false positives, FN the set of false negatives, and Sample the set of all reads in the sample.

Index metrics

We use two variants of the index metric as introduced in (7).

We assign to each classified read an integer between 0 and 9, called the read-index, as follows:

$$\begin{cases} 0, & \text{If the classified label is a true positive} \\ N \in \{1 \dots 8\}, & \text{If the classified label is a vague positive} \\ & \text{and is } N \text{ taxonomic ranks above the true} \\ & \text{label.} \\ 9, & \text{If the classified label is a false positive} \end{cases}$$

The number of ranks in the taxonomic tree is 8, which is why FPs are given a weight of 9.

We define two types of indexes:

- **Soft read index**: The soft index for a read (or s-index) is computed using rules 1-3 along with the additional rule that false negative read classifications (i.e. unclassified reads) are assigned an index 0.

- **Read index**: The index for a read is computed using rules 1-3 along with the additional rule that false negative read classifications (i.e. unclassified reads) are assigned an index 9.

The average read-index for all reads in a sample is called the sample *s-index* or sample *index*. Both indexes can be defined for a given taxonomic rank by promoting all true positive labels up to that given rank and then computing the index as above. Figures 3 and 7 compute index and s-index values for samples at species ranks.

The index metrics defined here deviate from their original conception in (7). Unlike the original, which assigns an *fp* read an index equal to the number of ranks to the common ancestor of the *fp* taxon label and the ground truth, our approach simplifies comparability and interpretation. By design, a lower index in our framework directly reflects higher classification precision.

Bracken experiments

Each of the 7040 classifications was also further processed with Bracken to compensate for library bias. Post-Bracken results for

Fig. 3: Boxplots of sample soft-index values for strain, plant associated, marine and mbarc datasets with various 1- and 2-step classifierers. The sample soft-index is computed by taking a weighted average of all sample reads, giving a weight of 0 to TPs and FNs and 9 to FPs. VP reads are given a weight corresponding to the number of ranks between the true taxon and the classified taxon label for that read.

each experiment are available in supplementary table S2[4] and visualisations in supplementary document.

The ground truth was for the CAMI2 samples obtained from the CAMI2 gold standard mapping, where reads that had no species-level mapping were first filtered out. Since Bracken by default redistributes every read to species-level, this allowed us to compare with a true read profile for each sample. For *in silico* samples, the ground truth was known by construction. The default Bracken cutoff of 10 reads for a taxon to be present was used in all cases.

Each sample was represented as a vector with entries in the range $[0, 1]$ where each entry represented the fraction of reads assigned to that taxon. We measured the following metrics:

- **LSE**: Euclidean distance from the ground truth profile: $\mathrm{LSE}(x, t)$
- **LSE log-10**: $\mathrm{LSE}(\log(x), \log(t))$
- **L1**: L1 (Manhattan) distance from the ground truth mapping: $\mathrm{L1}(x, t)$
- **L1 log-10**: $\mathrm{L1}(\log(x), \log(t))$

Simulated and mock sample dataset characteristics

We evaluated 2-step and 1-step classification across 6 sample families, of which 3 were simulated and 3 were mock sample datasets.

- **Simulated Communities**: Short-read samples simulated for the marine ($n = 10$) and rizosphere/plant_associated ($n = 20$, samples 0-19), microbial environments as well as the strain madness ($n = 100$) dataset from the well known CAMI2 challenges (13). These datasets contain simulated reads from a combination of reference and novel genomes, assembled from real metagenomic datasets and are widely used for benchmarking metagenomics tools, including classifiers and binners. Each sample contained, after filtering, on average 7.76×10^6 read pairs.
- **Mock Communities**: Short-read samples simulated from 225 complete genomes chosen at random from Kraken 2's std database. Assorted_Genomes_225 ($n = 10$) and Assorted_Genomes_mbarc_225 ($n = 10$) are simulated using CAMISIM (14) with the former simulated using the less noisy Illumina HiSeq quality profile from ART (15) and the latter, using the quality profile used to simulate the three CAMI2 datasets, i.e. the mbarc profile. The third dataset, i.e. Assorted_Genomes_Perfect_225 ($n = 10$) was simulated in an error free manner using CAMISIM. Each sample contained on average 3.46×10^6 read pairs.

The CAMI2 datasets were generated using genome contigs assembled from real metagenomic data. We further filtered each simulated metagenome to remove reads came from genomes that had taxon labels above a species level. This was done to identify each read with a single species of origin, since the fact that a few genomes had genus or above taxon labels was a limitation of the metagenomic assembler used to generate the CAMI2 datasets and not reflective of the underlying metagenomic sample. This also made counting the true positive classifications at a given taxonomic rank unambiguous, and allowed us to measure the quality of post-Bracken read profiles directly against the reference. The amount of reads filtered out varied between on average 10% (strain madness samples) to on average 20%(plant associated samples).

The strain, marine, and plant_associated datasets were selected because each presents unique challenges for metagenomic classification using the chosen genome libraries. As shown in table 4, these datasets progressively include more genomes that fall outside the std and rspc libraries, enabling us to assess whether certain trends hold consistently across datasets from varied environments, thus reinforcing the robustness of our results. The three mock datasets were created primarily to validate Slacken and serve as a stress test for classification with large libraries. Similar to the CAMI2 strain dataset, but simulated directly on genomes present in std, the results allowed us to show that Slacken 2-step classification using rspc can still recover comparable precision to Kraken 2 on std. This is a pathological case where using a larger library is a clear disadvantage.

---

[4] https://github.com/JNP-Solutions/Slacken/blob/master/metrics/All_bmetrics.tsv

Table 3. Number of distinct genomes

Dataset	In rspc	In std	Novel (rspc-std)[1]	Total
Strain	19	18	1-2	20
Marine	336	274	144-206	480
Plant_Associated	342	188	137-291	479
A.G	225	225	0-0	225
A.G.mbarc	225	225	0-0	225
A.G.Perfect	225	225	0-0	225

[1] Novel (rspc-std) N-M means N and M genomes had taxids outside rspc and std respectively.

A.G is short for *Assorted_Genomes*

For the CAMI2 datasets (strain, marine, and plant_associated), genomes are categorised by their assigned taxonomy, without requiring the exact genome to be present in the reference library. This contrasts with the custom assorted genome datasets, which were created using genomes that are already included in the standard Kraken 2 (*std*) library.

Results

2-step classification recovers specificity loss in growing reference libraries

We used three simulated and three in-silico datasets to compare the taxonomic binning performance of Slacken 1- (or Kraken 2) and 2-step methods, as well as their effectiveness as taxonomic profilers when used with Bracken. The simulated datasets—strain madness (strain), marine, and plant_associated—were sourced from the CAMI2 challenge (13) and are based on genomes assembled from actual sample metagenomes. The in-silico datasets were custom-designed and based on genomes from the standard Kraken2 library. We used the first three datasets to assess performance in a realistic scenario with unknown or novel genomes, while the latter three allowed us to evaluate classifier performance in an idealized controlled environment with only simulated sequencing noise (see section 2.7 for details). We present results below using the Assorted_Genomes_mbarc_225 (mbarc) in-silico dataset as the representative dataset (as trends were consistent across all three in-silico datasets), as mbarc has the same noise profile used in creating the CAMI2 samples.

Large reference libraries are known to affect the accuracy of k-mer-based LCA methods (4). We confirm this loss of classification specificity on our simulated and in-silico metagenomic datasets using both the rspc and std libraries. Figure 4 (right, unshaded region in each subplot) illustrates this effect, showing how true positive (TP) classifications with Slacken 1-step on the smaller std library become vague positive (VP) classifications, i.e. classified as some ancestor of their true taxon, with Slacken 1-step on the much larger rspc library.

We created eight Slacken classifiers, one for each combination of $R \in \{1, 10, 100\}$ (read count per taxon cutoffs) and library choice of std or rspc (as well as two 1-step classifiers – for details, see section 2.3). Figure 4 (left, shaded region in each subplot) demonstrates that the Slacken classifier with $R = 100$ on rspc (rspc_R100) effectively mitigates the specificity loss due to the larger library, and in the case of the in-silico samples even improves on the initial results.

Fig. 4: Each of the four plots contain fraction of total reads present at species-level for true positive (colour) and vague positive (grey) for the Slacken 1-step classifiers on the *std* and *rspc* library databases (right-unshaded region in each subplot). The blunting of classifications when using the larger *rspc* library is clearly shown by the decrease in TPs and increase in VPs. The rspc_R100 classifier (left shaded region in each subplot) mitigates the loss in read specificity due to 1-step classification with a larger library. Median values are mentioned beside each whisker plot.

Table 4 shows the size of the 2-step library for each classifier and sample family. The improvement in specificity was possible due to the significantly smaller size of the 2-step libraries relative to the reference libraries. As expected, the 2-step library sizes decrease with higher values of R. For each cutoff (R) value we detected more taxa in the larger genomic library (rspc). This is likely due to the fact that rspc has more species and subspecies level taxa than std (see 2.1 on how taxa are included in the 2-step library). We noted for the in-silico samples with the $R = 1$ heuristic, that the number of taxa selected was highly sensitive to added noise.

The 2-step method enhances classification specificity

The 2-step method enhances classification specificity by tailoring the library to the sample metagenome. By using a smaller, sample-representative library, classifications can be more precise, as long as the library adequately represents all genomes in the sample. On the other hand, it is important not to be too selective, as incomplete libraries may give rise to false positive read classifications or unclassified reads. This limitation is particularly relevant for real samples, which often contain novel genomes.

We evaluated the performance of the read-based 2-step classifiers on the strain, marine, plant_associated, and mbarc datasets. Notably, ∼ 60% and ∼ 43% of taxa in the plant_associated and marine samples, respectively, are absent in the std library, while both datasets have only about 30% of their taxa missing from rspc. The strain dataset has only one and two taxa missing from rspc and std libraries, respectively, whereas the mbarc dataset is fully contained within std (and, therefore, rspc).

Table 4. Number of species level taxa included in 2-step library for R1 classifiers

Dataset	Rspc			Std		
	R1	R10	R100	R1	R10	R100
Strain	1730[1]	590	256	513[1]	303	183
Marine	2253	1511	914	1594	1046	757
Plant_Associated	2396	1296	737	1890	1052	652
A.G	1082	197	175	488	201	182
A.G.mbarc	916	193	173	455	197	179
A.G.Perfect	192	188	178	193	188	182

[1] The strain dataset was analysed in two batches comprising of 49 and 51 samples respectively. This figure is the average number of the species included in the 2-step library.

Slacken 1-step classification with std and rspc use libraries with 31390 and 91822 species level taxa respectively. We observed that the largest 2-step libraries (with the R1 heuristic) are nearly 17× to 40× smaller than the 1-step libraries (i.e. std and rspc) respectively.

This allows us to assess the performance of the 2-step classifiers across different types of microbial communities and under different levels of reference library comprehensiveness. Figure 5 displays a stacked comparison of classifications using various Slacken 1- and 2-step classifiers across these datasets. We observed that Slacken's 2-step approach enhances species-level classifications across all datasets and reference libraries. Classifications with rspc produced more significant gains in species level classifications than with the smaller std library, yielding a mean increase of 15.7%, 13.4%, and 13.1% in species classifications with rspc, and a 12.4%, 5.3%, and 3.1% increase in species classifications with std on the strain, marine and plant_associated datasets, respectively (see table 5). This aligns with expectations, as the reduction in the size of the 2-step library is more pronounced with rspc than with std (see table 4).

2-step classification reduces overall sample index

Figure 6 shows that the increase in FPs between 1- and 2- step classifiers is negligible (∼ 0.6% of total classified reads at most on an average). Unclassified reads can, however, increase by 1.5% (mean increase, in the case of the std library), excluding outliers. This is seen in the case of the plant_associated dataset which, due to the low coverage with both std and rspc has more unclassified reads. Further reducing the size of the library can increase the phylogenetic distance between novel genomes and the library which could contribute to the increased number of FNs. We therefore need a way to measure and compare the quality of 1- and 2-step classifications, taking FPs and FNs into account.

Following a concept introduced by Wright et al (7), we define the sample index as a weighted average of all classified reads within a given sample. True positive (TP) reads are assigned a weight of 0, while false positive (FP) and false negative (FN) reads receive a weight of 9. Vague positive (VP) reads are assigned a weight based on the number of ranks separating the true taxon from the classified taxon label for that read (see section 2.5.1). The sample index serves as a useful comparison tool across classifications that use the same library since stricter 2-step read filters tend to yield higher FN and FP counts, although FP increases are typically

Fig. 5: Each barplot breaks down Slacken 2-step read classifications (as a fraction of total reads) into species, genus, family, classifications above family (up to but not inclusive of root) and unclassified reads on the *std* and *rspc* libraries. 2-step classifications tend to "squash" genus, family and higher classifications and increase classifications at species ranks or leave reads unclassified.

Fig. 6: Each of the four plots contain species level read fractions of total reads present for true positive (colour) and false positive (grey) for the various 2- and 1- step classifiers on the *std* and *rspc* library databases. The increase in TP classifications is contrasted with the increase in FPs as tighter read filters are used. The increase in FPs is < 0.6% in both rspc and std, omitting outliers.

Table 5. Fraction of total reads classified at different ranks for each dataset and classifier.

Dataset	Group	rspc_1-step	rspc_R1	rspc_R10	rspc_R100	std_1-step	std_R1	std_R10	std_R100
Assorted_Genomes_mbarc_225	Species	0.36	0.47	0.74	0.80	0.48	0.60	0.74	0.80
	Genus	0.46	0.41	0.16	0.10	0.39	0.29	0.17	0.10
	Family	0.11	0.10	0.08	0.08	0.10	0.09	0.08	0.08
	Above-Family	0.07	0.01	0.01	0.01	0.02	0.01	0.00	0.00
	Unclassified	0.00	0.00	0.01	0.02	0.00	0.00	0.01	0.01
marine	Species	0.66	0.69	0.73	0.79	0.79	0.81	0.82	0.84
	Genus	0.27	0.25	0.21	0.15	0.12	0.10	0.09	0.07
	Family	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01
	Above-Family	0.02	0.01	0.01	0.00	0.01	0.00	0.00	0.00
	Unclassified	0.04	0.04	0.04	0.04	0.08	0.08	0.08	0.08
plant_associated	Species	0.28	0.32	0.36	0.41	0.21	0.22	0.23	0.24
	Genus	0.56	0.55	0.51	0.47	0.46	0.46	0.44	0.43
	Family	0.02	0.01	0.01	0.01	0.02	0.01	0.01	0.01
	Above-Family	0.04	0.01	0.01	0.01	0.04	0.02	0.01	0.01
	Unclassified	0.10	0.11	0.11	0.11	0.28	0.29	0.30	0.31
strain	Species	0.06	0.07	0.13	0.21	0.23	0.28	0.29	0.36
	Genus	0.49	0.53	0.50	0.42	0.39	0.35	0.35	0.29
	Family	0.29	0.33	0.33	0.33	0.32	0.33	0.33	0.33
	Above-Family	0.17	0.07	0.04	0.03	0.05	0.03	0.02	0.02
	Unclassified	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01

insignificant. An index value of N implies that, on average, the classified label of a read is N ranks above the species level. Figure 7 shows a clear trend of decreasing index values between 1- and 2-step classifiers as the read filter is strengthened, indicating that the overall quality of read classifications improves with the 2-step classifiers.

The only exception to this trend appears in the plant_associated dataset, where the std-based 2-step classifiers consistently show higher index values. This likely reflects the previously mentioned poor fit of the std library to this dataset. In this case, we analyzed the quality of read classifications while omitting unclassified reads, also called soft-index (see section 2.5.1), and found that, among classified reads, the overall classification quality does indeed improve (see fig. 8).

2-step classification recovers lost precision in read profiling with Bracken

Slacken dynamically builds Bracken weights for 2-step libraries, enabling us to use Bracken for species-level read redistribution. We compared read fractions assigned by various 1- and 2-step Slacken classifiers against the expected ground truth profiles, using the L1 distance metric to assess the overall accuracy of read profiles generated through Bracken. Figure 9 illustrates that 2-step classifiers yield smaller L1 distances, with rspc-based 2-step methods showing the greatest overall reduction. Except for the plant_associated samples, which benefit greatly from being classified with the rspc library, there is an increase in L1 distance as the library grows under 1-step classification, which mirrors the loss of specificity in read binning. The 2-step method is able to recover the accuracy loss.

Fig. 7: Boxplots of sample index values for strain, plant_associated, marine and mbarc datasets with various 1- and 2-step classifiers. Sample index is computed by taking a weighted average of all sample reads, giving a weight of 0 to TPs and 9 to FPs and FNs. VP reads are given a weight corresponding to the number of ranks between the true taxon and the classfied taxon label for that read.

Fig. 8: The s-index or soft index is computed by taking a weighted average of all sample reads, giving a weight of 0 to TPs and FNs, and 9 to FPs. VP reads are given a weight corresponding to the number of ranks between the true taxon and the classifieded taxon label for that read. The h-index measures the quality of read classifications amongst classified reads only.

Fig. 10: Stacked bar charts to show the performance of various classifiers including rspc and std gold set classifiers. Gold set classifications exhibit an almost binary behaviour, i.e. either a read is classified at a species level or remains unclassified.

Gold set classifiers show the potential of 2-step classification with a perfect heuristic

We also analyzed the impact of classification using gold set libraries. The purpose of the 2-step method is to detect as many taxa truly present in the sample as possible, while filtering out taxa not in the sample. The actual set of taxa present in the sample metagenome is referred to as the gold set. To assess the potential maximum performance of the 2-step method, we classified each sample using its respective gold set as a genome filter. Figure 10 presents the performance of the gold set classifications using the rspc and std libraries. It is worth noting that the choice of library is significant here, as not all taxa in the gold set necessarily belong to the reference library. Therefore, the final gold set used is the intersection of the genomes from ground truth taxa for that sample and those present in the selected reference library.

We observed that gold set classifiers exhibit a nearly binary behaviour, meaning a read is either classified precisely at the species level or left unclassified. When dynamic libraries are too tight, they lose the capacity to classify reads from novel genomes as VPs and instead fail to classify them, resulting in FNs. We call this effect 'squashing the middle', where VP classifications are converted into either TPs or FNs. Even for samples with reads from real assembled metagenomes like those in the CAMI2 datasets, the gold set performs effectively in this regard. Figure 11 illustrates, somewhat unexpectedly, that the gold set classifications have a very low fraction of FPs, typically about $2-5\%$ lower than other classifiers. This is surprising, as our read-based filters generally show a trend of increasing FPs as the library size decreases.

The relationship between FPs and library size is not straightforward. Reducing the library size can potentially force reads to be incorrectly classified to the available reference genomes, increasing FPs. However, removing non resemblance genomes also removes these taxa as classification targets, reducing FPs. We

Fig. 9: L1 distance, computed between expected read count profile and computed read count profile, for samples in the strain, marine, plant_associated and in-silico datasets.

Fig. 11: False positive fraction of total sample reads for various 1- and 2-step classifiers as well as gold set classifiers on different datasets. Gold set classifiers tend to have very low percentages of false positives.

speculate that the reason the gold set classifiers have such few FPs is directly due to the maximization of the latter effect.

Discussion

More and better reference genomes are constantly becoming available, causing a conflict of aims for classifier tools based on genomic libraries. On the one hand, larger libraries can be preferable since they are good at avoiding false positives and have high sensitivity. On the other hand, a larger library leads to read classifications at higher levels in the taxonomic hierarchy, leading to vagueness, since fewer genomic regions are unique to a single taxon across the whole library. To address this in the context of the Kraken 2 minimizer-LCA classification method, we propose two-step classification. A static, large library is used initially to identify the genomes that are present in samples, and then a second library - a sample-tailored library - is built on the fly from only the genomes actually detected. The second step can then yield species-level classifications with a high specificity while the first step still guards against false positives and retains its sensitivity to a wide range of taxa.

Comparing 1-step classification results from the std library with those from the much larger rspc library, our results confirmed that broad reference databases result in increased vagueness. Using a simple, read-based criterion to include taxa in the dynamic library, we found that the 2-step method effectively mitigated this loss in specificity. The method improves overall assignment quality, shown by a decrease in the sample index between the 1-step and 2-step classifications.

The 2-step method needs an additional parameter over the 1-step method – a filter for selecting genomes in the 2-step library. This significantly impacts classification. If this filter is too permissive, specificity is reduced, making classifications similar to those of the 1-step method (or Kraken 2). On the other hand, an overly restrictive filter risks excluding genomes that should be represented in the sample. Incorrectly excluding a genome forces any reads from that genome to appear either as false negatives or as false positives from some other genome. This effect is amplified by the smaller size of the 2-step library, which can lead to notable decreases in minimizer-assigned LCAs.

From a quantitative biology perspective, applying a taxon read cutoff is practical, as kit and laboratory contaminants often introduce trace-level species, making ultra-low abundance taxa potential contaminants (16). While this can critically impact metagenomics in low biomass communities (8), sensitive classification tools (like Slacken and Kraken) can incorrectly detect contaminant taxa from even a single sequenced read, leading to many low-abundance false positive taxa in high biomass communities. Such taxa are typically addressed post-classification, where the classifier output is filtered for species above a certain read (or taxonomic) abundance threshold (17). However, this could lead to removal of low abundance taxa that are actually present. By eliminating ultra low abundance ($R = 1, 10, 100$) taxa prior to the 2-step classification, we are able to buy back precision, potentially increasing reads classified to true low abundance taxa in the final output.

The R100 heuristic performed well as a genome filter throughout. 2-step R100, using the rspc library, greatly increased species level classifications compared with 1-step classification. Every sample family that we studied showed improvement. For the CAMI2 strain samples, while using the rspc genome library, the fraction of species-level classifications was increased by 3.5x relative to 1-step, while for in silico samples (Assorted_genomes_mbarc_225), they were increased by 2.2x to a total of 80%. Classifications at higher levels (above family) were shifted downward substantially: from 17% to 3% in the strain samples, and from 7% to 1% in the in silico samples. The fractions of false positives and false negatives changed only very slightly. Based on our experiments, we believe that using the R100 heuristic together with a maximally large initial library would be a good starting point for most users. For users who are concerned about R100 possibly missing some taxa, the R10 heuristic is a more conservative alternative.

Using a read-based cutoff to reclassify reads has similarities with Bracken's default mode of operation. Bracken also employs a cutoff (by default 10) to select target species for redistribution of reads. However, Bracken redistributes hypothetical reads to arrive at an estimate of the true number of reads for each taxon, whereas our 2-step approach assigns specific reads to taxa.

Using ground truth taxon sets (gold set classifiers), we demonstrate the best performance achievable by a perfect genome filter. Although we found that the R100 filter performed well on most metrics, there is a large gap between R100 performance and gold set classifier performance that remains unexplored. Future investigations could explore more stringent read filters (higher R cutoffs) or other types of taxon selection criteria. For example, KrakenUniq (18) extends Kraken and Kraken 2 by tracking the number of distinct k-mers detected per taxon, a signal that could also be used as part of a 2-step selection filter.

While our CAMI2 results do not indicate significant problems with FP and FN reads relative to 1-step classification, unfortunately, removing taxa not detected by the read cutoff heuristic carries the risk of missing novel or unseen genomes. For example, if some reads classify at genus level but no species level descendants satisfy the cutoff under that genus, the entire genus would be excluded from the second library. We are actively investigating how to best handle this in the context of a 2-step method.

When using Slacken, we found that the cost and runtime per sample of the 2-step approach is comparable to regular Kraken 2 classification when using large sample libraries and when classifying multiple samples together. However, multisample classification affects read assignments as well as cost. We classify related samples together, since every sample can, through the genome detection heuristic, influence the 2-step library and thus the second step classification. This may make reproducibility difficult in a situation where sample sets grow or change over time. We are investigating best practices for such a scenario as part of our ongoing work. Alternatively, the two-step method can be used on a single sample at a time. This is always reproducible, although more costly.

There are generally two approaches to analyzing a sample metagenome: one aims to classify as many reads as possible, even at higher taxonomic ranks (especially for novel taxa), to capture a broad view of the entire sample's taxonomic diversity, despite potential novel genomes being present. The other focuses on precisely classifying reads from taxa already represented in the reference library, thereby limiting classification to known organisms. Slacken's 1-step (or Kraken 2) approach aligns with the first method when using large, representative libraries containing genomes spanning the tree of life. However, the second approach—achieving precise classification with a focus on known taxa—has been challenging because it traditionally requires smaller libraries. Using reference libraries from specific branches of the taxonomic tree has been shown to skew results, potentially increasing false positive classifications due to shared genomic regions and library contamination (6). Slacken's 2-step method addresses this issue by enhancing classification specificity while preserving the robustness of using a broad, comprehensive reference.

Conclusion

K-mer based metagenomic binning and profiling continues to be widely used. However, lowest common ancestor (LCA) based algorithms do not scale well as libraries keep growing, since classifications become increasingly vague when LCA taxa move higher up in the taxonomic tree. We find that sample-tailored minimizer libraries, which filter out non-resemblance genomes in a second step prior to classification based on a simple read count heuristic, overcome this limit by allowing the initial library to scale freely while the tailored library can produce specific classification results. This 2-step method moves classifications lower in the tree of life across all levels in the taxonomic hierarchy, a result that we observed for both the sequenced CAMI2 samples and *in silico* samples. Furthermore, 2-step classification with Slacken is comparable in cost to regular Kraken 2 classification when classifying multiple samples with a large library. Sample-tailored libraries set a new standard for precision and allow k-mer based

LCA methods to achieve better performance as genomic reference libraries keep growing.

Source code and data availability

Slacken is available as open source software under the GPL license at `https://github.com/JNP-Solutions/Slacken`. The same repository also includes the tools and scripts used for constructing the std and rspc libraries, and for sample filtering and evaluation of classifiers.

Supplementary data is available at `https://github.com/JNP-Solutions/Slacken/tree/master/metrics`.

Competing interests

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Author contributions statement

J.N.P and N.B conceived of the study, conducted experiments and analysed data. J.N.P. developed the Slacken software. J.N.P, N.B and S.G wrote and reviewed the manuscript.

Acknowledgments

This work was partially supported by the ONRG Grant for the Nobel Turing challenge to The Systems Biology Institute (Grant number: N62909–21–1–2032) for J.N.P, N.B and S.G.

References

1. Derrick E. Wood and Steven L. Salzberg. Kraken: ultrafast metagenomic sequence classification using exact alignments. *Genome Biology*, 15(3):1–12, March 2014.

2. Derrick E. Wood, Jennifer Lu, and Ben Langmead. Improved metagenomic analysis with Kraken 2. *Genome Biology*, 20(1):257, November 2019.

3. Jennifer Lu, Florian P. Breitwieser, Peter Thielen, and Steven L. Salzberg. Bracken: estimating species abundance in metagenomics data. *PeerJ Computer Science*, 3:e104, January 2017.

4. Daniel J. Nasko, Sergey Koren, Adam M. Phillippy, and Todd J. Treangen. RefSeq database growth influences the accuracy of k-mer-based lowest common ancestor species identification. *Genome Biology*, 19(1):165, October 2018.

5. Samuel D. Chorlton. Ten common issues with reference sequence databases and how to mitigate them. *Frontiers in Bioinformatics*, 4:1278228, March 2024.

6. Vanessa R. Marcelino, Edward C. Holmes, and Tania C. Sorrell. The use of taxon-specific reference databases compromises metagenomic classification. *BMC Genomics*, 21:184, February 2020.

7. Robyn J. Wright, André M. Comeau, and Morgan G. I. Langille. From defaults to databases: parameter and database choice dramatically impact the performance of metagenomic taxonomic classification tools. *Microbial Genomics*, 9(3):000949, March 2023.

8. Abraham Gihawi, Yuchen Ge, Jennifer Lu, et al. Major data analysis errors invalidate cancer microbiome findings. *mBio*, 14(5):e01607–23.

9. Jennifer Lu, Natalia Rincon, Derrick E. Wood, et al. Metagenome analysis using the Kraken software suite. *Nature Protocols*, 17(12):2815–2839, December 2022.

10. Daniel A Acheampong, Piroon Jenjaroenpun, Thidathip Wongsurawat, et al. CAIM: coverage-based analysis for identification of microbiome. *Briefings in Bioinformatics*, 25(5):bbae424, September 2024.

11. Matei Zaharia, Mosharaf Chowdhury, Michael J Franklin, et al. Spark: Cluster Computing with Working Sets. *2nd USENIX Workshop on Hot Topics in Cloud Computing*, 2010:95, 2010.

12. Umberto Ferraro Petrillo, Gianluca Roscigno, Giuseppe Cattaneo, and Raffaele Giancarlo. Fastdoop: a versatile and efficient library for the input of fasta and fastq files for mapreduce hadoop bioinformatics applications. *Bioinformatics*, 33(10):1575–1577, 2017.

13. Fernando Meyer, Adrian Fritz, Zhi-Luo Deng, et al. Critical Assessment of Metagenome Interpretation: the second round of challenges. *Nature Methods*, 19(4):429–440, April 2022.

14. Adrian Fritz, Peter Hofmann, Stephan Majda, et al. CAMISIM: simulating metagenomes and microbial communities. *Microbiome*, 7(1):17, February 2019.

15. Weichun Huang, Leping Li, Jason R. Myers, and Gabor T. Marth. ART: a next-generation sequencing read simulator. *Bioinformatics*, 28(4):593–594, February 2012.

16. Susannah J Salter, Michael J Cox, Elena M Turek, et al. Reagent and laboratory contamination can critically impact sequence-based microbiome analyses. *BMC Biology*, 12:87, November 2014.

17. Alexa B. R. McIntyre, Rachid Ounit, Ebrahim Afshinnekoo, et al. Comprehensive benchmarking and ensemble approaches for metagenomic classifiers. *Genome Biology*, 18(1):182, September 2017.

18. F. P. Breitwieser, D. N. Baker, and S. L. Salzberg. KrakenUniq: confident and fast metagenomics classification using unique k-mer counts. *Genome Biology*, 19:198, November 2018.