Structure-Based Generation of 3D Small-Molecule Drugs: Are We There Yet?

Bo Yang[1], Chijian Xiang[1,2], Tongtong Li[1], Yunong Xu[1], Jianing Li[1]*

1. Borch Department of Medicinal Chemistry and Molecular Pharmacology, Purdue University, West Lafayette, IN 47907
2. Department of Horticulture & Landscape Architecture, Purdue University, West Lafayette, IN 47907

* Jianing Li (jianing-li@purdue.edu)

Abstract:

Structure-based drug design (SBDD) plays a crucial role in preclinical discovery. Recently, structure-based generative algorithms have been developed to streamline the SBDD process, by generating novel, drug-like molecule designs based on the binding pocket structure of target protein. However, there is no effective metric to evaluate the chemical plausibility of molecules designed by these algorithms, which can limit further applications. In this study, we introduce two new metrics for assessing the chemical plausibility of generated molecules. Along with additional analyses, we demonstrate that these algorithms can generate chemically implausible structures with certain property distributions that differ from those of known drug-like molecules. We also compare results with high-throughput virtual screening hits for three protein targets (the c-SRC kinase, the Smoothened receptor, and the Dopamine D1 receptor). These metrics and analysis methods described here offer valuable tools for model developers and users to assess the chemical plausibility and drug-likeness of generated molecules, ultimately enhancing the use of structure-based generation in drug discovery.

1 **Keywords:** Generative AI, Hit identification, Drug discovery, Chemical plausibility,

2 Druglikeness

3 **TOC:**

1 Introduction

As drug discovery is often costly and lengthy,[1, 2] numerous efforts have been made

to accelerate it, reduce associated costs, and improve the success rate.[3, 4] Recent

advances in artificial intelligence and machine learning (AI/ML) have led to many new

applications to enhance drug discovery efforts.[5-7] Among these, generative AI stands out

as one of the most promising. It would be intriguing if generative AI could directly design

small-molecule candidates based on information about the therapeutic target, such as

the sequence, structure, mechanism, and so forth. A lingering question is: Are we there

yet? In other words, can we readily take the AI-designed molecules to any stage of

preclinical or even clinical studies? To that end, we developed two novel metrics in this

work for evaluating the chemical plausibility of molecules generated based on a three-

dimensional (3D) protein target structure. Generally, a structure-based generative model

learns the features of protein-ligand interactions during training and generates multiple

3D small molecules expected to bind to a predefined 3D binding pocket (Figure 1).

Figure 1. General workflow of structure-based generative algorithms. Protein-ligand complexes are
converted into machine-readable features and used as input to train the generative model. Once
trained, the model takes the binding pocket of interest as input and generates 3D ligand structures
with high affinity for the given binding pocket.

A fundamental idea in drug design is to efficiently search for drug-like candidates

from the vast chemical space, estimated to contain over 10^{60} possible compounds.[8]

Medicinal chemists hope to identify compounds that exhibit high potency and specificity

for the therapeutic target, as well as good drug-likeness, both in vitro and in vivo,

ultimately leading to successful clinical studies. Since the 1990s, the development of

structure-based drug design[9] (SBDD) in tandem with the rapid growth of the Protein

Data Bank (PDB) has led to numerous successful discoveries.[10-13] Currently, a popular

SBDD approach is molecular docking to screen large compound libraries, such as the

Enamine REAL database[14] and the ZINC database.[15] However, most compounds in

these libraries are likely to be rejected during docking, primarily due to steric clashes or

inadequate interactions with the binding pocket. A more efficient SBDD approach would

be to directly "grow" drug-like molecules based on the binding pocket structure (e.g.,

size, shape, amino acid arrangement, surface interaction, etc.). Built on this idea and

powered by the deep learning technique,[16, 17] structure-based generative algorithms

have been developed to learn the features of ligands and interaction patterns in known

protein-ligand complex structures and then generate potentially new compounds that

mimic these features or patterns.[18-20] As of spring 2025, there are at least 27k protein-

ligand complex structures in the PBD-bind database,[21] 689k modeled protein-ligand

binding complexes in the BindingNet v2 dataset,[22] and 22.6 million docking protein-

ligand complexes in the CrossDocked2020 (hereafter referred to as crossdock)

dataset,[23] which provide fast-growing datasets for training structure-based generative

models.

Current structure-based generative models primarily differ in their methods for

representing 3D features, incorporating domain knowledge, and generating compound

designs (Figure 2). While it was a long-standing challenge to represent the 3D features

of protein-ligand complexes, recent breakthroughs include the use of discrete voxelized

grids,[24] continuous methods like 3D molecular graphs and point clouds,[18, 19] and

Euclidean distance metrics.[25] 3D molecular graphs and point clouds have emerged as

the state-of-the-art representations in structure-based generative models because they

capture both atomic properties and bond connectivity. By directly encoding precise 3D

atomic coordinates, they also incorporate rich geometric information.[18, 26] These

combined features make them more expressive than voxelized grids or distance-based representations for modeling 3D molecules. Furthermore, some generative models incorporate domain knowledge, such as pharmacophores[27] or explicit protein-ligand interactions,[28] to guide the generation process. Incorporating domain knowledge may enhance the generation of molecules with better affinity or other properties. However, the restricted generation may also reduce the diversity of generated structures by adding more conditions on the generative process. Finally, two generative strategies have been pursued that can generate molecules auto-regressively (atom-by-atom or fragment-by-fragment) or in one shot.[26, 29] Overall, almost all the current models were designed to generate molecules conditioned on binding pocket structures with high docking scores. Besides docking scores, commonly used metrics to assess the quality of generated molecules include quantitative estimates of drug-likeness (QED)[30] and synthetic accessibility (SA) scores,[31] which are known to have their own limitations.[32, 33] Recently, Buttenschoen *et al.* introduced *PoseBusters*, a tool designed to evaluate the physical validity of ligand poses generated by deep learning models.[34] As a rigorous physical tool, *PoseBusters* has driven the development of generative models that produce more physically plausible conformations.[35] However, while other generative models have been shown to generate chemically implausible structures (i.e., structures that are not chemically stable or synthesizable),[36] the output of structure-based generative algorithms has yet to be examined rigorously from a medicinal chemistry perspective. Most studies have relied solely on the validity of SMILES strings or 3D structures as criteria for chemical plausibility, supplemented by distribution analyses of 2D structural properties. Nevertheless, these approaches are insufficient for comprehensively evaluating the chemical plausibility.[37-39] The absence of effective metrics impedes the ongoing development and enhancement of models that generate chemically plausible, drug-like molecules, which we consider essential for practical applications and for advancing drug discovery.

To evaluate the ability of generative algorithms to design chemically plausible and drug-like molecules, we introduced two novel metrics developed initially from a survey of drug-like molecules from the ZINC20 and ZINC22 databases.[15, 40] We applied these, along with an additional metric utilizing ring system occurrence from the ChEMBL

database,[36, 41] to provide a comprehensive assessment of the chemical plausibility of

molecules generated by seven structure-based generative algorithms (3D-Generative-

SBDD or known as 3DSBDD,[42] pocket2mol,[19] TargetDiff,[18] DecompDiff,[43] PMDM,[39]

Decompopt,[38] and MolSnapper[35]), in comparison with three control groups (FDA-

approved small molecule drugs, ChEMBL clinical small molecules, as well as the

crossdock dataset[23]) that are believed to contain drug-like molecules. Overall, we found

that molecules produced by the generative models are less drug-like compared to those

from the control groups, largely due to insufficient chemical plausibility and drug-

likeness. Further property-distribution analysis and visualizations identify contributory

factors—possibly stemming from the training datasets and model architectures—that

likely underlie this performance gap. To reduce potential bias from the target distribution

of the crossdock test set, we carefully chose three representative protein targets—the c-

Src kinase (PDB ID: 7WF5),[44] the Smoothened receptor (PDB ID: 5L7I),[45] and the

Dopamine D1 receptor (PDB ID: 7CKY)[46]—and compared the generated molecules with

high-throughput virtual screening (HTVS) hits. The generative algorithms could design

molecules with high predicted binding affinity, but they consistently faced challenges in

generating chemically plausible and drug-like compounds in our studies. Building on

these findings, our metrics and analyses offer practical guidance for refining structure-

based generative algorithms to yield more chemically plausible, drug-like molecule

designs.

Figure 2. Summary of current 3D structure-based generative algorithms. **(A)** The 3D structures of ligands and proteins can be represented using various formats, including voxelized grids, Cartesian coordinates, and Euclidean distance matrices. More recently, some models represent 3D data as tokens to enable the use of language models for 3D structure-based generation tasks. **(B)** In addition to using protein structures as conditional inputs for molecular generation, domain-specific knowledge such as pharmacophores and protein–ligand interactions can also be incorporated to guide the generative process. **(C)** These models can further be categorized by their generation strategies. Some adopt an auto-regressive approach, generating ligands atom-by-atom or fragment-by-fragment, while others follow a one-shot strategy, such as diffusion models, to generate the full molecule in one step.

Results

Are all the generated molecules chemically plausible and drug-like?

To ensure a fair comparison of structure-based generative models, all selected generative models were trained and tested on the same subsets of the CrossDock2020 dataset.[23, 42] To avoid training bias, we utilized pre-trained models to generate 100 molecules for each of the 100 proteins in the test set, aiming for a total of 10,000 molecules for the benchmarking study. However, we found that not all algorithms generated exactly 10,000 molecules (presumably due to their algorithm design, see a summary in Table S2). Some generated molecules were duplicates or invalid, as indicated by a `None` value returned during the conversion from SMILES or structure

data file (.sdf) to a Mol object using the RDKit package.[47] Table S2 also summarizes the

generation efficiency for each algorithm and the device used for generation for

reference, which is generally consistent with earlier studies.[48]

With these molecular structures generated by different models, we applied several

metrics to assess their chemical plausibility. The first metric involves extracting ring

systems from each generated molecule and recording their occurrence in the ChEMBL

database.[36, 41] ChEMBL is a manually curated database of bioactive molecules with

drug-like properties. If a ring system is uncommon in the ChEMBL compounds, its

chance of being either chemically plausible or drug-like can be low. The second and

third metrics evaluate whether the Bemis-Murcko[49] (BM) scaffolds of the molecules

appear among drug-like molecules in the ZINC20 (870 million) and ZINC22 (54.6 billion)

databases. If a molecule's BM scaffold isn't present in these databases, it might suggest

instability or a lack of drug-like properties. Additionally, it is worth noting that the "drug-

like molecules" in the ZINC databases are predicted based on molecular properties and

may not necessarily be truly drug-like, while some ZINC compounds have not been

synthesized but are predicted to be synthesizable. Additionally, a BM scaffold can be

absent from ZINC while still being chemically plausible, and the same is true for the ring

systems in ChEMBL. Our results clearly indicate that the three metrics used in this work

show high agreement between the three control groups (Figure 3), while inconsistency

is observed among the generated compounds.

Figure 3. Percentage of compounds that are evaluated with three metrics and the PAINS filter. All values are normalized. **(A)** The "min_freq > 100" metric is calculated by extracting the ring systems in each molecule and documenting the frequency of each ring system's occurrence in the ChEMBL database. If the least frequent ring system (some molecules may contain multiple ring systems) appears fewer than 100 times in ChEMBL, the molecule is considered potentially unstable or non-drug-like. The ratio is determined by dividing the number of molecules that meet this criterion by the number of unique molecules containing ring systems. **(B-C)** "BM scaffolds" are calculated by extracting the scaffolds of drug-like molecules from ZINC20 and ZINC22 databases. If the BM scaffolds of generated molecules are not found in these databases, it may suggest that the generated structures are either complex to synthesize or chemically implausible. The ratio is calculated by dividing the number of BM scaffolds present in ZINC by the total number of BM scaffolds from the generated molecules. **(D)** Percentages of molecules that pass the PAINS filter.

The three control groups (labeled as FDA, ChEMBL, and crossdock) consistently perform well on all metrics, which suggests that compounds in these groups are likely to share similar properties or drug-likeness. Over 69% of control-group molecules pass the ChEMBL ring-system metric, compared to fewer than 50% of algorithm-generated molecules (Figure 3A). A consistent difference was also found between our control molecules and the generated molecules using the two ZINC-based metrics, which

measure the percentage of BM scaffolds from ZINC20 and ZINC22 compounds (Figures 3B and 3C, respectively). The three control groups achieve about 10% higher results in both metrics than the generated groups, except for pocket2mol. Moreover, the highest percentages were often observed with the FDA-approved small molecules, followed by the ChEMBL clinical compound set and the crossdock set, indicating these metrics can identify the most druglike data set. This distinction between FDA-approved drugs and the other two control sets suggests that the presence of BM scaffolds may serve as a strict indicator of drug-likeness. Compared to molecules from the control groups, those generated by algorithms may be less chemically plausible or less drug-like in general, as revealed by the metrics applied here. In the later sections of this work, we analyzed the chemically implausible structures in the generative design and provided examples and additional analysis to support our findings.

Notably, the filter for pan-assay interference compounds, PAINS,[50] did not effectively exclude chemically implausible molecules, as shown by over 92% of molecules passing the filter across all datasets (Figures 3D and S4). The PAINS filter, along with other commonly used filters in our tests (Figure S4), was designed to identify chemical compounds that contain the substructures often linked to false-positive results in high-throughput screening experiments. These filters, which rely on substructure libraries, cannot verify the chemical stability or viability of newly generated molecules. It is possible that some of the generative models already account for PAINS. Overall, the PAINS filter and other filters may have subtle effects in removing chemically implausible molecules during generative design.

Figure 4. Radar charts to compare chemical property distributions in our datasets. The parameters we examined are defined as follows. *MW:* molecular weight; *AliR_C:* aliphatic ring count; *AroR_C:* aromatic ring count; *ChiA_C:* chiral atom count; *SA:* synthesis accessibility; *NHOH_C:* NH/OH group count; *HetA_C:* heteroatom count; *RotB_C:* rotatable bond count; *BriA_C:* bridgehead atom count. Percentages were calculated using the following values as denominators, with the average value serving as the numerator: MW=500, AliR_C=4, AroR_C=3, ChiA_C=6, SA=6, NHOH_C=6, HetA_C=10, RotB_C=8, and BriA_C=2.

What can cause chemical implausibility and low drug-likeness in generative design?

It is impractical to visually inspect our generated molecules one by one. To better understand why structure-based generative models design implausible compounds, we first plotted the distributions of several structural properties and descriptors and compared them with control datasets. Overall, the control groups exhibited similar distributions, indicated by the radar charts (Figure 4). In contrast, the distributions of

molecules generated by algorithms differ substantially from those of the control groups,

particularly with respect to chiral atom count, aliphatic ring count, and aromatic ring

count.(Figure 4). Detailed distributions, shown as violin plots, also highlight the

agreement within the control group and the discrepancies between the controls and the

generated molecules (Figure S2). To better understand these discrepancies, we

examined some of the implausible designs and identified possible causes for them from

a medicinal chemistry perspective.

Figure 5. Chemical property distributions show differences between the generated molecules and
control datasets. Corresponding chemically implausible structures are selected from molecules that
didn't pass ChEMBL ring metrics, and substructures associated with the distributions are highlighted
in red by RDKit. **(A)** The molecular weight distribution across datasets. **(B)** Examples of molecules
with low molecular weight, generated by 3DSBDD or pocket2mol. **(C)** Number of aliphatic rings and
aromatic rings distributions across datasets. **(D)** Example of chemically implausible molecules with
multiple aliphatic rings and one or no aromatic rings.

First, chemically unstable structures or substructures in the designs present a

common issue, even in low molecular-weight designs. For example, 3DSBDD and

pocket2mol generated relatively smaller molecules than the others. The average

molecular weight of molecules from these methods is under 255 Da, compared to over

280 Da for molecules from other algorithms tested in this work (Figure 5A). While these

designs may have some advantages regarding drug-likeness parameters or metrics

(such as synthesizability), the very restricted number of atoms and feasible bonds likely

requires more sophisticated designs. Nevertheless, we identified several unreasonable

ones in the generated datasets, such as a sp-hybridized carbon atom in a five-member

ring (Figure 5B). Chemically unstable structures can be found in every generated

dataset, suggesting that some fundamental chemical rules may still be missing in

current algorithms or models.

Second, the generated molecules typically contain too few aromatic rings but too

many aliphatic ones. The average number of aromatic rings per generated molecule for

each algorithm ranged from 0.5 to 1.75, with most algorithms generating fewer than 1

aromatic ring per molecule. In contrast, the control groups typically averaged more than

1.5 aromatic rings per molecule, with ChEMBL and crossdock molecules having values

close to 2 (Figures 5C and S6). Further, aside from pocket2mol, the other algorithms

produced more aliphatic rings, with average counts per molecule ranging from 1.35 to

2.5. This is generally higher than the control groups, which have fewer than 1.3 aliphatic

rings per molecule on average (Figure 5C). There can be a bias toward aliphatic ring

systems over aromatic ones in these generative algorithms. Several examples are

shown in Figure 5D to illustrate this bias in actual designs. Such bias can allow the

designed molecules to adopt non-flat scaffolds and maximize the contacts at the binding

pocket, but it may also lead to challenging synthesis or chemically implausible

structures.

Third, the generated molecules typically have more chiral centers. On average,

molecules generated by each algorithm contain between 2.7 and 3.6 chiral atoms per

molecule, with most algorithms producing more than 3.0. In comparison, crossdock and

ChEMBL molecules average around 1.6 chiral centers, while FDA molecules average

approximately 2.5. Current algorithms tend to generate more structurally complex

molecules, which may be harder to synthesize (Figures 6A and S6). Indeed, we

observed higher synthetic accessibility scores (predicted to be more challenging to

synthesize[51]) for the generated molecules, with an average SA score of over 4.1

(Figure 6B). Some typical designs with multiple chiral centers in complex ring systems

are shown in Figure 6C. However, the three control groups show lower SA scores: 3.6

for FDA-approved small-molecule drugs, 3.3 for ChEMBL clinical small molecules, and

3.3 for ligands in the crossdock dataset. Moreover, we observed that the distribution of

molecules produced by the algorithms differs significantly from that of their training set,

crossdock (Figure 4). This suggests that additional effort is required to learn the

chemical prior information encoded in the training molecules.

Figure 6. Distributions associated with structural complexity show differences between generated
molecules and control datasets. Corresponding chemically implausible structures are selected from
molecules that didn't pass ChEMBL ring metrics, and substructures associated with the distributions
are highlighted in red by RDKit. **(A)** Chiral atom count and synthetic accessibility (SA) score
distributions across datasets. **(B)** Example of molecules with multiple chiral atoms.

Finally, generated molecules have more NH and OH groups compared to the
control groups (Figures 7A and S6). On average, algorithm-generated molecules
contain 2.8 to 5.5 NH/OH groups per molecule, whereas the control groups average
fewer than 2.8. We highlight several example molecules (Figure 7B) generated by the
algorithms that contain multiple NH and OH groups. Although NH/OH groups are
common in drug-like molecules, an excess of these groups may negatively impact
permeability and other pharmacokinetic (PK) properties. The Lipinski's Rule of Five
suggests that a molecule with more than 5 hydrogen bond donors (OH and NH groups)
may have poor oral bioavailability, as they can increase molecular polarity and reduce
membrane permeability. Excessive NH and OH groups may hinder the drug's ability to
cross cell membranes and reach its target and introduce additional metabolically labile
sites on the molecule. The abundance of OH/NH groups may suggest that these
algorithms have learned favorable interactions between the molecule and protein, as
OH/NH groups significantly contribute to binding through hydrogen bonding and
electrostatic interactions. However, drug-likeness and chemical insights are not well
captured due to the structures they produced.

Figure 7. Specific functional groups distribution and example molecules. **(A)** The distribution of NH
and OH group count across datasets reveals that the algorithm prefers generating NH and OH

groups; substructures associated with the distributions are highlighted in red by RDKit. **(B)** Example of molecules with multiple OH/NH groups. **(C)** Four molecules that could meet all three metrics we applied, but are still not drug-like or difficult to synthesize.

How does generative design compare with high-throughput virtual screening (HTVS)?

As HTVS and the underlying technology, molecular docking, have been widely used, we assessed the HTVS and generative design approaches using the same protein targets. Notably, most of our tested algorithms were trained on the crossdock dataset; however, the protein targets in that dataset do not adequately represent the distribution of therapeutic targets of FDA-approved small molecules or ChEMBL clinical compounds. For instance, no G protein–coupled receptors (GPCRs) are included in the crossdock training and test set (Table S3). The variation in protein targets included in the training set may raise questions about the fundamental differences between the generated molecules and actual drugs or drug-like molecules, as well as how accurate these algorithms are for new targets, especially compared to HTVS or docking. While a thorough comparison might require experimental validation, in this work, we compared the generated molecules with the top-scoring molecules from HTVS, mainly focusing on the docking scores and three metrics. To ensure a fair comparison, we selected three drug targets: the C-Src kinase (PDB ID: 7WF5),[44] the Smoothened receptor (PDB ID: 5L7I),[45] and the Dopamine D1 receptor (PDB ID: 7CKY).[46] They were chosen because they were not in the training or test datasets used by these generative algorithms, their ligand-binding sites are deep and well-defined, and no conserved water molecules are present in the binding sites.

We only tested 3DSBDD, pocket2mol, and MolSnapper to generate 500 potential ligands for each of the three protein targets because DecompDiff and DecompOpt currently do not support user-defined proteins, and PMDM and TargetDiff failed to generate enough designs. Particularly, MolSnapper was evaluated under two conditions—generation with and without pharmacophore information derived from crystal ligands—to enable a more thorough comparison. In parallel, we carried out HTVS with one-tenth of the Enamine HTS collection (~174,000 molecules). The

average docking scores for all ligands from Enamine HTS collection are -8.3, -8.9, and -8.0 for docking to the PDB structures 7WF5, 5L7I, and 7CKY, respectively. The top 500 molecules with the lowest Autodock Vina docking scores from HTVS were identified as HTVS hits. The average docking scores of HTVS hits are -12.2, -12.4, and -10.9 for 7WF5, 5L7I, and 7CKY, respectively, which are better compared to those of generated molecules (Figure 8A). Overall, the generated designs from each algorithm show more favorable docking scores (more negative) than the average of all ligands but not the top 500 HTVS hits (Figure 8A). While over 75% of HTVS hits and under 65% of generated designs passed the 'min_freq > 100' measure, fewer than 55% of these molecules from either approach have passed the BM scaffolds metrics (Figures 8B-D). Since the BM-scaffold-based metrics are likely more stringent than the 'min_freq > 100' one, our results suggest that the molecules generated for these three targets are less drug-like than the training dataset (crossdock). Their chemical plausibility and drug-likeness in general were lower than HTVS hits from the Enamine HTS collection. These results highlight the importance of including chemical plausibility assessments in evaluating generative models to ensure high docking scores correspond to practically chemically plausible, drug-like molecules.

We also compared HTVS and generative design in terms of the balance between accuracy and efficiency, using the enrichment factor (EF)[48] and the time to generate a compound. The EF was defined as the ratio of the generated hit rate to the HTVS hit rate, with a given docking score threshold to determine a hit. We calculated the EF with a threshold varying from -8 kcal/mol to -12 kcal/mol, and a value of EF greater than 1 may indicate the effectiveness of generative design (Figure 8E, Table S4). We observed a general trend of EF increasing as the threshold becomes lower or more negative. MolSnapper consistently showed EF above 1, with or without pharmacophore information, but 3DSBDD and pocket2mol failed to generate molecules with strong docking scores for at least one target, indicated by EF close to 0 for at least one target (Figure 8E, Table S4). Given that the average docking time per molecule is 3.37 seconds for Vina-GPU 2.1,[52] and that all algorithms generated one molecule in under 30 seconds on average (Table S2). We suggest that with EF greater than 10, generative design with a robust algorithm like MolSnapper may provide a time-efficient approach

for identifying hit molecules. However, in the three protein targets we tested, high EF

was only achieved with a relatively high threshold (below -10 kcal/mol) and was highly

dependent on the target.

Figure 8. Comparison of molecules generated by different algorithms with high-throughput virtual
screening (HTVS) hits against C-Src kinase (PDB ID: 7WF5), the Smoothened receptor (PDB ID:
5L7I), and the dopamine D1 receptor (PDB ID: 7CKY). For MolSnapper, "p" indicates inclusion of
pharmacophore information from the crystal ligand during generation, whereas "np" indicates that
pharmacophore information was not used. Rows correspond to protein targets: first row, 7WF5;
second row, 5L7I; third row, 7CKY. (A) Vina score distributions for generated molecules, one-tenth of
the Enamine HTS collection, and HTVS hits. (B-D) Percentages of compounds satisfying three
quality-control metrics: ring_freq > 100; BM scaffolds exist in ZINC20; and BM scaffolds exist in
ZINC22. For this analysis, the top 500 HTS molecules ranked by Vina score were used to calculate
pass rates. (E) Enrichment factors for Vina scores of generated molecules relative to one-tenth of
the Enamine HTS collection (left to right: 7WF5, 5L7I, 7CKY).

Discussion

In summary, we have identified chemical implausibility in AI-designed molecules and several shortcomings of current generative algorithms for future enhancement. Two effective metrics based on the occurrence of BM scaffolds in ZINC20 and ZINC22 were developed to evaluate the generated designs. Along with the ring occurrence metric in ChEMBL, these metrics show that some generated molecules are neither chemically plausible nor drug-like when compared to the three control groups. Further structural and property analyses, supported by visual inspection, highlight potential weaknesses in the generated molecules that may contribute to their chemical implausibility and lower drug-likeness compared to the controls. Consistent with these findings, case studies on the c-Src kinase, the Smoothened receptor, and the Dopamine D1 receptor showed that, although generative algorithms were able to produce molecules with favorable docking scores, their chemical plausibility and drug-likeness are generally lower than HTVS hits from a chemical library like the Enamine HTS collection. These results underscore the necessity of incorporating chemical plausibility assessments into generative model evaluation to ensure that high docking scores translate into practically chemical plausible, drug-like molecules.

Beyond chemical plausibility and drug-likeness, which can be assessed from the 2D molecular graph, the quality of 3D binding poses of generated molecules is equally critical. Several studies have reported that current generative models often produce molecules with unreasonable 3D conformations, characterized by high strain energies and spatial clashes.[37, 53] Using PoseBuster,[34] PoseCheck[54] and Torsion library,[55] we evaluated the 3D binding poses of molecules generated by each algorithm on the crossdock test set and obtained results consistent with these previous studies (Table S5). Compared with ligands from the crossdock test set—whose binding poses were generated by docking—most of the algorithm generated conformations performed significantly worse on these metrics (Table S5). Post-processing strategies such as energy minimization and redocking are known to alleviate some of these issues;[37, 53, 56] however, even though this was not the primary focus of our study, the quality of 3D conformation generation remains an important challenge for 3D structure–based generative models.

It is evident that current 3D structure–based generative models exhibit suboptimal performance in capturing chemical prior information from the training set, as reflected by the chemically implausible structures generated, the low pass rates of our proposed metrics, and the low retrosynthesis success rates predicted by SynFormer[57] compared with control groups (Table S6). Commonly used metrics such as QED and SA fail to fully capture this lack of chemical plausibility (Table S6). Several strategies may help address this limitation. A straightforward approach is to apply compound filters,[41, 58] visual inspection, or carefully designed screening workflows[36, 59] to remove chemically implausible or non-drug-like molecules. Another approach is to pretrain models on synthesized or realistic molecular datasets to embed stronger chemical knowledge prior to engaging in structure-based generative tasks. Such pretraining is relatively common in chemical language models[60-62] but remains underexplored for graph-based models. Alternatively, reinforcement learning guided by chemical plausibility metrics—such as those introduced in this study—could steer molecular generation toward more plausible and drug-like structures.[63, 64] In addition, fragment-based generation approaches[65, 66] or synthesis-accessibility-aware models[67] can improve plausibility by leveraging the prior information encoded in fragments, building blocks, or reaction libraries. However, the breadth of chemical space explored is inherently constrained by the predefined nature of these resources. Finally, several recent studies have introduced AI-based post-processing models capable of either repairing problematic structures[68] or generating structurally similar but valid alternatives[57], which may provide another effective route for mitigating these challenges.

Another factor that may contribute to the suboptimal performance of those models on both 2D and 3D prospectives is the quality of the crossdock dataset. As its name suggests, crossdock was constructed by docking ligands from known protein-ligand complexes into protein with similar binding pockets. Thus, the protein-ligand complexes used for training and testing may not represent optimal binding pairs. As shown in Figure S8B, the van der Waals (vdw) volumes of ligands in the test set exhibit only a weak correlation with the pocket volume of the proteins, which may indicate the suboptimal interactions due to the crossdocking nature. Meanwhile, the crossdock dataset does not adequately represent the diversity of therapeutic targets. For example,

G protein-coupled receptors (GPCRs) are absent from both the training and test set (Table S3). This bias could influence its performance on more comprehensive, real-world drug discovery cases. Given that crossdock is currently the most widely used training set for 3D structure-based generative models, adopting newer and more comprehensive datasets—such as BindingNetV2[22] and Large Scale Docking (LSD) database[69]—could improve both performance and generalization by providing more robust and realistic protein-ligand complexes.

Conclusion Remarks

Although challenges remain, we still believe that 3D structure-based generative models hold tremendous potential to accelerate preclinical drug discovery. By leveraging structural information, these models can design diverse classes of pharmaceutical molecules,[70, 71] explore novel chemical space, generate molecules with a favorable Vina docking score, and provide valuable structural insights for medicinal chemists. Although these algorithms currently generate both promising and misleading molecules, further development is expected to produce higher-quality candidates, ultimately encouraging their routine use in medicinal chemistry. Together, our metrics and the analyses presented here provide valuable insights for model developers to improve these algorithms and enhance their utility in drug discovery. The code and data used in the work can be found at https://github.com/Kartinaa/Benchmarking_gene_model.

Method

Data curation: FDA approved small molecule drugs control set was extracted from DrugBank 5.1.12 database. After downloading the full database, a dedicated python script was used to extract the approved small molecule drugs as InChI format and save locally. The ChEMBL clinical small molecules control set was downloaded from the ChEMBL 34 database using website filters to exclude approved small molecules,

ensuring no redundancy with the FDA-approved control set. The CrossDocked2020 control dataset was created by converting all 3D ligands from the CrossDocked2020 dataset into SMILES format and removing duplicates. All control datasets are made publicly available at https://github.com/Kartinaa/Benchmarking_gene_model.

Regarding the datasets used in the metrics: ZINC20 drug-like molecules (0.87 billion) were downloaded from the ZINC20 database's drug-like subset with the "Wait OK" label. ZINC22 drug-like molecules (54.6 billion) were downloaded from the drug-like subsets in 2D trenches from the ZINC22 database. It is important to note that many of the synthesis-on-demand molecules in ZINC have not yet been synthesized. Therefore, their synthesizability is not guaranteed. For reference, the ZINC20 drug-like subset contains 688 FDA-approved small-molecule drugs, 2,621 ChEMBL clinical compounds, and 1,080 molecules from CrossDock2020. In comparison, the ZINC22 drug-like subset contains 810, 1,560, and 1,669 molecules in these control sets, respectively.

Molecule generation: As outlined in the manuscript, all algorithms compared in this study use the same training and test sets. The goal was to generate 100 molecules for each protein in the test set using pre-trained models, theoretically resulting in a total of 10,000 molecules per algorithm (100 molecules × 100 proteins in the test set). However, most algorithms did not generate exactly 10,000 molecules, and ensuring precisely 100 molecules per test protein was challenging. Since this study focuses on evaluating the chemical plausibility of the generated structures, the reasons for this variability are not discussed further.

All molecule generations were conducted using the default configurations or those recommended by the respective authors. One critical factor in molecular generation is the number of heavy atoms in the generated molecules, as this parameter can substantially influence model performance. The strategies used by each algorithm to determine the number of heavy atoms are summarized below. (1) Test set proteins. 3DSBDD and pocket2mol employed a frontier atom prediction model to decide whether to add additional atoms, thereby predicting the total number of heavy atoms. PMDM, DecompDiff, and DecompOpt used the heavy atom count of the corresponding ligands from the test set proteins. TargetDiff determined the heavy atom count based on a

predefined distribution derived from pocket size. MolSnapper used the ground-truth heavy atom number as the mean value to sample from a predefined distribution. (2) User-defined proteins. 3DSBDD and pocket2mol again predicted the heavy atom count for each generated molecule. PMDM used a user-defined heavy atom number. MolSnapper used the user-defined value as the mean for sampling from a predefined distribution. TargetDiff applied the same pocket-size–based predefined distribution as in the test set. DecompDiff and DecompOpt could only operate on the test set and were therefore excluded from user-defined target generation.

To ensure reproducibility, we briefly outline the parameters used for several algorithms: For Molsnapper, the `num_pharma_atoms` flag was set to `20` and `clash_rate` was set to 0.1, as indicated in the GitHub repository. For Decompdiff, the `prior_mode` flag was set to `ref_prior` following configuration file. For Decompopt, the `dup_num` variable in `sample_compose.sh` was set to 0, avoiding re-docking molecules into the binding pocket to improve generation efficiency. While this setting may reduce the performance of generated molecules on docking-based metrics, we expect that it does not significantly impact the chemical plausibility of the generated structures.

Metrics incorporation and property calculations: Before processing and evaluating the generated molecules, all structures were standardized using MolVS.[72] Specifically, salts were removed, tautomers were standardized, charges were neutralized, isotopes were standardized, functional groups such as nitro groups were normalized, and the molecules were sanitized. The canonical SMILES of standardized molecules generated by each algorithm are saved for further use. For ring system-based metrics, ring systems for each molecule were extracted using `useful_rdkit_utils` python library, which incorporates the ring system frequency data from the ChEMBL database. For the ZINC20 and ZINC22 drug-like sets, ring system frequencies were calculated using the same Python library and served as baselines for comparison with the ring system frequencies of the generated molecules. For BM scaffold-based metrics, the BM scaffolds were extracted from the ZINC20 and ZINC22 drug-like sets using the RDKit Python library. After removing redundancies, the BM scaffolds from each dataset

were saved locally and used as baselines to evaluate the occurrences of BM scaffolds

in the generated molecules. All chemical properties were calculated using the RDKit

Python library, and visualizations were created using Matplotlib, Seaborn, and RDKit

libraries. We performed a one-way ANOVA followed by Tukey's honestly significant

difference (HSD) test to assess the statistical significance of differences in mean values.

HTVS and enrichment factor calculation: All docking studies were performed

using AutoDock Vina.[73] Ligands were prepared with 'scrub.py' and

'mk_prepare_ligand.py', while proteins were prepared using 'mk_prepare_protein.py'.

HTVS was carried out with the default parameters of AutoDock Vina. For the Enamine

HTS collection, about one-tenth of the molecules (~178,000 compounds) were randomly

chosen to balance chemical diversity with computational efficiency.

The enrichment factor[48] is defined as follows:

13
$$EF(t) = \frac{N_{G-hit}(t)}{N_G} / \frac{N_{HTVS-hit}(t)}{N_{HTVS}} \qquad \text{(Eq. 1)}$$

Where $N_{G-hit}(t)$ is the number of generated molecules with docking scores lower than

defined docking score thresholds t. N_G is the number of generated molecules.

$N_{HTVS-hit}(t)$ is the number of HTVS molecules with docking scores lower than t, and

N_{HTVS} is the number of molecules in the HTVS library. If the EF value is greater than 1, it

means the generative model has better effectiveness at finding molecules with higher

affinity than the given docking score thresholds.

Author Contributions

The manuscript was prepared with contributions from all authors who have approved
the final version.

Notes

The authors declare no competing financial interest.

Acknowledgments

We sincerely thank Dr. Patrick Walters for his valuable suggestions and insights, which significantly improved this manuscript. We also extend our gratitude to Dr. Brian Shoichet (UC San Francisco), Dr. Jean-Louis Reymond (University of Bern), Dr. Conor Colley (Massachusetts Institute of Technology), Yu Chen (Freie Universität Berlin), and Ye Buehler (University of Bern) for their helpful discussions. This work was supported by NIH R01 awards (GM129431/GM143370) and the AnalytiXIN fellowship (to J.L.).

Refences

(1) Sertkaya, A.; Beleche, T.; Jessup, A.; Sommers, B. D. Costs of Drug Development and Research and Development Intensity in the US, 2000-2018. *JAMA Network Open* **2024**, *7* (6), e2415445-e2415445. DOI: 10.1001/jamanetworkopen.2024.15445 (acccessed 10/10/2024).

(2) Singh, N.; Vayer, P.; Tanwar, S.; Poyet, J.-L.; Tsaioun, K.; Villoutreix, B. O. Drug discovery and development: introduction to the general public and patient groups. *Frontiers in Drug Discovery* **2023**, *3*, Mini Review. DOI: 10.3389/fddsv.2023.1201419.

(3) Batool, M.; Ahmad, B.; Choi, S. A Structure-Based Drug Discovery Paradigm. *Int J Mol Sci* **2019**, *20* (11). DOI: 10.3390/ijms20112783 From NLM.

(4) Acharya, C.; Coop, A.; Polli, J. E.; Mackerell, A. D., Jr. Recent advances in ligand-based drug design: relevance and utility of the conformationally sampled pharmacophore approach. *Curr Comput Aided Drug Des* **2011**, *7* (1), 10-22. DOI: 10.2174/157340911793743547 From NLM.

(5) Abramson, J.; Adler, J.; Dunger, J.; Evans, R.; Green, T.; Pritzel, A.; Ronneberger, O.; Willmore, L.; Ballard, A. J.; Bambrick, J.; et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **2024**, *630* (8016), 493-500. DOI: 10.1038/s41586-024-07487-w.

(6) Krishna, R.; Wang, J.; Ahern, W.; Sturmfels, P.; Venkatesh, P.; Kalvet, I.; Lee, G. R.; Morey-Burrows, F. S.; Anishchenko, I.; Humphreys, I. R.; et al. Generalized biomolecular modeling and design with RoseTTAFold All-Atom. *Science* **2024**, *384* (6693), eadl2528. DOI: doi:10.1126/science.adl2528.

(7) Tropsha, A.; Isayev, O.; Varnek, A.; Schneider, G.; Cherkasov, A. Integrating QSAR modelling and deep learning in drug discovery: the emergence of deep QSAR. *Nature Reviews Drug Discovery* **2024**, *23* (2), 141-155. DOI: 10.1038/s41573-023-00832-0.

(8) Reymond, J.-L. The Chemical Space Project. *Accounts of Chemical Research* **2015**, *48* (3), 722-730. DOI: 10.1021/ar500432k.

(9) Anderson, A. C. The Process of Structure-Based Drug Design. *Chemistry & Biology* **2003**, *10* (9), 787-797. DOI: https://doi.org/10.1016/j.chembiol.2003.09.002.

(10) Erickson, J.; Neidhart, D. J.; VanDrie, J.; Kempf, D. J.; Wang, X. C.; Norbeck, D. W.; Plattner, J. J.; Rittenhouse, J. W.; Turon, M.; Wideburg, N.; et al. Design, Activity, and 2.8 Å Crystal Structure of a C_2 Symmetric Inhibitor Complexed to HIV-1 Protease. *Science* **1990**, *249* (4968), 527-533. DOI: doi:10.1126/science.2200122.

(11) Roberts, N. A.; Martin, J. A.; Kinchington, D.; Broadhurst, A. V.; Craig, J. C.; Duncan, I. B.; Galpin, S. A.; Handa, B. K.; Kay, J.; Kröhn, A.; et al. Rational design of peptide-based HIV proteinase inhibitors. *Science* **1990**, *248* (4953), 358-361. DOI: 10.1126/science.2183354 From NLM.

(12) Dorsey, B. D.; Levin, R. B.; McDaniel, S. L.; Vacca, J. P.; Guare, J. P.; Darke, P. L.; Zugay, J. A.; Emini, E. A.; Schleif, W. A. L-735,524: The Design of a Potent and Orally Bioavailable HIV Protease Inhibitor. *Journal of Medicinal Chemistry* **1994**, *37* (21), 3443-3451. DOI: 10.1021/jm00047a001.

(13) Bohacek, R. S.; McMartin, C.; Guida, W. C. The art and practice of structure-based drug design: a molecular modeling perspective. *Med Res Rev* **1996**, *16* (1), 3-50. DOI: 10.1002/(sici)1098-1128(199601)16:1<3::Aid-med1>3.0.Co;2-6 From NLM.

(14) Grygorenko, O. O.; Radchenko, D. S.; Dziuba, I.; Chuprina, A.; Gubina, K. E.; Moroz, Y. S. Generating Multibillion Chemical Space of Readily Accessible Screening Compounds. *iScience* **2020**, *23* (11), 101681. DOI: 10.1016/j.isci.2020.101681 From NLM.

(15) Tingle, B. I.; Tang, K. G.; Castanon, M.; Gutierrez, J. J.; Khurelbaatar, M.; Dandarchuluun, C.; Moroz, Y. S.; Irwin, J. J. ZINC-22−A Free Multi-Billion-Scale Database of Tangible Compounds for Ligand Discovery. *Journal of Chemical Information and Modeling* **2023**, *63* (4), 1166-1176. DOI: 10.1021/acs.jcim.2c01253.

(16) Askr, H.; Elgeldawi, E.; Aboul Ella, H.; Elshaier, Y. A. M. M.; Gomaa, M. M.; Hassanien, A. E. Deep learning in drug discovery: an integrative review and future challenges. *Artificial Intelligence Review* **2023**, *56* (7), 5975-6037. DOI: 10.1007/s10462-022-10306-1.

(17) Zhang, O.; Lin, H.; Zhang, H.; Zhao, H.; Huang, Y.; Hsieh, C.-Y.; Pan, P.; Hou, T. Deep Lead Optimization: Leveraging Generative AI for Structural Modification. *Journal of the American Chemical Society* **2024**. DOI: 10.1021/jacs.4c11686.

(18) Guan, J.; Qian, W. W.; Peng, X.; Su, Y.; Peng, J.; Ma, J. 3d equivariant diffusion for target-aware molecule generation and affinity prediction. *arXiv preprint arXiv:2303.03543* **2023**.

(19) Peng, X.; Luo, S.; Guan, J.; Xie, Q.; Peng, J.; Ma, J. Pocket2mol: Efficient molecular sampling based on 3d protein pockets. In *International Conference on Machine Learning*, 2022; PMLR: pp 17644-17655.

(20) Powers, A. S.; Yu, H. H.; Suriana, P.; Koodli, R. V.; Lu, T.; Paggi, J. M.; Dror, R. O. Geometric Deep Learning for Structure-Based Ligand Design. *ACS Central Science* **2023**, *9* (12), 2257-2267. DOI: 10.1021/acscentsci.3c00572.

(21) Liu, Z.; Su, M.; Han, L.; Liu, J.; Yang, Q.; Li, Y.; Wang, R. Forging the Basis for Developing Protein–Ligand Interaction Scoring Functions. *Accounts of Chemical Research* **2017**, *50* (2), 302-309. DOI: 10.1021/acs.accounts.6b00491.

(22) Zhu, H.; Li, X.; Chen, B.; Huang, N. Augmented BindingNet dataset for enhanced ligand binding pose predictions using deep learning. *npj Drug Discovery* **2025**, *2* (1), 1. DOI: 10.1038/s44386-024-00003-0.

(23) Francoeur, P. G.; Masuda, T.; Sunseri, J.; Jia, A.; Iovanisci, R. B.; Snyder, I.; Koes, D. R. Three-Dimensional Convolutional Neural Networks and a Cross-Docked Data Set for Structure-Based Drug Design. *Journal of Chemical Information and Modeling* **2020**, *60* (9), 4200-4215. DOI: 10.1021/acs.jcim.0c00411.

(24) Ragoza, M.; Masuda, T.; Koes, D. R. Generating 3D molecules conditional on receptor binding sites with deep generative models. *Chemical Science* **2022**, *13* (9), 2701-2713, 10.1039/D1SC05976A. DOI: 10.1039/D1SC05976A.

(25) Lu, W.; Wu, Q.; Zhang, J.; Rao, J.; Li, C.; Zheng, S. TANKBind: Trigonometry-Aware Neural NetworKs for Drug-Protein Binding Structure Prediction. *bioRxiv* **2022**, 2022.2006.2006.495043. DOI: 10.1101/2022.06.06.495043.

(26) Xiang, Y.-T.; Huang, G.-Y.; Shi, X.-X.; Hao, G.-F.; Yang, G.-F. 3D molecular generation models expand chemical space exploration in drug design. *Drug Discovery Today* **2025**, *30* (1), 104282. DOI: https://doi.org/10.1016/j.drudis.2024.104282.

(27) Alakhdar, A.; Poczos, B.; Washburn, N. Pharmacophore-Conditioned Diffusion Model for Ligand-Based De Novo Drug Design. *arXiv preprint arXiv:2505.10545* **2025**.

(28) Huang, Z.; Yang, L.; Zhou, X.; Zhang, Z.; Zhang, W.; Zheng, X.; Chen, J.; Wang, Y.; Bin, C.; Yang, W. Protein-ligand interaction prior for binding-aware 3d molecule diffusion models. In *The Twelfth International Conference on Learning Representations*, 2024.

(29) Lin, H.; Zhao, G.; Zhang, O.; Huang, Y.; Wu, L.; Liu, Z.; Li, S.; Tan, C.; Gao, Z.; Li, S. Z. CBGBench: Fill in the Blank of Protein-Molecule Complex Binding Graph. *arXiv preprint arXiv:2406.10840* **2024**.

(30) Bickerton, G. R.; Paolini, G. V.; Besnard, J.; Muresan, S.; Hopkins, A. L. Quantifying the chemical beauty of drugs. *Nat Chem* **2012**, *4* (2), 90-98. DOI: 10.1038/nchem.1243 From NLM.

(31) Ertl, P.; Schuffenhauer, A. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *Journal of Cheminformatics* **2009**, *1* (1), 8. DOI: 10.1186/1758-2946-1-8.

(32) Yu, J.; Wang, J.; Zhao, H.; Gao, J.; Kang, Y.; Cao, D.; Wang, Z.; Hou, T. Organic Compound Synthetic Accessibility Prediction Based on the Graph Attention Mechanism. *Journal of Chemical Information and Modeling* **2022**, *62* (12), 2973-2986. DOI: 10.1021/acs.jcim.2c00038.

(33) Zhu, W.; Wang, Y.; Niu, Y.; Zhang, L.; Liu, Z. Current Trends and Challenges in Drug-Likeness Prediction: Are They Generalizable and Interpretable? *Health Data Science* **2023**, *3*, 0098. DOI: doi:10.34133/hds.0098.

(34) Buttenschoen, M.; Morris, G. M.; Deane, C. M. PoseBusters: AI-based docking methods fail to generate physically valid poses or generalise to novel sequences. *Chemical Science* **2024**, *15* (9), 3130-3139.

(35) Ziv, Y.; Marsden, B.; Deane, C. M. MolSnapper: Conditioning Diffusion for Structure Based Drug Design. *bioRxiv* **2024**, 2024.2003.2028.586278. DOI: 10.1101/2024.03.28.586278.

(36) Walters, P. Generative Molecular Design Isn't As Easy As People Make It Look. 2024.

(37) Liu, H.; Qin, Y.; Niu, Z.; Xu, M.; Wu, J.; Xiao, X.; Lei, J.; Ran, T.; Chen, H. How Good are Current Pocket-Based 3D Generative Models?: The Benchmark Set and Evaluation of Protein Pocket-Based 3D Molecular Generative Models. *Journal of Chemical Information and Modeling* **2024**. DOI: 10.1021/acs.jcim.4c01598.

(38) Zhou, X.; Cheng, X.; Yang, Y.; Bao, Y.; Wang, L.; Gu, Q. DecompOpt: Controllable and Decomposed Diffusion Models for Structure-based Molecular Optimization. *arXiv preprint arXiv:2403.13829* **2024**.

(39) Huang, L.; Xu, T.; Yu, Y.; Zhao, P.; Chen, X.; Han, J.; Xie, Z.; Li, H.; Zhong, W.; Wong, K.-C.; et al. A dual diffusion model enables 3D molecule generation and lead optimization based on target pockets. *Nature Communications* **2024**, *15* (1), 2657. DOI: 10.1038/s41467-024-46569-1.

(40) Irwin, J. J.; Tang, K. G.; Young, J.; Dandarchuluun, C.; Wong, B. R.; Khurelbaatar, M.; Moroz, Y. S.; Mayfield, J.; Sayle, R. A. ZINC20—A Free Ultralarge-Scale Chemical Database for Ligand Discovery. *Journal of Chemical Information and Modeling* **2020**, *60* (12), 6065-6073. DOI: 10.1021/acs.jcim.0c00675.

(41) Walters, P. Mining Ring Systems in Molecules for Fun and Profit. 2022.

(42) Luo, S.; Guan, J.; Ma, J.; Peng, J. A 3D generative model for structure-based drug design. *Advances in Neural Information Processing Systems* **2021**, *34*, 6229-6239.

(43) Guan, J.; Zhou, X.; Yang, Y.; Bao, Y.; Peng, J.; Ma, J.; Liu, Q.; Wang, L.; Gu, Q. DecompDiff: Diffusion Models with Decomposed Priors for Structure-Based Drug Design. In Proceedings of the 40th International Conference on Machine Learning, Proceedings of Machine Learning Research; 2023.

(44) Guo, M.; Duan, Y.; Dai, S.; Li, J.; Chen, X.; Qu, L.; Chen, Z.; Wei, H.; Jiang, L.; Chen, Y. Structural study of ponatinib in inhibiting SRC kinase. *Biochemical and Biophysical Research Communications* **2022**, *598*, 15-19. DOI: https://doi.org/10.1016/j.bbrc.2022.02.001.

(45) Byrne, E. F. X.; Sircar, R.; Miller, P. S.; Hedger, G.; Luchetti, G.; Nachtergaele, S.; Tully, M. D.; Mydock-McGrane, L.; Covey, D. F.; Rambo, R. P.; et al. Structural basis of Smoothened regulation by its extracellular domains. *Nature* **2016**, *535* (7613), 517-522. DOI: 10.1038/nature18934.

(46) Xiao, P.; Yan, W.; Gou, L.; Zhong, Y.-N.; Kong, L.; Wu, C.; Wen, X.; Yuan, Y.; Cao, S.; Qu, C.; et al. Ligand recognition and allosteric regulation of DRD1-Gs signaling complexes. *Cell* **2021**, *184* (4), 943-956.e918. DOI: 10.1016/j.cell.2021.01.028 (acccessed 2025/09/11).

(47) RDKit: Open-source cheminformatics. https://www.rdkit.org.

(48) Wang, S.; Lin, T.; Peng, T.; Xing, E.; Chen, S.; Kara, L. B.; Cheng, X. TopMT-GAN: a 3D topology-driven generative model for efficient and diverse structure-based ligand design. *Chemical Science* **2025**, *16* (6), 2796-2809, 10.1039/D4SC05211K. DOI: 10.1039/D4SC05211K.

(49) Bemis, G. W.; Murcko, M. A. The Properties of Known Drugs. 1. Molecular Frameworks. *Journal of Medicinal Chemistry* **1996**, *39* (15), 2887-2893. DOI: 10.1021/jm9602928.

(50) Baell, J. B.; Holloway, G. A. New Substructure Filters for Removal of Pan Assay Interference Compounds (PAINS) from Screening Libraries and for Their Exclusion in Bioassays. *Journal of Medicinal Chemistry* **2010**, *53* (7), 2719-2740. DOI: 10.1021/jm901137j.

(51) Ertl, P.; Schuffenhauer, A. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *J Cheminform* **2009**, *1* (1), 8. DOI: 10.1186/1758-2946-1-8 From NLM.

(52) Tang, S.; Ding, J.; Zhu, X.; Wang, Z.; Zhao, H.; Wu, J. Vina-GPU 2.1: Towards Further Optimizing Docking Speed and Precision of AutoDock Vina and Its Derivatives. *IEEE/ACM Trans Comput Biol Bioinform* **2024**, *21* (6), 2382-2393. DOI: 10.1109/tcbb.2024.3467127 From NLM.

(53) Sanjrani, N.; Coupry, D. E.; Pogány, P.; Palmer, D. S.; Pickett, S. D. Benchmarking 3D Structure-Based Molecule Generators. *Journal of Chemical Information and Modeling* **2025**. DOI: 10.1021/acs.jcim.5c01020.

(54) Harris, C.; Didi, K.; Jamasb, A. R.; Joshi, C. K.; Mathis, S. V.; Lio, P.; Blundell, T. Benchmarking Generated Poses: How Rational is Structure-based Drug Design with Generative Models? *arXiv preprint arXiv:2308.07413* **2023**.

(55) Penner, P.; Guba, W.; Schmidt, R.; Meyder, A.; Stahl, M.; Rarey, M. The Torsion Library: Semiautomated Improvement of Torsion Rules with SMARTScompare. *Journal of Chemical Information and Modeling* **2022**, *62* (7), 1644-1653. DOI: 10.1021/acs.jcim.2c00043.

(56) Feng, W.; Wang, L.; Lin, Z.; Zhu, Y.; Wang, H.; Dong, J.; Bai, R.; Wang, H.; Zhou, J.; Peng, W.; et al. Generation of 3D molecules in pockets via a language model. *Nature Machine Intelligence* **2024**, *6* (1), 62-73. DOI: 10.1038/s42256-023-00775-6.

(57) Gao, W.; Luo, S.; Coley, C. W. Generative artificial intelligence for navigating synthesizable chemical space. *arXiv preprint arXiv:2410.03494* **2024**.

(58) Remington, J. M.; McKay, K. T.; Beckage, N. B.; Ferrell, J. B.; Schneebeli, S. T.; Li, J. GPCRLigNet: rapid screening for GPCR active ligands using machine learning. *J Comput Aided Mol Des* **2023**, *37* (3), 147-156. DOI: 10.1007/s10822-023-00497-2 From NLM.

(59) McKay, K.; Hamilton, N. B.; Remington, J. M.; Schneebeli, S. T.; Li, J. Essential Dynamics Ensemble Docking for Structure-Based GPCR Drug Discovery. *Frontiers in Molecular Biosciences* **2022**, *Volume 9 - 2022*, Original Research. DOI: 10.3389/fmolb.2022.879212.

(60) Wu, K.; Xia, Y.; Deng, P.; Liu, R.; Zhang, Y.; Guo, H.; Cui, Y.; Pei, Q.; Wu, L.; Xie, S.; et al. TamGen: drug design with target-aware molecule generation through a chemical language model. *Nature Communications* **2024**, *15* (1), 9360. DOI: 10.1038/s41467-024-53632-4.

(61) Wang, J.; Luo, H.; Qin, R.; Wang, M.; Wan, X.; Fang, M.; Zhang, O.; Gou, Q.; Su, Q.; Shen, C.; et al. 3DSMILES-GPT: 3D molecular pocket-based generation with token-only large language model. *Chemical Science* **2025**, *16* (2), 637-648, 10.1039/D4SC06864E. DOI: 10.1039/D4SC06864E.

(62) Noutahi, E.; Gabellini, C.; Craig, M.; Lim, J. S.; Tossou, P. Gotta be SAFE: a new framework for molecular design. *Digital Discovery* **2024**, *3* (4), 796-804.

(63) Wang, J.; Qin, R.; Wang, M.; Fang, M.; Zhang, Y.; Zhu, Y.; Su, Q.; Gou, Q.; Shen, C.; Zhang, O.; et al. Token-Mol 1.0: tokenized drug design with large language models. *Nature Communications* **2025**, *16* (1), 4416. DOI: 10.1038/s41467-025-59628-y.

(64) Jiang, L.; Sun, S.; Qi, B.; Fu, Y.; Xu, X.; Li, Y.; Zhou, D.; Fu, T. Chem3DLLM: 3D Multimodal Large Language Models for Chemistry. *arXiv preprint arXiv:2508.10696* **2025**.

(65) Wang, S.; Liang, D.; Wang, J.; Dong, K.; Zhang, Y.; Liang, H.; Xu, X.; Song, T. FraHMT: A Fragment-Oriented Heterogeneous Graph Molecular Generation Model for Target Proteins. *Journal of Chemical Information and Modeling* **2024**. DOI: 10.1021/acs.jcim.4c00252.

(66) Powers, A. S.; Lu, T.; Koodli, R. V.; Xu, M.; Gu, S.; Karelina, M.; Dror, R. O. MedSAGE: Bridging Generative AI and Medicinal Chemistry for Structure-Based Design of Small Molecule Drugs. *bioRxiv* **2025**. DOI: 10.1101/2025.05.10.653107 From NLM.

(67) Wang, M.; Li, S.; Wang, J.; Zhang, O.; Du, H.; Jiang, D.; Wu, Z.; Deng, Y.; Kang, Y.; Pan, P.; et al. ClickGen: Directed exploration of synthesizable chemical space via modular reactions and reinforcement learning. *Nature Communications* **2024**, *15* (1), 10127. DOI: 10.1038/s41467-024-54456-y.

(68) Park, J. H.; Song, H. J.; Lee, S. W. ChemFixer: Correcting Invalid Molecules to Unlock Previously Unseen Chemical Space. *IEEE J Biomed Health Inform* **2025**, *Pp.* DOI: 10.1109/jbhi.2025.3593825 From NLM.

(69) Hall, B. W.; Tummino, T. A.; Tang, K.; Mailhot, O.; Castanon, M.; Irwin, J. J.; Shoichet, B. K. A Database for Large-Scale Docking and Experimental Results. *Journal of Chemical Information and Modeling* **2025**, *65* (9), 4458-4467. DOI: 10.1021/acs.jcim.5c00394.

(70) Tao, H.; Yang, B.; Farhangian, A.; Xu, K.; Li, T.; Zhang, Z.-Y.; Li, J. Covalent-Allosteric Inhibitors: Do We Get the Best of Both Worlds? *Journal of Medicinal Chemistry* **2025**, *68* (4), 4040-4052. DOI: 10.1021/acs.jmedchem.4c02760.

(71) Guan, J.; Peng, X.; Jiang, P.; Luo, Y.; Peng, J.; Ma, J. LinkerNet: fragment poses and linker co-design with 3D equivariant diffusion. *Advances in Neural Information Processing Systems* **2024**, *36*.

(72) *MolVS: Molecule Validation and Standardization.* https://molvs.readthedocs.io/en/latest/ (accessed 2025 07/25).

(73) Eberhardt, J.; Santos-Martins, D.; Tillack, A. F.; Forli, S. AutoDock Vina 1.2.0: New Docking Methods, Expanded Force Field, and Python Bindings. *Journal of Chemical Information and Modeling* **2021**, *61* (8), 3891-3898. DOI: 10.1021/acs.jcim.1c00203.