Brain-Guided Convolutional Neural Networks Reveal Task-Specific Representations in Scene Processing

Bruce C. Hansen[1][*], Michelle R. Greene[2], Henry A.S. Lewinsohn[1], Audrey E. Kris[1], Sophie Smyth[1], & Binghui Tang[1]

[1] Department of Psychological & Brain Sciences, Neuroscience Program, Colgate University, Hamilton NY

[2] Barnard College, Columbia University, Department of Psychology, New York, NY

[*]Corresponding author (bchansen@colgate.edu)

Abstract

Scene categorization is the dominant proxy for visual understanding, yet humans can perform a large number of visual tasks within any scene. Consequently, we know little about how different tasks change how the scene is processed, represented, and its features ultimately used. Here, we developed a novel brain-guided convolutional neural network (CNN) where each convolutional layer was separately guided by neural responses taken at different time points while observers performed two different tasks on the same set of images. We then reconstructed each layer's activation maps via deconvolution to spatially assess how different features were used as a function of task. The brain-guided CNN made use of image features that human observers identified as being crucial to complete each task starting around 244 ms and persisted to 402 ms. Critically, because the same images were used across the two tasks, the CNN could only succeed if the neural data captured task-relevant differences. Our analyses of the activation maps across layers revealed that the brain's spatiotemporal representation of local image features evolves systematically over time. This underscores how distinct image features emerge at different stages of processing, shaped by the observer's goals and behavioral context.

Introduction

The human brain rapidly encodes and represents complex scene information from our visual environment, enabling a variety of intelligent behaviors. A leading framework for characterizing visual representations of scenes is a hierarchical feedforward sweep through the ventral visual system. In this process, features of increasing complexity are extracted and combined to achieve a semantic classification of the environment [1-6]. This framework has been supported by psychophysical (e.g., [7]), MEG (e.g., [8]), EEG (e.g., [9-10]), and fMRI (e.g., [11-12]) evidence. It has also inspired the development of deep convolutional neural networks (CNNs) in computer vision, which can achieve human-level classification performance [13], and are known to correlate with different processing stages (both spatially and temporally) along the visual hierarchy (e.g., [14-15]).

Despite these successes, the feedforward model relies on two oversimplifications that limit our understanding of scene representations. First, although scene categorization is an important aspect of visual perception (e.g., [16]), it is unlikely to be the only goal. We use different information in an environment to achieve different goals. For example, walking through an environment may only require understanding major paths and their relative difficulty (e.g., [18-19]), while searching for a specific object engages knowledge of what the object looks like and where it is likely to appear (e.g., [20-23]). Second, neural scene representations are highly dynamic, even with static images (reviewed in [24]). This suggests that the underlying representational codes for scenes are not fixed but vary spatially (across the scene) over time—even in the earliest stages of processing [25-26]. Therefore, a more complete characterization of complex visual processing should examine how the visual system uses specific scene features over time and how this varies with the observer's task.

In previous work, we have shown that neural responses to images of scenes use different features over time and that an observer's task can dramatically alter feature use [9]. For example, relatively low-level features, such as multi-scale oriented filters, were only used when observers discriminated the dominant orientations in a scene. In contrast, the lexical distance between category names was only used when observers assessed the similarity between scene category names. This suggests that the brain does not simply create a fixed categorical state based exclusively on the environment. Instead, it creates a representation that best matches the behavioral goals of the observer, likely resulting from a dynamic interplay between expectations and attention [27-32]. While that approach revealed how global task-modulated scene information was used over time, it did not examine how task-related information varied over image location, nor how different image locations were prioritized dynamically over time.

To address this issue, Hansen and colleagues [26] developed a spatial mapping analysis for EEG data called Dynamic Electrode-to-Image (DETI) mapping. This method provided a much more refined understanding of the neural dynamics for scenes and established when different scene regions contribute to the neural code. Specifically, DETI mapping established how spatial frequency-selective neural populations prioritized different image locations over time. However, the mapping of EEG responses to image regions was only carried out with one experimental task, so we could not determine how an observer's task altered the image-region coding of scene information.

Ideally, we would map the image locations containing task-relevant information to real-
time neural signals. While DETI showed that this is straightforward for easily parameterized
features such as spatial frequency, scaling this approach to the higher-level representations
underlying goals and tasks is not trivial. A major hurdle is establishing the utility of each image
region for any given task, which involves numerous assumptions about what should be
considered useful and when it should become useful.
As CNNs link image location information with higher-level outputs, this work
investigates training a novel CNN that processes images as input and uses the corresponding
neural responses over time to guide how the weighted image information is passed through
each subsequent layer. Previous studies have used "brain guidance" to improve CNN
robustness for classification by aligning CNNs with neural responses [33-42]. However, our
approach visualizes the image features used while participants perform different visual tasks.
Essentially, this involves training a CNN to differentiate between identical images using neural
signals from participants performing different tasks on those images. Stated differently, we
asked the network to take in an image and predict what task the observer was engaged in while
viewing that image. CNNs require structural differences between images to differentiate them.
Without neural guidance, a CNN would fail to differentiate between identical sets of images.
Therefore, our approach forces the network to evaluate each layer's filter responses against
task-evoked neural responses to achieve accurate task classification.
This brain-guided CNN approach allows us to reconstruct activation maps (via
deconvolution [43]) for each CNN layer and image. Those maps can illustrate the image regions
containing task-relevant information (as measured by EEG) at a given time point in visual
processing. We then compare those maps against maps generated from human behavior to
show when and how different image features may support task-oriented behavior. Critically,
our aim is not to improve CNNs per se, but to use a brain-guided CNN as a tool for
understanding how and when the visual system uses task-relevant features. Our results show
that a CNN can successfully differentiate between identical sets of images when augmented
with neural responses sampled at different timepoints. Crucially, the network makes use of
task-relevant image regions beginning around 244 ms to achieve successful task classification.
Interestingly, the network struggled to classify the task for images where the task-relevant
regions were largely overlapping. This indicates that neural responses generated by those
images were more similar between the two tasks, which would be expected if task-relevant
information were accurately captured by the CNN. This study thus advances our understanding
of how the visual system prioritizes task-relevant visual information over time.
167
168
169   **Results**
170
Participants (N = 24) completed two pre-cued tasks (object and scene function) on the same set
of images while their neural responses were recorded via EEG, generating two separate ERP
datasets (one per task). The object task assessed participants' confidence in whether a
particular cued object was present in the image, while the function task evaluated the
likelihood that a specific cued action could be performed in the scene (see the Methods section
for further details). Additionally, an independent set of observers (N = 50) viewed the same

image set and marked image regions they believed contained useful features for each task.
Each image was marked separately for the object and function tasks. The behavioral
experiment generated task-relevant 'information utility' (IU) maps for each image, identifying
regions relevant to each task. IU maps were used to assess the extent to which each layer in
our brain-guided CNN utilized the same regions as human participants for performing each task.
Only the participant averaged ERP data for each task were used to guide the CNN during
training. After a brief discussion of our behavioral results (Section 1) and introductory remarks
on the brain-guided CNN (Section 2), we show findings from our analyses of the convolutional
layers in that network (Sections 3 - 4).
186
1.0 Overall Behavioral Responses
We constructed information utility (IU) maps to provide a behavioral reference for analyzing
the image reconstructions at each network layer (detailed in the next section). Those maps
were built based on 50 independent observers who each clicked on 10 image regions that they
thought were the most relevant to either the possible locations of an object, or locations
relevant for a scene function.   Example IU maps, along with the averages across all maps within
each task, are shown in **Figure 1**.

Figure 1. *Top two rows: example object and function IU maps for two different stimuli. Bottom row: averaged*
object and function IU maps (averaged over all stimuli). See text for further detail.
197
198 The averaged maps in **Figure 1** show that relevant locations for the object task were distributed
199 broadly across image space, with a slight concentration in the center. For the function task
200 however, the most informative regions were largely concentrated along lower portion of the
201 image. In subsequent analyses, we examine the extent to which the brain-guided convolutional
202 neural network's layers correspond to these task-relevant regions.
203
2.0 The Brain-Guided Convolutional Neural Network
The basic architecture and general operations of the brain-guided convolutional neural network
presented here are inspired by those of AlexNet [44], see a detailed account of the brain-guided
architecture in the Methods section, and **Figure 2** for an illustration. Each network layer was
guided by a different ERP timepoint that represented times where neural responses were
maximally dissimilar across tasks (see Methods section). Neural dissimilarity between tasks is
important because it suggests task-based information is being encoded. Further, because the
neural data are the only means for the network to differentiate between identical images, it is
important that the network is guided by neural responses that are as distinct as possible across
tasks.
The network was trained on the same 64 images used in the EEG and behavioral
experiments (see Methods for more detail about the images). During training, the network
predicted a given image's task using the image's pixel values and its corresponding task-driven
neural responses at four different time points (one for each convolutional layer). Once trained,
we used a deconvolution algorithm [43] to reconstruct the activation maps for each input
image and each layer and analyzed those maps against the IU maps in order to identify how and
when task-related features become available.
221

Figure 2. *Illustration of our brain-guided CNN and neural similarity pooling operation. Top: the network consisted of four convolutional layers, each being guided by neural responses sampled from one of four different sequential time points from ERP data measured across all images and both tasks. The output of the network consisted of a single decision node that predicted which task an observer was performing on the image. Bottom: we replaced the typical max-pooling operation with a neural similarity pooling operation that selected filter outputs that most closely matched the neural response elicited by each image (see Methods section for further detail).*

3.0 Network Performance and Analysis Results

We trained our brain-guided CNN 10 times, each time using a different random initialization of the weights across all layers. The following sub-sections detail the results of the model's performance analysis, as well as our behavioral response and reconstruction analysis.

3.1 Network Classification Performance

Across the 10 training runs, the brain-guided CNN correctly predicted the task that the observer was engaged in 90% of the time. Specifically, we stopped network training once ~90% accuracy was achieved due to the limited gain in accuracy with more learning epochs. The decision node consisted of a traditional sigmoid activation function, with a correct object task classification being a zero and a correct function task classification being a 1. Object classifications were counted as correct if the sigmoid output fell below 0.4 and function classifications were counted as correct if the sigmoid output was above 0.6. Outputs that fell within the 0.4-0.6 range were counted as incorrect. **Figure 3** shows the response to each image, averaged across training run, when paired with neural responses to the object task (red bars) and to the same set of images when paired with neural responses for the function task (blue bars). The difference between each identical image pair was assessed for statistical significance using a

248 paired samples t-test. All but one of the unique 64 pairs were found to be statistically
249 significant (all P's < .003). The image that did not reach statistical significance was trending
250 toward significance (P = 0.083).

251
252 **Figure 3.** *Overall network performance. Image order is identical for the two sets of classifications. Error bars are*
253 *95% confidence intervals computed over the 10 different training runs.*
254
3.2 Layer-by-layer Stimulus Reconstruction Analyses
Next, we examined the extent to which reconstructed images at each convolutional
layer could predict the IU maps that provided task-relevant image locations. This allows us to
assess whether and when the network makes use of task-relevant image regions.
For each task, stimuli were reconstructed as activation maps across the convolutional
layers using the deconvolution procedure outlined by [43]. Briefly, this process involves passing
an image through a trained network and performing the following steps: (1) unpooling the
pooled neural similarity output by mapping it back to its original pre-pooling locations, (2)
applying the leaky ReLU operator to rectify the responses, and (3) convolving the unpooled
maps with the transposed filters. The resulting activation maps were summed and normalized
across filters to create a final activation map for each image and task, producing one activation
map per image-task pair. **Figure 4** illustrates this processing pipeline. Additionally, activation
maps were generated for each of the 10 training runs, resulting in 10 activation maps for each
image and task.

Figure 4. *Illustration of the network training and evaluation pipeline for a single image. The network was trained stochastically. Each time an image was passed through the network, it was accompanied by either neural data from the object task or the function task. Once the network was able to classify the task at ~90% accuracy, we computed activation maps for each layer and each task.*

Before conducting the activation map analysis, we estimated a null distribution for the
activation maps by creating activation maps for each task whereby the filter weights for each
layer were randomized (i.e., untrained weights), and the neural responses were shuffled across
images. We repeated this process 50 times with different random weights and a different
shuffled order of neural signals for each (50 random activation maps for each layer, image, and
task). Next, for each activation map, we computed the dot product between each 3x3 region in
each activation map to the corresponding location in each of the random activation maps. We
then took the average across all of those distance maps for each image and task. Each of the
averaged distance maps were normalized to 1 and then subtracted from 1. That ensures that
regions with high dissimilarity (where the activation maps contained activations that were
much larger than expected by chance) had the highest values. The dissimilarity maps were then
used to weight the activations maps, thereby ensuring that only activations that were greater
than expected by chance would carry more weight in the activation map analysis.
To compare activation maps between the two tasks at each layer, we first took the
difference between a given object activation map and function activation map. At locations
where the differences were greater than zero (larger activation for objects than functions), the
difference value was mapped to the corresponding location in a new activation map (an object-
only activation map). At locations where the differences were less than zero (larger activation
for functions than objects) the absolute value of the difference value was mapped to the
corresponding location in a new activation map (a function-only activation map). Each object-
only and function only activation map was then weighted by the activation dissimilarity maps
mentioned in the previous paragraph. Lastly, the non-normalized dot product was taken
between each activation map and it's corresponding IU map. This process was repeated for
each image and task and then averaged over all images within a given task. See **Figure 5a** for
an illustration of this analysis. As a relative control, a given activation map was dotted with the
IU map from the other task (e.g., dot product between an object activation map and function IU
map from the same image). The larger the products between matching activation maps and IU
maps relative to mismatched, the more the network was using regions specific to neural
response that the task elicited. The above analysis was repeated for each of the 10 training
runs and averaged (**Figure 5b**). Independent samples t-tests conducted on each match vs
mismatched map pair show that task relevant region information use for both the object and
functions tasks begins around 244 ms and persists out to at least 402 ms. Importantly, the
relative differences that were observed at 244 ms and 402 ms were observed for each of the 10
training runs and were therefore robust to different random weight initializations.
We next examined the relative dissimilarity (Euclidean distance) of each image's
activation maps across both tasks at each convolutional layer. The paired distances were then
normalized and submitted to a one-way ANOVA, which yielded a significant effect of layer,
$F(3,252) = 7.53$, $P < .000$, with conv1 M = 0.278, conv2 M = 0.363, conv3 M = 0.468, and conv4
M = 0.399. Follow-up independent t-tests revealed significant differences between conv1,
conv2, and conv3, (all Ps < 0.03) indicating that as the images made their way through the
brain-guided network, the distances between activations for each image between the two tasks
were increased, suggesting more distinct task-relevant representations emerged over time.
318

One question raised by the results shown in **Figure 5b** is whether all four convolutional layers were necessary, or whether a simpler network guided at the relevant time points could achieve a similar result. To test that, we scaled back our network to only have one convolutional layer (each time point used in the full network, separately), followed by a fully connected layer and decision node. We found that, while the smaller network could learn to differentiate the tasks, it did so in a way that did not utilize task-relevant information, suggesting that the representations built up across earlier layers are necessary to create later task-relevant representations. Lastly, to test whether the apparent build-up of task relevant information use is not simply a byproduct of having more layers in the network, we shuffled the time-specific neural data across the layers and conducted the activation map analysis using the behavioral IU maps. The results showed that the network made use of local region information in a manner that was inconsistent with behavior (all Ps > .05 for all match vs mismatched IU map pairs).

Figure 5. a) *Illustration of our activation map analysis for an example image and network layer. We first took the absolute difference between two corresponding activation maps for any given stimulus and weighted those values by activation maps that would be expected by chance alone. We then took the dot product between the weighted difference maps and their corresponding task IU map (and the control map from the opposite task). See text for further detail.* *b)* *Results from our activation map analysis described in the text (and illustrated in Figure 5a). Error bars are 95% confidence intervals computed over 10 training runs. The network is considered to be using task relevant information when the reconstruction activation is higher when the reconstruction activation came from the same task as the IU map compared to when that same activation map was weighted by an IU map from the other task. For example, when tasked with classifying a given image when given neural data from the object tasks, the network used object relevant information when compared to information that was more relevant to the function task.*

345
3.3 Assessing the degree of overlap across tasks
The averaged IU maps in **Figure 1** suggest that, to a reasonable extent, function and object
information tended to have different location distributions in our images. Nevertheless, **Figure
6a** also shows signs of overlap between the regions useful for each task. However, the critical
question is whether the IU maps (object and function) for each image are sufficiently different.
To asses that, we computed the Euclidean distance between each image's utility maps in MDS
space (**Figure 6b**). The distance distribution shows a slight bimodal tendency, suggesting two
distributions, one for a set of images with similar IU maps and another with largely dissimilar IU
maps.

356
357 ***Figure 6.*** *(a) the first two MDS dimensions for the object (red) and function (blue) IU maps. While there is good*
358 *separation between the types of IU maps, there is some overlap. (b) Euclidean distance for each IU map pair*
359 *showing an approximately bimodal distribution.*

360
To assess whether the differences between task relevant regions overlap across the
images could explain the differences between the ERPs measured for each task, we conducted
a split-half analysis along Euclidean distances (x-axis line in **Figure 6b**). That is, the ERP data
were split according to images with similar IU maps (N = 32 images) between the two tasks
(images below the median) and images with dissimilar IU maps (N = 32 images). We the
computed a time-resolved (11ms sliding window) regression analysis between windowed ERPs
from each task (**Figure 7**). Larger R2s indicate smaller differences between the ERPs for each
task. The R2 plots show overall higher R2s for images with similar IU maps, suggesting that task
effects were weaker for those images. By contrast, images with largely dissimilar IU maps had
smaller R2s. To assess the extent of the R2 differences as they relate to the timepoints and
electrodes that we used for network training, we averaged the R2s across the relevant
electrodes within 11 ms windows centered on each of our four target timepoints (**Figure 7**).
The overall R2s are relatively low (all less than 0.25) due to our efforts to select time points and
corresponding electrodes with low similarity (see Method section), yet there is a trend for
increasing dissimilarity over time between the two sets of images.

Is the brain-guided CNN's accuracy lower for classifying images with similar IU maps
because their ERPs are less distinct and their task-relevant regions overlap? To investigate that,
we analyzed the model's classification performance across 10 training runs. We calculated the
difference between the decision node's output and the target response for each task (0 for
objects and 1 for functions), and averaged these differences for images with similar and
dissimilar IU maps, and performed an independent samples t-test, which resulted in a
significant difference between the two sets, $t(62) = 2.15$, $P = 0.0357$, Cohen's $d = 0.54$. The
mean difference for the similar IU map group $M = 0.2231$ was larger compared to the dissimilar
IU map group $M = 0.1806$. Smaller values mean better classification, with 95% confidence
intervals of [0.002 0.082]. These results suggest that while the model performs well overall, it
struggles more with images where the task-relevant regions overlap, likely because those
images produce ERPs that were more similar between the two tasks.
388

389
Figure 7. (a) Time by electrode matrices showing time-resolved R2 values between ERP data from each task, but for
images with similar IU maps (left) or dissimilar IU maps (right). Lower values indicate the potential for task related
ERP effects. (b) Summary plot showing averaged R2s at the targeted time points and electrodes. Note the
reduction in mean R2 over time between tasks for images with dissimilar IU maps. (c) Topographic scalp plots
showing between task R2 values at the four targeted time points for stimuli with similar (top) vs dissimilar (bottom)
IU maps.
396

One possible explanation for this difference could be that the images themselves
differed with respect to their physical characteristics. We examined image-based differences
between images that generated similar versus dissimilar IU maps within a tSNE-based image
space (see the Methods section for more detail). No apparent clustering of images with similar
vs dissimilar IU maps was observed. It therefore does not seem that the differences in ERP
similarity between the two tasks can be accounted for by low-level image characteristics (see
Supplementary Figure S1 for more details).
404
405
406   **Discussion**
407
The results of the performance analysis on our brain-guided CNN show that neural responses
generated by identical images with two different tasks could be used to guide a relatively
standard CNN to differentiate between identical sets of images (**Figure 3).** Crucially, not only
could the network learn to differentiate identical images based on task-related neural variance,
but it did so by making differential use of image regions that an independent group of raters
found useful to complete each task. Further, the network was relatively stable across different
learning sessions with different filter weight initializations in terms of both task classification
accuracy, as well as the associated activation map constructions obtained via deconvolution.
Task-relevant feature use emerged relatively later in neural processing (starting at ~244 ms,
Figure 5b). That finding is consistent with previous M/EEG work [45, 9, 46]. For example, our
previous work examined when different task-related features begin to explain unique ERP
variance [9]. However, that work did not attempt to localize the neural responses to task-
relevant regions. Other work has mapped local task-relevant features to neural responses by
creating stimuli where task-relevant information is localized only in specific, non-overlapping
image locations [45]. While this is a powerful inferential aid, real-world scenes contain regions
that are potentially useful across multiple tasks. By contrast, this work addresses those
shortcomings by revealing that image locations that support task demands are prioritized in the
neural responses.
The analysis of the behavioral IU maps revealed, across all of our task prompts and
images, that most of the object-relevant regions of information were broadly distributed with a
slight central concentration, while the function-relevant regions were largely concentrated
around the bottom of the images. Nevertheless, at the individual map level, we found an
approximate bimodal distribution whereby half of our images could be quantified as containing
overlapping task relevant regions. That is, our independent raters found certain regions in
some of our images useful to complete both the object and the function task. The other half of
our images could be classified as having task informative regions that largely did not overlap.
Strikingly, this result predicts differential task-related effects. For example, if the neural data
are separable based on task, ERPs generated by images with similar IU maps should be more
similar compared to ERPs evoked by images with dissimilar IU maps. **Figure 7** shows the results
of that analysis and suggests that when testing for task related effects in neural processing, it is
important to consider the relative overlap between informative regions across tasks. Further,
our image structure analysis (**Supplemental Figure S1**) shows that this relationship cannot be
explained by differences in the structural content of the images. Lastly, not only did the

relative overlap between informative regions across tasks predict task effects in the ERP data,
but it also coincided with the brain-guided network's performance on images with similar IU
maps vs. those with dissimilar IU maps. Specifically, the network struggled more when
differentiating identical images that yielded similar IU maps compared to those with dissimilar
IU maps. To our knowledge, this is the first investigation to report such a relationship and
should be very useful for future work in understanding how behavioral goals in visual
environments influence the neural representation of task relevant information.
This work used neural information to guide the training of a CNN. Unlike other work
that used brain guidance to improve CNN performance [33-42], our goal was to leverage the
localization power of CNNs to provide insight into task-related visual processing differences.
However, future computer vision efforts may be aided by understanding how the human visual
system uses different scene features for various tasks based on the approach presented here.
While the success of our brain-guided CNN opens new and exciting paths for similar
applications in other domains of systems neuroscience, it is not without its limitations. For
example, the neural similarity pooling operation that we used here relies on finding the
smallest distance between an image's neural response and filter outputs within each pooling
region. This can be problematic for noisier datasets where the pattern of neural responses
across images is less stable, thereby making it harder for the network to differentiate images
based on task in any meaningful way. One possible solution would be to incorporate a fitting
procedure within the similarity pooling operation that considers how any given filter responds
across all images in the stimulus set, and then maps the residual between the input image's
response and the fit to the corresponding location within a given pooling region. Then, as with
our current neural similarity pooling operation, find the smallest residual in the pooling region
and map its corresponding filter response to the pooled output image for that filter. Because
the fitting would be relative to all images, the residual would be more stable for each training
iteration. We did pilot that approach with a single brain-guided CNN layer, and found that the
resulting activation maps had less noise and had more gradual variations between regions of
low and high activation. However, because that process requires passing all images through
the layer before the fitting can take place, the compute time grew exponentially as more layers
were added. Another limitation is that, by feeding each layer's output into the next, we are
assuming that the neural sources at time x feed directly (and entirely) into the sources at the
next timepoint $x + \Delta t$. Future developments of this network might handle that by taking into
account predictive signaling between electrodes at different time points (e.g., Granger
causality) to not only select which electrodes to use for brain guidance, but to also facilitate
which (and how many) time points (i.e., convolutional layers) to use. Next, the network was
only trained to differentiate between two tasks, so a more robust test of this type of network
would include more tasks using the same set of images. Lastly, more convolutional and/or fully
connected layers might provide more refined insight into how and when observers make use of
task relevant information. It's also possible that further insights could be gained by using the
neural responses to guide network operations other than at the pooling stage. Nevertheless,
the network reported here was highly successful in differentiating images based on task-driven
neural data, and crucially, made use of the same image regions that human observers found
useful to complete the task.
484

485 **Methods**
486
Apparatus
All stimuli were presented on a 23.6" VIEWPixx/EEG scanning LED-backlight LCD monitor with 1
ms black-to-white pixel response time. Maximum luminance output of the display was 100
cd/m^2, with a frame rate of 120 Hz and resolution of 1920 x 1080 pixels. Single pixels
subtended .0382° of visual angle as viewed from 35 cm. Head position was maintained with an
Applied Science Laboratories (ASL) chin rest.
493
Participants
A total of 36 participants were recruited for this experiment. Of those, nine failed to complete
all four recording sessions and three were excluded for having fewer than 50% valid trials
following artifact rejection. The age of the remaining 24 participants (17 female, 22 right-
handed) ranged from 18-22 (median age = 20). All participants had normal (or corrected to
normal) vision as determined by standard ETDRS acuity charts and were compensated for their
time. This study was reviewed and approved by Colgate University's Institutional Review Board,
and all methods involving human participants were performed in accordance with the
guidelines set forth by that board. All participants gave written informed consent before
participating.
504
Stimuli
Unless noted otherwise, images were selected using the same methods reported in [26].
Specifically, we sampled images from a large database of real-world scenes consisting of 2500
photographs that varied in content from purely natural to purely carpentered (both indoor and
outdoor), with various mixtures of natural/carpentered environments in between [47]. All
images were 512 x 512 pixels (subtending 19.55° visual angle) and converted to grayscale using
the standard weighted sum conversion in MatLab.
For the purposes of stimulus presentation and analysis, all images were calibrated
according to the following procedures. First, each image was fit with a hard-edge circular
window (with a diameter of 512 pixels) whereby all pixels that fell outside of the circular
window were set to zero. Next, each image was converted to an array, I(y), that included only
the pixels that fell within the circular window and were made to possess the same root mean
square (RMS) contrast and mean pixel luminance. Holding RMS contrast and mean luminance
constant is an important step as it ensures that the variation in neural response magnitude
across images is due to structural/semantic variations as opposed to global contrast or
luminance variations across the images.
Root mean square contrast is defined as the standard deviation of all pixel luminance
values divided by the mean of all pixel luminance values. Image arrays were set to have the
same RMS contrast and zero mean using the following operations.
524

525
$$I_{sc} = \frac{1}{2} * \frac{I_{zm}}{\max|I_{zm}|}$$

526   with I_{zm} defined as:

527
$$I_{zm} = I(y) - \left(\frac{1}{Y} \sum_{i=1}^{Y} I(y_i) \right)$$

528 The pixels values of each image array are first normalized to fall between [-.5 .5] with zero
529 mean as follows,

530
$$RMS_{sc} = 2 * \sqrt{\frac{1}{Y-1} \sum_{i=1}^{Y} I_{sc}(y_i)^2}$$

531
We then calculated an RMS scaling factor, $S_{rms} = (2*RMS_t)/RMS_{sc}$, with RMS_t set to a
reasonable target RMS value. By reasonable, we mean a value that did not result in significant
(> 5%) clipping of the resulting pixel values. That value was 0.20 for the images used in the
current study. Finally, each image array was scaled to have an RMS equal to RMS_t and reassign
to I(y) as follows: I(y) = 127*(I_{sc}*S_{rms}). Note that scaling by 127 puts the scaled pixel values of
I(y) back in the original range of I_{zm}.
Stimulus images were selected according to an image state-space sampling procedure as
follows [26]. All images in the database were left in vector form after RMS normalization.
When in array form, each cell constitutes a coordinate in a high-dimensional image state-space
where each coordinate takes on a pixel luminance value ranging from [-127, 127]. An angular
distance matrix was then constructed by calculating the angular distance (in degrees) between
each image array and every other image array as follows:
544

545
$$\theta = arcos \left(\frac{\vec{I_i} \cdot \vec{I_j}}{\|\vec{I_i}\| * \|\vec{I_j}\|} \right) * \frac{180}{\pi}$$

546
From there, the angular distance matrix was projected into a lower dimensional space (2D) via
t-distributed stochastic neighbor embedding (t-SNE) [48]. Projecting the images into this space
enables a general lower dimensional organization of images based on their structural attributes
defined by pixel luminance.
From this set, 80 images were selected by uniformly sampling from the lower
dimensional t-SNE space. Each of the three dimensions was divided into 10 bins, and when
possible, one image was randomly selected from each bin. This procedure ensured that
different regions in our image state-space were represented in the stimulus set. We chose to
use 80 images to have as many images as possible while keeping the overall length of the
recording sessions to a practical limit. All selected images maintained their RMS of .20 (defined
above) but had their mean pixel luminance set to 127 and then fit with a circular linear edge-
ramped window (512-pixel diameter, ramped to the mean pixel luminance) to obscure the
square frame of the images. That step ensures that the contrast changes at the boundaries of
the image were not biased to any particular orientation [49].
561
562 *Assigning Task Targets to Stimuli*
563

Each stimulus image was assigned one object target as well as one function target from a set of
16 functions and 15 objects. The assignments were fixed for each image and did not change
across the entire experiment. Assignments were determined by a preliminary experiment that
asked observers (N=475, recruited on Amazon's Mechanical Turk) to check off objects that
could be found in a scene, or functions that could be performed in the scene from sets of 17
objects and functions, derived from the Scene Attribute Dataset [50]. One hundred participants
ranked each image for both objects and functions, and the most consistently-selected object
and function were used in subsequent experiments.
572
Experimental Procedure
The current study consisted of two behavioral tasks, namely an object identification confidence
task and a function likelihood assessment task. Both tasks were run using the same set of 80
images. The experiment consisted of four recording sessions, with sessions blocked by task
(two sessions for each behavioral task). The order of the task blocks was counter-balanced in
an alternating sequence across participants (that is, participants never completed two identical
task blocks back-to-back). The time to complete each session ranged between 58-70 min, and
the time between sessions varied between two days and one week. Within each session, all 80
stimuli were presented 15 times, resulting in a total of 30 presentations per image over both
recording sessions for each task (stimulus presentation order within each task block was
randomized).
Each trial began with a 500 ms fixation followed by a task cue screen (1000 ms). For the
object task, the prompt took the general form of "How confident are you that there is a X
here?", with X set to a particular object for the up-coming stimulus image. For the function
task, the prompt took the general form of "How likely are you to X here?", with X set to a
particular function for the up-coming stimulus image. Twenty percent of the images (N = 16)
had distractor labels (objects that were not in the image or functions that could not be
performed in the image) as manipulation checks to ensure that the participants made an
honest effort to engage with each task). The cue screen was followed by a variable duration
(500-750 ms) blank mean luminance screen to allow any fixation-driven activity to dissipate.
The blank screen was immediately followed by the stimulus interval (500 ms) that was then
followed by a variable 100-250 ms blank mean luminance screen, followed by a response
screen. The response screen prompted to give a confidence (object task) or likelihood (function
task) rating on a 1-4 scale (1 being least, four being most) using a button box. Response time
was unlimited, but participants were encouraged to respond as quickly as they could.
598
EEG Recording and Processing
All continuous EEGs were recorded in a Faraday chamber using Electrical Geodesics
Incorporated's (MagStim EGI) Geodesic EEG acquisition system (GES 400). All EEGs were
obtained by means of Geodesic Hydrocel sensor nets consisting of a dense array of 128
channels (electrolytic sponges). The online reference was at the vertex (Cz), and the
impedances were maintained below 50 kΩ (EGI amplifiers are high-impedance). All EEG signals
were amplified and sampled at 1000 Hz. The digitized EEG waveforms were first highpass
filtered at a 0.1 Hz cut-off frequency to remove the DC offset, and then lowpass filtered at a 45
Hz cutoff frequency to eliminate 60 Hz line noise.

Continuous EEGs were divided into 600 ms epochs, i.e., 99 ms before stimulus onset and
500 ms following stimulus onset (0 ms). Trials that contained eye movements or eye blinks
during data epochs were excluded from analysis via magnitude thresholding followed by visual
inspection. Additionally, all epochs were subjected to algorithmic artifact rejection whereby
voltages exceeding +/- 100 μV or transients greater than +/- 100 μV were omitted from further
analysis. These trial rejection routines resulted in a median of 19% (range 4% - 28%) of total
trials being rejected across participants for the object task, and a median of 17% (range 2% -
34%) of total trials being rejected across participants for the function task. The difference in
rejection percentages between the two tasks was not statistically significant (paired samples t-
test, t(23) = 0.372, P = 0.7133). Each epoch was then re-referenced offline to the net average,
and baseline-corrected to the last 99 ms of the blank interval that preceded the image interval.
Finally, ERPs were constructed for each participant by averaging the processed epochs across
trials for each valid image at each electrode, resulting in two 128 x 600 x 64 ERP data matrices
for each participant (one matrix per task). Valid images were those with a task cue that was
congruent with the content in the stimulus images – distractor images did not contain any
useful regional information because their contents did not match either of the task cues. The
full dataset (59 GB) is available upon request from the corresponding author.
625
Electrode and Time Point Selection for Brain-Guidance
The primary task of the brain-guided CNN was to differentiate between identical sets of images
based on their neural responses across the two EEG experiment tasks. It is therefore important
that the neural responses from any given electrode and time point for each task be as
uncorrelated as possible. That is, it is crucial to select data that is showing a task-based
difference in the neural response, otherwise, the network would use near identical neural
responses from each task to differentiate between identical sets of images, thereby setting up
the network to fail. To identify which electrodes and time points showed significant task-
related differences, we conducted a time-resolved R^2 analysis, comparing participant averaged
ERPs from the function task to those from the object task on a per-electrode basis to identify
time points and electrodes that differed between tasks. Starting from the stimulus onset and
advancing in 1 ms steps, we used an 11 ms time window centered on each time point. For each
image and task, we calculated the average ERP within the window, producing two 64 x 1
vectors (one for each task). We then computed the R^2 between these vectors, then converted it
to a dissimilarity using 1-Pearson ρ^2 defined below, with subscript *e* denoting the electrode, *i*
indicating a given stimulus, and μ being the mean across all images for each task.
642

$$D_e = 1 - \left(\frac{\sum_{i=1}^{N} (Obj_i - Obj_\mu)(Func_i - Func_\mu)}{\sqrt{\sum_{i=1}^{N} (Obj_i - Obj_\mu)^2 \sum_{i=1}^{N} (Func_i - Func_\mu)^2}} \right)^2$$

644
We chose an 11 ms time window so that peak component variability over small and/or short
time intervals could be captured. Also, we excluded the electrodes immediately around the
ears, on the brow line of the forehead, and cheeks as those electrodes are most susceptible to
noise that, leaving 105 electrodes for the neural dissimilarity analysis. After calculating a

dissimilarity metric, D, for each electrode at each time point, we set a dissimilarity threshold of
0.7, selecting all electrodes with Ds exceeding that value. That threshold was chosen to ensure
that the sphering operation applied to the neural data (explained in the next section) would
provide sphered components that closely resembled the original neural data, as sphering highly
correlated variables often results in sphered components that do not correlate well with the
original variables. Once the electrodes were gathered for each time point, we computed the
average D across these electrodes on a time point-by-time point basis. We then selected the
time points (and corresponding electrodes) with the highest dissimilarity that were separated
by at least 100 ms. This separation was chosen to capture distinct ERP signals while still
covering the full stimulus interval, avoiding the temporal correlation typical of nearby time
points (see **Figure 8** below). Three time points stand out, namely 144 ms (3 electrodes), 244 ms
(12 electrodes), and 402 ms (60 electrodes). Unfortunately, the dissimilarity peak at 144 ms
only had 3 electrodes, so we used the next peak (159 ms), which had 8 electrodes. All of those
time points are relatively late in visual processing, so we selected 64 ms (95 electrodes) as an
example of an early time point that is consistent with the initial processing of visual information
[51].

665
Figure 8. *Dissimilarity analysis results.*

Preparing the Neural Data for Network Guidance
Neural data for each task were selected at four time points (and corresponding electrodes) by
averaging each image's ERP within an 11 ms time window centered on each time point on an
electrode-by-electrode basis and then averaged over electrodes to yield one neural response
per image. This resulted in two 64 x 4 neural response matrices (one for each task), that were
then normalized to the absolute maximum at each time point and within each task. To remove
any shared variance between and within tasks and between time points, we sphered the data
according to all possible task and time point pairs using the zero-phase component algorithm
(ZCA, [52]). All sphered components correlated with their original versions at or above r = 0.90.
It is the sphered components that were used to guide network operations at each convolutional
layer (i.e., one sphered component per image and per task and time point).

Brain-Guided Convolutional Layers

To ease the computational demand on the network, input images were downsampled from 512 x 512 pixels to 128 x 128 pixels, giving an input layer dimensionality of 128 x 128 x 1. To assist in protecting against exploding gradients, the pixel luminance values of the downsampled images were scaled to 1% of their original RMS-contrast normalized range and set to have a mean pixel value of zero. The first convolutional layer received neural responses from the earliest time point (64 ms post-stimulus onset) and consisted of 100 7 x 7 filters (7 x 7 x 100). Each filter was convolved with the input image with a stride of two pixels and a pooling stride of two pixels, resulting in a 32 x 32 response output for each filter (32 x 32 x 100). The filter dimensions and stride lengths were chosen to aid in constructing well-sampled activation maps (discussed in the Results section) [43]. In terms of spatial frequency, a 7 x 7 filter has a frequency range of 18.28 – 36.57 cycles per picture (0.94 – 1.88 cycles per degree when scaled up to the ERP experiment viewing conditions). Brain guidance was incorporated by replacing the traditional max-pooling operation with a 'neural-similarity pooling' operation, applied to the output of the convolution operation. Specifically, for each filter, the output of the convolution between that filter and the image was mapped to a 64 x 64 filter response matrix. A 3 x 3 pooling region was then moved across that response matrix with a stride of two. For each pooling region, the absolute difference between the z-scored filter responses and the neural response was calculated, creating a 3 x 3 matrix of absolute differences. The smallest distance within each pooling region was selected and assigned to a 32 x 32 pooled output matrix for each filter (see **Figure 2** for an illustration). This approach differs from typical max-pooling, as the neural-similarity pooling operation selects filter responses that most closely match the neural response for each image. That is, it identifies the raw filter response in each pool region that best aligns with the neural response. Before being passed to the next layer, this pooled matrix was passed through a leaky rectified linear unit (leaky ReLu) with a slope coefficient of 0.1. The leaky ReLu was chosen to capture both positive and negative neural responses, as ERPs consist of deflections in both directions.

$$f(x) = \begin{cases} 0.1x, & x < 0 \\ x, & x \geq 0 \end{cases}$$

Convolutional layers 2-4 performed the neural-similarity pooling exactly as described for layer 1 (pooling region 3 x 3), with the only exception being that each layer used neural responses from different time points (layer 2 = 159 ms, layer 3 = 244 ms, and layer 4 = 402 ms). Layer 2 consisted of 170 5 x 5 filters (5 x 5 x 170). Each filter was convolved with the output from layer 1 with a stride of one pixel and a pooling stride of one pixel, resulting in a 32 x 32 response output for each filter (32 x 32 x 170). Layer 3 consisted of 170 3 x 3 filters (3 x 3 x 170). Each filter was convolved with the output from layer 2 with a stride of one pixel and a pooling stride of one pixel, resulting in a 32 x 32 response output for each filter (32 x 32 x 170). Finally, layer 4 consisted of 150 3 x 3 filters (3 x 3 x 150). Each filter was convolved with the output from layer 3 with a stride of one pixel and a pooling stride of one pixel, resulting in a 32 x 32 response output for each filter (32 x 32 x 170).

721   The number of filters for each layer was set through preliminary testing to ensure that
722   the overall network accuracy for discriminating between the two tasks was reasonably high (at
723   or above 90%).
724
Fully-Connected Layer and Decision Node
The fully-connected layer consisted of 280 nodes, each performing the standard weighted sum,
with the output passed through a standard sigmoid activation function. The number of fully
connected nodes was determined by preliminary testing. The decision layer consisted of a
single node, using the same weighted sum and activation function as nodes in the fully-
connected layer. Because the network made a binary decision (object task or function task),
only a single output node was necessary.
732
Backpropagation and Deconvolution
Backpropagation for the network followed the typical CNN operations with a few exceptions
based on the simplicity of the network, its task, and to avoid over-correcting filter weights
when the fit was good between any given filter and the neural response. For example, the
decision layer error, E, simply consisted of the difference between the target response (1 =
function task, 0 = object task) and the output of the decision node sigmoid. Each layer had a
different learning rate, ε, to help differentially control the weight adjustments. The specific
learning rates that we used were determined through preliminary testing. To update the
weights in the fully-connected layer, we used the first derivative of the decision node sigmoid,
the output from layer 4, and the first derivative of each fully-connected node's sigmoid to
adjust the weights in the fully-connected layer. This process computed the loss, L, for the layer.
Updating the fully-connected layer weights then followed the usual form: $w_i = w_i + \varepsilon(L*E)$.
Updating the weights in the convolutional layers followed the traditional operations (e.g., [44]),
with the gradient loss from the previous layer being convolved by 180°-rotated filters from the
subsequent layer, and then scaled by the network error along with the first derivative of the
output node's sigmoid to compute the gradient loss for the current layer. The weight
adjustments consisted of scaling the current layer's weights by the gradient loss along with that
layer's input. To prevent any one filter's weights from being over-corrected due to a good fit
with the neural response despite a classification error, the weight update values were further
scaled by the average absolute distance between that filter's response and the neural response.
This meant that if a filter's response was, on average, close to the neural response, the updates
were reduced in proportion to these filter response distances, avoiding excessive corrections.
An additional scalar was added based on the distance between each filter's response (location
specific) and the neural response. Adding that scalar only improved network performance by a
fraction of a percent overall and could be removed. We chose to use it only to maximize the
best possible performance, even if the difference was negligible. Finally, to help control for
gradient explosion, the updated weights were L2-normalized.
To reconstruct the activation maps for each layer, image, and task, we followed the
deconvolution routine of [43]. Briefly, on the forward pass of a given image and corresponding
neural responses, each *trained* convolutional layer of the brain-guided network was linked to a
"switch" operator that un-pooled the pooled matrix, then passed through the leaky ReLu
activation function and filtered with the transpose of that layer's filters. Then, within each

layer, each filter's activation reconstruction was summed with the other reconstructions and
normalized by the maximum activation for each image.
767
Network Training
The brain-guided CNN was trained stochastically, whereby each image was paired with one of
two neural responses (the corresponding participant-averaged responses for the object or
function task). Thus, for each training iteration, 128 images (64 paired with object task neural
data and 64 paired with the function task neural data) were passed through the network. For
each iteration, image order was shuffled to ensure that the network did not learn any particular
pattern of input images. Training was halted when the network reached ~90% task
classification accuracy (at which point the error curve largely leveled off). We opted to use
participant-averaged ERPs due to the impracticality of repeated training runs for each
participant (training this particular network took a considerable amount of time for each
training run). However, we found that each participant's data were excellent predictors of the
averaged set, suggesting that the mean data sets were well representative of each participant's
own data set (see **Supplementary Figure S2**). The code for the network and training routine is
available upon request from the corresponding author.
782
Building the Behavioral Information Utility (IU) Maps
Fifty observers were recruited on Prolific. Each observer viewed each of the 80 images and
were tasked to click with a mouse or track pad the 10 image locations that were most relevant
to the function or object. Each participant completed each task with images and tasks
presented in a random order. Each image had an assigned function and object (see the
Experimental Procedure section) that was written above the scene image. Observers were
limited to desktop and laptop environments for the experiment (i.e., tablet, phone, and other
mobile OS were blocked) to ensure that images were displayed large enough to perform the
task well. Images were programmed to be displayed at 50% the height of each observer's
screen, but because each observer completed the experiment on their own computer, the
actual image size varied across observers. The experiment took an average of 42 minutes to
complete and observers were compensated $12 for their time.
Using the crowd-sourced click data, IU maps were built for each stimulus and task (two
sets of IU maps were constructed). For each image and task, the clicks were aggregated across
participants onto one map. The aggregated clicks were then convolved with a 32x32 pixel
Gaussian kernel and normalized to the maximum so that the values in each IU map ranged from
0 to 1. We chose a 32x32 pixel kernel so as to minimize the overlap between object and
function task-relevant regions, but that was not always possible as detailed in the Results
section.

References

1. Ungerleider, L. G., & Mishkin, M. (1982). Two cortical visual systems. *In D. J. Ingle, M. A. Goodale, & R. J. W. Mansfield (Eds.),* Analysis of visual behavior (pp. 549–586). MIT Press.

2. Milner, A. D., & Goodale, M. A. (2006). *The visual brain in action.* Oxford University Press.

3. Kravitz, D. J., Saleem, K. S., Baker, C. I., & Mishkin, M. (2011). The ventral visual pathway: An expanded neural framework for the processing of object quality. *Trends in Cognitive Sciences, 15*(5), 227–236.

4. DiCarlo, J. J., Zoccolan, D., & Rust, N. C. (2012). How does the brain solve visual object recognition? *Neuron, 73*(3), 415–434.

5. Grill-Spector, K., & Weiner, K. S. (2014). The functional architecture of the ventral visual cortex. *Annual Review of Neuroscience, 37*, 167–188.

6. Groen I. I. A., Silson, E.H., & Baker C. I. (2017). Contributions of low- and high-level properties to neural processing of visual scenes in the human brain. Phil. Trans. R. Soc. B37220160102

7. Serre, T., Oliva, A., & Poggio, T. (2007). A feedforward architecture accounts for rapid categorization. *Proc. Natl. Acad. Sci. U.S.A.,*104 (15) 6424-6429.

8. Cichy RM, Pantazis D, Oliva A. Resolving human object recognition in space and time. Nat Neurosci. 2014 Mar;17(3):455-62.

9. Greene, M. R., & Hansen, B. C. (2020). The influence of object recognition and scene context on visual search in natural scenes. *The Journal of Neuroscience, 40*(17), 3455–3464.

10. Dwivedi, K., Sadiya, S., Balode, M.P. *et al.* (2024). Visual features are processed before navigational affordances in the human brain. *Sci Rep* 14, 5573.

11. Kravitz DJ, Saleem KS, Baker CI, Mishkin M. (2011). A new neural framework for visuospatial processing. Nat Rev Neurosci, 12(4), 217-30.

12. DiCarlo, J. J., Zoccolan, D., & Rust, N. C. (2012). How does the brain solve visual object recognition? *Neuron, 73*(3), 415–434.

13. Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., … & Fei-Fei, L. (2015). ImageNet large scale visual recognition challenge. *International Journal of Computer Vision, 115*(3), 211–252.

14. Cichy, R. M., Khosla, A., Pantazis, D., Torralba, A., & Oliva, A. (2017). Dynamics of scene representations in the human brain revealed by magnetoencephalography and deep neural networks. Neuroimage, 153, 346-358.

853 15. Greene, M. R., & Hansen, B. C. (2018). Shared representations of objects and scenes in
854 human visual cortex. *PLoS Computational Biology, 14*(11), e1006610.
855

856 16. Feldman, N. H., Griffiths, T. L., & Morgan, J. L. (2009). The influence of categories on
857 perception: Explaining the perceptual magnet effect as optimal statistical
858 inference. *Psychological Review, 116*(4), 752–782.
859

860 17. Bonner MF, Epstein RA. Coding of navigational affordances in the human visual system.
861 (2017). Proc Natl Acad Sci U S A., 114(18), 4793-4798.
862

863 18. Hayhoe MM. (2017). Vision and Action. Annu Rev Vis Sci., 3, 389-413.
864

865 19. Harel, A., Nador, J. D., Bonner, M. F., & Epstein, R. A. (2022). Early electrophysiological
866 markers of navigational affordances in scenes. *Journal of Cognitive Neuroscience, 34*(3), 397–
867 410.
868

869 20. Malcolm, G. L., & Henderson, J. M. (2010). Combining top-down processes to guide eye
870 movements during real-world scene search. *Journal of Vision, 10*(2), Article 4.
871

872 21. Wolfe JM, Võ ML, Evans KK, Greene MR. (2011) Visual search in scenes involves selective
873 and nonselective pathways. Trends Cogn Sci., 15(2), 77-84.
874

875 22. Alexander, R. G., & Zelinsky, G. J. (2012). Effects of part-based similarity on visual search:
876 The Frankenbear experiment. *Vision Research, 54,* 20–30.
877

878 23. Wolfe, J. M. (2014). Approaches to visual search: Feature integration theory and guided
879 search. In A. C. Nobre & S. Kastner (Eds.), *The Oxford handbook of attention* (pp. 11–55). Oxford
880 University Press.
881

882 24. Kaiser D, Cichy RM. (2021). Parts and Wholes in Scene Processing. J Cogn Neurosci, 34(1), 4-
883 15.
884

885 25. Zhan, J., Ince, R.A.A., van Rijsbergen, N., & Schyns, P.G. (2019). Dynamic Construction of
886 Reduced Representations in the Brain for Perceptual Decision Behavior, Current Biology, 29(2),
887 319-326.
888

889 26. Hansen BC, Greene MR, Field DJ (2021) Dynamic Electrode-to-Image (DETI) mapping reveals
890 the human brain's spatiotemporal code of visual information. PLoS Comput Biol 17(9):
891 e1009456.
892

893 27. Navalpakkam, V., & Itti, L. (2005). Modeling the influence of task on attention. *Vision
894 Research, 45*(2), 205–231.
895

896 28. Petersen SE, Posner MI. (2012). The attention system of the human brain: 20 years after.
897 Annu Rev Neurosci., 35, 73-89.
898
899 29. Cohen MA, Alvarez GA, Nakayama K, Konkle T. (2017). Visual search for object categories is
900 predicted by the representational architecture of high-level visual cortex. J Neurophysiol.,
901 117(1), 388-402.
902
903 30. Snyder, A.C., Yu, B.M., & Smith, M.A. (2021). A Stable Population Code for Attention in
904 Prefrontal Cortex Leads a Dynamic Attention Code in Visual Cortex Journal of Neuroscience, 41
905 (44) 9163-9176.
906
907 31. Denison, R. N. (2024). Visual temporal attention from perception to computation. *Nature*
908 *Reviews Psychology, 3*(4), 261–274.
909
910 32. Palmieri, H., Carrasco, M. (2024). Task demand mediates the interaction of spatial and
911 temporal attention. *Sci Rep* 14, 9228.
912
913 33. Dapello, J., Kar, K., Schrimpf, M., Geary, R.B., Ferguson, M., Cox, D.D., & and DiCarlo, J.J.
914 (2023). Aligning Model and Macaque Inferior Temporal Cortex Representations Improves
915 Model-to-Human Behavioral Alignment and Adversarial Robustness, The Eleventh International
916 Conference on Learning Representations.
917
918 34. Federer, C., Xu, H., Fyshe, A., & Zylberberg, J. (2020). Improved object recognition using
919 neural networks trained to mimic the brain's statistical properties, Neural Networks,131, 103-
920 114.
921
922 35. Hansen, B.C., *Gephart, I.S.H.*, *Gobo, V.E.*, Greene, M.R., & Field, D.J. (2022). Uncovering
923 the spatiotemporal dynamics of goal-driven efficient coding with a brain-supervised sparse
924 coding network. Cognitive Computational Neuroscience Conference.
925
926 36. Li, Z., Brendel, W., Walker, E.Y., Cobos, E., Muhammad, T. Reimer, J., et al. (2019). Learning
927 From Brains How to Regularize Machines, arXiv preprint, 1911.05072.
928
929 37. Z Lu, Y Wang, JD Golomb (2024). Achieving More Human Brain-Like Vision via Human EEG
930 Representational Alignment. arXiv preprint, 2401.17231.
931
932 38. Pirlot, C., Gerum, R.C., Efird, C., Zylberberg, J., & Fyshe, A. (2022). Improving the Accuracy
933 and Robustness of CNNs Using a Deep CCA Neural Data Regularizer. arXiv preprint, 2209.02582.
934
935 39. Safarani, S., Nix, A., Willeke, K., Cadena, S.A., Restivo, K. Denfield, G., et al. (2021). Towards
936 robust vision by multi-task learning on monkey visual cortex. arXiv preprint, 2107.14344
937
40. Shao, Z., Ma, L., Li, B., Beck, D.M. (2024). Leveraging the Human Ventral Visual Stream to
Improve Neural Network Robustness. arXiv preprint, 2405.02564.

41. Spampinato, C., Palazzo, S., Kavasidis, I., Giordano, D., Souly, N., & Shah, M. (2017). Deep
Learning Human Mind for Automated Visual Classification, *IEEE Conference on Computer Vision*
and Pattern Recognition (CVPR), Honolulu, HI, USA, 4503-4511.

42. Quan, S., Yan, J., Guo, K., Zheng, Y., Dong, M., & Liang, J. (2024).
Multimodal contrastive learning for brain–machine fusion: From brain-in-the-loop modeling to
brain-out-of-the-loop application, Information Fusion,110,102447.

43. Zeiler, M.D., Fergus, R. (2014). Visualizing and Understanding Convolutional Networks. In:
Fleet, D., Pajdla, T., Schiele, B., Tuytelaars, T. (eds) Computer Vision – ECCV 2014. ECCV 2014.
Lecture Notes in Computer Science, vol 8689.

44. Krizhevsky, A., Sutskever, I. & Hinton, G.E. (2012). ImageNet Classification with Deep
Convolutional Neural Networks. dvances in Neural Information Processing Systems 25 (NIPS
2012).

45. Duan, Y., Zhan, J., Gross, J., Ince, R.A.A., Schyns, P.G. (2024). Pre-frontal cortex guides
dimension-reducing transformations in the occipito-ventral pathway for categorization
behaviors. Current Biology, 34, 3392-3404.

46. Greene, M.R. & Rohan, A. (in press) The brain prioritizes the basic level of object category
abstraction. Scientific Reports.

47. Hansen, B.C., Field, D.J., Greene, M.R., *Olson, C.*, & Miskovic, V. (2019). Towards a state-
space geometry of neural responses to natural scenes: A steady-state approach. NeuroImage,
201, 1-18.

48. van der Maaten, L. J. P., & Hinton, G. E. (2008). Visualizing High-Dimensional Data Using t-
SNE. Journal of Machine Learning Research, 9, 2579-2605.

49. Hansen, B.C. & Essock, E.A. (2004). A horizontal bias in human visual processing of
orientation and its correspondence to the structural components of natural scenes. Journal of
Vision, 4, 1044-1060.

50. Patterson, G., Xu, C., Su, H., & Hays, J. (2014). The SUN Attribute Database: Beyond
Categories for Deeper Scene Understanding. International Journal of Computer Vision, Volume
108, 59 - 81.

51. Hansen, B.C., Haun, A.M., Johnson, A.P., & Ellemberg, D. (2016). On the Differentiation of
Foveal and Peripheral Early Visual Evoked Potentials. Brain Topography, 29, 506-514.

52. Kessy, A., Lewin, A., & Strimmer, K. (2015). Optimal Whitening and Decorrelation. The
American Statistician, 72, 309-314.

Acknowledgements

Thank you to Isabel Gephart, Tori Gobo, and Harrison Howe for their help with data collection, and to our funding sources: James S. McDonnell Foundation grant (220020430) to BCH; National Science Foundation grant (1736394) to BCH and MRG.

Data Availability Statement

All EEG data files, IU maps, and network code are available upon request from the corresponding author.