Simple controls exceed best deep learning algorithms and reveal foundation model effectiveness for predicting genetic perturbations

Daniel R. Wong[1*], Abby S. Hill[1], Robert Moccia[1]

1. Machine Learning and Computational Sciences, Pfizer Worldwide Research Development and Medical, 610 Main Street, Cambridge, Massachusetts 02139, USA

* correspondence: daniel.wong@pfizer.com

Abstract

Modeling genetic perturbations and their effect on the transcriptome is a key area of pharmaceutical research. Due to the complexity of the transcriptome, there has been much excitement and development in deep learning (DL) because of its ability to model complex relationships. In particular, the transformer-based foundation model paradigm emerged as the gold-standard of predicting post-perturbation responses. However, understanding these increasingly complex models and evaluating their practical utility is lacking, along with simple but appropriate benchmarks to compare predictive methods. Here, we present a simple baseline method that outperforms both state of the art (SOTA) in DL and other proposed simpler neural architectures, setting a necessary benchmark to evaluate in the field of post-perturbation prediction. We also elucidate the utility of foundation models for the task of post-perturbation prediction via generalizable fine-tuning experiments that can be translated to different applications of transformer-based foundation models to tasks of interest. Furthermore, we provide a corrected version of a popular dataset used for benchmarking perturbation prediction models. Our hope is that this work will properly contextualize further development of DL models in the perturbation space with necessary control procedures.

Introduction

Understanding the phenotypic effects of genetic perturbations is a fundamental area of research in biology[1,2]. Due to the complex and interconnected circuitry of the human genome[3], understanding perturbational effects and the repercussions this can have on other genes is a difficult task. Perturb-seq[4] emerged as a tool to aid this discovery effort by measuring complex post-perturbation transcription profiles. This can be done at scale, facilitating the surge of data in the single-cell discipline[5–7]. Knowing what exact transcriptional changes result from different perturbations would be pivotal for both understanding human biology and progressing drug discovery. Since systematically perturbing genes can be an expensive and time-consuming endeavor, the idea of *in-silico*[8,9] modeling and prediction becomes an attractive means of cost-efficient hypothesis generation. Hence, there have been a flurry of computational methods and especially DL ones to address this unmet need[1].

Transformer-based models[10] have captivated much of recent scientific efforts in a broad range of fields[11–14]. As excitement around large language model (LLM) success in Natural Language Processing grows[15], so too do efforts of applying core concepts of LLMs to the "language" of biology[16–20]. Indeed the idea of "foundation models"[21] is of particular excitement. Key to the idea of foundation models is the notion that pre-training on large amounts of data can yield model weights that capture foundational knowledge of the domain on which the model was trained. For single-cell biology, this can be a foundational understanding of complex gene networks learnable via self-supervision[22]. These foundation models can then be fine-tuned to adapt to related tasks, such as post-perturbation prediction. The promise is that foundational knowledge of fundamental biology can even bolster generalization to related tasks and new data via fine-tuning on much smaller datasets than the large corpus on which the foundation model was trained[21,23]. The prospect of

potentially overcoming small data regimes via foundation models would indeed be a paradigm shift, especially in the field of computational biology and pharmaceutical research where data sets are often small, siloed[24,25], and expensive to produce. Practically evaluating and understanding these exciting prospects in pharmaceutical use cases will be of great importance in advancing AI-driven drug discovery.

As a result of the excitement around foundation models in biology, there has been a large uptake of studies and methods that model single-cell biology via transformers[23,26–31]. With rising excitement and rapid development of new studies and methods, rigorous evaluation and proper attention needs to be given to understanding the performance and inner-workings of these black-box models, their limitations, and the biological context in which they can be most effective. Furthermore, as research in this area grows, we must standardize metrics and common-sense benchmarks to evaluate new methods[32–35].

For the task of directly predicting the post-perturbation transcriptome, two DL methods achieved SOTA performance. The first is a graph-based learning method called GEARS[36]. The second is a transformer-based foundation model called scGPT[27]. In this study, we evaluate these two methods and compare them to a much simpler method that achieves SOTA performance, necessitating the need for more standard benchmarking. We also evaluate the prospect of foundation weights and the transformer architecture for improving post-perturbation prediction performance. Through this study we hope to inform further model development for predicting single-cell perturbation responses.

Results

To evaluate the utility of the leading DL methods for the post-perturbation prediction task, we analyzed their performance on three Perturb-seq datasets: Adamson[37], Norman[38], and Replogle K562 Essential[39] (Methods). Due to the ease of data loading, many studies[27,28,34–36] have recently used the ready-made datasets provided by the GEARS[36] repository for training and evaluating models. However, for the popular Adamson dataset, which consists of three independent experiments, we addressed mistakes in GEARS's labeling of this dataset and provide a corrected version (Table 1). We took the largest of the three constituent experiments, which focuses on the unfolded protein response, and denoted this as the "Corrected Adamson UPR" dataset, which we use for our main analyses (Methods). We fine-tuned a pre-trained scGPT Human model[27] using the default parameters that the authors provided for fine-tuning on Perturb-seq data. We also trained GEARS using default parameters. For evaluating prediction of the transcriptome for held-out perturbations, Roohani et al.[36] proposed measuring the Pearson correlation between the actual and predicted expression. As a further metric, Pearson correlation can be computed over just the top 20 differentially expressed (DE) genes for a perturbation (denoted Pearson DE). Cui et al.[27] further adapted the Pearson and Pearson DE scores by subtracting control expression to get a more granular metric that measures similarity between differences called Pearson delta (PD). Similarly, this can be computed for just the top 20 differentially expressed genes and is denoted as Pearson DE Delta (PDED) (Methods). Supplemental Figure 1 provides a pictorial illustration of the different standard metrics. Since delta metrics provide a more informative readout of transcriptional changes[27], we focus our analyses on these scores.

CRISPR-informed mean is a SOTA predictor.
As a simple competitive method for predicting the effects of held-out perturbations on transcriptomic expression, we calculated the mean expression for each gene over the perturbed cells in the training set and stipulated this as a prediction for the test set. It is important to note that the training set perturbations were completely disjoint from the test set perturbations. We denote this model as the "mean model" (Methods). For the PD metric, the mean model outperformed GEARS for all datasets (mean absolute distance (MAD) = 0.07) and outperformed scGPT for all datasets (MAD = 0.10) (Figure 1). For the PDED metric, the mean model exceeded GEARS for 2/3 datasets (MAD = 0.07 across all datasets), while scGPT outperformed the mean

model for 2/3 datasets (MAD = 0.06) (Figure 1). Similarly, mean as a superior predictor to GEARS and competitive with a different LLM is reported by Märtens et al.[40] for the Replogle dataset.

From a visual representation of the top 20 differentially expressed genes across perturbations on which scGPT excelled with the highest PDED scores (Figure 1B), we observe why the mean expression of perturbed cells is a competitive predictor: a single perturbation with target=T does not induce much change in gene expression of cells with target=T (denoted $cells_{target=T}$) relative to the expression of all other perturbed cells with target other than T (denoted $cells_{target≠T}$) (Figure 1C). Hence, simply predicting the average of perturbed $cells_{target≠T}$ results in a profile similar to the average over $cells_{target=T}$ (the ground truth). For the highly performant perturbations in Figure 1B, the distribution of T's expression in $cells_{target=T}$ is dissimilar to the distribution of T's expression in all other perturbed $cells_{target≠T}$. In contrast, $cells_{target=T}$ and all other perturbed $cells_{target≠T}$ have similar distributions for DE genes other than T. Quantifying this observation with the Wasserstein distance across all perturbations, we found that this trend held for both CRISPRi datasets (Adamson and Replogle K562 Essential) and (to a lesser extent) for the CRISPRa Norman dataset (Figure 1D).

Since predicting expression of the target gene is trivial for an effective CRISPRi experiment, we constructed a stronger predictor that exploits this biological knowledge. As a more informed but simple method, we implemented a model we denote as the "CRISPR-informed mean model" that leverages prior information about Perturb-seq and how CRISPRi should reduce transcriptomic expression to near 0 and how CRISPRa should enhance expression. This model predicts the mean of all perturbed cells in the training set for all genes except for the target gene T. For CRISPRi the model predicts 0 expression for T. For CRISPRa the model doubles the training set's mean expression of T and stipulates this as its prediction for T (Methods). Since CRISPRi in practice hardly eliminates expression in full[41] and CRISPRa has a wide range of enhancement based on the biological context[42], this model is an overly simplistic approximation. However, this simple model that leverages known biological priors resulted in SOTA performance (Figure 1A). For the PD metric, the CRISPR-informed model outperformed both GEARS (MAD = 0.09) and scGPT (MAD = 0.11) for all three datasets. For the PDED metric, the CRISPR-informed model outperformed on GEARS on 2/3 datasets (MAD = 0.13) and outperformed or was equivalent to scGPT (MAD = 0.03) on all datasets. For the Norman dataset, which used CRISPRa, the CRISPR-informed model lagged slightly behind GEARS (PDED difference = 0.03) and was near equivalent with scGPT (PDED difference = 0.002).

To help standardize the field of perturbational modeling, recent work from Wu et al.[34] proposed other simple neural baseline models by which to measure new ML methods: Linear Additive, Latent Additive, and Decoder Only. These models utilized simple feed-forward neural architectures. We compared CRISPR-informed mean to these other models and found that CRISPR-informed mean was more performant than all other simple neural models for all datasets (Figure 1A). We also assessed performance of all models using the rank metric, a new metric proposed by Wu et al.[34] for assessing post-perturbation prediction that focuses on triaging perturbations (Figure 1E). We found similar results, with CRISPR-informed mean surpassing all DL models for all datasets. Rank improvement ranged from 4.7-213.9x better than GEARS and 3.9-155.4x better than scGPT depending on the dataset. CRISPR-informed mean also had substantially better rank than all other simple neural baseline models for all datasets.

Neither foundation weights nor transformer attention provide a competitive advantage
Along with establishing proper benchmarks, it is important to understand the feasibility of foundation models transferring learned knowledge derived from pre-training into improving related tasks[21]. Even more important than this is a general framework that can test this feasibility for the sake of assessing future model development. To determine whether the single-cell foundation model weights could aid with the related post-perturbation prediction task, we compared a fully fine-tuned scGPT model, which had all foundation weights loaded from the Human CP model, to different fine-tuned scGPT models that selectively withheld different

foundation weights prior to fine-tuning (Figure 2A). For the first weight-loading permutation, we trained a model that had an identical architecture to the fully fine-tuned scGPT model but initialized with random weights instead of leveraging any pre-trained weights (scGPT no-pretraining). We found that the metrics on the held-out test set were near identical across datasets, with no noticeable difference in performance between the fully fine-tuned foundation model and the model trained from random weight initialization. The average PD difference across all datasets between the fully fine-tuned model and scGPT no-pretraining was only 0.01 (Figure 2B). For PDED, this average difference was only 0.02.

For the second weight-loading permutation, we loaded all the foundation weights minus the learned encoder weights (withholding the learned gene embedding values and the expression encoder). We observed an average PD difference of 0.03, and an average PDED difference of 0.007. For the last permutation, we loaded all the foundation weights minus the transformer weights. The self-attention mechanism, which is the key innovation that defines transformers[10], is completely contained within this transformer block. A similar trend held, with an average PD difference of 0.008, and an average PDED difference of 0.004. scGPT with a randomly initialized transformer did slightly better than the fully fine-tuned model on average. As an additional experiment, we ensured the persistence of foundation weights by fine-tuning the pre-trained scGPT foundation model using a popular alternative to full fine-tuning for LLMs called Low Rank Adaptation (LoRa)[43], which relies on freezing the foundation weights and learning rank decomposition matrices. We found that the LoRa models slightly underperformed against the fully fine-tuned models (Supplemental Figure 2), which seems consistent with LoRa applied in other contexts[44,45].

To answer the question of whether the transformer architecture provides a competitive advantage over simpler architectures, we trained a competing model that is identical to scGPT, but without the transformer encoder (denoted as "Simple Affine", Figure 3A). After training the Simple Affine model using random weight initialization, we found that this model was competitive with the scGPT model without pre-training (PD MAD = 0.03, PDED MAD = 0.02) indicating that the transformer architecture adds little utility over a simpler architecture for post-perturbation prediction (Figure 3B). Despite having similar performance results, scGPT trained 19-20x slower than Simple Affine depending on the dataset (Figure 3C) and was about 1.6x the size of Simple Affine (Figure 3D).

For the sake of consistency with other studies, we also report the corresponding results when we trained models on the GEARS version of the Adamson dataset (Supplemental Figure 3). We also report results when we trained models on the entirety of the corrected Adamson dataset, utilizing all three of its constituent experiments (Supplemental Figure 4).

Discussion

Predicting the post-perturbation transcriptome is a difficult task that has many opportunities for further development. At least for this task, current DL and foundation models do not yet demonstrate meaningful improvement over simple but inadequate methods. As new computational models are being developed, there must be an adoption of standard benchmarks and methods like CRISPR-informed mean to properly assess new methods. Although a SOTA predictor, a CRISPR-informed mean is not sufficient for most drug discovery use-cases because it does not contextualize gene to gene interactions, cannot be used in zero-shot settings because different datasets often have different means, and cannot possibly model nuanced changes in expression. This sort of baseline model cannot be applied to experiments where the target is unknown, which is common in drug discovery settings especially with small molecule perturbations. Since Perturb-seq is a destructive process and cannot result in true pairings between pre and post perturbation cells[4], predicting the post-perturbation transcriptome is innately a prediction of a statistical distribution. This fact, coupled with the fact that CRISPR perturbations result in subtle and minimal transcriptional changes across the entire

transcriptome (as evident by high Pearson correlations between $cells_{target=T}$ and $cells_{target≠T}$, Figure 1C), reinforces how statistical baselines like mean (and related but more biologically-sensible versions of mean) are appropriate metrics that need to be included in all post-perturbation prediction benchmarks. Despite being similar, the CRISPR-informed mean model often substantially outperformed the standard mean model across all datasets for rank and Pearson metrics (Figure 1A, 1E), necessitating its inclusion in all future benchmarking. This also reveals the sensitivity of current metrics to changes in prediction of just one or two genes, which is essential for a data type in which expression is not that differentiable between perturbations. Models that are to exceed mean or variants of it must also be sensitive enough to detect and learn from subtle transcriptional changes, while also being general enough to reflect universal gene relationships. For the fundamental question of how perturbing one gene affects other genes, any prospective model that underperforms against this simple model, which has no possibility of reflecting gene to gene interactions, cannot be regarded with high confidence. Hence CRISPR-informed mean can serve as a benchmark to inform whether any new models developed can be of practical use in discerning subtle changes in biology.

We appreciate the many community efforts towards increased standardization and benchmarking, such as the simple neural models presented by Wu et al[34]. The underlying themes of such work are commendable for improving the field of perturbation modeling via standardized benchmarks and reproducible science. Since CRISPR-informed mean is both more performant than these neural baseline models (Figure 1A) and easier to implement, we advocate for the adoption of CRISPR-informed mean as the simplest and most performant benchmark for post-perturbation prediction tasks over all DL and non-DL baselines we studied. As new proposed ML methods get increasingly more complex, we must ensure that such designs merit the extra complexity, and right-size their performance with interpretable and sensible baselines. We expect that leveraging known biology directly in model development beyond the simplistic design of CRISPR-informed mean will be an avenue of further research. As important as having standardized model benchmarks, standardized datasets are just as essential for furthering community development of perturbation models. By providing a corrected version of a popular dataset used by the ML community, we hope to avoid any future analyses based off erroneous data labeling, encourage greater scrutiny for pre-processing data and checking the work of others, and facilitate easy adoption of a useful dataset ready for ML analyses.

The idea of attention is perhaps a promising solution to complex gene to gene relationships. However, as with most transformer-based models, copious and diverse training data is required, for which Perturb-seq may not currently have enough to model complex post-perturbation responses[6]. Hence, as important as standardized benchmarking and competing models are, so too is the need for the generation of diverse, large perturbational datasets if we are to leverage the full utility of transformer models and replicate their high performance in the NLP space fueled by large datasets[46]. Furthermore, as more investigation continues in developing transformer-based foundation models for application in the single-cell space, proper attention controls like the ones demonstrated in Figure 2 are also needed to assess whether these foundation models can truly translate foundational biological knowledge to pertinent tasks of interest. For this specific task of post-perturbation prediction, if the foundation model had proper gene-to-gene attention, then it was not advantageous over simpler models without self-attention. If the proper attention was not present to begin with, then it certainly was not learned during fine-tuning (such that it could substantially benefit performance compared to simpler models), nor would we expect it to be robustly learned given the small dataset sizes. The control experiments we studied here can be applied in general to various use cases of fine-tuning large foundation models. These controls will be invaluable in assessing if such models can provide foundational knowledge for performance improvement of downstream tasks. Perhaps these should be standard practices and sanity checks whenever one proposes a new foundation model advertising increased utility to related tasks. Both procedures of withholding foundation weights prior to fine-tuning and stripping architectures of their attention mechanisms should drastically reduce performance if a model is indeed properly translating learned foundational knowledge. Even though the transformer-based foundation models underperformed

simpler models, it is worth noting that transformer-based models may yield both better gene correlations across perturbations and better PD scores for perturbations across genes compared to non-attention based (but otherwise equivalent) model architectures. This advantage may be slight with magnitude varying by dataset and by whether pre-training was employed (Supplemental Figure 5). This provides a more optimistic but tempered outlook on the promise of transformers and large pretraining applied to single cell perturbation modeling.

Since larger models tend to require more data to perform well and avoid overfitting[46], it is essential to check if simpler architectures can deliver similar performance while being more efficient (Figure 3), especially in a data-sparse field like Perturb-seq. If transformers are employed, we must ensure that whatever learned self-attention merits the extra complexity and compute costs. Since data is expensive to generate, another opportunity for improved performance is to leverage known biological knowledge directly into modeling. As observed with the large performance gains of CRISPR-informed mean over simple mean, introducing biological priors can be a small but beneficial modification. Foundation models also present a similar opportunity of injecting known biology, but we need not forego other simpler ways to leverage biological knowledge in computational models. We imagine that a combination of both would be the most advantageous, necessitating close interdisciplinary collaboration between computer scientists and biologists to achieve fundamental understanding of foundation models and ways they can be adapted to the biological domain.

In conclusion, we present three examples of simple controls: CRISPR-informed mean, selective withholding of foundation weights prior to fine-tuning, and removal of self-attention. Collectively, these controls set new gold standards for performance, shed light on the current state of the field, and provide proper checks for the further development of computational models applied to single-cell biology. We also hope that our work correcting a popular dataset would serve as a case study for promoting heightened attention towards data preprocessing for ML training. Although we are optimistic about the potential for DL and foundation models to transform perturbational analyses in single-cell biology, we advocate for the adoption of similar controls and a deeper understanding of increasingly complex models.

Methods

Dataset Curation

We downloaded the GEARS Adamson, Norman, and Replogle K562 Essential datasets from the Harvard Dataverse using the GEARS interface in June 2024. For the Replogle K562 Essential dataset, we filtered out cells$_{target=T}$ for all T that was not present in the transcriptomic readout.

We also provide the Corrected Adamson dataset. Briefly, the original pre-processing in the GEARS repository contained perturbed cells mislabeled as control cells. We downloaded the original source data from the NCBI Gene Expression Omnibus (GSE90546) to generate AnnData files for each of the three experiments included in the submission. The cell metadata was then compared back to what was documented in the curation of the same dataset provided by the GEARS authors. This revealed a substantial number of cells where the condition label disagreed. Many of these mismatches were the result of cells mislabeled as "ctrl" (i.e. control) in GEARS, but with gene perturbations documented in the cell_identities.csv files provided in the original Adamson et al. paper[37]. We corrected the labels of these cells mislabeled as control and created a new AnnData object for release. See https://github.com/pfizer-opensource/perturb_seq/tree/main/dataset_correction/ for all source code used to generate the corrected dataset. All datasets and URLs are provided in Table 1.

Dataset	URL

Corrected Adamson	https://zenodo.org/uploads/14337872
GEARS Adamson (Deprecated)	https://dataverse.harvard.edu/api/access/datafile/6154417
Norman	https://dataverse.harvard.edu/api/access/datafile/6154020
Replogle K562 Essential	https://dataverse.harvard.edu/api/access/datafile/7458695

Table 1: dataset locations.

Dataset Splitting

For all datasets, we constructed the training, validation, and test sets such that any unique perturbation was randomly assigned to only one of the sets. Dataset sizes and perturbation counts are shown in Supplemental Figure 6. Some perturbations in the Norman dataset utilized combinations of multiple genes (e.g. a single perturbation could have multiple gene targets A and B for A≠B). Combination perturbations are counted as unique perturbations and are each only present in one of the three sets.

DE Gene Selection

Selection of DE genes was identical to the methods used in Cui et al.[27] and Roohani et al.[36] For a perturbation P, we used scanpy's rank_genes_groups function grouped by the perturbation condition. We used all control cells in the dataset as the reference for the t-test. We performed DE gene selection independently for each perturbation.

Mean models

The mean model computed the mean expression of every gene across all the perturbed cells in the training set. The model returned the mean vector m as its prediction for all cells regardless of the query perturbation.

E_{ij} = expression of cell i for gene j
C_p = set of perturbed cells in the training set
m_j = value for gene j in mean vector

$$m_j = \frac{\sum_{\forall i \in C_p} E_{ij}}{|C_p|}$$

For the CRISPR-informed mean model, the model returned m as its prediction as defined by the following:

t = target gene
if CRISPRi:

$$m_t = 0$$

$$m_{j \neq t} = \frac{\sum_{\forall i \in C_p} E_{ij}}{|C_p|}$$

if CRISPRa:

$$m_t = 2 \times \frac{\sum_{\forall i \in C_p} E_{it}}{|C_p|}$$

$$m_{j \neq t} = \frac{\sum_{\forall i \in C_p} E_{ij}}{|C_p|}$$

DL Models

We trained The GEARS model (version = 0.1.2) using the default hyperparameters presented in the original study, a batch size of 64 cells, and 20 epochs of training. We trained scGPT (version = 0.2.1) fully fine-tuned by loading the published Human CP foundation model weights and fine-tuning with the same hyperparameters and setup as the original study's fine-tuning on Perturb-seq data: batch size of 64, 15

epochs, learning rate of 0.0001, embedding size of 512, 12 transformer blocks, and 8 attention heads. For the scGPT model trained with random weight initialization (Figure 2), we did not load the pre-trained Human CP foundation weights and instead randomly initialized all model weights using Pytorch's default weight instantiation for all weights in the model. We applied the same training procedure and hyperparameters as scGPT fully fine-tuned. For the various models that selectively loaded subsets of the pre-trained foundation weights from Human CP and initialized the rest at random (Figure 2), we also applied the same training procedure as scGPT fully fine-tuned. For all DL models, we trained 10 independent models from 10 different random initializations and kept the train-validation-test split constant across all models. We selected the final model weight for a given training run according to the default scheme for each method as follows. For scGPT, we selected the model weights that resulted in the highest Pearson correlation over all genes in the validation set. For GEARS, we selected the model weights that resulted in the lowest mean squared error over DE genes. We trained all models using a single Nvidia H100 GPU.

Training other simple neural baseline models

For the simple baseline neural models presented by Wu et al.[34] (Linear Additive, Latent Additive, and Decoder Only) we trained these models using the default hyperparameters, a batch size of 64, and 15 epochs. We used the same training, validation, and test sets as the DL models. During a training run, we selected the model weights according to the default validation selection by choosing the ones that had the lowest mean squared error loss between predicted and actual expression over the validation set.

Performance Metrics

Roohani et al.[36] and Cui et al.[27] collectively proposed four Pearson metrics for assessing how well the post-perturbation transcriptome can be predicted. They can be described as follows:

t = target gene

C_c = set of control cells

C_t = set of perturbed cells$_{target=t}$

G = set of all genes in the transcriptome

G_{DE_c} = set of 20 top differentially expressed genes for C_c

G_{DE_t} = set of 20 top differentially expressed genes for C_t

E_{ij} = actual expression of cell i for gene j

$\hat{E}_{ij}$ = predicted expression of cell i for gene j

C_{mean} = mean of control cells (all genes) $= \frac{\sum_{\forall i \in C_c, \forall j \in G} E_{ij}}{|C_c|}$

C_{mean_DE} = mean of control cells (just DE genes) $= \frac{\sum_{\forall i \in C_c, \forall j \in G_{DE\_c}} E_{ij}}{|C_c|}$

y_t = average of true expressions for C_t (all genes) $= \frac{\sum_{\forall i \in C_t, \forall j \in G} E_{ij}}{|C_t|}$

$\hat{y}_t$ = average of predictions for C_t (all genes) $= \frac{\sum_{\forall i \in C_t, \forall j \in G} \hat{E}_{ij}}{|C_t|}$

y_{t_DE} = average of true expressions for C_t (just DE genes) $= \frac{\sum_{\forall i \in C_t, \forall j \in G_{DE\_t}} E_{ij}}{|C_t|}$

$\hat{y}_{t\_DE}$ = average of predictions for C_t (just DE genes) $= \frac{\sum_{\forall i \in C_t, \forall j \in G_{DE\_t}} \hat{E}_{ij}}{|C_t|}$

Pearson(t) = Pearson correlation($\hat{y}_t$, y_t)
Pearson DE(t) = Pearson correlation($\hat{y}_{t\_DE}$, y_{t_DE})
Pearson Delta(t) = Pearson correlation($\hat{y}_t$ - C_{mean}, y_t - C_{mean})
Pearson DE Delta(t) = Pearson correlation($\hat{y}_{t\_DE}$ - C_{mean_DE}, y_{t_DE} - C_{mean_DE})

For summary Pearson metrics reported in the Results section, we averaged the Pearson scores over every target:

P = the set of all perturbations

$$\text{Summary Pearson Metric} = \frac{\sum_{\forall t \in P} Pearson\ Metric(t)}{|P|}$$

For the rank metric[34], the rank score of a perturbation with target=t is calculated as the index of the average prediction for t in a sorted list of all average predictions for all perturbations (including target=t). The list is sorted from highest cosine similarity (to the actual average expression of cells with target=t) at the lowest index to lowest cosine similarity at the highest index. Lower ranks indicate better prediction, with a perfect prediction having rank = 0.0 and expectation from random having rank = 0.5.

Data and Code Availability
All datasets are public and can be found at the links provided in Table 1.
All source code is available at: https://github.com/pfizer-opensource/perturb_seq

Conflicts of Interest
There are no conflicts of interest to declare.

Figures

Figure 1: CRISPR-informed mean as SOTA predictor.

(a) Performance bar charts on held-out test set for different models. Error bars span plus and minus one standard deviation of 10 independently trained models applied to the same test set.

(b) Boxplots of top 20 DE genes for a subset of scGPT's high performing held-out perturbation conditions for each dataset. Target gene T is boxed in red when T is among the top 20 DE genes. The title of each plot denotes the dataset, perturbation condition, and scGPT's Pearson DE score for predicting the expression of

$\text{cells}_{\text{target}=T}$. In the figure legend "T≠condition" denotes all perturbed $\text{cells}_{\text{target}\neq T}$ in the dataset. "T=condition" denotes all $\text{cells}_{\text{target}=T}$.

(c) Boxplots of Pearson correlations between average expression of $\text{cells}_{\text{target}=T}$ and average expression of perturbed $\text{cells}_{\text{target}\neq T}$ repeated over each target T in the whole dataset. Pearson correlation was calculated over all genes for all perturbations in the dataset.

(d) Boxplots of Wasserstein distances. Left: boxplots of Wasserstein distances between (1) expression of T in $\text{cells}_{\text{target}=T}$ and (2) expression of T in perturbed $\text{cells}_{\text{target}\neq T}$. Right: boxplots of Wasserstein distances $\forall$ gene $D \neq T \in$ DE genes between (1) expression of D in $\text{cells}_{\text{target}=T}$ and (2) expression of D in perturbed $\text{cells}_{\text{target}\neq T}$. Boxplots are computed over all perturbations in the dataset.

(e) Rank comparisons between different methods over the held-out perturbation test set. A rank of 0.0 indicates a perfect score, and a rank of 0.5 is the expected score from a random prediction. For held-out perturbation with target=T, the reference gene expression used to compute rank was the average of the ground truth expression of $\text{cells}_{\text{target}=T}$ over all genes. Since, the prediction of the mean model is the same for all perturbations, the cosine similarity to reference is the same for all perturbations and results in a random rank. For each model type, we used the best-performing model from the ten independently trained models that achieved the highest PDED performance on the test set.

a

b

Figure 2: Performance of weight and architecture permutations.

(a) scGPT model architecture for the Perturb-seq task. Here we denote 3 different ways to selectively use the foundation weights. (1) No-pretraining, i.e. not using them at all and initializing all weights randomly (2) loading the foundation input encoder weights and initializing al other weights randomly and (3) loading the foundation transformer encoder weights and initializing all other weights randomly.

(b) Performance bar charts on held-out test set for different baseline models. Error bars span plus and minus one standard deviation of 10 independently trained models.

Figure 3: Simple Affine model is competitive with transformer-based model.
(a) Architecture of the Simple Affine model.
(b) Performance bar charts on held-out test set for different baseline models. Error bars span plus and minus one standard deviation of 10 independently trained models.
(c) Bar charts comparing Simple Affine and scGPT average training time per epoch for each dataset on one Nvidia H100 GPU.
(d) Bar charts comparing Simple Affine and scGPT model sizes.

Supplemental Figures

Supplemental Figure 1: Pictorial representation of Pearson metrics for measuring post-perturbation prediction performance.
(a) Pearson and Pearson DE scores. y_{ti} = actual expression of cells with target=t_i.
(b) Person Delta and Pearson DE Delta scores.

Supplemental Figure 2: Performance bar charts on held-out test set comparing LoRa fine-tuned scGPT to other models. Error bars span plus and minus one standard deviation of 10 independently trained models applied to the same test set.

Supplemental Figure 3: Results for the Deprecated GEARS Adamson dataset. (a) – (d) performance bar charts on held-out test set for different models. Error bars span plus and minus one standard deviation of 10 independently trained models applied to the same test set.

(a) Baseline performance across different models.

(b) Various pre-training controls.

(c) Simple affine performance.

(d) LoRa fine-tuning.

(e) Boxplots of top 20 DE genes for an example high-performing held-out perturbation condition (same perturbation as shown in the original scGPT paper[27]).

Supplemental Figure 4: Results for the Corrected GEARS Adamson dataset. All models were trained on the corrected combination of the three sub-experiments.

(a) – (d) performance bar charts on held-out test set for different models. Error bars span plus and minus one standard deviation of 10 independently trained models applied to the same test set.

(a) Baseline performance across different models.

(b) Various pre-training controls.

(c) Simple affine performance.

(d) LoRa fine-tuning.

(e) Boxplots of top 20 DE genes for an example high-performing held-out perturbation condition.

Supplemental Figure 5: Comparing attention-based models to attention-free models with and without pre-training. Plots of gene-level Pearson correlations between actual condition means and predicted means (left) and perturbation-level PD (right). Violin plots were used when data points exceeded 500 points else swarm plots. Perturbation-level PD is calculated using the actual and predicted expression of all genes for a given condition. Gene-level Pearson correlations are calculated using the transpose of those matrices, with the correlation calculated between the actual and predicted expression of each gene across all perturbations. X-axis indicates which model the predictions come from: (1) simple affine, (2) simple affine with pretrained input encoder weights, (3) scGPT architecture without pretraining and (4) fully fine-tuned scGPT.
(a) Adamson UPR experiment data only
(b) Norman single and double perturbation data
(c) Norman just single perturbation data (the same gene can be present in both train and test for double perturbation data, but not single)
(d) Replogle K562 essential dataset. There is an apparent improvement in predictions using scGPT compared to the other models. The best-predicted conditions are those for which ribosomal proteins (RP) are targeted (5 conditions in the test set), and the best-predicted genes are those that change in RP targeted conditions. This observed effect may be biologically relevant learning resulting from the combination of the scGPT architecture and the pre-training, but we cannot rule out the possibility that it could be the result of an unknown or unobserved technical artifact.

Supplemental Figure 6: Cell and perturbation counts.

(a) Cell counts for each dataset for each data split.

(b) Unique perturbation counts. Combination perturbations in the Norman dataset are counted as unique.

References

1. Gavriilidis, G. I., Vasileiou, V., Orfanou, A., Ishaque, N. & Psomopoulos, F. A mini-review on perturbation modelling across single-cell omic modalities. *Comput. Struct. Biotechnol. J.* **23**, 1886–1896 (2024).

2. Ji, Y., Lotfollahi, M., Wolf, F. A. & Theis, F. J. Machine learning for perturbational single-cell omics. *Cell Syst.* **12**, 522–537 (2021).

3. Badia-I-Mompel, P. *et al.* Gene regulatory network inference in the era of single-cell multi-omics. *Nat. Rev. Genet.* **24**, 739–754 (2023).

4. Dixit, A. *et al.* Perturb-seq: Dissecting molecular circuits with scalable single-cell RNA profiling of pooled genetic screens. *Cell* **167**, 1853-1866.e17 (2016).

5. Angerer, P. *et al.* Single cells make big data: New challenges and opportunities in transcriptomics. *Curr. Opin. Syst. Biol.* **4**, 85–91 (2017).

6. Peidli, S. *et al.* scPerturb: harmonized single-cell perturbation data. *Nat. Methods* **21**, 531–540 (2024).

7. Yao, D. *et al.* Scalable genetic screening for regulatory circuits using compressed Perturb-seq. *Nat. Biotechnol.* **42**, 1282–1295 (2024).

8. Bunne, C. *et al.* How to build the virtual cell with artificial intelligence: Priorities and opportunities. *arXiv [q-bio.QM]* (2024).

9. Palsson, B. The challenges of in silico biology. *Nat. Biotechnol.* **18**, 1147–1150 (2000).

10. Vaswani, A., Shazeer, N., Parmar, N. & Uszkoreit, J. Attention is all you need. https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

11. Anil, R. *et al.* PaLM 2 Technical Report. *arXiv [cs.CL]* (2023).

12. Dosovitskiy, A. *et al.* An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv [cs.CV]* (2020).

13. Vorontsov, E. *et al.* A foundation model for clinical-grade computational pathology and rare cancers detection. *Nat. Med.* 1–12 (2024).

14. Huang, C.-Z. A. *et al.* Music Transformer. *arXiv [cs.LG]* (2018).

15. Yang, J. *et al.* Harnessing the power of LLMs in practice: A survey on ChatGPT and beyond. *ACM Trans. Knowl. Discov. Data* (2024) doi:10.1145/3649506.

16. Bhattacharya, M., Pal, S., Chatterjee, S., Lee, S.-S. & Chakraborty, C. Large language model to multimodal large language model: A journey to shape the biological macromolecules to biological sciences and medicine. *Mol. Ther. Nucleic Acids* **35**, 102255 (2024).

17. Jiang, J. *et al.* A review of transformers in drug discovery and beyond. *J. Pharm. Anal.* 101081 (2024).

18. Choi, S. R. & Lee, M. Transformer architecture and attention mechanisms in genome data analysis: A comprehensive review. *Biology (Basel)* **12**, (2023).

19. Avsec, Ž. *et al.* Effective gene expression prediction from sequence by integrating long-range interactions. *Nat. Methods* **18**, 1196–1203 (2021).

20. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science* **379**, 1123–1130 (2023).

21. Bommasani, R. *et al.* On the opportunities and risks of foundation models. *arXiv [cs.LG]* (2021).

22. Ericsson, L., Gouk, H., Loy, C. C. & Hospedales, T. M. Self-supervised representation learning: Introduction, advances and challenges. *arXiv [cs.LG]* (2021).

23. Szałata, A. *et al.* Transformers in single-cell omics: a review and new perspectives. *Nat. Methods* **21**, 1430–1443 (2024).

24. Denton, N. *et al.* Data silos are undermining drug development and failing rare disease patients. *Orphanet J. Rare Dis.* **16**, 161 (2021).

25. Asiimwe, R. *et al.* From biobank and data silos into a data commons: convergence to support translational medicine. *J. Transl. Med.* **19**, 493 (2021).

26. Theodoris, C. V. *et al.* Transfer learning enables predictions in network biology. *Nature* **618**, 616–624 (2023).

27. Cui, H. *et al.* scGPT: toward building a foundation model for single-cell multi-omics using generative AI. *Nat. Methods* **21**, 1470–1480 (2024).

28. Hao, M. *et al.* Large-scale foundation model on single-cell transcriptomics. *Nat. Methods* **21**, 1481–1491 (2024).

29. Yang, F. *et al.* scBERT as a large-scale pretrained deep language model for cell type annotation of single-cell RNA-seq data. *Nat. Mach. Intell.* **4**, 852–866 (2022).

30. Bian, H. *et al.* ScMulan: A multitask generative pre-trained language model for single-cell analysis. in *Lecture Notes in Computer Science* 479–482 (Springer Nature Switzerland, Cham, 2024).

31. Levine, D. *et al.* Cell2Sentence: Teaching large language models the language of biology. 27299–27325 (21--27 Jul 2024) doi:10.1101/2023.09.11.557287.

32. Boiarsky, R., Singh, N., Buendia, A., Getz, G. & Sontag, D. A deep dive into single-cell RNA sequencing foundation models. *bioRxiv* 2023.10.19.563100 (2023) doi:10.1101/2023.10.19.563100.

33. Kedzierska, K. Z., Crawford, L., Amini, A. P. & Lu, A. X. Assessing the limits of zero-shot foundation models in single-cell biology. *bioRxiv* 2023.10.16.561085 (2023) doi:10.1101/2023.10.16.561085.

34. Wu, Y. *et al.* PerturBench: Benchmarking machine learning models for cellular perturbation analysis. *arXiv [cs.LG]* (2024).

35. Ahlmann-Eltze, C., Huber, W. & Anders, S. Deep learning-based predictions of gene perturbation effects do not yet outperform simple linear methods. *bioRxiv* 2024.09.16.613342 (2024) doi:10.1101/2024.09.16.613342.

36. Roohani, Y., Huang, K. & Leskovec, J. Predicting transcriptional outcomes of novel multigene perturbations with GEARS. *Nat. Biotechnol.* **42**, 927–935 (2024).

37. Adamson, B. *et al.* A multiplexed single-cell CRISPR screening platform enables systematic dissection of the unfolded protein response. *Cell* **167**, 1867-1882.e21 (2016).

38. Norman, T. M. *et al.* Exploring genetic interaction manifolds constructed from rich single-cell phenotypes. *Science* **365**, 786–793 (2019).

39. Replogle, J. M. *et al.* Mapping information-rich genotype-phenotype landscapes with genome-scale Perturb-seq. *Cell* **185**, 2559-2575.e28 (2022).

40. Martens, K., Donovan-Maiye, R. & Ferkinghoff-Borg, J. Enhancing generative perturbation models with llm-informed gene embeddings. https://openreview.net/pdf?id=eb3ndUlkt4.

41. Larson, M. H. *et al.* CRISPR interference (CRISPRi) for sequence-specific control of gene expression. *Nat. Protoc.* **8**, 2180–2196 (2013).

42. Gilbert, L. A. *et al.* Genome-scale CRISPR-mediated control of gene repression and activation. *Cell* **159**, 647–661 (2014).

43. Hu, E. J. *et al.* LoRA: Low-Rank Adaptation of large language models. *arXiv [cs.CL]* (2021).

44. Biderman, D. *et al.* LoRA learns less and forgets less. *arXiv [cs.LG]* (2024).

45. Xia, W., Qin, C. & Hazan, E. Chain of LoRA: Efficient fine-tuning of language models via residual learning. *arXiv [cs.LG]* (2024).

46. Kaplan, J. *et al.* Scaling laws for neural language models. *arXiv [cs.LG]* (2020).