Exploring the visual system of the Black Grouse (*Lyrurus tetrix*): Combining experimental and molecular approaches to inform strategies for reducing collisions

Simon Potier[1*], Jean-Marc Lassance[2], Constance Blary[3], Justine Coulombier[4], Sandrine Berthillot[4], Jérôme Cavailhes[4], Charleyne Buisson[4], Virginie M. Dos Santos[5], Christine Andraud[6] and Marjorie A. Liénard[7*]

Simon Potier, Expert Scientifique, Foucrainville, France

GIGA Institute, University of Liège, Belgium

CEFE, Univ Montpellier, CNRS, EPHE, IRD, Montpellier, France

Parc national de la Vanoise, Chambéry, France

Association Observatoire des Galliformes de Montagne, Sevrier, France

Centre de Recherche sur la Conservation des Collections, CNRS, Muséum National d'Histoire Naturelle, France

Laboratory of Molecular Biology of Sensory Systems, GIGA Institute, University of Liège, Belgium

Corresponding authors: *sim.potier@gmail.com; marjorie.lienard@uliege.be

ORCID IDs:

S.P.: 0000-0003-3156-7846

J-M.L.: 0000-0002-3675-6956

C.B.: 0000-0001-6204-9983

VMDS: 0009-0008-1660-7639

C.A.: 0000-0002-3112-9363

M.A.L.: 0000-0003-3193-3666

Keywords: visual field, contrast vision, spectral sensitivity, opsin, bird collision

Abstract

Understanding the visual systems of birds can inform conservation efforts and mitigate the impact of collisions with man-made structures. Here we investigate the visual abilities of the black grouse *Lyrurus tetrix* (Galliformes: Phasianidae), a European mountain bird highly vulnerable to collisions with aerial infrastructures. Using behavioural assays, we show that black grouse have wide monocular lateral visual fields, extensive binocular overlap and a minimal blind area behind the head, altogether indicating the ability to detect aerial objects from different fields of view. The spatial resolution and contrast sensitivity of the black grouse are in the low avian range but align with the ecology of a prey species and allow to establish the limits of detection of an object size and contrast under variable environmental conditions. To characterize the range of wavelengths perceived, the four cone visual pigments (SWS1, SWS2, Rh2, and LW) were reconstituted and characterized functionally, showing detection of light across a spectral range spanning the visible spectrum up to 650 nm and with limited sensitivity below 400 nm. Combined with spectral and achromatic modelling analyses, our results inform on the limits of detection of aerial objects and the perception of existing visual markers, offering practical perspectives to continue mitigating black grouse collisions.

Introduction

Collisions are a recognised major source of bird mortality worldwide (Rosenberg et al., 2019, Loss et al., 2014), especially with glass or other reflective building surfaces (Machtans et al., 2013), wind turbines (Marques et al., 2014, Bernardino et al., 2018, Drewitt & Langston, 2008), power lines and aerial cables that intrude into the open airspace. With the rise of ski resorts in alpine regions, the development of road networks, ground and aerial infrastructures and cable transport systems (e.g., catex, cable cars, surface lifts) have substantially reshaped landscapes over the last fifty years, notably increasing habitat fragmentation and reducing natural wildlife habitats and refuges for mountain avifauna, in particular for ground-nesting birds (Watson & Moss, 2004, Segelbacher et al., 2008, Bech et al., 2013, Matysek et al., 2021). Ski resort areas have also been associated with high collision rates, especially for Galliformes (Miquet, 1990, Bevanger, 1998, Buffet & Dumont-Dayot, 2013).

The black grouse, *Lyrurus tetrix* (Phasianidae, previously *Tetrao tetrix*) is a highly sedentary ground-nesting gallinaceous bird that forages for terrestrial invertebrates, berries, plant shoots or leaves (Hambálková et al., 2024). The black grouse is sensitive to habitat change and human disturbances (Bernardino et al., 2018), and commonly exposed to a range of

collision hazards. Documented effects include for instance deer fences in Scotland populations (Baines & Summers, 1997), power lines in Scandinavia (Bevanger, 1995), and ski lift cables in Alpine regions (Miquet, 1990, Buffet & Dumont-Dayot, 2013). When comparing black grouse population abundance in natural habitats versus ski resorts in the south-western Swiss alps, Patthey et al. (2008) quantified that habitat topology and ski lift density were already associated with 15% reduced local black grouse abundance but without linking it to collisions *per se* (Patthey et al., 2008). In the French alps, where the black grouse population is smaller and more isolated than in Scandinavian regions, around 400 deaths of black grouse have been recorded near aerial infrastructures since 1964, which represented ca. 70% of the total Galliformes death counts over that period (Corona & Dos Santos, 2023, OGM, 2010). According to earlier estimates of the French Alpine black grouse population in 2010 (OGM, 2010), collisions caused mortality in 2.5% of the population. This number is likely conservative since it excluded individuals that collide in flight but might die outside search areas, and since the probability of detecting carcasses is very low (Bech et al., 2012).

Figure 1. Aerial cables and ski lifts equipped with visual markers in the French Alps. Visual markers are indicated with arrows (see also Table S3 and Figure 7 for alternative designs). (A) Example of *black Firefly* markers (15 x 9 cm) on aerial electrical cables. (B-D) Examples of *Crocfast* and *Birdmarks* markers (13.5 cm in diameter) seen against (B) a green background, (C) a cloudy background, and (D) a clear sky. Photographs credit: VPN: A,C; JML: B, D.

For more than 20 years, numerous ski resorts have equipped hazardous ski lifts with visual markers, small plastic or metallic devices (Figure 1, Table S1) designed to increase

visibility through size, movement in the wind, reflective properties, and contrasting colour
patterns (Dos Santos et al., 2021). However, the effectiveness of these markers can differ among
target species and environmental conditions (Ferrer et al., 2020), and it remains unclear whether
black grouse perceive hazardous obstacles introduced into their flight paths. To assess current
solutions and possibly guide the development and efficient placement of visual markers,
knowledge of avian species-specific vision, ecology and behaviour should necessarily be
considered (Martin, 2011a, Martin, 2022, Martin & Banks, 2023).

Vision is the primary sensory modality for most avian species, collecting accurate and
instantaneous environmental information from different directions and over varying distances
(Land & Nilsson, 2012). Avian visual systems influence object detection for various tasks, and
are shaped by natural history and ecology such as diel activity patterns, navigation, foraging
strategies, or predator-prey interactions (Odeen & Håstad, 2010, Wu et al., 2016, Outomuro et
al., 2017, Hauser & Chang, 2017, Cooney et al., 2019, Caves et al., 2024, Blary et al., 2024).

While object detection is influenced by its properties, the bird flight behaviour and the
environmental light conditions, together with the bird's visual characteristics appear to be
important factors, including the fields of view, spatial resolution, as well as both its contrast
and spectral sensitivity (Martin, 2022). The visual field is the volume of space around the head
from which visual input is gathered at any given time (Martin, 2017a). It therefore determines
whether an artificial structure or object falls within a blind area or within a bird's field of view.
In the latter case, the binocular region allows estimation of time before contact (Martin, 2009,
Martin, 2017b, Martin et al., 2012).

An object must also reach a minimum size at a distance threshold to be detected prior
to collision (Martin, 2022), which can be informed by determining spatial resolution. Spatial
resolution is the ability to resolve two points as separate, and is a measure also used to quantify
how well birds can distinguish fine details, defining their visual acuity (Land & Nilsson, 2012).
Target detection further requires the ability to discern contrasts between an object and the
background, or patterns within an object, and is defined by the eye contrast sensitivity. Finally,
the spectral sensitivity of the avian eye is determined by different cone photoreceptors, which
shape how birds detect wavelengths of light and perceive colours (Potier et al., 2020, Kelber,
2019, Stavenga & Wilts, 2014, Wu et al., 2016). Most avian visual systems have four single
cone types that each contain one opsin visual pigment exhibiting distinct maximal wavelength
sensitivity (λ_{max}) when forming complexes bound to 11,*cis*-retinal: SWS1 360-420 nm, SWS2
430-460 nm, Rh2 470-510 nm, LWS 530-560 nm (reviewed in Hagen et al., 2023). Bird cone
opsins typically mediate a tetrachromatic colour vision system, in combination with cone-

specific oil-droplet filters (Kelber, 2019). In birds, the short-wavelength sensitive 1 opsin (SWS1) absorbance range also varies from ultraviolet-sensitive to violet-sensitive (reviewed in Hauser et al., 2014, Hagen et al., 2023, Carvalho et al., 2007). Studying species-specific visual characteristics can inform about the limits of object detection in natural and human-made environments.

Despite the long interest in black grouse conservation efforts, we still know relatively little about its visual system. A behavioural study has shown that black grouse display a preference to eat naturally UV-reflecting waxy European blueberries (*Vaccinium myrtillus*) (Siitari et al., 2002). Physiological and molecular studies in other galliform species including chicken, quail, turkey and peacock also suggest a potential for some UV sensitivity in these species (Bowmaker et al., 1997, Hart et al., 1999, Cuthill et al., 2000). Despite these reports, our understanding of black grouse vision remains fragmentary, with many aspects of their visual capabilities still uncharacterised.

The aim of the present study was thus to quantify components of the black grouse visual system that impact object detectability. Specifically, we used a combination of reflex-like behaviours, ophthalmoscopy and molecular biology to assess the black grouse visual fields, spatial resolution, contrast sensitivity, and wavelength absorbance of cone visual pigments. We then measured the reflectance properties of anti-collision visual markers placed on ski lifts and discuss the black grouse visual system characteristics in the context of marker detection, as well as the risk of flight collision under variable visual environmental conditions.

Material and methods

(a) Birds and study location

Two 4-month-old male black grouse individuals belonging to the breeding centre of Frank Grosemans (Belgium) were used to study visual fields, spatial resolution and contrast sensitivity.

(b) Visual fields

A non-invasive procedure was used to measure visual field characteristics in alert birds (Martin & Portugal, 2011). Each bird was held firmly for 20-30 min in a plastic restraining tube of the appropriate size to avoid any movement, with its legs cushioned by foam rubber and gently immobilized together with surgical tape (Micropore 1530/1B). The head was held following a natural position and placed at the centre of a visual field apparatus, a device that permits the

eyes to be examined from known positions around the head. The bill was immobilized in a

specifically manufactured steel and aluminium bill holder, and held with micropore tape,

keeping the nostrils clear for normal breathing. The bill holder surfaces were coated with cured

silicone sealant to provide a cushioned, non-slip surface. The bird's head and eyes were

photographed (iphone 13, Apple) while in the apparatus to determine the eye positions in the

skull, the horizontal separation between the centre of both eyes, the eye-to-bill-tip distance and

the bill length.

Visual field parameters were measured using an ophthalmoscopic reflex technique, with

the perimeter's coordinate system following latitude-longitude conventions and the equator

aligned to the median sagittal plane, which divides the head vertically and symmetrically into

left and right hemispheres. This coordinate system is used throughout the presentation of

results. We first examined the eyes using an ophthalmoscope mounted on the perimeter arm

with an accuracy of $\pm 0.5°$ to measure the boundaries of the retina projection from the positions

that the eyes spontaneously adopted when they were fully rotated forwards, *i.e.* converged for

estimation of binocular area boundaries, and backwards *i.e.* diverged for estimations of the blind

area behind the head. The degree of eye movements and pecten projection were not measured

to minimise restraint time.

We corrected our measurements to a hypothetical viewing point placed at infinity, based

on the distance used in the visual field apparatus and the horizontal separation of the eyes

(Martin, 1984). Using these corrected values, we constructed a topographical map of the visual

field, including the lateral fields, binocular field, cyclopean field *i.e.* the total field around the

head comprising the combined monocular fields of both eyes, and blind areas above and behind

the head. The limits of the visual field were determined at 10° elevation intervals in an arc

starting behind the head then above and in front of the head, down to an elevation 50° below

the horizontal plane of the bill-tip. At elevations where the bill holder blocked our view,

binocular field width was interpolated as the mean of the binocular field widths immediately

above and below these elevations (Martin & Portugal, 2011).

(c) Spatial resolution

Spatial resolution (SR), or visual acuity, is the ability to perceive spatial detail. SR can be

estimated from retinal photoreceptor or ganglion cell density in the retina (Coimbra et al., 2012,

Lisney et al., 2012b), estimates that closely correlate with behavioural measures of visual acuity

across vertebrates (Caves et al., 2024). There is also a strong positive correlation between visual

acuity and eye size, which is obtained by measuring corneal diameter. Corneal measures thus offer the advantage of being non-destructive, while providing estimates of visual acuity that are comparable to those obtained from behavioural estimation (Potier et al., 2016, Caves et al., 2024).

Corneal diameters (CD) were measured from calibrated eye photographs with ImageJ 1.41 (Schneider et al., 2012) to obtain Axial Length (AL, in mm) using the formula for diurnal animals (Hall & Ross, 2007):

$$AL = \frac{CD}{10^{-0.22}}$$

Spatial resolution (SR, in cycles per degree, abbreviated cpd) was calculated following the function derived from Caves et al. (2024):

$$SR = 10^{(0.26 \, + \, 0.81*log_{10}(AL))}$$

(d) Contrast sensitivity

(i) Experimental set-up

We used an eye reflex-like behaviour setup to study the contrast sensitivity of each individual, following Wagner et al. (2022) and Blary et al. (2024). This approach yields peak contrast sensitivities comparable to those obtained with the operant conditioning method (Blary et al., 2024). The eye reflexes, or optocollic reflexes, are caused by involuntary compensatory mechanisms for image stabilization, *i.e.,* the bird follows the moving object by eyes to keep the image stationary on the retina (Wagner et al., 2022). Because most birds have limited eye movements between 2 and 18° (Martin, 2009, O'Rourke et al., 2010), they follow the object with large head movements. To estimate the optocollic reflex (OCR), birds were placed into a U-shaped box adapted to their size (60 x 40 x 44 cm ; L x W x H), with a black wooden floor and ceiling, and clear polycarbonate walls (3 mm) (Figure 3A). The walls allow the bird to see the stimulus without influencing visual abilities (Blary et al., 2024). The ceiling consisted of two wooden boards spaced 5 cm apart: a perforated panel to allow air flow through and a smaller solid panel preventing the bird from seeing through the holes. All wooden surfaces were painted matte black (Liberty black Matt, GoodHome). A rear wooden door allowed the bird to be positioned inside the box. The box was placed at the centre of an octagon (radius 69cm) formed by computer monitors (Acer KG1 Series, 28 inches, 4K 3840x2160 px, 60 Hz) in portrait orientation, with their centres aligned to the level of the bird's head. The stimulus covered 236

x 46°of the visual field (horizontal x vertical), sufficient to elicit an OCR (Schmid & Wildsoet,

1998, Blary et al., 2024).

The monitors and the bird were enclosed in an opaque black cloth tent (300 x 300 x 250

cm) with the monitor bases and floor also covered in black cloth to minimize external visual

cues. The experimenter remained outside the tent throughout the experiment. A video camera

(25 frames per second; Sony DCR-SR55 HD) positioned above the monitors recorded the bird's

behaviour and a smartphone (iphone 13, Apple) connected to an external screen allowed

continuous remote monitoring.

(ii) Stimuli

Stimuli consisted of vertical sinusoidal achromatic gratings of varying spatial frequencies and

contrasts generated in Matlab (R2021) using Psychtoolbox (Brainard, 1997). Monitors were

driven by MacBook Pro (Apple) via an 8-Port 4K/60Hz HDMI splitter (ST128HD20,

StarTech). The angular velocity of the gratings was set to $20°$ s^{-1}, matching values used in

closely related species (Blary et al., 2024). To obtain the contrast sensitivity function (CSF) –

including peak contrast sensitivity, its corresponding spatial frequency, and the high cut-off

frequency (*i.e.* the highest spatial frequency detected at a Michelson contrast of 1) – we used

six spatial frequencies (0.47, 0.56, 0.85, 1.06, 1.27 and 1.59 cpd) and Michelson contrasts

ranging from 0.012 and 0.99 (Table S2). Specifically, Michelson contrast is defined as:

239
$$Michelson\ contrast = \frac{I_{max} - I_{min}}{I_{max} + I_{min}}$$

where I_{min} and I_{max} are the minimum and maximum luminance; values range from 0% (no

contrast) to 100% (perfect black-white difference). For each contrast level, luminance

differences between the darkest and lightest regions of the monitor centre were measured with

a luxmeter (Hagner ScreenMaster, B. Hagner, Sweden) and expressed in candelas per square

meter (cd/m^2).

Each stimulus was displayed for 20 s (Schmid & Wildsoet, 1998, Shi & Stell, 2013,

Wagner et al., 2022, Blary et al., 2024), with stimulus direction (clockwise or anticlockwise)

varied in a pseudorandom order, limiting consecutive identical directions to three. Illuminance

at the bird's head was 110 lux inside the U-shaped box and 321 lux outside, and stimulus

brightness was 73 cd/m^2.

(iii) Experimental procedure
253
Computer monitors were switched on 20 minutes before to the experiment to reach maximum
brightness. Following the bird's placement in the device, a 10-minute habituation period was
observed before the experimental session began. The experimenter visually assessed the
presence of the optocollic reflex (OCR) in accordance with standard practice (Schmid &
Wildsoet, 1998, Shi & Stell, 2013, Blary et al., 2024). Each session began with maximum
contrast (Michelson contrast = 0.99) to ensure that the bird was expressing an OCR detectable
by the experimenter. Contrast was then varied stepwise as described in Blary et al. (2024), to
identify the threshold at which birds no longer exhibited the reflex. Each trial combined a
specific combination of spatial frequency and contrast and was separated by at least 5 seconds
of an isoluminant homogeneous grey screen (longer if the bird did not look at the monitors).
We applied the "four of five" criterion: each combination was presented five times, and a
response was considered reliable if the OCR occurred in at least 4 trials (Shi & Stell, 2013,
Blary et al., 2024). The lowest contrast meeting this criterion was defined as the threshold
contrast. Once determined, the experiment was repeated at the same angular velocity with a
different spatial frequency. All session were video-recorded, allowing retrospective verification
of OCR presence or absence.
270

(e) Detection distance
Under optimal conditions, the distance at which an object can be detected and avoided depends
on three factors: the spatial resolution, reaction time (t_{react}) and flight speed (v) (Martin, 2022).
In birds, it would seem reasonable to consider that a minimum $t_{react} = 2s$ is necessary to initiate
a change in flight path (Martin, 2022). Using the allometric relationship between body mass
and cruising flight speed presented by Alerstam et al. (2007), the mean body mass of black
grouse (1,068.7 g; Dunning 2007) predicts a typical v of 16.04 m·s⁻¹. If the object only needs
to be visible during reaction, the minimum detection distance (D) of an object while in flight is
D = 2v. Therefore, the minimal detection distance of an object is 2*16.04 = 32 m.
From this minimal detection distance, the spacing (d) between two objects (*e.g.* two
adjacent visual markers) while actively flying can be estimated using the trigonometric
relationship between angle and detection distance as follow: d = 2*D. tan(θ/2), where θ is the
binocular overlap angle in radians.
Under optimal conditions, the minimum width of an object (w) to meet the spatial-
frequency limit of one cycle can be estimated using w = D. tan($\frac{1}{2SR} * \frac{\pi}{180}$), where SR = Spatial

Resolution. A factor of 2 is applied to *SR* because visual acuity is expressed in cpd, and one
cycle corresponds to two resolvable bars; birds can therefore discriminate two objects within a
single cycle.

(f) Opsin λ_{max} characterization via heterologous expression
291
(i) Collection of eye tissues and extraction of ribonucleic acid (RNA).

Ocular tissue, including the retina, was dissected by a veterinarian from an accidentally killed
adult female black grouse collected in Bourg-Saint-Maurice France (ID: JB-2021-E001, POIA
Birdski Project 2020-2023 Vanoise), respecting permits in place. The collected tissue was
directly preserved in DNA/RNA reagent (Zymo Research) and stored at -20° C. Before
extraction, the tissue sample was removed from the stabilization solution, briefly dried and then
ground to a fine powder in a mortar cooled with liquid nitrogen. We then proceeded with RNA
extraction with a Monarch Total RNA miniprep kit (NEB) following the manufacturer's
instructions. The integrity of the RNA was evaluated using a bioanalyzer and the quantity
assessed using a Qubit High Sensitivity RNA assay (Invitrogen).

(ii) cDNA libraries and RNA-sequencing.

Five hundred micrograms of high-quality RNA were used to prepare a deoxyribonucleic acid
(DNA) library following the protocol detailed in NEBNext Ultra II Directional RNA library
prep kit for Illumina (NEB), including the following specifications: selection of messenger
RNA (mRNA), a selected average size of 500 base pairs for fragmentation, and the addition of
Illumina adapters. The quality of the cDNA library was evaluated using a bioanalyzer as well
as by quantitative PCR (Polymerase Chain Reaction). Paired-end sequencing (2x150bp) was
performed on an Illumina NovaSeq6000 equipped with an S4 flowcell (NovaSeq Control
Software 1.8.0/RTA v3.4.4, SciLifeLab, Stockholm, Sweden). In total, we obtained 197.8
million read pairs. The transcriptome sequencing data have been deposited into the European
Nucleotide Archive (ENA) under the project accession PRJEB86944.

(iii) Pre-assembly filtering

Raw reads were first preprocessed by correcting and excluding aberrant reads using the k-mer-
based read-error correction tool Rcorrector (Song & Florea, 2015). We next proceeded to
adapter removal and quality trimming (--quality-cutoff=20) using cutadapt version 4.2 (Martin,
2011b). During that step, we also removed read pairs with either read shorter than 36 bp. Next,

we removed reads corresponding to rRNA sequences by mapping the reads against a custom

database built from SILVA SSU and LSU datasets (release 138.1) (Quast et al., 2013) using

bowtie2 (Langmead & Salzberg, 2012). Finally, reads corresponding to mitochondrial sequence

were extracted using MITGARD (Nachtigall et al., 2021). The final set of assembly-ready reads

contained 173.8 million read pairs.

(iv) *De novo* transcriptome assembly and annotation

De novo assembly of the pre-processed paired-end reads was performed using Trinity v2.14.0

(Garber et al., 2011) with default parameters. Completeness of the assembly was assessed with

BUSCO v3.0.2 (Simão et al., 2015) using the Vertebrata and Aves datasets. We applied the

pipeline implemented in Trinotate v3.2.1 (Bryant et al., 2017) to predict candidate protein

coding regions within transcript sequences using TransDecoder v5.5.0

(https://github.com/TransDecoder/TransDecoder) and to generate a functional annotation of the

transcriptome data. We retrieved full-length candidate opsin transcripts from the resulting

annotation table (Dataset S1).

(vi) Opsin functional expression

Opsin-specific oligonucleotide primers (Table S3) encompassing two distinct restriction sites

were designed to amplify the coding region of each identified visual opsin (SWS1, SWS2, Rh2,

LW) by PCR using retinal cDNA synthesized using the GoScript protocol (Promega) as

template. After verification by agarose gel electrophoresis, expected amplified product sizes

were gel-purified using the Monarch DNA gel extraction kit (NEB), digested with restriction

enzymes, subcloned into the linearized pcDNA5-FLAG-T2A-mruby2 expression vector

(Liénard et al., 2021), and propagated into a Q5 strain of *Escherichia coli* bacteria (NEB). After

incubation of individual bacterial colonies in Luria-Broth culture medium containing

ampicillin, DNA plasmids were purified, and each construct sequence was verified by Sanger

sequencing. A stock of 480 micrograms for each final plasmid was prepared following the

ZymoPURE II Plasmid MidiPrep kit protocol (Zymo).

(vii) Protein purification, absorbance measurement and UV-VIS analyses

Each plasmid was transfected into human embryonic kidney cells (HEK293T, ThermoFisher)

following the PASHE procedure (Liénard et al., 2022). Briefly, 11-*cis*-retinal was added in

solution in the dark (under red light) 6h post transfection. Cells were collected and the total

membrane fraction solubilized using 1% n-Dodecyl-D-Maltoside detergent (DDM) 48h after

transfection, and the opsin fraction bound to FLAG resin and incubated overnight. The next day, the opsin-FLAG complex was purified and eluted using FLAG peptide, subsequently concentrated by centrifugation at 4000 rpm and 4°C for 50 min prior to ultraviolet-visible (UV-VIS) spectroscopy. The absorbance of each purified rhodopsin (opsin in complex with the chromophore) was measured in the dark from 1.5 μL aliquots using a NanoDrop 2000/2000c UV-VIS spectrophotometer (ThermoFisher). For each rhodopsin, we estimated lambda max by nonlinear fitting of the absorbance data using a visual pigment template (Govardovskii et al., 2000a). We performed 1,000 bootstrap replicates to compute lambda max estimates and the associated confidence intervals (Liénard et al., 2022) in R v. 3.6.6. using the rsample (Frick et al., 2022) and tidymodels (Kuhn & Wickham, 2020) packages.

(f) Modeling of spectral sensitivity in cone photoreceptors

To derive a theoretical effective eye spectral sensitivity in the black grouse, which depends on the visual pigment opsin λ_{max} and oil droplet filtering, we modelled the relationship between each cone opsin λ_{max} and a parsimonious microspectrophotometric oil droplet λ_{cut} for Galliformes (Stavenga & Wilts, 2014). The mid-wavelengths of absorbance, *i.e.* where the droplet transmits 50% (or λ_{mid}) were inferred for the C, Y and R oil droplet types as follows: For the C-type droplet expressed in SWS2, the established empirical relationship is approximated as $C_{mid} = 0.82 \times \lambda_{max\_SWS1} + 75$, providing C-type λ_{mid} at 430-434 nm (Hart & Vorobyev, 2005); For Y- and R-type droplets expressed in Rh2 and LWS cones, Y_{mid} 515 nm and R_{mid} 560 nm were applied (Hart, 2001, Bowmaker et al., 1997, Hart & Hunt, 2007). Droplet transmission slopes were modelled with 0.2 log unit/10nm, consistent with Hart (2001), with moderate slopes of k = 0.15 for SWS2 and k = 0.12 for Rh2 and LWS. The plotted normalized effective photoreceptor sensitivity range is the product of opsin absorbance x droplet transmission, attenuated relative to opsin absorbance (Dataset 3).

The exponentially decaying visual pigment absorbance spectrum allows to calculate the upper limit of cone sensitivity, sensitivity which is not extended by lateral filtering alone (Bernard, 1979) and can be obtained from the visual Govardovskii template (Govardovskii et al., 2000b) at the wavelength intercepting 5% sensitivity.

(g) Reflectance spectrum of visual marker devices

Reflectance measurements were carried out using a high-performance spectrophotometer, Cary 5000 Ultraviolet-Visible-Near Infrared (UV-VIS-NIR) spectrophotometer (Agilent) capturing wavelengths every 1 nm from 300 to 780 nm using a photomultiplier tube detector. A reference

blank (spectralon) was used for baseline before each measurement. Detection markers installed

in ski resort stations were sampled and their characteristics are described in Table S1. Most

materials were opaque, therefore not transmitting light rays and preventing measures of light

transmission. Two types of reflectance were measured: i) *diffuse reflectance*, in which the

incident light is scattered in many directions, and ii) *combined diffuse and specular reflectance*,

which includes both scattered and reflected components. Specular reflection corresponds to the

direct, angle-dependent reflection and is generally more perceptible at greater distances than

diffuse reflection. We measured each component separately, yet in most optical situations, both

diffuse and specular components contribute simultaneously to the reflected signal.

To quantify the achromatic contrast between different materials of the same object, we

computed Michelson contrast values for the mean spectral reflectance of each material surface.

For each sampled area, we averaged the reflectance spectrum over the full measurement range

(300–780 nm), yielding a single value representing overall reflectance intensity. The Michelson

contrast between two surfaces R_1 and R_2 was calculated as:

$$C_{Michelson} = \frac{\max(R_1, R_2) - \min(R_1, R_2)}{\max(R_1, R_2) + \min(R_1, R_2)}$$

406   This metric provides a relative measure of contrast that is independent of absolute luminance.

407   We then estimated the inverse contrast value (1/C) to compare with the maximum spectral

408   sensitivity of the black grouse. (Datafile S4). Transparent floats are not included in this analysis

409   as they are composed of a single type of material.

Results

(a) Black grouse visual fields

The maximum binocular overlap of the male black grouse covered 40° and is positioned 30° above the bill-tip direction (Figure 2A). At rest, the black grouse has a field of view covering 353°, including a frontal binocular overlap of 28°, lateral fields of 162.5° each, and a blind sector of only 7° behind the head (Figure 2B). Therefore, when black grouses fly at the same altitude as an object (*e.g.* a visual marker), the minimal spacing between two adjacent markers for them to be visible to the black grouse is d = 2*32 *tan(28°) ~16 m. The vertical extent of the binocular field in the median sagittal plane covers 170° (Figure 2C), extending from 0° to 100° in between the head tip (0°) and the bill-tip (100°), 40° behind the head tip, and 30° below the bill-tip plane (100° -140°) (Figure 2C). At the head tip (0°), the binocular field has a width of 6°.

Figure 2. Visual fields of the black grouse. (**A**) Orthographic projection of the retinal field boundaries from both eyes. A latitude and longitude coordinate system is used with the equator aligned vertically in the median sagittal plane. The bird head is positioned at the centre of a schematic globe, and the projection of the bill tip corresponds to the black triangle. The grid lines are drawn at 10° intervals in latitude, and at 20° intervals in longitude. (**B**) Section through the horizontal plane corresponding to the bold line on panel A, and showing the binocular overlap (green), lateral fields (white) and blind spot (brown) in black grouse. (**C**) Binocular field as a function of vertical elevation in the median sagittal plane. The bird head orientation is shown with the direction of the bill tip. All values are in degrees, and the grid is at 10° intervals. Values represent the mean visual field for two measured individuals.

(b) Eye size, visual acuity and detection distance

The measured Corneal Diameter (CD) from close-up photographs was 8.00 mm for both individuals. The estimated Axial Length (AL) was 13.28 mm, which corresponds to a spatial

440   resolution (SR) of 9.81 c/deg. With a SR = 9.81c/deg, the minimal width (*w*) of an object to be

441   detected at 32m is $w = 32 * \tan(\frac{1}{2*9.81} * \frac{\pi}{180}) \sim 0.028m = 28.5mm$.

443   (c) Contrast sensitivity
444

To assess the bird's ability to distinguish features in its visual environment, we projected stripe

patterns with varying contrast and spatial frequencies. Figure 3B shows that contrast sensitivity

decreased progressively with increasing spatial frequency—corresponding to a smaller distance

to object or increase in object size. Contrast sensitivity also decreased with decreasing spatial

frequency—corresponding to a longer distance to object or reduction in object size. This typical

contrast sensitivity pattern results in an inverse U-shaped curve (Figure 3B). The estimated

optical cut-off frequency, *i.e.* the point at which the stripe pattern becomes too fine for the eye

to resolve, was 0.85 cycles per degree (cpd) for individual A and 1.06 cpd for individual B. The

average optical cutoff frequency was 0.95 cpd, corresponding to a maximum contrast sensitivity

of 16.67 (Figure 3B). This sensitivity corresponds to a Michelson contrast (C_m) of 6% (*i.e.*

contrast sensitivity = 16.67 = $1/C_m$; C_m = 1/16.67 ~ 0.0599 or 5.99%), which means that black

grouse can distinguish a signal until it is only 6% brighter than the surrounding background.

We then estimated the maximal spatial resolution in a moving environment, that is the detection

limit of the visual system when contrast sensitivity is set to 1 (or C_m = 1/1 = 1 = 100%), *i.e.*

only a black and white grating with 100% contrast would be just detectable. Based on Figure

3B, at a contrast sensitivity of 1, the spatial frequency reaches 1.6 cpd (Figure 3B).

Figure 3. **Contrast sensitivity of the black grouse.** Contrast sensitivity is defined as the inverse of contrast threshold, as a function of spatial frequency. (**A**) Picture of a black grouse in the apparatus where eyes face monitors displaying gradient stripes. (**B**) Dashed red and blue lines represent contrast sensitivity, expressed as the inverse of Michelson Contrast ($1/C_m$) values, for individual A and B. The black curve represents the mean. (**C**) Comparison of the contrast sensitivity between the black grouse (blue curve) and representative species also prone to collisions based on values from Blary et al. (2024). Coloured curves correspond to the following species: red, Golden eagle; yellow, Griffon vulture; green, Bald ibis; orange, Demoiselle crane. Scales in B and C are logarithmic.

     (d) Opsin absorbance
471

We determined the range of absorbance of the four cone opsins (SWS1, SWS2, Rh2, LW)

expressed in the black grouse retina as determined via RNA expression profiling. Active

rhodopsin complexes were reconstituted *in vitro* by addition of 11-*cis*-retinal, purified and

analysed by ultraviolet-visible spectroscopy to determine their absorbance profiles. These

analyses showed that the black grouse SWS1 and SWS2 opsins absorb maximally at λ_{max} of

393 ± 2nm (Figure 4A), and λ_{max} of 436 ± 3nm (Figure 4B), respectively. We then measured

the absorbance of black grouse Rh2 and LW, which displayed maximum sensitivity to light at

482 nm ± 2.5 nm (Figure 4C) and 545 ± 2.5 nm (Figure 4D), respectively. Black grouse cone

opsins thus perceive wavelengths from ca. 350 nm to 643 nm (Figure 5A) when applying a

visual template fit with a 5% sensitivity cut-off for the lower and upper absorbance shoulders

of SWS1 and LW, respectively.

Figure 4: Absorbance range of *Lyrurus tetrix* visual cone opsins purified in complex with 11,*cis*-
retinal. (A-D) The black dots represent the average absorbance across replicates at every wavelength,
whereas the lines represent the curve-fitting of individual bootstrap replicates. (A) SWS1 (n = 7), (B)
SWS2 (n = 6), (C) Rh2 (n = 3), (D) LW (n = 7), where n is the number of measurements of protein
aliquots with active rhodopsin complexes. For each rhodopsin, relative absorbance data are fitted to a
visual template with polynomial function analyses computed in R to obtain the estimates of lambda max
following 1,000 bootstrap replicates. Values in parentheses represent the lower and upper bounds of the
95% confidence intervals. Accompanying data are provided in Dataset S2.

(e) Modelled spectral sensitivity

Using the empirical visual pigment λ_{max}, which provide the UV-visible spectral range and

maximal wavelength perception (Figure 5A), we then modelled the effect of oil droplets on

theoretical effective photoreceptor sensitivity in SWS, Rh2 and LW cones (Figure 5B-C). In

SWS1 cones, spectral sensitivity corresponds to the visual pigment sensitivity and in SWS2

cones, sensitivity is maximized above 449 nm (Figure 5B). In Rh2 and LW cones, Y- and R-

type oil droplets tends to shift the resulting maximal cone spectral sensitivity to longer

wavelengths, which modelling indicate would likely be maximised above 525 nm and 560 nm,

respectively (Figure 5C). Because oil droplet filters do not alter the long-wavelength limb of

absorption by the expressed opsin, the maximal wavelength perceived by the LW photoreceptor

remains at ~643 nm, corresponding to the 5% sensitivity cut-off by the descending absorbance

shoulder (Figure 5).

507
508
Figure 5: **Visual opsin pigment absorbance range and modelled spectral sensitivity in the black**
grouse. (**A**) The visual pigment absorbance range confers wavelength perception from ca. 350 nm to
643 nm, where opsin absorbance lowers to 5% sensitivity (dashed horizontal grey line). (**B**) Theoretical
effective SWS cone spectral sensitivity is calculated as SWS * oil droplet sensitivity. SWS1 cones have
transparent T-type oil droplets that transmit light (T = 1) and the effective SWS1 cone spectral sensitivity
is similar to the opsin-based absorbance range. In SWS2 cones, C-type droplets filter short wavelengths
under 430 nm, following the relationship established by Hart and Vorobyev (2005), modelled as a likely
shift of the SWS2 peak sensitivity to approximately 449 nm. (**C**) Theoretical effective Rh2 and LW cone
spectral sensitivities. Y- and R-type droplet transmission λ_{mid} values vary moderately across avian
species (Y-type 505-515 nm, R-type: 585-613 nm) and estimates of Y-λ_{mid} = 515 nm and R-λ_{mid} = 560
nm are used here, based on known microspectrophotometry average values in other Galliformes such as
Gallus gallus (Table S4) (Hart, 2001), parsimoniously placing the range of effective cone sensitivity
from 525 to 580 nm for Rh2 and from 574 to 643 nm for LWS. Modelling scripts are presented as
accompanying Dataset S3.

Avian SWS1 opsins are divided into ultraviolet (λ_{max} < 385 nm) and violet-sensitive

(λ_{max} >385 nm) types (Hauser et al., 2014), and the black grouse visual pigment, based on its

λ_{max} is classified in the violet range but nevertheless absorbs a small fraction of UV light (Figure

3, Figure 4A). We aligned and compared SWS1 opsin sequences between the black grouse and

additional representative avian species with known SWS1 opsin absorbance, highlighting

amino acid residues at positions previously found involved in spectral tuning (Figure 6) (Hauser

et al., 2014, Hagen et al., 2023). The black grouse SWS1 opsin lacks the cysteine residue present

in all true ultraviolet sensitive opsins with λ_{max} < 370 nm (Figure 6) and share different degrees

of sequence similarities at those spectral positions, with the Chicken (λ_{max} 419 nm) and Pigeon

(λ_{max} 393 nm) SWS1 opsins.

535
Figure 6. SWS1 opsin phylogeny of representative bird species with known SWS1 visual pigment
maximal absorbance (λ_{max}). Vertebrate SWS1 pigments are divided into two subtypes (UVS λ_{max} 355-
385 nm, VS λ_{max} 385-455 nm) (Hauser et al., 2014) and different circle colours are used to represent
UV-shifted (black) to more violet-shifted light. Maximal absorbance peak values measured from
purified visual pigments are indicated after each species name and are taken from Hart (2001) and Hart
and Hunt (2007). Key amino acid sites and residue substitutions contributing to avian SWS1 maximal
sensitivity (reviewed in Hauser et al. (2014)) are indicated along phylogenetic branches, with numbering
relative to bovine rhodopsin residue positions (Acc. number AAA30674). The ancestral avian violet
SWS1 sensitivity was inferred in Hagen et al. (2023). OH refers to amino acids bearing a hydroxyl
group. Dots in the alignment correspond to a conserved residue with the consensus sequence in grey (+
indicates a variable site). Sequence accession numbers: Chicken NP_990769, Budgeriar
NP_001298010, Canary NP_001289029, Zebrafinch NP_001070172, Common starling
XP_014746280, hooded crow XP_039427152, Common cormorant ABS86975.1, Pigeon
NP_001269750.

(f) Reflectance spectra of visual markers

Visual markers show spectral reflectance within the visible spectrum, and a few materials show

reflectance in the ultraviolet range below 400 nm and long-wavelength light above 750 nm

(Figure 7, Figures S1 to S8). For most materials except the polished stainless-steel plate (Figure. S7), the specular and diffuse reflection components are nearly identical (Figures S1 to S8). Due to the variety of existing designs, some materials show relative reflectance values exceeding 100% owing to fluorescent elements.

Figure 7. Examples of aerial cables equipped with visual markers and their diffuse reflectance profiles (see also Table S1 for more designs, and Figures S1-S8 for a comparison between diffuse and specular reflectance). Photographs of (**A**) a *stainless-steel plate* (8 x 8 cm) installed on aerial cables transporting explosives in the context of avalanche control. (**B**) a *transparent float* (7.5 x 4.5 cm) installed on the safety rope of ski lifts. (**C**) a *black firefly* (15 x 9 cm) installed on chairlifts. (**D**) a patterned *flag* (16 x 16 cm) installed on aerial cables for transporting explosives in the context of avalanche control. (**E**) a white orange *Birdmark* (diameter 13.5 cm) installed on chairlifts and safety ropes of ski lifts. Reflectance spectra are measured from 300 nm to 780 nm. Reflectance within the visible range for a human eye is coloured from violet (400 nm) to red (750 nm). Reflectance outside the visible range for a human eye (< 400 nm and > 750 nm) are coloured in black.

(g) internal contrasts of visual markers

For most visual markers, internal achromatic contrast between different materials was generally below the black grouse maximal sensitivity contrast of 16.67 (Figure 8), in other words most of these visual features have enough brightness contrast to be perceived by the black grouse visual system. Reversely, specific combinations of adjacent materials may not meet the necessary contrast threshold for detection by black grouse. The orange retroreflectors on *Birdmarks*, but not the yellow one, exhibited a low achromatic contrast (*i.e.* a high

1/Michelson contrast) with the paddle, contrast which falls outside of the limits of sensitivity

for the black grouse. Similarly, the achromatic contrast observed for the yellow retroreflector

and the paddle on the *White Crocfast* appears outside the contrast detection limits. For the *White*

Firefly, the white beacon lacked sufficient contrast with the adjacent yellow retroreflector. For

the *Black Firefly*, both the yellow and phosphorescent retroreflectors showed low achromatic

contrast; however, this is partially mitigated by the presence of the black beacon, which

provides a degree of visual separation between the elements.

587
588
Figure 8. **Heatmap representation of internal contrasts in visual markers composed of multiple**
materials. Contrasts are calculated as the inverse of the Michelson contrast threshold. Squares outlined
in black indicate cases where contrasts fall below the maximum contrast sensitivity of the black grouse
(1/Michelson contrast <= 16,67), suggesting that the visual system can perceive the difference in
brightness between components of the visual marker, which exceeds the smallest brightness difference
detectable by the black grouse visual system at its peak Critical Flicker Fusion (CFF) frequency, that is
when the visual system is most sensitive to changes in brightness. See also Dataset S4.

Discussion

Constraints in bird visual perception have been suggested as one of the factors contributing to variable risks of collisions with man-made structures (Martin, 2011a, Martin, 2022, Martin & Banks, 2023). In this study, we examined visual characteristics of the black grouse, specifically its visual fields, contrast sensitivity, corneal size (and the estimated visual acuity), as well as visual pigment spectral range, to gain a better understanding of its multifaceted vision, and discuss how these factors may affect the perception of obstacles and visual markers.

Visual fields

Avian visual fields reflect ecological differences, such as in navigation and foraging, parental care, or predator detection, and vary significantly among avian species (Martin, 2017b). The visual field configuration of the black grouse shows that this species has an exceptionally extended visual field in both the horizontal and vertical planes. From more than 250 avian species studied to date (Martin, 2017a, Potier et al., 2018a, Cantlay et al., 2023, Potier et al., 2023), only four have a blind visual sector behind the head smaller than that of the black grouse (7°), *i.e.* the Eurasian woodcock *Scolopax rusticola* (Martin, 1994) and three duck species, the Mallard *Anas platyrhynchos*, the Northern pintail *Anas acuta* and the Pink-eared duck *Malacorhynchus membranaceus* (Martin, 1986, Guillemain & Fritz, 2002, Martin, 2007).

In the context of avian collision, both the binocular overlap and vertical extent of the binocular field are important parameters. The binocular overlap is thought to function primarily in the detection of symmetrically expanding optic flow-fields that provide almost instantaneous information on the direction of travel and time-to-contact a target, whereas the vertical extent defines whether birds can see in the direction of their flight path (Martin, 2009, Martin & Portugal, 2011, Martin et al., 2012, Martin, 2017a, Martin, 2022).

The black grouse frontal binocular field covers 28° on the horizontal plane, in agreement with typical avian values (20°-40°) (Martin, 2017b), and has a wide maximal binocular overlap of 40°, located 30° above the eye bill-tip direction (Figure 2A,C), which is similar to other visual ground forager species such as the Southern caracara *Caracara plancus* (Potier et al., 2017). Together, the binocular field of the black grouse is well adapted to its ground foraging behaviour.

The vertical extent of the binocular field allows black grouse to gain a comprehensive
visual coverage of the celestial hemisphere, and the ability to see the way ahead irrespective of
their head position. This configuration should therefore enable black grouse to detect aerial
objects. In Galliformes, however, suborbital ridges develop in adult males (Lindén & Väisänen,
1986) or during the breeding season (Lamond et al., 2025), suggesting that the vertical binocular
field may be somewhat reduced in older males, which merit further quantification across
development, including comparison with females.

In contrast to the black grouse, many large raptors, such as some eagles, vultures or
hawks (Accipitriformes) may fail to see the way ahead (Martin et al., 2012, Portugal et al.,
2017, Potier et al., 2018a). Hence, while in flight visualizing the ground below for food, their
limited field of view would comparatively provide none or only intermittent information about
the flight path ahead (Martin et al., 2012).

Thus the finding that black grouse can detect objects in a wide horizontal and also in
the vertical plane is informative to directly optimize aerial man-made structures, by modifying
e.g. an object's size or spacing, its internal contrasts or contrast relative to the environmental
background, or its spectral properties (colours), and/or using visual markers (Martin, 2022) to
improve the detection of object.

Spatial resolution, visual acuity and detection distance

Avian spatial resolution is highly variable, from as low as 4 cpd in the barn owl *Tyto alba* to as
high as 142 cpd in the Wedge-tailed eagle *Aquila audax* (reviewed in Martin (2017a)). The
black grouse has a spatial resolving power of 9.81 cpd, which is relatively low. Its visual acuity,
estimated from eye size, is nevertheless very similar to that of closely related species in the
Order Galliformes, ranging from 9.7 cpd in the Japanese quail *Coturnix japonica* to 13 cpd in
the Sharp-tailed grouse *Tympanuchus phasianellus* (Lisney et al., 2012a). Although additional
precision may be gained through approaches based on photoreceptor density or behavioural
assays, these results show that eye size remains a reliable proxy for spatial resolution (Kiltie,
2000, Caves et al., 2024) and can provide estimates comparable to those obtained with operant
conditioning (Potier et al., 2016).

Spatial resolution informs at which distance black grouse can detect objects in optimal
environmental conditions, that is i) with no air distortion and a clear sky, ii) for a black object
on a white background (*i.e.* high contrast scenario), iii) high daylight level, and iv) with the bird
visually fixing the object with its acute centre of vision (Land & Nilsson, 2012, Martin, 2017b,
Martin, 2022). Under optimal conditions, the shortest distance at which the black grouse can

detect two adjacent objects while in flight is 32 m, a conservative minimal value that may increase depending notably on bird motion, atmospheric turbulence or directional lightning in mountain, conditions all known to affect flight in real time. Considering the visual acuity as a proxy of corneal diameter, trigonometric calculations indicate that, to be detected at 32 m, an object should be of a minimum width of 28.5 mm. This measure is 4 to 5 times larger than the smallest object detectable by an average human eye with its spatial resolution of 40-50 cpd (Martin, 2017b). In addition, in a natural scene, optimal conditions are rarely reached; spatial resolution declines up to 5-fold with decreasing light levels *e.g.* on a cloudy day, or at dusk and dawn (Land & Nilsson, 2012, Martin, 2022). To compensate for this lower resolution, the object width should linearly be increased 5 times, therefore reaching a minimum width of 142.5mm, a width currently only met by *flag* designs (15 cm x 15 cm, Figure 7D, Table S3).

Contrast sensitivity

The maximum contrast sensitivity of the black grouse (16.67) is in the middle range compared to various birds, *e.g.* from 4.8 in the Bourke's parrot *Neopsephotus bourkii* to 31 in the American kestrel *Falco sparverius* (Hirsch, 1982, Lind et al., 2012, Blary et al., 2024). Values in birds are typically lower than contrast sensitivity observed in other vertebrates such as most rodents (30) or human (close to 200) (De Valois et al., 1974, O'Carroll & Wiederman, 2014). Since the black grouse maximum contrast sensitivity is ~10x lower compared to a human eye, a dark aerial cable or a dark lift structure against a dark green forest background, or a visual marker against a snowy background (Figure 1) would be more difficult for a black grouse eye to detect compared to a human eye. Consequently, choosing markers with high internal object contrasts (Figure 8), as well as high contrast with the surrounding environment (Martin, 2022) should further aid black grouse in detecting aerial infrastructures under variable light conditions.

Spectral range

The spectral characteristics of the black grouse visual opsin pigments align with avian pigment sensitivities (reviewed in Hagen et al. (2023), and together its four avian cone opsins absorb wavelengths of light spanning ultraviolet to red from ca. 350 to 643 nm. Whereas transmission properties of cone oil droplets in the black grouse are not yet known, models based on other galliform species are informative to infer the black grouse effective spectral sensitivity (Figure 5). In SWS1 cones, transparent T-type oil droplets do not absorb light (Hart &

Vorobyev, 2005), so maximal spectral sensitivity aligns primarily with the SWS1 visual pigment λ_{max}. Differences in absorbance characteristics of the avian ocular media can also tune UV sensitivity since the cornea typically also filters a portion of UV light, albeit with large interspecific variation among species *i.e.* low and high cut-offs vary between ~315 and 370 nm (reviewed in Hart and Vorobyev (2005)). The violet-sensitive black grouse SWS1 pigment, with an absorbance peak around 393 nm, would likely be capable of detecting some signals in the UV range, even in the case of a relatively high corneal filtering that would absorb short-UV wavelengths. Behavioural research has shown that black grouse preferentially choose UV-reflecting berries (Siitari et al., 2002), suggesting that black grouse SWS1 cones indeed enable perceiving at least some long ultraviolet wavelengths, although further work characterizing the UV absorbance of black grouse lenses is needed. Differences in opsin λ_{max} are largely contributed by molecular variation at tuning spectral sites and have been shown to influence colour perception in vertebrates (Hauser et al., 2014, Hagen et al., 2023). The ecological consequences of small variations within avian violet-sensitive pigments however remain to be studied in more detail.

Together with the black grouse SWS2 pigment absorbance, the modelled spectral sensitivity of SWS2 cones (λ_{max} 449 nm) after C-filtering aligns closely with in vivo measurements in related galliform bird species, such as the Japanese quail (*Coturnix japonica*, $\lambda_{max} \sim 450$ nm; (Bowmaker et al., 1993)) or domestic chicken (*Gallus gallus*, $\lambda_{max} \sim 450$ nm; (Bowmaker et al., 1997)), indicating that black grouse SWS2 cones are primarily sensitive to wavelengths above 400 nm up to 534 nm. Rh2 cones are sensitive from above 500 nm to 580 nm with maximal spectral sensitivity predicted at 525 nm after Y-filtering. This wavelength effectively defines the upper limit for opponency between Rh2 and LWS cones and therefore sets the functional limit for chromatic colour discrimination, which based on our values of pigment absorbance and sensitivity modelling in black grouse is restricted to the blue–yellow range. The LWS cones have a predicted spectral peak sensitivity at 574 nm after R-filtering, and an upper sensitivity limit at 643 nm, defined by the LW pigment, allowing black grouse to perceive the brightness of orange and red objects. However, because the chromatic contrast is limited by Rh2 sensitivity, most wavelengths above ~600 nm are likely not distinguished as colours, although achromatic (brightness) perception remains effective up to the LWS 5% sensitivity cut-off at ~643nm. Compared to humans, whose MWS and LWS cones are shifted to 535 nm and 564 nm (Kelber, 2019), respectively, black grouse are thus less capable of chromatically discriminating red–orange hues.

Detection abilities of visual markers and considerations for future optimisation

Across a large diversity of materials used to build visual markers currently in use in ski areas in the French Alps, we found that all tend to reflect visible wavelengths of light in the range of perception of the black grouse. Wavelengths shorter than 400 nm are rarely reflected overall, and some of the red visual markers include long-wavelength reflectance above 650 nm, presumably beyond the limits of black grouse perception.

For the black grouse, a marker may thus not benefit from chromatic contrasts above 600nm (*i.e.* adjacent yellow and orange, or orange and red patterns would be inefficient). Reversely, visual markers would provide strong chromatic contrasts if they reflect light from 400 nm to 580 nm (*i.e.* from violet/blue to yellow/orange spectra), and potentially also achromatic signals from long-UV reflectance (~370-400 nm), although the latter would need to be tested experimentally. In the Sandhill Cranes *Grus canadensis*, for which the SWS1 pigment of a closely related *G. americana* species has a λ_{max} at 404 nm (Porter et al., 2014), night collisions with power lines decreased by 98% after introducing UV lamps emitting short wavelengths (380-390 nm) on power poles (Dwyer et al., 2019), suggesting some UV sensitivity, similarly to the black grouse. Although black grouse are mainly diurnal and their flight behaviour differs from cranes, increased UV-contrast could be considered in future modelling or field studies to assess their perception against natural backgrounds (Baasch et al., 2022), and under varying natural environmental light.

Chromatic contrasts and spectral sensitivity are thus important to consider in collision contexts (Fernández-Juricic et al., 2011, Zheng et al., 2022), and greater differences in the reflectance spectra of spatially adjacent materials correspond to higher internal contrasts, which several visual markers readily possess, such as the *crocfast*, *flags* and *firefly* designs (Figure 8). In line with our observations, high-contrast striped coloured patterns have recently been shown to reduce bird approaches on wind turbines, interestingly possibly due to a resemblance with unattractive aposematic patterns (Hancock et al., 2025).

In addition to chromatic contrasts, luminance is a highly reliable parameter across different light levels (Land & Nilsson, 2012) and at longer distance because the achromatic spatial resolution is generally higher than the chromatic one (Lind & Kelber, 2011, Potier et al., 2018b). A high internal contrast would both increase visual discrimination against different types of background and improve detection under variable light conditions. Finally, since birds rely on their binocular field to assess the direction of travel and time to contact with an object in their flight path, two adjacent visual makers should be just visible in the bird's binocular field

(Martin, 2022). In the case of the black grouse, adjacent markers should be placed no further
apart than 17 m and have a minimal width of 142 mm to ensure reliable continuous perception
while in flight. This study provides valuable sensory insights applied to the issue of black grouse
collisions on aerial anthropogenic infrastructures. To robustly link these visual sensory
mechanisms to collision-related mortality will ultimately require field-based ecological
validation of cable detection behaviour with and without visual markers.

Ethics

767 Ethical approval for the handling and restraint of birds was granted under the permit number
768 APAFIS# 31775-31775-2021041311196892 v5.

Data accessibility

770 All data are available as electronic supplementary materials (SI file) accompanying this
771 manuscript or can be accessed via Figshare https://figshare.com/s/dc412ea22f2eca8ff869
772 (Datasets 1 to 4).

Conflict of interest declaration

774 The authors declare no competing interests.

Funding

This study was funded by the Vanoise National Parc (VNP) as part of a European project
entitled POIA BirdSki, with the assistance of the European Union and the National Agency for
Cohesion of Territory under the Interregional Convention of the Alps massif, and in partnership
with ASTERS-CEN74 and the Mountain Galliformes Observatory (OGM), with support from
the FNADT – Alps Massif (National Fund for Territorial Planning and Development), and with
research grants from the Swedish Research Council (VR-2020-05107) and the Belgian F.R.S-
FNRS (MISU F.6002.24) to MAL. JML is supported by a MISU grant from the FRS-FNRS
(F.6002.22).

Acknowledgements

785 The authors thank Frank Grosemans for permission to access black grouse individuals, Pascal
786 Barla for expertise on spectral rays, the Fédération des Chasseurs de Savoie (FDC73), Catherine
787 Desnos and Pascale Malchiodi for logistical and technical assistance, and two anonymous

References

Alerstam, T., Rosén, M., Bäckman, J., Ericson, P. G. P. & Hellgren, O. 2007. Flight Speeds among Bird Species: Allometric and Phylogenetic Effects. *PLOS Biology* **5**: e197.

Baines, D. & Summers, R. W. 1997. Assessment of Bird Collisions with Deer Fences in Scottish Forests. *Journal of Applied Ecology* **34**: 941-948.

Bech, N., Barbu, C. M., Quéméré, E., Novoa, C., Allienne, J. F. & Boissier, J. 2013. Pyrenean ptarmigans decline under climatic and human influences through the Holocene. *Heredity* **111**: 402-409.

Bech, N., Beltran, S., Boissier, J., Allienne, J., Resseguier, J. & Novoa, C. 2012. Bird mortality related to collisions with ski-lift cables: do we estimate just the tip of the iceberg? *Animal Biodiversity and Conservation* **35**: 95-98.

Bernard, G. 1979. Red-absorbing Visual Pigment of Butterflies. *Science* **203**: 1125-1127.

Bernardino, J., Bevanger, K., Barrientos, R., Dwyer, J. F., Marques, A. T., Martins, R. C., Shaw, J. M., Silva, J. P. & Moreira, F. 2018. Bird collisions with power lines: State of the art and priority areas for research. *Biological Conservation* **222**: 1-13.

Bevanger, K. 1995. Estimates and Population Consequences of Tetraonid Mortality Caused by Collisions with High Tension Power Lines in Norway. *Journal of Applied Ecology* **32**: 745-753.

Bevanger, K. 1998. Biological and conservation aspects of bird mortality caused by electricity power lines: a review. *Biological Conservation* **86**: 67-76.

Blary, C. L. M., Duriez, O., Bonadonna, F., Mitkus, M., Caro, S. P., Besnard, A. & Potier, S. 2024. Low achromatic contrast sensitivity in birds: a common attribute shared by many phylogenetic orders. *Journal of Experimantal Biology* **227**: jeb246342.

Bowmaker, J. K., Heath, L. A., Wilkie, S. E. & Hunt, D. M. 1997. Visual pigments and oil droplets from six classes of photoreceptor in the retinas of birds. *Vision Research* **37**: 2183-2194.

Bowmaker, J. K., Kovach, J. K., Whitmore, A. V. & Loew, E. R. 1993. Visual pigments and oil droplets in genetically manipulated and carotenoid deprived quail: A microspectrophotometric study. *Vision Research* **33**: 571-578.

Brainard, D. H. 1997. The Psychophysics Toolbox. *Spatial Vision* **10**: 433-6.

Bryant, D. M., Johnson, K., Tia, D., Tickle, T., Couger, M. B., Payzin-Dogru, D., Lee, T., Leigh, N., Kuo, T., Davis, F., Bateman, J., Bryant, S., Guzikowski, A., Tsai, S., Coyne, S., Ye, W., Freeman, R. J., Peshkin, L., Tabin, C., Regev, A., Haas, B. & Whited, J. 2017. A Tissue-Mapped Axolotl De Novo Transcriptome Enables Identification of Limb Regeneration Factors. *Cell reports* **18**: 762-776.

Buffet, N. & Dumont-Dayot, E. (2013) Bird collisions with overhead ski-cables: a reducible source of mortality. In: *The Impacts of Skiing and Related Winter Recreational Activities on Mountain Environments*. pp. 123-136. Eureka select.

Cantlay, J. C., Martin, G. R., McClelland, S. C., Potier, S., O'Brien, M. F., Fernández-Juricic, E., Bond, A. L. & Portugal, S. J. 2023. Binocular vision and foraging in ducks, geese and swans (Anatidae). *Proceedings of the Royal Society B: Biological Sciences* **290**: 20231213.

Carvalho, L. S., Cowing, J. A., Wilkie, S. E., Bowmaker, J. K. & Hunt, D. M. 2007. The molecular evolution of avian ultraviolet- and violet-sensitive visual pigments. *Molecular Biology and Evolution* **24**: 1843-52.

Caves, E. M., Fernández-Juricic, E. & Kelley, L. A. 2024. Ecological and morphological correlates of visual acuity in birds. *Journal of Experimental Biology* **227**: jeb246063.

Coimbra, J. P., Nolan, P. M., Collin, S. P. & Hart, N. S. 2012. Retinal Ganglion Cell Topography and Spatial Resolving Power in Penguins. *Brain Behavior and Evolution* **80**: 254-268.

Cooney, C. R., Varley, Z. K., Nouri, L. O., Moody, C. J. A., Jardine, M. D. & Thomas, G. H.
2019. Sexual selection predicts the rate and direction of colour divergence in a large
avian radiation. *Nature Communications* **10**: 1773.

Corona, M. & Dos Santos, V. M. (2023) Evolution du parc des câbles aériens et cas de
percussion de l'avifaune recensés au sein des domaines skiables des Alpes. pp. 188.

Cuthill, I. C., Partridge, J. C., Bennett, A. T. D., Church, S. C., Hart, N. S. & Hunt, S. (2000)
Ultraviolet Vision in Birds. In: *Advances in the Study of Behavior*, Vol. 29 (Slater, P. J.
B., Rosenblatt, J. S., Snowdon, C. T. & Roper, T. J., eds.). pp. 159-214. Academic Press.

De Valois, R. L., Morgan, H. & Snodderly, D. M. 1974. Psychophysical studies of monkey
Vision-III. Spatial luminance contrast sensitivity tests of macaque and human observers.
Vision Research **14**: 75-81.

Dos Santos, V. M., Bernard-Laurent, A., Menoni, C., Montadert, M., Novoa, C., Amblard, B.,
Gabrieli, J. & Milhau, B. (2021) Suivi des galliformes de montagnes alpins et
pyrénéens. Bilan de la décennie 2010-2019. (OGM, ed.). pp. 64.

Drewitt, A. L. & Langston, R. H. 2008. Collision effects of wind-power generators and other
obstacles on birds. *Ann N Y Acad Sci* **1134**: 233-66.

Dwyer, J., Pandey, A., McHale, L. & Harness, H. 2019. Near-ultraviolet light reduced Sandhill
Crane collisions with a power line by 98%. *The Condor* **121**: 1-10.

Fernández-Juricic, E., Gaffney, J., Blackwell, B. F. & Baumhardt, P. 2011. Bird strikes and
aircraft fuselage color a correlational study. *Human-Wildlife Interactions* **5**: 224-234.

Ferrer, M., Morandini, V., Baumbusch, R., Muriel, R., De Lucas, M. & Calabuig, C. 2020.
Efficacy of different types of "bird flight diverter" in reducing bird mortality due to
collision with transmission power lines. *Global Ecology and Conservation* **23**: e01130.

Frick, H., Chow, F., Kuhn, M., Mahoney, M., Silge, J. & Wickham, H. (2022) Rsample:
General Resampling Infrastructure. R package version 1.1.1. pp.

Garber, M., Grabherr, M., Guttman, M. & Trapnell, C. 2011. Computational methods for
transcriptome annotation and quantification using RNA-seq. *Nature* **8**: 421-423.

Govardovskii, V., Fyhrquist, N., Reuter, T., Kuzmin, D. & Donner, K. 2000a. In search of the
visual pigment template. *Visual Neurosciences* **17**: 509-528.

Govardovskii, V. I., Fyhrquist, N., Reuter, T., Kuzmin, D. G. & Donner, K. 2000b. In search
of the visual pigment template. *Vis Neurosci* **17**: 509-28.

Guillemain, M. & Fritz, H. 2002. Temporal variation in feeding tactics: exploring the role of
competition and predators in wintering dabbling ducks. *Wildlife Biology* **8**: 81-90.

Hagen, J. F. D., Roberts, N. S. & Johnston, R. J. 2023. The evolutionary history and spectral
tuning of vertebrate visual opsins. *Developmental Biology* **493**: 40-66.

Hall, M. I. & Ross, C. F. 2007. Eye shape and activity pattern in birds. *Journal of Zoology* **271**:
437-444.

Hambálková, L., Cukor, J., Brynychová, K., Ševčík, R., Vacek, Z., Vacek, S., Skoták, V.,
Linda, R. & Andersen, O. 2024. Black grouse (Lyrurus tetrix) population status, reasons
for decline and potential conservation measures from Western and Central Europe to
Fennoscandia: a literature review. *Frontiers in Ecology and Evolution* **Volume 12 -**
2024.

Hancock, G., Lehtonen, H., Brown, T., Ejjite, A., Nokelainen, O., Mappes, J. & Winters, S.
2025. Biologically inspired warning patterns deter birds from wind turbines. *bioRxiv*.

Hart, N. S. 2001. The visual ecology of avian photoreceptors. *Progress in Retinal Eye Research*
20: 675-703.

Hart, N. S. & Hunt, D. M. 2007. Avian visual pigments: characteristics, spectral tuning, and
evolution. *The American Naturalist* **169**: S7-26.

Hart, N. S., Partridge, J. C. & Cuthill, I. C. 1999. Visual pigments, cone oil droplets, ocular media and predicted spectral sensitivity in the domestic turkey (Meleagris gallopavo). *Vision Res* **39**: 3321-8.

Hart, N. S. & Vorobyev, M. 2005. Modelling oil droplet absorption spectra and spectral sensitivities of bird cone photoreceptors. *J Comp Physiol A Neuroethol Sens Neural Behav Physiol* **191**: 381-92.

Hauser, F. & Chang, B. 2017. Insights into visual pigment adaptation and diversity from model ecologcial and evolutionary systems. *Current opinion in genetics & development* **47**: 110-120.

Hauser, F. E., van Hazel, I. & Chang, B. S. W. 2014. Spectral tuning in vertebrate short wavelength-sensitive 1 (SWS1) visual pigments: Can wavelength sensitivity be inferred from sequence data? *Journal of Experimental Zoology* **322**: 529-539.

Hirsch, J. 1982. Falcon visual sensitivity to grating contrast. *Nature* **300**: 57-58.

Kelber, A. 2019. Bird colour vision - from cones to perception. *Current opinion in Behavioral Sciences* **30**: 34-40.

Kiltie, R. A. 2000. Scaling of visual acuity with body size in mammals and birds. *Functional Ecology* **14**: 226-234.

Kuhn, M. & Wickham, H. (2020) Tidymodels: a collection of packages for modeling and machine learning using tidyverse principles. . pp.

Lamond, A. E. R., Potier, S., Fontaine, L., Martin, G. R. & Portugal, S. J. 2025. The visual impediment of cranial ornamentation in male *Chrysolophus* pheasants. *Biology Letters* **21**: 20250405.

Land, M. F. & Nilsson, D. E. 2012. *Animal eyes*. Oxford, Oxford

Langmead, B. & Salzberg, S. L. 2012. Fast gapped-read alignment with Bowtie 2. *Nature Methods* **9**: 357-9.

Liénard, M. A., Bernard, G. D., Allen, A., Lassance, J., Song, S., Childers, R., Yu, N., Ye, D., Stephenson, A., Valencia-Montoya, W., Salzman, S., Whitaker, M., Calonje M, Zhang, F. & Pierce, N. 2021. The evolution of red colour vision is linked to coordinated rhodopsin tuning in lycaenid butterflies. *PNAS* **118** e2008986118.

Liénard, M. A., Valencia-Montoya, W. A. & Pierce, N. E. 2022. Molecular advances to study the function, evolution and spectral tuning of arthropod visual opsins. *Philosophical Transactions of the Royal Society B: Biological Sciences* **377**: 20210279.

Lind, O. & Kelber, A. 2011. The spatial tuning of achromatic and chromatic vision in budgerigars. *Journal of Vision* **11**: 2-2.

Lind, O., Sunesson, T., Mitkus, M. & Kelber, A. 2012. Luminance-dependence of spatial vision in budgerigars (*Melopsittacus undulatus*) and Bourke's parrots (*Neopsephotus bourkii*). *Journal of Comparative Physiology A* **198**: 69-77.

Lindén, H. & Väisänen, R. A. 1986. Growth and Sexual Dimorphism in the Skull of the Capercaillie *Tetrao urogallus*: A Multivariate Study of Geographical Variation. *Ornis Scandinavica (Scandinavian Journal of Ornithology)* **17**: 85-98.

Lisney, T. J., Iwaniuk, A. N., Bandet, M. V. & Wylie, D. R. 2012a. Eye Shape and Retinal Topography in Owls (Aves: Strigiformes). *Brain Behavior and Evolution* **79**: 218-236.

Lisney, T. J., Iwaniuk, A. N., Kolominsky, J., Bandet, M. V., Corfield, J. R. & Wylie, D. R. 2012b. Interspecifc variation in eye shape and retinal topography in seven species of galliform bird (Aves: Galliformes: Phasianidae). *Journal of Comparative Physiology A* **198**: 717-31.

Loss, S. R., Will, T., Loss, S. S. & Marra, P. P. 2014. Bird–building collisions in the United States: Estimates of annual mortality and species vulnerability. *The Condor: Ornithological Applications* **116**: 8-23.

Machtans, C., Wedeles, C. & Bayne, E. 2013. A First Estimate for Canada of the Number of Birds Killed by Colliding with Building Windows. *Avian Conservation and Ecology* **8**.

Marques, A. T., Batalha, H., Rodrigues, S., Costa, H., Pereira, M. J. R., Fonseca, C., Mascarenhas, M. & Bernardino, J. 2014. Understanding bird collisions at wind farms: An updated review on the causes and possible mitigation strategies. *Biological Conservation* **179**: 40-52.

Martin, G. 2011a. Understanding bird collisions with man-made objects: a sensory ecology approach. *Ibis* **153**: 239-254.

Martin, G. 2017a. *The sensory ecology of birds*. Oxford University Press.

Martin, G. & Portugal, S. 2011. Differences in foraging ecology determine variation in visual fields in ibises and spoonbills (Threskiornithidae). *Ibis* **153**: 662-671.

Martin, G., Portugal, S. & Murn, C. 2012. Visual fields, foraging and collision vulnerability in Gyps vultures. *Ibis* **154**: 626-631.

Martin, G. R. 1984. The visual fields of the tawny owl, *Strix aluco* L. *Vision Research* **24**: 1739-1751.

Martin, G. R. 1986. Total panoramic vision in the mallard duck, *Anas platyrhynchos*. *Vision Research* **26**: 1303-5.

Martin, G. R. 1994. Visual fields in woodcocks *Scolopax rusticola* (Scolopacidae; Charadriiformes). *Journal of Comparative Physiology A* **174**: 787-793.

Martin, G. R. 2007. Visual fields and their functions in birds. *Journal of Ornithology* **148**: 547-562.

Martin, G. R. 2009. What is binocular vision for? A birds' eye view. *Journal of Vision* **9**: 14-14.

Martin, G. R. 2017b. What Drives Bird Vision? Bill Control and Predator Detection Overshadow Flight. *Front Neurosci* **11**: 619.

Martin, G. R. 2022. Vision-Based Design and Deployment Criteria for Power Line Bird Diverters. *Birds* **3**: 410-422.

Martin, G. R. & Banks, A. N. 2023. Marine birds: Vision-based wind turbine collision mitigation. *Global Ecology and Conservation* **42**: e02386.

Martin, M. 2011b. Cutadapt removes adapter sequences from high-throughput sequencing reads. *Embnet Journal* **17**: 3.

Matysek, M., Gwiazda, R., Figarski, T., Zięba, F., Klimecki, M., Mateja, R., Krzan, P. & Piątek, G. 2021. What habitat parameters are important for the survival of ground nests in mountain forests? Recommendations for protection of Hazel Grouse *Tetrastes bonasia* based on an experiment with artificial nests. *Bird Study* **68**: 258-266.

Miquet, A. 1990. Mortality in black grouse Tetrao tetrix due to elevated cables. *Biological Conservation* **54**: 349-355.

Nachtigall, P. G., Grazziotin, F. G. & Junqueira-de-Azevedo, I. L. M. 2021. MITGARD: an automated pipeline for mitochondrial genome assembly in eukaryotic species using RNA-seq data. *Briefings in Bioinformatics* **22**: bbaa429.

O'Carroll, D. C. & Wiederman, S. D. 2014. Contrast sensitivity and the detection of moving patterns and features. *Philos Trans R Soc Lond B Biol Sci* **369**: 20130043.

O'Rourke, C. T., Hall, M. I., Pitlik, T. & Fernández-Juricic, E. 2010. Hawk Eyes I: Diurnal raptors differ in visual fields and degree of eye movement. *PLOS ONE* **5**: e12802.

Odeen, A. & Håstad, O. 2010. Pollinating birds differ in spectral sensitivity. *Journal of Comparative Physiology A* **196**: 91-6.

OGM (2010) https://www.observatoire-galliformes-montagne.com/Tetras-lyre.html. Vol. 2025. pp.

Outomuro, D., Söderquist, L., Johansson, F., Ödeen, A. & Nordström, K. 2017. The price of
looking sexy: visual ecology of a three-level predator–prey system. *Functional Ecology*
31: 707-718.
Patthey, P., Wirthner, S., Signorell, N. & Arlettaz, R. 2008. Impact of outdoor winter sports on
the abundance of a key indicator species of alpine ecosystems. *Journal of Applied*
Ecology **45**: 1704-1711.
Porter, M. L., Kingston, A. C., McCready, R., Cameron, E. G., Hofmann, C. M., Suarez, L.,
Olsen, G. H., Cronin, T. W. & Robinson, P. R. 2014. Characterization of visual
pigments, oil droplets, lens and cornea in the whooping crane Grus americana. *J Exp*
Biol **217**: 3883-90.
Portugal, S. J., Murn, C. P. & Martin, G. R. 2017. White-headed Vulture Trigonoceps
occipitalis shows visual field characteristics of hunting raptors. *Ibis* **159**: 463-466.
Potier, S., Bonadonna, F., Kelber, A. & Duriez, O. 2016. Visual acuity in an opportunistic
raptor, the chimango caracara (*Milvago chimango*). *Physiology and Behaviour* **157**:
125-8.
Potier, S., Bonadonna, F., Martin, G. R., Isard, P.-F., Dulaurent, T., Mentek, M. & Duriez, O.
2017. Visual configuration of two species of Falconidae with different foraging
ecologies. *Ibis* **160**: 54-61.
Potier, S., Duriez, O., Cunningham, G. B., Bonhomme, V., O'Rourke, C., Fernández-Juricic, E.
& Bonadonna, F. 2018a. Visual field shape and foraging ecology in diurnal raptors.
Journal of Experimental Biology **221**: jeb177295.
Potier, S., Mitkus, M. & Kelber, A. 2018b. High resolution of colour vision, but low contrast
sensitivity in a diurnal raptor. *Proceedings of the Royal Society B: Biological Sciences*
285: 20181036.
Potier, S., Mitkus, M. & Kelber, A. 2020. Visual adaptations of diurnal and nocturnal raptors.
Seminars in Cell & Developmental Biology **106**: 116-126.
Potier, S., Roulin, A., Martin, G. R., Portugal, S. J., Bonhomme, V., Bouchet, T., de Romans,
R., Meyrier, E. & Kelber, A. 2023. Binocular field configuration in owls: the role of
foraging ecology. *Proceedings of the Royal Society B: Biological Sciences* **290**:
20230664.
Quast, C., Pruesse, E., Yilmaz, P., Gerken, J., Schweer, T., Yarza, P., Peplies, J. & Glöckner,
F. O. 2013. The SILVA ribosomal RNA gene database project: improved data
processing and web-based tools. *Nucleic Acids Research* **41**: D590-6.
Rosenberg, K. V., Dokter, A. M., Blancher, P. J., Sauer, J. R., Smith, A. C., Smith, P. A.,
Stanton, J. C., Panjabi, A., Helft, L., Parr, M. & Marra, P. P. 2019. Decline of the North
American avifauna. *Science* **366**: 120-124.
Schmid, K. L. & Wildsoet, C. F. 1998. Assessment of visual acuity and contrast sensitivity in
the chick using an optokinetic nystagmus paradigm. *Vision Research* **38**: 2629-2634.
Schneider, C. A., Rasband, W. S. & Eliceiri, K. W. 2012. NIH Image to ImageJ: 25 years of
image analysis. *Nature Methods* **9**: 671-675.
Segelbacher, G., Manel, S. & Tomiuk, J. 2008. Temporal and spatial analyses disclose
consequences of habitat fragmentation on the genetic diversity in capercaillie (Tetrao
urogallus). *Mol Ecol* **17**: 2356-67.
Shi, Q. & Stell, W. K. 2013. Die Fledermaus: regarding optokinetic contrast sensitivity and
light-adaptation, chicks are mice with wings. *PLoS One* **8**: e75375.
Siitari, H., Viitala, J. & Hovi, M. 2002. Behavioural evidence for ultraviolet vision in a tetraonid
species – foraging experiment with black grouse *Tetrao tetrix*. *Journal of Avian Biology*
33: 199-202.

Simão, F. A., Waterhouse, R. M., Ioannidis, P., Kriventseva, E. V. & Zdobnov, E. M. 2015.
BUSCO: assessing genome assembly and annotation completeness with single-copy
orthologs. *Bioinformatics* **31**: 3210-2.
Song, L. & Florea, L. 2015. Rcorrector: efficient and accurate error correction for Illumina
RNA-seq reads. *GigaScience* **4**: 48.
Stavenga, D. G. & Wilts, B. D. 2014. Oil droplets of bird eyes: microlenses acting as spectral
filters. *Philos Trans R Soc Lond B Biol Sci* **369**: 20130041.
Wagner, H., Pappe, I. & Nalbach, H. O. 2022. Optocollic responses in adult barn owls (*Tyto*
furcata). *Journal of Comparative Physiology A* **208**: 239-251.
Watson, A. & Moss, R. 2004. Impacts of ski-development on ptarmigan (Lagopus mutus) at
Cairn Gorm, Scotland. *Biological Conservation* **116**: 267-275.
Wu, Y., Hadly, E. A., Teng, W., Hao, Y., Liang, W., Liu, Y. & Wang, H. 2016. Retinal
transcriptome sequencing sheds light on the adaptation to nocturnal and diurnal
lifestyles in raptors. *Scientific Reports* **6**: 33578.
Zheng, K., Liang, D., Wang, X., Han, Y., Griesser, M., Liu, Y. & Fan, P. 2022. Contrasting
coloured ventral wings are a visual collision avoidance signal in birds. *Proc Biol Sci*
289: 20220678.
1050