spEMO: Exploring the Capacity of Foundation Models for Analyzing Spatial Multi-Omic Data

Tianyu Liu[1,2], Tinglin Huang[3], Rex Ying[3], Hongyu Zhao[1,2*]

[1]Interdepartmental Program in Computational Biology & Bioinformatics, Yale University, New Haven, 06511, CT, USA.
[2]Department of Biostatistics, Yale University, New Haven, 06511, CT, USA.
[3]Department of Computer Science, Yale University, New Haven, 06511, CT, USA.

*Corresponding author(s). E-mail(s): hongyu.zhao@yale.edu;
Contributing authors: tianyu.liu@yale.edu; tinglin.huang@yale.edu; rex.ying@yale.edu;

Abstract

Several pathology foundation models have been designed by pre-training a model with pathology information for disease-centered downstream applications. These models have been treated as a breakthrough for pathology research. Along with pathology images, we can also measure spatial multi-omic expression levels for each spot, which provide additional information for understanding the spatial context. However, we still lack an effective tool to leverage the contributions of these technologies. Here, we present a novel artificial intelligence system, named as spEMO, to incorporate the embeddings from pathology foundation models and large language models to analyze spatial multi-omic data. Overall, spEMO outperforms foundation models trained only with single-modality data through introducing better representations. Our method also explores different approaches to combining information from various sources and shows the contributions of integrating external embedding information to handle different novel downstream applications, including spatial domain identification, spot-type prediction, whole-slide disease-state prediction and interpretation, multi-cellular interaction inference, and medical report generation. Furthermore, we define a new task of multi-modal alignment to assess the information retrieval ability of pathology foundation models. This task offers a new direction to evaluate the quality of foundation models and gain insights for model development.

Keywords: Spatial Multi-Omic Data Analysis, Foundation Model, Spatial Domain Identification, Spot-Type Prediction, Disease-Associated Prediction, Cell-Cell Interaction, Medical Report Generation.

1 Introduction

Pathology analysis for needs to accomplish various tasks, and it is challenging for a pathologist to make the right decision based on the limited and complex data [1–4]. Recently, pathologists have started using machine-learning-based methods to assist pathology analysis [5, 6], but models trained with limited data and knowledge might not provide enough support [7]. Therefore, efforts have been made to collect large-scale pathology data, demonstrated by several pathology foundation models (PFM) pre-trained with pathology image data [8–11]. In addition, pathologists also collect multimodal information, for example, gene expression profiles from spatial transcriptomics [12, 13] and biological feature text descriptions [14], to make a better decision together with image data. Furthermore, the image feature from PFMs might also help the analysis of other modality data, presenting another potential use of these foundation models.

A foundation model (FM) is defined as a model pre-trained with large-scale datasets and is capable of handling various downstream tasks [15]. There exist both general FMs such as ChatGPT [16] and Claude [17], and domain-specific FMs such as UNI [8] and scGPT [18], defined by the knowledge scope used for model training. Specifically, in pathology, researchers can pre-train a PFM based on various pathology images and generate robust representations of different images, and perform various experiments to investigate the generalization ability of such representation. Moreover, spatial transcriptomics is closely linked with these pathology images, as the process of sequencing gene expression in the spatial context always involves the screening of the background tissue slide. By collecting large-scale spatial transcriptomic data, people can also train an FM for analyzing the gene expression patterns across different spatial positions of spots [19, 20]. Recently, researchers have developed multi-omic spatial sequencing to simultaneously measure different omic data (including genes, proteins, chromatin accessibility, etc.) from one slide [21, 22], which can further enrich the modality for describing the cell activity at the spatial level. Considering the possibility of joint spatial multi-omic features and pathological images, we believe that it is feasible to design a system to achieve this goal.

Although it has been shown that training a PFM can enhance the image classification accuracy [8] as well as gene expression prediction performance [23], the necessity of having an FM trained based on transcriptomics or other omic data is not resolved yet. Several papers [24–27] discussed the limitations of FMs pre-trained with single-cell transcriptomics, e.g., their inferior performance to simple linear regression in certain tasks. Since the noise level of sequencing data is high and difficult to eliminate, pre-training another FM with such data is extremely challenging. Fortunately, recently developed methods such as GenePT [28] and scELMo [29] open a new direction by utilizing embeddings from FMs trained with other modalities to analyze single-cell

multi-omic data, and their experiments demonstrate that embeddings generated based on external biology knowledge can help analyze such data and gain biological insights. Since we have not seen such methods designed for analyzing spatial data, especially spatial transcriptomic data, we explore the capacity of such design for understanding the spatial context of biological features.

Here, we introduce a novel system for **Sp**atial Multi-Modal Data Analysis with **E**mbeddings from Various Foundation **Mo**dels, known as spEMO. As an extension of scELMo, spEMO inherits its ability to use embeddings from LLMs as one external information and enriches the library of prior biology information by integrating the embeddings from whole slide images (WSIs) with the help of PFMs. spEMO not only combines the embeddings from other FMs with spatially-resolved sequencing data as a zero-shot learning framework, but it can also introduce such embeddings into task-specific experts to improve the ability to handle different downstream tasks. We demonstrate that spEMO improves the performance of spatial domain identification, spatial feature extraction, and spot-type prediction for both spatial transcriptomics and spatial multi-omic data, without extra cost. Furthermore, we consider several novel biomedical applications for multi-modal healthcare in this manuscript, including disease-state prediction, multi-cellular interaction inference, and medical report generation, and patch-expression alignment based on spatial transcriptomics. These tasks can be further explored for uncovering the potential of spEMO for novel biology discovery as well as evaluating the quality of image embeddings from PFMs. Overall, we believe that spEMO can define a common paradigm for integrating existing knowledge and using it to analyze new data.

2 Results

Overview of spEMO. spEMO is an artificial intelligence system (AIS) for spatial multi-omic data analysis by integrating external knowledge as embeddings extracted from FMs. We support two different settings of spEMO, known as zero-shot learning [30] design and fine-tuning design [31]. The former framework allows users to directly combine the embeddings from PFMs and LLMs for projecting spatial data into a new space, and the latter framework allows users to integrate embeddings with known methods to enhance their performances. The spot-level embeddings are computed by splitting the whole slide image into several patches with a pre-selected radius. Furthermore, we define and perform several new tasks to demonstrate the power of multi-modal pathology analysis. The overall pipeline of spEMO is summarized in Figures 1 (a) and (b).

spEMO improves spatial domain identification by introducing features with strong spatial correlation. A fundamental challenge of spatial multi-omic data analysis is the identification of spatial domains or niches [32–34]. Such specific patterns are always treated as a specific group of cells with co-localization and thus similar biological functions. Similar to the analysis of single-cell multi-omic data, the naive approach to annotate the spatial domain information is based on principal components (PCs) [35] of expression profiles. Meanwhile, there are methods to improve the accuracy of domain identification with the help of deep learning design but with

Fig. 1 The landscape of spEMO. (a) The zero-shot learning framework of spEMO. Here we introduce embeddings from PFMs and LLMs to help the analysis of spatial multi-omic datasets, by transferring the selected dataset from the expression space to the embedding space. (b) The fine-tuning framework of spEMO. By integrating the image representations and expression profiles to domain-expert methods, spEMO is capable of performing more downstream applications.

little reference to the use of PFMs to address this task. In this work, we hypothesize that the embeddings from PFMs may contribute to accurate domain identification by either combining the spot embeddings with corresponding PCs or integrating the embeddings into the input data of task-specific methods, or both. We considered a dataset consisting of spatial transcriptomic samples from the human brain, known as SpatialLIBD [36, 37]. This dataset contains annotated spatial domain information and is collected through the 10X Genomics Visium platform. We tested the ability of spEMO to identify spatial domains under different settings, shown in Figure 2 (a). The metrics of this task include Normalized Mutual Information (NMI), Adjusted Rand Index (ARI), and Averaged Silhouette Width (ASW). These metrics are widely used in evaluating clustering performance [28, 29, 38], and we averaged them in our comparisons of different methods. Here the default clustering algorithm is Leiden, and all

methods except the series of SC3 [39] and SpaGCN [33] are based on such algorithm. SpaGCN and SC3 are task-specific methods for spatial domain identification and spot clustering. Novae [20] represents using the embeddings from a spatial transcriptomics foundation model for clustering. PCA represents using the PCs for clustering, and spatial represents using spatial locations. LLMemb represents using the embeddings from LLM for clustering, referred from the *wa* mode of scELMo. To select the most suitable PFM for this task, we combined PCs with embeddings from four PFMs, including GPFM [11], UNI [8], GigaPath [10] and Virchow2 [40]. These methods are either novel or reported with good performance in benchmarking analysis [41]. According to Extended Data Figure 1, GPFM is the best setting to generate embeddings for this task, and thus we have PCA+GPFM to represent the concatenation of PCs and GPFM embedding, and SpaGCN+GPFM represents the combination of GPFM embeddings with SpaGCN. We also test the best radius for generating image patches for each spot, shown in Extended Data Figure 2. Since they do not show obvious differences, we select the radius of 112 to match the default setting of a public pathology dataset [41]. Our results show that incorporating the embeddings from GPFM can significantly improve the performance of SpaGCN (p-value=3e-2 based on the Wilcoxon Rank-sum test for NMI scores, p-value=1e-1 based on the Wilcoxon Rank-sum test for Avg scores), and it also surpasses other the settings. It seems that the zero-shot learning setting, known as PCA+GPFM, is not the optimal choice for this task, as its overall performance is worse than others with the exception of PCs. Finally, we visualize the best clustering result in Figure 2 (b), where SpaGCN with embeddings from PFMs identifies regions including WM, L1, L3, and L6.

To understand the reason for such improvement, we further assessed the autocorrelation score between the features of embeddings from GPFM and the spot location. The Moran's I score and Geary's C score are used here for evaluation. These two scores are common metrics for evaluating the auto-correlation level and a higher Moran's I score represents a stronger correlation. The trend in Geary's C score is inversely proportional to the trend in Moran's I score due to differences in the way it is calculated. According to Figure 2 (c), the embeddings from GPFM have stronger features correlating with spatial information than PCs (p-value=2e-3 based on Wilcoxon Rank-sum test for Moran's I scores), and thus they can better describe the spatial pattern in a given sample. We also compared the embeddings from PFMs and traditional image features for this clustering task based on two new Visium datasets (Visium H&E and Visium Fluorescence (Fluo)) from Squidpy [42], and these embeddings also have better performances shown in Extended Data Figures 3 (a) and (b), which further supports our conclusions. Therefore, these results suggest that incorporating image embeddings from PFMs can improve the accuracy of spatial domain identification.

spEMO improves domain identification of multi-omic spatial data. We explored the possibility of using spEMO to improve spatial domain identification for multi-omic datasets. Such data have recently become available through technological advances with few having expert labels. Here we focus on one spatial dataset with measurements of both gene expression profiles and protein information from human lymph node [21] as well as expert annotations [21]. Since this dataset does not contain image information, we consider including gene and protein description embeddings

from LLMs for clustering. Meanwhile, we also consider the performance of using single modality information for clustering, denoted as RNA only and ADT only. As shown in Figure 2 (d), incorporating LLM embeddings can improve the accuracy of spatial domain identification, and the results are even comparable with domain-specific method SpatialGLUE [21]. We also found that the concatenation (LLMemb RNA||ADT) and addition (LLMemb RNA+ADT) of embeddings do not show obvious differences for this task. We further visualize the best clustering result in Figure 2 (e), which shows that spEMO clearly identifies cortex, capsule, and pericapsular adipose tissue.

spEMO can annotate spot types more accurately. Another important task in spatial transcriptomic data analysis is the annotation of spots, either for niche information or cell-type information. Similar to the cell-type annotation task in single-cell transcriptomics analysis, annotation of spot types can also be treated as a multi-label classification task based on training a classifier from the reference spatial datasets and then performing inference based on the testing dataset. Here we utilized both the Visium data from SpatialLIBD and that from Squidpy to test the contribution of image embeddings for this task. First, we tested the effect of different classifiers for spot annotation based on the Visium data from SpatialLIBD under different settings, shown in Figure 4 (a). We found that XGB and LR are the top two classifiers for annotating spot types. However, since XGB meets OOM errors when using the combination of expression features and image embeddings as inputs, it is hard for us to test the contribution of including mode modality data, and thus we finally choose LR as our final choice. The results for the same set of datasets under different input features are shown in Figure 4 (b). This figure shows that using the combination of gene expression profiles from HVGs and image embeddings from UNI has the best performance, which outperformed the choice of only using HVGs (p-value=3e-2 based on Wilcoxon Rank-sum test) as well as only using PCs (p-value=5e-8 based on Wilcoxon Rank-sum test) significantly. Moreover, incorporating image embeddings from different PFMs all can improve the annotation performance. Furthermore, increasing the patch radius can also improve the annotation performance, and thus the annotation accuracy may be further improved through the adjustment of patch size.

Our results based on the data from Squidpy are summarized in Extended Data Figures 5 (a) and (b). We found that combining expression profiles from HVGs and image embeddings can improve the prediction performance when the testing dataset is selected as the Visium fluo dataset, which could be explained as the strong relationship between image quality and prediction performance improvement.

spEMO integrates image embeddings for whole-slide disease-associated prediction. Disease diagnosis is a key task for pathology research with success of machine learning for disease prediction based on pathology information [43, 44]. In real data application, we collect training datasets with known disease information and predict the unknown disease state in a new dataset, as a multi-label classification problem. By investigating the disease-state annotation of the HEST dataset [41], we are also interested in the capacity to utilize gene expression information as well as pathology information for disease-state prediction. We first cleaned the disease-state labels and performed qualify control for the HEST dataset, and selected human tissues

Fig. 2 Understanding the contribution of spEMO for spatial domain identification. (a) The evaluation results of different methods for domain identification of spatial transcriptomic datasets. (b) The visualization of clustering performance based on the selected slide. The upper panel is colored by cortical layers, and the lower panel is colored by clustering labels. (c) The evaluation results of different settings for capturing spatial auto-correlated features. (d) The evaluation results of different methods for domain identification of spatial multi-omic datasets. (e) The visualization of clustering performance based on the multi-omic slide. The left panel is colored by expert annotation, and the right panel is colored by clustering labels.

Fig. 3 Visualization of embeddings colored by different metadata. (a) UMAP visualization based on the gene expression profiles colored by disease states (upper panel) and tissues (lower panel). (b) UMAP visualization based on the image embeddings colored by disease states (upper panel) and tissues (lower panel).

for experiments. We selected GPFM for generating image embeddings. We first illustrated the sample-level representation of gene expression levels and image embeddings by performing dimension reduction with UMAP [45], and colored them by different labels, including disease states and tissues. Based on Figures 3 (a) and (b), we found that pseudobulk gene expression matrices and image embeddings convey different information. For example, gene expression profiles captured the heterogeneity of healthy samples brought by tissue differences, while image embedding information helps us distinguish more disease states such as COAD and EPM, which are two subtypes of cancer [46, 47]. Moreover, according to Extended Data Figures 6 (a) and (b), embeddings from pseudobulk gene expression are less affected by batch effect, demonstrated by the comparison based on batch_Average Silhouette Width (ASW) score (0.46 for expression embeddings, and 0.42 for image embeddings). Therefore, the learned embeddings are not driven by batch effect and their distribution is mostly determined by disease-associated signals.

Considering the similarity of samples from the same study, we had two task settings with two levels of difficulty. We denoted the two different cross-validation settings as sample-level cross validation (SampleCV) and study-level cross validation (StudyCV). Based on our assumption, StudyCV is more difficult but closer to the real application scenarios. For both settings, we chose three-fold cross validation. We illustrate the comparisons of different classifiers with gene expression profiles for disease-state prediction in Figure 4, and LR has obviously strong performance in this task. We then

compared different input settings based on the results shown in Figure 4 (b) for the SampleCV mode, and it is clear that only using the image embeddings with LR could also have good performances. If we combine gene expression profiles and image embeddings as input, the LR model will be further boosted. Moreover, we can also improve the combination setting with the Oversampling algorithm (RandomOverSample) [48] shown in the given figure, and it outperforms the pseudobulk setting significantly (p-value=0.0025 based on Wilcoxon Rank-sum test). The selected method MultiMIL based on multi-instance learning did not perform well in this task, which could be caused by overfiting or the noise level in the training dataset. Therefore, image embeddings can help build a classifier with higher accuracy in identifying the disease states of spatial transcriptomic samples. To further interpret the prediction performances after introducing the image embeddings with PFMs, we show the confusion matrix of different validation sets based on the best setting in Figure 4 (c). According to this figure, our method can successfully capture the correct disease-state information with a relatively large sample size. For some diseases with a small number of samples (for example, GBM and PPAD), our method was more error prone, which was limited by the diversity of training data. Therefore, we believe that it is important to sequence more spatial transcriptomic samples with such diseases to build a more accurate classifier. We also visualize the results for StudyCV in Extended Data Figure 7, which did not show significant improvement by integrating the image information with expression profiles. To explore the possibility of enhancing model performance with different sampling designs, we considered the oversampling and undersampling approaches [48] to address the label imbalance problem in the training dataset, and the corresponding results are shown in Extended Data Figures 8 (a) and (b) for the SampleCV and StudyCV settings. However, the undersampling approach cannot contribute to performance improvement, while both approaches cannot significantly improve the model performance under the StudyCV setting. Therefore, there is still room for developing a better classifier. We finally test if we can use a voting ensemble to perform prediction rather than constructing the inputs by concatenating gene expression profiles with image embeddings, and the results are shown in Extended Data Figures 9 (a) and (b). We did not find obvious difference between the default setting and the voting setting, and thus our selection for model construction may be optimal.

Furthermore, inspired by [49], we explored the capacity of using spEMO to infer drug response at the individual level based on different omics. Previous methods for drug response prediction all start from expression profiles only [49–51], while in this section we utilized spEMO to predict the drug responses for each patient based on the WSI information. We utilized the dataset from a breast cancer cohort with trastuzumab as the treatment. In Extended Data Figure 10 (a), we performed clustering based on both gene expression information (GEX) as well as WSI embeddings encoded by GPFM (spEMO), and we found that the latter option has better clustering performance. The advantages of using image embeddings are also reflected in the results of prediction evaluation, shown in Extended Data Figure 10 (b). Details of our method and sample split are summarized in the Methods section. Therefore, we demonstrated that spEMO can also provide novel insights for understanding the heterogeneity of drug responses.

Fig. 4 Results of utilizing image embeddings for possibly improving disease-state prediction. (a) Comparisons of different classifiers under the SampleCV mode using selected metrics. (b) Comparisons of different input settings under the SampleCV mode using selected metrics. (c) The confusion matrices of all validation sets under the SampleCV mode. (d) The C-index comparison across different input settings for survival prediction. (e) The training loss curves of survival prediction between two modes with or without image embeddings.

Finally, we also found that introducing novel features such as image embeddings can help in predicting the survival information and further enhancing survival analysis [52], demonstrated through the analysis of The Cancer Genome Atlas (TCGA) data [53]. Here we collected ~ 900 samples from the cancer-type COAD as well as the paired gene expression profiles at the whole-slide level. To demonstrate that using gene expression profiles and embeddings from GPFM can improve model performance in survival prediction, we selected DeepSurv [54] as a baseline model and considered three different input types: only using gene expression (gene), only using image embeddings

(image), and using both gene expression and image embeddings (gene+image). The C-index [55] from the testing dataset with the 10-fold cross-validation is used to evaluate the prediction performance. According to Figure 4 (d), the mode gene+image reached the highest C-index score, and the improvement is significant compared with the mode based only on image embeddings (p-value=0.03 based on the Wilcoxon Rank-sum test). Furthermore, the mode gene+image also had faster convergence speed and reduced the overfiting effect compared with the second-place mode, demonstrated in Figure 4 (e). Therefore, spEMO can also provide prediction enhancement for survival analysis, which further strengthens the importance of our proposed method for clinical practice.

spEMO helps in inferring novel multi-cellular interactions from cancer slides. It has been shown that the patch information can be utilized as features for predicting the gene expression levels in the selected region, which can be treated as a regression problem [56, 57]. However, as far as we know, there are few methods have examined its utility in biological discoveries after predicting gene expression based on patch information. Here, we investigated the possibility of leveraging the predicted gene expression information from images to detect novel cell-cell (or spot-spot) communication and interaction from the COAD samples. Here we collected four COAD samples with WSI information from the HEST dataset, denoted as TENX111, TENX149, TENX148, and TENX147. We then utilized STFlow [56], a state-of-the-art image-to-expression predictor, to generate 50 genes with corresponding expression profiles of the selected samples. The location of each patch is determined by the default setting of the HEST dataset. We first used Moran's I score to detect spatially variable genes and visualize the top-ranked gene by the scores of different samples in Figure 5 (a). According to this figure, STFlow can generate genes with clear spatially expressed patterns, which also correspond to the functions of these genes. Therefore, we could analyze the predicted spatial transcriptomic data for information communication. Next, we chose COMMOT [58] as the tool for analyzing multi-cellular interactions. We followed the tutorial of this tool and computed the Leiden cluster results based on expression profiles and visualized it in Figure 5 (b). According to this figure, some clusters show clear spatially-enriched gene expression levels, such as clusters 2 and 11. Further analysis focused on a newly detected CXCL13-CCR7 interaction. While both genes are known to play key roles in immune responses [59, 60], their combined activity has not previously been reported in COAD. By mapping signal direction onto the spatial transcriptomic data of sample TENX111, we observed strong interaction signals in clusters 2, 9, and 11 (Figure 5 (c)). These findings suggest that CXCL13-CCR7-mediated communication may be particularly active in specific tumor regions and could represent a novel target for immunological investigation. Future experiments focusing on these regions may unveil new opportunities for understanding COAD pathogenesis and for developing targeted therapeutic strategies.

spEMO can generate medical reports with a multi-modal instruction setting. Medical reports are important for doctors to provide effective diagnosis and treatment for patients, and very recent methods [61–63] have demonstrated the capacity of using pathology images to generate corresponding medical reports with pre-trained model based on paired image-text data. However, access to such functions

Fig. 5 The analysis of multicellular interaction based on predicted gene expression profiles. (a) The expression levels of spatially variable genes across the four samples. (b) The Leiden cluster labels computed based on gene expression profiles for sample TENX111. (c) The signal direction of cell-cell interaction CXCL13-CCR7 computed based on the sample TENX111.

for these methods is restricted by hospital policy or specific request, and these methods also not consider gene expression levels as an extra modality in generating medical reports. Therefore, we consider a new task for generating medical reports with foundation models by using both pathology images and gene expression information as prompts. Here we computed the top 10 highly variable genes (HVGs) based on HEST data for different diseases and paired the gene information with pathology images as

well as disease and tissue information to generate the medical report. Our multi-modal agents used in this task are GPT4-o and GPT4-o1 [64]. These models are demonstrated as strong foundation models for interpreting and reasoning with multi-modal inputs. To evaluate the quality of generated reports without real medical reports, we consider two perspectives, including the completeness and consistency of model outputs. We also compared the multi-modal information (denoted as gene+image) with other ablation designs, including only using the whole slide image as input (denoted as image) or HVG information (denoted as gene). Details of our experiment design are discussed in the Methods section.

A good model's output should keep a good balance between report completeness and report consistency, as an extremely long document might lose consistency in report format and disease similarity, while an extremely short document might not offer enough information for doctors or patients. We evaluated the output completeness based on the report length and the output consistency based on the Pearson Correlation Coefficients (PCCs) across text embeddings from the medical reports of different diseases. As the results shown in Figures 6 (a) and (b), the gene+image mode reaches a good balance between the length of generated reports and the consistency of generated reports, and also demonstrated by significance of the statistical tests annotated in the figure legend. Moreover, the generated information for 18 diseases also matches known biomedical documents, with minimal hallucination effect. Furthermore, we found that incorporating multi-modal information can also inspire foundation models to unify the contributions of different modalities, for example, only the gene+image mode links the histopathological findings (highlighted in red) with genetic information (highlighted in purple) for suggesting a medical report, shown in Figures 6 (c)-(e). Moreover, the generated report also did not contain the privacy information of the patients who contributed the samples, which is also an advantage of using foundation models for generating medical reports. We also investigated the stability of the gene+image mode by changing the random seeds with the same multi-modal prompts, with very high correlation of generated reports from different seeds, shown in Extended Data Figure 11. We also tested Prism [62] but its outputs contain incorrect disease labels for all kinds of testing data. Finally, we tried GPT4-o1 to explore the possibility of model enhancement with stronger reasoning ability, and we found that GPT4-o1 could generate more comprehensive information for histopathological image analysis. Since GPT4-o1 does not provide API access for now, we believe that it has a great potential to generate more professional reports and plan to evaluate its performance in the future. The generated reports can be found in Supplementary File 1.

spEMO defines a new metric for evaluating PFMs with extra modality. Training and evaluation are two important steps to developing a good PFM. The traditional approach for evaluating the quality of embeddings from a PFM relies on the reconstruction loss [8, 10], which is indirect and lacks interpretation for its linkage with downstream applications. Recently, HEST [41] considered evaluating the performances of using embeddings from different PFMs to predict the corresponding gene expression at the spot level. However, the predicted results may not be reliable due to the noise level of transcriptomic data [65], and the evaluation conclusions are also

Fig. 6 Evaluations and examples for the medical report generation task. The statistical test used here is two-side Wilcoxon Rank-sum test. (a) Evaluation results of completeness across different diseases (p-value=1.52e-5 for gene+image mode vs. image mode; p-value=7.63e-6 for gene+image mode vs. gene mode; p-value=7.63e-6 for gene mode vs. image mode). (b) Evaluation results of consistency for different modes. Each boxplot contains the PCCs from different disease (p-value=1.21e-23 for gene+image mode vs. image mode; p-value=7.8e-27 for gene+image mode vs. gene mode; p-value=7.84e-27 for gene mode vs. image mode). (c) Medical report example from a COAD sample with gene+image mode. (d) Medical report example from a COAD sample with image mode. (e) Medical report example from a COAD sample with gene mode.

confounded by the choices of classifiers, as demonstrated by our previous analysis for annotation and disease-state prediction. Therefore, inspired by [66], we considered a new evaluation task for the embeddings of PFMs. For a single spot, we consider matching the embeddings of its background image and embeddings from its gene expression vector, as a retrieval task. There are several advantages of considering the setting of multi-modal alignment over predicting gene expression or other downstream tasks used for comparison. First, the encoder can embed the gene expression profiles in a space with lower dimensions and thus reduce the noise level, supported by previous research [67, 68]. Therefore, our assessment of the qualify of image embeddings will be more reliable. Secondly, finding the corresponding spot based on image embeddings can yield key information beyond the gene expression, such as the disease status of the sample, gender, age, and other important metadata [69]. Finally, it has been shown that precise multi-modal alignment for single-cell multi-omic data is difficult [70], and thus we assume that this task will also be challenging for PFMs without pre-training with transcriptomic data to achieve. A more challenging task may also stimulate further PFM research.

Here we utilize the same datasets that are used by HEST for evaluating the performances of gene expression prediction, including a series of spatial transcriptomic samples across different diseases. In total, we have datasets from 10 different diseases. The separation of training and testing datasets is pre-defined for different patients. We trained an encoder with the same architecture for the gene expression profiles to learn gene expression representation, and minimize the distance between the spot-wise similarity based on such representation and the spot-wise similarity based on image embeddings from different PFMs, including GPFM [11], UNI [8], GigaPath [10], Ciga [71], and CTransPath [72]. We included three metrics for evaluating the alignment performance based on the testing dataset, including cross-entropy loss (CEL), top 1 precision (Precision@1), and top 10 precision (Precision@10). Details of methods and metrics are included in the Methods section. Our results are summarized in Table 2, which shows that the best model for this task is UNI, followed by GigaPath and GPFM. Furthermore, none of the methods have a high Precision@1 score, suggesting the task's difficulty. One possible reason is that the spot with similar biological functions might have similar gene expression profiles, which might confuse the model for making the correct decision. However, the low score of Precision@10 further supports the necessity of developing a PFM with a strong ability to identify the linkage between gene expression and image features, which can further enhance the function of similar spot retrieval. Meanwhile, considering the gene expression embeddings from single-cell foundation models [18, 73] or spatial transcriptomic foundation models in the pre-training stage might also contribute to the improvement of model performance in this task.

3 Discussion

The contributions of pathology foundation models (PFMs), as well as large language models (LLMs), have been demonstrated by various applications in their specific

CEL (↓)					
	Ciga	ctranspath	GPFM	UNI	Gigapath
IDC	6.74(.427)	5.99(.457)	4.92(.410)	4.81(.476)	4.68(.440)
PRAD	8.45(.182)	8.38(.162)	7.70(.247)	7.50(.285)	7.43(.323)
PAAD	5.59(.035)	4.95(.034)	4.22(.075)	3.75(.105)	3.77(.140)
SKCM	5.70(.096)	4.46(.089)	3.95(.128)	3.57(.204)	5.47(.296)
COAD	6.11(.049)	5.59(.010)	4.86(.033)	4.26(.105)	4.25(.101)
READ	6.85(.311)	6.57(.291)	5.95(.357)	5.36(.385)	5.47(.296)
CCRCC	8.20(.108)	8.07(.095)	7.38(.091)	7.23(.103)	7.16(.100)
HCC	6.56(.028)	6.59(.015)	6.16(.049)	5.53(.126)	5.72(.042)
LUNG	5.24(.079)	4.35(.123)	3.48(.057)	3.13(.135)	2.93(.182)
LYMPH_IDC	7.42(.047)	7.18(.047)	6.55(.052)	6.07(.036)	6.14(.062)
Average	6.686	6.213	5.517	**5.121**	5.302
Precision@1(%) (↑)					
	Ciga	ctranspath	GPFM	UNI	Gigapath
IDC	1.24(.005)	2.89(.010)	7.55(.023)	7.58(.029)	8.38(.030)
PRAD	0.24(.000)	0.28(.000)	0.67(.001)	1.05(.002)	1.22(.003)
PAAD	2.68(.003)	5.61(.000)	10.95(.009)	16.94(.012)	17.78(.014)
SKCM	3.75(.004)	7.92(.000)	13.30(.018)	20.49(.036)	8.57(.017)
COAD	1.83(.001)	2.96(.001)	6.56(.002)	11.30(.014)	12.11(.005)
READ	1.24(.003)	1.59(.004)	4.25(.011)	8.12(.021)	8.57(.017)
CCRCC	0.18(.000)	0.20(.000)	0.52(.000)	0.63(.000)	0.77(.000)
HCC	1.84(.001)	1.39(.001)	3.29(.003)	8.61(.002)	6.95(.002)
LUNG	3.74(.001)	9.67(.008)	18.35(.009)	24.16(.012)	28.34(.021)
LYMPH_IDC	0.38(.001)	0.61(.000)	1.48(.000)	3.46(.002)	3.21(.001)
Average	1.712	3.312	6.692	**10.234**	9.59
Precision@10(%) (↑)					
	Ciga	ctranspath	GPFM	UNI	Gigapath
IDC	8.93(.031)	17.40(.057)	34.21(.077)	35.52(.095)	38.33(.089)
PRAD	2.01(.005)	2.20(.004)	5.04(.010)	6.57(.015)	7.29(.018)
PAAD	17.69(.003)	30.29(.001)	47.16(.023)	58.32(.024)	58.20(.025)
SKCM	23.86(.008)	38.53(.006)	52.01(.049)	60.55(.048)	30.02(.048)
COAD	12.67(.001)	19.53(.002)	33.34(.013)	46.70(.026)	47.27(.016)
READ	8.41(.027)	10.83(.027)	19.84(.050)	30.83(.066)	30.02(.048)
CCRCC	1.63(.001)	1.80(.001)	4.22(.002)	4.98(.003)	5.60(.004)
HCC	9.22(.002)	8.13(.006)	14.95(.001)	27.67(.018)	23.91(.005)
LUNG	23.99(.013)	42.72(.030)	63.50(.022)	71.30(.023)	75.80(.036)
LYMPH_IDC	3.56(.001)	4.79(.002)	10.17(.002)	17.46(.008)	16.60(.007)
Average	11.197	17.622	28.444	**35.99**	33.304

Table 1 Evaluations of different PFMs for the multi-modal alignment task. Here in the bracket, we report the averaged metric scores and their standard deviation for each dataset, as well as a final average score computed based on all the datasets. The direction of the arrow indicates the relationship between higher scores and better (or lower) performance. ↓ means that a higher score corresponds to worse model performance, and ↑ means a higher score corresponds to better model performance.

domains, e.g., pathology image analysis or text generation. However, we lack effective approaches to transferring such success in extended biological areas, for example, the analysis of spatial transcriptomic datasets or multi-omic spatial datasets. Here we introduce spEMO as a novel system that integrates the embeddings from PFMs and (or) LLMs and the expression profiles from multi-omic spatial datasets to perform joint analysis. In our comprehensive experiments, we demonstrated that spEMO can help with various important tasks in the analysis of spatial domains including

spatial domain identification, spot-type annotation, and disease-state prediction as a new task. Furthermore, we also defined a new task for evaluating different PFMs and motivating further exploration of multi-modal data integration for data-driven discovery.

spEMO has a strong ability to identify the spatial domains for both spatial transcriptomic data and multi-omic spatial data by computing a new spot-level embedding as a combination of expression profiles and embeddings from other FMs. Moreover, we can also utilize spEMO to transfer the spot annotation of known spatial datasets to annotate new datasets, which further supports the importance of using embeddings with prior as a bridge to link multi-modal information with specific biomedical datasets. We also explored the potential of using joint embeddings to predict the disease states from various whole-slide samples and discovered the strong ability of linear classifiers with such embedding to perform prediction in this task. Therefore, spEMO provides reliable features to identify and understand different types of diseases. Furthermore, spEMO can also inspire new discoveries based on uncovering novel cellular interactions, predicting survival information and generating medical reports. Finally, we considered the flawed nature of existing evaluation methods for PFM pre-training and thus proposed a new task for screening out better FMs. For this multi-modal alignment task, although UNI has the best alignment performance, there still exists a large space for the improvement of different PFMs to identify the correct match. Therefore, this challenging task may motivate future developments of PFMs for multi-modal pathology analysis.

There are limitations of the current implementation of spEMO. First, we found that the improvement of introducing information from PFMs might not always obviously improve the model performance, especially in the disease-state prediction task with StudyCV partition. Moreover, the model performance is limited by the size of the training dataset, and thus our approach might not fully uncover the ability of embeddings from multi-modal information.

In summary, we believe that spEMO offers a new direction for analyzing multi-omic data with the help of various FMs. In the future, this system can be further improved by incorporating more powerful FMs as well as considering more meaningful tasks to improve clinical utility and gain. As an example, we still expect to see models focusing on the joint pre-training with pathology image information and gene expression information, which has been explored in recent work [74].

4 Methods

Problem definition. For a typical spatial dataset $(X^{n \times m}, I^{p \times q \times 3})$ after normalization [75] with n spots and m features for the expression profile (X) and $p \times q$ as image (I) dimensions under the RGB setting, our target is to utilize the text description and its embeddings from a large language model as two mapping functions $(\mathcal{LLM}(), \mathcal{LLM}_{e}())$ for processing feature-level metadata information $f^{m \times 1}$, and a pathology function model as another mapping function $(\mathcal{PFM}_{e}())$ for processing image information, to formalize a set of spot embeddings for spatial data analysis.

₄₈₁ Now we define the embedding generation layer of $\mathcal{LLM}()$ as $\mathcal{LLM}_{\mathrm{e}}()$, and the set
₄₈₂ of patches from a whole-slide image as I'_r, where r represents the radius of patches.
₄₈₃ Our spot embeddings can be represented as:

$$e_F = \mathcal{LLM}_{\mathrm{e}}(\mathcal{LLM}(Prompt(F))),$$
$$e_I = \mathcal{PFM}_{\mathrm{e}}(I'_r),$$
$$e_{spots} = Agg(e_F, e_I),$$

₄₈₄ where $Prompt$ is a mapping function that can transfer the name of input data to
₄₈₅ the prompt space F. The prompts can be used as the input of language models.
₄₈₆ The function $Agg()$ represents the method we used to aggregate the embeddings of
₄₈₇ all features for each spot. This setting is different for different downstream tasks, to
₄₈₈ achieve the optimal performance of spEMO. We will discuss the details of different
₄₈₉ downstream applications. Furthermore, we only consider the mode wa of scELMo [29]
₄₉₀ in this manuscript. That is, we divide each entry in a row of X by the sum of its
₄₉₁ row. Considering the spot with index i and the corresponding function for averaging
₄₉₂ $AVG_{wa}()$, we can define this process as:

$$AVG_{wa}(X_i) = \frac{X_i}{sum(X_i)},$$
$$e_{spots} = AVG_{wa}(X)e_f || e_I.$$

₄₉₃ Furthermore, e_I represents the set of image embeddings from a PFM, and $*||*$
₄₉₄ represents the concatenation function. The final generated embeddings e_{spots} can be
₄₉₅ treated as a new representation of each spot and further improve the downstream
₄₉₆ applications related to spatial multi-omic data processing.

₄₉₇ **Spatial domain identification.** For this task, our target is to perform cluster-
₄₉₈ ing based on the spatial transcriptomic dataset and multi-omic spatial dataset. For
₄₉₉ the transcriptomic dataset, we considered the e_{spots} with different sources, including
₅₀₀ PCs (PCA), image embeddings only (GPFM[11]), the concatenation of PCs and image
₅₀₁ embeddings (PCA+GPFM), spatial location only (*Spatial*) and embeddings from
₅₀₂ LLMs only (LLMemb). We also consider the enhanced version of SpaGCN [33] with
₅₀₃ image embeddings (SpaGCN+GPFM), which is generated by changing the adjacency
₅₀₄ matrix computation process of SpaGCN based on the new averaged image embeddings.
₅₀₅ Based on our evaluation, the best setting is SpaGCN+GPFM. To understand the con-
₅₀₆ tribution of image embeddings for this task, we computed the auto-correlation scores
₅₀₇ between spatial location and image embeddings and demonstrated the advantages of
₅₀₈ capturing more spatial-aware features with the help of image embeddings.

₅₀₉ For the multi-omic dataset, since we cannot find the source of image informa-
₅₁₀ tion, we consider the e_{spots} from PCs computed by gene expression (RNA only), PCs
₅₁₁ computed by protein expression (ADT only), embeddings of LLMs with gene text
₅₁₂ description (LLMemb RNA only), embeddings of LLMs with protein text description
₅₁₃ (LLMemb ADT only), the addition of LLMemb RNA only mode and LLMemb ADT
₅₁₄ only mode (LLMemb RNA+ADT), and the concatenation of LLMemb RNA only

mode and LLMemb ADT only mode (LLMemb RNA||ADT). Based on our evaluation, the concatenation of embeddings from LLMs has the best performance.

Spot-type annotation. For this task, our target is to predict the spot types of the testing dataset based on training a classifier. We performed cross validation based on different samples of two datasets to report the variance of metrics. Our classifiers [76, 77] used in this section include LogisticRegression (LR), Support Vector Classifier (SVC), Random Forest Classifier (RF), and XGBClassifier (XGB). Our input data contain both expression level information and embedding level information, including PCs of gene expression profiles (PCs), highly-variable gene expression profiles (HVG), image embeddings (GPFM, default radius is 112), and the concatenation of HVG and image embeddings (HVG+GPFM (x), HVG+UNI (x), HVG+GigaPath (x); where x represents the radius).

Disease-associated prediction. For the disease-state prediction task, we intend to utilize the multi-modal information to predict the disease-state labels of different samples in the testing dataset. Our classifier used in this section includes LR for pseudobulk-level data and MultiMIL [78] for spot-level data. The settings of input data are very similar to the spot-type annotation task. The difference is for the sample-level prediction without the consideration of spot-level heterogeneity, we utilized the averaged gene expression and image embeddings across the spots in one sample to construct the input data, also known as the pseudobulk setting. For the multi-instance learning framework, our input data is defined at the spot level. We considered splitting the training and testing dataset under both sample ids and study ids, denoted as SampleCV and StudyCV, respectively. For the drug response prediction task, we perform dimension reduction based on PCA for both embeddings from PFMs and bulk-level gene expression profiles to obtain the latent representations, and then perform clustering and classification to validate the contributions of PFMs. The predictor used in this step is LR, and we control the ratio of training samples and testing samples as 7:3. For the survival prediction task, we combine expression profiles with image embeddings and utilize DeepSurv [54] for predicting the survival function based on 10 fold cross-validation test and report the metrics under these testing datasets.

Multi-cellular interaction inference. In this task, we infer novel cell-cell interactions based on the predicted gene expression profiles from a whole slide image based on STFlow [56]. The image is divided into several patches and thus the expression profiles are measured for the centroid of each patch. We then utilized COMMOT [58] to compute the strength of the sender gene, receiver gene, and signal direction. The samples are from HEST 1k with tissue as Bowel and disease state as COAD. The training data are from Xenium.

Medical report generation. For this task, we extract the highly variable gene information of cancer samples and rank them by dispersion to obtain a gene list. We then input the gene list, metadata information as well as the whole-slide image into the multimodal foundation models (GPT4-o and GPT4-o1) as prompts to generate medical reports. We select one sample for each disease in HEST 1k for evaluation.

Multi-modal information alignment. For this task, we define a new task as well as a new metric for evaluating the performance of different PFMs. A good set of image embeddings should also match the other modality from the same dataset.

Therefore, we investigate the performance of PFM embeddings in matching the corresponding gene expression profiles from the same spot, across different datasets from HEST [41]. Therefore, we train a new encoder for gene expression profiles to learn the spot representation by minimizing the distance between paired image embeddings and gene expression embeddings in the training dataset. In the testing dataset, we tested the alignment between image embeddings and gene expression embeddings based on various metrics and thus offered a new task for embedding quality assessment.

Evaluation and metrics. In this section, we introduce the metrics we used for evaluating in different tasks and the performances of their corresponding methods.

For spatial domain identification, we included NMI, ARI, ASW and their averaged values (Avg) for the comparison. Details of these metrics, referred from [24, 38], are introduced below:

1. Normalized Mutual Information (NMI): NMI is a score to evaluate the performance of biological information conservation. We compute this score based on the mutual information between the optimal Leiden clusters and the known spatial domains and then take the normalization. $NMI \in (0, 1)$ and higher NMI means better performance.

2. Adjusted Rand Index (ARI): ARI is a score to evaluate the performance of biological information conservation. ARI is used to evaluate the agreement between optimal Leiden clusters and spatial domains. $ARI \in (0, 1)$ and higher ARI means better performance.

3. Average Silhouette Width (ASW): We only have spatial-main ASW (ASW) for this metric. For one spot, ASW calculates the ratio between the inner cluster distance and the intra cluster distance for this spot. Therefore, higher ASW means better biological information conservation. To make all metrics consistent, for ASW, we take the normalization, that is:

$$ASW = \frac{ASW^{raw} + 1}{2}.$$

All metrics (including the averaged score) are in (0,1), and a higher score means better model performance.

For spot-type annotation, we included Accuracy and Weighted F1 score (Weighted F1) for the comparison. Details of these metrics [76] are introduced below:

1. Accuracy: The accuracy score is defined the proportion of correct matching between predicted labels y_p and observed labels y_t:

$$Accuracy = \frac{\sum_{i=1}^{n} I(y_p^i = y_t^i)}{n},$$

where $I()$ represents the indicator function. The weighted F1 score requires us to compute the F1 score ($F1$) of different classes, as well as the proportion of samples with corresponding label. Therefore, if we have N classes and for class j the proportion is defined as w_j, the Weighted F1 score is computed as:

$$Weighted\ F1 = \sum_{j=1}^{N} w_j F1_j.$$

Both of metrics are in (0,1), and a higher score means better model performance.

For disease-state prediction, our metrics are the same as we used in evaluating methods for spot-type annotation, as they are both multi-label classification problems.

For drug response prediction, we utilize the metrics the same as we used in evaluating methods for disease-state prediction, as it is also binary classification problem.

For survival prediction, we utilize C-index to evaluate the prediction performance of survival function. C-index [79] is a generalization of the area under the ROC curve (AUC) that can take into account censored data. It is similar to AUC evaluation criteria.

For multi-modal alignment, our metrics included Cross-Entropy Loss (CEL) and top k precision (Precision@k). Details of these metrics are introduced below:

1. Cross-Entropy Loss (CEL): In our training stage, we first pair the image and gene expression vector. We then minimize the CEL between the dot product of embeddings from images and embeddings from gene expression profiles and the identity matrix. Considering the dot product matrix as $(l_{1,1}, l_{1,2}, ..., l_{n,n})$ and the identity matrix as $(y_{1,1}, y_{1,2}, ..., y_{n,n})$, and the CEL is computed by:

$$CEL_s = -\sum_{c=1}^{n} \log \frac{\exp{(x_{s,c})}}{\sum_{k=1}^{C} \exp{(x_{s,k})}} y_{s,c},$$

$$CEL = \frac{\sum_{s=1}^{S} CEL_s}{S}.$$

Here S represents the number of samples in the testing dataset.

2. Top k Precision (Precision@k): Here we still compare the dot product matrix with the identify matrix for each sample to compute the precision in top k candidates ranked by the dot product value. The choices of k include 1, 10, and 20.

The range of CEL is in $(0, \infty)$, and the range of Precision@k is in (0,1). A lower score of CEL means better model performance, where a higher score of Precision@k means better model performance.

Baselines. In this section, we introduce the baseline models for different tasks. Since we have discussed the settings introduced in this manuscript in the previous section, we only discuss domain expert methods.

For spatial domain identification, we consider SC3 [39], SpaGCN, Novae [20], and SpatialGLUE [21] as expert methods. SC3 is a clustering algorithm designed for single-cell RNA sequencing clustering by considering the averaged performances of k-means results under different resolutions. SpaGCN is a Graph Neural Network (GNN) designed for clustering of spatial transcriptomics. SpaGCN computes the adjacency matrix of spots based on both spatial locations and pixels of background images and then trains a GNN for self-supervised clustering. Novae is a foundation model trained with large-scale spatial transcriptomic data. SpatialGLUE is a method designed for spatial multi-omic clustering, which sets up GNNs for different modalities and learn their joint embeddings used for clustering.

For spot-type annotation, we consider various classifiers as expert methods. Logistic Regression is designed as a linear classifier by running linear regression after logit

function transformation. Support Vector Classifier is a classifier based on support vectors from hyperplanes. Random Forest is used to perform classification based on aggregating different decision trees. XGBclassifier is a classifier based on the boosting algorithm.

For disease-state annotation, we consider MultiMIL as an expert method. MultiMIL is a Multi-Instance Learning (MIL) algorithm for multi-omic single-cell data analysis. It first learns cell embeddings and then aggregates cell embeddings into sample embeddings by attention mechanism. The loss function combines both reconstruction loss for expression profiles and classification loss for disease states.

For multi-modal alignment, the expert methods contain different pathology foundation models. Their motivation is to pre-train an image encoder with large-scale pathology image datasets.

For all domain-expert methods, we used their parameters reported by the original authors for experiments, as they are already optimized for the given task.

Dataset availability. All of the datasets used in this manuscript are publicly available. We summarize the dataset statistics and download information in Supplementary File 2.

Code availability and reproductivity. To generate the text descriptions and corresponding embeddings, we rely on the API of OpenAI. To generate the embeddings from pathology foundation models, we reply on Yale High-performance Computing Center (YCRC) and utilize one NVIDIA A100 GPU with up to 50 GB RAM. To run spEMO and compare it with other methods, we utilize one NVIDIA A100 GPU with up to 150 GB RAM.

The codes of spEMO can be found in https://github.com/HelloWorldLTY/spEMO. The licence is MIT license.

5 Ethics and Inclusion.

Although spEMO is not biased to gender, races, and other factors, the users are solely responsible for the content they generate with models in spEMO, and there are no mechanisms in place for addressing harmful, unfaithful, biased, and toxic content disclosure. Any modifications of the models should be released under different version numbers to keep track of the original models related to this manuscript.

The target of current spEMO only serves for academic research. The users cannot use it for other purposes. Finally, we are not responsible for any effects of the use of the model.

6 Acknowledgements.

We thank Minsheng Hao for the suggestions of naming the model. We also thank Dr. Ning Sun, Dr. Wengong Jin, and Dr. Tinyi Chu for the suggestions of model comparison.

7 Author contributions.

T.L. designed this study. T.L. designed the model. T.L. and T.H. run all the experiments. T.L., T.H., R.Y. and H.Z. wrote the manuscript. R.Y. supported the computation resources. H.Z. supervised this project.

8 Competing interests.

The authors declare no competing interests.

References

[1] Song, A.H., Jaume, G., Williamson, D.F., Lu, M.Y., Vaidya, A., Miller, T.R., Mahmood, F.: Artificial intelligence for digital and computational pathology. Nature Reviews Bioengineering **1**(12), 930–949 (2023)

[2] Bera, K., Schalper, K.A., Rimm, D.L., Velcheti, V., Madabhushi, A.: Artificial intelligence in digital pathology—new tools for diagnosis and precision oncology. Nature reviews Clinical oncology **16**(11), 703–715 (2019)

[3] Niazi, M.K.K., Parwani, A.V., Gurcan, M.N.: Digital pathology and artificial intelligence. The lancet oncology **20**(5), 253–261 (2019)

[4] Al-Janabi, S., Huisman, A., Van Diest, P.J.: Digital pathology: current status and future perspectives. Histopathology **61**(1), 1–9 (2012)

[5] Neto, P.C., Montezuma, D., Oliveira, S.P., Oliveira, D., Fraga, J., Monteiro, A., Monteiro, J., Ribeiro, L., Gonçalves, S., Reinhard, S., *et al.*: An interpretable machine learning system for colorectal cancer diagnosis from pathology slides. NPJ precision oncology **8**(1), 56 (2024)

[6] Shaban, M., Bai, Y., Qiu, H., Mao, S., Yeung, J., Yeo, Y.Y., Shanmugam, V., Chen, H., Zhu, B., Weirather, J.L., *et al.*: Maps: Pathologist-level cell type annotation from tissue images through machine learning. Nature Communications **15**(1), 28 (2024)

[7] Zhang, S., Metaxas, D.: On the challenges and perspectives of foundation models for medical image analysis. Medical image analysis **91**, 102996 (2024)

[8] Chen, R.J., Ding, T., Lu, M.Y., Williamson, D.F., Jaume, G., Song, A.H., Chen, B., Zhang, A., Shao, D., Shaban, M., *et al.*: Towards a general-purpose foundation model for computational pathology. Nature Medicine **30**(3), 850–862 (2024)

[9] Lu, M.Y., Chen, B., Williamson, D.F., Chen, R.J., Liang, I., Ding, T., Jaume, G., Odintsov, I., Zhang, A., Le, L.P., et al.: Towards a visual-language foundation model for computational pathology. arXiv preprint arXiv:2307.12914 (2023)

[10] Xu, H., Usuyama, N., Bagga, J., Zhang, S., Rao, R., Naumann, T., Wong, C., Gero, Z., González, J., Gu, Y., et al.: A whole-slide foundation model for digital pathology from real-world data. Nature, 1–8 (2024)

[11] Ma, J., Guo, Z., Zhou, F., Wang, Y., Xu, Y., Cai, Y., Zhu, Z., Jin, C., Lin, Y., Jiang, X., Han, A., Liang, L., Chan, R.C.K., Wang, J., Cheng, K.-T., Chen, H.: Towards A Generalizable Pathology Foundation Model via Unified Knowledge Distillation (2024). https://arxiv.org/abs/2407.18449

[12] Moses, L., Pachter, L.: Museum of spatial transcriptomics. Nature methods **19**(5), 534–546 (2022)

[13] Williams, C.G., Lee, H.J., Asatsuma, T., Vento-Tormo, R., Haque, A.: An introduction to spatial transcriptomics for biomedical research. Genome Medicine **14**(1), 68 (2022)

[14] Wheeler, D.L., Barrett, T., Benson, D.A., Bryant, S.H., Canese, K., Chetvernin, V., Church, D.M., DiCuccio, M., Edgar, R., Federhen, S., *et al.*: Database resources of the national center for biotechnology information. Nucleic acids research **35**(suppl_1), 5–12 (2007)

[15] Bommasani, R., Hudson, D.A., Adeli, E., Altman, R., Arora, S., Arx, S., Bernstein, M.S., Bohg, J., Bosselut, A., Brunskill, E., et al.: On the opportunities and risks of foundation models. arXiv preprint arXiv:2108.07258 (2021)

[16] OpenAI: GPT-4 Technical Report (2023)

[17] Models, C.: Model card and evaluations for claude models (2023). https://www-files.anthropic.com/production/images/Model-Card-Claude-2.pdf

[18] Cui, H., Wang, C., Maan, H., Pang, K., Luo, F., Duan, N., Wang, B.: scgpt: toward building a foundation model for single-cell multi-omics using generative ai. Nature Methods, 1–11 (2024)

[19] Schaar, A.C., Tejada-Lapuerta, A., Palla, G., Gutgesell, R., Halle, L., Minaeva, M., Vornholz, L., Dony, L., Drummer, F., Bahrami, M., et al.: Nicheformer: a foundation model for single-cell and spatial omics. bioRxiv, 2024–04 (2024)

[20] Blampey, Q., Benkirane, H., Bercovici, N., Andre, F., Cournede, P.-H.: Novae: a graph-based foundation model for spatial transcriptomics data. bioRxiv, 2024–09 (2024)

[21] Long, Y., Ang, K.S., Sethi, R., Liao, S., Heng, Y., Olst, L., Ye, S., Zhong, C., Xu, H., Zhang, D., et al.: Deciphering spatial domains from spatial multi-omics with spatialglue. Nature Methods, 1–10 (2024)

[22] Deng, Y., Bai, Z., Fan, R.: Microtechnologies for single-cell and spatial multi-omics. Nature Reviews Bioengineering **1**(10), 769–784 (2023)

[23] Jia, Y., Liu, J., Chen, L., Zhao, T., Wang, Y.: Thitogene: a deep learning method for predicting spatial transcriptomics from histological images. Briefings in Bioinformatics **25**(1), 464 (2024)

[24] Liu, T., Li, K., Wang, Y., Li, H., Zhao, H.: Evaluating the utilities of foundation models in single-cell data analysis. bioRxiv, 2023–09 (2023)

[25] Kedzierska, K.Z., Crawford, L., Amini, A.P., Lu, A.X.: Assessing the limits of zero-shot foundation models in single-cell biology. bioRxiv, 2023–10 (2023)

[26] Boiarsky, R., Singh, N.M., Buendia, A., Getz, G., Sontag, D.: A deep dive into single-cell rna sequencing foundation models. bioRxiv, 2023–10 (2023)

[27] Ahlmann-Eltze, C., Huber, W., Anders, S.: Deep learning-based predictions of gene perturbation effects do not yet outperform simple linear methods. bioRxiv, 2024–09 (2024)

[28] Chen, Y.T., Zou, J.: Genept: A simple but hard-to-beat foundation model for genes and cells built from chatgpt. bioRxiv, 2023–10 (2023)

[29] Liu, T., Chen, T., Zheng, W., Luo, X., Zhao, H.: scelmo: Embeddings from language models are good learners for single-cell data analysis. bioRxiv, 2023–12 (2023)

[30] Pourpanah, F., Abdar, M., Luo, Y., Zhou, X., Wang, R., Lim, C.P., Wang, X.-Z., Wu, Q.J.: A review of generalized zero-shot learning methods. IEEE transactions on pattern analysis and machine intelligence **45**(4), 4051–4070 (2022)

[31] Church, K.W., Chen, Z., Ma, Y.: Emerging trends: A gentle introduction to fine-tuning. Natural Language Engineering **27**(6), 763–778 (2021)

[32] Zeng, Y., Yin, R., Luo, M., Chen, J., Pan, Z., Lu, Y., Yu, W., Yang, Y.: Identifying spatial domain by adapting transcriptomics with histology through contrastive learning. Briefings in Bioinformatics **24**(2), 048 (2023)

[33] Hu, J., Li, X., Coleman, K., Schroeder, A., Ma, N., Irwin, D.J., Lee, E.B., Shinohara, R.T., Li, M.: Spagcn: Integrating gene expression, spatial location and histology to identify spatial domains and spatially variable genes by graph convolutional network. Nature methods **18**(11), 1342–1351 (2021)

[34] Heydari, A.A., Sindi, S.S.: Deep learning in spatial transcriptomics: Learning from the next next-generation sequencing. Biophysics Reviews **4**(1) (2023)

[35] Abdi, H., Williams, L.J.: Principal component analysis. Wiley interdisciplinary reviews: computational statistics **2**(4), 433–459 (2010)

[36] Maynard, K.R., Collado-Torres, L., Weber, L.M., Uytingco, C., Barry, B.K., Williams, S.R., Catallini, J.L., Tran, M.N., Besich, Z., Tippani, M., *et al.*: Transcriptome-scale spatial gene expression in the human dorsolateral prefrontal cortex. Nature neuroscience **24**(3), 425–436 (2021)

[37] Pardo, B., Spangler, A., Weber, L.M., Page, S.C., Hicks, S.C., Jaffe, A.E., Martinowich, K., Maynard, K.R., Collado-Torres, L.: spatiallibd: an r/bioconductor package to visualize spatially-resolved transcriptomics data. BMC genomics **23**(1), 434 (2022)

[38] Luecken, M.D., Büttner, M., Chaichoompu, K., Danese, A., Interlandi, M., Müller, M.F., Strobl, D.C., Zappia, L., Dugas, M., Colomé-Tatché, M., *et al.*: Benchmarking atlas-level data integration in single-cell genomics. Nature methods **19**(1), 41–50 (2022)

[39] Kiselev, V.Y., Kirschner, K., Schaub, M.T., Andrews, T., Yiu, A., Chandra, T., Natarajan, K.N., Reik, W., Barahona, M., Green, A.R., *et al.*: Sc3: consensus clustering of single-cell rna-seq data. Nature methods **14**(5), 483–486 (2017)

[40] Zimmermann, E., Vorontsov, E., Viret, J., Casson, A., Zelechowski, M., Shaikovski, G., Tenenholtz, N., Hall, J., Fuchs, T., Fusi, N., et al.: Virchow 2: Scaling self-supervised mixed magnification models in pathology. arXiv preprint arXiv:2408.00738 (2024)

[41] Jaume, G., Doucet, P., Song, A.H., Lu, M.Y., Pérez, C.A., Wagner, S.J., Vaidya, A.J., Chen, R.J., Williamson, D.F., Kim, A., Mahmood, F.: HEST-1k: A dataset for spatial transcriptomics and histology image analysis. In: The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track (2024). https://openreview.net/forum?id=mlhFJE7PKo

[42] Palla, G., Spitzer, H., Klein, M., Fischer, D., Schaar, A.C., Kuemmerle, L.B., Rybakov, S., Ibarra, I.L., Holmberg, O., Virshup, I., *et al.*: Squidpy: a scalable framework for spatial omics analysis. Nature methods **19**(2), 171–178 (2022)

[43] Schaumberg, A.J., Juarez-Nicanor, W.C., Choudhury, S.J., Pastrián, L.G., Pritt, B.S., Prieto Pozuelo, M., Sotillo Sanchez, R., Ho, K., Zahra, N., Sener, B.D., *et al.*: Interpretable multimodal deep learning for real-time pan-tissue pan-disease pathology search on social media. Modern pathology **33**(11), 2169–2185 (2020)

[44] Ravindra, N., Sehanobish, A., Pappalardo, J.L., Hafler, D.A., Dijk, D.: Disease state prediction from single-cell data using graph attention networks. In: Proceedings of the ACM Conference on Health, Inference, and Learning, pp. 121–130 (2020)

[45] McInnes, L., Healy, J., Saul, N., Großberger, L.: Umap: Uniform manifold approximation and projection. Journal of Open Source Software **3**(29), 861 (2018) https://doi.org/10.21105/joss.00861

[46] Labianca, R., Beretta, G.D., Kildani, B., Milesi, L., Merlin, F., Mosconi, S., Pessi, M.A., Prochilo, T., Quadri, A., Gatta, G., *et al.*: Colon cancer. Critical reviews in oncology/hematology **74**(2), 106–133 (2010)

[47] Stemmermann, G.: Extrapelvic carcinoma metastatic to the uterus. American Journal of Obstetrics and Gynecology **82**(6), 1261–1266 (1961)

[48] LemaẄtre, G., Nogueira, F., Aridas, C.K.: Imbalanced-learn: A python toolbox to tackle the curse of imbalanced datasets in machine learning. Journal of machine learning research **18**(17), 1–5 (2017)

[49] Hoang, D.-T., Dinstag, G., Shulman, E.D., Hermida, L.C., Ben-Zvi, D.S., Elis, E., Caley, K., Sammut, S.-J., Sinha, S., Sinha, N., et al.: A deep-learning framework to predict cancer treatment response from histopathology images through imputed transcriptomics. Nature Cancer, 1–13 (2024)

[50] Liu, T., De Brouwer, E., Kuo, T., Diamant, N., Missarova, A., Wang, H., Hao, M., Bravo, H.C., Scalia, G., Regev, A., et al.: Learning multi-cellular representations of single-cell transcriptomics data enables characterization of patient-level disease states. bioRxiv, 2024–11 (2024)

[51] Lin, Z., Sun, W.: Supervised deep learning with gene annotation for cell classification. bioRxiv, 2024–07 (2024)

[52] Jaume, G., Vaidya, A., Chen, R., Williamson, D., Liang, P., Mahmood, F.: Modeling dense multimodal interactions between biological pathways and histology for survival prediction. Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (2024)

[53] Weinstein, J.N., Collisson, E.A., Mills, G.B., Shaw, K.R., Ozenberger, B.A., Ellrott, K., Shmulevich, I., Sander, C., Stuart, J.M.: The cancer genome atlas pan-cancer analysis project. Nature genetics **45**(10), 1113–1120 (2013)

[54] Katzman, J.L., Shaham, U., Cloninger, A., Bates, J., Jiang, T., Kluger, Y.: Deepsurv: personalized treatment recommender system using a cox proportional hazards deep neural network. BMC medical research methodology **18**, 1–12 (2018)

[55] GitHub: Pycox. https://github.com/havakv/pycox

[56] Anonymous: Predicting spatial transcriptomics from histology images via biologically informed flow matching. In: Submitted to The Thirteenth International Conference on Learning Representations (2024). under review. https://openreview.net/forum?id=sYrdb3mhM4

[57] Lee, Y., Liu, X., Hao, M., Liu, T., Regev, A.: Pathomclip: Connecting tumor histology with spatial gene expression via locally enhanced contrastive learning

835 of pathology and single-cell foundation model. bioRxiv, 2024–12 (2024)

[58] Cang, Z., Zhao, Y., Almet, A.A., Stabell, A., Ramos, R., Plikus, M.V., Atwood, S.X., Nie, Q.: Screening cell–cell communication in spatial transcriptomics via collective optimal transport. Nature methods **20**(2), 218–228 (2023)

[59] Kazanietz, M.G., Durando, M., Cooke, M.: Cxcl13 and its receptor cxcr5 in cancer: inflammation, immune response, and beyond. Frontiers in endocrinology **10**, 471 (2019)

[60] Förster, R., Davalos-Misslitz, A.C., Rot, A.: Ccr7 and its ligands: balancing immunity and tolerance. Nature Reviews Immunology **8**(5), 362–371 (2008)

[61] Ding, T., Wagner, S.J., Song, A.H., Chen, R.J., Lu, M.Y., Zhang, A., Vaidya, A.J., Jaume, G., Shaban, M., Kim, A., et al.: Multimodal whole slide foundation model for pathology. arXiv preprint arXiv:2411.19666 (2024)

[62] Shaikovski, G., Casson, A., Severson, K., Zimmermann, E., Wang, Y.K., Kunz, J.D., Retamero, J.A., Oakley, G., Klimstra, D., Kanan, C., et al.: Prism: A multimodal generative foundation model for slide-level histopathology. arXiv preprint arXiv:2405.10254 (2024)

[63] Lu, M.Y., Chen, B., Williamson, D.F., Chen, R.J., Zhao, M., Chow, A.K., Ikemura, K., Kim, A., Pouli, D., Patel, A., *et al.*: A multimodal generative ai copilot for human pathology. Nature **634**(8033), 466–473 (2024)

[64] Hurst, A., Lerer, A., Goucher, A.P., Perelman, A., Ramesh, A., Clark, A., Ostrow, A., Welihinda, A., Hayes, A., Radford, A., et al.: Gpt-4o system card. arXiv preprint arXiv:2410.21276 (2024)

[65] Wang, Y., Song, B., Wang, S., Chen, M., Xie, Y., Xiao, G., Wang, L., Wang, T.: Sprod for de-noising spatially resolved transcriptomics data based on position and image information. Nature methods **19**(8), 950–958 (2022)

[66] Xie, R., Pang, K., Chung, S., Perciani, C., MacParland, S., Wang, B., Bader, G.: Spatially resolved gene expression prediction from histology images via bimodal contrastive learning. Advances in Neural Information Processing Systems **36** (2024)

[67] Huang, M., Zhang, Z., Zhang, N.R.: Dimension reduction and denoising of single-cell rna sequencing data in the presence of observed confounding variables. BioRxiv, 2020–08 (2020)

[68] Lopez, R., Regier, J., Cole, M.B., Jordan, M.I., Yosef, N.: Deep generative modeling for single-cell transcriptomics. Nature methods **15**(12), 1053–1058 (2018)

[69] Heimberg, G., Kuo, T., DePianto, D.J., Salem, O., Heigl, T., Diamant, N., Scalia, G., Biancalani, T., Turley, S.J., Rock, J.R., et al.: A cell atlas foundation model for scalable search of similar human cells. Nature, 1–3 (2024)

[70] Lance, C., Luecken, M.D., Burkhardt, D.B., Cannoodt, R., Rautenstrauch, P., Laddach, A., Ubingazhibov, A., Cao, Z.-J., Deng, K., Khan, S., Liu, Q., Russkikh, N., Ryazantsev, G., Ohler, U., participants, N..M., Pisco, A.O., Bloom, J., Krishnaswamy, S., Theis, F.J.: Multimodal single cell data integration challenge: Results and lessons learned. In: Kiela, D., Ciccone, M., Caputo, B. (eds.) Proceedings of the NeurIPS 2021 Competitions and Demonstrations Track. Proceedings of Machine Learning Research, vol. 176, pp. 162–176. PMLR, ??? (2022). https://proceedings.mlr.press/v176/lance22a.html

[71] Vorontsov, E., Bozkurt, A., Casson, A., Shaikovski, G., Zelechowski, M., Severson, K., Zimmermann, E., Hall, J., Tenenholtz, N., Fusi, N., et al.: A foundation model for clinical-grade computational pathology and rare cancers detection. Nature Medicine, 1–12 (2024)

[72] Wang, X., Yang, S., Zhang, J., Wang, M., Zhang, J., Yang, W., Huang, J., Han, X.: Transformer-based unsupervised contrastive learning for histopathological image classification. Medical image analysis **81**, 102559 (2022)

[73] Theodoris, C.V., Xiao, L., Chopra, A., Chaffin, M.D., Al Sayed, Z.R., Hill, M.C., Mantineo, H., Brydon, E.M., Zeng, Z., Liu, X.S., et al.: Transfer learning enables predictions in network biology. Nature, 1–9 (2023)

[74] Xu, Y., Wang, Y., Zhou, F., Ma, J., Yang, S., Lin, H., Wang, X., Wang, J., Liang, L., Han, A., et al.: A multimodal knowledge-enhanced whole-slide pathology foundation model. arXiv preprint arXiv:2407.15362 (2024)

[75] Wolf, F.A., Angerer, P., Theis, F.J.: Scanpy: large-scale single-cell gene expression data analysis. Genome biology **19**, 1–5 (2018)

[76] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., *et al.*: Scikit-learn: Machine learning in python. the Journal of machine Learning research **12**, 2825–2830 (2011)

[77] Chen, T., Guestrin, C.: Xgboost: A scalable tree boosting system. In: Proceedings of the 22nd Acm Sigkdd International Conference on Knowledge Discovery and Data Mining, pp. 785–794 (2016)

[78] Litinetskaya, A., Shulman, M., Hediyeh-zadeh, S., Moinfar, A.A., Curion, F., Szalata, A., Omidi, A., Lotfollahi, M., Theis, F.J.: Multimodal weakly supervised learning to identify disease-specific changes in single-cell atlases. bioRxiv, 2024–07 (2024)

[79] Antolini, L., Boracchi, P., Biganzoli, E.: A time-dependent discrimination index for survival data. Statistics in medicine **24**(24), 3927–3944 (2005)

 # A Supplementary figures

Extended Data Fig. 1 Testing the contributions of image embeddings from different PFMs for spatial domain identification. Our metircs are NMI, ARI, ASW and their average value (Avg).

Extended Data Fig. 2 Testing the contributions of the patch size of image used for generating embeddings. Here the selected PFM is GPFM. Our metircs are NMI, ARI, ASW and their average value (Avg).

Extended Data Fig. 3 Spatial domain identification performances of the two Visium datasets from Squidpy. (a) Benchmarking results based on the Visium H&E dataset across different image features. (b) Benchmarking results based on the Visium fluo dataset across different image features.

Extended Data Fig. 4 Comparisons of classifiers and settings for spot-type annotation. (a) The evaluation of the performances of different classifiers. (b) The evaluation of the performances of different input settings based on LR.

a

b

Extended Data Fig. 5 Spot-type prediction performances of the two Visium datasets from Squidpy. (a) Benchmarking results by using Visium fluo as testing dataset across different input settings. (b) Benchmarking results by using Visium H&E as testing dataset across different input settings.

Extended Data Fig. 6 Embeddings from different resources colored by studies. (a) The UMAP based on embeddings from pseudo-bulk gene expression profiles. (b) The UMAP based on embeddings from PFMs. The study labels are shown below.

Extended Data Fig. 7 Disease-state prediction performances by setting the cross-validation labels as studies.

Extended Data Fig. 8 Comparisons between imbalance learning methods and raw methods. Here **raw** represents the default setting. We also tested clustering-based oversampling approach but met running errors due to small neighbor size. (a) Classification results based on the SampleCV setting across different sampling methods. (b) Classification results based on the StudyCV setting across different sampling methods.

Extended Data Fig. 9 Comparisons between major voting methods and raw methods. Here **raw** represents the default setting. (a) Classification results based on the SampleCV setting across different sampling methods. (b) Classification results based on the StudyCV setting across different sampling methods.

Extended Data Fig. 10 Comparisons between gene expression profiles and spEMO for understanding drug response for individuals. (a) Clustering results based on different input settings. (b) Prediction results based on different input settings.

Extended Data Fig. 11 Correlations of text embeddings based on the descriptions generated with different random seeds under the gene+image mode. We consider 10 different seeds for COAD report generation.