Shared and individual tuning curves for social vision

Rekha S. Varrier[1], Zishan Su[1], Qi Liang[1], Tory Benson[1], Eshin Jolly[1]and Emily S. Finn[1]

[1]Department of Psychological and Brain Sciences, Dartmouth College, Hanover 03755

Corresponding authors:

Rekha S. Varrier: rvarrier@uni-bonn.de and

Emily S. Finn: emily.s.finn@dartmouth.edu

Abstract

A stimulus with light is clearly visual; a stimulus with sound is clearly auditory. But what makes a stimulus "social", and how do judgments of socialness differ across people? Here, we characterize both group-level and individual thresholds for perceiving the presence and nature of a social interaction. We take advantage of the fact that humans are primed to see social interactions—e.g., chasing, playing, fighting—even in very un-lifelike stimuli such as animations of geometric shapes. Unlike prior work using these stimuli, we exploit their most advantageous property, which is that their visual features are fully parameterizable. We use this property to construct psychophysics-inspired "social tuning curves" for individual subjects. Social tuning curves are stable within individuals, unique across individuals, and show some relationship to socio-affective traits. Results support the view that social information processing begins early in the perceptual hierarchy. Further, our approach lays the foundation for a generative account of social perception in single subjects.

Introduction

A hallmark of the human species is our extraordinary sociality, which depends on reading and responding to others' behavior in ways that are largely effortless and shared across the population. Yet despite this shared general framework, there are substantial idiosyncrasies in how people perceive, interpret, and react to social information[1–5]. Many of these individual differences simply reflect variation in personality traits and social styles. Yet, extreme deviations from typical social processing are also central to developmental conditions such as autism[6–10], as well as mental illnesses such as schizophrenia[11,12], paranoia[13] and depression[14–17].

Social information can take many forms, including linguistic cues, facial cues, and whole-body motion cues. While humans get nuanced information from linguistic and facial cues, motion cues are necessary for some of our most basic evolutionary social behaviors that are conserved across species: e.g., pursuing, evading, playing, fighting, and courting[18,19]. Humans are primed to perceive these types of interactions even in very un-lifelike stimuli: for example, when faced with videos of simple geometric shapes moving around the screen, even without prompting, most neurotypical people will construct narratives to explain the shapes' movements in terms of goals, beliefs, and desires. This highly robust observation dates back at least to Heider and Simmel[20] and has since been leveraged to study social perception in a wide variety of contexts and populations[21–24]. The effect holds across cultures, suggesting a biological origin[18]. Along with related phenomena such as pareidolia[25]—the tendency to perceive faces in inanimate objects—this suggests an automaticity to social information processing that belies its typical conceptualization as a high-level cognitive process. Indeed, recent work supports the notion that core components of a social interaction can be extracted by the human visual system using fast, bottom-up processes[26], which is likely evolutionarily adaptive for a species that depends heavily on its sociality for survival[27,28].

While using simple geometric-shape animations as experimental stimuli has yielded important insights into behavioral, cognitive, and neural aspects of social perception, most past work using these stimuli has substantial limitations. Studies typically use a small number of manually generated animations handcrafted by human experimenters to be either obviously social or obviously non-social, with no systematic variation or control over visual features[3,29,30]. Subjects' responses are then classified as accurate or inaccurate with respect to these "ground

truth" experimenter labels. Furthermore, even given a stimulus deemed "social" by most people,

different individuals may be perceiving different *types* of social interactions in that same

stimulus; the *nature* of the perceived interaction is rarely probed (and if it is, it is usually

assumed to have a ground truth label —e.g., helping versus hindering—for which the

experimenters again have clear "ground truth" labels in mind)[31–33]. Together, these practices

often produce ceiling effects and compress individual variability in behavior (at least in

normative populations), which is unrealistic given that most real-world social scenarios are

complex and may engender different interpretations across people.

Here, we exploit a highly advantageous yet hitherto under-used property of such

animations—namely, that they are algorithmically controllable and amenable to principles of

visual psychophysics—to characterize people's socio-perceptual tendencies at both the group and

individual level. We study two processes: (1) how people detect the presence of an interaction

and (2) how people discriminate between types of interactions. By parametrically varying motion

attributes[22], we programmatically generate a large set of animations and use participants'

subjectively reported percepts to construct "social tuning curves" capturing shared trends and

individual differences. Throughout, we adopt the perspective that socialness is in the eye of the

beholder: in other words, there is no "correct" and "incorrect"; whatever percept is reported is

the ground truth for that trial for that participant. We *embrace* ambiguous stimuli—i.e., those that

yield high variability in reported percepts—as a feature rather than a bug, as these offer an

opportunity to probe the limits of what makes a stimulus social, and how these limits differ for

different individuals. We use this framework to show that robust individual differences in socio-

perceptual tendencies exist atop group-level trends, that these individual differences are reliable

over a period of months, and that they may be related (albeit likely in complex, nonlinear ways)

to traits indexing real-world social and affective function.

Methods

Table 1: Summary of the experiments

Experiment type		Social detection	Social discrimination
Task		Presence vs. absence of social interactions	Valence discrimination: play vs. fight
Parametrized motion attribute		Chase directness	Charge speed
Sample size	**Pilot experiments (free-text responses)**	N = 60	N =103, with cover story N =102, without cover story
	Main experiments	N = 312, session 1 (N = 240 returned for session 2)	N = 319, session 1 (N = 269 returned for session 2)
	Supplementary experiments (controlled for correlated motion)	N = 308	
	Within-subject mixed-task design	N = 279	

Participants

All data collection and analysis procedures were approved by the Committee for the Protection of Human Subjects of Dartmouth College. All data were collected online (http://www.prolific.com/). We used the following selection criteria: Participants had to (1) be fluent in English, (2) have their location set as the USA or UK and (3) not have participated in our previous studies with similar stimuli. For consistency in data quality, all studies – except for the retest sessions where participants (identified using their 24-character Prolific IDs) were invited to complete a second session – were typically launched at 9am Eastern US time on Prolific and closed when the desired sample size was reached (usually about 2pm Eastern US time). The retest sessions were launched 2 months (Mean=71.0 days, SD=5.6 days; detection

task) or 1 month (Mean=32.8 days, SD=7.7 days; discrimination task) after their respective first

sessions and were left open for about 6 weeks until no participants signed up for the task in at

least 1 week, with the goal to encourage as many participants as possible to return. Note that the

aim of the second sessions was to test the retest reliability (i.e., how similar behavior was on two

independent sessions), so the exact time gap between the sessions did not need to be the same,

we only required that the session not be so close that we would see effects of perceptual learning

or task-specific memory.

Stimuli

Stimuli were simple animations generated using a custom JavaScript-based software called

psyanim (https://github.com/thefinnlab/psyanim-2). Each animation had two circular agents

(radius 12 px): one black and one gray, set against a white background in a world of size 800px x

600px (see Fig 1a and all the stimuli here; exact stimuli for the individual experiments will be

linked in-text near the description of that behavior). At the start of an animation, the agents were

on either side of the center of the screen (coordinates: 400, 300): left (coordinates: 250, 300) and

right (coordinates: 550, 300). In each experiment, the black agent started on the left (gray on the

right) in half of the animations, and vice versa in the other half. The animations were 6s

(detection task) or 8s (discrimination task) long with a frame rate of 60 Hz. A key difference

between this study and most past work on social perception using animations is that we

generated our animations purely programmatically using quantifiable, parameterizable motion

attributes (Fig 1a). Each experiment consisted of 7 levels of stimuli where one motion attribute

of interest varied linearly while all other attributes were held constant. These attributes were

chosen such that people's perception of a social scene on a scale from the most non-social to

most social (detection task) or from most playful to most aggressive (discrimination task) varied

along the attribute of interest. In the following sub-sections, we describe these motion attributes

as well as the animations in more detail.

Detection task

To manipulate percepts as to the presence versus absence of a social interaction (detection task),

we relied on the motion attribute *chase directness*, which governs the fidelity with which one

agent (the "predator") chases the other agent (the "prey"). This attribute was originally described

by Gao et al.[22], where it was called "chase subtlety" and was found to robustly influence people's

ability to detect social interactions (in particular, chases). Chase subtlety was originally defined

in angles, i.e., by how many degrees a predator could deviate from a perfect heat-seeking path

between itself and the prey at each time step. Thus, a *chase subtlety* of 0° would indicate a very

direct chase, a *chase subtlety* of 90° would indicate a somewhat noisy chase where the predator

can go off-path by up to 90° clockwise or 90° counterclockwise, and *chase subtleties* > 90°

would indicate very noisy chasing behaviors where the predator can occasionally even move

away from the prey. Here, we reversed and normalized the subtlety angle to derive *chase*

directness ($\frac{180 - chaseSubtlety}{180}$), such that the higher the directness, the more obvious (detectible)

the chase. Details on how this was implemented in *psyanim* is below.

<u>*Chase animations*</u>

In the animations we generated, one agent is the predator and the other is the prey. Predator/prey

assignment was counterbalanced across stimuli in terms of both start position (left/right of the

center) and color (gray/black). The predator was programed to chase the prey at varying levels of

chase directness and the prey was programmed to flee from the predator when it was within a

certain radius. When the predator agent was beyond its field of view (or the distance between

them was greater than the "*safety distance*"), the prey agent simply wandered around the screen.

We included the wandering behavior so as to prevent the fleeing behavior from looking too

obvious, so that people did not make decisions purely based on the prey. All variable attributes

other than *chase directness* governing the motions of the predator and prey were held constant

over all animations (i.e., over all levels of chase directness). The relevant attributes are described

below:

Chase directness: Every 350ms (set by an attribute called *subtlety lag* explained in the

next paragraph), the predator picks a value from a uniform distribution that ranges from

[–*chaseSubtlety*, *chaseSubtlety*], where *chaseSubtlety* ∈ {0°, 30°, 60°, 90°, 120°,150°}. (i.e.,

chase directness ∈ {1, 0.833, 0.667, 0.5, 0.333, 0.167}). These behaviors are illustrated in Fig

1a. To get a feel for what these values mean, we encourage readers to watch some of the

animations, available on GitHub (the stimuli used for session 1 chase detection experiments here,

and those for session 2 experiments are here).

Other attributes: All attributes besides *chase directness* were set to be constant across

animations. Some of the relevant attributes that influenced how the animations were perceived

were optimized by manual piloting during stimulus development. These were, for the predator:

(i) *maximum chase speed* = 1.5px/frame (frame rate = 60), (ii) *maximum chase acceleration* =

0.1px/frame^2 and (iii) *subtlety lag* = 350ms (how often the agent recomputes its chase direction;

lower values will make the animation more jittery). For the prey: (i) *flee subtlety* = 30° (the

angle which an agent can deviate from the true direction away from the predator — this

parameter helps to avoid fleeing looking very obvious), (ii) *safety distance* = 100px (distance

below which the agent flees from the predator; above this, it wanders), (iii) *maximum flee speed*

= 1.8px/frame, (iv) *maximum flee acceleration*: 0.15px/frame^2, (v) *maximum wander speed* =

1.5px/frame, *maximum wander acceleration* = 0.1px/frame^2, (vi) *maximum seek speed* =

3.5px/frame and (viii) *maximum seek acceleration* = 0.05px/frame^2 (the seek behavior is

included in the prey algorithm to keep it away from the boundaries/walls/edges of the world so

that it does not get stuck in a corner). The flee speed and acceleration of the prey were set to be

slightly higher than those of the predator to ensure that the predator never actually catches the

prey.

"Invisible chase" control condition

With this control, we sought to rule out an alternative possibility for how *chase directness* might

influence socialness perception that is less related to a chase *per se* and more related to general

motion contingency between the two agents. Specifically, observers may notice that the predator

and prey trajectories are linked more tightly in time at higher *chase directness* (where

immediately after the prey changes direction, the predator too will change direction) than at

lower *chase directness* (where the predator will not change direction as quickly and obviously

upon the prey changing direction). Participants may simply be using this heuristic—i.e., whether

the prey changing direction prompts the predator to change direction—instead of the actual chase

between the predator and prey. To test for this possibility, inspired by Gao et al.[22], in a subset of

behavioral experiments we included an additional set of control stimuli, where the actual prey

was initialized at a randomly chosen location on the screen for each animation but was made

invisible. The predator and a visible "mimicking" agent each started at one of the two regular

starting locations (left and right of center as described at the start of the **Stimuli** section). The

mimicking agent copies the true prey's trajectory but with a 180° rotation (i.e., if the invisible

prey moves up and to the right, the mimicking agent will move down and to the left). The

animations used for this study are here. For illustrative purposes, the invisible (true) prey is

shown in yellow in these exemplars (participants never saw the yellow dots!). There were only 2

relevant parameters for the mimicking agent in *psyanim*: (i) *name or ID of the agent* to mimic

(i.e., the invisible true prey), (ii) *angleOffset* = 180° (how much to offset the movement in

angles).

Wander behavior

We also generated animations where both the agents were wandering independently, meaning

that there was no programmed contingency between their motion patterns. The speed and

acceleration of the two wandering agents matched that of the predator and prey agents in the

main chase animations (pseudo-predator and pseudo-prey agents, respectively) to make these

animations as close as possible to the chase animations. These animations serve as an additional

check as to whether participants use the speed of an agent as a heuristic to help identify the

predator (since, in chase animations, the predator always moved slightly slower than the prey so

as to avoid catching it as described above). Although these animations were generated differently

to the chase animations described above (where one of the agents is designed to chase the other,

however inefficiently), they are conceptually equivalent to a chase with *chase directness* = 0

(subtlety 180°; i.e., where the predator is equally likely to move in any direction irrespective of

the prey's position). Hence, we use these as our experimental stimuli for *chase directness* = 0 in

the social detection experiments. These stimuli can be seen here.

The relevant parameters for these animations in *psyanim* were: (i) *maximum wander*

speed (for the pseudo-predator agent = 1.5px/frame, pseudo-prey agent = 1.8px/frame) , (ii)

maximum wander acceleration (for the pseudo-predator agent = 0.1px/frame^2, for the pseudo-

prey agent = 0.15px/frame^2), (iii) maximum angle change per frame = 35° (how much the

movement direction can change from one frame to the next), (iv) minimum screen boundary

distance = 50px (the distance agents try to maintain from the screen boundary).

 Discrimination task

To study how people discriminate between positive and negative social interactions, we varied

the attribute *charge speed* in a novel social interaction scene that is different from the chase

detection task discussed above. This scene was inspired by the presence of physical contact in

the real world for common positive as well as negative interactions (e.g., hugs, high-fives,

physical fights)[34] and how speed can be a clue to valence, with slower movements being usually

perceived as more peaceful/positive, and faster movements as more aggressive/negative[19].

When generating these animations, both agents were set to have the same goal: to wander

for a certain period and then charge at the other agent at the predetermined *charge speed* which

varies between 1.5px/frame and 9px/frame (stimuli in Fig 1a and here). Once one agent initiates

a charge, the other agent will respond after a short delay; following contact, both agents will

return to wandering.

As with the detection task, several features were kept at constant values after extensive

in-lab piloting. These were: (i) *minTargetDistanceForCharge* = 200px,

maxTargetDistanceForCharge = 500px (the between-agent distance range within which

collisions would be initiated), (ii) *mean charge delay* =200ms, *jitter* =100ms (how long the

second agent waits after the first agent charges at it), (iii) *mean break duration*: 2000ms,

jitter=200ms (the duration for which two agents wander between consecutive charges), (iv)

maximum wander speed: 1.5px/frame, (v) maximum wander acceleration=0.1px/frame^2, (iii)

wander panic distance=800px (minimum distance at which a wandering agent will charge back

at another agent).

Quality-checking stimuli

We quality checked all generated animations for both the detection and the discrimination tasks.

Animations were manually checked by at least two lab members and were removed if they

contained glitchy/flickery movement patterns, if the agents got stuck in the corners or stuck to

each other for extended periods, and/or if one or both agents went offscreen. At all stages, bad

animations were replaced with new ones of the same type (e.g., same *chase directness* value,

predator color and start position) to obtain the targeted number of animations. For the detection

task, our final stimulus set included 84 chase animations (12 animations at each of 7 *chase*

directness levels, including animations generated via the wander algorithm which served as

chase directness=0) and 84 'invisible chase' animations (control; 12 animations at each of the
chase directness levels used in the chase animations plus animations generated via the wander
algorithm which served as *chase directness* = 0). Within these sets, the starting position (left
versus right of center) and the role of predator versus prey was counterbalanced between the gray
and black agent across animations, so that when participants were presented with an animation,
there was no expectation of what they would see next based on the position or the color of the
predator.

For *charge speed* (discrimination) stimuli, we removed bad animations according to
similar criteria as described for the detection stimuli. In addition, we ensured that all animations
in the final set had the same number of actual collisions (two), since differences in the number of
collisions could have influenced percepts independently of *charge speed*, which was the main
motion attribute of interest. The final set of discrimination stimuli contained 20 animations at
each of 7 *charge speed* levels for a total of 140 animations. Within this set, the initial position of
the gray and black agents was counterbalanced across animations.

Fig 1: Social detection and discrimination tasks. (a) Static schematics of the animation stimuli
for the detection (left) and discrimination (right) tasks to illustrate the effect of varying motion
attributes (chase directness and charge speed, respectively) on agents' trajectories. (b) The
response screen that was presented following each animation in the main experiments. Both
tasks required participants to rate their percept of the preceding animation on a continuous bar,
and the detection task (left) additionally asked participants to identify the agent that was doing

the chasing. In both experiments, the positions of the slider labels ("Moving independently"/

"Chasing" or "Playing"/"Fighting") on the left versus right were counterbalanced across

participants.

Animacy cover story

Attributing intentions to moving shapes entails judgments of two related yet distinct features –

animacy and socialness. Animacy is a widely used concept that applies to entities that are

considered alive[35]. These entities exhibit signs of self-propelled, non-Newtonian motion by

seeming to engage in goal-directed behavior[36] and responding to their surroundings (e.g.,

changing speed or direction to avoid an obstacle). In our view, animacy is necessary but not

sufficient for socialness: animacy can be detected in displays of single agents, in which by

definition there is no social interaction present, but in multi-agent displays, to the extent that

agents are perceived to be socially interacting, they must also be perceived as animate (i.e., as

possessing a mind that would be motivated to engage in social behavior). Our goal here was to

isolate the concept of *socialness* above and beyond animacy. Because differences in percepts of

animacy might confound judgments of socialness, to encourage uniform perception of animacy

across both animations and participants to the extent possible, we provided a cover story that the

agents (dots) represented children in a public park. This was the exact story participants

received: "*We recently videotaped a public park where nearby children go, with the goal of*

capturing the essence of children's behaviors within a familiar park setting. To protect the

*identities of these young people, we used an algorithm that represents **a pair of children as two***

***dots**, each tracing the path of an individual child.*" We used this cover story to set the context in

all of our experiments except in the early pilot experiments, since the goal of the latter was to

evaluate how participants spontaneously interpret the animations even without any context.

Pilot experiments (open-ended responses)

All pilot and main experiments were programmed and run using the *jsPsych* platform[37] with a

custom plugin (https://github.com/thefinnlab/psyanim-2) to present the *psyanim* animations.

Pilot experiment design

We first conducted a set of small-scale studies where participants could freely describe the

animations. Before imposing explicit, constrained rating scales, our goal was to verify that these

animations do in fact spontaneously evoke percepts that fall approximately along the intended

axes from non-social to social (detection task) or playful to aggressive (discrimination task).

In these experiments, each participant was presented with 7 animations (1 animation for

each level of the motion attribute as described under **Stimuli**). For the detection task, we did not

use the cover story. For the discrimination task we ran two versions – one without and one with

the cover story. In what follows, unless otherwise noted, we present data from the version *with*

the cover story. After watching each animation, participants responded to the following prompt

to indicate what the dots could have represented: "Briefly describe what the dots were doing.

Guess if you do not know." (In the discrimination task with the cover story, the text varied

slightly: "Describe what the dots were doing using a word or a short phrase"). The task lasted

~5-10 min overall.

Pilot experiment data analysis

We analyzed the free-response data using techniques from natural language processing. In each

experiment (detection and discrimination tasks), we derived the average "meaning" of

descriptions at each stimulus level using semantic embeddings. Specifically, we used

Bidirectional Encoder Representations from Transformers (BERT)[38] language models as

implemented in the Python library *SentenceTransformers* (https://huggingface.co/sentence-

transformers/all-MiniLM-L6-v2). For each description, we get a 384-dimensional vector

embedding. We then averaged across all embeddings at each stimulus level (detection task: 12

unique stimuli per level of *chase directness* x 5 observers per stimulus = 60 observations per

level of *chase directness*; discrimination task: 20 stimuli per level of *charge speed* x 5 observers

per stimulus = 100 observations per level of *charge speed*).

In an initial exploratory/data-driven analysis, we compared this mean vector to the

embeddings of *all* 8432 English verbs from the natural language toolkit (nltk;

https://www.nltk.org/howto/wordnet.html) to identify the 5 verbs whose embeddings it was

closest to. To more clearly isolate the *differences* in percepts across levels, we then removed

words that appeared in at least 6 of the 7 motion attribute levels within each experiment.

In a follow-up, more hypothesis-driven analysis, we quantified the change in percepts

across stimulus levels by computing the similarity of mean embeddings at each level to our

expected percepts at either ends of the response scale (detection task: "chasing", "moving

independently"; discrimination task: "playing", "fighting"). We expected that, as the motion

attribute value increased, descriptions' similarity to one extreme ("chasing" or "fighting") would

increase and similarity to the other extreme ("moving independently" or "playing") would

decrease. To quantify this, we took the difference between embeddings' similarity scores to both

extrema ($difference\_score = score\_chasing - score\_moving\_independently$ for the

detection task and $difference\_score = score\_fighting - score\_playing$ for the

discrimination task), giving us one difference_score per trial. Later, scores were compared using

a linear mixed effects model (LME; *pymer4* package[39]):

$difference\_score \sim motion\_attribute + (1|subID)$, where for the detection and

discrimination tasks, $motion\_attribute$ referred to *chase directness* and *charge speed*,

respectively.

Finally, for the discrimination task only, we quantified how the valence, or "sentiment",

of the descriptions varied across attribute levels. We used a RoBERTa-base model[40]

(https://huggingface.co/cardiffnlp/twitter-roberta-base-sentiment-latest/tree/main) to

automatically quantify sentiment, which yields a positive, negative, and neutral score for each

description. Our dependent variable $difference\_score$ was the difference between the negative

and positive sentiment scores for each description. Similar to the approach to semantic similarity

described in the previous analysis, the effect of the motion attribute (namely, *charge speed*) on

these values was computed using the LME: $difference\_score \sim charge\ speed +$

$(1|subID) + (1|stimID)$.

We noted that free-text descriptions were overall biased toward positive sentiment (Fig

S1c, left). This could likely be because of our cover story about the dots representing children in

a park, which carries a strong prior toward playful interactions. To check this, we ran an

additional small pilot batch without a cover story too (all else remained the same).

Results from the analyses of free text responses in these pilot experiments showed

evidence favoring our hypotheses that (1) in the detection study, as *chase directness* increases,

animations are seen as more social, and (2) in the discrimination study, as *charge speed*

increases, interactions are seen as more aggressive and negatively valenced. Together, the pilot

experiments confirmed that the stimuli we generated algorithmically could spontaneously—i.e.,

without prompting with explicit choices of possible interactions—evoke percepts along the

intended axes, and this gave us the confidence to move forward with our main experiments using

these axes to structure responses, described in the next section.

Main experiments

Main experiment design

Our first two main experiments consisted of only detection or only discrimination trials,

respectively, while the third main experiment was a mixed-task design in which the same

participants performed both the detection and discrimination tasks. We used the same cover story

described above (about the dots being children in a public park) in all the main experiments.

For the detection study, there were 84 trials per participant (12 trials per *chase directness*

level x 7 levels) with 7 optional breaks (one every 12 trials). In the supplementary experiments

that also included the invisible chase control condition, there were 6 stimuli at each motion

attribute level (2 conditions x 7 stimulus levels x 6 trials per level). After each trial, participants

gave two responses: (1) they rated, on a continuous scale, to what degree one of the two dots was

chasing the other versus moving independently (with the location of the labels on the left versus

right extremes of the scale kept constant within participant, but counterbalanced across

participants), (2) they identified the dot that was chasing the other, in a two-alternative forced

choice. Both questions were presented on the same page, and the page timed out in 10s. The

instruction specific to this task (after the cover story was presented) was as follows: "*Some*

videos depict a situation in which **one dot is chasing the other**; *other videos depict a situation in*

which the dots are **moving independently**. *You will be asked to* **rate how much you think the**

dots are interacting (meaning one dot is chasing the other) versus moving independently. *For*

all videos, you will also be asked to determine **which dot was chasing the other**. *If there was no*

chase in a particular video, just make a guess.". Participants performed one practice trial before

the experiment began.

For the discrimination study, there were 70 trials per participant (10 trials per *charge*

speed level x 7 levels) with 7 self-timed breaks (one every 10 trials). After each trial, participants

rated on a continuous scale to what degree the dots were engaged in a positive (playing) versus

negative (fighting) interaction (as with the detection task, the label positions were

counterbalanced across participants). This response page also timed out in 10s. The instruction

specific to this task (after the cover story was presented) was as follows: "*Some videos depict a*

*situation in which the children are engaged in a **positive interaction (e.g., playing)**; other videos*

*depict a situation in which the children are engaged in a **negative interaction (e.g., fighting)**.*

*After each video, you will be asked to **rate to what extent the children (dots) were engaged in a***

***positive or negative interaction** on a continuous bar. There are no right or wrong answers here,*

so if you are unsure, just guess!". Participants performed two practice trials before the

experiment.

In the third main experiment (mixed-task design study), detection and discrimination

animations were presented in six interleaved blocks: block sequence with 14 trials each (121212

or 212121, where 1=detection task and 2=discrimination task; one of the two block sequences

was randomly selected for each participant. Here too, there were 84 trials in total: 42 detection

trials (6 at each level of *chase directness*) and 42 discrimination trials (6 at each level of *charge*

speed). The 42 animations from each task (detection or discrimination) were randomized *across*

the 3 blocks of the task. Participants performed two practice trials each for the detection and

discrimination experiments at the start of the experiment.

The primary task portion of all three experiments (detection, discrimination, or mixed-

task design) lasted ~15-20 min. At the end of the primary task portion, we presented participants

with the trait questionnaires described below under **Trait measures**. The sequence of the

questionnaires was counterbalanced across participants.

Quality checks during data acquisition. We performed a few data quality checks during

data acquisition to exclude poor participants within the first few minutes of the study. First, after

the instructions, including the cover story about the dots representing children in a park, but

before the start of the main experiment, we presented participants with a multiple-choice

question as to what the dots represented. The options were "animals", "balls", "adults",

"children", "magnets". The correct answer was "children" (as mentioned clearly in the cover

story). If participants responded incorrectly, they were given one chance to correct their answer,

and if their second response was also incorrect, they were immediately excluded from the study.

(Note that this same question was asked again *after* the main task and used for a second quality-

check analysis, see below). Participants were also warned that they may not be compensated if

they missed (i.e., timed out on) more than 10% of trials. We also excluded participants who

413 opened other tabs or had bad internet connections by including a demo animation on the very

414 first page and checking playback duration in real time. If the duration of this page was much

415 higher than 6 or 8s (actual duration of the animations), this meant that the animation did not play

416 as normal, and either paused (because of other open tabs and the participant not paying attention)

417 or played very slowly (possibly because of a slow internet connection). Participants who stayed

418 on the demo animation page for longer than a liberal threshold of 20s were immediately

419 excluded from the study. Besides these online quality checks *during* the experiments, we

420 conducted further quality checks at the data analysis stage to exclude poor participants.

421 *Main experiment analysis*

422 Data analysis was similar across all main experiments unless specified otherwise.

424 *Exclusion criteria*

425 First, we excluded participants with bad or unreliable data, as defined by meeting one or more of

426 the following criteria: (i) missing responses (i.e., timing out) on more than 5% of all trials; (ii)

427 incorrect responses in the post-main-experiment debrief question asking them to identify what

428 the dots represented shown (note that this question is identical to the question asked at the

429 beginning of the main experiment, but the rationale here is that if by the end of the main

430 experiment participants had forgotten what the dots represented, their perception and ratings

431 could have been affected by whatever they assumed the dots to represent by the end); (iii) (for

432 the detection task alone) incorrectly identifying the predator in more than one third of animations

433 with directness=1 (rationale: the chase/predator identity is very obvious in these animations, so

434 incorrect answers here are most likely failures of attention); (iv) lingering on the animation page

435 for more than 20s in at least 5% of trials (each animation was only programmed to last 6 or 8s,

436 and so the page should have lasted for a similar duration; any longer indicates that they may have

437 clicked away from the experiment tab and/or had a slow internet connection); (v) failing to

438 respond to ≥ 10% of items on one or more trait questionnaires; or (vi) missing at least one (out of

439 five) attention-check items in the trait questionnaires. Trait questionnaires are described in detail

440 in the **Trait measures** section.

Separate detection and discrimination experiments

Group-level analyses: We first analyzed data at the group level to ascertain shared tendencies in

how motion attributes affect social percepts. Participants' ratings were coded on a 0–1 scale: (i)

detection task: *moving independently* = 0, *chasing* = 1; (ii) discrimination task: *playing* = 0 and

fighting = 1. For the detection task, we used the response to the predator identification question

to compute accuracy (0 or 1 on each trial). We used linear mixed-effects analyses to quantify the

effect of each motion attribute while controlling for confounding variables using the following

model: $rating \sim motion\_attribute\_level + mean\_dist + trial\_number + (1|subID) +$

$(1|stimID)$. Here $rating$ refers to participant responses indicating the level of

$socialness$ (degree of *chasing*) or $aggressiveness$ (degree of *fighting*). The term

$motion\_attribute\_level$ refers to degree of either $chase\ directness$ (detection) or

$charge\ speed$ (discrimination) and could take one of 7 levels. Additional terms are: (i)

$mean\_dist$, the distance between the two agents averaged across all frames; we included this

term because past work has shown that agents that are closer together are more likely to be

perceived as interacting[6]; (ii) trial number, indicating serial order over the course of the

experiment (to check for any drift in ratings over time); and random-effects terms for (iii) subject

identity and (iv) specific animation identity (exemplar). For the predator-identification question

in the detection task, we ran a logistic regression model with $accuracy$ (0/1) as the dependent

variable and the same main- and random-effects predictor terms as above.

Individual-level analyses: We next analyzed data at the individual level to determine the extent

to which participants differed in their socio-perceptual tendencies, how robust these differences

were across sessions, and how detection and discrimination tendencies covary with one another

and with other socio-affective traits. Our primary approach to analyzing individual-level data

was to compute single-subject "tuning curves" for detection and/or discrimination behavior. We

averaged each participant's responses at each motion attribute level (*chase directness* or *charge*

speed level for detection and discrimination tasks, respectively). For each participant, we plotted

motion attribute level (normalized to a 0-1 range; x-axis) against average rating across

animations at that level (y-axis). Similar to the group-level results shown in Fig 3, visual

inspection suggested that individual detection ratings followed a sigmoid shape, while

discrimination ratings followed a more linear trend. We empirically tested both sigmoid and

linear fits to evaluate which one better fit each type of data and verified this pattern: the Akaike

Information Criterion (AIC) – which indicates which of two models fits the data better (lower

AIC indicates better fits) – was lower for the sigmoid fits in the detection task (mean difference

sigmoid – linear fits $\leq$ –7.84, p <.001 based on paired t-test in all the detection experiments) and

higher for the sigmoid fits in the discrimination task (mean difference sigmoid – linear fits $\geq$

3.47, p <.001 in all the discrimination experiments, Fig S2). Hence, we used sigmoid fits to

characterize each participant's response data in the detection task and linear fits to characterize

responses in the discrimination task.

482   The sigmoid curve-fitting equation was : $S(x) = \gamma + (1 - \gamma - \lambda) \dfrac{1}{1 - e^{-\frac{(x-\alpha)}{\beta}}}$, where $x =$

483   the value of the motion attribute (*chase directness* or *charge speed*); γ and $\lambda =$ the lower/upper

484   asymptote of the curve; α, β = center, slope. The linear equation was: $L(x) = c + m * x$,

485   where $x =$ the motion attribute (*chase directness* or *charge speed*); c = the lower intercept of the

486   line; m = slope. For both functions, we calculated several key parameters from the fitted curve of

487   each participant:

488   *Shifts from extremes*: Lower bias lb and upper bias ub (lower and upper intercepts,

489   respectively) reflect ratings at the lowest and highest levels of the motion attribute — in other

490   words, how close to the extremes of the rating scale a participant is willing to go. For linear fits,

491   lb = intercept c.

492   *Bias*: This parameter was derived from the above-mentioned bias terms (lb and ub) as a

comprehensive summary of people's bias that also factors in apparent biases due to differences

in overall confidence or perceptual vividness. The bias term thus measures to what degree people

avoid the lowest end of the scale relative to how much they avoid the two ends of the scale in

general (which could reflect lower confidence overall or a less intense effect of stimuli overall).

We quantified this as $\dfrac{lb}{lb+ub}$. A bias of 0.5 means that there is no bias towards one end of the

scale, bias < 0.5 means that people are more biased towards the lower end, and bias > 0.5 means

that people are more biased towards the upper end. In the detection task, bias > 0.5 can be

interpreted as a predisposition to see things as social ("chasing") more than non-social ("moving

independently"); in the discrimination task, bias > 0.5 can be interpreted as a predisposition

toward seeing things as more like "fighting" than "playing".

Midpoints: Two types of midpoints can be derived from each curve: an objective

midpoint $(x_{obj} = f^{-1}(S(x) = 0.5))$ and a subjective midpoint (subj_center, α). The objective

midpoint is the motion attribute value at which the participant's rating crosses the absolute

midpoint of the rating scale (0.5 for all participants). The subjective midpoint is the motion

attribute value at which the participant's rating crosses the halfway point of *their own* behavioral

curve (e.g., for a participant whose ratings vary between from 0.4 and 0.8, their mid-point would

be the motion attribute level at which the tuning curve crosses 0.6). Here we mostly focus here

on the objective midpoint, which we call the point of subjective equivalence (**PSE**) because it is

similar in spirit to PSE as defined in traditional visual psychophysics work (i.e., the stimulus

feature level at which options A and B are equally likely in a two-alternative forced-choice

discrimination task [41]).

Range: The distance between the lowest and highest ratings on the Y-axis. This

parameter can be interpreted in multiple ways: it quantifies how much of the total response scale

participants use, how much participants differentiate between stimuli at extreme (lowest and

highest end) motion attribute levels, and except in cases of strong response biases, might reflect

how confident people are in their percepts (especially at the lowest and highest motion attribute

values). This is defined as $1 - lb - ub$.

Sigma (σ; sigmoid fit only): Sigma or the inverse of the slope ($\frac{1}{\beta}$) determines the steepness

of the sigmoid curve during its transition from perceiving something as "moving independently"

(at lower *chase directness* levels) to "chasing" (at higher *chase directness* levels) in the detection

task. A smaller sigma (or a higher slope) indicates that participants perceive something as more

social (Δ_{rating}) with the smallest change in the sensory evidence (change in *chase directness* or

$\Delta_{\text{chase directness}}$) — this can be interpreted as people exhibiting higher confidence when rating the

intermediate, ambiguous stimuli. A higher sigma (or lower slope) indicates that participants need

a lot more sensory evidence ($\Delta_{\text{chase directness}}$) to rate something as more social (Δ_{rating}) — this may reflect

lower confidence and/or a more gradual evidence-based shift in the perceptual intensity of

stimuli at the ambiguous middle levels.

We plotted covariance matrices (Pearson *r*) between the various parameters within the

detection and discrimination tasks. Based on these covariances as well as test-retest reliability of

the curve fit parameters (described in detail below), in what follows, we focus on three main

curve-fit parameters that are both relatively reliable and not highly collinear with one another:

PSE, range and bias. These terms are illustrated in Fig 2. Since PSE covaries tightly with range

and bias in the linear fits specifically and it is not possible to change PSE without changing

either the range or the bias, we only use range and bias for the discrimination task.

Fig 2: Fitting social tuning curves to individuals' reported percepts. (a) We fit sigmoid

(detection experiments; top) or linear (discrimination experiments; bottom) curves to individual-

participant rating data and used the resulting curve parameters to characterize individual

participants. (b) Schematics of how each parameter can vary across participants. The upper

rows show sigmoid fits as used for the detection task, and the lower rows show the linear fits

used for the discrimination task. Each plot shows curves for three different hypothetical

participants.

We tested the robustness of each person's tuning curve by using parameters calculated on

data from their first session to fit the same participant's data in their second session 1–2 months

later (and vice versa) and calculating the residual normalized root-mean squared error (NRMSE)

between the curve and the true data points. We used a paired t-test to compare the NRMSE from

this within-participant fit to the NRMSE from the mean across-participant fit (calculated by

averaging the curve-fit parameter values across all other participants in the same session. This

quantified the extent to which an individual's tuning curve offered a better prediction of their

own held-out data than generic tuning curves based on group data. Further, we calculated the

intra-class correlation coefficient (ICC) of each curve-fit parameter of interest to measure test-

retest reliability across the two sessions (ICC2, single random raters, as implemented by the

Python package *pingouin*).

Mixed-task experiments

In these experiments, the same participants performed both the detection and discrimination

tasks. Data extraction and curve-fitting was performed similarly to the separate detection and

discrimination experiments described above. For each participant, we obtained tuning curves for

both detection and discrimination. We studied how socio-perceptual tendencies in the two tasks

relate by calculating the Pearson correlation coefficient between all possible pairs of curve-fit

parameters across the detection and discrimination tasks. Here, we restricted our analyses to only

the most robust curve-fit parameters: bias, range and PSE for the detection task, and bias and

range for the discrimination task (5 total).

568   Traits were scored as described under **Trait measures**, giving us 14 dimensions in total

569   (5 for AQ, 2 for PANAS, 5 for NEO-FFI, 1 for loneliness and 1 for number of friends). As a

570   first-level exploratory analysis, we first performed trait-behavior correlations (Pearson *r*)

571   between each trait dimension and curve fit parameter (14 x 5 = 70 total correlations). We report

572   both uncorrected results and results after correcting for multiple comparisons using the

573   Benjamini-Hochberg procedure.

574   We next performed inter-subject representational similarity analysis (IS-RSA)[42] to test

the second-order hypothesis that pairs of subjects who are more similar in their curve-fit

parameters are also more similar in their pattern of trait scores. Specifically, we computed a set

of subject-by-subject representational dissimilarity matrices (RDMs) reflecting the Euclidean

distance between each pair of subjects': (i) pattern of trait scores (14x1 vectors), (ii) detection

tuning curve parameters (3x1 vectors), (iii) discrimination tuning curve parameters (2x1 vectors),

or (iv) combined tuning curve parameters across both tasks (5x1 vectors). We then correlated

(Pearson *r*) the vectorized upper triangles of the trait RDM with each of the three curve-

parameter RDMs. We assessed the significance of each IS-RSA r value non-parametrically using

a Mantel test, in which subject-vector assignment is randomly shuffled in one of the two RDMs

5,000 times to generate a null distribution of *r* values expected by chance. The true *r* value is

compared against this null distribution to derive a *p* value using the formula:

$$p = \frac{(\text{\# permutations exceeding true value} + 1)}{(\text{\# permutations} + 1)}.$$

Trait measures

We chose individual-difference measures of interest based on past findings that behavior on

social perception and cognition tasks often differs between populations (e.g., neurotypical versus

autistic, patients with depression versus healthy controls) and/or covaries in the normative

population with socio-affective and personality traits. Past work has shown that people higher on

autism-like phenotypes are less likely to detect intentions and interactions in social animation

displays[6–10], while people with higher internalizing symptom scores (related to anxiety and social

withdrawal) and a higher desire for social connection are *more* likely to detect intentions and

interactions[5,43–46]. Other studies have associated depression with impaired emotion recognition of

social stimuli (hypersensitivity to negative cues, hyposensitivity to positive cues)[14–17]. We

assessed autism-like traits with the autism quotient (AQ) questionnaire[47], loneliness with the

UCLA loneliness scale[48], and general affect with the Positive and Negative Affect Schedule

(PANAS)[49]. We also administered the NEO five-factor inventory for multidimensional

personality (NEO-FFI; more popularly known as the "Big five")[50]. Finally, we asked participants

to state the number of close friends they had, since this metric provides additional information

about participants' real-world social tendencies.

Our final battery thus consisted of five entities: (i) AQ, (ii) PANAS, (iii) NEO-FFI, (iv)

UCLA loneliness scale and (v) the self-reported number of friends. Details of each questionnaire

are given below.

The AQ consists of 50 total items measuring five subdomains: social skill deficits,

communication deficits, attention-switching deficits, heightened attention to details and

imagination deficits. For each item, participants had four response choices ("Definitely

disagree", "Slightly disagree", "Slightly agree", "Definitely agree"). We reverse-scored the items

that were intended to be as per the instructions from the creators; however, when assigning a

score on each item, we assigned responses scores between 0 and 3 (where 3 → less neurotypical

and more autistic) in place of binarizing responses (assigning 0 to the first two levels and 1 to the

last two levels). Higher scores on each subdomain indicate more autism-like phenotypes (e.g.,

greater social skill deficits).

PANAS consists of 20 total items, 10 measuring positive affect and 10 measuring

negative affect. Participants responded on a five-point scale ("Very slightly or not at all ", "A

little", "Moderately", "Quite a bit", "Extremely"). Each response was coded between 0 and 4, and

there were no reverse-scored items. This scale results in separate scores for positive and negative

affect.

NEO-FFI consists of 60 total items measuring five dimensions: openness, extraversion,

neuroticism, conscientiousness, agreeableness. Participants responded on a five-point scale

("Strongly disagree", "Disagree", "Neutral", "Agree", "Strongly agree") coded between 1 and 5.

This scale yields a summary score for each of the five dimensions.

The UCLA loneliness scale consists of 20 total items that measure a single dimension.

Participants responded on a 4-point scale ("Never", "Rarely", "Sometimes", "Always") scored

between 1 and 4. Higher scores indicate higher loneliness. Lastly, participants also responded to

the following question with an integer value: "*Please estimate the number of **close friends** that*

you have, where "close friends" are people that you feel at ease with and can talk to about

private matters."

Within each questionnaire we also added one attention check question (e.g., for AQ, the

question was this: "If you are doing your best to complete this survey honestly, choose

'Definitely agree'.") to confirm that participants were paying attention to the questions. The

accuracy on these questions was used as a quality check criterion during data pre-processing

(described under *Main experiment analysis*).

Code and data availability

636   All stimuli, data and code will be available upon publication at:

637   https://github.com/thefinnlab/psyanim_behav_paper1

Results

We systematically studied how people perceive the presence and nature of a social interaction using sets of algorithmically generated fully parameterized animations. Each animation consisted of two agents—one gray and one black circle—that were programmed to move in certain ways with respect to one another. Critically, the animations varied parametrically along one motion attribute and were controlled for all other low-level visual features. We conducted three sets of experiments: (1) detection studies, in which participants rated the extent to which the agents appeared to be interacting (i.e., one agent chasing another) versus moving independently, (2) discrimination studies, in which participants rated the extent to which the agents appeared to be fighting versus playing, and (3) a mixed-task study where participants performed both the detection and discrimination experiments (see stimuli [here](#) and details in Fig 1). Below, we describe group-level and individual behavioral patterns for both social detection and discrimination, as well as how these two behaviors compare to one other and to self-reported social and affective traits.

Simple motion attributes influence the detection of both the presence and nature of social interactions

Varying simple motion attributes reliably affects social percepts at the group level

For detection experiments, we varied the attribute *chase directness*, which determines the fidelity with which the movement of one agent (the predator) is contingent on the other agent (the prey): more direct chases should look more obviously social, less direct chases should look more like agents moving independently. For discrimination experiments, in which the two agents come together and move apart in succession, we varied the attribute *charge speed*, which determines how fast the agents approach one another: slower should look more playful, faster should look more aggressive/fight-like.

Pilot experiments

We first performed pilot experiments to test that these animations could spontaneously evoke

percepts along the intended continua without any explicit prompting. In these experiments,

participants watched animations and gave free-response text descriptions, which we quantified

using tools from natural language processing. Indeed, we found that varying *chase directness*

elicited percepts along a continuum from moving independently (non-social) to chasing (social),

while varying *charge speed* elicited percepts along a continuum from positive/playing to

negative/fighting (see **Supplementary Results** and Fig S1). These results gave us confidence to

move forward to our main experiments, in which we replaced free responses with these continua

as predetermined rating scales.

Detection experiments

In our main social detection experiments (see Table 1 for sample sizes and other relevant

information), after watching each animation, participants (1) rated how social it was on a

continuous scale ranging from "moving independently" to "chasing" (henceforth referred to as

"socialness rating"), and (2) identified the predator agent by color. In line with our expectations

and past work [22], we found that as chase directness increased, ratings shifted towards "chasing"

(b=0.805, p<.001; Fig 3a). Social perception did not seem to change with time (indexed as the

trial number; b=–0.001, p=.779), suggesting that there was no measurable "drift" in ratings

toward more social or more non-social over the course of the experiment. We also observed that,

similar to subjective ratings, predator identification accuracy increased as chases became more

direct (logistic regression b=4.735, p<.001; Fig S3a); this result further confirmed that

participants were, on average, experiencing the chase in the expected way based on the

generating algorithm (i.e., they correctly perceived its directionality, especially in the case of the

more direct chases).

Participants might have been using visual features other than *chase directness* to form

their judgments of socialness. For example, past work has shown that agents that are closer

together are more likely to be perceived as interacting[6]. That more-direct chases also resulted in a

narrowing of the distance between the two agents over time was an unavoidable consequence of

our animation-generation algorithm (where the predator was programmed to chase after the

prey); indeed, in our stimulus set, chase directness and mean distance between agents over the

course of the animation were correlated across animations (Pearson r=–0.69, p<.001). Hence, to

account for other visual features beyond *chase directness* that participants may have been using,

we ran additional models including mean distance between agents as a covariate. While this term

was also a significant predictor of socialness ratings (b=–0.432, p<.001) and this model fit the

data better (AIC=–12325 compared to the AIC of the model without mean distance, –12293;

lower AIC indicates a better fit), *chase directness* captured additional unique variance in

socialness percepts (b=0.603, p<.001). Further, mean distance was not a predictor of the predator

identification accuracy (b=–0.716, p=.179) and also did not meaningfully improve the model fit

for accuracy (AIC without and with mean distance = –7986 and –7984, respectively).

Lastly, participants may have been relying on other heuristics to form socialness

judgments. Since a chase typically results in correlated movement patterns between two agents

(when the prey changes direction, the predator is likely to do so a moment later), this correlation

will be stronger for more direct chases than less direct chases. However, agents can also show

correlated motion without necessarily having one chase the other—i.e., one agent could change

direction every time the other one does but be equally likely to turn away from (or orthogonal to)

the path of the other. To test whether participants are simply relying on nonspecific correlated

motion as a heuristic, also inspired by Gao et al.[22], we ran a separate experiment in an

independent set of participants where we replaced half of the directness 0.167 to 1 chases (6

levels) with a non-social "invisible chase" control. In these trials, the predator was chasing a true

prey agent that was made invisible to observers, while a visible "fake" prey mimicked the true

prey's trajectory reflected over a 180° rotation. In this way, correlated motion between the two

agents was preserved—when the true prey changed direction, so did both visible agents (the

predator and the mimicking agent)—but not necessarily in a manner consistent with chasing. In

line with our prediction, we saw that while in the true chase condition, socialness ratings

increased with *chase directness* (b=0.471, p<.001), in the invisible chase condition, if anything,

there was a slight trend in the opposite direction (socialness ratings decreased as directness

increased; b=–0.146, p<.001; Fig S3b). This suggests that the increase in socialness with chase

directness is not merely because of correlated motion in general, but rather correlated motion that

is specifically consistent with pursuit behavior. In sum, in line with Gao et al.[22], these

experiments show that the motion attribute *chase directness* influences how social stimuli are

perceived to be at the group level.

Discrimination task

Once a social interaction is detected, the next step is to discriminate the *nature* of that

interaction; past work[20,30] and real-life experience suggest that given the same sensory input,

there may be even more variability across people in their percepts of *how* agents are interacting

than simply *if* they are interacting. Interactions can be characterized along several dimensions,

but a fundamental one is valence—i.e., how positive or negative is the interaction?[51] Using our

parametric approach, we explored changes in the valence of social percepts between "playing"

and "fighting". Playing and fighting, which are preserved throughout much of the animal

kingdom, involve two agents moving apart and coming back together in quick succession. We

manipulated the speed with which our agents approached each other (*charge speed*) to determine

whether this simple motion cue could reliably affect percepts of an interaction's valence, with

slower speeds looking more friendly (like "playing") and higher speeds looking more aggressive

(like "fighting").

In these experiments (see Table 1), participants watched each animation and rated it on a

continuous scale from "playing" to "fighting". We found that as the *charge speed* increased,

interactions were perceived as more aggressive (b = 0.622, p < .001; Fig 3b). The effect of

charge speed persisted when controlling for the mean distance between the two agents (which

also affected ratings such that higher mean distances predicted slightly less aggressive ratings;

b=−0.057, p=.008)) and trial number as an index of time (for which we found that percepts of

aggressiveness also weakly increased over the course of the experiment; b=0.024, p<.001).

Together, results indicate that social percepts—both the presence and nature of an

interaction—can be manipulated by simple motion attributes in ways that are generally shared

across people. Despite these commonalities, to what extent are there stable and meaningful

individual differences in these socio-perceptual tendencies? We probe this question next.

Fig 3: Group-level behavior on the detection and discrimination tasks. (a) As chases become

more direct, observers were more likely to report percepts closer to the "chasing" (social

interaction) end of the scale. At less direct chases, ratings were lower (i.e., closer to "moving

independently ["moving ind."]). (b) As the charge speed (speed at which agents charge at each

other) increased, interactions were perceived to be more aggressive (closer to the "fighting" end

of the scale). At lower charge speeds, ratings were closer to "playing". N= 312 and 319 in

panels (a) and (b), respectively. Errorbars represent the 95% confidence interval.

759 Robust individual differences in social perception exist atop group-level

760 tendencies

Even given these shared general tendencies, individuals often vary in their percepts of social

interactions, especially when faced with ambiguous scenarios. To quantify this across-subject

variability, inspired by psychophysics approaches, we fit individual participants' rating data with

a sigmoid (detection experiments) or linear function (discrimination experiments; see **Methods**)

to derive individual "social tuning curves". For detection curves, we focused on three main

parameters: (i) point of subjective equality (PSE), the value of *chase directness* at which the

participant's percept crosses the midpoint of the rating scale (0.5); higher values indicate that

more evidence is needed to declare something "social"; (ii) range, the difference between ratings

at the lowest (0) and highest (1) levels of *chase directness*; higher values may reflect higher

perceptual vividness, certainty or diversity in percepts; and (iii) bias, the extent to which ratings

are skewed toward one end of the scale; higher values (> 0.5) indicate a bias toward social

("chasing") while lower values (< 0.05) indicate a bias toward nonsocial ("moving

independently"). For discrimination curves, we focused on two main parameters: (i) range, the

difference between ratings at the lowest (0) and highest (1) levels of *charge speed*; higher values

may reflect higher perceptual vividness, certainty or diversity in percepts; and (ii) bias, the extent

to which ratings are skewed toward one end of the scale; higher values (> 0.5) indicate a bias

toward "fighting" while lower values (< 0.5) indicate a bias toward "playing". See Fig 2 for a

schematic of these parameters.

While the vast majority of subjects showed the same general directionality as the group-

level trends, fine-grained properties of tuning curves differed between subjects (see Fig 4a for

sample participants [all data in Fig S4 and S5] and Fig 4b for full distributions of parameters of

interest). To test the stability of these tuning curves within participants, we had participants

return for a second session 1–2 months later, in which the task design was identical to the first

session except that we used previously unseen animations (generated using the same algorithms).

Visual inspection showed that idiosyncrasies in behavior and tuning curves were largely

preserved across sessions (e.g., Fig 4a).

We quantified the stability and uniqueness of tuning curves in two ways. First, we used

parameters calculated on data from a participant's first session to fit the same participant's data

in their second session (or vice versa). To test the extent to which curve parameters were both

stable within people and distinct across people, we compared this within-participant fit to the

mean across-participant fit calculated by using each participant's curve to fit data from all other

participants in the same session. Participants' ratings were generally better predicted by their

own curves from a different session than the average of everyone else's curves in the same

sessions (Fig 4c, middle and right violin plots within each subplot; outliers omitted for clarity;

detection task: mean difference (MD)=0.04 and 0.05 when fitting session 2 data to session 1 and

vice versa, both p<.001; discrimination task: MD=0.07 (p=.006) and 0.08 (p=.06) when fitting

session 2 data to session 1 and vice versa). Second, we calculated the intra-class correlation

coefficient between parameters fit to data within each session for each parameter of interest. In

the detection task (sigmoid fit), PSE, range and bias showed moderate to good reliability; in the

discrimination task (linear fit), slope and bias showed generally moderate reliability (Fig 4d; see

Fig S6a-b for data on other parameters that were less reliable and/or redundant with the main

curve-fit parameters of interest and Fig S6c for the covariance between all curve-fit parameters).

Overall, then, individual tuning curves for both social detection and discrimination were both

stable within subjects (reliable across sessions) and unique between subjects, suggesting a trait-

like component.

Fig 4: Individual differences in social tuning curves. (a) Tuning curves for sample participants

in two distinct sessions. Dots represent mean ratings at each motion attribute level, and the line

shows the best fitting sigmoid (detection) or linear curve (discrimination). For the full versions,

see Fig S4 and S5. (b) Histograms showing the full distributions of the main curve-fit parameters

of interest from all subjects in session 1 (left, detection experiment; right, discrimination

experiment). PSE, point of subjective equality. (c) Predicting individuals' single-session ratings

using curve parameters fit to their own data from the same session (left), their own data from a

different session (middle), or the average parameters from all other participants in the same

session (right). NRMSE=normalized root mean square error; lower values indicate better fits.

(d) Test-retest reliability between sessions 1 and 2 of the main curve-fit parameters of interest.

Each dot represents a participant. Test-retest reliability for other parameters is shown in Fig S6.

***= p < .001, **= p < .01, ·= p<.1.

Individual social detection and discrimination tendencies are only weakly related

Social detection and discrimination both exhibit shared tendencies as well as robust individual

differences, but how do behaviors relate across the two tasks? In other words, are individuals'

discrimination tendencies predictable from their detection tendencies (and vice versa)? For

example, people who are more prone to seeing social interactions in the first place might also be

more prone to seeing them in a more positive (or negative) light. To study this, we conducted a

third experiment in which a new set of participants performed both the detection and

discrimination tasks in interleaved blocks in a single session. We successfully replicated the

group-level behavioral trends (Fig 3) in this new group of people (see Fig S7). We then fit

sigmoid and linear curves to each individual's detection and discrimination data, respectively. As

a sanity check, we verified that the covariances across curve-fit parameters within each task

(detection task: PSE, range, bias; discrimination task: range, bias) were comparable to earlier

experiments (Fig 5).

Next, we correlated curve-fit parameters across participants both within and across tasks.

Focusing on between-task correlations (highlighted part of the matrix in Fig 5), the majority of

pairwise correlations were weak, suggesting that detection and discrimination behavior are

overall relatively independent. We did, however, find two significant relationships. First, the

"range" parameter correlated moderately across tasks (r=0.44, q<.05). This indicates that people

who distinguished social ("chasing") from non-social ("moving independently") more strongly

also distinguished negative interactions ("fighting") more from positive interactions ("playing")

more strongly. This could reflect people's general confidence/willingness to use extremes

(people who are more confident may have used a wider range of the rating scale in both tasks)

and/or the extent to which their percepts are sensitive to sensory evidence (people whose

percepts vary more strongly with sensory evidence would have a higher range in both tasks). The

second result was that people who showed a higher bias toward socialness ("chasing") in the

detection task also showed a higher range (more distance between extremes) in the

discrimination task (r=.39, q<.05). This suggests that people who are more predisposed to

detecting social interactions may also be more sensitive to motion cues and/or more certain when

discriminating between different types of interactions. Still, on the whole, social discrimination

tendencies were largely not directly predictable from detection tendencies and vice versa. This

suggests that behavior on the two tasks may be complementary in revealing individual

differences in social perception, and combining information about detection and discrimination

tuning curves likely better characterizes individuals' socio-perceptual tendencies than one task

alone.

Fig 5: Correlation between the main curve-fit parameters of interest from the social detection

and discrimination tasks in the mixed-design experiment (within-subject design). Across tasks

(black box), only two moderate pairwise correlations emerged, suggesting that each task

provides non-redundant information on individuals' socio-perceptual tendencies. Significant

correlations (FDR q < .05) are displayed in bold text.

Combining individuals' social detection and discrimination behavior best

relates to trait differences

How do socio-perceptual tendencies as measured by behavior on our detection and

discrimination tasks relate to real-world variability in social function? In past work, behavior on

related tasks has been found to differ in various clinical and subclinical conditions including

autism[6–10], internalizing symptoms[5], depression[14–17] and loneliness[44,45]. In our final set of

analyses, we studied if and how properties of individuals' social tuning curves covaried with

social, affective, and personality traits as measured by established self-report scales (see

Methods for details).

873   We first performed exploratory correlations between all trait scores (14 total) with all 5 (3

for detection, 2 for discrimination) curve-fit parameters. Although some significant correlations

emerged, none survived multiple comparison corrections (Fig 6a). The uncorrected correlations

suggested that: (1) more extraverted (E) individuals had lower social thresholds (PSE) in the

detection task; (2) individuals with higher communication deficits (comm) had less of a bias

toward "social" responses, and individuals with (3) higher openness (O) and (4) lower negative

affect (neg) showed higher uncertainty (lower range) in discriminating between positive and

negative interactions. The first two of these were in line with past work and our *a priori*

hypothesis that individuals with social interaction deficits might have higher thresholds (i.e.,

need more evidence) to detect social information.

883   One possibility is that, rather than first-order relationships between single tuning-curve

parameters and single trait dimensions, relationships between traits and social detection/

discrimination behavior are more complex—perhaps multivariate and/or nonlinear. To explore

this possibility, we used inter-subject representational similarity analysis (IS-RSA[42]) to test for a

second-order relationship: in other words, to test the hypothesis that individuals with more

similar tuning curves in one or both tasks are also more similar in their pattern of trait scores.

Results showed that indeed, we could recover such a second-order relationship, but the effect

was significant only when combining information about tuning curves from both detection and

discrimination tasks (Fig 6b). Thus, features of individuals' social detection and discrimination

behavior in our controlled experimental setting may carry a meaningful, albeit weak, signal as to

self-reported real-world social functioning. Taken alongside the relatively weak correlations

between detection and discrimination tuning curves seen in the previous section, these results

suggest that social detection and discrimination behavior each carry unique information about an

individual's socio-perceptual tendencies.

Fig 6: (a) Exploratory pairwise Pearson correlations between each trait score and each curve fit parameter in both the detection and discrimination tasks (exploratory analysis). Correlations that are significant at p < 0.05 (uncorrected for multiple comparisons) are shown in darker red/blue. (b) Results from an inter-subject representational similarity analysis (IS-RSA) testing the second-order hypothesis that pairs of participants with more similar socio-perceptual tendencies on our task(s) also have more similar patterns of trait scores. This relationship is significant only when combining parameters from both detection and discrimination tasks (purple), not when using parameters from a single task alone (blue and red). Abbreviations: Autism Quotient (AQ) questionnaire subscales – 'soc': social skill deficits, 'attn': attention-switching deficits, 'img': imagination deficits, 'det': heightened attention-to-detail and 'comm': communication deficits; Positive and Negative Affect Schedule (PANAS) subscales – 'pos': positive affect and 'neg': negative affect; Big 5 (NEO-FFI) subscales – 'N': neuroticism, 'E':

911 *extraversion, 'O': openness, 'A': agreeableness and 'C': conscientiousness; 'UCLA': UCLA*

912 *loneliness scale; '# fr.': number of friends.*

Discussion

Here, we used a psychophysics-inspired approach to characterize both group-level tendencies

and individual differences in social perception. We found both strong commonalities in how

people use relatively low-level motion attributes to arrive at percepts of the presence (detection

experiments) and nature (discrimination experiments) of a social interaction, and robust

individual differences that were replicable over a period of months and showed some—albeit

weak and complex—relationships to trait phenotypes.

Our approach lends a level of rigor and precision to the study of social perception.

While some notable past work has used parametric stimulus manipulations[22,52–56], here, we

extend this approach to individual-subject data to recover single-person social tuning curves that

are both reliable and unique. Generating stimuli algorithmically makes our approach

simultaneously more objective and more subjective: more objective because we can create

parametric manipulations using quantitatively defined features (rather than relying on

handcrafted stimuli created and labeled via experimenter intuition[30]) and thereby generalize

beyond item-level effects, and more subjective because we are eschewing any notions of a

ground truth and classifying behavior according to observers' own reports[57], which better reflects

what happens in the real world—where different people can and do interpret the same social

situation differently.

Social cognition is traditionally considered a high-level abstract cognitive process,

but more recent work has found evidence that recognizing and processing social information

begins earlier in the perceptual hierarchy than previously thought[26,56,58–60], and artificial

intelligence can extract basic cues as to the presence and nature of social information using fast,

automatic, visually-based processes[56]. The recently proposed "third visual pathway" in the brain,

which runs along the lateral surface from early visual regions into the superior temporal sulcus

and is specialized for extracting social information from dynamic cues, embodies the theory that

our visual system might be especially attuned to social information, given its evolutionary

importance[59]. Our work adds to this growing body of work by showing that parametrically

varying meaningful "mid-level" visual motion attributes[61] even in very stripped-down, simplified

stimuli can directly modulate social percepts at both the group and individual level, thus

confirming that social perception involves visual evidence accumulation with both an objective

and subjective component. Of note, autism is a condition marked by deficits with social

cognition, but also altered basic visual processing[62,63]; the idea that perception is the fundamental

starting point for social cognition might lead us to discover hierarchical links between

aberrations in these two domains.

While the motion attributes we used here, *chase directness* and *charge speed*, were

sufficient to evoke varying social detection and discrimination percepts respectively, we also

acknowledge that social percepts are governed by many more dimensions than these two. We

propose the idea of individual social perception "landscapes" that can be conceptualized as a

multidimensional space spanned by objectively defined axes (e.g., motion attributes such as our

chase directness and *charge speed*, plus many others) where the dimensions themselves are

fixed, but sensitivity to these dimensions varies across people and can be expressed in terms of

tuning curve parameters. In Fig 7, we show a two-dimensional schematic of what these

landscapes might look like and how they might vary. In this example, the horizontal axis

represents an attribute that influences *if* a social interaction is perceived (detection; e.g., *chase*

directness) and the vertical axis represents an attribute that influences *how* a social interaction is

perceived (discrimination; e.g., *charge speed*). A healthy neurotypical individual (Fig 7a) might

show moderate sensitivity to objective evidence for socialness (indicated by the saturation

gradient along the horizontal axis); once information is generally deemed social, percepts of the

nature of that information are generally balanced between positive and negative interactions

(even vertical distribution of pink and blue). On the other hand, someone with an autism-like

phenotype (Fig 7b) might have lower sensitivity to social information—in other words, they

might require higher doses of objective evidence to detect a social interaction. For someone with

a depression-like phenotype (Fig 7c), detection sensitivity may be largely normal, but

discrimination might be skewed toward negative percepts. Lastly, someone with

psychosis/paranoia-like traits (Fig 7d) might show both heightened sensitivity to socialness and a

bias towards negative percepts—in other words, a proneness to read social intentions,

particularly nefarious ones, into scenarios that others might perceive as non-social or, at most,

social yet neutral. While we explored only two possible dimensions here, and did not include

clinical populations, we see the present set of experiments as a first step toward discovering and

characterizing these landscapes—which, because they are based on more implicit behavioral

readouts, are possibly less prone to overt bias than self-report measures and therefore a useful

complement to existing trait scales. Importantly, our results showed that relationships with

classical traits emerged only when combining the two tasks (detection and discrimination),

indicating that each axis carries unique variance; adding more dimensions (i.e., using more

complex, yet still parameterized stimuli) will likely enhance our ability to characterize real-world

social and affective function.

Fig 7. 2D projection of social perception landscapes with detection (not social ↔ social) and

discrimination (positive ↔ negative) along the horizontal and vertical axes, respectively. How

subjective percepts of the presence and nature of social interactions may present in (a) a

neurotypical individual versus individuals with (b) autistic, (c) depressive or (d) psychotic traits

who show, respectively, reduced progression towards social with sensory evidence (large faded

area), increased biases towards negative percepts (large blue zone even at typically neutral or

positive evidence), and an increased social sensitivity as well as bias towards negative (leftward

saturation combined with expanded blue territory), respectively.

Future work can combine our psychophysics-inspired task framework with additional readouts such as reaction times, eye-tracking, physiological measures and/or neuroimaging to yield a more comprehensive picture of the evidence accumulation and decision-making strategies, attentional processes, and other computations underlying individuals' social-perceptual judgments. There may be a role for generative AI in bridging the gap between the highly impoverished stimuli used here and the full complexity of real-world social information— i.e., we may be able to use generative AI to create more naturalistic-feeling stimuli that are nevertheless still parameterized along known axes. In closing, we note that while the vast majority of past work on social perception and cognition has focused on passive (third person) perception of others' interactions—which is indeed an important part of social cognition—many of our most salient and important social experiences are ones in which we are an active (first-person) participant. One final advantage of our framework is that it can be easily adapted to a first-person context, in which participants themselves are controlling one of the agents and the other agents are programmed to behave in a certain way toward them. This opens the door to generating and comparing social tuning curves between passive and active scenarios, as well as extracting more latent behavioral readouts such as participants' movement trajectories, which we anticipate will provide an even richer and more useful picture of social perception at both the group and individual levels.

Acknowledgements

This work was funded by R01MH129648 (E.S.F.), Neukom CompX Faculty Grant (E.S.F.). We thank Tommy Botch and Clara Sava-Segal for their support and guidance with NLP models and several analyses suggestions, Ahmed Elyamani and Danrae Pray for their help with developing the software, Peng Liu and Jordan Selesnick for their inputs in the preliminary stages of the experiments, undergraduate RAs Alison Sasaki and Eliana Stanford for help with quality-checking stimuli, piloting the experiments and testing the *psyanim* software, and Beyond Bounds Creative for their help with schematics in Fig 7.

References

1. Abassi, E. & Papeo, L. Behavioral and neural markers of visual configural processing in social scene perception. *NeuroImage* **260**, 119506 (2022).

2. Hull, K., Van Hedger, K. & Van Hedger, S. C. Absorption relates to individual differences in visual face pareidolia. *Curr Psychol* **43**, 4458–4474 (2024).

3. Nguyen, M., Vanderwal, T. & Hasson, U. Shared understanding of narratives is correlated with shared neural responses. *NeuroImage* **184**, 161–170 (2019).

4. Ratajska, A., Brown, M. I. & Chabris, C. F. Attributing Social Meaning to Animated Shapes: A New Experimental Study of Apparent Behavior. *The American Journal of Psychology* **133**, 295–312 (2020).

5. Varrier, R. S. & Finn, E. S. Seeing Social: A Neural Signature for Conscious Perception of Social Interactions. *J. Neurosci.* **42**, 9211–9226 (2022).

6. Rasmussen, C. E. & Jiang, Y. V. Judging social interaction in the Heider and Simmel movie. *Quarterly Journal of Experimental Psychology* **72**, 2350–2361 (2019).

7. Zwickel, J., White, S. J., Coniston, D., Senju, A. & Frith, U. Exploring the building blocks of social cognition: spontaneous agency perception and visual perspective taking in autism. *Social Cognitive and Affective Neuroscience* **6**, 564–571 (2011).

8. Klin, A. & Jones, W. Attributing social and physical meaning to ambiguous visual displays in individuals with higher-functioning autism spectrum disorders. *Brain and Cognition* **61**, 40–53 (2006).

9. Vandewouw, M. M. *et al.* Do shapes have feelings? Social attribution in children with autism spectrum disorder and attention-deficit/hyperactivity disorder. *Transl Psychiatry* **11**, 1–11 (2021).

10. Lisøy, R. S. *et al.* Seeing minds – a signal detection study of agency attribution along the

autism-psychosis continuum. *Cognitive Neuropsychiatry* **0**, 1–17 (2022).

11. Langdon, R., Boulton, K., Connaughton, E. & Gao, T. Perceiving and attributing

intentionality in schizophrenia. *Cognitive Neuropsychiatry* **25**, 269–280 (2020).

12. Horan, W. P. *et al.* Disturbances in the spontaneous attribution of social meaning in

schizophrenia. *Psychological Medicine* **39**, 635–643 (2009).

13. Castiello, S., Ongchoco, J. D. K., van Buren, B., Scholl, B. J. & Corlett, P. R. Paranoid and

teleological thinking give rise to distinct social hallucinations in vision. *Commun Psychol* **2**,

1–12 (2024).

14. Kohler, C. G., Hoffman, L. J., Eastman, L. B., Healey, K. & Moberg, P. J. Facial emotion

perception in depression and bipolar disorder: A quantitative review. *Psychiatry Research*

188, 303–309 (2011).

15. Liu, W., Huang, J., Wang, L., Gong, Q. & Chan, R. C. K. Facial perception bias in patients

with major depression. *Psychiatry Research* **197**, 217–220 (2012).

16. Krause, F. C., Linardatos, E., Fresco, D. M. & Moore, M. T. Facial emotion recognition in

major depressive disorder: A meta-analytic review. *Journal of Affective Disorders* **293**, 320–

328 (2021).

17. Kaletsch, M. *et al.* Major Depressive Disorder Alters Perception of Emotional Body

Movements. *Front. Psychiatry* **5**, (2014).

18. Barrett, H. C., Todd, P. M., Miller, G. F. & Blythe, P. W. Accurate judgments of intention

from motion cues alone: A cross-cultural study. *Evolution and Human Behavior* **26**, 313–331

(2005).

19. Blythe, P. W., Todd, P. M. & Miller, G. F. How motion reveals intention: Categorizing

social interactions. in *Simple heuristics that make us smart* 257–285 (Oxford University

Press, New York, NY, US, 1999).

20. Heider, F. & Simmel, M. An Experimental Study of Apparent Behavior. *The American

Journal of Psychology* **57**, 243–259 (1944).

21. Abell, F., Happé, F. & Frith, U. Do triangles play tricks? Attribution of mental states to

animated shapes in normal and abnormal development. *Cognitive Development* **15**, 1–16

(2000).

22. Gao, T., Newman, G. E. & Scholl, B. J. The psychophysics of chasing: A case study in the

perception of animacy. *Cognitive Psychology* **59**, 154–179 (2009).

23. Isik, L., Koldewyn, K., Beeler, D. & Kanwisher, N. Perceiving social interactions in the

posterior superior temporal sulcus. *Proceedings of the National Academy of Sciences* **114**,

E9145–E9152 (2017).

24. Scholl, B. J. & Tremoulet, P. D. Perceptual causality and animacy. *Trends in Cognitive

Sciences* **4**, 299–309 (2000).

25. Zhou, L.-F. & Meng, M. Do you see the "face"? Individual differences in face pareidolia.

Journal of Pacific Rim Psychology **14**, e2 (2020).

26. McMahon, E. & Isik, L. Seeing social interactions. *Trends in Cognitive Sciences* (2023)

doi:10.1016/j.tics.2023.09.001.

27. Dunbar, R. I. M. The social brain hypothesis – thirty years on. *Annals of Human Biology* **51**,

2359920 (2024).

28. Frith, C. & Frith, U. *What Makes Us Social?* (MIT Press, 2023).

29. Barch, D. M. *et al.* Function in the human connectome: task-fMRI and individual differences

in behavior. *Neuroimage* **80**, 169–189 (2013).

30. Castelli, F., Happé, F., Frith, U. & Frith, C. Movement and Mind: A Functional Imaging

Study of Perception and Interpretation of Complex Intentional Movement Patterns.

NeuroImage **12**, 314–325 (2000).

31. Hamlin, J. K., Wynn, K. & Bloom, P. Social evaluation by preverbal infants. *Nature* **450**,

557–559 (2007).

32. Rutherford, M. D. & Kuhlmeier, V. A. *Social Perception: Detection and Interpretation of*

Animacy, Agency, and Intention. (MIT Press, 2013).

33. Ullman, T. *et al.* Help or Hinder: Bayesian Models of Social Goal Inference. in *Advances in*

Neural Information Processing Systems vol. 22 (Curran Associates, Inc., 2009).

34. Neri, P., Luu, J. Y. & Levi, D. M. Meaningful interactions can enhance visual discrimination

of human agents. *Nat Neurosci* **9**, 1186–1192 (2006).

35. Trompenaars, T., Kaluge, T. A., Sarabi, R. & de Swart, P. Cognitive animacy and its relation

to linguistic animacy: evidence from Japanese and Persian. *Language Sciences* **86**, 101399

(2021).

36. Schultz, J. & Frith, C. D. Animacy and the prediction of behaviour. *Neuroscience &*

Biobehavioral Reviews **140**, 104766 (2022).

37. Leeuw, J. R. de, Gilbert, R. A. & Luchterhandt, B. jsPsych: Enabling an Open-Source

Collaborative Ecosystem of Behavioral Experiments. *Journal of Open Source Software* **8**,

5351 (2023).

38. Wang, W. *et al.* MiniLM: Deep Self-Attention Distillation for Task-Agnostic Compression

of Pre-Trained Transformers. Preprint at https://doi.org/10.48550/arXiv.2002.10957 (2020).

39. Jolly, E. Pymer4: Connecting R and Python for Linear Mixed Modeling. *Journal of Open*

Source Software **3**, 862 (2018).

40. Loureiro, D., Barbieri, F., Neves, L., Anke, L. E. & Camacho-Collados, J. TimeLMs:

Diachronic Language Models from Twitter. Preprint at

https://doi.org/10.48550/arXiv.2202.03829 (2022).

41. Gescheider, G. A. *Psychophysics: Method, Theory, and Application*. (Taylor & Francis

Group, 1985).

42. Finn, E. S. *et al.* Idiosynchrony: From shared responses to individual differences during

naturalistic neuroimaging. *NeuroImage* **215**, 116828 (2020).

43. Epley, N., Akalis, S., Waytz, A. & Cacioppo, J. T. Creating Social Connection Through

Inferential Reproduction: Loneliness and Perceived Agency in Gadgets, Gods, and

Greyhounds. *Psychol Sci* **19**, 114–120 (2008).

44. Gardner, W. L., Pickett, C. L., Jefferis, V. & Knowles, M. On the Outside Looking In:

Loneliness and Social Monitoring. *Pers Soc Psychol Bull* **31**, 1549–1560 (2005).

45. Powers, K. E., Worsham, A. L., Freeman, J. B., Wheatley, T. & Heatherton, T. F. Social

Connection Modulates Perceptions of Animacy. *Psychol Sci* **25**, 1943–1948 (2014).

46. Tomova, L. *et al.* Acute social isolation evokes midbrain craving responses similar to

hunger. *Nat Neurosci* **23**, 1597–1605 (2020).

47. Baron-Cohen, S., Wheelwright, S., Skinner, R., Martin, J. & Clubley, E. The Autism-

Spectrum Quotient (AQ): Evidence from Asperger Syndrome/High-Functioning Autism,

Males and Females, Scientists and Mathematicians. *J Autism Dev Disord* **31**, 5–17 (2001).

48. Russell, D., Peplau, L. A. & Ferguson, M. L. Developing a Measure of Loneliness. *Journal*

of Personality Assessment (1978) doi:10.1207/s15327752jpa4203_11.

49. Watson, D., Clark, L. A. & Tellegen, A. Development and validation of brief measures of

positive and negative affect: The PANAS scales. *Journal of Personality and Social*

Psychology **54**, 1063–1070 (1988).

50. Franić, S., Borsboom, D., Dolan, C. V. & Boomsma, D. I. The Big Five Personality Traits:

Psychological Entities or Statistical Constructs? *Behav Genet* **44**, 591–604 (2014).

51. Santavirta, S., Malén, T., Erdemli, A. & Nummenmaa, L. A taxonomy for human social

perception: Data-driven modeling with cinematic stimuli. *J Pers Soc Psychol* (2024)

doi:10.1037/pspa0000415.

52. Horovitz, S. G., Rossion, B., Skudlarski, P. & Gore, J. C. Parametric design and correlational

analyses help integrating fMRI and electrophysiological data during face processing.

NeuroImage **22**, 1587–1595 (2004).

53. Johansson, M., Mecklinger, A. & Treese, A.-C. Recognition Memory for Emotional and

Neutral Faces: An Event-Related Potential Study. *Journal of Cognitive Neuroscience* **16**,

1840–1853 (2004).

54. Looser, C. E. & Wheatley, T. The Tipping Point of Animacy: How, When, and Where We

Perceive Life in a Face. *Psychol Sci* **21**, 1854–1862 (2010).

55. Schultz, J. & Bülthoff, H. H. Perceiving animacy purely from visual motion cues involves

intraparietal sulcus. *NeuroImage* **197**, 120–132 (2019).

56. Malik, M. & Isik, L. Relational visual representations underlie human social interaction

recognition. *Nat Commun* **14**, 7317 (2023).

57. Peters, M. A. K. Introspective psychophysics for the study of subjective experience.

Cerebral Cortex bhae455 (2024) doi:10.1093/cercor/bhae455.

58. Gandolfo, M. *et al.* Converging evidence that left extrastriate body area supports visual

sensitivity to social interactions. *Current Biology* **34**, 343-351.e5 (2024).

59. Pitcher, D. & Ungerleider, L. G. Evidence for a Third Visual Pathway Specialized for Social

Perception. *Trends in Cognitive Sciences* **25**, 100–110 (2021).

60. Thieu, M. K., Ayzenberg, V., Lourenco, S. F. & Kragel, P. A. Visual looming is a primitive

for human emotion. *iScience* **27**, (2024).

61. McMahon, E., Bonner, M. F. & Isik, L. Hierarchical organization of social action features

along the lateral visual pathway. (2023).

62. Choi, Y. B., Mentch, J., Haskins, A. J., Van Wicklin, C. & Robertson, C. E. Visual

processing in genetic conditions linked to autism: A behavioral study of binocular rivalry in

individuals with 16p11.2 deletions and age-matched controls. *Autism Research* **16**, 831–840

(2023).

63. Robertson, C. E. & Baron-Cohen, S. Sensory perception in autism. *Nat Rev Neurosci* **18**,

671–684 (2017).

1165