Shared and individual tuning curves for social vision

Rekha S. Varrier[1,2], Zishan Su[1], Qi Liang[1], Tory G. Benson[1,3], Eshin Jolly[1,4] and Emily S. Finn[1]

[1]Department of Psychological and Brain Sciences, Dartmouth College, Hanover, New Hampshire, USA.

[2]Center for Economics and Neuroscience, University of Bonn, Germany.

[3]Department of Psychology, Rutgers University, New Jersey USA.

[4]Department of Psychology, University of California San Diego, California, USA.

Corresponding authors:

Rekha S. Varrier: rvarrier@uni-bonn.de and

Emily S. Finn: emily.s.finn@dartmouth.edu

Abstract

Stimuli with light are clearly visual; stimuli with sound are clearly auditory. But what makes a stimulus "social", and how do socialness judgments differ across people? Here, we characterize group-level and individual thresholds for perceiving the presence and nature of a social interaction. We leverage the fact that humans see social interactions—e.g., chasing, playing, fighting—even in very un-lifelike stimuli like animations of geometric shapes. Unlike prior work using these stimuli, we exploit their most advantageous property: their visual features are fully parameterizable. Using this property, we construct psychophysics-inspired "social tuning curves" for individual subjects. We find not only that simple visual features influence social perception, but also that the exact relationship (shape of the curve) is unique to and stable within each person, thus supporting the view that social information processing begins early in the perceptual hierarchy. Further, individual differences in social tuning curves are related to socio-affective traits. Our approach lays the foundation for a generative account of social perception in single individuals.

Introduction

A hallmark of the human species is our extraordinary sociality, which depends on reading and responding to others' behavior in ways that are largely effortless and shared across the population. Yet despite this shared general framework, there are substantial idiosyncrasies in how people perceive, interpret, and react to social information[1–5]. Many of these individual differences simply reflect variation in personality traits and social styles. Yet, marked deviations from typical social processing are also central to developmental conditions such as autism[6–10], as well as mental illnesses such as schizophrenia[11,12], paranoia[13] and depression[14–17].

Social information can take many forms, including linguistic cues, facial cues, and whole-body motion cues. While humans get nuanced information from linguistic and facial cues, motion cues are necessary for some of our most basic evolutionary social behaviors that are conserved across species: e.g., pursuing, evading, playing, fighting, and courting[18,19]. Humans are primed to perceive these types of interactions even in very un-lifelike stimuli: for example, when faced with videos of simple geometric shapes moving around the screen, even without prompting, most neurotypical people will construct narratives to explain the shapes' movements in terms of goals, beliefs, and desires. This highly robust observation dates back at least to Heider and Simmel[20] and has since been leveraged to study social perception in a wide variety of contexts and populations[21–24]. The effect holds across cultures, suggesting a biological origin[18]. Along with related phenomena such as pareidolia[25]—the tendency to perceive faces in inanimate objects—this suggests an automaticity to social information processing that belies its typical conceptualization as a high-level cognitive process. Indeed, recent work supports the notion that core components of a social interaction can be extracted by the human visual system using fast, bottom-up processes[26], which is likely evolutionarily adaptive for a species that depends heavily on its sociality for survival[27,28].

While using simple geometric-shape animations as experimental stimuli has yielded important insights into behavioral, cognitive, and neural aspects of social perception, most past work using these stimuli has substantial limitations. Studies typically use a small number of manually generated animations handcrafted by human experimenters to be either obviously social or obviously non-social, with no systematic variation or control over visual features[3,29,30]. Participants' responses are then classified as accurate or inaccurate with respect to these "ground

truth" experimenter labels. Furthermore, even given a stimulus deemed "social" by most people,

different individuals may be perceiving different *types* of social interactions in that same

stimulus; the *nature* of the perceived interaction is rarely probed (and if it is, the experimenters

often have a ground truth label in mind —e.g., helping versus hindering)[31–33]. Together, these

practices often produce ceiling effects and compress individual variability in behavior, at least in

normative populations, which is unrealistic given that most real-world social scenarios are

complex and may engender different interpretations across people.

Here, we exploit a highly advantageous yet hitherto under-used property of such

animations—namely, that they are algorithmically controllable and amenable to principles of

visual psychophysics—to characterize people's socio-perceptual tendencies at both the group and

individual level. While some previous studies have used a similar approach to explore

animacy[34–36], in the context of social perception and individual differences therein, this approach

remains underexplored. We study two processes: (1) how people detect the presence of an

interaction and (2) how people discriminate between types of interactions. By parametrically

varying motion attributes[22], we programmatically generate a large set of animations and use

participants' subjectively reported percepts to construct "social tuning curves" that captures

hared trends and individual differences. Throughout, we adopt the perspective that socialness is

in the eye of the beholder: in other words, there is no "correct" and "incorrect"; whatever percept

is reported is the ground truth for that trial for that participant. We *embrace* ambiguous stimuli—

i.e., those that yield high variability in reported percepts—as a feature rather than a bug, as these

offer an opportunity to probe the limits of what makes a stimulus social, and how these limits

differ for different individuals. We use this framework to show that robust individual differences

in socio-perceptual tendencies exist atop group-level trends, that these individual differences are

reliable over a period of months, and that they ´ show some relationship to traits indexing real-

world social and affective function.

Methods

Table 1: Summary of the experiments

Experiment type		Social detection	Social discrimination
Task		Presence vs. absence of social interactions	Discrimination: Playful vs. aggressive interactions
Parametrized motion attribute		Chase directness	Charge speed
Sample size after excluding bad participants (see "Exclusion criteria")	**Pilot experiments (free-text responses)**	N = 60*	N =103 N =102*
	Main experiments	N = 312, session 1 (N = 240 returned for session 2)	N = 319, session 1 (N = 269 returned for session 2)
	Control experiment (controlled for correlated motion)	N = 308	NA
	Within-subject mixed-task design	N = 279	

*these batches did not use the cover story about what the dots represented; all others did. see sections 'Pilot
experiment design' and 'Main experiment design' for details.

Participants

All data collection and analysis procedures were approved by the Committee for the Protection

of Human Subjects of Dartmouth College. All data were collected online

(http://www.prolific.com/). We used the following selection criteria: participants had to (1) be

fluent in English, (2) have their location set as the USA or UK and (3) not have participated in

our previous studies with similar stimuli. For consistency in data quality, all studies – except for

the retest sessions where participants (identified using their 24-character Prolific IDs) were

invited to complete a second session – were typically launched at 9am Eastern US time on

Prolific and closed when the desired sample size was reached (usually about 2pm Eastern US

time). The retest sessions were launched 2 months (Mean=71.0 days, SD=5.6 days; detection

task) or 1 month (Mean=32.8 days, SD=7.7 days; discrimination task) after their respective first

sessions and were left open for about 6 weeks until no participants had completed the task for at

least 1 week, with the goal to encourage as many participants as possible to return. Note that the

aim of the second sessions was to test the retest reliability (i.e., how similar behavior was on two

independent sessions), so the exact time gap between the sessions did not need to be the same,

we only required that the session not be so close that we would see effects of perceptual learning

or task-specific memory.

Stimuli

Stimuli were simple animations generated using a custom JavaScript-based software called

psyanim (https://github.com/thefinnlab/psyanim-2). Each animation had two circular agents

(radius 12 px): one black and one gray, set against a white background in a world of size 800px x

600px (see Fig 1a and all the stimuli at

https://github.com/thefinnlab/psyanim_behav_paper1/tree/master/stimuli/; exact stimuli for the

individual experiments will be linked in-text near the description of that behavior). At the start of

an animation, the agents were on either side of the center of the screen (coordinates: 400, 300):

left (coordinates: 250, 300) and right (coordinates: 550, 300). In each experiment, the black agent

started on the left (gray on the right) in half of the animations, and vice versa in the other half.

The animations were 6s (detection task) or 8s (discrimination task) long with a frame rate of 60

Hz. A key difference between this study and most past work on social perception using

animations is that we generated our animations purely programmatically using quantifiable,

parameterizable motion attributes (Fig 1a). Each experiment consisted of 7 levels of stimuli

where one motion attribute of interest varied linearly across levels while all other attributes were

held constant. These attributes were chosen such that people's perception of a social scene on a

scale from the most non-social to most social (detection task) or from most playful to most

aggressive (discrimination task) varied along the attribute of interest. In the following sub-

sections, we describe these motion attributes as well as the animations in more detail.

Detection task

To manipulate percepts as to the presence versus absence of a social interaction (detection task),

we relied on the motion attribute *chase directness*, which governs the fidelity with which one

agent (the "predator") chases the other agent (the "prey"). This attribute was originally described

by Gao et al.[22], where it was called "chase subtlety" and was found to robustly influence people's

ability to detect social interactions (in particular, chases). Chase subtlety was originally defined

in angles, i.e., by how many degrees a predator could deviate from a perfect heat-seeking path

between itself and the prey at each time step. Thus, a *chase subtlety* of 0° would indicate a very

direct chase, a *chase subtlety* of 90° would indicate a somewhat noisy chase where the predator

can go off-path by up to 90° clockwise or 90° counterclockwise, and *chase subtleties* > 90°

would indicate very noisy chasing behaviors where the predator can occasionally even move

away from the prey. Here, we reversed and normalized the subtlety angle to derive *chase*

directness ($\frac{180 - chaseSubtlety}{180}$), such that the higher the directness, the more obvious (detectible)

the chase. Details on how this was implemented in *psyanim* are below.

Chase animations

In the animations we generated, one agent is the predator and the other is the prey. Predator/prey

assignment was counterbalanced across stimuli in terms of both start position (left/right of the

center) and color (gray/black). The predator was programmed to chase the prey at varying levels

of *chase directness* and the prey was programmed to flee from the predator when it was within a

certain radius. When the predator agent was beyond its field of view (or the distance between

them was greater than the "*safety distance*"), the prey agent simply wandered around the screen.

We included the wandering behavior to prevent the fleeing behavior from looking too obvious,

so that people did not make decisions purely based on the prey. All variable attributes other than

chase directness governing the motions of the predator and prey were held constant over all

animations (i.e., over all levels of *chase directness*). The relevant attributes are described below:

Chase directness: Every 350ms (set by an attribute called *subtlety lag* explained in the

next paragraph), the predator picks a value from a uniform distribution that ranges from

[–*chaseSubtlety*, *chaseSubtlety*], where *chaseSubtlety* ∈ {0°, 30°, 60°, 90°, 120°,150°}. (i.e.,

chase directness ∈ {1, 0.833, 0.667, 0.5, 0.333, 0.167}). These behaviors are illustrated in Fig

1a. To get a feel for what these values mean, we encourage readers to watch some of the

animations, available on GitHub (the stimuli used for session 1 chase detection experiments here,

and those for session 2 experiments are here).

Other attributes: All attributes besides *chase directness* were set to be constant across

animations. Some of the relevant attributes that influenced how the animations were perceived

were optimized by manual piloting during stimulus development. These were, for the predator:

(i) *maximum chase speed* = 1.5px/frame (frame rate = 60), (ii) *maximum chase acceleration* =

0.1px/frame^2 and (iii) *subtlety lag* = 350ms (how often the agent recomputes its chase direction;

lower values will make the animation more jittery). For the prey: (i) *flee subtlety* = 30° (the angle

which an agent can deviate from the true direction away from the predator — this parameter

helps to avoid fleeing looking very obvious), (ii) *safety distance* = 100px (distance below which

the agent flees from the predator; above this, it wanders), (iii) *maximum flee speed* =

1.8px/frame, (iv) *maximum flee acceleration*= 0.15px/frame^2, (v) *maximum wander speed* =

1.5px/frame, (vi) *maximum wander acceleration* = 0.1px/frame^2, (vii) *maximum seek speed* =

3.5px/frame and (viii) *maximum seek acceleration* = 0.05px/frame^2 (the seek behavior is

included in the prey algorithm to keep it away from the boundaries/walls/edges of the world so

that it does not get stuck in a corner). The flee speed and acceleration of the prey were set to be

slightly higher than those of the predator to ensure that the predator never actually catches the

prey.

"Invisible chase" control condition

With this control, we sought to rule out an alternative possibility for how *chase directness* might

influence socialness perception that is less related to a chase *per se* and more related to general

motion contingency between the two agents. Specifically, observers may notice that the predator

and prey trajectories are linked more tightly in time at higher *chase directness* (where

immediately after the prey changes direction, the predator too will change direction) than at

lower *chase directness* (where the predator will not change direction as quickly and obviously

upon the prey changing direction). Participants may simply be using this heuristic—i.e., whether

the prey changing direction prompts the predator to change direction—instead of the actual chase

between the predator and prey. To test for this possibility, inspired by Gao et al.[22], in a subset of

behavioral experiments we included an additional set of control stimuli, where the actual prey

was initialized at a randomly chosen location on the screen for each animation but was made

invisible. The predator and a visible "mimicking" agent each started at one of the two regular
starting locations (left and right of center as described at the start of the **Stimuli** section). The
mimicking agent copies the true prey's trajectory but with a 180° rotation (i.e., if the invisible
prey moves up and to the right, the mimicking agent will move down and to the left). The
animations used for this study are here. For illustrative purposes, the invisible (true) prey is
shown in yellow in these exemplars (participants never saw the yellow dots!). There were only 2
relevant parameters for the mimicking agent in *psyanim*: (i) *name or ID of the agent* to mimic
(i.e., the invisible true prey), (ii) *angleOffset* = 180° (how much to offset the movement in
angles).
197
Wander behavior
We also generated animations where both the agents were wandering independently, meaning
that there was no programmed contingency between their motion patterns. The speed and
acceleration of the two wandering agents matched that of the predator and prey agents in the
main chase animations (pseudo-predator and pseudo-prey agents, respectively) to make these
animations as close as possible to the chase animations. These animations serve as an additional
check as to whether participants use the speed of an agent as a heuristic to help identify the
predator (since, in chase animations, the prey always moved slightly faster than the predator to
avoid being caught as described above). Although these animations were generated differently
than the chase animations described above (where one of the agents is designed to chase the
other, however inefficiently), they are conceptually equivalent to a chase with *chase directness* =
0 (subtlety 180°; i.e., where the predator is equally likely to move in any direction irrespective of
the prey's position). Hence, we use these as our experimental stimuli for *chase directness* = 0 in
the social detection experiments. These stimuli can be seen here.
212   The relevant parameters for these animations in *psyanim* were: (i) *maximum wander*
213   *speed* (for the pseudo-predator agent = 1.5px/frame, pseudo-prey agent = 1.8px/frame) , (ii)
214   *maximum wander acceleration* (for the pseudo-predator agent = 0.1px/frame^2, for the pseudo-
215   prey agent = 0.15px/frame^2), (iii) *maximum angle change per frame* = 35° (how much the
216   movement direction can change from one frame to the next), (iv) *minimum screen boundary*
217   *distance* = 50px (the distance agents try to maintain from the screen boundary).
218

Discrimination task

To study how people discriminate between positive and negative social interactions, we varied

the attribute *charge speed* in a novel social interaction scene that is different from the chase

detection task discussed above. This scene was inspired by the presence of physical contact in

the real world for common positive as well as negative interactions (e.g., hugs, high-fives,

physical fights)[37] and how speed can be a clue to valence, with slower movements being usually

perceived as more peaceful/positive, and faster movements as more aggressive/negative[19].

When generating these animations, both agents were set to have the same goal: to wander

for a certain period and then charge at the other agent at the predetermined *charge speed* which

varies between 1.5px/frame and 9px/frame (stimuli in Fig 1a and here). Once one agent initiates

a charge, the other agent will respond after a short delay; following contact, both agents will

return to wandering.

As with the detection task, several features were kept at constant values across levels of

charge speed after extensive in-lab piloting. These were: (i) *minTargetDistanceForCharge* =

200px, *maxTargetDistanceForCharge* = 500px (the between-agent distance range within which

collisions would be initiated), (ii) *mean charge delay* =200ms, *jitter* = 100ms (how long the

second agent waits after the first agent charges at it), (iii) *mean break duration* = 2000ms, *jitter* =

200ms (the duration for which two agents wander between consecutive charges), (iv) *maximum*

wander speed = 1.5px/frame, (v) *maximum wander acceleration* = $0.1px/frame^2$, (vi) *wander*

panic distance = 800px (minimum distance at which a wandering agent will charge back at

another agent).

Quality-checking stimuli

We quality checked all generated animations for both the detection and the discrimination tasks.

Animations were manually checked by at least two lab members and were removed if they

contained glitchy/flickery movement patterns, if the agents got stuck in the corners or stuck to

each other for extended periods, and/or if one or both agents went offscreen. At all stages, bad

animations were replaced with new ones of the same type (e.g., same *chase directness* value,

predator color and start position) to obtain the target number of animations. For the detection

task, our final stimulus set included 84 chase animations (12 animations at each of 7 *chase*

directness levels, including animations generated via the wander algorithm which served as

chase directness = 0) and 84 'invisible chase' animations (control; 12 animations at each of the

chase directness levels used in the chase animations plus animations generated via the wander

algorithm which served as *chase directness* = 0). Within these sets, the starting position (left

versus right of center) and the role of predator versus prey was counterbalanced between the gray

and black agent across animations, so that when participants were presented with an animation,

there was no expectation of what they would see based on the position or the color of the

predator.

For *charge speed* (discrimination) stimuli, we removed bad animations according to

similar criteria as described for the detection stimuli. In addition, we ensured that all animations

in the final set had the same number of actual collisions (two), since differences in the number of

collisions could have influenced percepts independently of *charge speed*, which was the main

motion attribute of interest. The final set of discrimination stimuli contained 20 animations at

each of 7 *charge speed* levels for a total of 140 animations. Within this set, the initial position of

the gray and black agents was counterbalanced across animations.

Fig 1: Social detection and discrimination tasks. (a) Static schematics of the animation stimuli

for the detection (left) and discrimination (right) tasks to illustrate the effect of varying motion

attributes (chase directness and charge speed, respectively) on agents' trajectories. The two dots

at the beginning and the end of each trajectory represent the agents' positions at the start of the

trial and after about 1/4th of the total duration of the animation (at time 1.5s for the detection

task and 2s for the discrimination task). For the detection task (left), the yellow zone in the

schematic at the top of each directness subplot indicates the range of directions the predator is
allowed to take in pursuing the prey (the smaller the range, the higher the directness; directness
= (180-subtlety)/180). For the discrimination task (right), the red part of the trajectory indicates
when agents switch from wandering to charging at each other. (b) The response screen that was
presented following each animation in the main experiments. Both tasks required participants to
rate their percept of the preceding animation on a continuous bar, and the detection task (left)
additionally asked participants to identify the agent that was doing the chasing. In both
experiments, the positions of the slider labels ("Moving independently"/ "Chasing" or
"Playing"/"Fighting") on the left versus right were counterbalanced across participants.
281
Animacy cover story
Attributing intentions to moving shapes entails judgments of two related yet distinct features –
animacy and socialness. Animacy is a widely used concept that applies to entities that are
considered alive[38]. These entities exhibit signs of self-propelled, non-Newtonian motion by
seeming to engage in goal-directed behavior[39] and responding to their surroundings (e.g.,
changing speed or direction to avoid an obstacle). In our view, animacy is necessary but not
sufficient for socialness: animacy can be detected in displays of single agents, in which by
definition there is no social interaction present, but in multi-agent displays, to the extent that
agents are perceived to be socially interacting, they must also be perceived as animate (i.e., as
possessing a mind that would be motivated to engage in social behavior). Our goal here was to
isolate the concept of *socialness* above and beyond animacy. Because differences in percepts of
animacy might confound judgments of socialness, to encourage uniform perception of animacy
across both animations and participants to the extent possible, we provided a cover story that the
agents (dots) represented children in a public park. We chose this cover story because (1) it was
believable (people care about children's privacy), (2) it was relatable (something most people
have experience seeing) and (3) it helps us to test various behaviors with the same cover story –
both interpersonal activities like chasing, playing and fighting, and the non-social option of
moving independently. However, as we discuss later, this did introduce a bias towards perceiving
playful interactions in the discrimination task. This was the exact story participants received:
"We recently videotaped a public park where nearby children go, with the goal of capturing the
essence of children's behaviors within a familiar park setting. To protect the identities of these

*young people, we used an algorithm that represents **a pair of children as two dots**, each tracing*
the path of an individual child." We used this cover story to set the context in all experiments
except in the early pilot experiments, since the goal of the latter was to evaluate how participants
spontaneously interpret the animations without any prompting or context.
307

Pilot experiments (open-ended responses)

309 All pilot and main experiments were programmed and run using the *jsPsych* platform[40] with a
310 custom plugin (https://github.com/thefinnlab/psyanim-2) to present the *psyanim* animations.

Pilot experiment design

We first conducted a set of small-scale studies where participants could freely describe the
animations. Before imposing explicit, constrained rating scales, our goal was to verify that these
animations do in fact spontaneously evoke percepts that fall approximately along the intended
axes from non-social to social (detection task) or playful to aggressive (discrimination task).
In these experiments, each participant was presented with 7 animations (1 animation for
each level of the motion attribute as described under **Stimuli**). For the detection task, we did not
use the cover story. For the discrimination task we ran two versions – one without and one with
the cover story. In what follows, unless otherwise noted, we present data from the version *with*
the cover story (a quick scan of the pilot data had shown that *without* the cover story, the dots
were described by many participants as inanimate or using ambiguous, mechanical terms,
especially at lower *charge speed* levels). After watching each animation, participants responded
to the following prompt to indicate what the dots could have represented: "Briefly describe what
the dots were doing. Guess if you do not know." (In the discrimination task with the cover story,
the text varied slightly: "Describe what the dots were doing using a word or a short phrase"). The
task lasted ~5-10 min overall.

Pilot experiment data analysis

We analyzed the free-response data using techniques from natural language processing. In each
experiment (detection and discrimination tasks), we derived the average "meaning" of
descriptions at each stimulus level using semantic embeddings. Specifically, we used
Bidirectional Encoder Representations from Transformers (BERT)[41] language models as

implemented in the Python library *SentenceTransformers* (https://huggingface.co/sentence-

transformers/all-MiniLM-L6-v2). For each description (participant response, ranging from a

phrase to a short sentence or two), we get a single 384-dimensional vector embedding. We then

averaged across all embeddings at each stimulus level (before averaging, detection task: 12

unique stimuli per level of *chase directness* x 5 observers per stimulus = 60 observations per

level of *chase directness*; discrimination task: 20 stimuli per level of *charge speed* x 5 observers

per stimulus = 100 observations per level of *charge speed*. After averaging, there was 1

embedding per *chase directness* level or *charge speed* level).

In an initial exploratory/data-driven analysis, we compared this mean vector to the

embeddings of *all* 8432 English verbs from the natural language toolkit (nltk;

https://www.nltk.org/howto/wordnet.html) to identify the 5 verbs whose embeddings it was

closest to. To more clearly isolate the *differences* in percepts across levels, we then removed

words that appeared in at least 6 of the 7 motion attribute levels within each experiment.

In a follow-up, more hypothesis-driven analysis, we quantified the change in percepts

across stimulus levels by computing the similarity of mean embeddings at each level to our

expected percepts at either ends of the response scale (detection task: "chasing", "moving

independently"; discrimination task: "playing", "fighting"). We expected that, as the motion

attribute value increased, descriptions' similarity to one extreme ("chasing" or "fighting") would

increase and similarity to the other extreme ("moving independently" or "playing") would

decrease. To quantify this, we took the difference between embeddings' similarity scores to both

extrema ($difference\_score = score\_chasing - score\_moving\_independently$ for the

detection task and $difference\_score = score\_fighting - score\_playing$ for the

discrimination task), giving us one $difference\_score$ per trial. Later, scores were compared

using a linear mixed effects model (LME; *pymer4* package[42]):

$difference\_score \sim motion\_attribute + (1|subID)$, where for the detection and

discrimination tasks, $motion\_attribute$ referred to *chase directness* and *charge speed*,

respectively.

Finally, we performed two additional analyses specific to for the discrimination task. In

the first analysis, we quantified how the valence, or "sentiment", of the descriptions varied

across attribute (*charge speed*) levels. We used a RoBERTa-base model[43]

(https://huggingface.co/cardiffnlp/twitter-roberta-base-sentiment-latest/tree/main) to

automatically quantify sentiment, which yields a positive, negative, and neutral score for each description. Our dependent variable $sentiment\_score$ was the difference between the negative and positive sentiment scores for each description. Similar to the approach to semantic similarity described in the previous analysis, the effect of the motion attribute (namely, $charge\ speed$) on these values was computed using the LME: $sentiment\_score \sim charge\ speed + (1|subID) + (1|stimID)$. In the second analysis, we quantified how arousal varied across attribute levels. For this, we used the National Research Council Canada (NRC) Valence, Arousal and Dominance (NRC-VAD) Lexicon[44] which contains arousal scores for individual words. We split each response into words, computed their arousal scores and averaged these scores for each text response to get a single arousal_score. Next, we used the LME $arousal\_score \sim charge\ speed + (1|subID) + (1|stimID)$ to assess how arousal changes with $charge\ speed$, and lastly, we ran the model $sentiment\_score \sim charge\ speed + arousal\ score + (1|subID) + (stimID)$ to assess if changes in arousal explained away effects of $charge\ speed$ on valence.

We noted that free-text descriptions were overall biased toward positive sentiment (Fig S1c, left). This is likely because of our cover story about the dots representing children in a park, which induces a strong prior toward playful interactions. To check this, we ran an additional small pilot batch without a cover story (all else remained the same).

Results from the analyses of free text responses in these pilot experiments showed evidence favoring our hypotheses that (1) in the detection study, as *chase directness* increases, animations are seen as more social, and (2) in the discrimination study, as *charge speed* increases, interactions are seen as more aggressive, with a higher arousal and negatively valenced. Together, the pilot experiments confirmed that the stimuli we generated algorithmically could spontaneously—i.e., without prompting with explicit choices of possible interactions—evoke percepts along the intended axes, and this gave us the confidence to move forward with our main experiments using these axes to structure responses, described in the next section.

Main experiments

 Main experiment design

Our first two main experiments consisted of only detection or only discrimination trials,

respectively, while the third main experiment was a mixed-task design in which the same

participants performed both the detection and discrimination tasks. We used the same cover story

described above (about the dots being children in a public park) in all the main experiments.

For the detection study, there were 84 trials per participant (12 trials per *chase directness*

level x 7 levels) with 7 optional breaks (one every 12 trials). In the control experiment that also

included the invisible chase control condition, there were 6 stimuli at each motion attribute level

(2 conditions x 7 stimulus levels x 6 trials per level). After each trial, participants gave two

responses: (1) they rated, on a continuous scale, to what degree one of the two dots was chasing

the other versus moving independently (with the location of the labels on the left versus right

extremes of the scale kept constant within participant, but counterbalanced across participants),

(2) they identified the dot that was chasing the other, in a two-alternative forced choice. Both

questions were presented on the same page, and the page timed out in 10s. The instruction

specific to this task (after the cover story was presented) was as follows: "*Some videos depict a*

*situation in which **one dot is chasing the other**; other videos depict a situation in which the dots*

*are **moving independently**. You will be asked to **rate how much you think the dots are***

***interacting (meaning one dot is chasing the other) versus moving independently**. For all*

*videos, you will also be asked to determine **which dot was chasing the other**. If there was no*

chase in a particular video, just make a guess.". Participants performed one practice trial before

the experiment began.

For the discrimination study, there were 70 trials per participant (10 trials per *charge*

speed level x 7 levels) with 7 self-timed breaks (one every 10 trials). After each trial, participants

rated on a continuous scale to what degree the dots were engaged in a positive (playing) versus

negative (fighting) interaction (as with the detection task, the label positions were

counterbalanced across participants). This response page also timed out in 10s. The instruction

specific to this task (after the cover story was presented) was as follows: "*Some videos depict a*

*situation in which the children are engaged in a **positive interaction (e.g., playing)**; other videos*

*depict a situation in which the children are engaged in a **negative interaction (e.g., fighting)**.*

*After each video, you will be asked to **rate to what extent the children (dots) were engaged in a***

***positive or negative interaction** on a continuous bar. There are no right or wrong answers here,*

so if you are unsure, just guess!". Participants performed two practice trials before the
experiment.

In the third main experiment (mixed-task design study), detection and discrimination
animations were presented in six interleaved blocks: block sequence with 14 trials each (121212
or 212121, where 1= detection task and 2 = discrimination task; one of the two block sequences
was randomly selected for each participant. Here too, there were 84 trials in total: 42 detection
trials (6 at each level of *chase directness*) and 42 discrimination trials (6 at each level of *charge
speed*). The 42 animations from each task (detection or discrimination) were randomized *across*
the 3 blocks of the task. Participants performed two practice trials each for the detection and
discrimination experiments at the start of the experiment.

The primary task portion of all three experiments (detection, discrimination, or mixed-
task design) lasted approximately 15-20 min. At the end of the primary task portion, we
presented participants with the trait questionnaires described below under **Trait measures**. The
sequence of the questionnaires was counterbalanced across participants.

Quality checks during data acquisition. We performed a few data quality checks during
data acquisition to exclude poor participants within the first few minutes of the study. First, after
the instructions, including the cover story about the dots representing children in a park, but
before the start of the main experiment, we presented participants with a multiple-choice
question as to what the dots represented. The options were "animals", "balls", "adults",
"children", "magnets". The correct answer was "children" (as mentioned clearly in the cover
story). If participants responded incorrectly, they were given one chance to correct their answer,
and if their second response was also incorrect, they were immediately excluded from the study.
(Note that this same question was asked again *after* the main task and used for a second quality-
check analysis, see below.) Participants were also warned that they may not be compensated if
they missed (i.e., timed out on) more than 10% of trials. We also excluded participants who
opened other tabs or had bad internet connections by including a demo animation on the very
first page and checking playback duration in real time. If the duration of this page was much
higher than 6 or 8s (actual duration of the animations), this meant that the animation did not play
as normal, and either paused (because of other open tabs and the participant not paying attention)
or played very slowly (possibly because of a slow internet connection). Participants who stayed
on the demo animation page for longer than a liberal threshold of 20s were immediately

excluded from the study. Besides these online quality checks *during* the experiments, we

conducted further quality checks at the data analysis stage to exclude participants with poor data

quality.

Main experiment analysis

Data analysis was similar across all main experiments unless specified otherwise.

Exclusion criteria

First, we excluded participants with bad or unreliable data, as defined by meeting one or more of

the following criteria: (i) missing responses (i.e., timing out) on more than 5% of all trials; (ii)

incorrect responses in the post-main-experiment debrief question asking them to identify what

the dots represented (note that this question is identical to the question asked at the beginning of

the main experiment, but the rationale here is that if by the end of the main experiment

participants had forgotten what the dots represented, their perception and ratings could have been

affected by whatever they assumed the dots to represent by the end); (iii) (for the detection task

alone) incorrectly identifying the predator in more than one third of animations with *chase*

directness = 1 (rationale: the chase/predator identity is very obvious in these animations, so

incorrect answers here are most likely failures of attention); (iv) lingering on the animation page

for more than 20s in at least 5% of trials (each animation was only programmed to last 6 or 8s,

and so the page should have lasted for a similar duration; any longer indicates that they may have

clicked away from the experiment tab and/or had a slow internet connection); (v) failing to

respond to $\geq$ 10% of items on one or more trait questionnaires; or (vi) missing at least one (out of

five) attention-check items in the trait questionnaires. Trait questionnaires are described in detail

in the **Trait measures** section.

Separate detection and discrimination experiments

Group-level analyses: We first analyzed data at the group level to ascertain shared tendencies in

how motion attributes affect social percepts. Participants' ratings were coded on a 0–1 scale: (i)

detection task: *moving independently* = 0, *chasing* = 1; (ii) discrimination task: *playing* = 0 and

fighting = 1. We used linear mixed-effects analyses to quantify the effect of each motion attribute

while controlling for confounding variables using the following model:

rating ~ motion_attribute_level + mean_dist + trial_number + (1|subID) +

(1|*stimID*). Here *rating* refers to participant responses indicating the level of

socialness (degree of *chasing*) or *aggressiveness* (degree of *fighting*). The term

motion_attribute_level refers to degree of either *chase directness* (detection) or

charge speed (discrimination) and could take one of 7 levels. Additional terms are: (i)

mean_dist, the distance between the two agents averaged across all frames; we included this

term because past work has shown that agents that are closer together are more likely to be

perceived as interacting[6]; (ii) trial number, indicating serial order over the course of the

experiment (to check for any drift in ratings over time); and random-effects terms for (iii)

participant identity and (iv) specific animation identity (exemplar). For the predator-

identification question in the detection task, we ran a logistic regression model with *accuracy*

(0/1) as the dependent variable and the same main- and random-effects predictor terms as above.

Individual-level analyses: In addition to showing group-level effects of these motion attributes

on social perception, we also expected to see individual differences in how social perception

varies *across* the motion attribute levels – for instance, some participants' perception may

change linearly with the motion attribute levels whereas others' perception may follow a non-

linear sigmoid pattern. Similarly, some participants may perceive social or aggressive stimuli at

lower *chase directness* or *charge speed* levels than others. Hence, we next analyzed data at the

individual level to determine the extent to which participants differed in their socio-perceptual

tendencies, how stable these differences were across sessions, and how detection and

discrimination tendencies covary with one another and with other socio-affective traits. Our

primary approach to analyzing individual-level data was to compute single-subject "tuning

curves" for detection and/or discrimination behavior. We averaged each participant's responses

at each motion attribute level (*chase directness* or c*harge speed* level for detection and

discrimination tasks, respectively). For each participant, we plotted motion attribute level

(normalized to a 0-1 range; x-axis) against average rating across animations at that level (y-axis).

Similar to the group-level results shown in Fig 3, visual inspection suggested that individual

detection ratings followed a sigmoid shape, while discrimination ratings followed a more linear

trend. We empirically tested both sigmoid and linear fits to evaluate which one better fit each

type of data and verified this pattern: the Akaike Information Criterion (AIC) – which indicates

which of two models fits the data better (lower AIC indicates better fits) – was lower for the

sigmoid fits in the detection task (mean difference sigmoid – linear fits ≤ -7.84, $p < .001$ based

on paired t-test in all the detection experiments) and higher for the sigmoid fits in the

discrimination task (mean difference sigmoid – linear fits ≥ 3.47, $p < .001$ in all the

discrimination experiments, Fig S2). Hence, we used sigmoid fits to characterize each

participant's response data in the detection task and linear fits to characterize responses in the

discrimination task.

The sigmoid curve-fitting equation was : $S(x) = \gamma + (1 - \gamma - \lambda)\,\dfrac{1}{1 - e^{-\frac{(x-\alpha)}{\beta}}}$, where $x =$

the value of the motion attribute (*chase directness* or *charge speed*); γ and λ = the lower/upper

asymptote of the curve; α, β = center, slope. The linear equation was: $L(x) = c + m * x$,

where x = the motion attribute (*chase directness* or *charge speed*); c = the lower intercept of the

line; m = slope. For both functions, we calculated several key parameters from the fitted curve of

each participant:

Shifts from extremes: Lower bias lb and upper bias ub (lower and upper intercepts,

respectively) reflect ratings at the lowest and highest levels of the motion attribute — in other

words, how close to the extremes of the rating scale a participant is willing to go. For linear fits,

lb = intercept c.

Bias: This parameter was derived from the above-mentioned bias terms (lb and ub) as a

comprehensive summary of people's bias that also factors in apparent biases due to differences in

overall confidence or perceptual vividness. The bias term thus measures to what degree people

avoid the lowest end of the scale relative to how much they avoid the two ends of the scale in

general (which could reflect lower confidence overall or a less intense effect of stimuli overall).

We quantified this as $\dfrac{lb}{lb+ub}$. A bias of 0.5 means that there is no bias towards one end of the scale,

bias < 0.5 means that people are more biased towards the lower end, and bias > 0.5 means that

people are more biased towards the upper end. In the detection task, bias > 0.5 can be interpreted

as a predisposition to see things as social ("chasing") more than non-social ("moving

independently"); in the discrimination task, bias > 0.5 can be interpreted as a predisposition toward

seeing things as more like "fighting" than "playing".

Midpoints: Two types of midpoints can be derived from each curve: an objective midpoint

($x_{obj} = f^{-1}(S(x) = 0.5)$) and a subjective midpoint (subj_center, α). The objective midpoint is

the motion attribute value at which the participant's rating crosses the absolute midpoint of the

rating scale (0.5 for all participants). The subjective midpoint is the motion attribute value at which

the participant's rating crosses the halfway point of *their own* behavioral curve (e.g., for a

participant whose ratings vary between from 0.4 and 0.8, their mid-point would be the motion

attribute level at which the tuning curve crosses 0.6). Here we mostly focus on the objective

midpoint, which we call the point of subjective equivalence (**PSE**) because it is similar in spirit to

PSE as defined in traditional visual psychophysics work (i.e., the stimulus feature level at which

options A and B are equally likely in a two-alternative forced-choice discrimination task[45]).

Range: The distance between the lowest and highest ratings on the y-axis. This parameter

can be interpreted in multiple ways: it quantifies how much of the total response scale participants

use, how much participants differentiate between stimuli at extreme (lowest and highest end)

motion attribute levels, and except in cases of strong response biases, might reflect how confident

people are in their percepts (especially at the lowest and highest motion attribute values). This is

defined as $1 - lb - ub$.

Sigma (σ; sigmoid fit only): Sigma or the inverse of the slope $(\frac{1}{\beta})$ determines the steepness

of the sigmoid curve during its transition from perceiving something as "moving independently"

(at lower *chase directness* levels) to "chasing" (at higher *chase directness* levels) in the detection

task. A smaller sigma (or a higher slope) indicates that participants perceive something as more

social (Δ_{rating}) with the smallest change in the sensory evidence (change in *chase directness* or Δ_{chase}

$_{directness}$) – this can be interpreted as people exhibiting higher confidence when rating the intermediate,

ambiguous stimuli. A higher sigma (or lower slope) indicates that participants need a lot more

sensory evidence ($\Delta_{chase\ directness}$) to rate something as more social (Δ_{rating}) – this may reflect lower

confidence and/or a more gradual, evidence-based shift in the perceptual intensity of stimuli at the

ambiguous middle levels.

We plotted covariance matrices (Pearson r) between the various parameters within the detection

and discrimination tasks. Based on these covariances as well as test-retest reliability of the curve

parameters (described in detail below), in what follows, we focus on three main curve parameters

that are both relatively reliable and not highly collinear with one another: PSE, range and bias.

These terms are illustrated in Fig 2. Since range covaries tightly with PSE in the linear fits

specifically and it is not possible to change range without changing the PSE, we only use PSE

and bias for the discrimination task. Approximations were made to PSE $\notin [0,1]$. In participants

with a strong social bias (detection task) or aggressiveness bias (discrimination task) at the

lowest motion attribute level (lb > .5, ub < .5; see Fig 2), PSE < 0, = ∞ or it is not computed;

hence, this was approximated to 0 (detection task: N = 11 out of 312 total in session 1, N = 10

out of 240 total in session 2, N = 9 out of 279 total in the mixed-task design; discrimination task:

N = 1 out of 319 total in session 1, N = 1 out of 269 total in session 2, N = 2 out of 279 total in

the mixed-task design). In participants with a strong non-social bias (detection task) or a

playfulness bias (discrimination task) at the highest motion attribute level (lb < .5, ub >.5), PSE

> 1, = ∞ or it is not computed; this too was approximated to 1 (detection task: N = 0 for detection

task session 1 & 2; discrimination task: N = 1 out of 319 total in session 1, N = 0 in session 2, N

= 1 out of 279 in the mixed-task design). Lastly, range < 0 suggests a flipped curve (e.g.,

socialness rating is highest in purely wandering stimuli and lowest at *chase directness* = 1) – this

was rare and hard to interpret, hence these participants too were excluded from further analyses

(detection task: N = 0 for detection task session 1, 2 and the mixed-task design; discrimination

task : N = 8 out of 319 total in session 1, N = 5 out 269 total in session 2, N = 3 out of 279 total

in the mixed-task design).

Fig 2: Fitting social tuning curves to individuals' reported percepts. (a) We fit sigmoid

(detection experiments; top) or linear (discrimination experiments; bottom) curves to individual-

participant rating data and used the resulting curve parameters to characterize individual

participants. (b) Schematics of how each parameter can vary across participants. The upper

rows show sigmoid fits as used for the detection task, and the lower rows show the linear fits

used for the discrimination task. Each plot shows curves for three different hypothetical

participants.

We tested the robustness of each person's tuning curve by using parameters calculated on data from their first session to fit the same participant's data in their second session 1–2 months later (and vice versa) and calculating the residual normalized root-mean squared error (NRMSE) between the curve and the true data points. We used a paired t-test to compare the NRMSE from this within-participant fit to the NRMSE from the mean across-participant fit (calculated by averaging the curve parameter values across all other participants in the same session. This quantified the extent to which an individual's tuning curve offered a better prediction of their own held-out data than generic tuning curves based on group data. Further, we calculated the intra-class correlation coefficient (ICC) of each curve parameter of interest to measure test-retest reliability across the two sessions (ICC2, single random raters, as implemented by the Python package *pingouin*).

Mixed-task experiments

In these experiments, the same participants performed both the detection and discrimination tasks. Data extraction and curve-fitting was performed similarly to the separate detection and discrimination experiments described above. For each participant, we obtained tuning curves for both detection and discrimination. We studied how socio-perceptual tendencies in the two tasks relate by calculating the Pearson correlation coefficient between all possible pairs of curve parameters across the detection and discrimination tasks. Here, we restricted our analyses to only the most robust curve parameters: bias, range and PSE for the detection task, and bias and PSE for the discrimination task (5 total).

Traits were scored as described under **Trait measures** below, giving us 14 dimensions in total (5 for AQ, 2 for PANAS, 5 for NEO-FFI, 1 for loneliness and 1 for number of friends). To study how traits relate to behavior on our task, we performed multiple linear regressions fitting the curve parameters to the trait dimensions. To get the most sensitive index of trait-behavior correlations and to reduce redundant analyses (which can lead to multiple comparison errors), we first combined two terms that measure similar properties — PSE and bias — in a composite index in both the detection and discrimination tasks (separately). In the detection task, this index

reflects sensitivity to social information in that both higher bias and lower PSE reflect the

tendency to report social interactions at lower social evidence levels. In the discrimination task,

this index reflects people's tendency to report interactions as aggressive, in that higher bias

means higher aggressiveness ratings even at the lowest *charge speed* and lower PSE means

lower *charge speed* at which animations are first perceived as aggressive. Since bias is measured

on the y-axis (ratings) and PSE is measured on the x-axis (stimulus level), both measures were

first normalized across participants by z-scoring; PSE_z was then subtracted from bias_z. This

term will be henceforth referred to as *bias – PSE*. Next, we performed 4 multiple linear

regressions: the 14 trait dimensions were fitted to the *bias – PSE* and *range* parameters from the

detection and discrimination tasks. To assess statistical significance of each predictor (trait), for

each of the 4 models, we bootstrapped (sampled with replacement) participants 1000 times and

calculated the 95% confidence interval (CI) for each of the 14 regression coefficients. Traits

whose 95% CIs do not cross 0 are deemed significant predictors of the respective curve

parameter. To further assess overall goodness of each model, we performed permutation tests by

scrambling the curve parameters *(bias – PSE* and *range)* with respect to the trait scores across

participants 10,000 times and computed the fraction of permuted models whose R^2 value was

higher than that of the true model (p-value).

Trait measures

We chose individual-difference measures of interest based on past findings that behavior on

social perception and cognition tasks often differs between populations (e.g., neurotypical versus

autistic, people with depression versus without) and/or covaries in the normative population with

socio-affective and personality traits. Past work has shown that people scoring higher on autism-

like phenotypes are less likely to detect intentions and interactions in social animation displays[6–

10], while people with more internalizing symptoms (related to anxiety and social withdrawal) and

a higher desire for social connection are *more* likely to detect intentions and interactions[5,46–49].

Other studies have associated depression with impaired emotion recognition of social stimuli

(hypersensitivity to negative cues, hyposensitivity to positive cues)[14–17]. We assessed autism-like

traits with the autism quotient (AQ) questionnaire[50], loneliness with the UCLA loneliness scale[51],

and general affect with the Positive and Negative Affect Schedule (PANAS)[52]. We also

administered the NEO five-factor inventory for multidimensional personality (NEO-FFI; a

measure of the "Big Five")[53]. Finally, we asked participants to state the number of close friends

they had, since this metric provides additional information about participants' real-world social

tendencies.

Our final battery thus consisted of five entities: (i) AQ, (ii) PANAS, (iii) NEO-FFI, (iv)

UCLA loneliness scale and (v) the self-reported number of friends. Details of each questionnaire

are given below.

The AQ consists of 50 total items measuring five subdomains: social skill deficits,

communication deficits, attention-switching deficits, heightened attention to details and

imagination deficits. For each item, participants had four response choices ("Definitely

disagree", "Slightly disagree", "Slightly agree", "Definitely agree"). We reverse-scored the items

that were intended to be as per the instructions from the creators; however, when assigning a

score on each item, we assigned responses scores between 0 and 3 (where 3 → less neurotypical

and more autistic) in place of binarizing responses (assigning 0 to the first two levels and 1 to the

last two levels). Higher scores on each subdomain indicate more autism-like traits (e.g., greater

social skill deficits).

PANAS consists of 20 total items, 10 measuring positive affect and 10 measuring

negative affect. Participants responded on a five-point scale ("Very slightly or not at all", "A

little", "Moderately", "Quite a bit", "Extremely"). Each response was coded between 0 and 4, and

there were no reverse-scored items. This scale results in separate scores for positive and negative

affect.

NEO-FFI consists of 60 total items measuring five dimensions: openness, extraversion,

neuroticism, conscientiousness, agreeableness. Participants responded on a five-point scale

("Strongly disagree", "Disagree", "Neutral", "Agree", "Strongly agree") coded between 1 and 5.

This scale yields a summary score for each of the five dimensions.

The UCLA loneliness scale consists of 20 total items that measure a single dimension.

Participants responded on a 4-point scale ("Never", "Rarely", "Sometimes", "Always") scored

between 1 and 4. Higher scores indicate higher loneliness. Lastly, participants also responded to

the following question with an integer value: "*Please estimate the number of* **close friends** *that*

you have, where "close friends" are people that you feel at ease with and can talk to about

private matters."

Within each questionnaire we also added one attention check question (e.g., for AQ, the

question was this: "If you are doing your best to complete this survey honestly, choose

'Definitely agree'.") to confirm that participants were paying attention to the questions. The

accuracy on these questions was used as a quality check criterion during data pre-processing

(described under *Main experiment analysis above*).

Correlations among the 14 trait dimensions are shown in Fig S7.

Code and data availability

All stimuli, data and code will be available upon publication at:

https://github.com/thefinnlab/psyanim_behav_paper1

Results

We systematically studied how people perceive the presence and nature of a social interaction using sets of algorithmically generated animations. Each animation consisted of two agents—one gray and one black circle—that were programmed to move in certain ways with respect to one another. Critically, the animations varied parametrically along one motion attribute and were controlled for all other low-level visual features. We conducted three sets of experiments: (1) detection studies, in which participants rated the extent to which the agents appeared to be interacting (i.e., one agent chasing another) versus moving independently, (2) discrimination studies, in which participants rated the extent to which the agents appeared to be fighting versus playing, and (3) a mixed-task study where participants performed both the detection and discrimination experiments (see stimuli here and details in Fig 1). Below, we describe group-level and individual behavioral patterns for both social detection and discrimination, as well as how these two behaviors compare to one other and to self-reported social and affective traits.

Simple motion attributes influence percepts of both the presence and nature of social interactions

For detection experiments, we varied the attribute *chase directness*, which determines the fidelity with which the movement of one agent (the predator) depends on the other agent (the prey): more direct chases should look more obviously social, less direct chases should look more like agents moving independently. For discrimination experiments, in which the two agents come together and move apart in succession, we varied the attribute *charge speed*, which determines how fast the agents approach one another: slower should look more playful, faster should look more aggressive/fight-like.

Pilot experiments

We first performed pilot experiments to test that these animations could spontaneously evoke percepts along the intended continua without any explicit prompting. In these experiments, participants watched animations and gave free-response text descriptions, which we quantified using tools from natural language processing. Indeed, we found that varying *chase directness* elicited percepts along a continuum from moving independently (non-social) to chasing (social),

while varying *charge speed* elicited percepts along a continuum from positive/playing/low

arousal to negative/fighting/high arousal (see **Supplementary Results** and Fig S1).These results

gave us confidence to move forward to our main experiments, in which we replaced free

responses with these continua as predetermined rating scales.

Detection experiments

In our main social detection experiments (see Table 1 for sample sizes and other relevant

information), after watching each animation, participants (1) rated how social it was on a

continuous scale ranging from "moving independently" to "chasing" (henceforth referred to as

"socialness rating"), and (2) identified the predator agent by color. In line with our expectations

and past work[22], we found that as *chase directness* increased, ratings shifted towards "chasing"

($b = 0.805$, $p < .001$; Fig 3a). This shift follows a non-linear (sigmoid) pattern overall, as

evidenced by the lower AIC in all the detection experiments for sigmoid compared to linear fits

(Fig S2a; mean difference in model fits $AIC_{sigmoid} - AIC_{linear} \leq -7.84$; $p < .001$ in the paired t-

tests in all the detection experiments). Social perception did not seem to change with time

(indexed as the trial number; $b = -0.001$, $p = .779$), suggesting that there was no measurable

"drift" in ratings toward more social or more non-social over the course of the experiment. We

also observed that, similar to subjective ratings, predator identification accuracy increased as

chases became more direct (logistic regression $b = 4.735$, $p < .001$; Fig S3a); this result further

confirmed that participants were, on average, experiencing the chase in the expected way based

on the generating algorithm (i.e., they correctly perceived its directionality, especially in the case

of the more direct chases).

Participants might have been using visual features other than *chase directness* to form

their judgments of socialness. For example, past work has shown that agents that are closer

together are more likely to be perceived as interacting[6]. That more-direct chases also resulted in a

narrowing of the distance between the two agents over time was an unavoidable consequence of

our animation-generation algorithm (where the predator was programmed to chase after the

prey); indeed, in our stimulus set, chase directness and mean distance between agents over the

course of the animation were correlated across animations (Pearson $r = -0.69$, $p < .001$). Hence,

to account for other visual features beyond *chase directness* that participants may have been

using, we ran additional models including mean distance between agents as a covariate. While

this term was also a significant predictor of socialness ratings ($b = -0.432, p < .001$) and model

including this term fit the data better (AIC -12325 compared to AIC -12293 for the model

without mean distance; lower AIC indicates a better fit), *chase directness* had a significant effect

on the socialness ratings even in the model including mean distance ($b = 0.603, p < .001$).

Further, mean distance was not a predictor of the predator identification accuracy ($b = -0.716, p$

$= .179$) and also did not meaningfully improve the model fit for accuracy (AIC without and with

mean distance $= -7986$ and -7984, respectively).

Lastly, participants may have been relying on other heuristics to form socialness

judgments. Since a chase typically results in correlated movement patterns between two agents

(when the prey changes direction, the predator is likely to do so a moment later), this correlation

will be stronger for more direct than less direct chases. However, agents can also show correlated

motion without one necessarily chasing the other—i.e., one agent could change direction every

time the other one does but be equally likely to turn away from (or orthogonal to) the path of the

other. To test whether participants are simply relying on nonspecific correlated motion as a

heuristic, also inspired by Gao et al.[22], we ran a separate control experiment in an independent

set of participants where we replaced half of the directness 0.167 to 1 chases (6 levels) with a

non-social "invisible chase" control. In these trials, the predator was chasing a true prey agent

that was made invisible to observers, while a visible "fake" prey mimicked the true prey's

trajectory reflected over a 180° rotation. In this way, correlated motion between the two agents

was preserved—when the true prey changed direction, so did both visible agents (the predator

and the mimicking agent)—but not necessarily in a manner consistent with chasing. In line with

our prediction, we saw that while in the true chase condition, socialness ratings increased with

chase directness ($b = 0.471, p < .001$), in the invisible chase condition, if anything, there was a

slight trend in the opposite direction (socialness ratings decreased as directness increased; $b =$

$-0.146, p < .001$; Fig S3b). Both models also included mean distance between agents as a

predictor term, and in both conditions, as mean distance increased, the animations were seen as

less social (chase: $b = -0.684, p < .001$; invisible chase [control]: $b = -0.493, p < .001$). This

suggests that the increase in socialness with *chase directness* is not merely because of correlated

motion in general, but rather correlated motion that is specifically consistent with pursuit

behavior. In sum, in line with Gao et al.[22], these experiments show that the motion attribute

chase directness influences how social stimuli are perceived to be at the group level.

Discrimination task

Once a social interaction is detected, the next step is to discriminate the *nature* of that

interaction; past work[20,30] and real-life experience suggest that given the same sensory input,

there may be even more variability across people in their percepts of *how* agents are interacting

than simply *if* they are interacting. Interactions can be characterized along several dimensions,

but a fundamental one is valence—i.e., how positive or negative is the interaction?[54] Using our

parametric approach, we explored changes in the valence of social percepts between "playing"

and "fighting". Playing and fighting, which are preserved throughout much of the animal

kingdom, involve two agents moving apart and coming back together in quick succession. We

manipulated the speed with which our agents approached each other (*charge speed*) to determine

whether this simple motion cue could reliably affect percepts of an interaction's valence, with

slower speeds looking more friendly (like "playing") and higher speeds looking more aggressive

(like "fighting").

In these experiments (see Table 1), participants watched each animation and rated it on a

continuous scale from "playing" to "fighting". We found that as the *charge speed* increased,

interactions were perceived as more aggressive ($b = 0.622$, $p < .001$; Fig 3b). Unlike in the

detection task, this relationship, at least within the tested range, was linear, as verified by the

comparison between linear and sigmoid curve fits (Fig S2b; mean difference in model fits,

$\text{AIC}_{\text{sigmoid}} - \text{AIC}_{\text{linear}} \geq 3.47$, $p < .001$ in all the discrimination experiments). The effect of *charge*

speed persisted when controlling for the mean distance between the two agents (which also

affected ratings such that higher mean distances predicted slightly less aggressive ratings; $b =$

-0.057, $p = .008$)) and trial number as an index of time (for which we found that percepts of

aggressiveness also weakly increased over the course of the experiment; $b = 0.024$, $p < .001$).

Together, results indicate that social percepts − both the presence and nature of an

interaction − can be manipulated by simple motion attributes in ways that are generally shared

across people. The differences in the shapes of the tuning curves between experiments

(sigmoidal for detection, linear for discrimination) may be because presence is more of a

categorical variable while valence is a more continuous property, though it is also possible that

the discrimination curve would become sigmoidal at more extreme *charge speeds*. To what

extent are there stable and meaningful individual differences in these socio-perceptual

tendencies? We probe this question next.

Fig 3: Group-level behavior on the detection and discrimination tasks. (a) As chases become

more direct, observers were more likely to report percepts closer to the "chasing" (social

interaction) end of the scale. At less direct chases, ratings were lower (i.e., closer to "moving

independently ["moving ind."]). (b) As the charge speed (speed at which agents charge at each

other) increased, interactions were perceived to be more aggressive (closer to the "fighting" end

of the scale). At lower charge speeds, ratings were closer to "playing". N = 312 and 319 in

panels (a) and (b), respectively. Error bars represent the 95% confidence interval.

828 Robust individual differences in social perception exist atop group-level

829 tendencies

Even given these shared general tendencies, individuals often vary in their percepts of social

interactions, especially when faced with ambiguous scenarios. To quantify this across-subject

variability, inspired by psychophysics approaches, we fit individual participants' rating data with

a sigmoid (detection experiments) or linear function (discrimination experiments; see **Methods**)

to derive individual "social tuning curves". For detection curves, we focused on three main

parameters: (i) point of subjective equality (PSE), the value of *chase directness* at which the

participant's percept crosses the midpoint of the rating scale (0.5); higher values indicate that

more evidence is needed to declare something "social"; (ii) range, the difference between ratings

at the lowest (0) and highest (1) levels of *chase directness*; higher values may reflect higher

perceptual vividness, certainty or diversity; and (iii) bias, the extent to which ratings are skewed

toward one end of the scale; higher values (> 0.5) indicate a bias toward social ("chasing") while

lower values (< 0.5) indicate a bias toward nonsocial ("moving independently"). For

discrimination curves, we focused on two main parameters: (i) PSE, the *charge speed* at which

participants' percept crosses the midpoint (0.5; i.e., percept switches from play to fight), lower

values reflect a lower threshold to detect aggressive interactions ; and (ii) bias, the extent to

which ratings are skewed toward one end of the scale; higher values (> 0.5) indicate a bias

toward "fighting" while lower values (< 0.5) indicate a bias toward "playing". See Fig 2 for a

schematic of these parameters.

While the vast majority of participants showed the same general directionality as the

group-level trends, fine-grained properties of tuning curves differed between participants (see

Fig 4a for sample participants [all data in Fig S4 and S5] and Fig 4b for full distributions of

parameters of interest). To test the stability of these tuning curves within participants, we had

participants return for a second session 1–2 months later, in which the task design was identical

to the first session except that we used previously unseen animations (generated using the same

algorithms). Visual inspection showed that idiosyncrasies in behavior and tuning curves were

largely preserved across sessions (e.g., Fig 4a). The main curve parameters did show some

systematic session-to-session variation in both tasks, but their magnitudes were very small:

namely, in the detection task, people discriminate slightly less between social and non-social

interactions (lower range) in session 2, and in the discrimination task, people are slightly less

biased towards aggressive ratings in session 2 (see Fig S6a for details).

We quantified the stability and uniqueness of tuning curves in two ways. First, we used

parameters calculated on data from a participant's first session to fit the same participant's data

in their second session (or vice versa). To test the extent to which curve parameters were both

stable within people and distinct across people, we compared this within-participant fit to the

mean across-participant fit calculated by using each participant's curve to fit data from all other

participants in the same session. Participants' ratings were generally better predicted by their

own curves from a different session than the average of everyone else's curves in the same

sessions (Fig 4c, middle and right violin plots within each subplot; outliers omitted for clarity;

detection task: mean difference (MD) = 0.04 and 0.05 when fitting session 2 data to session 1

and vice versa, both $p < .001$; discrimination task: MD = 0.07 ($p = .006$) and 0.08 ($p = .06$) when

fitting session 2 data to session 1 and vice versa). Second, we calculated the intra-class

correlation coefficient between parameters fit to data within each session for each parameter of

interest. In the detection task (sigmoid fit), PSE, range and bias showed moderate to good

reliability; in the discrimination task (linear fit), PSE and bias showed generally moderate
reliability (Fig 4d; see Fig S6b-c for data on other parameters that were less reliable and/or
redundant with the main curve parameters of interest and Fig S6d for the covariance between all
curve parameters). Overall, then, individual tuning curves for both social detection and
discrimination were both stable within participants (reliable across sessions) and unique between
participants, suggesting a trait-like component.

Fig 4: Individual differences in social tuning curves. (a) Tuning curves for sample participants
in two distinct sessions. Dots represent mean ratings at each motion attribute level, and the line
shows the best fitting sigmoid (detection) or linear curve (discrimination). For the full versions,
see Fig S4 and S5. (b) Histograms showing the full distributions of the main curve parameters of
interest from all participants in session 1 (left, detection experiment; right, discrimination
experiment). PSE, point of subjective equality. (c) Predicting individuals' single-session ratings

using curve parameters fit to their own data from the same session (left), their own data from a different session (middle), or the average parameters from all other participants in the same session (right). NRMSE=normalized root mean square error; lower values indicate better fits. (d) Test-retest reliability between sessions 1 and 2 of the main curve parameters of interest. Each dot represents a participant. Test-retest reliability for other parameters is shown in Fig S6. *** = p < .001, ** = p < .01, · = p < .1.

Individual social detection and discrimination tendencies are only weakly related

Social detection and discrimination both exhibit shared tendencies as well as robust individual differences, but how do behaviors relate across the two tasks? In other words, are individuals' discrimination tendencies predictable from their detection tendencies (and vice versa)? For example, people who are more prone to seeing social interactions in the first place might also be more prone to seeing them in a more positive (or negative) light. To study this, we conducted a third experiment in which a new set of participants performed both the detection and discrimination tasks in interleaved blocks in a single session. We successfully replicated the group-level behavioral trends (Fig 3) in this new group of people (see Fig S8). We then fit sigmoid and linear curves to each individual's detection and discrimination data, respectively.

Next, we correlated curve parameters across participants both within and across tasks. The within-task correlations were overall similar to the correlations from the individual detection and discrimination tasks (Fig S6d). Focusing on between-task correlations (highlighted part of the matrix in Fig 5), the majority of pairwise correlations were weak, suggesting that detection and discrimination behavior are overall relatively independent. We did, however, find three significant relationships that survived multiple comparison correction (false discovery rate or FDR $q < .05$). First, the *range* parameter correlated moderately across tasks ($r = 0.44$). This indicates that people who distinguished social ("chasing") from non-social ("moving independently") more strongly also distinguished negative interactions ("fighting") more from positive interactions ("playing") more strongly. This could reflect people's general confidence/willingness to use extremes (people who are more confident may have used a wider range of the rating scale in both tasks) and/or the extent to which their percepts are sensitive to sensory evidence (people whose percepts vary more strongly with sensory evidence would have

a higher range in both tasks). Next, people who showed a higher bias toward socialness

("chasing") in the detection task also showed a higher range (more distance between extremes) in

the discrimination task ($r = .37$). This suggests that people who are more predisposed to

detecting social interactions may also be more sensitive to motion cues and/or more certain when

discriminating between different types of interactions. Lastly, people who showed a higher bias

towards socialness had a lower PSE, i.e., they characterized interactions as aggressive at lower

charge speeds ($r = -0.16$). Still, on the whole, social discrimination tendencies were largely not

directly predictable from detection tendencies and vice versa. This suggests that behavior on the

two tasks may be complementary in revealing individual differences in social perception, and

combining information about detection and discrimination tuning curves likely better

characterizes individuals' socio-perceptual tendencies than one task alone.

Fig 5: Correlation between the main curve parameters of interest from the social detection and

discrimination tasks in the mixed-task experiment (within-subject design). Across tasks (black

box), only two moderate pairwise correlations emerged, suggesting that each task provides non-

redundant information about individuals' socio-perceptual tendencies. Significant correlations

(FDR q < .05) are displayed in bold text.

Traits explain some of the individual differences in socio-perceptual

tendencies

How do socio-perceptual tendencies as measured by behavior on our detection and
discrimination tasks relate to real-world variability in social function? In past work, behavior on
related tasks has been found to differ in various clinical and subclinical conditions including
autism[6–10], internalizing symptoms[5], depression[14–17], and loneliness[47,48]. In our final set of
analyses, we studied if and how properties of individuals' social tuning curves covaried with
social, affective, and personality traits as measured by established self-report scales (see
Methods for details).

We performed a series of multiple linear regressions using the trait scores (14 total) to
predict two curve parameters each from the detection and discrimination tasks. The first
parameter was a combined index, created by subtracting PSE from bias (*bias – PSE*; see
Methods for details); this term captures sensitivity to see social and aggressive interactions in the
detection and discrimination tasks, respectively. The second was the *range* parameter. We
performed separate regressions for the detection and discrimination task (4 regressions in total).

For the detection task, the multiple regression to predict *bias – PSE* showed that
individuals with lower communication deficits (*comm*) and agreeableness scores (*agree*) but
higher extraversion scores (*extr*) were more likely to perceive social interactions (95%CI: *comm*
= [–0.89, –0.19], *agree* = [–0.64, –0.12], *extr* = [0.002, 0.78]). In addition to these specific
relationships, the full detection model performed well in a permutation test to test its overall
exploratory power (where bias – PSE was permuted 10k times and their R^2 values compared
against the true model R^2; p = .03). For the discrimination task, the multiple regression showed
that individuals who were less lonely were more likely to perceive aggressive interactions in the
(95%CI: *lone* = [–0.83, –0.09]); however, the overall discrimination model performed poorly in a
permutation test (*p* = .5), suggesting that this result should be interpreted with caution.

The multiple regression to predict *range* showed that individuals with higher negative
affect (*neg*) had a higher *range* (used more of the non-social to social scale) in the detection task
(95%CI: *neg* = [0.04, 0.35]) and that people with lower communication deficits, higher negative
affect and conscientiousness had a higher *range* (used more of the play-fight scale; 95%CI:
comm = [–0.43, –0.01], neg = [0.04, 0.36], C = [0.02, 0.34]) in the discrimination task. Here the
overall goodness of model fit was the opposite of what we saw with *bias – PSE*; while the
discrimination model fit was better than the permutations (p = .004), the detection model
performed poorly (*p* = .55).

To conclude, we found some evidence that individual differences in social sensitivity (*bias –*

PSE from the detection task) and the discriminability between playful and aggressive interactions

(*range* from the discrimination task) showed some relationships with socio-affective traits. In

particular, the relationships with social sensitivity in the detection task are in line with past work

and our *a priori* hypotheses that individuals who are more skilled at social interactions (lower

communication deficits) and more motivated to engage in social interactions (higher

extraversion) are also more likely to perceive social information in their environment. The

relationships with *range* in the discrimination task should be interpreted in light of our cover

story, which induced a general expectation of playfulness; the significant terms suggest that

higher general negative affect, more carefulness (higher conscientiousness) and stronger social

skills (lower communication deficits) may underlie better discriminability between positive and

negative social interactions, or, in other words, less of a bias to see only playful interactions.

(a) Sensitivity (bias - PSE)

(b) Range

Fig 6: Results from the multiple linear regression between task behavior (curve parameter = f(traits)) and the 14 trait dimensions. Regression estimates for (a) the combined sensitivity index bias – PSE, which reflects sensitivity towards social (detection) or aggressive (discrimination) interactions and (b) range. The statistical significance of the regression coefficients was obtained by bootstrapping (sampling with replacement) participants 1000 times and estimating the 95% CI of each regression coefficient. The black markers show the mean, and the blue/red lines show the 95%CI. The histograms at the lower right section within each subplot show how the true model fit (vertical black line) compares to 10000 permutations (shuffles of the curve parameter; grey histogram). *= p < .05, ** = p < .01, ***= p< .001. Abbreviations: Autism Quotient (AQ) questionnaire subscales – 'soc': social skill deficits, 'attn': attention-switching deficits, 'img': imagination deficits, 'det': heightened attention-to-detail and 'comm': communication deficits; Positive and Negative Affect Schedule (PANAS) subscales – 'pos': positive affect and 'neg': negative affect; Big 5 (NEO-FFI) subscales – 'neur': neuroticism, 'extr': extraversion, 'open': openness, 'agree': agreeableness and 'consc': conscientiousness; 'lone': loneliness score; '# fr.': number of friends.

Discussion

Here, we used a psychophysics-inspired approach to characterize both group-level tendencies and individual differences in social perception. We found strong commonalities in how people use relatively low-level motion attributes to arrive at percepts of the presence (detection experiments) and nature (discrimination experiments) of a social interaction, and also robust individual differences that were replicable over a period of months and showed some relationships to trait phenotypes.

Our approach lends a level of rigor and precision to the study of social perception. While some notable past work has used parametric stimulus manipulations[22,55–58], here, we extend this approach to individual-subject data to recover single-person social tuning curves that are both reliable and unique. Generating stimuli algorithmically makes our approach simultaneously more objective and more subjective: more objective because we can create parametric manipulations using quantitatively defined features (rather than relying on handcrafted stimuli created and

labeled via experimenter intuition[30]) and thereby generalize beyond item-level effects, and more

subjective because we are eschewing any notions of a ground truth and classifying behavior

according to observers' own reports[59], which better reflects what happens in the real world—

where different people can and do interpret the same social situation differently.

Social cognition is traditionally considered a high-level process, but more recent work

has found evidence that recognizing and processing social information begins earlier in the

perceptual hierarchy than previously thought[26,60–63], and artificial intelligence can extract basic

cues as to the presence and nature of social information using fast, automatic, visually-based

processes[60]. The recently proposed "third visual pathway" in the brain, which runs along the

lateral surface from early visual regions into the superior temporal sulcus and is specialized for

extracting social information from dynamic cues, embodies the theory that our visual system

might be especially attuned to social information, given its evolutionary importance[62]. Our work

adds to this growing body of work by showing that parametrically varying meaningful "mid-

level" visual motion attributes[64] even in very stripped-down, simplified stimuli can directly

modulate social percepts at both the group and individual level, thus confirming that social

perception involves visual evidence accumulation with both an objective and subjective

component. Of note, autism is a condition marked by deficits with social cognition, but also

altered basic visual processing[65,66]; the idea that perception is the fundamental starting point for

social cognition might lead us to discover hierarchical links between aberrations in these two

domains.

While the motion attributes we used here, *chase directness* and *charge speed*, were

sufficient to evoke varying social detection and discrimination percepts respectively, we also

acknowledge that social percepts are governed by many more dimensions than these two. We

propose the idea of individual social perception "landscapes" that can be conceptualized as a

multidimensional space spanned by objectively defined axes (e.g., motion attributes such as our

chase directness and *charge speed*, plus many others) where the dimensions themselves are

fixed, but sensitivity to these dimensions varies across people and can be expressed in terms of

tuning curve parameters. In Fig 7, we show a two-dimensional schematic of what these

landscapes might look like and how they might vary. In this example, the horizontal axis

represents an attribute that influences *if* a social interaction is perceived (detection; e.g., *chase*

directness) and the vertical axis represents an attribute that influences *how* a social interaction is

perceived (discrimination; e.g., *charge speed*). A healthy neurotypical individual (Fig 7a) might

show moderate sensitivity to objective evidence for socialness (indicated by the saturation

gradient along the horizontal axis); once information is generally deemed social, percepts of the

nature of that information are generally balanced between positive and negative interactions

(even vertical distribution of pink and blue). Someone with an autism-like phenotype (Fig 7b)

might have lower sensitivity to social information—in other words, they might require higher

doses of objective evidence to detect a social interaction. For someone with a depression-like

phenotype (Fig 7c), detection sensitivity may be largely normal, but discrimination might be

skewed toward negative percepts. Lastly, someone with psychosis/paranoia-like traits (Fig 7d)

might show both heightened sensitivity to socialness and a bias towards negative percepts—in

other words, a proneness to read social intentions, particularly nefarious ones, into scenarios that

others might perceive as non-social or, at most, social yet neutral. While we explored only two

possible dimensions here, and did not include clinical populations, we see the present set of

experiments as a first step toward discovering and characterizing these landscapes—which,

because they are based on more implicit behavioral readouts, are possibly less prone to overt bias

than self-report measures and therefore a useful complement to existing trait scales. In support of

this, our results showed that each axis carries some unique variance in its association with socio-

affective traits – while both social sensitivity in the detection task and range in the discrimination

task were associated with better communication skills, social sensitivity was also uniquely

associated with higher extraversion and lower agreeableness, while discrimination range was

associated with higher negative affect and conscientiousness. Adding more dimensions (i.e.,

using more complex, yet still parameterized stimuli) will likely enhance our ability to

characterize real-world social and affective function.

1066

1067

Fig 7. 2D projection of social perception landscapes with detection (not social ↔ social) and discrimination (positive ↔ negative) along the horizontal and vertical axes, respectively. How subjective percepts of the presence and nature of social interactions may present in (a) a neurotypical individual versus individuals with (b) autistic, (c) depressive or (d) psychotic traits who show, respectively, reduced progression towards social with sensory evidence (large faded area), increased biases towards negative percepts (large blue zone even at typically neutral or positive evidence), and an increased social sensitivity as well as bias towards negative (leftward saturation combined with expanded blue territory), respectively.

Future work can combine our psychophysics-inspired task framework with additional readouts such as reaction times, eye-tracking, physiological measures and/or neuroimaging to yield a more comprehensive picture of the evidence accumulation and decision-making strategies, attentional processes, and other computations underlying individuals' social-perceptual judgments. There may be a role for generative AI in bridging the gap between the highly impoverished stimuli used here and the full complexity of real-world social information— i.e., we may be able to use generative AI to create more naturalistic-feeling stimuli that are nevertheless still parameterized along known axes. In closing, we note that while the vast majority of past work on social perception and cognition has focused on passive (third person) perception of others' interactions—which is indeed an important part of social cognition—many

of our most salient and important social experiences are ones in which we are an active (first-person) participant. One final advantage of our framework is that it can be easily adapted to a first-person context, in which participants themselves are controlling one of the agents and the other agents are programmed to behave in a certain way toward them. This opens the door to generating and comparing social tuning curves between passive and active scenarios, as well as extracting more latent behavioral readouts such as participants' movement trajectories, which we anticipate will provide an even richer and more useful picture of social perception at both the group and individual levels.

Acknowledgements

This work was funded by R01MH129648 (E.S.F.), Neukom CompX Faculty Grant (E.S.F.). We thank Tommy Botch and Clara Sava-Segal for their support and guidance with NLP models and several analyses suggestions, Ahmed Elyamani and Danrae Pray for their help with developing the software, Peng Liu and Jordan Selesnick for their inputs in the preliminary stages of the experiments, undergraduate RAs Alison Sasaki and Eliana Stanford for help with quality-checking stimuli, piloting the experiments and testing the *psyanim* software, and Beyond Bounds Creative for their help with schematics in Fig 7.

References

1. Abassi, E. & Papeo, L. Behavioral and neural markers of visual configural processing in social scene perception. *NeuroImage* **260**, 119506 (2022).

2. Hull, K., Van Hedger, K. & Van Hedger, S. C. Absorption relates to individual differences in visual face pareidolia. *Curr Psychol* (2023) doi:10.1007/s12144-023-04670-6.

3. Nguyen, M., Vanderwal, T. & Hasson, U. Shared understanding of narratives is correlated with shared neural responses. *NeuroImage* **184**, 161–170 (2019).

4. Ratajska, A., Brown, M. I. & Chabris, C. F. Attributing Social Meaning to Animated Shapes:

A New Experimental Study of Apparent Behavior. *The American Journal of Psychology*

133, 295–312 (2020).

5. Varrier, R. S. & Finn, E. S. Seeing Social: A Neural Signature for Conscious Perception of

Social Interactions. *J. Neurosci.* **42**, 9211–9226 (2022).

6. Rasmussen, C. E. & Jiang, Y. V. Judging social interaction in the Heider and Simmel movie.

Quarterly Journal of Experimental Psychology **72**, 2350–2361 (2019).

7. Zwickel, J., White, S. J., Coniston, D., Senju, A. & Frith, U. Exploring the building blocks of

social cognition: spontaneous agency perception and visual perspective taking in autism.

Social Cognitive and Affective Neuroscience **6**, 564–571 (2011).

8. Klin, A. & Jones, W. Attributing social and physical meaning to ambiguous visual displays in

individuals with higher-functioning autism spectrum disorders. *Brain and Cognition* **61**, 40–

53 (2006).

9. Vandewouw, M. M. *et al.* Do shapes have feelings? Social attribution in children with autism

spectrum disorder and attention-deficit/hyperactivity disorder. *Transl Psychiatry* **11**, 1–11

(2021).

10. Lisøy, R. S. *et al.* Seeing minds – a signal detection study of agency attribution along the

autism-psychosis continuum. *Cognitive Neuropsychiatry* **0**, 1–17 (2022).

11. Langdon, R., Boulton, K., Connaughton, E. & Gao, T. Perceiving and attributing

intentionality in schizophrenia. *Cognitive Neuropsychiatry* **25**, 269–280 (2020).

12. Horan, W. P. *et al.* Disturbances in the spontaneous attribution of social meaning in

schizophrenia. *Psychological Medicine* **39**, 635–643 (2009).

13. Castiello, S., Ongchoco, J. D. K., van Buren, B., Scholl, B. J. & Corlett, P. R. Paranoid and

teleological thinking give rise to distinct social hallucinations in vision. *Commun Psychol* **2**,

1–12 (2024).

14. Kohler, C. G., Hoffman, L. J., Eastman, L. B., Healey, K. & Moberg, P. J. Facial emotion

perception in depression and bipolar disorder: A quantitative review. *Psychiatry Research*

188, 303–309 (2011).

15. Liu, W., Huang, J., Wang, L., Gong, Q. & Chan, R. C. K. Facial perception bias in patients

with major depression. *Psychiatry Research* **197**, 217–220 (2012).

16. Krause, F. C., Linardatos, E., Fresco, D. M. & Moore, M. T. Facial emotion recognition in

major depressive disorder: A meta-analytic review. *Journal of Affective Disorders* **293**, 320–

328 (2021).

17. Kaletsch, M. *et al.* Major Depressive Disorder Alters Perception of Emotional Body

Movements. *Front. Psychiatry* **5**, (2014).

18. Barrett, H. C., Todd, P. M., Miller, G. F. & Blythe, P. W. Accurate judgments of intention

from motion cues alone: A cross-cultural study. *Evolution and Human Behavior* **26**, 313–331

(2005).

19. Blythe, P. W., Todd, P. M. & Miller, G. F. How motion reveals intention: Categorizing

social interactions. in *Simple heuristics that make us smart* 257–285 (Oxford University

Press, New York, NY, US, 1999).

20. Heider, F. & Simmel, M. An Experimental Study of Apparent Behavior. *The American*

Journal of Psychology **57**, 243–259 (1944).

21. Abell, F., Happé, F. & Frith, U. Do triangles play tricks? Attribution of mental states to

animated shapes in normal and abnormal development. *Cognitive Development* **15**, 1–16

(2000).

22. Gao, T., Newman, G. E. & Scholl, B. J. The psychophysics of chasing: A case study in the

perception of animacy. *Cognitive Psychology* **59**, 154–179 (2009).

23. Isik, L., Koldewyn, K., Beeler, D. & Kanwisher, N. Perceiving social interactions in the

posterior superior temporal sulcus. *Proceedings of the National Academy of Sciences* **114**,

E9145–E9152 (2017).

24. Scholl, B. J. & Tremoulet, P. D. Perceptual causality and animacy. *Trends in Cognitive*

Sciences **4**, 299–309 (2000).

25. Zhou, L.-F. & Meng, M. Do you see the "face"? Individual differences in face pareidolia.

Journal of Pacific Rim Psychology **14**, e2 (2020).

26. McMahon, E. & Isik, L. Seeing social interactions. *Trends in Cognitive Sciences* (2023)

doi:10.1016/j.tics.2023.09.001.

27. Dunbar, R. I. M. The social brain hypothesis – thirty years on. *Annals of Human Biology* **51**,

2359920 (2024).

28. Frith, C. & Frith, U. *What Makes Us Social?* (MIT Press, 2023).

29. Barch, D. M. *et al.* Function in the human connectome: task-fMRI and individual differences

in behavior. *Neuroimage* **80**, 169–189 (2013).

30. Castelli, F., Happé, F., Frith, U. & Frith, C. Movement and Mind: A Functional Imaging

Study of Perception and Interpretation of Complex Intentional Movement Patterns.

NeuroImage **12**, 314–325 (2000).

31. Hamlin, J. K., Wynn, K. & Bloom, P. Social evaluation by preverbal infants. *Nature* **450**,

557–559 (2007).

32. Rutherford, M. D. & Kuhlmeier, V. A. *Social Perception: Detection and Interpretation of*

Animacy, Agency, and Intention. (MIT Press, 2013).

33. Ullman, T. *et al.* Help or Hinder: Bayesian Models of Social Goal Inference. in *Advances in*

Neural Information Processing Systems vol. 22 (Curran Associates, Inc., 2009).

34. Schultz, J., Friston, K. J., O'Doherty, J., Wolpert, D. M. & Frith, C. D. Activation in

Posterior Superior Temporal Sulcus Parallels Parameter Inducing the Percept of Animacy.

Neuron **45**, 625–635 (2005).

35. Schultz, J. & Bülthoff, H. H. Parametric animacy percept evoked by a single moving dot

mimicking natural stimuli. *Journal of Vision* **13**, 15 (2013).

36. Palmer, C. J., Kim, P. & Clifford, C. W. G. Gaze behavior as a visual cue to animacy.

Journal of Experimental Psychology: General **152**, 425–447 (2023).

37. Neri, P., Luu, J. Y. & Levi, D. M. Meaningful interactions can enhance visual discrimination

of human agents. *Nat Neurosci* **9**, 1186–1192 (2006).

38. Trompenaars, T., Kaluge, T. A., Sarabi, R. & de Swart, P. Cognitive animacy and its relation

to linguistic animacy: evidence from Japanese and Persian. *Language Sciences* **86**, 101399

(2021).

39. Schultz, J. & Frith, C. D. Animacy and the prediction of behaviour. *Neuroscience &*

Biobehavioral Reviews **140**, 104766 (2022).

40. Leeuw, J. R. de, Gilbert, R. A. & Luchterhandt, B. jsPsych: Enabling an Open-Source

Collaborative Ecosystem of Behavioral Experiments. *Journal of Open Source Software* **8**,

5351 (2023).

41. Wang, W. *et al.* MiniLM: Deep Self-Attention Distillation for Task-Agnostic Compression

of Pre-Trained Transformers. Preprint at https://doi.org/10.48550/arXiv.2002.10957 (2020).

42. Jolly, E. Pymer4: Connecting R and Python for Linear Mixed Modeling. *Journal of Open*

Source Software **3**, 862 (2018).

43. Loureiro, D., Barbieri, F., Neves, L., Anke, L. E. & Camacho-Collados, J. TimeLMs:

Diachronic Language Models from Twitter. Preprint at

https://doi.org/10.48550/arXiv.2202.03829 (2022).

44. Mohammad, S. M. NRC VAD Lexicon v2: Norms for Valence, Arousal, and Dominance for

over 55k English Terms. Preprint at https://doi.org/10.48550/arXiv.2503.23547 (2025).

45. Gescheider, G. A. *Psychophysics: Method, Theory, and Application*. (Taylor & Francis

Group, 1985).

46. Epley, N., Akalis, S., Waytz, A. & Cacioppo, J. T. Creating Social Connection Through

Inferential Reproduction: Loneliness and Perceived Agency in Gadgets, Gods, and

Greyhounds. *Psychol Sci* **19**, 114–120 (2008).

47. Gardner, W. L., Pickett, C. L., Jefferis, V. & Knowles, M. On the Outside Looking In:

Loneliness and Social Monitoring. *Pers Soc Psychol Bull* **31**, 1549–1560 (2005).

48. Powers, K. E., Worsham, A. L., Freeman, J. B., Wheatley, T. & Heatherton, T. F. Social

Connection Modulates Perceptions of Animacy. *Psychol Sci* **25**, 1943–1948 (2014).

49. Tomova, L. *et al.* Acute social isolation evokes midbrain craving responses similar to

hunger. *Nat Neurosci* **23**, 1597–1605 (2020).

50. Baron-Cohen, S., Wheelwright, S., Skinner, R., Martin, J. & Clubley, E. The Autism-

Spectrum Quotient (AQ): Evidence from Asperger Syndrome/High-Functioning Autism,

Males and Females, Scientists and Mathematicians. *J Autism Dev Disord* **31**, 5–17 (2001).

51. Russell, D., Peplau, L. A. & Ferguson, M. L. Developing a Measure of Loneliness. *Journal*

of Personality Assessment (1978) doi:10.1207/s15327752jpa4203_11.

52. Watson, D., Clark, L. A. & Tellegen, A. Development and validation of brief measures of

positive and negative affect: The PANAS scales. *Journal of Personality and Social*

Psychology **54**, 1063–1070 (1988).

53. Franić, S., Borsboom, D., Dolan, C. V. & Boomsma, D. I. The Big Five Personality Traits:

Psychological Entities or Statistical Constructs? *Behav Genet* **44**, 591–604 (2014).

54. Santavirta, S., Malén, T., Erdemli, A. & Nummenmaa, L. A taxonomy for human social

perception: Data-driven modeling with cinematic stimuli. *J Pers Soc Psychol* (2024)

doi:10.1037/pspa0000415.

55. Horovitz, S. G., Rossion, B., Skudlarski, P. & Gore, J. C. Parametric design and correlational

analyses help integrating fMRI and electrophysiological data during face processing.

NeuroImage **22**, 1587–1595 (2004).

56. Johansson, M., Mecklinger, A. & Treese, A.-C. Recognition Memory for Emotional and

Neutral Faces: An Event-Related Potential Study. *Journal of Cognitive Neuroscience* **16**,

1840–1853 (2004).

57. Looser, C. E. & Wheatley, T. The Tipping Point of Animacy: How, When, and Where We

Perceive Life in a Face. *Psychol Sci* **21**, 1854–1862 (2010).

58. Schultz, J. & Bülthoff, H. H. Perceiving animacy purely from visual motion cues involves

intraparietal sulcus. *NeuroImage* **197**, 120–132 (2019).

59. Peters, M. A. K. Introspective psychophysics for the study of subjective experience.

Cerebral Cortex bhae455 (2024) doi:10.1093/cercor/bhae455.

60. Malik, M. & Isik, L. Relational visual representations underlie human social interaction

recognition. *Nat Commun* **14**, 7317 (2023).

61. Gandolfo, M. *et al.* Converging evidence that left extrastriate body area supports visual

sensitivity to social interactions. *Current Biology* **34**, 343-351.e5 (2024).

62. Pitcher, D. & Ungerleider, L. G. Evidence for a Third Visual Pathway Specialized for Social

Perception. *Trends in Cognitive Sciences* **25**, 100–110 (2021).

63. Thieu, M. K., Ayzenberg, V., Lourenco, S. F. & Kragel, P. A. Visual looming is a primitive

for human emotion. *iScience* **27**, (2024).

64. McMahon, E., Bonner, M. F. & Isik, L. Hierarchical organization of social action features

along the lateral visual pathway. (2023).

65. Choi, Y. B., Mentch, J., Haskins, A. J., Van Wicklin, C. & Robertson, C. E. Visual

processing in genetic conditions linked to autism: A behavioral study of binocular rivalry in

individuals with 16p11.2 deletions and age-matched controls. *Autism Research* **16**, 831–840

(2023).

66. Robertson, C. E. & Baron-Cohen, S. Sensory perception in autism. *Nat Rev Neurosci* **18**,

671–684 (2017).

1259

1260

1261