SwiftMHC: A High-Speed Attention Network for MHC-Bound Peptide Identification and 3D Modeling

Coos Baakman[1], Giulia Crocioni[2], Daniel T. Rademaker[1,3,4,5], David Frühbuß[1,5], Yannick J. M. Aarts[6], Li C. Xue[1*]

[1] Medical BioSciences department, Radboud University Medical Center, 6525 GA Nijmegen, The Netherlands

[2] Netherlands eScience Center, Amsterdam, The Netherlands

[3] Biosystems Data Analysis, University of Amsterdam, 1090 GE Amsterdam, the Netherlands

[4] HIMS-Biocat, University of Amsterdam, Science Park 904, Amsterdam 1098 XH, The Netherlands

[5] Amsterdam Machine Learning Lab, University of Amsterdam, Science Park 900, 1098 XH Amsterdam, The Netherlands

[6] Adaptation Physiology Group, Department of Animal Sciences, Wageningen University and Research, PO Box 338, 6700 AH, Wageningen, the Netherlands

*corresponding author

Abstract

Cancer immunotherapies show promise in eliminating tumors, but identifying tumor peptides that bind patient MHC proteins to trigger immune responses remains challenging. The vast peptide-MHC diversity makes experimental identification costly, emphasizing the need for computational predictions.

To address scalability, we introduce SwiftMHC, an attention network for identifying MHC-bound peptides and generating all-atom 3D structures simultaneously. SwiftMHC processes cases in 0.01 to 2.2 seconds on a single A100 GPU, overcoming the speed bottleneck of structure-based approaches. It rivals or surpasses state-of-the-art tools, including an AlphaFold-based approach, in binding affinity prediction and 3D modeling.

SwiftMHC showcases the advantages of task-specific AI trained on physics-derived synthetic data for speed and precision. Optimized for HLA-A*02:01 9-mers, it can be adapted to other MHC alleles. Its speed and accuracy may enable the community to identify peptides distinct from self-peptides at T-cell exposed surfaces, ensuring safer therapies, expanding immunotherapy targets, and accelerating development.

Main

Advances in understanding T cell immunity have led to breakthroughs in cancer immunotherapy, where the immune system is trained to recognize and destroy cancer cells, offering a promising alternative to traditional treatments with fewer side effects[1]. T cells are activated when their T-cell receptor (TCR) recognizes tumor-specific peptides presented on the tumor cell surface by the class I major histocompatibility complex (MHC-I) proteins (**Fig. 1A** for molecular details). However, these therapies face challenges, including high costs, long development time and toxicity risks[1,2].

Currently, the limited number of available target peptides is one of the major bottlenecks of cancer immunotherapies[3].

To address these challenges, reliably and efficiently identifying MHC-bound peptides is essential. In humans, MHCs are encoded by highly polymorphic human leukocyte antigen (HLA) alleles, with approximately 40,000 variants currently identified[4]. These MHC molecules present tumor-derived peptides on cell surfaces, facilitating T cell activation. The ability of a tumor peptide to bind strongly to a patient's specific MHC alleles is a critical prerequisite for successful immunotherapy, as it determines the initiation of an immune response against the tumor. Mass spectrometry (MS) is proven to be a powerful technology for directly identifying MHC-binding peptides from patient-derived tumor samples or cell lines in a high-throughput manner[5]. However, the application of MS in immunopeptidome identification is limited by challenges in sensitivity and scalability, highlighting the need for predictive computational approaches.

Many predictive methods have been developed to identify MHC-binding peptides[6,7], which have recently already made significant contributions in cancer immunotherapies design[8]. State-of-the-art (SOTA) tools, such as MHCflurry[9] and netMHCpan[10] use both the sequence of the MHC binding groove and the peptide sequence as input. However, these sequence-based approaches have notable limitations: they fail to consider critical structural features of MHC-peptide interactions, require extensive data due to their dependence on sequence information, and struggle to efficiently handle peptides of varying lengths.

Alternatively, 3D structure-based approaches offer several compelling advantages: 1) they naturally handle peptide length variability in 3D space; 2) they are sensitive to mutations in both the spatial and energy landscapes; 3) they are potentially more robust for rare alleles due to the high conservation of MHC structures (**Fig. 1BC**); 4) 3D structures provide fundamental insights into the mechanisms of immunotherapies. However, experimental methods like X-ray crystallography, NMR and cryo-EM are labor-intensive and cannot keep up with the diversity of pMHCs. To date, only ~1000 pMHC structures are available in the Protein Data Bank (PDB, www.rcsb.org)[11]. Therefore, complementary 3D modeling techniques are valuable tools. PANDORA[12] and APE-Gen 2.0[13] are physics-based homology modeling methods that can generate multiple MHC-I or MHC-II models within minutes, while also providing energy scores that may indicate binding affinity (BA). AlphaFold[14,15], a general-purpose deep learning (DL) based 3D protein modeling tool, uses computationally expensive modules to process multiple sequence alignments (MSAs), which are often unavailable for short MHC-bound peptides lacking sufficient evolutionary information. AlphaFold2-FineTune[16] is a specialized version of AlphaFold2 designed to predict BA for pMHC interactions on generated 3D structures. Instead of generating MSAs, it requires user-provided query-to-template alignments, saving time by eliminating the need to search large sequences in databases. However, it still relies on AlphaFold2's computationally intensive Evoformer module to process the alignments, a limitation Mikhaylov et al.[17] also encountered when attempting a similar approach. MHCfold uses convolutional neural networks to predict 3D pMHC structures and then use multi-headed attention on the

predicted structures to predict BAs. However, the structures generated by MHCfold contain only backbones and rely on tools like MODELLER[18] or SCWRL4[19] for side-chain modelling. Recent studies have shown that BA predictors that take 3D models as input are more robust than sequence-based methods[20]. However, these methods require two steps: first, building the 3D pMHC models (which takes seconds to minutes) , then feeding them into geometric deep learning networks (GDLs) for BA predictions. This two-step process is time-consuming and limits scalability, especially when screening large numbers of mutated proteins from patient' samples. There is a clear need for a time-efficient system capable of simultaneously predicting 3D structures and BA.

Figure 1. The TCR-peptide-MHC class I (TCR:pMHC-I) complex and neoantigens: their central role in immune surveillance and T-cell-mediated immune attacks on tumor cells. A. TCR nomenclature and the TCR:pMHC-I complex. A TCR has two chains (α and β chains), each having three loops (CDR1, CDR2, and CDR3), where CDR3 plays the primary role in interacting with the peptide**.** The image on the right shows the structural representation of a TCR:pMHC-I complex based on PDB entry 7RTR. **B.** Structural alignment of five different MHC alleles: HLA-A*02:01 (Homo sapiens, PDB ID: 5HHN), HLA-B*27:05 (Homo sapiens, PDB ID: 5IB2), HLA-C*08:01(Homo sapiens, PDB ID: 4NT6), H-2Kd (Mus musculus, PDB ID: 1VGK), and UAA106 (Ctenopharyngodon idella, bony fish, PDB ID: 6LBE). The MHC G-domains all consist of two α-helices and a β-sheet.

The peptides are bound in the MHC binding groove. The root mean square deviation (RMSD) values for the structural alignment of these G-domains are all below 0.8 Å, demonstrating highly conserved MHC structures across different alleles and species. **C.** Sequence alignment of MHC G-domains. The sequence alignment of the MHC G-domains from the five alleles shown in panel B demonstrates high diversity in the MHC sequences. The alignment was generated using Clustal Omega[21] and visualized in MRS[22] with colors representing the charge, hydrophobicity, size and shape of amino acid side chains. Blue cylinders above the sequences indicate α-helices, while red arrows denote β-strands.

Here, we present SwiftMHC, a fast DL system that simultaneously predicts pMHC-I BA and generates corresponding 3D structures (**Fig. 2A**). By leveraging the conserved architecture of MHC proteins and avoiding computationally intensive MSA-based modules like AlphaFold's Evoformer, SwiftMHC ensures rapid and accurate predictions. To address the challenge of modeling peptide conformations without evolutionary constraints, we enhance the training dataset with physics-based 3D models and biochemistry-derived BA data, synergistically improving both structural and affinity predictions. SwiftMHC utilizes a residue-to-residue attention mechanism to learn to predict BA and structural features based on interactions between neighboring amino acids. Specifically, its Self Attention network modules extract residue representations using neighborhood information of peptide and MHC, respectively, while its cross-attention network module encodes interaction-specific weights, enabling simultaneous 3D modeling and BA prediction.

The compact design of SwiftMHC establishes it as the fastest 3D modeller and the fastest structure-based BA predictor for pMHC-I with SOTA predictive accuracy. This work highlights the promise of building specialized DL systems on physics-derived 3D models, especially in data-scarce domains such as CDR3 loop modeling for T-cell receptors (TCRs) and antibody-antigen interactions, where evolutionary information is absent. Finally, we discuss the limitations of SwiftMHC and avenues for future improvement.

Key contributions of this work include:

1. Showcasing the advantages of task-specific small AI trained on physics-derived synthetic data to achieve remarkable speed and precision over general-purpose big AI (like AlphaFold).
2. Demonstrating SwiftMHC's performance for HLA-A*02:01 9-mer peptides, one of the most prevalent alleles in the human population[23–25]. SwiftMHC enables large-scale screening of patient tumor genomes, expanding the repertoire of potential target peptides.
3. Overcoming the speed bottleneck of structure-based MHC-peptide AI predictors. Structure-based predictors are shown to have better generalizability than the popular sequence-base approaches but are limited by their speed[20,26].
4. Enabling 3D model prediction for safer therapies. The ability to predict 3D peptide models in a fraction of second has the potential to screen for tumor peptides distinct from self-peptides on T-cell-exposed surfaces, paving the way for safer and more targeted cancer immunotherapies.

Results

SwiftMHC architecture

The SwiftMHC network utilizes a residue-to-residue attention mechanism to learn to predict BA and structural features based on interactions between neighboring amino acids. (**Fig. 2A**). Specifically, we apply Self Attention networks on MHC structures and peptide sequences, respectively, to update each residue's representations with its neighborhood information. Then we apply cross-attention networks to learn the attention weights between MHC and peptide residues, which are expected to encode the interaction information between the peptide and the MHC. This information is used to predict the 3D models and the BA.

Modelling flexible peptides requires efficient representation of residues and their movement in space. The bond angle between nitrogen (N), alpha carbon (Cα), and carbonyl carbon (C) is relatively fixed due to the constraints imposed by the molecular geometry and electronic structure of these atoms. Following AlphaFold2's approach[15], we model each residue backbone as a rigid-body triangle with the bond angle N-Cα-C of 109°, allowing free rotation and translation in space while reducing the sampling space (**Fig. 2B**). We use unit quaternions to represent the rotations of a peptide residue as they are more efficient and compact than 3×3 rotation matrices (requiring only 4 parameters vs. 9), and offer better numerical stability. Thus the movement of each residue backbone is modeled as a local frame, which encodes the rotation (i.e., a unit quaternion represented as a vector of 4×1) and translation (a 3×1 vector) of each residue relative to a global coordinate system (**Suppl. Mat. Subsection 1.2.1**). Additionally, the peptide bond torsion angle (ω) is typically 180° or 0°, adding rigidity to the backbone (**Fig. 2C**). We take advantage of this with an auxiliary loss on ω along with other structure losses (**Suppl. Mat. Subsection 2.4.3**). See Methods "Computational Efficiency" for additional design choices improving computational efficiency.

Figure 2. SwiftMHC architecture A. Flow diagram of SwiftMHC. The inputs are the MHC protein structure, consisting of r_j residues, and a peptide sequence of r_i residues. The model comprises four key modules: (1) the MHC Self Invariant Point Attention (IPA) module, which processes the MHC structure; (2) the Peptide Self Attention module, which processes the peptide sequence; (3) the Cross Attention Structure module, which captures interactions between MHC and peptide residues; and (4) the BA Predictor module. Residue distances in the MHC structure are encoded in a proximity matrix, calculated as $1 / (1 + d_{ij})$, where d_{ij} is the shortest distance between heavy atoms of residue pairs. The MHC backbone is described using local frames. Both MHC and peptide sequences are represented as one-hot encoded tensors with dimensionality c_s and the structures have maximally n atoms per residue. *(c_s=32 and n=14 in this study).* **B.** Local frames for a peptide composed of five residues. Backbone local frames are sequentially numbered. Triangles mark the atoms involved in determining the frame orientation (N, Cα and C). **C.** The torsion angle representation of a peptide with two residues. Different peptide conformations can be derived by rotating torsion angles. Each torsion angle corresponds to a rigid group. Every residue has a backbone rigid group and several sidechain rigid groups The atoms in the rigid group are repositioned as the torsion angle is modified. The backbone torsion angles are φ, ψ and ω. The ω torsion angles have an empty rigid group, but the rigid groups for φ and ψ both contain one atom, though hydrogens are actually only added in the end and only if OpenMM is used. The side chain torsion angles are χ_1, χ_2, χ_3 and χ_4. Their corresponding rigid groups contain side chain atoms.

The algorithm is structured into four primary modules (**Fig. 2A**).

1. **MHC Self Invariant Point Attention (IPA) Module** (**Algorithm 2** in **Suppl. mat.**): The purpose of this module is to encode each MHC residue based on its amino acid type and its structural neighbors. This module iteratively applies Self Attention to the MHC structure, drawing inspiration from the AlphaFold2 invariant point attention (IPA) technique to make the residues update each other. It was designed to represent and process interactions between amino

acids. For attention weight calculation of each pair of the r_j MHC residues, it utilizes the one-hot-encoded sequence representation of the pairing MHC amino acid types and a r_j x r_j x 1 proximity matrix that captures their geometric distances. These attention weights are used for updating the MHC residue features. Those r_j updated feature vectors are the output of this Self Attention submodule.

2. **Peptide Self Attention Module (Algorithm 3** in **Suppl. mat.)**: The purpose of this module is to encode each peptide residue based on its amino acid type and its sequence neighbors. It applies Self Attention iteratively (twice, can be configured) to the peptide sequence, allowing the r_i residues to be notified of each other by means of residue-to-residue updating. Relative positional encoding was used to provide residue positions to the attention network . Updating allows residues to know their position in the peptide, allowing the network to distinguish between them. This peptide Self Attention submodule outputs a sequence of r_i updated peptide residue feature vectors.

3. **Cross Attention Structure Module (Algorithm 4** in **Suppl. mat.)**: The purpose of this module is to update each peptide residue based on the interaction between it and the MHC residues. The updated peptide encoding is used to predict peptide structure and as input of the BA prediction module. This module iteratively performs cross-attention between the r_i peptide residues and r_j MHC residues, employing a Cross IPA on the previously updated residue feature vectors and their geometric distances. Throughout these iterations, the module not only updates the peptide features but also refines the peptide's structural representation from an initial starting point at the center of the MHC groove. The MHC features are kept fixed in this module. The first step in this structural refinement process is prediction of backbone frames (residue positions + orientations), followed by side-chain torsion angle prediction and finally placement of atoms in the cartesian space.

4. **BA Prediction Module (Algorithm 8** in **Suppl. mat.)**: To allow SwiftMHC to accommodate different peptide lengths, we designed a *residue-wise* BA predictor. The contribution of each residue to BA is predicted by a multi-layer perceptron (MLP), which processes updated peptide residue features produced by the structural module. The end result of the BA predictor is the sum of the MLP outputs over all peptide residues. This BA value is trained to approach 1 - log50000(Kd) or 1 - log50000(IC50), where K_d and IC_{50} are experimentally determined binding constants.

The SwiftMHC network is trained by a loss function with multiple terms on BA, FAPE, torsion angle and other structural violations. (**Suppl. Subsection 2.6**). The *BA loss* quantifies the difference between the predicted and true binding affinities between a peptide and the MHC. *The Frame Aligned Point Error (FAPE)* measures the discrepancy in the positions of peptide atoms (both backbone and side chain) between the true and predicted structures. The *Torsion angle loss* assesses differences in torsion angles between the true and predicted structures. *Structural violations*, which include abnormal bond lengths, bond angles, or atomic clashes, are incorporated only during the fine-tuning phase of training (see Methods and **Suppl. Subsection 3.1***)*.

By default, SwiftMHC predicts BA and 3D models without running OpenMM refinement. For BA predictions, users may skip writing predicted 3D models to disk to avoid performance slowdowns, referred to as SwiftMHC-BA. Alternatively, enabling short OpenMM refinement produces high-quality models, referred to as SwiftMHC-OpenMM.

SwiftMHC archives SOTA-comparable BA Prediction

In this study we focus on HLA-A*02:01, one of the most prevalent MHC alleles, observed in 95.7% of Caucasians and 94.3% of Native Americans[23], and has been extensively studied in clinical trials[3]. Additionally, we focused on 9-mer peptides, the most frequent binding peptide length for MHC class I (MHC-I), as shown in **Suppl. Fig. 1A**.

We assessed the BA prediction performance of SwiftMHC using 7,726 BA data points obtained from IEDB[27] (see Methods). To objectively evaluate SwiftMHC's performance on unseen peptides, we clustered the data into ten groups and conducted leave-one-cluster-out cross-validation (see Methods). Additionally, we compared SwiftMHC with three state-of-the-art prediction methods: MHCflurry[9], AlphaFold2-FineTune[16] and MHCfold[28]. MHCflurry[9] is an ensemble of sequence-based machine learning models, AlphaFold2-FineTune and MHCfold are both DL frameworks that predict structure and BA at the same time (**Table 1**). MHCfold's reliance on side chain modeling and PDB generation may slow processing. For fair comparison with SwiftMHC-BA, these features were disabled during BA evaluation (referred to as "MHCfold-BA").

Comparative evaluation of methods trained and tested on the same datasets ensures fairness by reducing data variability. While MHCflurry was retrained under our experimental conditions, AlphaFold2-FineTune and MHCfold were evaluated using publicly available pretrained models. We did not retrain AlphaFold2-FineTune, because of limited time and computational resources. It is likely that at least some, if not all, of our test cases were included in the training data of these two methods (see **Methods** for details about the data overlap). This overlap could lead to inflated performance results.

We evaluated the performance of the BA predictor using the area under the receiver operating characteristic curve (AUC) as the evaluation metric. To meet the binary classification requirements of AUC, we categorized peptides as binding to their MHC when their ground truth IC_{50} or Kd values were below 500 nanomolar (nM) and as non-binding otherwise.

Table 1. Methods evaluated for BA prediction and structure prediction

Methods	Type	Input	3D modeling	Numerical BA prediction	Binary BA Classification
SwiftMHC	DL-based	MHC structure, peptide sequence	✔	✔	✔
AlphaFold2 -FineTune[16]*	DL-based	pMHC sequence, other pMHC template structures	✔	✔	
MHCfold[28]*	DL-based	pMHC sequence	✔	✔	
PANDORA[12]	physics-based	peptide sequence, MHC allele name/sequence	✔		
Ape-Gen 2.0[13]	physics-based	peptide sequence, MHC allele name	✔		
MHCflurry[9]	DL-based	pMHC sequence		✔	

* These methods were used as provided without retraining on our own defined train-sets, thereby risking train-test contamination and potential inflated performances of those methods.

Our results demonstrate that SwiftMHC reliably predicts MHC-binding peptides with a median of AUC of 0.91, outperforming the three SOTA methods (**Fig. 3A**). Notably, SwiftMHC is among the fastest binding affinity predictors (0.01s/case when the user does not need to write the predicted structures on the hard disk), only slightly slower than the sequence-based method MHCflurry (0.007s) and the structure-based method MHCfold with only BA prediction (0.007s) (**Fig. 3B**). MHCfold-BA, without sidechain modelling, is slightly faster than SwiftMHC, which always predicts sidechains, but shows lower AUC than the other three methods. This reduced BA prediction accuracy may stem from MHCfold's less accurate 3D models (**Fig. 4A**), underscoring the critical role of precise 3D modeling for reliable BA prediction.

A

B

Figure 3. BA prediction quality and speed comparison to SOTA methods. The 7,726 BA data points were separated into 10 clusters. MHCflurry was retrained on the same data as SwiftMHC. The asterisks (*) denote the methods that were not retrained and might have seen the test data. **A.** The box plots display the distribution of the AUC for each of the 10 HLA-A*02:01 9-mer peptide clusters. A perfect model has an AUC of 1, while a model with no discrimination has an AUC of 0.5. The box represents the interquartile range (IQR), which is the range between the first quartile (Q1) and the third quartile (Q3). The line inside the box indicates the median (Q2) of the dataset. The whiskers extend from the box to the smallest and largest values within 1.5 times the IQR from Q1 and Q3, respectively. Data points outside of this range are considered outliers and are marked as circles individually. **B.** The bar plot displays the speed of each of the four methods.

SwiftMHC delivers Angstrom-level accuracy in all-atom pMHC structure prediction with high computational efficiency

We evaluated SwiftMHC and four SOTA methods for modeling 3D pMHC-I structures: AlphaFold2-FineTune[16] (DL-based), MHCfold[28] (DL-based), PANDORA 2.0 (physics-based)[12] and Ape-Gen 2.0 (physics-based)[13] (**Table 1**). The evaluations were performed on 202 HLA-A*02:01 9-mer X-ray structures, which are clustered into 10 clusters based on the peptide sequence similarity (**Suppl. Fig. 1B**). To objectively evaluate the performance of SwiftMHC, we ensured that the X-ray structures and PANDORA 3D models from the same cluster were not included in the training dataset for SwiftMHC.

PANDORA and Ape-Gen 2.0 rely on homology modeling, using X-ray structures as templates to predict new pMHC-I 3D conformations. To ensure unbiased evaluation, we excluded any X-ray structures containing the same peptide to prevent their use as templates by these methods.

SwiftMHC-OpenMM produces highly accurate pMHC-I 3D models with a median Cα-RMSD of 1.19 Å (**Fig. 4A**), comparable to three other state-of-the-art methods (median Cα-RMSD: 0.87–1.21 Å), outperforming MHCfold, which had a median Cα-RMSD of 3.65 Å. Notably, SwiftMHC excels in computational efficiency, processing each case in just 0.9 seconds for raw output (0.01 seconds per case on the BA test sets, excluding PDB file writing) and 2.2 seconds when OpenMM energy minimization is included (**Fig. 4B**).

Outlier analysis. The peptide-binding groove of HLA-A*02:01 has two primary deep pockets, P2 and P9, which are critical for peptide binding and stabilization[29]. With few exceptions (e.g., 2GTW below), the P2 and P9 pockets commonly anchor the 2nd and the 9th residues of the peptide. Most of the 3D models from SwiftMHC have a backbone structure similar to their X-ray counterpart, with common anchor positions 2 and 9 (**Fig. 4C**). The top outlier for SwiftMHC and PANDORA is 2GTW, of which the X-ray structure has anchor positions 1 and 9, but it is predicted with anchor positions 2 and 9 (**Fig. 4D**). Note that, PANDORA uses netMHCpan for anchor prediction, and SwiftMHC, trained on PANDORA models, likely inherits netMHCpan-based prediction errors, affecting its accuracy. MHCfold exhibited a notably higher median Cα-RMSD (3.65Å) compared to the other methods (0.87-1.32Å). Although AlphaFold2-FineTune achieved a low median Cα-RMSD, it produced many outliers, including at least two 3D models in which one end of the peptides was positioned outside the MHC groove (**Fig. 4E**). In contrast, in the top three outlier 3D models generated by Ape-Gen 2.0, the peptide center loop was overly buried within the MHC groove, making it less surface-exposed compared to the corresponding X-ray structures(**Fig. 4F**).

A

Quality of Structure Prediction

peptide Cα RMSD to X-ray (Å)

AlphaFold2-FineTune* — RMSD median: 0.87 Å
MHCfold with MODELLER* — RMSD median: 3.65 Å
PANDORA — RMSD median: 1.21 Å
Ape-Gen 2.0 — RMSD median: 0.74 Å
SwiftMHC — RMSD median: 1.32 Å
SwiftMHC-OpenMM — RMSD median: 1.19 Å

B

Speed of Structure Prediction

seconds per pMHC case

AlphaFold2-FineTune* with MODELLER* 14.7 s
MHCfold 12.4 s
PANDORA 7.1 s
Ape-Gen 2.0 60.3 s
SwiftMHC 0.9 s (0.01 s without saving structures to disk)
SwiftMHC-OpenMM 2.2 s

C. SwiftMHC, average case, Cα-RMSD: 1.19 Å

P2   P9

D. SwiftMHC, outlier, Cα-RMSD: 3.04 Å

E. AlphaFold2-FineTune, outlier, Cα-RMSD: 8.96 Å

F. APE-Gen 2.0, outlier, Cα-RMSD: 4.18 Å

Figure 4. Structural prediction quality and speed assessment on 202 X-ray structures. The 9-mer peptides of 202 HLA-A02:01 X-ray structures were split in 10 clusters and modeled using several methods. AlphaFold2-FineTune and MHCfold are marked with an asterisk (*) as they could not be

retrained and may have seen at least part of our test data resulting in inflated results (see Methods for details about the data overlap). The other methods were employed using a 10-fold cross validation. **A.** Peptide Cα-RMSD values comparing 3D models to X-ray structures. Light blue: DL-based methods. Gray: Physics-based methods. SwiftMHC (with and without OpenMM refinement) performs comparably to SOTA methods. **B.** Average modeling speed per case, measured in batch mode. SwiftMHC achieves 0.01 s/case without outputting structures, processing larger batches from BA data consisting of 7,726 cases total, 533 to 678 cases per cluster, up to 64 cases per batch. With structure output and OpenMM, SwiftMHC achieves 0.9–2.2 s/case reproducing X-ray test data consisting of 202 cases total, 1–57 cases per batch, one batch per cluster. SwiftMHC is the fastest method tested. **C.** Example SwiftMHC model (PDB ID: 1HHK; Cα-RMSD: 1.19 Å), overlaid with its X-ray structure. P2 and P9 anchor residues are labeled. **D.** An exception (PDB ID: 2GTW) where SwiftMHC predicts different anchors than in the X-ray structure, achieving the highest tested Cα-RMSD (3.04 Å). **E.** Outlier by AlphaFold2-FineTune (PDB ID: 3MRG; RMSD: 8.96 Å). N-terminal anchor is incorrect. **F.** Outlier by APE-Gen 2.0 (PDB ID: 2JCC; RMSD: 4.18 Å). The central loop is misaligned, despite correct anchors.

Structural analyses reveal that SwiftMHC-generated 3D models closely approximate the quality of X-ray structures

In addition to RMSD, we assessed model quality by evaluating van der Waals clashes, chirality, and backbone dihedral angles.

Number of van der Waals clashes. The OpenMM energy minimization step in SwiftMHC effectively reduces van der Waals clashes (see definition in Methods), which occur when atoms are positioned too closely. Across the 202 test cases, these reductions are comparable to levels achieved by other methods (**Fig. 5A**), highlighting the importance of a final molecular dynamics step to ensure the physical realism of the 3D models.

Chirality. Chirality in amino acids refers to the property where an amino acid molecule is non-superimposable on its mirror image: L- and D-enantiomers. Chirality plays a crucial role in the structure and function of biomolecules, as the spatial arrangement of groups affects how amino acids interact with other molecules. Except for glycine, amino acids are chiral molecules and the vast majority of amino acids in proteins and enzymes of living organisms are in the L-form. In the 202 test x-ray cases, some amino acids lacked side-chain atoms, which we restored using OpenMM PDBfixer[30]. However, in some instances, PDBfixer introduced D-form amino acids. Since both SwiftMHC and AlphaFold2-FineTune use these structures as input for model generation, we specifically examined D-form amino acids that were introduced in the models (**Table 2**). SwiftMHC maintains chirality by rotating and translating local frames of amino acids, as well as placing the chiral hydrogen before executing OpenMM. As a result, it produced L-form amino acids in the generated peptide structures. However, when OpenMM was used for energy minimization, some L-form amino acids were converted to D-form. APE-Gen 2.0, which also relies on OpenMM, exhibited the same issue and even introduced D-form amino acids in the peptide structure. In contrast, AlphaFold2-FineTune and PANDORA, which do not use OpenMM, did not introduce any D-form amino acids. MHCfold, which predicts individual atomic positions around the chiral Cα atom, introduced a D-form amino acid in one of its models.

Dihedral angles of the peptide backbone. The backbone torsion angles, ϕ (phi) and ψ (psi), define the conformation of a protein's backbone. These angles are constrained by steric clashes, such as repulsions between side-chain atoms or backbone atoms, which limit the range of energetically favorable conformations a protein can adopt. Validating computational 3D protein models includes verifying that the dihedral angles fall within the naturally observed regions of the Ramachandran plot, as deviations can signal errors in the model. To this end, we generated Ramachandran plots for the X-ray structures and the 3D models produced by all six methods (**Fig. 5B** and **Suppl. Fig. 9**). The φ and Ψ torsion angles produced by the DL part of SwiftMHC are restricted to several small areas in the Ramachandran plot (**Fig. 5B**). After energy minimization in OpenMM these angles were more widespread and the SwiftMHC distribution became more closely with that of experimentally determined X-ray structures.

ω torsion angles and Cis/trans configurations. "Trans" and "Cis" refer to the geometric configuration around peptide bonds, specifically involving the arrangement of the atoms adjacent to the peptide bond (the amide bond between the carbonyl carbon of one amino acid and the amide nitrogen of the next). The trans configuration is the most common configuration found in proteins, as it is generally more stable due to less steric hindrance between the side chains of the amino acids. In the trans configuration, the dihedral angle around the peptide bond is approximately 180°.

All five methods generated 3D models in which the ω torsion angles do not correspond to those observed experimentally in the X-ray structures (**Fig. 5C**). For instance, in the case with PDB ID 5SWQ, all methods predict an asparagine-glycine peptide bond with an ω angle ranging from 160.0° to 200.0° (trans), whereas the X-ray structure shows this angle as -0.6° (cis). Similarly, SwiftMHC predicts seven glutamate-proline peptide bonds with ω angles between 160.0° and 200.0° (trans), while the X-ray structures indicate that these angles fall between -20.0° and 20.0° (cis). Notably, OpenMM appears to shift these specific angles outside the trans range, approaching 140°. Furthermore, SwiftMHC predicts nearly all ω angles in the trans conformation, although the energy minimization step in OpenMM slightly alters these angles in some cases. An extreme case is the isoleucine-proline bond in the SwiftMHC 3D model for 5ENW. This ω angle was almost flipped by OpenMM from -178° (trans) to 7° (cis).

Table 2. Methods evaluated for amino acid chirality in predicted structures

Methods	PDBfixed* X-ray structures used as input	OpenMM used	Average number of chiral amino acids per model**	Number of D-amino acids introduced in the MHC	Number of D-amino acids introduced in the peptide
MHCfold with MODELLER			174	1	0
AlphaFold2-FineTune	✔		173	0	0

APE-Gen 2.0	✔	263	22	12
PANDORA		263	0	0
SwiftMHC	✔	174	0	0
SwiftMHC-OpenMM	✔	✔	174	9	0

*OpenMM PDBfixer[30] was used to restore missing side-chain atoms in some of the 202 X-ray structures, which resulted in the introduction of 11 D-form amino acids.

**Some methods model the entire class I MHC protein structure, while others model only the G-domain, leading to differences in the total number of amino acids.

Figure 5. Structural characterizations of SwiftMHC-generated 3D models for the 202 x-ray test cases. A. Distribution of number of clashes and the sum of their van der Waals radii overlaps per 3D model/structure. **B.** Distribution of backbone φ and ψ torsion angles as a Ramachandran plot for both SwiftMHC 3D models and the X-ray structures. **C.** Distribution of the ω peptide bond torsion angle for all 3D models and X-ray structures.

Combined BA and Structural Training Enhance Predictive Performance

We assessed whether the BA data and structural modeling enhance each other's predictive performance. For this, we conducted 10-fold cross-validation with either BA or structural loss terms disabled, measuring the performance of the other. SwiftMHC-openMM was used in this experiment.

We found that the predicted 3D models deviated significantly more from their corresponding X-ray structures when BA losses were excluded from training (**Fig. 6A**). Many models showed errors, particularly in modeling peptide anchor positions, where this did not happen when BA loss was included in the training (**Fig. 6C**). Additionally, when SwiftMHC was trained without structural loss terms (i.e.,FAPE, torsion, bond length violations, bond angle violations and clashes), the quality of BA predictions was substantially reduced, with the median AUC dropping from 0.91 to 0.72 (**Fig. 6B**). These findings demonstrate that the experimentally determined BA data and the predicted structural models complement each other, enhancing their combined predictive performance.

Figure 6. The impact of structural and BA loss terms on structural or BA prediction performance. A. The quality of SwiftMHC-generated OpenMM-refined 3D models for regular training vs. training without BA loss, illustrating the BA data enhanced the 3D model quality. *Note that the 3D model for PDB entry 1BD2 is missing from the set of 3D models created without BA loss, as this particular model was structurally compromised to the extent that OpenMM could not successfully perform energy minimization. **B.** BA prediction performance for regular training vs. training without structural losses, showing PANDORA models enhanced the accuracy of BA prediction. **C.** An example case (PDB ID: 5MER) to show the models generated by regular training (left) vs. training w/o the BA data (right) . Green: SwiftMHC 3D models refined by OpenMM; White: X-ray structures. Without the BA loss in the training, SwiftMHC failed to generate correct anchors for the peptide (right panel, peptide Cα-RMSD: 4.66 Å), while with regular training it can generate realistic peptide conformation (left panel, peptide Cα-RMSD: 1.15 Å). Anchor positions 2 (P2) and 9 (P9) are labeled.

Discussion

We introduce SwiftMHC, an attention-based neural network for the rapid and accurate identification of MHC-bound peptides and predicts their structures. SwiftMHC delivers high-resolution 3D models with a median Cα-RMSD of 1.19 Å, with a remarkable efficiency by processing each case in just 0.01 to 2.2 seconds in batch mode on a single A100 GPU. Operating up to 1200 times faster than current state-of-the-art modeling methods, including an AlphaFold-based approach (**Fig. 3B**), SwiftMHC effectively overcomes the speed bottleneck of structure-based binding affinity (BA) predictors while maintaining exceptional accuracy in both BA prediction and 3D modeling. This proof-of-concept study focuses on HLA-A*0201 9-mers, a relatively simple case for sequence-based predictors. Expanding the training set to include additional alleles is expected to enhance SwiftMHC's generalizability, matching the reported 5–11% over sequence-based methods[20]. As the fastest pMHC-I structure predictor, SwiftMHC facilitates large-scale peptide screening for vaccine development and immunotherapy research. Its high efficiency enhances the ability to identify novel neoantigens from the diverse range of tumor-derived peptide fragments, while providing detailed 3D models for studying molecular interactions and T-cell recognition. Furthermore, SwiftMHC's speed offers the potential to construct the first comprehensive 3D self-peptide-HLA (human MHC) library. Such a library could be pivotal for identifying TCR-therapy peptide targets that differ from self-peptides on T-cell-exposed surfaces, ultimately contributing to the development of safer and more effective therapeutic strategies.

The speed and reliability of SwiftMHC is attributed to two key innovations: removing the computationally demanding MSA attention module—since MHC structures are conserved and peptides lack evolutionary information—and incorporating physics-derived pMHC-I 3D models into training. While the AI industry often focuses on large, general-purpose models like AlphaFold3[14], training these models requires vast amounts of data, which is resource-intensive and energy-draining. Additionally, the complexity of training large neural networks makes them difficult to optimize, leading to high energy consumption during both training and inference. In contrast, we demonstrate that smaller networks like SwiftMHC, when augmented with extensive task-specific, physics-based synthetic data, can overcome these challenges. This approach achieves superior efficiency without compromising accuracy.

Lastly, while optimized for pMHC complexes, our SwiftMHC strategy can be adapted for broader applications, including protein-peptide interactions and CDR3 loop modeling for antibody-antigen and TCR:pMHC-I complexes. The flexibility and the lack of evolutionary signal of peptides and CDR3 loops pose significant challenges for accurate modeling, even for advanced methods like AlphaFold[31]. Capturing peptide and CDR3 conformational changes upon binding is critical for advancing therapeutic TCR and antibody design and improving our understanding of immune recognition and defense.

Model Limitations

This proof-of-concept study has several limitations. First, SwiftMHC is currently restricted to HLA-A*02:01 9-mer peptides. However, its algorithm is designed to easily incorporate training sets for additional alleles and peptides of varying lengths.

Second, for computational efficiency, we choose to design SwiftMHC to use fixed MHC orientations not allowing random orientation options. This limitation could be addressed by redesigning the network to incorporate rotation-translation equivariance, such as using backbone frames based on the MHC protein's intrinsic orientation rather than identity frames.

Third, SwiftMHC does not yet account for peptides with post-translational modifications (PTMs) such as phosphorylation, glycosylation, methylation, and acetylation. Addressing this would require training on datasets with sufficient examples of PTM-modified structures. While SwiftMHC cannot currently model PTMs directly, it can generate reasonable starting conformations for downstream molecular dynamics (MD) simulations of modified peptides.

Finally, the speed evaluation of our study was conducted using a maximum batch size of 64 pMHC cases, optimized for large datasets (~8000 cases, as in the BA test datasets) that efficiently filled most batches. However, SwiftMHC's efficiency may decline when processing very small datasets with only a handful of cases per batch. Additionally, the impact of software initialization time, which may reduce efficiency for smaller datasets, was not explored.Further investigation into time consumption for larger datasets could offer additional insights into its performance efficiency.

Methods

Data composition

In this study, we focus on HLA-A*02:01 alleles and 9-mer peptides. For this, 7,726 BA data points were collected from IEDB[27] and 202 X-ray structures were collected from the PDB[11]. OpenMM PDBfixer[30] was used to fill in missing heavy atoms in these X-ray structures in cases where a residue was incomplete. To critically evaluate the generalizability of our predictor and to prevent data leakage, BA and X-ray data were merged together and Gibbs clustered[32] based on their peptide sequences. This was performed using GibbsCluster 2.0, with a cluster similarity penalty (λ) set to 0.8 and a small cluster weight (σ) set to 5. The data points were separated into 10 clusters, each of which was used for testing SwiftMHC using a leave-one-cluster-out cross-validation principle (**Suppl. Fig. 1B**).

From the left-out cluster of each fold, the BA data points were used to evaluate the BA prediction quality, while the X-ray structures from that same cluster were used for evaluating structure prediction quality. The BA data points of the remaining 9 clusters were used for training (90% of data) and validation (10%). X-ray crystallographic data were excluded from the training and validation datasets to assess the network's 3D modeling performance when trained solely on physics-based 3D model data, though including X-ray data would likely enhance our performance.

Since SwiftMHC requires structural data for training, we generated 3D models for each pMHC-I complex in the BA dataset using PANDORA. For each pMHC-I complex, the 3D model with the lowest molecular probability density function score (molpdf) energy score was selected to be used as input to SwiftMHC.

Data Preprocessing

SwiftMHC gradually updates the peptide structure from identity frames (**Suppl. Algorithm 4**), that is, the starting positions of all peptide residues are at the origin and their N-Cα-C plane overlaps so that they all have the same orientation. This design requires all input structural data in the same orientation, so we superimposed the pMHC-I complex of all X-ray structures and PANDORA 3D models on a reference MHC structure (PDB ID: 3MRD) before training and testing. The reference structure was prepared by isolating the G-domain and placing the geometric center of the MHC binding groove at the origin. All other structures or PANDORA 3D models were structurally aligned to this reference using the PyMOL align command[33] with its default settings: 2.0 Å as outlier rejection cutoff, 5 outlier rejection cycles and using BLOSUM62 for sequence alignment.

Additionally, some values were pre-calculated from the aligned pMHC-I structures, so that SwiftMHC can quickly access them. Those variables were: *ground truth frames*, *ground truth torsion angles*, *MHC proximity matrix*, *peptide and MHC amino acid sequences*, *residue masks* and *ground truth BA*. See **Suppl. Subsection 1.2** for details about these variables.

Software and libraries used

SwiftMHC was developed using Python 3.12 (www.python.org) and implemented with the PyTorch 2.0.1 library[34] for deep learning functionalities. OpenFold 1.0.0[35] was utilized for key tasks such as FAPE and torsion loss calculations, deriving frames from atomic coordinates, reconstructing atomic coordinates from predicted frames, and performing frame operations. The design of SwiftMHC's IPA modules was also partially inspired by OpenFold code. For handling PDB files, BioPython 1.8.4[36] was employed for parsing and representation. Structural refinements were performed using OpenMM 8.1.1[30].

Training

Ten SwiftMHC network models were trained for each of the 10 peptide clusters, using 10 distinct training datasets. Training consisted of two phases (**Suppl. Subsection 3.1**): the first phase takes a maximum of 1000 epochs and back propagates on loss terms, based on BA regression and amino acid similarity between true and predicted peptide structure. The second phase takes a maximum of 100 epochs and includes additional loss terms, based on bond length, bond angle and interatomic distance violations (**Suppl. Subsection 2.6**).

During training, both phases were executed for each network model. An early stopping condition was applied, allowing a phase to terminate early if the total loss on the validation dataset ceased to improve (**Suppl. Section 3.2**). The network model

with the lowest total loss on the validation dataset in the first phase was selected to be the initial model in the next phase.

Post Processing the Resulting Structures

Once a pMHC-I structure is predicted and PDB to disk writing is enabled, SwiftMHC by default runs OpenMM[30] to minimize its energy using an amber99sb force field. To prevent chirality issues in non-glycine backbones, the hydrogen atom attached to the chiral Cα atom is added by SwiftMHC before running OpenMM. All other hydrogen atoms are added by OpenMM.

Computational Efficiency

For speed purposes, several design choices were made for SwiftMHC. Since the MHC structure remains fixed, its backbone frames and distance matrix can be precalculated and reused throughout the prediction process. This avoids repeated computations. The preprocessed data was stored in an HDF5 file format to facilitate quick access and efficient data management. For an efficient cross attention computation, MHC residues that do not lie close to the peptide are masked out, meaning that they do not contribute to any operation in that module (**Suppl. Fig. 3**). PDB structures are generally only written to disk on demand and never during training. In addition, we replaced the traditional 3x3 rotation matrix operations with quaternion operations, reducing numerical computations and improving efficiency.

The *time consumption* of executing a fully trained SwiftMHC network model was measured on a single NVIDIA A100 GPU (40 GiB HBM2 memory with 5 active memory stacks per GPU) and 32 Intel Xeon Platinum 8360Y CPUs and 16 x 32 GiB 3.2 GHz DDR4 memory available. We made SwiftMHC allocate 16 worker processes to read input data and 16 builder processes to write out structural data in PDB format. For comparing speed, SOTA methods were executed on the same hardware configuration as SwiftMHC. We measured the exact time duration of every method to complete with one-hundredth of a second precision.

SOTA methods

We compared SwiftMHC against several SOTA methods (**Table 1**) on BA prediction and/or structure prediction qualities. Four methods were compared for their speed and BA prediction quality: SwiftMHC, AlphaFold2-FineTune[16], MHCflurry[9] and MHCfold[28]. The AUC was used as a BA quality metric. We classified a peptide as binding to its MHC if IC_{50} or K_d was below 500 nM and as non-binding otherwise. Six methods were compared for reproducing the 202 X-ray structures: SwiftMHC, SwiftMHC-OpenMM, AlphaFold2-FineTune[16], PANDORA[12], APE-Gen 2.0[13] and MHCfold[28]. For comparing speed, all SOTA methods were executed on the same hardware configuration as SwiftMHC.

AlphaFold2-FineTune is a modified version of AlphaFold2, where the weights and biases of the network model have been fine-tuned using pMHC BA and X-ray pMHC structural data. AlphaFold2-FineTune achieves faster processing times than standard AlphaFold2 by omitting template searching and multiple sequence alignments.

Instead, it requires the user to provide a query-to-template alignment. A second reason for the increased speed of AlphaFold2-FineTune compared to the standard AlphaFold2 tool is that it does not refine its output structures using an Amber forcefield in OpenMM, which is typically employed for energy minimization in the standard AlphaFold2 pipeline.

We used the 202 X-ray HLA-A*02:01 9-mer structures as templates for AlphaFold2-FineTune. For selecting templates, the Gibbs clustering was used. This means that for each target peptide from a specific cluster, the pMHC-I X-ray structures from the other nine clusters were selected as the template set. To create MHC alignments as input for AlphaFold2-FineTune, the target G-domain MHC sequences were aligned to the template MHC sequences using the BioPython pairwise alignment tool[36] with default settings (Needleman-Wunsch algorithm, match score 1, mismatch score 0, gap scores 0). For peptide alignment, the 9-mer peptides were aligned in a one-to-one manner (i.e., position one aligned with position one, position two with position two, and so on). Other components of the X-ray structures, such as β2-microglobulin and the α3 domain, were excluded from the alignments. The time to make these alignments was not included in the computation time of AlphaFold2-FineTune. The quality of structural predictions was assessed by comparing the 202 X-ray HLA-A*02:01 9-mer structures against 3D models predicted by AlphaFold2-FineTune. The total runtime required to process these 202 entries was documented.

To assess the quality of BA predictions, we compared 7,726 experimental BA values against predictions generated by AlphaFold2-FineTune. Due to redundancy in the pMHC-I sequences (sometimes there are multiple BA values per complex) and the computational demands of running AlphaFold2-FineTune, we ran AlphaFold2-FineTune on the 6,057 non-redundant data. The total runtime required to process these 6,057 entries was documented. This evaluation aimed to measure AlphaFold2-FineTune's ability to differentiate true binders (experimental K_d or IC_{50} < 500 nM) from true non-binders, following a similar approach to that described in [16]. For each pMHC-I entry, the negative mean of the MHC-to-peptide and peptide-to-MHC position-aligned error (PAE) values was used as a predictive score. These scores were compared with experimental BA values to calculate the AUC for each cluster. The prediction scores that correspond to the repeated sequence entries were replicated, ensuring each experimental BA value was compared to its corresponding prediction score.

MHCfold[28] is a deep learning tool that first predicts the structures of both the peptide and the MHC molecule from their sequences using convolutional neural networks (CNNs). It then employs a modified version of multi-headed attention along with a structure-derived distance matrix, similar to IPA, to predict BA as either binding or non-binding. To evaluate the BA and structural prediction quality of the MHCfold algorithm, we used the MHC G-domain sequences along with corresponding peptide sequences as inputs. For this MHCfold was set to predict BA only, excluding structure generation. We used MHCfold to predict BA for all 7,726 data points and calculated the AUC based on the predictions. The total runtime was measured. Additionally, MHCfold was used to generate pMHC structures for all 202 X-ray complexes. For

this. MHCfold was set to predict both the 3D structure and BA and to use MODELLER for reconstructing the side chains. The total runtime for creating the 202 3D models, including the time required for MODELLER, was measured. The resulting 3D models were subsequently evaluated.

PANDORA is a 3D modeling approach, specialized to predict the structure of pMHC complexes for both class I and II. It does so by using a database of MHC templates and a multiple sequence alignment of their conserved domains. It uses homology modeling to build the model and keeps the peptide's anchors restrained. To evaluate the performance of PANDORA[12] structure predictions, we made it generate pMHC-I 3D models for each of the 202 available X-ray structures. PANDORA was configured to output 20 3D models per case (the default setting) and the 3D model with the lowest molpdf score was selected. To prevent data leakage, templates containing peptides identical to those in the target 3D model were excluded from the 3D modeling process. To properly measure the process time consumption, PANDORA was executed within a multiprocessing pool configuration with 32 cores. The total processing time required for the pool to complete all 202 3D models was recorded.

ApeGen 2.0 is a tool that generates an ensemble of peptide-MHC conformations within a chosen number of iterations. In each iteration, it first searches the Protein Data Bank (PDB) for a suitable MHC template, then anchors the atoms of the first and last two residues of the given peptide as in the template. Between these anchor positions, it samples for peptide backbone conformations that geometrically fit best using Random Coordinate Descent (RCD)[37]. On the resulting backbone conformations, OpenMM PDBFixer[30] samples for side chains to complete the structure. Finally SMINA[38] energy minimization is performed on both the peptide and MHC to fix steric clashes. The best resulting structure may be used as input for the next iteration.

To evaluate the structure prediction performance of APE-Gen 2.0[13], we employed this software to 3D model the pMHC complex for each of the 202 available X-ray structures. APE-Gen 2.0 was set to output 20 3D models per case (the default setting) and the 3D model with the lowest APE-Gen 2.0 Affinity score was selected. To prevent data leakage, templates containing identical peptides to those in the target 3D model were excluded from the set. By default, an APE-Gen 2.0 process runs in a Docker container, using 8 CPU cores to pool the RCD and SMINA computations. For comparing APE-Gen 2.0's runtime with other SOTA methods on the same software and hardware settings, we ran APE-Gen 2.0 outside a Docker container as a single process with 32 cores. The total processing time for APE-Gen 2.0 to generate all 202 3D models was recorded. These resulting 3D models were subsequently evaluated.

MHCflurry[9] is a SOTA sequence-based BA predictor which consists of an ensemble of MLPs. We retrained MHCflurry on our 7,726 BA data points by a 10-fold leave-one-cluster-out cross-validation approach for each of the 10 peptide clusters (**Suppl. Fig. 1B**). The retraining process was carried out using the allele-specific scripts, provided by MHCflurry. In each iteration, one cluster was held out as the test set, while the remaining nine clusters were used to create a training set (90%) and a network model selection set (10%). The selected network models were subsequently

used to predict BA for the peptides from the remaining cluster. The predicted BA values from MHCflurry were compared to experimental BA values (binding or non-binding) by calculating AUC. The processing time was measured.

The training data overlap between AlphaFold2-FineTune, MHCfold and our test data

We did not retrain AlphaFold2-FineTune, because of limited time and computational resources. Instead, we utilized a pretrained network model obtained from the publicly available source (https://files.ipd.uw.edu/pub/alphafold_finetune_motmaen_pnas_2023/datasets_alphafold_finetune_v2_2023-02-20.tgz). We identified that 10 (5%) of the 202 X-ray structures in our test set were part of AlphaFold2-FineTune's training dataset. Moreover, AlphaFold2-FineTune was fine-tuned from the AlphaFold2 model, which had been trained on PDB entries deposited before the 30th of April 2018[16], which dates after the deposition date of 164 of our 202 X-ray structures. Therefore it is likely that these structures were included in AlphaFold2's training dataset.

MHCfold could not be retrained for this evaluation due to the absence of a training script. Therefore, we utilized the pretrained network model available from the public source (https://github.com/dina-lab3D/MHCfold/blob/main/v7_date_5_9_2022.zip) to generate MHCfold predictions for the evaluation. For structural prediction, this model was trained on PDB entries deposited before November of 2021 with resolution higher than 3.5 Å [28]. This includes 200 of our 202 X-ray structures and therefore it is likely that these structures were included in MHCfold's training dataset.

For BA prediction, both the AlphaFold2-FineTune and MHCfold models were reportedly trained on the netMHCpan training set[16,28] which incorporates pMHC binding data from the IEDB. Since our datasets were also derived from the IEDB, it is plausible that some, if not all, of our test data was included in the training sets of these two pretrained models.

These overlaps could have inflated the results of AlphaFold2-FineTune and MHCfold.

Evaluation of Structure Prediction

To calculate *Cα-RMSD*, all the 3D models were superposed in ProFit[39] to the MHC G-domains of the corresponding X-ray structures. To account for structural variations, the two most N-terminal residues were omitted from the G-domain superposition due to their absence in some structures. Similarly, the C-terminal residue was excluded from the superposition analysis because its orientation varies significantly across different X-ray structures. The remaining portion of the HLA-A*02:01 sequence, encompassing the amino acids (IMGT numbering 3-179) was utilized for superposition. ProFit was used to calculate RMSD for the peptide Cα atoms to quantify the differences between the predicted 3D models and their corresponding X-ray structures. This analysis was performed for each 3D model across all methods to identify which 3D models exhibited the greatest similarity to their respective X-ray counterparts.

Chiralities were determined per amino acid from the positions of the N, C and C□ atoms around the Cα atoms using Numpy.

Ramachandran plots were generated by calculating the backbone ψ and φ torsion angles for each residue in the peptide using BioPython[36].

ω *torsion angles* of the peptide typically approximate 180°. To verify this, the angles were calculated for each peptide bond across all 3D structures using NumPy[40]. The distributions of ω angles from the predicted 3D models and the X-ray structures were plotted to identify any differences.

Van der Waals clashes are considered energetically unfavorable and should be minimal. To identify overlaps between the van der Waals radii of non-bonded atom pairs in the peptide, the distances between atoms in the 3D structures were calculated using NumPy[40]. A clash was defined as occurring when two atomic centers were closer than the sum of their van der Waals radii, with exceptions made for 1) protons for which the position is usually determined by calculation, not prediction; 2) for atoms within the same residue, as those are usually either part of a ring system or connected to each other with zero, one or two atoms in between; 3) for the backbone atoms of two connected residues; 4) two connected residues where one is proline, of which the side chain is connected to the backbone; 5) two cysteines that can be disulfide bonded. Any other pair of atoms that were positioned too close to each other was considered clashing. The number and severity of clashes were compared across all 3D models.

Data availability

The trained SwiftMHC network and related datasets (including PANDORA 3D models, BA data, torsion angles, clash counts, chiralities, RMSD and BA predictions) will be accessible on Zenodo with a DOI upon acceptance of the manuscript for publication.

Code availability

The code for data preprocessing, training, evaluation, and prediction is available at https://github.com/X-lab-3D/swiftmhc.

Author contributions

CB: Design and Development of the software. Running Experiments. Writing the manuscript. GC: Manuscript review and editing. DR: Manuscript review and editing and consultation on deep learning-related questions. David: Manuscript review, editing and testing the code. YA: Manuscript review and editing, examine possible chirality problems in AlphaFold3-generated models. LX: Design and supervise the project. Manuscript review and editing. All authors have reviewed and edited this manuscript.

Declaration of generative AI and AI-assisted technologies in the writing process

During the preparation of this work the author(s) used ChatGPT (https://chatgpt.com) in order to improve the writing style. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the content of the publication.

Acknowledgement

This project was supported by the Hanarth Fonds, the Kika foundation (grant number 454) and NWO-XS (OCENW.XS23.2.130). The computation was partly supported by the NVIDIA Academic Grant Program. We thank SurfSara for their generous GPU and CPU computing resources (grant numbers EINF2380, EINF-10427 and EINF-11930). We also thank Dario Marzella for providing the dataset and helpful discussions.

References

1. Bagchi, S., Yuan, R. & Engleman, E. G. Immune Checkpoint Inhibitors for the Treatment of Cancer: Clinical Impact and Mechanisms of Response and Resistance. *Annu. Rev. Pathol. Mech. Dis.* **16**, 223–249 (2021).

2. Johnson, D. B., Nebhan, C. A., Moslehi, J. J. & Balko, J. M. Immune-checkpoint inhibitors: long-term implications of toxicity. *Nat. Rev. Clin. Oncol.* **19**, 254–267 (2022).

3. Baulu, E., Gardet, C., Chuvin, N. & Depil, S. TCR-engineered T cell therapy in solid tumors: State of the art and perspectives. *Sci. Adv.* **9**, eadf3700 (2023).

4. Barker, D. J. *et al.* The IPD-IMGT/HLA Database. *Nucleic Acids Res.* **51**, D1053–D1060 (2023).

5. Purcell, A. W., Ramarathinam, S. H. & Ternette, N. Mass spectrometry–based identification of MHC-bound peptides for immunopeptidomics. *Nat. Protoc.* **14**, 1687–1707 (2019).

6. Nielsen, M., Andreatta, M., Peters, B. & Buus, S. Immunoinformatics: Predicting Peptide–MHC Binding. *Annu. Rev. Biomed. Data Sci.* **3**, 191–215 (2020).

7. Antunes, D. A., Abella, J. R., Devaurs, D., Rigo, M. M. & Kavraki, L. E. Structure-based Methods for Binding Mode and Binding Affinity Prediction for Peptide-MHC Complexes. *Curr. Top. Med. Chem.* **18**, 2239–2255 (2019).

8. Lin, M. J. *et al.* Cancer vaccines: the next immunotherapy frontier. *Nat. Cancer* **3**, 911–926 (2022).

9. O'Donnell, T. J., Rubinsteyn, A. & Laserson, U. MHCflurry 2.0: Improved Pan-Allele Prediction of MHC Class I-Presented Peptides by Incorporating Antigen Processing. *Cell Syst.* **11**, 42-48.e7 (2020).

10. Reynisson, B., Alvarez, B., Paul, S., Peters, B. & Nielsen, M. NetMHCpan-4.1 and NetMHCIIpan-4.0: improved predictions of MHC antigen presentation by concurrent motif deconvolution and integration of MS MHC eluted ligand data. *Nucleic Acids Res.* **48**, W449–W454 (2020).

11. Burley, S. K. *et al.* RCSB Protein Data Bank: Celebrating 50 years of the PDB with new tools for understanding and visualizing biological macromolecules in 3D. *Protein Sci.* **31**, 187–208 (2022).

12. Parizi, F. M. *et al.* PANDORA v2.0: Benchmarking peptide-MHC II models and software improvements. *Front. Immunol.* **14**, 1285899 (2023).

13. Abella, J. R., Antunes, D. A., Clementi, C. & Kavraki, L. E. APE-Gen: A Fast Method for Generating Ensembles of Bound Peptide-MHC Conformations. *Molecules* **24**, 881 (2019).

14. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **630**, 493–500 (2024).

15. Jumper, John. Highly accurate protein structure prediction with AlphaFold. *nature* (2021).

16. Motmaen, A. *et al.* Peptide-binding specificity prediction using fine-tuned protein structure prediction networks. *Proc. Natl. Acad. Sci.* **120**, e2216697120 (2023).

17. Mikhaylov, V. *et al.* Accurate modeling of peptide-MHC structures with AlphaFold. *Structure* **32**, 228-241.e4 (2024).

18. Benjamin Webb & Andrej Sali. Protein Structure Modeling with MODELLER. in *functional genomics* vol. 1654 39–54 (2017).

19. Krivov, G. G., Shapovalov, M. V. & Dunbrack, R. L. Improved prediction of

protein side‑chain conformations with SCWRL4. *Proteins Struct. Funct. Bioinforma.* **77**, 778–795 (2009).

20. Marzella, D. F. *et al.* Improving generalizability for MHC-I binding peptide predictions through geometric deep learning. Preprint at https://doi.org/10.1101/2023.12.04.569776 (2023).

21. Sievers, F. & Higgins, D. G. Clustal Omega. *Curr. Protoc. Bioinforma.* **48**, (2014).

22. Hekkelman, M. L. & Vriend, G. MRS: a fast and compact retrieval system for biological data. *Nucleic Acids Res.* **33**, W766–W769 (2005).

23. Ellis, J. M. *et al.* Frequencies of HLA-A2 alleles in five U.S. population groups. *Hum. Immunol.* **61**, 334–340 (2000).

24. Cao, K. *et al.* Analysis of the frequencies of HLA-A, B, and C alleles and haplotypes in the five major ethnic groups of the United States reveals high levels of diversity in these loci and contrasting distribution patterns in these populations. *Hum. Immunol.* **62**, 1009–1030 (2001).

25. Ayed, K., Ayed‑Jendoubi, S., Sfar, I., Labonne, M. ‑P. & Gebuhrer, L. HLA class‑I and HLA class‑II phenotypic, gene and haplotypic frequencies in Tunisians by using molecular typing data. *Tissue Antigens* **64**, 520–532 (2004).

26. Moon, S., Zhung, W. & Kim, W. Y. Toward generalizable structure‑based deep learning models for protein–ligand interaction prediction: Challenges and strategies. *WIREs Comput. Mol. Sci.* **14**, e1705 (2024).

27. Vita, R. *et al.* The Immune Epitope Database (IEDB): 2018 update. *Nucleic Acids Res.* **47**, D339–D343 (2019).

28. Aronson, A., Hochner, T., Cohen, T. & Schneidman-Duhovny, D. Structure modeling and specificity of peptide-MHC class I interactions using geometric deep learning. Preprint at https://doi.org/10.1101/2022.12.15.520566 (2022).

29. Zhang, C., Anderson, A. & DeLisi, C. Structural principles that govern the peptide-binding motifs of class I MHC molecules. *J. Mol. Biol.* **281**, 929–947

(1998).

30. Eastman, P. *et al.* OpenMM 7: Rapid development of high performance algorithms for molecular dynamics. *PLOS Comput. Biol.* **13**, e1005659 (2017).

31. Yin, R. & Pierce, B. G. Evaluation of ALPHAFOLD antibody–antigen modeling with implications for improving predictive accuracy. *Protein Sci.* **33**, e4865 (2024).

32. Andreatta, M., Alvarez, B. & Nielsen, M. GibbsCluster: unsupervised clustering and alignment of peptide sequences. *Nucleic Acids Res.* **45**, W458–W463 (2017).

33. WL DeLano. Pymol: An open-source molecular graphics tool. (2002).

34. Imambi, S., Prakash, K. B. & Kanagachidambaresan, G. R. PyTorch. in *Programming with TensorFlow* (eds. Prakash, K. B. & Kanagachidambaresan, G. R.) 87–104 (Springer International Publishing, Cham, 2021). doi:10.1007/978-3-030-57077-4_10.

35. Ahdritz, G. *et al.* OpenFold: Retraining AlphaFold2 yields new insights into its learning mechanisms and capacity for generalization. Preprint at https://doi.org/10.1101/2022.11.20.517210 (2022).

36. Chapman, B. & Chang, J. Biopython: Python tools for computational biology. *ACM SIGBIO Newsl.* **20**, 15–19 (2000).

37. Chys, P. & Chacón, P. Random Coordinate Descent with Spinor-matrices and Geometric Filters for Efficient Loop Closure. *J. Chem. Theory Comput.* **9**, 1821–1829 (2013).

38. Koes, D. R., Baumgartner, M. P. & Camacho, C. J. Lessons Learned in Empirical Scoring with smina from the CSAR 2011 Benchmarking Exercise. *J. Chem. Inf. Model.* **53**, 1893–1904 (2013).

39. Martin, Andrew CR, and Craig T. Porter. ProFit. University College London; Prof Andrew C. R. Martin's group (2009).

40. Harris, C. R. *et al.* Array programming with NumPy. *Nature* **585**, 357–362 (2020).