PAPER

Benchmarking Data Leakage on Link Prediction in Biomedical Knowledge Graph Embeddings

Galadriel Brière,[1,*] Thomas Stosskopf,[1,2] Benjamin Loire[1,3] and Anaïs Baudot[1,4,*]

[1]Aix Marseille Univ, INSERM, MMG, Marseille, France, [2]Present address: Aix Marseille Univ, INSERM, TAGC, Marseille, France, [3]Servier IRIS, Saclay, France and [4]CNRS, Marseille, France

[*]Corresponding author. marie-galadriel.briere@univ-amu.fr, anais.baudot@univ-amu.fr

Abstract

In recent years, Knowledge Graphs (KGs) have gained significant attention for their ability to organize complex biomedical knowledge into entities and relationships. Knowledge Graph Embedding (KGE) models facilitate efficient exploration of KGs by learning compact data representations. These models are increasingly applied to biomedical KGs for link prediction, for instance to uncover new therapeutic uses for existing drugs.

While numerous KGE models have been developed and benchmarked for link prediction, existing evaluations often overlook the critical issue of data leakage. Data leakage leads the model to learn patterns it would not encounter when deployed in real-world settings, artificially inflating performance metrics and compromising the overall validity of benchmark results. In machine learning, data leakage can arise when (1) there is inadequate separation between training and test sets, (2) the model leverages illegitimate features, or (3) the test set does not accurately reflect real-world inference scenarios.

In this study, we implement a systematic procedure to control train-test separation for KGE-based link prediction and demonstrate its impact on models' performance. In addition, through permutation experiments, we investigate the potential use of node degree as an illegitimate predictive feature, finding no evidence of such leveraging. Finally, by evaluating KGE models on a curated dataset of rare disease drug indications, we demonstrate that performance metrics achieved on real-world drug repurposing tasks are substantially worse than those obtained on drug-disease indications sampled from the KG.

Key words: Knowledge Graph Embedding, Data Leakage, Link Prediction, Drug Repurposing, Rare Diseases

Introduction

Biomedical knowledge encompasses diverse associations across multiple scales of biological organization. At the *molecular level*, biomolecules such as genes, proteins, or metabolites are organized into networks that capture intricate biomolecular interactions, such as gene regulatory networks, protein–protein interaction (PPI) networks or metabolic pathways. These molecular networks are further structured at the *cellular level*, where they coordinate functions within and across cell populations. At the *tissue and organ levels*, interactions between cell populations and tissues play a key role in regulating physiological processes. At the *clinical level*, relationships between diseases, phenotypes, and therapeutic compounds reflect shared pathophysiological properties. Biomedical knowledge also encompasses domain-specific ontologies such as the Gene Ontology (1) or the Human Phenotype Ontology (2), which provide standardized terminologies and hierarchical organizations for this complex, heterogeneous biological knowledge. Taken altogether, this large-scale and heterogeneous domain knowledge coalesce into Knowledge Graphs (KGs), which represent entities and their relationships using triples in the form $(head, relation, tail)$. KGs provide an intuitive and unified representation of multi-scale biological knowledge.

By combining the structured knowledge stored in KGs with Machine Learning (ML) approaches, Knowledge Graph Embedding (KGE) methods encode entities and relations into continuous, low-dimensional latent vector spaces while preserving the fundamental structural, topological, and semantic characteristics of KGs. These latent representations facilitate data exploration and enable efficient inference of novel interactions (3), a task known as link prediction.

Drug repurposing, which involves finding new therapeutic uses for existing drugs, stands out as a critical application of link prediction where KGE can have a significant impact (4). By leveraging the ability of KGE to predict novel drug–disease associations and drug–target interactions, researchers can identify potential drug candidates more efficiently, reducing the time and cost associated with traditional drug discovery processes.

Despite the significant potential of KGE-based link prediction in biomedicine, challenges remain in evaluating the reliability and generalizability of these models. One key issue is data leakage. Data leakage can artificially inflate any ML predictor performance and undermine the validity of the evaluation process. Data leakage is defined as "*the relationship between (i) the reported performance scores of an ML-based predictor, (ii) the data used to train or validate the predictor, (iii) the data used to generate the reported performances of the ML-based predictor and (iv) the data on which the ML-based predictor should be run at inference time once it is deployed in its intended use case*" (5; 6).

Data leakage can be caused by multiple mechanisms. First, improper split of KG triples can result in data redundancy and dependencies between training and test sets, compromising the separation required between these datasets. *Akrami et al.* (7) demonstrated this issue through the study of widely-used non-biomedical benchmark KGs (*FB15k*, *WN18*, and *YAGO3-10*). Their findings revealed that eliminating these redundancies caused a significant decrease in the reported performance of the KGE models. The authors concluded that, under realistic conditions, KGE models do not provide an effective solution for the task of link prediction.

Second, ML models may exploit illegitimate features as proxies for prediction. This phenomenon has been observed in the context of sequence-based PPI prediction using deep learning models (8). In this study, the authors showed that prediction performance could be driven by features unintentionally exposed to the model during training, such as node degree in the PPI network, rather than the actual protein sequences the models were intended to learn from. By randomizing the training PPI network via degree-preserving network permutations, they demonstrated that the models retained significant predictive power despite the absence of biologically meaningful edges. This experiment highlighted the model reliance on topological shortcuts rather than on biologically relevant features. Such exploitation of illegitimate features has not specifically been demonstrated in KGE approaches. However, in theory, in KGE, access to the graph structure encoded through the set of triples can enable models to rely on properties such as node degree as shortcuts for predicting novel links. This highlights the importance of investigating whether KGE models rely on such structural properties for their prediction, as failing to do so may lead to overestimating their true predictive capabilities.

Finally, data leakage can occur when the training and test data share similar data distributions, which differ from the distribution of inference data encountered at model deployment. This type of leakage often stems from sampling bias, where test data are not representative of the distribution encountered during inference, leading to inflated performance metrics that fail to reflect the model's actual deployment capabilities (5). In a KG, entities may exhibit varying levels of connectivity, with some entities having numerous documented interactions and others having only sparse connections. When test triples are sampled randomly from the KG, their entity connectivity distribution is likely to mirror that of the training data. However, at deployment, inference might involve entities with connectivity patterns that differ significantly from those observed in the training set. This potential discrepancy motivates the need to evaluate model performance under conditions that reflect realistic inference scenarios.

To the best of our knowledge, existing benchmarks for biomedical KG analysis have not examined data leakage issues thoroughly. Some benchmarks implemented measures to mitigate contamination of the test set by redundancies with the training set. For instance, (9) ensured that known reverse relations, such as "is_a" and "is_a_reverse," were allocated within the same split. In another example, (10) proposed an evaluation protocol based on "cold-start" triples, which ensured that the models were evaluated on entirely new and unseen combinations of entities and relations. Similarly, (11) presented an evaluation framework termed "free-setting", in which all triples involving the relation to be predicted were removed from the training set. Lastly, (12) highlighted potential biases in inferring links for underrepresented entities in biomedical KGs, but these biases were not empirically assessed for their impact on model performance. Overall, while these efforts addressed certain aspects of data leakage, they did not systematically identify and mitigate the full range of leakage sources. Addressing this gap is essential for improving the robustness and reliability of models and benchmarks in the biomedical domain.

In this study, we propose strategies to systematically evaluate the impact of the three sources of data leakage described in (5). Our framework intends to enable comprehensive assessments of KGE models' performance under controlled data leakage conditions, with particular emphasis on drug repurposing scenarios. We develop specific experimental protocols for evaluating each source of data leakage:

- **Data Leakage 1 (DL1): Inadequate Separation of Training and Test Sets.** We propose a procedure to eliminate dependencies between training and test datasets. We then assess the effect of this data leakage mitigation procedure on KGE model performance by comparing the results obtained on datasets with and without proper train-test split. By comparing performance metrics, we can quantify the artificial inflation of the evaluation results caused by data dependency between the training and test sets.
- **Data Leakage 2 (DL2): Use of Illegitimate Features.** We investigate whether KGE models use node degree as a proxy feature for prediction. To test this, we compare models' performance between two scenarios: using the original dataset and a permuted version where drug-disease indications are randomly shuffled while maintaining each node's original degree. This comparison enables us to quantify the influence of node degree as an illegitimate feature.
- **Data Leakage 3 (DL3): Non-Representative Test Sets.** We obtain a curated dataset of drug indications for rare diseases from the Orphanet database (13) and use these indications as an inference set to simulate real-world deployment. By comparing models' performance between this inference set and the standard test set of drug-disease indications sampled from the KG, we assess the models' capacities to generalize to infer drug repurposing opportunities for rare diseases.

Material and Methods

Definitions

Knowledge Graph and Knowledge Graph Embedding

A Knowledge Graph (KG) is a directed multi-relational graph, where entities and their relationships are represented as triples (h, r, t). In this representation, h and t are the head and tail entities, while r is the directed relation connecting them.

Knowledge Graph Embeddings (KGE) models encode entities and relations from a KG into continuous vector spaces

that capture latent patterns in the KG, facilitating downstream tasks such as link prediction. The embeddings are learned by comparing the scores of positive and negative triples, with negative triples generated through a process called Negative Sampling. A detailed formalization of KG and KGE within the encoder-decoder framework is available in the Supplementary Material.

Link prediction task

In the link prediction task, the goal is to complete a missing triple within the KG. Specifically, link prediction aims to predict either t in $(h, r, ?)$ or h in $(?, r, t)$. Each KGE model employs its own scoring function, which is used to quantify the plausibility of a triple (h, r, t). During evaluation, given a head h (resp. tail t) and a relation r, the decoder evaluates all possible candidates for the tail t (resp. head h) and ranks them based on the scores. The highest-ranked entity can then be selected to complete the triple, thus allowing the inference of missing links in the KG.

Training, Test, and Inference Sets

In this study, we define the following sets of triples:

- *Training Set:* The training set refers to the collection of triples used during the model training phase. In practice, this set is composed of two subsets: the training subset, which is directly used for optimizing the model parameters, and the validation subset, which is used to tune hyperparameters and prevent overfitting. For simplicity, we collectively refer to these subsets as the training set.
- *Test Set:* The test set consists of triples that were set aside and hidden during the training phase. For each triple in the test set, either the head or tail entity is masked, and the model's ability to rank the correct entity among all possible entities is evaluated.
- *Inference Set:* In real-world deployment, an inference set would consist of incomplete triples in which either the head or tail entity is unknown and needs to be predicted. Here, we leverage a dataset containing known drug-rare disease indications curated from Orphanet (Orphan Drug Indications). We use this dataset as an inference set with a ground-truth to evaluate the performance of the models. We expect this analysis to reflect realistic drug repurposing applications for rare diseases.

Data

Knowledge Graph

We used ShepherdKG, a biomedical KG dedicated to rare disease diagnosis (14). This KG was derived from PrimeKG (15), a KG developed for precision medicine applications, and includes additional knowledge from Orphanet (13), a comprehensive database for rare diseases. ShepherdKG contains 10 entity types and 30 relationship types (Supplementary Tables S1 and S2). The KG dataset was divided as follows: 90% of the triples were assigned to the training set (including 10% of the triples reserved as the validation subset); the remaining 10% of the triples were allocated to the test set.

Orphan Drug Indications

To create the inference set, we obtained access to Orphanet's (13) dataset of Orphan drugs indicated for rare diseases, comprising 4915 drug-rare disease associations. Of these, 829 associations involved drug and disease entities present in the ShepherdKG. These 829 associations were retained as the

inference set. The majority of the excluded associations involve gene therapies, which are entities not included in ShepherdKG, explaining the significant reduction. Among the 829 retained drug-disease associations, 164 were already included in ShepherdKG and were removed from the KG to ensure they were only present in the inference dataset.

Models and Implementation

Models

We used the TorchKGE Python library (16), which proposes implementations for several state-of-the-art KGE models. We investigated two types of KGE models, namely translational models (TransE (17) and TransD (18)) and bilinear models (RESCAL (19), DistMult (20), ANALOGY (21), ComplEx (22), and HolE (23)). Translational models represent relations as transformations in the embedding space, typically aiming to capture the relationship between entities through geometric operations like translations or rotations in the embedding space. In contrast, bilinear models use multiplicative interactions between embeddings, often through tensor operations (24).

Negative Sampling

Three negative sampling strategies are implemented in TorchKGE:

- In *Uniform Negative Sampling*, either the head or the tail of a triple is replaced with a randomly selected entity, following a uniform probability distribution across all entities in the KG;
- In *Bernoulli Negative Sampling*, the likelihood of replacing the head or tail of a triple depends on the mapping characteristics of the relation (i.e., one-to-many, many-to-one or many-to-many), aiming to minimize the generation of false negatives (25);
- In *Positional Negative Sampling*, the head or tail entity is replaced by an entity sampled from the set of entities that have already appeared at the same position (i.e., head or tail) in a triple involving the same relation. This strategy has the advantage of producing more realistic negative triples than Uniform Negative Sampling (26).

To take advantage of each negative sampling approach, we implemented a strategy that generates multiple types of negative triples for each positive triple. For each positive triple, we generated five negative triples using Uniform Negative Sampling, five negative triples using Bernoulli Negative Sampling, and one negative triple using Positional Negative Sampling.

Evaluation metrics

To evaluate the models on link prediction tasks on the validation set (i.e. the subset of the training set), test set, and inference set, we used the filtered Mean Reciprocal Rank (MRR), a metric that measures the quality of ranked predictions by assessing the position of the first correct entity among all candidates ranked by the decoder. Higher MRR values indicate better performance, reflecting the model's effectiveness in prioritizing correct links.

Model Training

All models were trained using PyTorch (27) and PyTorch-Ignite (28) libraries. The training process employed the Adam optimizer, configured with a learning rate of 0.001 and a weight decay of 0.001. All models were trained with an embedding dimension of 200 for both entities and relations, and a batch size

of 4096. For translational models, we used the Margin Loss with the margin set to 1. For bilinear models, we used the Binary Cross-Entropy Loss. All models were trained in two settings:

- **Short training**: Models were evaluated every 20 epochs on the validation set using the MRR metric. Early stopping was triggered if the validation MRR did not improve for 10 consecutive evaluations (i.e., 20 × 10 epochs), with training limited to a maximum of 500 epochs. The model with the highest validation MRR during training was saved for testing.
- **Long training**: Identical to short training, but with the patience parameter extended to 20 evaluations (i.e., 20 × 20 epochs), and training limited to a maximum of 1000 epochs.

For all experiments, we reported the best MRR of the two trainings on the test set.

Hardware and computational environment

All experiments were conducted on the Jean Zay supercomputer using a single NVIDIA V100 GPU with 32 GB of memory.

DL1 - Inadequate Separation of Training and Test Sets

In KGE-based link prediction tasks, dependencies between training and test sets due to inadequate data separation (called here Data Leakage 1, DL1) can arise from two distinct scenarios, as described by *Akrami et al.* (7).

First, when splitting the dataset into training and test sets, overlapping information between the splits may go undetected. This happens when the KG contains semantically related relations, known as near-duplicate or near-reverse-duplicate relations (7). For example, in a biomedical KG, relations like "(protein)-binds to-(protein)" and "(protein)-interacts with-(protein)" can be considered *near-duplicates* as they convey similar meanings. Similarly, reverse relations, such as "(drug)-inhibits-(protein)" and "(protein)-is inhibited by-(drug)" can be considered as *near-reverse-duplicates* as they convey symmetric semantic meanings. When these semantically related relations are randomly distributed across training and test sets without proper control, they create unwanted information leakage. Overall, failing to identify and account for semantically redundant relations can compromise the separation of the training and test data. As proposed by *Akrami et al.*, semantically redundant relations can be detected by investigating whether, for two given relations, the heads and tails overlap exceeds predefined thresholds θ_1 and θ_2. These two thresholds account for asymmetric redundancy, where one relation may be redundant with respect to another without implying mutual redundancy (7). The complete mathematical formulation of this redundancy detection process is described in the Supplementary Materials (Equations S1 and S2).

Second, the KG may include *Cartesian product* relations, in which a large proportion of possible head-tail entity pairs are connected. In a biomedical KG, an example of such Cartesian product relation could be "(gene)-expressed in-(cell type)" for ubiquitously expressed genes (i.e. housekeeping genes). Cartesian product relationships can be identified by comparing the number of observed connections between the heads and tails covered by the relation with the total number of possible connections, and determining whether this proportion exceeds a predefined threshold θ (7). The specific mathematical formulation for this identification is provided in the Supplementary Materials (Equation S3).

DL1 Detection and Control Procedure

In order to detect and control DL1, we designed a preprocessing procedure to identify semantically redundant and Cartesian product relations within the KG, and ensure appropriate separation between training and test sets. This protocol is divided into several steps described below.

Step 1: Filtering Reverse Triples For every relationship type r, if a triple (a, r, b) exists in the KG, its reverse triple (b, r, a) is removed from the KG. This step addresses cases where the same relation r is used in both directions, which can be problematic since some KGE models (such as TransE and TransD) cannot encode symmetric relationships, while others (like DistMult) inherently impose symmetry on all relations. For undirected relationships, triple directionality is handled separately in Step 3 of this procedure.

Step 2: Identifying Semantically Redundant and Cartesian Product Relations For every possible pair of relations (r_1, r_2), we compute their semantic redundancy to identify near-duplicate and near-reverse-duplicate relations, using thresholds θ_1 and θ_2 set to 0.8. Additionally, for every relationship r, Cartesian product relations are identified using a threshold θ set to 0.8. Relations identified as semantically redundant are flagged for subsequent processing.

Step 3: Handling Directionality for Undirected Relations While most KGE models operate on directed triples, biomedical KGs often contain inherently undirected relationships. To accommodate these undirected interactions in our models, we systematically generate reverse triples with a new relation name. For any undirected relation r, we add a reverse counterpart r_{rev}. Specifically, for every triple (a, r, b), we add (b, r_{rev}, a). Because r and r_{rev} convey the same semantic information, the pair (r, r_{rev}) is flagged and added to the list of semantically redundant relations identified in Step 2.

Step 4: KG Split with Controlled Train-Test Separation At this stage, semantically redundant relations and Cartesian product relations have been identified and flagged. The KG is split into training and test sets, with the following considerations:

- For semantically redundant relations flagged in Step 2, as well as relationships made directed by the addition of their reverse in Step 3, redundant triples are removed from the training set. Specifically, for any triple placed in the validation or test set, its redundant counterparts are excluded from the training set.
- For Cartesian product relations flagged in Step 2, we ensure that all triples involving a given head (or tail) with the Cartesian relation r are placed in the same split.

Evaluation of DL1

To evaluate the impact of DL1 on KGE model performance, we compared link prediction results obtained on ShepherdKG with and without the application of the DL1 detection and control procedure described above. To create the dataset with DL1, steps 1 to 3 of the DL1 detection and control procedure were applied, but instead of using step 4's controlled splitting procedure, the data was randomly split into training and test sets. To create the dataset without DL1, the full DL1 detection and control procedure was applied, including step 4, thereby ensuring proper train-test separation.

For both datasets, KGE models were trained using the same hyperparameters and evaluation metrics for consistency. Link prediction performance was measured for the prediction of all

relations (i.e., global performance), for the prediction of relations flagged in the DL1 detection and control procedure (i.e., performance on semantically redundant and Cartesian product relations), and for the prediction of the indication relation, which connects drugs to their indicated diseases.

DL2 - Investigating Node Degree as an Illegitimate Predictive Feature

To evaluate whether KGE models rely on node degree as an illegitimate feature for predicting new links (called here Data Leakage 2, DL2), we designed a permutation experiment. The underlying rationale is that if models utilize node degree as a predictive shortcut rather than learning meaningful semantic patterns, their performance should remain relatively stable when connections are randomized while preserving entity degrees. Formally, for a given relation r, we randomly permuted the tail entities while preserving the degrees of the heads and tails. Specifically, for a relation r connecting the set of heads H and the set of tails T, each tail in a triple is replaced by selecting a new entity randomly from the set T.

For this experiment, we used the ShepherdKG where DL1 had been controlled using the DL1 detection and control procedure described in DL1 Detection and Control Procedure. The permutation was applied to the indication relation between steps 3 and 4 of the DL1 detection and control pipeline. We compared the performance of KGE models trained on the permuted versus original version of the KG.

DL3 - The Test Set is not Representative of the Inference Set

To investigate the presence and impact of a dependency between the training and test sets that would not naturally occur between the training and inference sets (called here Data Leakage 3, DL3) in the context of drug repurposing, we compared KGE models' performance in predicting drug indications from the test set and from the inference set. We trained models on ShepherdKG where DL1 had been controlled through the DL1 detection and control procedure described in DL1 Detection and Control Procedure, then evaluated their prediction performance on a test set randomly sampled from the KG drug indications and on an inference set composed of curated orphan drug indications described in Orphan Drug Indications. This setup allowed us to evaluate whether models trained and evaluated on drug indications from ShepherdKG can generalize to predict orphan drug indications.

Availability

The ShepherdKG used in this study is available at https://zitniklab.hms.harvard.edu/projects/SHEPHERD/.

The dataset of orphan drugs is available upon request from Orphanet at https://www.orphadata.com/samples/.

All code and results are openly available on GitHub at https://github.com/galadrielbriere/drug_repurposing_kge_benchmark. The repository provides both the implementation to reproduce the results obtained in this study and a reusable framework for assessing data leakage in any KG, including the DL1 detection and control procedure, the permutation procedure, and the complete models and training implementations.

Results

Experiment 1: Assessing the Impact of Training-Test Set Separation (DL1) on Model Performance

Existing benchmarks on biomedical KGs using similar KGE models and reporting MRR values show MRR ranging from 0.1 (corresponding to an average rank of 10) (12) to 0.8 (corresponding to an average rank of 1.25) (9). This large range in performance may stem from differences in KG structure and model training protocols. However, DL1 (i.e., improper separation of training and test data) has not been systematically investigated in these benchmarks, leaving open the question of whether data leakage contributes to these observed performance disparities.

To assess the impact of DL1 on model performance, we trained and evaluated seven KGE models (Material and Methods) on two variants of ShepherdKG: the ShepherdKG where only the steps 1 and 3 of the DL1 detection and control procedure (Material and Methods) were applied, followed by random train-test splitting (i.e., KG with DL1), and the ShepherdKG where all four steps of the DL1 detection and control procedure were applied to ensure proper train-test separation (i.e., KG without DL1).

The application of the DL1 detection and control procedure on the ShepherdKG resulted in the removal of $1,336,637$ reverse triples at Step 1. Most of these removed triples ($1,336,314$) were drug-drug relations, as for every $(h, \text{drug-drug}, t)$, the reverse triple $(t, \text{drug-drug}, h)$ was also included in the KG. At Step 2, we did not identify any semantically redundant or Cartesian product relations (using θ_1, θ_2, and θ set to 0.8). Because most KGE models consider directed relations, three undirected relations were made directed at Step 3: drug-drug similarity ($drug\_drug$ relation), disease-disease similarity ($disease\_disease$ relation), and protein-protein interactions ($protein\_protein$ relation). For these relations, the reverse was included with a different relation name (e.g., $drug\_drug\_rev$) to avoid introducing symmetric relationships. Including these reverse triples creates a semantic redundancy in the KG, which was removed at Step 4 of the DL1 detection and control procedure for the KG controlling for data leakage but retained for the KG where data leakage was not controlled.

Our results reveal that an inadequate separation of training and test data inflated the performance metrics, as measured by global MRR (Figure 1-a), for the ANALOGY, ComplEx, and HolE models. The impact was most pronounced for ComplEx, where the presence of DL1 increased MRR from 0.302 to 0.377 (a 24.9% increase), followed by ANALOGY with an increase from 0.305 to 0.364 (a 19.5% increase). HolE showed a smaller increase from 0.234 to 0.261 (an 11.4% increase).

In contrast, we did not observe differences in the performances of RESCAL, DistMult, TransE, and TransD with or without DL1 control. However, despite their apparent insensitivity to DL1, DistMult, TransE, and TransD consistently underperformed regardless of whether DL1 was controlled or not, with MRR values below 0.15. This MRR corresponds to an average rank of the correct triple being approximately 7. On the other hand, ANALOGY, ComplEx, HolE, and RESCAL achieved better results even in the absence of DL1, with MRR values of at least 0.25, corresponding to an average rank of the correct triple being approximately 4. We hypothesize that the apparent insensitivity of DistMult, TransE, and TransD to DL1 control might be due to their limited capacity to capture complex patterns in the data. Indeed, both DistMult and TransE

Figure 1. Impact of Training-Test Set Separation on KGE Model Performance (DL1). **(a)** Global MRR: performance of the models across all relations in the test set. **(b)** MRR for Redundant Relations: Model performance on the relations identified by the DL1 detection and control procedure as requiring special handling during train-test separation. **(c)** MRR for the Indication Relation: Model performance on drug-disease indications. Performance shown with (red) and without (blue) DL1.

were evaluated in Akrami et al.'s study (7), and were found to be impacted by DL1. However, the KG considered in our study, with approximately 5.5 million triples, is substantially larger than the non-biomedical KGs evaluated in Akrami's study, containing between 150000 and 1 million triples. This might indicate that in our study, these models reached a performance plateau relatively early, potentially making them less sensitive to DL1 control.

The relatively strong performance of RESCAL with or without DL1 control suggests that this model might be less impacted by DL1 compared to other high-performing methods. RESCAL computes embeddings through tensor factorization, capturing global relationships between entities (29). This collective learning mechanism might reduce the tendency to overfit specific patterns in the training data, thereby mitigating the effects of data leakage.

In addition to analyzing the global MRR, which considers all the KG's relations, we compute the MRR for relations that were semantically redundant between the training and test sets. These semantically redundant relations are causing DL1 (Figure 1-b). For these relations, the gap between the reported performance of models trained with and without DL1 was even more pronounced, as expected. For ANALOGY, ComplEx, and HolE, the MRR increased by 42%, 45%, and 16%, respectively, in the presence of DL1. RESCAL, however, continued to report nearly equal MRR values across the two settings, similar to its performance for the global MRR. DistMult, TransE, and TransD showed poor performances, regardless of the presence of DL1, with MRR values below 0.1.

These results clearly indicate that some KGE models are sensitive to DL1, and that the top-performing models are particularly affected. Indeed, our findings highlight the significant impact of DL1 on the evaluation of KGE models, particularly for semantically redundant relations, where its presence can lead to artificially high evaluation metrics. These findings underscore the critical importance of controlling DL1 during model evaluation.

In addition, we wondered whether DL1-affected relations could potentially help the prediction of non-DL1 affected relations. Specifically, the indication relation between drugs and diseases is not semantically redundant in the KG (i.e. is not affected by DL1). We tested if the presence of DL1-affected relations in the KG might, in some way, assist in predicting the non-DL1 affected drug-disease indication triples. The

results in Figure 1-c are inconclusive. The prediction performance is overall low in all models, reaching 0.2 at best. For the indication relation, ANALOGY showed worse predictions in the presence of DL1, while no clear impact of DL1 was observed on the performance of the other models. These results suggest that introducing semantic redundancy through DL1, in addition to compromising the reliability of model evaluation, does not provide any consistent benefits for predicting non-redundant relations like drug-disease indications.

Experiment 2: Investigating Node Degree as an Illegitimate Predictive Feature (DL2)

A second potential source of data leakage we examined is the use of node degree as an illegitimate feature. To test this data leakage source in the context of the prediction of drug-disease indications, we designed an experiment in which the indication triples in the KG were permuted while preserving the original degree of entities (Material and Methods). Our hypothesis is that if the models rely on node degree as an illegitimate feature, the MRR for the indication relations should remain similar between models trained on the original and on the permuted KGs.

Our results, presented in Figure 2, indicate that the models did not rely on node degree as a predictive feature. Indeed, models trained on the KG with permuted indication triples exhibited significantly poorer predictive performance for this relation as compared to models trained on the original KG. However, permuting the indication triples did not affect model performance on predicting other types of relations, as the global MRR is similar (Supplementary Figure S1). These findings suggest that the indication relation does not provide information used by the models to predict other types of relationships.

Experiment 3: Evaluating the Reliability of Test Set Performance as an Indicator of Inference Performance (DL3)

The reliability and utility of the performance metrics obtained on the test set depends on how well the test set represents real-world inference scenarios. Since test sets are typically sampled from the same KG as the training data, they inherently share similar statistical properties with the training set. However, at

MRR for the Indication Relation

Figure 2. Assessment of node degree exploitation as an illegitimate feature (DL2) in drug-disease indication prediction. Comparison of MRR between original indication triples (blue) and permuted indication triples with preserved node degrees (red).

deployment time, the models might encounter entities and relationships with substantially different characteristics compared to those observed during training and evaluation.

We examine whether evaluating models on test data randomly sampled from the same KG as the training data provides reliable performance indicators for real-world drug repurposing inference. To do so, we compare the performance of the models obtained on the test set and on an inference set of rare disease indications from Orphanet (13) (Orphan Drug Indications).

The results, shown in Figure 3-a, indicate that while the best-performing models achieved MRRs around 0.2 on the test set, their performance on the inference set is close to 0. The best-performing model on the inference set, RESCAL, achieved an MRR of only 0.01, corresponding to an average rank of 100 for the correct predictions.

To understand the reasons behind such poor generalization on the inference dataset, we analyzed the connectivity patterns of drug and disease entities. For each entity belonging to either the test or the inference set, we computed the number of indication relations it participates in in the training set.

We found that, as shown in Figure 3-b, drugs and diseases from the test set have significantly higher numbers of known indications in the training set as compared to drugs and diseases from the inference set.

We further investigated whether drugs with a higher number of indications in the training set were predicted more accurately than those with fewer indications. The test set was partitioned into two groups: drugs with more than 10 indications in the training set (592 test drugs) and drugs with 10 or fewer indications in the training set (254 test drugs). The results, displayed in Figure 3-c, show that, across all models, drugs with more frequent indications in the training set were predicted more accurately than drugs with 10 and fewer known indications.

Our experimental results demonstrate significant limitations of current KGE models for drug repositioning applications. While these models achieve reasonable performance on the test set, their predictive capabilities exhibit a strong dependence on the number of known drug indications in the training data.

The models systematically underperform when predicting indications for drugs with a few number of known indications and show particularly poor generalization to rare disease applications. The reliance on a high number of known indications to predict new drug repositioning opportunities for a given drug severely limits the models' practical applicability, as the identification of novel indications for less-studied drugs and diseases represents a critical need. These findings expose a significant inconsistency between model performance as measured by conventional evaluation procedures and actual inference capabilities in a real-world drug repositioning scenario.

Discussion

Data leakage poses a critical challenge in the evaluation of KGE models, as it can lead to inflated performance metrics that do not reflect real-world applicability. In this study, we systematically assessed the impact of three sources of data leakage on the performance of popular KGE models for link prediction in a biomedical KG. Our findings highlight the necessity of systematically identifying and mitigating different sources of data leakage to ensure a realistic assessment of model performance. As KGE models remain largely black boxes, transparent reporting of measures to address data leakage is crucial to improve the reliability and reproducibility of KGE-based link prediction. We advocate for the adoption of standardized practices to evaluate and mitigate data leakage, not only in KGE studies but also in the broader machine learning community.

In our first experiment, we demonstrated that improper separation between training and test triples can result in artificially inflated performance metrics, which fail to reflect the true capabilities of models obtained when DL1 is controlled. This underscores the importance of adopting consistent and transparent evaluation protocols across studies. In this study, we developed and implemented a systematic protocol for detecting and controlling DL1 when performing link prediction tasks. We make this protocol publicly available to the research community and encourage its adoption to ensure robust evaluation of KGE models. Additionally, we identified specific challenges related to undirected relations in KGs. Indeed, the conversion of undirected relations to directed relations through the inclusion of reverse relationship, which is necessary because most KGE models operate exclusively on directed relations, can introduce data leakage issues. While thorough cleaning of the training set as we proposed here can mitigate redundancy caused by reverse relations, optimal strategies for handling undirected relations remain an open question. Further investigations are needed to determine whether treating undirected triples as directed in their original orientation or including reverse relations with controlled redundancy yields superior results.

Our second experiment, dedicated to investigating whether KGE models use node degree as an illegitimate feature for their predictions, did not find evidence of node degree being used as a proxy. However, this does not rule out the possibility that other illegitimate features might be exploited by the models and remain to be identified. For instance, one potential area for further investigation is the role of community structure within the KG. Community structure, characterized by densely connected subgraphs, could implicitly provide shortcuts for predictions, allowing models to rely only on local graph topology rather than true semantic generalization. Exploring to which extent KGE models might be biased by such structural features would be an important next step to better understand their true capabilities.

Figure 3. Test Set and Inference Set Comparisons (DL3) **(a)** MRR comparison between test set indications (blue) and inference set indications (pink). **(b)** Distribution of the number of training set indications (shown on a logarithmic scale) for drugs and diseases across test and inference sets. Statistical significance was assessed using the Mann-Whitney-Wilcoxon test (two-sided). Annotations indicate significance levels: **** ($P \leq 1 \times 10^{-4}$). **(c)** MRR comparison between drugs with frequent (> 10 indications, dark blue) versus sparse (≤ 10 indications, light blue) indications in the training set.

In our third experiment, we demonstrated that models performing well on the test set, split from the initial KG, failed to generalize to an unrelated inference dataset corresponding to a real-world drug repurposing inference scenario in rare diseases. This generalization gap was further demonstrated by our analysis of prediction performance stratified by drug indication frequencies in the training data, which revealed significantly better performance for drugs with more than 10 known indications. This frequency-dependent performance pattern suggests fundamental limitations in the models' ability to generalize beyond well-characterized entities. A compelling direction for investigation would be to analyze the topological distances between the drug and disease entities predicted by the models and those present in the training data. For drugs (resp. diseases) with numerous known indications, we hypothesize that the models may predominantly predict diseases (resp. drugs) that are closely connected within the KG structure to the drug's (resp. diseases's) known indications from the training set. Such a pattern would suggest that the models' generalization capacity is constrained to predicting drug and disease candidates within close neighborhoods, rather than identifying drug repurposing opportunities that bridge distant regions of the KG. As future work, we plan to explore strategies such as (i) limiting the number of indication examples in the training set, (ii)

excluding drugs or diseases with known indications in the training data from the test set, or (iii) systematically withholding entire disease categories (e.g., cancers or metabolic diseases) from training to evaluate the models' predictive performance exclusively on these held-out classes. Such systematic evaluations would help establish more robust frameworks for assessing generalization capabilities in drug repurposing applications.

We also aim to extend our experiments to include other popular KGE models, particularly deep learning-based approaches such as Graph Neural Networks (30; 31). While these models are known for strong performance and generalization, their reliance on neighborhood aggregation could amplify data leakage by propagating redundant information. Investigating their behavior under controlled scenarios would help clarify whether their generalization holds in real-world settings or is influenced by structural biases in the data. To facilitate such investigations, we have extended our framework by implementing an integration between TorchKGE decoders and PyTorch Geometric (32) encoders. This enables researchers to systematically evaluate data leakage while exploring advanced neural architectures. The extended framework is publicly available through our GitHub repository (Availability).

Competing interests

No competing interest is declared.

Author contributions statement

G.B. and A.B. conceived the study. G.B. implemented, conducted the experiments, and analyzed the results. T.S. developed the proof of concept for the study. B.L. reviewed and contributed to the implementation. A.B. supervised the project. G.B. and A.B. wrote the manuscript. All authors reviewed and approved the final manuscript.

Acknowledgments

This work was supported by MarMaRa (Marseille Maladies Rares), the French National Research Agency through the CA-MUDI project (ANR-21-CE45-0001), and the European Rare Diseases Research Alliance (ERDERA). This project was provided with computer and storage resources by GENCI at IDRIS thanks to the grant 2024-AD010315786 on the supercomputer Jean Zay's V100 and A100 partition. We acknowledge Orphanet and INSERM for providing the dataset of orphan drugs used in this study. We thank Elias Ventre for his thorough manuscript review and valuable scientific input.

References

1. The Gene Ontology Consortium *et al.*, "The gene ontology knowledgebase in 2023," *Genetics*, vol. 224, no. 1, 2023.
2. S. Köhler *et al.*, "The human phenotype ontology in 2021," *Nucleic acids research*, vol. 49, no. D1, pp. D1207–D1217, 2021.
3. Z. Chen *et al.*, "Knowledge graph completion: A review," *Ieee Access*, vol. 8, pp. 192 435–192 456, 2020.
4. D. N. Sosa *et al.*, "Contexts and contradictions: a roadmap for computational drug repurposing with knowledge inference," *Briefings in bioinformatics*, vol. 23, no. 4, p. bbac268, 2022.
5. J. Bernett *et al.*, "Guiding questions to avoid data leakage in biological machine learning applications," *Nature Methods*, vol. 21, no. 8, pp. 1444–1453, 2024.
6. S. Kaufman *et al.*, "Leakage in data mining: Formulation, detection, and avoidance," *ACM Transactions on Knowledge Discovery from Data (TKDD)*, vol. 6, no. 4, pp. 1–21, 2012.
7. F. Akrami *et al.*, "Realistic re-evaluation of knowledge graph completion methods: An experimental study," in *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*, 2020, pp. 1995–2010.
8. J. Bernett *et al.*, "Cracking the black box of deep sequence-based protein–protein interaction prediction," *Briefings in Bioinformatics*, vol. 25, no. 2, p. bbae076, 2024.
9. D. Chang *et al.*, "Benchmark and best practices for biomedical knowledge graph embeddings," in *Proceedings of the conference. Association for Computational Linguistics. Meeting*, vol. 2020. NIH Public Access, 2020, p. 167.
10. R. Celebi *et al.*, "Evaluation of knowledge graph embedding approaches for drug-drug interaction prediction in realistic settings," *BMC bioinformatics*, vol. 20, pp. 1–14, 2019.
11. M. Alshahrani *et al.*, "Application and evaluation of knowledge graph embeddings in biomedical data," *PeerJ Computer Science*, vol. 7, p. e341, 2021.
12. S. Zheng *et al.*, "Pharmkg: a dedicated knowledge graph benchmark for bomedical data mining," *Briefings in bioinformatics*, vol. 22, no. 4, p. bbaa344, 2021.
13. S. Pavan *et al.*, "Clinical practice guidelines for rare diseases: the orphanet database," *PloS one*, vol. 12, no. 1, p. e0170365, 2017.
14. E. Alsentzer *et al.*, "Few shot learning for phenotype-driven diagnosis of patients with rare genetic diseases," *medRxiv*, 2024.
15. P. Chandak *et al.*, "Building a knowledge graph to enable precision medicine," *Scientific Data*, vol. 10, no. 1, p. 67, 2023.
16. A. Boschin, "Torchkge: Knowledge graph embedding in python and pytorch," in *International Workshop on Knowledge Graph: Mining Knowledge Graph for Deep Insights*, Aug 2020.
17. A. Bordes *et al.*, "Translating embeddings for modeling multi-relational data," *Advances in neural information processing systems*, vol. 26, 2013.
18. G. Ji *et al.*, "Knowledge graph embedding via dynamic mapping matrix," in *Proceedings of the 53rd annual meeting of the association for computational linguistics and the 7th international joint conference on natural language processing (volume 1: Long papers)*, 2015, pp. 687–696.
19. M. Nickel *et al.*, "A three-way model for collective learning on multi-relational data." in *Icml*, vol. 11, no. 10.5555, 2011, pp. 3 104 482–3 104 584.
20. B. Yang, Yih *et al.*, "Embedding entities and relations for learning and inference in knowledge bases," *arXiv preprint arXiv:1412.6575*, 2014.
21. H. Liu *et al.*, "Analogical inference for multi-relational embeddings," in *International conference on machine learning*. PMLR, 2017, pp. 2168–2178.
22. T. Trouillon *et al.*, "Complex embeddings for simple link prediction," in *International conference on machine learning*. PMLR, 2016, pp. 2071–2080.
23. M. Nickel *et al.*, "Holographic embeddings of knowledge graphs," in *Proceedings of the AAAI conference on artificial intelligence*, vol. 30, no. 1, 2016.
24. T. Shen *et al.*, "A comprehensive overview of knowledge graph completion," *Knowledge-Based Systems*, vol. 255, p. 109597, 2022.
25. Z. Wang *et al.*, "Knowledge graph embedding by translating on hyperplanes," in *Proceedings of the AAAI conference on artificial intelligence*, vol. 28, no. 1, 2014.
26. R. Socher *et al.*, "Reasoning with neural tensor networks for knowledge base completion," *Advances in neural information processing systems*, vol. 26, 2013.
27. A. Paszke *et al.*, "Automatic differentiation in pytorch," 2017.
28. V. Fomin *et al.*, "High-level library to help with training neural networks in pytorch," https://github.com/pytorch/ignite, 2020.
29. D. Krompaß *et al.*, "Non-negative tensor factorization with rescal," in *Tensor Methods for Machine Learning, ECML workshop*, 2013, pp. 1–10.
30. T. N. Kipf *et al.*, "Semi-supervised classification with graph convolutional networks," *arXiv preprint arXiv:1609.02907*, 2016.
31. P. Velickovic *et al.*, "Graph attention networks," *stat*, vol. 1050, no. 20, pp. 10–48 550, 2017.
32. M. Fey *et al.*, "Fast graph representation learning with PyTorch Geometric," in *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.