RegFormer: A Single-Cell Foundation Model Powered by Gene Regulatory Hierarchies

Luni Hu[1,†], Hua Qin[1,†], Yilin Zhang[1], Yi Lu[1], Ping Qiu[1], Zhihan Guo[1], Lei Cao[1], Wenjian Jiang[1], Qianqian

Chen[1], Yanbang Shang[1], Tianyi Xia[1], Ziqing Deng[1], Xun Xu[2,*], Shuangsang Fang[1,*], Yuxiang Li[2,*], Yong

Zhang[2,*]

1. BGI Research, Beijing 102601, China

2. BGI Research, Wuhan 430074, China

*Correspondence: zhangyong2@genomics.cn   (Y.Z)   liyuxiang@genomics.cn   (X.L),

fangshuangsang@genomics.cn (S.F.), xuxun@genomics.cn (X.X.)

† These authors contributed equally as the first authors.

Abstract

Single-cell RNA sequencing (scRNA-seq) enables high-resolution profiling of cellular diversity, but current computational models often fail to incorporate regulatory priors, handle data sparsity, or efficiently process long gene sequences. Here, we present RegFormer, a foundation model that integrates gene regulatory networks (GRNs) with Mamba-based state-space modeling, overcoming the scalability and context-length limitations of Transformer architectures. RegFormer encodes each gene through dual embeddings, a value embedding for quantitative expression and a token embedding for regulatory identity, organized within a GRN-guided gene order to capture both expression dynamics and hierarchical regulation. Pretrained on 26 million human single cells spanning 45 tissues and diverse biological contexts, RegFormer achieves superior scalability and biological fidelity. Across comprehensive benchmarks, it consistently outperforms state-of-the-art single-cell foundation models (scGPT, Geneformer, scFoundation, and scBERT), delivering higher clustering accuracy, improved batch integration, and more precise cell type annotation. RegFormer also reconstructs biologically coherent GRNs, accurately models transcriptional responses to genetic perturbations, and enhances drug response prediction across cancer cell lines. By combining regulatory priors with efficient long-sequence Mamba modeling, RegFormer establishes a biologically grounded and scalable framework for single-cell representation learning, enabling deeper mechanistic insight into gene regulation and cellular state transitions.

Introduction

Single-cell RNA sequencing (scRNA-seq) has revolutionized our understanding of cellular heterogeneity, gene expression dynamics, and the complex regulatory networks that underpin cellular processes[1-3]. By enabling the detailed characterization of individual cells, scRNA-seq has unveiled key biological mechanisms involved in tissue development[4], disease progression[5], and responses to environmental stimuli[6]. Large-scale initiatives like the Human Cell Atlas exemplify the growing scope of single-cell transcriptomics, providing comprehensive maps of cellular diversity across tissues and disease contexts[7]. Despite these transformative insights, computational methods for analyzing scRNA-seq data remain fragmented, with models often tailored for specific tasks and lacking scalability across diverse datasets and cellular states[8-10], underscoring the need for a unified, integrated analytical framework capable of performing multiple tasks simultaneously with higher accuracy and consistency.

To address this gap, recent advances have led to the development of single-cell foundation models, such as scGPT[11], Geneformer[12], scFoundation[13], and scBERT[14], which aim to provide a general-purpose solution for the analysis of scRNA-seq data. These models leverage deep learning techniques, which have proven effective at capturing complex patterns within high-dimensional, sparse scRNA-seq datasets. By learning representations of gene expression profiles, these models can achieve strong performance in tasks like cell annotation and genetic perturbation prediction. However, despite their success, these models typically rely on natural language processing (NLP) algorithms[15, 16], which are inherently designed for sequential data, such as text or genomic sequences. While these approaches are beneficial in certain contexts, they do not fully address the unique challenges posed by scRNA-seq data, specifically the unordered nature of gene expression measurements across individual cells. Unlike traditional sequence data, where elements (such as nucleotides or words) follow a fixed order, scRNA-seq data lacks this inherent structure, which makes it difficult for sequence-based models to capture the complex, non-linear interactions between genes and the hierarchical relationships that define cellular states.

To overcome these limitations, biological prior knowledge, particularly that derived from gene regulatory networks (GRNs), has been increasingly incorporated into scRNA-seq analysis[17-19]. GRNs represent the intricate regulatory relationships between genes and provide a framework for understanding how gene expression is regulated within cellular contexts. These networks capture key biological insights that are not immediately apparent from raw gene expression data alone, such as transcriptional hierarchical

dependencies, and spatial-temporal regulation of gene activity[20, 21]. GRN-based priors enable models to

capture regulatory mechanisms more faithfully and enhance biological relevance. This not only enhances

the accuracy of predictions but also provides richer, more biologically grounded insights into the

underlying regulatory mechanisms that govern cellular behavior and function. The integration of GRNs

allows for the modeling of hierarchical dependencies between genes, which is critical for understanding

cellular dynamics, differentiation, and disease mechanisms.

Mamba Blocks provide an innovative solution for analyzing high-dimensional, sparse datasets by enabling

flexible representation learning and hierarchical modeling of gene interactions. Unlike traditional

transformer architectures, which often struggle with computational complexity, Mamba Blocks are

specifically engineered to effectively address the intricacies of scRNA-seq data[22].Existing models such as

DGRNA[23], Orthrus[24], and SC-MAMBA2[25], which are also based on Mamba architecture, primarily focus

on scRNA-seq data and broader RNA biology tasks. DGRNA excels at modeling RNA sequences, while

Orthrus specializes in splicing dynamics. However, these models may not fully capture the complexities of

scRNA-seq data, which are essential for understanding cellular states. Although SC-MAMBA2 performs

well in single-cell analysis, it tends to emphasize gene-gene interactions without integrating biological

prior knowledge.By leveraging hierarchical insights from gene regulatory networks, Mamba Blocks

enhance our understanding of cellular behavior and function, effectively addressing the need for more

biologically grounded computational models in single-cell research.

Here, we present RegFormer, a foundation model tailored for scRNA-seq analysis. RegFormer integrates

GRNs with a Mamba-based state-space architecture optimized for high-dimensional and sparse expression

data. This design enables efficient modeling of long-range dependencies across gene sequences, capturing

both local interactions and global regulatory hierarchies. Through generative pretraining on 26 million

human cells, RegFormer learns gene expression dynamics together with the hierarchical structure of gene

regulation, enhancing biological fidelity. By incorporating GRN-guided priors, it effectively models

transcriptional dependencies within regulatory hierarchies, providing mechanistic insights into gene

control and cellular behavior. Across diverse benchmarks, including cell annotation, GRN reconstruction,

genetic perturbation prediction, and drug response modeling, RegFormer consistently outperforms existing

foundation models such as scGPT and Geneformer. Together, these advances position RegFormer as a

scalable framework for decoding complex transcriptional programs and advancing single-cell biology.

Results

RegFormer leverages regulatory priors for single-cell modeling with Mamba.

RegFormer is a foundation model that integrates regulatory priors into single-cell transcriptome modeling through the combination of gene regulatory networks (GRNs) and Mamba sequence modeling (**Fig. 1A**). For large-scale pretraining, we curated a harmonized collection of 26 million human single cells spanning 45 tissues, multiple sequencing technologies, and diverse developmental and disease contexts (**Supplementary Fig. S1B-E**). Data preprocessing followed a unified pipeline: raw matrices were imported as AnnData objects, filtered for low-quality genes and cells, normalized, log-transformed, and written into LMDB for efficient large-scale training (**Supplementary Fig. S1A**).

To incorporate biological prior knowledge, we constructed GRNs by linking transcription-factor (TF) motifs to their downstream targets using curated motif-to-gene mappings. The networks were refined via Node2Vec embeddings and iterative edge removal until a directed acyclic graph (DAG) was obtained (**Supplementary Fig. S2A**). This process retained > 92 % of edges while preserving degree and path-length distributions (**Supplementary Fig. S2B-F**). The final network contained 13.4 % TF nodes and 86.6 % target genes arranged across hierarchical regulatory depths (**Supplementary Fig. S3A-C**). Genes were then topologically sorted along this hierarchy to align expression matrices with regulatory order (**Fig. 1B**)..

Within this GRN-ordered framework, RegFormer encodes each gene using dual embeddings: a value embedding representing quantitative expression and a token embedding representing the gene's regulatory identity (**Fig. 1C**). These embeddings are processed by Mamba blocks, which combine multi-layer perceptrons, convolutional operations, and state-space modules to capture both local interactions and long-range dependencies (**Fig. 1D**). During pretraining, RegFormer is optimized through three complementary self-supervised objectives, masked-value prediction, gene expression prediction, and regulatory role prediction, which together enable the model to learn quantitative variation, expression reconstruction, and hierarchical regulatory relationships (**Fig. 1E**). Together, these components form a unified framework that integrates biological priors with sequence modeling to learn the regulatory principles underlying single-cell gene expression.

Mechanistic validation of GRN guidance and architectural design.

We further evaluated how regulatory priors and architectural design influence RegFormer's learning

behavior through systematic ablation and functional analyses. All models were trained on **1 million blood cells** and **evaluated across eight validation datasets** to ensure robust and comparable assessment. (**Supplementary Figs. S4-S13**). RegFormer embeddings accurately captured transcriptional hierarchy and maintained proximity between transcription factors and their targets. Compared with randomly initialized or MLM-based controls, RegFormer achieved higher transcription factor classification accuracy and stronger correlations between gene embeddings and regulatory degree, indicating that the learned representations closely align with the underlying GRN topology (**Supplementary Figs. S5-S6**). Functionally, reconstructed GRNs derived from RegFormer embeddings exhibited greater biological coherence: across eight blood validation datasets, GRN-guided models yielded more enriched pathways and higher cross-dataset functional similarity than non-GRN variants (**Supplementary Fig. S7**), demonstrating that regulatory priors improve biological fidelity.

Ablation experiments further elucidated the contribution of each architectural component. Replacing Mamba blocks with Transformer layers weakened cell-level representation and reduced preservation of gene-level regulatory relationships (**Supplementary Fig. S8**), indicating that the state-space formulation more effectively captures hierarchical transcriptomic dependencies. Across blood validation datasets, GRN-guided RegFormer consistently achieved higher Average Silhouette Width (ASW) scores than the Random variant, confirming the advantage of incorporating regulatory priors (**Supplementary Fig. S9A**). Removing the token embedding and retaining only value embeddings led to lower clustering performance, suggesting that regulatory context encoded by gene tokens is essential for representing cell-type structure (**Supplementary Fig. S9B**). Substituting the regression-based value prediction with binary classification (BinCls) also decreased ASW scores, indicating that modeling gene expression as a continuous variable captures quantitative variation more accurately (**Supplementary Fig. S9C**). When individual pretraining objectives, including masked-value prediction (MVP), gene-expression prediction (GEPC), or regulatory-role prediction (TOPO), were removed, model performance consistently declined across datasets, with the largest decrease observed when the TOPO objective was omitted (**Supplementary Fig. S9D**).

Similarly, shuffling or removing GRN edges substantially reduced ASW performance and weakened degree correlations and reconstruction precision (**Supplementary Fig. S10**), underscoring the essential contribution of authentic regulatory topology to model stability and biological coherence. Notably, extending the input sequence from 1.2k to 10k genes further improved clustering resolution and functional

consistency (**Supplementary Fig. S11**). The longer input sequence provided a more comprehensive

regulatory context and enabled the model to capture long-range dependencies across transcriptional

modules, thereby enhancing both biological insight and scalability. In addition, compared with graph

neural network frameworks, RegFormer achieved higher accuracy at both the gene and cell levels

(**Supplementary Fig. S12**).

Together, GRN-guided gene ordering, dual-embedding design, and Mamba-based long-sequence modeling

act synergistically to allow RegFormer to capture cross-hierarchical regulatory relationships within an

expanded gene space, establishing a biologically grounded and scalable framework for single-cell

representation learning.

RegFormer achieves superior single-cell embeddings across tissues.

Single-cell foundation models have emerged as powerful tools for representing, classifying, and analyzing

the complex information embedded within single-cell datasets. Using the BioLLM benchmarking

framework[26], we systematically evaluated the representation capacity of RegFormer against state-of-the-art

single-cell foundation models, including scGPT, GeneFormer, scFoundation, and scBERT, across multiple

human tissue datasets (**Fig. 2**). RegFormer consistently achieved higher Average Silhouette Width (ASW)

scores, indicating superior separation of biologically distinct cell populations. In the human lung dataset,

representing a discretized single-cell transcriptome, RegFormer accurately resolved epithelial, endothelial,

and immune lineages, effectively capturing fine-grained intra-tissue heterogeneity (**Fig. 2A**). In the bone

marrow dataset, representing a continuous single-cell trajectory, RegFormer outperformed other models in

distinguishing early myeloid and lymphoid progenitors (**Fig. 2B**). In the dendritic cell dataset, RegFormer

maintained subtype consistency across batches while achieving high cell-type ASW and low batch ASW

values, demonstrating strong batch invariance (**Fig. 2C**). In the pancreas dataset, the model robustly

separated endocrine, exocrine, and stromal compartments, even in the presence of substantial technical

variation (**Fig. 2D**).

Performance analyses across varying numbers of highly variable genes (HVGs) further confirmed the

scalability and stability of RegFormer embeddings (**Supplementary Fig. S13**). Both RegFormer-1.2k and

RegFormer-10k maintained consistently high ASW scores across HVG subsets, whereas other models

showed marked performance declines as the number of features decreased. The broader-context 10k

variant provided additional gains, indicating that longer gene sequences supply a more complete regulatory

context and enhance the model's ability to capture gene regulatory information.

RegFormer enhances cell type annotation performance across diverse datasets.

To further evaluate the downstream application of RegFormer, we benchmarked its performance on cell

type annotation tasks across six representative datasets, in comparison with leading single-cell foundation

models. RegFormer-10k and RegFormer-1.2k consistently achieved higher Macro-averaged F1 score

(Macro-F1) and comparable accuracy values than all baseline models, demonstrating more precise and

generalizable cell type classification (**Fig. 3A**). In the Zheng68k dataset, RegFormer accurately

reconstructed the fine-grained immune landscape, effectively distinguishing closely related CD4 and CD8

T-cell subsets (**Fig. 3B-C**). Across additional tissues including blood, liver, small intestine, kidney, and

M.S., RegFormer generated the most coherent UMAP embeddings and exhibited the highest diagonal

concentration in confusion matrices, indicating faithful label recovery and minimal cross-type confusion

(**Supplementary Fig. S14**).

In quantitative analyses, RegFormer achieved the highest macro-average precision (AP) across all

benchmark datasets (**Supplementary Fig. S15A**). The model maintained stable predictive performance

across cell types of varying abundance and showed stronger recognition ability for rare cell populations

(**Supplementary Fig. S15B**). When finetuned on downstream cell type annotation tasks, both RegFormer-

10k and RegFormer-1.2k achieved higher Macro-F1 and accuracy compared with scratch training (**Fig. 3D**

and Supplementary Fig. S16A). Confusion matrix comparisons further showed improved subtype

classification consistency after finetuning (**Supplementary Fig. S16B**), and cell type–wise precision

analyses demonstrated consistent performance gains across different cell categories (**Supplementary Fig.**

S16C).

Together, these results demonstrate that RegFormer provides accurate, scalable, and generalizable cell type

annotation across heterogeneous single-cell datasets, with the extended 10k variant further improving fine-

grained resolution and rare cell type recognition through broader gene coverage and regulatory context

integration.

RegFormer reconstructs biologically coherent gene regulatory networks.

We next evaluated the ability of RegFormer to reconstruct gene regulatory networks (GRNs) from single-

cell gene expression data. Gene embeddings derived from the pretrained model were used to compute

pairwise cosine similarity between genes, and the resulting similarity matrices were interpreted as putative

regulatory connections between transcription factors and their targets (**Fig. 4A**). Applied to the human lung

dataset (**Fig. 4B**), RegFormer-inferred GRNs exhibited higher functional similarity than those generated by

existing single-cell foundation models (**Fig. 4C**). RegFormer also achieved the highest Gene Ontology

(GO) enrichment counts across a range of clustering resolutions (**Fig. 4D**), indicating that its embeddings

better preserve biologically relevant gene interactions.

Analysis of regulon activity revealed a strong correspondence between transcription factor expression and

inferred regulon scores across diverse lung cell types (**Fig. 4E**). Case studies of canonical regulators

further supported the biological validity of the inferred networks (**Fig. 4F and Supplementary Fig. S17**).

The regulon activity and expression of GATA3 were predominantly enriched in T cells, consistent with its

established role as a master regulator of T-cell differentiation. In contrast, SPI1 (PU.1) activity and

expression were concentrated in macrophage and monocyte-associated clusters, in line with its key role in

myeloid lineage commitment. The reconstructed GATA3 and SPI1 regulons included canonical immune-

related targets such as IL16, POU2AF1, CD14, and CLEC7A, accurately reflecting their roles in adaptive

and innate immune regulation (**Fig. 4F**).

Comparisons between the input and reconstructed GRNs further demonstrated stronger cross-cell-type

correlations among regulatory edges and improved concordance between transcription factors and their

predicted targets (**Supplementary Fig. S18A-B**). Functional enrichment analyses revealed that the

reconstructed networks provided enhanced representation of biologically relevant pathways, particularly

those related to immune activation, morphogenesis, and neurogenesis (**Supplementary Fig. S18C-D**).

Collectively, These findings indicate that RegFormer enables the reconstruction of biologically coherent

and functionally meaningful GRNs, providing a robust framework for linking single-cell gene expression

profiles to underlying regulatory mechanisms.

RegFormer enables accurate modeling of genetic perturbations

Building on its ability to reconstruct static gene regulatory architectures, we next examined whether

RegFormer embeddings could also capture dynamic transcriptional responses under genetic perturbations.

By integrating pretrained gene embeddings with the GEARS framework, RegFormer predicts post-

perturbation expression states from unperturbed profiles, modeling how transcriptional programs shift in

response to targeted perturbations (**Fig. 5A**).

Across both the Adamson and Norman CRISPR perturbation datasets, RegFormer achieved the lowest

mean squared error (MSE) and highest Pearson correlation among all single-cell foundation models tested,

including scFoundation and scGPT (**Fig. 5B, D**). Predicted versus observed Δ-expression values showed

near-perfect linear correspondence ($R^2 > 0.97$) for representative perturbations such as UFL1 and KMT2A,

confirming that RegFormer embeddings effectively encode regulatory dependencies (**Fig. 5C, E and**

Supplementary Fig. S19). Cosine similarity analysis further revealed that differentially expressed genes

exhibited higher embedding proximity to the perturbed transcription factor than nonresponsive genes,

suggesting that RegFormer effectively captures the regulatory dependencies driving transcriptional

responses (**Fig. 5C, E and Supplementary Fig. S19**).

Together, these findings demonstrate that RegFormer embeddings provide a unified representation that

generalizes from static GRN topology to dynamic perturbation effects, enabling accurate modeling of

transcriptional responses across diverse perturbation contexts.

RegFormer improves drug response prediction across diverse cancer cell lines.

Having demonstrated its ability to model both regulatory structure and perturbation dynamics, we next

evaluated whether RegFormer embeddings could improve drug response prediction across cancer cell lines.

We integrated RegFormer-derived gene expression embeddings with molecular graph representations of

drug structures using a uniform graph convolutional network to predict IC50 values (**Fig. 6A**). Across

multiple benchmarks, RegFormer achieved the highest Pearson Correlation Coefficient (PCC) and

Spearman Rank Correlation Coefficient (SRCC) among all compared models, including DeepCDR,

GeneFormer, scGPT, scBERT and scFoundation (**Fig. 6B-D and and Supplementary Fig. S20A-B**).

Predicted versus observed IC50 values showed strong linear correspondence across both drugs and cancer

types (**Fig. 6C**), and maintained high precision for the top five best-predicted compounds (**Fig. 6D**). In

leave-drug-out blind tests, RegFormer consistently outperformed DeepCDR, achieving higher PCC across

nearly all unseen drugs (**Fig. 6E and Supplementary Fig. S20C**).

Beyond numerical accuracy, pathway-level analyses revealed that RegFormer captured biologically

meaningful mechanisms of drug sensitivity. For example, Bortezomib responses were associated with

TNF-α signaling via NF-κB[27], while SN-38 responses were linked to p53-mediated apoptosis[28] (**Fig. 6F**).

These results indicate that RegFormer embeddings significantly improve predictive performance in drug

response prediction.

Discussion

The introduction of RegFormer marks a major advance in single-cell RNA sequencing (scRNA-seq)

analysis, addressing long-standing challenges in data sparsity, biological relevance, and scalability. By

integrating gene regulatory networks (GRNs) within a Mamba-based architecture, RegFormer bridges

biological knowledge with efficient long-sequence modeling, setting new benchmarks across key

analytical tasks including cell annotation, GRN reconstruction, genetic perturbation prediction, and drug

response modeling.

A central innovation of RegFormer is its use of GRNs to model hierarchical regulatory relationships

fundamental to cellular identity. Unlike prior models such as scBERT and GeneFormer, which either

lacked biological priors or were constrained by limited context windows, RegFormer orders genes

according to GRN-guided topology, allowing the model to learn regulation in a biologically meaningful

sequence. Performance remains sensitive to the quality and completeness of GRN priors, incomplete or

noisy networks may distort ordering or weaken hierarchical signal propagation. Future work may employ

context-specific or probabilistic GRNs to enhance adaptability across tissues. To ensure hierarchical

consistency, cycles in GRNs are removed to form a directed acyclic graph (DAG), which preserves most

structure but may omit feedback loops important for regulation. Developing differentiable or dynamic

cycle-handling mechanisms could mitigate this limitation.

Architecturally, RegFormer represents a departure from Transformer-based models such as scGPT,

GeneFormer, and scFoundation, which rely on quadratic attention mechanisms that limit both scalability

and effective context length (**Supplementary Table S2**). In contrast, RegFormer's Mamba Blocks adopt a

state-space formulation with linear time complexity, enabling efficient modeling of extended gene

sequences encompassing up to 10,000 genes. This formulation preserves long-range regulatory

dependencies across transcriptional modules that are often attenuated or truncated in attention-based Transformers, thereby enhancing the model's ability to represent coherent regulatory programs and global transcriptional coordination. Future work will extend benchmarking to full-transcriptome contexts, enabling comprehensive assessment of Mamba's genome-scale modeling capacity and its potential to capture hierarchical regulatory organization across the entire transcriptome.

Empirical evaluations demonstrate that RegFormer achieves superior performance across diverse human tissues and datasets. In cell annotation tasks, it consistently outperforms existing models, yielding more precise classifications and clearer clustering that reveal cellular heterogeneity and subtle subtypes. Its strong performance across datasets and batch conditions highlights robust generalization, making RegFormer a versatile tool for single-cell transcriptomics. In GRN construction, RegFormer generates high-resolution networks that align closely with known pathways and transcription factor activities, as exemplified by its accurate identification of key regulators such as GATA3 and SPI1. Despite these advances, challenges remain in scaling to larger datasets and addressing the dependence on GRN completeness. Future work will incorporate dynamic and context-specific regulatory networks and extend the framework to multi-omics integration for more comprehensive modeling of cellular states. Collectively, these results establish RegFormer as a powerful foundation model that unifies biological priors with advanced machine learning to enhance robustness, and discovery potential in single-cell research.

Reference

1.   Choi, Y.H. & Kim, J.K. Dissecting Cellular Heterogeneity Using Single-Cell RNA Sequencing. *Mol Cells* **42**, 189-199 (2019).
2.   Papalexi, E. & Satija, R. Single-cell RNA sequencing to explore immune cell heterogeneity. *Nat Rev Immunol* **18**, 35-45 (2018).
3.   Gawad, C., Koh, W. & Quake, S.R. Single-cell genome sequencing: current state of the science. *Nat Rev Genet* **17**, 175-188 (2016).
4.   He, P. et al. The changing mouse embryo transcriptome at whole tissue and single-cell resolution. *Nature* **583**, 760-767 (2020).
5.   van Galen, P. et al. Single-Cell RNA-Seq Reveals AML Hierarchies Relevant to Disease Progression and Immunity. *Cell* **176**, 1265-1281 e1224 (2019).
6.   Sheu, K.M., Pimplaskar, A. & Hoffmann, A. Single-cell stimulus-response gene expression trajectories reveal the stimulus specificities of dynamic responses by single macrophages. *Mol Cell* **84**, 4095-4110 e4096 (2024).
7.   Regev, A. et al. The Human Cell Atlas. *Elife* **6** (2017).
8.   Ryu, Y., Han, G.H., Jung, E. & Hwang, D. Integration of Single-Cell RNA-Seq Datasets: A Review of Computational Methods. *Mol Cells* **46**, 106-119 (2023).
9.   Heumos, L. et al. Best practices for single-cell analysis across modalities. *Nat Rev Genet* **24**, 550-572 (2023).
10.   Saliba, A.E., Westermann, A.J., Gorski, S.A. & Vogel, J. Single-cell RNA-seq: advances and future challenges. *Nucleic Acids Res* **42**, 8845-8860 (2014).
11.   Cui, H. et al. scGPT: toward building a foundation model for single-cell multi-omics using generative AI. *Nat Methods* **21**, 1470-1480 (2024).

12. Theodoris, C.V. et al. Transfer learning enables predictions in network biology. *Nature* **618**, 616-624
(2023).
13. Hao, M. et al. Large-scale foundation model on single-cell transcriptomics. *Nature Methods* **21**, 1481-
1491 (2024).
14. Yang, F. et al. scBERT as a large-scale pretrained deep language model for cell type annotation of
single-cell RNA-seq data. *Nature Machine Intelligence* **4**, 852-866 (2022).
15. Bian, H. et al. General-purpose pre-trained large cellular models for single-cell transcriptomics.
National Science Review **11**, nwae340 (2024).
16. Ma, Q., Jiang, Y., Cheng, H. & Xu, D. Harnessing the deep learning power of foundation models in
single-cell omics. *Nat Rev Mol Cell Biol* **25**, 593-594 (2024).
17. Schafer, P.S.L., Dimitrov, D., Villablanca, E.J. & Saez-Rodriguez, J. Integrating single-cell multi-
omics and prior biological knowledge for a functional characterization of the immune system. *Nat
Immunol* **25**, 405-417 (2024).
18. Doddahonnaiah, D. et al. A Literature-Derived Knowledge Graph Augments the Interpretation of
Single Cell RNA-seq Datasets. *Genes (Basel)* **12** (2021).
19. Kim, D. et al. Gene regulatory network reconstruction: harnessing the power of single-cell multi-omic
data. *NPJ Syst Biol Appl* **9**, 51 (2023).
20. Emmert-Streib, F., Dehmer, M. & Haibe-Kains, B. Gene regulatory networks and their applications:
understanding biological and medical problems in terms of networks. *Front Cell Dev Biol* **2**, 38 (2014).
21. Fang, S. et al. Stereopy: modeling comparative and spatiotemporal cellular heterogeneity via multi-
sample spatial transcriptomics. *Nat Commun* **16**, 3741 (2025).
22. Gu, A. & Dao, T.J.a.p.a. Mamba: Linear-time sequence modeling with selective state spaces. (2023).
23. Yuan, Y., Chen, Q. & Pan, X. DGRNA: a long-context RNA foundation model with bidirectional
attention Mamba2. *bioRxiv*, 2024.2010.2031.621427 (2024).
24. Fradkin, P. et al. Orthrus: Towards Evolutionary and Functional RNA Foundation Models. *bioRxiv*,
2024.2010.2010.617658 (2024).
25. Zhao, Y. et al. SC-MAMBA2: Leveraging State-Space Models for Efficient Single-Cell Ultra-Long
Transcriptome Modeling. *bioRxiv*, 2024.2009.2030.615775 (2024).
26. Qiu, P. et al. BioLLM: A standardized framework for integrating and benchmarking single-cell
foundation models. *Patterns (N Y)* **6**, 101326 (2025).
27. Sung, M.H. et al. Dynamic effect of bortezomib on nuclear factor-kappaB activity and gene expression
in tumor cells. *Mol Pharmacol* **74**, 1215-1222 (2008).
28. Liu, Y. et al. Inhibition of Akt signaling by SN-38 induces apoptosis in cervical cancer. *Cancer Lett*
274, 47-53 (2009).

Methods

Data Collection and Preprocessing

We curated a large-scale corpus comprising 26 million human single cells across 45 tissues from the CZ CELLxGENE database, encompassing multiple sequencing platforms, developmental stages, and disease contexts. Each dataset was converted into an AnnData object and processed through a standardized pipeline to ensure consistency and scalability for model pretraining. As shown in Supplementary **Fig. S1A**, cells with fewer than 200 detected genes and genes outside the defined vocabulary were removed. Datasets were checked for scaling status, normalized using scanpy.pp.normalize_total when raw count data were detected, and log-transformed with scanpy.pp.log1p when the maximum expression value exceeded 25. Zero-expressed genes were filtered, and all processed AnnData objects were serialized into LMDB format to facilitate efficient data streaming during large-scale pretraining. Dataset distributions across tissues, sequencing platforms, developmental stages, and disease states are summarized in Supplementary **Fig. S1B-E**, highlighting the diversity and coverage of the pretraining corpus.

Construction of Guided Gene Regulatory Networks

We constructed guided gene regulatory networks (GRNs) to encode transcriptional dependencies that inform model pretraining. As illustrated in **Supplementary Fig. S2A**, transcription factor (TF) motif-gene associations were derived from curated motif-scanning results (hg19-tss-centered-10kb-10species.mc9nr.genes_vs_motifs.rankings.feather) and mapped to TF identities using the motif annotation table (motifs-v9-nr.hgnc-m0.001-o0.0.tbl). Genes were filtered based on the predefined vocabulary to ensure consistency with the pretraining corpus.

For each TF, a directed edge was established to its top-20k ranked target genes, generating an initial regulatory graph G. Node embeddings were then learned using the Node2Vec algorithm, which captures higher-order connectivity patterns within the graph. To eliminate feedback loops and ensure acyclicity, edges were iteratively removed based on cosine similarity between node embeddings. In each cycle, the edge with the lowest similarity was deleted until a directed acyclic graph (DAG) was obtained. This process retained over 92% of edges while preserving degree and path-length distributions (**Supplementary Figs. S2B-F**). The final DAG was exported in DGL (.dgl) formats for downstream integration into the RegFormer pretraining pipeline.

RegFormer Architecture

Model Overview

RegFormer is a foundation model for single-cell transcriptomics that integrates gene regulatory network

(GRN) priors with a state space-based sequence modeling framework. Each cell is represented as an

ordered gene sequence derived from the GRN topology, allowing the model to capture both expression

magnitude and regulatory context. The architecture consists of a dual-embedding input layer, a stack of

Mamba-based state space blocks for contextual encoding, and multiple pretraining objectives for self-

supervised representation learning.

Topological Sorting

Input genes were ordered according to a directed acyclic gene regulatory network (GRN), denoted as

$G = (V, E)$, where nodes V represent genes and directed edges $(g_i \rightarrow g_j)$ in E denote transcriptional

regulation from gene g_i to gene g_j.

To preserve causal directionality, nodes were arranged by topological depth, ensuring that upstream

regulators always precede their downstream targets within each input sequence. Formally, the topological

order

$$pi: V \rightarrow \{1, 2, \dots, |V|\}$$

satisfies the condition

$$pi(g_i) < \pi(g_j), \quad \forall (g_i \rightarrow g_j) \in E$$

which guarantees that information propagates along biologically valid regulatory paths during sequence

modeling.

In implementation, topological sorting was performed using the dgl.topological_nodes_generator function,

which iteratively yields node batches from the source layer to the sink layer of the acyclic GRN, providing

a depth-wise traversal consistent with the model's sequential encoding.

For ablation experiments, randomized and edge-perturbed graphs $G' = (V, E')$ were generated by shuffling

or removing a subset of edges while maintaining node identity and approximate degree distribution.

Dual-Embedding Scheme

Each gene token was represented by two complementary embeddings: a token embedding encoding gene

identity and a value embedding encoding normalized expression magnitude. The two embeddings were

summed and linearly projected into a shared latent space before entering the encoder. Formally, the

representation of gene g_i is given by

$$\square_i = \mathbf{E}_{\text{token}}(g_i) + \mathbf{E}_{\text{value}}(x_i)$$

where $\mathbf{E}_{\text{token}}$ maps the discrete gene index g_i to a learnable embedding vector, and $\mathbf{E}_{\text{value}}$ projects the

normalized expression value x_i through a linear transformation. The resulting sequence $\mathbf{H}_0 =$

$[\mathbf{h}_1, \mathbf{h}_2, \ldots, \mathbf{h}_N]$ serves as input to the Mamba encoder stack. This dual scheme enables the model to jointly

learn categorical and quantitative aspects of gene regulation and supports robust generalization across

datasets with heterogeneous expression scales.

Mamba-Based State Space Blocks

The core encoder of RegFormer consists of stacked Mamba blocks, each implementing a selective state

space model (SSM) that efficiently captures long-range dependencies in gene sequences. The state space

dynamics are defined as

$$h_{t+1} = \mathbf{A}\,\mathbf{h}_t + \mathbf{B}\,\mathbf{x}_t$$

$$y_t = \mathbf{C}\,\mathbf{h}_t$$

464 where $\mathbf{h}_t$ denotes the hidden state at position t, $\mathbf{x}_t$ the input embedding, and $\mathbf{A}, \mathbf{B}, \mathbf{C}$ are learnable transition,

465 input, and output matrices, respectively.

467 In the Mamba implementation, these continuous dynamics are approximated through depthwise

468 convolution and gated activation mechanisms, expressed as

$$H' = \sigma(\mathbf{W}_g * \mathbf{H}) \odot (\mathbf{W}_s * \mathbf{H})$$

where $*$ denotes a one-dimensional convolution along the sequence dimension, σ is a sigmoid gating

function, and $\odot$ represents elementwise multiplication. This formulation enables selective state updates

and efficient modeling of directional regulatory dependencies with linear computational complexity in

sequence length.

Compared with attention-based architectures, the Mamba-based state space formulation allows RegFormer

to capture global regulatory context with reduced memory usage and improved scalability across long gene

sequences.

Pretraining Objectives

RegFormer was pretrained using multiple self-supervised objectives designed to capture complementary

aspects of transcriptional regulation. Three core tasks were implemented: Masked Value Prediction (MVP),

Gene Expression Prediction for Cells (GEPC), and Regulatory Topology Modeling (TOPO). All objectives

were jointly optimized under a weighted sum loss function.

To encourage local feature reconstruction, a subset of gene expression values was randomly masked, and

the model was trained to predict their original magnitudes based on surrounding context. The loss was

computed as mean squared error between predicted and observed values:

$$\mathcal{L}_{\mathrm{MVP}} = \frac{1}{|\mathcal{M}|} \sum_{i \in \mathcal{M}} (\hat{x}_i - x_i)^2$$

487 where $\mathcal{M}$ denotes the set of masked positions, x_i is the true normalized expression value, and $\hat{x}_i$ is the

488 model's prediction.

490 To align cell- and gene-level representations, a masked value decoder (MVC) was trained to reconstruct

491 expression profiles from cell embeddings and query-specific gene vectors. For a given cell embedding **c**

492 and gene query vectors $\mathbf{q}_i$, the decoder computes

$$\hat{x}_i = q_i^{\mathsf{T}} W c$$

493 where **W** is a learnable projection. The resulting mean squared error loss encourages the cell embedding to

494 encode global expression state:

$$\mathcal{L}_{\mathrm{GEPC}} = \frac{1}{N} \sum_{i=1}^{N} (\hat{x}_i - x_i)^2$$

496 To learn regulatory directionality, the model was trained to predict the next gene token in a topologically

497 sorted GRN sequence. Given the predicted logits $\mathbf{z}_t$ and target indices y_t, a cross-entropy objective was

498 applied:

$$\mathcal{L}_{\mathrm{TOPO}} = -\frac{1}{T} \sum_{t=1}^{T} \log p\,(y_t \mid z_t)$$

500 where masking was applied to non-regulatory or padding tokens to prevent trivial reconstruction. This

501 objective enforces that embeddings respect the causal direction of transcriptional regulation.

503   All pretraining objectives were combined using adaptive weighting:

$$\mathcal{L}_{\text{total}} = \lambda_{\text{MVP}}\mathcal{L}_{\text{MVP}} + \lambda_{\text{GEPC}}\mathcal{L}_{\text{GEPC}} + \lambda_{\text{TOPO}}\mathcal{L}_{\text{TOPO}}$$

where λ_i are task-specific coefficients chosen to balance gradient magnitudes. The masking ratio was set to

40% for all tasks, and loss terms were dynamically sanitized to prevent numerical instabilities during

mixed-precision distributed training.

Systematic Ablations

Ablation Design

To dissect the contributions of individual architectural and pretraining components, we conducted a series

of controlled ablation experiments (**Supplementary Figs. S4**). Each variant was initialized from the same

configuration as the main RegFormer model and trained under identical optimization settings on **1 million**

blood cells to ensure fair comparability. All experiments were performed using distributed data parallelism

on 20 NVIDIA A100 GPUs (40 GB each).

To isolate the effects of core architectural modules, several variants were derived from the base Mamba

framework. In the ***Random Sequence (Random)*** configuration, gene order within each input sequence was

randomly permuted to remove graph-guided topological sorting. The ***Value-Only Embedding***

(OnlyValueEmb) variant excluded the gene identity token embedding, retaining only quantitative value

embeddings to assess the contribution of gene-level contextual information. The ***Transformer Substitution***

(Transformer) variant replaced Mamba blocks with Transformer encoder layers of equal hidden

dimension (256), feed-forward expansion (×4), and dropout rate (0.1), enabling a direct comparison

between state-space and attention-based modeling. Finally, the ***Classification Head (BinCls)*** variant

reformulated the value prediction task as a categorical classification problem optimized with a cross-

entropy loss instead of mean squared error, testing sensitivity to prediction granularity.

To examine the influence of GRN topology on representation learning, two structural perturbations were

introduced. In the ***Edge Shuffling (Shuffled)*** variant, 30% of edges were randomly reassigned while

preserving node-degree distribution, thereby disrupting local connectivity but maintaining overall graph

density. In the ***Edge Removal (Removed)*** variant, 30% of regulatory edges were randomly deleted to

evaluate robustness under incomplete GRN priors. Both perturbations maintained consistent node identity

and vocabulary alignment across models.

The effects of pretraining objectives were further examined by selectively removing or isolating self-

supervised tasks. Three objectives—Masked Value Prediction (MVP), Gene Expression Prediction

(GEPC), and Regulatory Role Prediction (TOPO)—were evaluated through *Single-Objective variants*

(only MVP, only NTP, only GEPC) that retained one task and *Objective-Removal variants (w/o MVP,*

w/o NTP, w/o GEPC) that excluded one task while keeping the remaining two active. In addition, a

Masked Language Modeling (MLM) variant replaced continuous-value masking with discrete token-level

masking, analogous to classical language modeling objectives in NLP, to assess how token-based context

reconstruction affects representation learning. All ablation models used a consistent masking ratio (40%)

and loss-balancing scheme identical to the main model.

To assess the effect of input coverage, two sequence lengths, 1.2k and 10k genes, were used across all

ablation settings. Both configurations shared identical architectures, masking ratios, and optimization

parameters.

Together, these systematically designed ablations established a unified framework for quantifying how

regulatory priors, architectural components, and pretraining objectives collectively shape RegFormer's

learning behavior and representational capacity.

GNN comparison

To assess the contribution of regulatory priors and state-space modeling, we compared RegFormer with

graph neural network (GNN)–based pretraining frameworks operating on global gene co-expression graphs.

The comparative GNN model adopted a four-layer relational graph attention network (Relational GATv2)

with eight attention heads per layer, hidden dimension 512, ReLU activation, and dropout 0.2.

Global gene graphs were constructed by computing pairwise Pearson correlations among 3,000 highly

variable genes and retaining the top 30 positively correlated partners ($|r| > 0.2$) per gene as edges, yielding

an undirected weighted adjacency matrix used for all GNN training. The model was pretrained using two

self-supervised objectives, masked-value reconstruction of gene expression and masked-edge prediction,

optimized jointly with Adam under a cosine decay schedule ($\gamma = 0.9$), batch size 256, and automatic mixed

precision (AMP). Approximately 15% of nodes and edges were randomly masked per batch.

Training proceeded for five epochs with early stopping based on validation loss. Node embeddings from

the final layer were extracted for downstream analyses, including cell embedding, clustering, and GRN

reconstruction. All models used identical data preprocessing, vocabulary, and evaluation settings as

RegFormer to ensure comparability.

Performance Assessment

To evaluate the representational quality of RegFormer, we performed complementary analyses at both the

gene and cell levels. At the gene level, we examined whether the embeddings captured regulatory

hierarchy through two tasks. In Task 1, each node in the gene regulatory network (GRN) was labeled as a

transcription factor (TF) if it had outgoing edges, a target if it had only incoming edges, or isolated if

unconnected. A logistic regression classifier was trained to distinguish TFs from non-TFs using 60/40

stratified splits, repeated 20 times with different random seeds, and mean macro-precision and macro-

recall were reported. In Task 2, canonical correlation analysis (CCA) was performed between node

embeddings and their in- and out-degree vectors to quantify the alignment between embedding geometry

and regulatory connectivity. Higher classification accuracy and stronger correlations indicated that

RegFormer embeddings more effectively encoded transcriptional directionality and hierarchical

organization than randomized or ablated variants. At the cell level, embeddings were extracted from the

final encoder layer, and the Adjusted Silhouette Width (ASW) for cell type was computed across **eight**

blood validation datasets to assess biological separability and cluster coherence.

Downstream Tasks

All downstream benchmarking of baseline single-cell foundation models was carried out within the

BioLLM framework, which provides a standardized and reproducible pipeline encompassing data

preprocessing, embedding generation, and task-specific evaluation using datasets listed in **Supplementary**

Table S1.

Cell Embedding

Cell embedding extraction and benchmarking of existing single-cell foundation models were performed

using the BioLLM framework to maintain a consistent preprocessing and evaluation pipeline. Each model

followed its native input configuration and feature constraints. Geneformer and scGPT, limited by

maximum sequence lengths of 2,048 and 1,200 tokens, respectively, were provided with the top 3,000

highly variable genes (HVGs) as input features. In contrast, RegFormer, scBERT, and scFoundation

processed complete gene expression matrices without gene filtering to retain full transcriptomic coverage.

Gene expression values were normalized according to each model's original preprocessing protocol.

RegFormer generated cell embeddings through three alternative pooling strategies, while scGPT used the

CLS token representation, Geneformer averaged non-padded token embeddings, and scFoundation applied

max pooling.

To evaluate the embedding quality, Average Silhouette Width (ASW) was calculated for both cell type and

batch labels across multiple tissues. ASW was computed under two conditions, using all genes or 3,000

HVGs, to assess the effect of gene selection, and additional experiments varied the number of HVGs from

2,000 to 15,000. All analyses were implemented using the BioLLM framework, with Scanpy for data

preprocessing, UMAP for visualization, and scikit-learn for ASW computation.

Cell Type Annotation

Cell type annotation was performed in both intra-dataset and inter-dataset settings to evaluate each

foundational model's classification performance. Each dataset was divided into training and testing subsets

at an 80:20 ratio, with the training portion further split into training and validation sets (90:10). Full gene

expression profiles were retained to ensure consistency across models, and 3,000 highly variable genes

(HVGs) were selected for training.

For RegFormer, fine-tuning was conducted using a linear classification head attached to the average-

pooled cell embedding derived from Mamba encoder outputs. All models were trained for 20 epochs, with

learning rates set to their recommended defaults: 0.0001 for scGPT and scFoundation, 0.001 for scBERT,

0.00005 for Geneformer, and 0.0001 for RegFormer. The effect of fine-tuning vs scratch training were

further evaluated on the Zheng68k dataset.

Gene Regulatory Network Construction

Gene Regulatory Networks (GRNs) were reconstructed from pretrained model embeddings to evaluate

gene–gene relationships. Gene expression matrices (cells x genes) were first input into the RegFormer

pretrained model to generate gene representations, where each gene was encoded as a high-dimensional

embedding vector. Pairwise cosine similarity was then computed between all gene embeddings to quantify

transcriptional association strength, resulting in a symmetric gene-gene similarity matrix. This matrix was

interpreted as a weighted gene regulatory network, in which nodes represent genes and edge weights

correspond to the embedding-derived similarity scores. Transcription factors (TFs) were used as potential

regulators, and their top-20 target genes were identified based on cosine similarity values. The resulting

networks were subsequently analyzed for topological properties and biological coherence, serving as the

foundation for downstream clustering and functional enrichment analyses.

Genetic Perturbation

To evaluate how well single-cell foundational models capture causal regulatory relationships, we

conducted a gene perturbation prediction task using the Norman and Adamson datasets from the GEARS

benchmark. Each dataset profiles single-cell transcriptomic responses following CRISPR-based gene

perturbations, providing a suitable testbed for assessing generalization beyond observational data.

In this analysis, each foundational model provided pretrained gene embeddings obtained through

representation learning across large-scale single-cell datasets. These embeddings were used to initialize the

feature representations of genes within a co-expression-derived Genetic Relationship Graph, which serves

as the structural backbone of the perturbation predictor. By replacing the default feature initialization with

biologically informed embeddings, we aimed to examine whether pretrained regulatory representations

enhance the model's ability to infer transcriptional responses to perturbations.

All experiments were conducted under identical optimization settings to ensure fairness. The

dimensionality of each embedding was aligned with the hidden size of the perturbation model, and training

was performed for 20 epochs with a batch size of 32. Model parameters were fine-tuned while preserving

the pretrained embedding space, allowing adaptation to perturbation-specific contexts without disrupting

foundational gene representations. Performance was assessed on held-out perturbations by comparing

predicted and observed gene expression changes.

Drug Response

Drug response prediction was performed using the DeepCDR framework on two large pharmacogenomic

resources: the Genomics of Drug Sensitivity in Cancer (GDSC), which provides half-maximal inhibitory

concentration (IC$_{\square\square}$) measurements across cancer cell lines, and the Cancer Cell Line Encyclopedia

(CCLE), which contains matched gene expression, mutation, and DNA methylation profiles.

DeepCDR models drug efficacy by integrating chemical and molecular features through a multi-branch

neural network. Drug molecular structures are represented as graphs and encoded by a graph convolutional

network (GCN), while three parallel subnetworks independently extract latent biological features from

CCLE mutation, expression, and methylation data. The outputs from all branches are fused through a

convolutional aggregation module to predict IC$_{\square\square}$ values for each drug–cell line pair.

To incorporate representations from single-cell foundational models, the CCLE gene expression profiles

were first converted into embedding vectors using pretrained models such as RegFormer. Each cell line's

expression vector was passed through the pretrained model in inference mode to obtain a fixed-length

embedding, which was normalized and used to replace the original expression input of DeepCDR's

transcriptomic subnetwork. This procedure allowed the model to leverage biologically structured

representations learned from large-scale single-cell data.

For all experiments, the embedding dimension was matched to the hidden size of the DeepCDR

architecture to ensure consistent input dimensionality. Training and testing were conducted on GPU

devices under a leave-one-drug-out cross-validation protocol, in which data associated with a single drug

were held out during training and used exclusively for evaluation. Each model was trained using the Adam

optimizer with a batch size of 64 and learning rate of $1\times10_{\square\square}$ for 50 epochs, and the best checkpoint was

selected based on validation performance. Predictive accuracy was quantified by the Pearson correlation

coefficient (PCC) and Spearman rank correlation between the predicted and observed IC$_{\square\square}$ values across

test drug–cell pairs.

Evaluation Metrics

Cell Embedding Metrics

To assess the quality of learned cell embeddings, we evaluated both cell type clustering and batch effect

removal within the embedding space. The primary evaluation metric was the Average Silhouette Width

(ASW), which quantifies the balance between intra-cluster cohesion and inter-cluster separation.

For cell type clustering, ASW values range from 0 to 1, where 0 indicates poorly defined clusters, 0.5

suggests moderate overlap, and 1 reflects well-separated cell types. Higher ASW values indicate better-

defined cell clusters, demonstrating more accurate embedding performance. Formally, the ASW for cell

types is given by:

$$\text{ASW}_{\text{cell}} = \frac{1}{|C|} \sum_{i \in C} \frac{b(i) - a(i)}{\max\{a(i), b(i)\}}$$

693   where $a(i)$ is the mean intra-cluster distance of cell i, $b(i)$ is the smallest mean distance to another cluster,

694   and C is the set of all cell type labels.

696   For batch effect evaluation, ASW was computed using batch labels instead of cell types. A score of 0

697   indicates optimal mixing across batches, while deviations from 0 indicate batch effects. To facilitate

698   comparison, batch ASW values were converted by subtracting them from 1, yielding:

$$\text{ASW}_{\text{batch}} = 1 - \text{ASW}_{\text{raw}}$$

Thus, a score of 1 represents complete batch integration and 0 denotes total separation.

Cell Type Annotation Metrics

The performance of cell type annotation was evaluated by comparing predicted and true labels using three

complementary metrics: Accuracy, Macro-F1, and weighted average precision (Weighted AP). These

metrics jointly assess both overall correctness and per-class balance, providing a robust evaluation of

annotation performance across imbalanced cell populations.

The accuracy was defined as the proportion of correctly predicted labels among all cells:

$$Accuracy = \frac{1}{N} \sum_{i=1}^{N} \mathbb{I}(\hat{y}_i = y_i)$$

708   where N is the total number of cells, y_i is the true label, $\hat{y}_i$ is the predicted label, and $\mathbb{I}$ is the indicator

709   function.

711   To account for class imbalance, the Macro-F1 score was computed as the average of per-class F1 scores,

712   where each class-specific F1 is defined by the harmonic mean of its precision and recall:

$$\text{Macro} - \text{F1} = \frac{1}{n}\sum_{i=1}^{n}\frac{2P_i R_i}{P_i + R_i}$$

713   where P_i and R_i denote the precision and recall for class i, respectively.

715   In addition, to emphasize class frequency during evaluation, we computed the Weighted Average Precision

716   (Weighted AP), which weights each class-specific average precision AP_i by its relative cell proportion w_i:

$$\text{Weighted} = \sum_{i=1}^{n} w_i \times AP_i, \quad \text{where} \quad w_i = \frac{N_i}{\sum_j N_j}$$

Here, AP_i represents the area under the precision–recall curve for class i, and N_i is the number of cells

belonging to class i. Weighted AP therefore reflects both prediction quality and dataset composition,

offering a comprehensive measure of annotation performance.

Gene Regulatory Network Metrics

To assess the biological coherence of model-derived Gene Regulatory Networks (GRNs), we computed a

Functional Similarity Index (FSI) based on Gene Ontology (GO) Biological Process annotations. Genes

sharing at least one GO term were connected to form a reference adjacency matrix A_{GO}, while each model

provided a corresponding gene–gene network A_{model} derived from embedding proximity. The FSI

quantifies the agreement between model-inferred and GO-based connectivity using cosine similarity:

$$\text{FSI} = \frac{A_{\text{GO}} \cdot A_{\text{model}}}{\|A_{\text{GO}}\|_2 \|A_{\text{model}}\|_2}$$

Higher values indicate stronger alignment with functional gene relationships.

The k-means clustering algorithm was applied to the model-derived gene networks to identify gene

modules based on their connectivity patterns. By varying the number of clusters from 5 to 30 in increments

of 5, we explored the modular structure of reconstructed GRNs at different granularities. For each

clustering level, Gene Ontology (GO) enrichment analysis was performed on the resulting modules, and

the number of significantly enriched Biological Process terms $P_{\text{adj}} < 0.05$ was recorded. Models with

higher enrichment counts demonstrated stronger biological coherence, as illustrated in the GO (Biological

Process) enrichment curves across clustering resolutions.

Genetic Perturbation Metrics

To benchmark models on perturbation response prediction, we followed the GEARS evaluation protocol.

Performance was assessed using the Mean Squared Error (MSE) and Pearson Correlation Coefficient (PCC)

between predicted and experimentally observed differential gene expression values:

$$\mathrm{MSE} = \frac{1}{n} \sum_{i=1}^{n} (\hat{y}_i - y_i)^2$$

$$r = \frac{\sum_i (y_i - \bar{y})(\hat{y}_i - \bar{\hat{y}})}{\sqrt{\sum_i (y_i - \bar{y})^2 \sum_i (\hat{y}_i - \bar{\hat{y}})^2}}$$

743 where y_i and $\hat{y}_i$ denote the observed and predicted differential expressions, respectively.

745 **Drug Response Metrics**

746 For drug sensitivity prediction, we used preprocessed data from DeepCDR and evaluated model

747 performance using both the Pearson Correlation Coefficient (PCC) and the Spearman's Rank Correlation

748 Coefficient (SRCC) between predicted and actual IC50 values:

$$r_{\mathrm{PCC}} = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum_i (x_i - \bar{x})^2 \sum_i (y_i - \bar{y})^2}}$$

$$\rho_{\mathrm{SRCC}} = 1 - \frac{6 \sum_i d_i^2}{n(n^2 - 1)}$$

752 where d_i is the rank difference between predicted and observed IC50 values for the i-th drug--cell pair.

753 Higher PCC and SRCC values indicate stronger agreement between model predictions and experimental

754 outcomes.

Data availability

757 All benchmarking dataseting used in the research were collected from published sources, with detailed

758 descriptions provided in **Supplementary Table S1**.

Code availability

761 RegFormer is packaged, and distributed as an open-source, publicly available repository at

762 https://github.com/BGIResearch/RegFormer.

Funding

This work is supported by the National Natural Science Foundation for Young Scholars of China (32300526) and National Key R&D Program of China (2022YFC3400400).

Acknowledgement

We acknowledge the Stomics Cloud platform (https://cloud.stomics.tech/) for providing GPU computational resources. We thank the colleagues in our research group for inspiring discussion and their contributions.

Author contributions

Y.Z., Y.L. and S.F. conceptualized the study. L.H. was responsible for the model design and tool implementation. L.H., H.Q. Y.Z., Y.L. P.Q., and Z.G. performed data analysis and model evaluation. L.C., W.J., Q.C., Y.S., T.X. and Z.D. contributed key ideas and advice. L.H. wrote the manuscript. X.X, Y.L., S.F. and Y.Z. supervised the study.

Figure Legends

Figure 1. Overview of the RegFormer framework.

(A) The RegFormer pretraining and finetuning workflow. Large-scale pretraining on 26 million human cells was performed using graph topological sorting, value/token embeddings, and Mamba blocks, followed by downstream tasks including cell embedding, gene regulatory network (GRN) inference, cell type annotation, perturbation modeling, and drug response prediction.

(B) Graph topological sorting strategy for constructing regulatory dependencies from gene expression matrices.

(C) The embedding module design integrating value embeddings and gene encoders into sequence embeddings.

(D) Architecture of the Mamba block within the encoder.

(E) Pretraining schemes including masked value prediction, gene expression prediction, and regulatory role prediction.

Figure 2. Benchmarking RegFormer Embedding against single-cell foundation models.

(A) ASW scores and UMAP projection of cell types in the human lung dataset.

(B) ASW scores and UMAP projection of cell types in the human bone marrow dataset.

(C) ASW scores and UMAP projection of cell type and batch information in the human dendritic cell (humanDC) dataset.

(D) ASW scores and UMAP projection of cell type and batch information in the human pancreas (hPancreas) dataset.

Figure 3. Cell type annotation performance of RegFormer.

(A) Macro-F1 and accuracy across seven benchmark datasets, shown for RegFormer-10k, RegFormer-1.2k, Geneformer, scBERT, scGPT, and scFoundation.

(B) UMAP projections of cell type annotations on the Zheng68k dataset, comparing ground truth with predictions from different models.

(C) Confusion matrices of predicted versus true labels on Zheng68k across different models.

(D) Comparison of RegFormer-10k and RegFormer-1.2k in accuracy and Macro-F1 under scratch training and finetuning settings on Zheng68k dataset.

(E) Dot plots showing correspondence between predicted and true cell type labels for RegFormer-10k (left)

and RegFormer-1.2k (right), with dot size proportional to predicted label proportion, solid circles

representing finetune, and open circles representing scratch training.

Figure 4. Gene regulatory network inference with RegFormer.

(A) Workflow for GRN construction from gene expression profiles, using RegFormer embeddings and

cosine similarity to infer regulatory links.

(B) UMAP projection of cell types in the human lung dataset.

(C) Functional similarity index of inferred GRNs comparing RegFormer with existing single-cell

foundation models.

(D) Gene Ontology (GO, Biological Process) enrichment analysis across different numbers of gene

clusters, comparing results from RegFormer and other single-cell foundation models.

(E) Heatmaps showing regulon activity scores and transcription factor (TF) expression patterns across

diverse lung cell types.

(F) Case studies of GATA3 and SPI1 regulons, including UMAP visualizations of regulon scores (top), TF

expression (middle), and the corresponding inferred GRN subnetworks (bottom).

Figure 5. Perturbation modeling with RegFormer embeddings.

(A) Schematic of perturbation prediction using embeddings from single-cell foundation models combined

with the Gears model, integrating GeneID embeddings and perturbation embeddings to predict perturbed

states.

(B) Prediction performance on the Adamson CRISPR perturbation dataset, evaluated by mean squared

error (MSE, left) and Pearson correlation (right), comparing GEARS, scFoundation, scGPT, RegFormer-

1.2k, and RegFormer-10k.

(C) Example perturbation UFL1+ctrl: scatter plot of predicted versus true Δ expression (left) and gene

embedding cosine similarity between the perturbed TF and differentially expressed (DE) genes or other

genes (right).

(D) Prediction performance on the Norman CRISPR perturbation dataset, assessed by MSE (left) and

Pearson correlation (right).

(E) Example perturbation KMT2A+ctrl: scatter plot of predicted versus true Δ expression (left) and gene

embedding cosine similarity between the perturbed TF and differentially expressed (DE) genes or other

genes (right).

Figure 6. Drug response prediction using RegFormer.

(A) Overview of the IC50 prediction framework. RegFormer embeddings of cell line gene expression and precomputed embeddings of drug structure are integrated through a uniform graph convolutional network to predict drug sensitivity (IC50).

(B) Comparison of prediction performance across models, including deepCDR, scBERT, scGPT, Geneformer, scFoundation, RegFormer-1.2k, and RegFormer-10k, evaluated by Spearman (SRCC) and Pearson (PCC) correlation coefficients.

(C) Predicted versus true IC50 values for all drugs (left) and across all cancer types (right), showing high correlation between predicted and observed responses.

(D) Predicted versus true IC50 values for the top five most accurately predicted drugs, demonstrating strong linearity.

(E) Leave-drug-out blind test, where RegFormer consistently achieves higher PCC than DeepCDR across unseen drugs.

(F) Pathway-level interpretation of drug responses, highlighting TNF-α signaling via NF-κB (Bortezomib) and p53 pathway (SN-38), with normalized enrichment scores (NES) and FDR values shown.

Figure 1

Figure 2

A

B

C

D

A

B

C

D

E

Figure 4

Figure 5

Figure 6