Survival Reinforced Transfer Learning for Multicentric Proteomic Subtyping and Biomarker Discovery

Linhai Xie[1, 2 #], Pei Jiang[1, 2 #], Cheng Chang[1, 3*]

[1]*State Key Laboratory of Medical Proteomics, Beijing Proteome Research Center, National Center for Protein Sciences (Beijing), Beijing Institute of Lifeomics, Beijing 102206, China.*

[2]*International Academy of Phronesis Medicine (Guangdong), Guangdong, 510320, China.*

[3]*Research Unit of Proteomics Driven Cancer Precision Medicine, Chinese Academy of Medical Sciences, Beijing, China.*

\# Equal contribution.

*Corresponding authors

Email: changcheng@ncpsb.org.cn (Cheng C)

Running title: *Xie L et al / Transfer Learning for Proteomic Subtyping*

The number of words: 9918

The number of references: 45

The number of figures: 6

The number of supplementary figures: 13

The number of supplementary tables: 2

The number of letters in the article title: 98

The number of letters in the running title: 56

The number of keywords: 6

The number of words in Abstract: 163

Abstract

Omics-based molecular subtyping in large-scale and multicentric cohort studies is a prerequisite for proteomics-driven precision medicine (PDPM). However, keeping the subtypes with robust molecular features and significant associations with prognosis among different cohorts is challenging due to the biological heterogeneity and technical inconsistency. Herein, we propose a subtyping algorithm, named Survival Reinforced Patient Stratification (SRPS), to adapt the known subtypes from the discovery cohort to another by simultaneously preserving the distinct prognosis and molecular characteristics of each subtype. SRPS has been benchmarked on simulated and real-world datasets, where it shows a 12% increase in classification accuracy and possesses the best prognostic discriminations. Moreover, based on the calculated subtype significance score, an 'unpopular' protein, Peptidylprolyl Isomerase C (PPIC), was identified as the top-1 remarkable protein for subtyping the hepatocellular carcinoma (HCC) patients with the worst prognosis. Eventually, PPIC was experimentally proved to be a pro-cancer protein in HCC, confirming our work as a practice of interpretable machine learning guided biological discovery in PDPM research.

Keywords: SRPS; Transfer learning; Subtyping; Proteomics; Biomarker discovery; PPIC

Introduction

Proteomic subtyping has been broadly applied in oncology research on large cohorts with an important goal of stratifying patients with inconsistent levels of prognosis according to the proteomic features[1–6]. Thorough analysis of differentially expressed proteins between subtypes is able to suggest the potential prognosis biomarkers and drug targets for clinical applications and therefore the research paradigm of proteomics-driven precision medicine (PDPM) was proposed[1]. However, to deliver the molecular stratification of patients from a scientific discovery to a clinical guidance, a fundamental step is to expand its validity to multiple independent clinical cohorts[7–10] to eliminate the sample bias in a single cohort with a relatively small sample size. Unfortunately, such an expansion of existing molecular subtypes on multiple cohorts is difficult due to unignorable inter-cohort data heterogeneity that stems from both biological divergence and technical inconsistency. Hence, the problem we investigate in this manuscript is how to transfer prognosis-discriminative molecular subtypes from a source cohort to a target cohort which we term as cohort adaptation for molecular subtyping in large-scale and multicentric cohorts.

Commonly applied supervised classification approaches[11,12] lack the generalization ability between data with biased drifts. Correspondingly, batch effect removal algorithms[13,14] were proposed for integrating data partially corrupted with batch effects, albeit with the risk of over correction that may lead to unreliable downstream analysis[15]. Another alternative is domain adaptation technique[16–19] in transfer learning. It can search for data representations that are invariant between cohorts while distinct for each subtype in the source cohort. Nevertheless, its drawback in our scenario is not being able to effectively preserve the prognosis discrimination of subtypes from the source cohort to the target cohort.

As shown in **Figure 1**, we introduce a novel algorithm named Survival Reinforced Patient Stratification (SRPS) for adapting prognostic discriminative patient stratification from the source cohort to a target cohort. SRPS optimizes a classifier to predict the subtype of a patient only based on the molecular profile through two learning paradigms. In the source cohort, it learns the biological features of the known subtypes through supervised learning; while in the target cohort, it learns to maximize the prognostic discrimination between subtypes through reinforcement learning. Hence, SRPS can preserve both the proteomic feature and prognostic significance of each subtype when transferring the subtypes between cohorts.

The performance of SRPS has been benchmarked on both synthetic and realistic datasets (Table S1) against 5 other baseline methods. Experimental results on synthetic datasets corroborate that SRPS outperformed baseline methods by a large margin, 12% higher accuracy and almost 100% greater Log-rank score than the baselines method in average on the target cohort with significant batch effects. As for the real-world datasets, after demonstrating comparable accuracy on the source cohort and ssGSEA similarity between source and target cohorts, SRPS achieves the highest survival discrimination in both overall survival (OS) and recurrence-free survival (RFS) clinical outcomes.

Furthermore, model explanation is always desired for biological and clinical application of machine

learning[20,21] and several strategies[22–24] have been proposed to interpret complicated models. For this purpose, we

designed the network architecture of the classifier with only a single dense layer which enabled a straightforward

translation of model parameters with a subtype significance score. By applying the scoring function to models that

transferred subtypes between two hepatocellular carcinoma (HCC) cohorts, we observed insightful reasons for the

enhanced prognosis discrimination of the classifier. It allocates higher weights on proteins which are originally

discriminative in prognosis. More importantly, the scoring function indicated Peptidylprolyl Isomerase C (PPIC) as

the most significant protein when subtyping a group of HCC patients with the worst prognosis. It was able to

dissect patients into two groups with significantly different prognosis on two HCC cohorts for both OS and RFS,

and for the first time, its promotion in proliferation, migration and colony formation of HCC cells were proved on

cell lines experiments. These results suggest a potential clinical application of PPIC as a prognostic biomarker.

Results

SRPS improves the classification accuracy for prognosis-discriminative subtypes when batch effects exist

between cohorts.

SRPS aims at improving subtyping accuracy by using the correlation between lifetimes and subtypes through deep

reinforcement learning. It lays on two basic assumptions: 1) feature-based subtyping can be improved by exploiting

prognosis information; 2) prognosis information can be effectively exploited through deep reinforcement learning.

To prove them, 121 pairs of toy datasets (Figure S1) were simulated, and three different patient stratification

strategies are compared in various levels of batch effect between source and target cohorts and the correlation

between subtypes and lifetimes (survival correlation). The performance of feature-based stratification strategy

based on supervised learning is only affected by the batch effect (**Figure 2**A). On the contrary, the accuracy of

survival-based stratification method (Survival), which divides patients with a boundary at 30 of lifetime in the

target cohort, is only related to the survival correlation (Figure 2B). SRPS (Figure 2C) shows a more robust

performance either with severe batch effects as well as low survival correlation due to the consideration of both

features and prognosis information.

According to the residual accuracy maps between each two strategies, the survival-based method significantly

outperforms DNN within the upper right area ($p<0.0001$) with strong survival correlation and large batch effects

(Figure 2D), it proves that it is possible to improve classification accuracy in this situation by only considering

prognosis information. By contrast, the comparison between SRPS and DNN (Figure 2E) not only shows a

significant improvement within upper right area ($p<0.0001$), but also for the whole area ($p<0.0001$). Furthermore, it

shows no significant performance inferiority within the upper right area compared to survival-based method

(Figure 2F). It proves that SRPS can highly exploit the prognosis information through deep reinforcement learning.

SRPS outperforms comparative approaches and ablated models in simulated datasets.

Here we lend credence to the state-of-the-art (SOTA) performance of SRPS on 2 pairs of simulated datasets (Figure

S2) by comparing it with 5 competitive methods, including Random Forests (RF)[11] and Deep Neural Network

(DNN)[12] for supervised learning, RF combined with Harmony (RFH)[13] and Deep Adversarial Neural Network

(DANN)[16] for batch effect removal and domain adaptation techniques, semi-deepCLife[25] for prognosis-guided

approach. Then model ablation study was carried out by removing a certain component of reinforcement learning,

i.e., SRPS (no baseline), or replacing reinforcement learning with an alternative approach, i.e., SRPS (soft). The

evaluation metrics include classification accuracy, ssGSEA similarity, log-rank score and C-index. The mean and

standard deviation of all metrics were reported according to a 5-fold cross-validation test which was repeated for 5

times.

Comparison with baseline methods. When testing on datasets without batch effect, all these algorithms exhibit

excellent prediction accuracy (above 0.9) on both source and target cohorts, showing their generalization ability on

samples drawn from the similar distribution as training data (**Figure 3**A). However, their performance degenerates

to varying degrees when batch effect exists (Figure 3D).

As the pure supervised learning methods, Random Forests (RF) and Deep Neural Network (DNN) have

obvious but reasonable drop of accuracy on the target cohort with a biased distribution drift. RF combined with

Harmony (RFH) enhances accuracy compared to the above two approaches on the target cohort, nonetheless, with a

non-trivial accuracy drop on source cohort. Its attempts to remove batch effects diminishes the biological feature of

each subtype which may partially stem from the fact of not using the labels in the source cohort. Domain

Adversarial Neural Network (DANN) is the most powerful baseline approach, though, still falls behind SRPS

especially on the target cohort. Although there are other domain adaptation approaches implementing more

sophisticated learning mechanisms such as conditional domain adversarial network (CDAN)[26] and maximum

classifier discrepancy (MCD)[17], they did not achieve higher subtyping accuracy through our observations (Figure

S3). Semi-deepCLife, as the most similar competitive algorithm to SRPS, possesses an accuracy only comparative

to DANN. There might be two reasons. First, the survival loss of deepCLife does not specify which subtype should

have a superior prognosis. This may incur conflicts with the label-based supervision loss during training. The other

one could be the lack of random exploration in stochastic gradient descents with a large batch which was required

for an accurate estimation of lifetime distributions. Therefore, the straightforward compound of deepCLife and

supervised learning is not an effective solution. In contrast, SRPS outperforms all competing methods by a large

margin when batch effects exist between cohorts. More specifically, it improves the target domain accuracy by 12%

compared to the second-ranked model, DANN.

The diagnostic discrimination ability of each model is also illustrated. For the case without batch effect

(Figure 3B and 3C), all methods have high log-rank score and C-index, since they have shown accurate prediction

in subtypes which are strongly correlated to prognosis, both for source and target cohorts. On the contrary, their

diagnostic discrimination decreases remarkably on the target cohort with large batch effects (Figure 3E and 3F). As

expected, SRPS enhances the log-rank score by more than 100% compared to the best baseline model.

Model ablation study. Here we verified the contribution of two critical reinforcement learning-related components.

We firstly eliminated the reward baseline estimator which is important for gradient stabilization in many policy

gradient-based reinforcement learning algorithms[27]. The gradients estimated by REINFORCE[28] are calculated from

random samples and always cause noisy rewards. As shown in Figure. 3, the accuracy, log-rank score and C-index

on the target cohort reported for SRPS (no baseline) have higher standard deviation than the full SRPS method,

indicating the high variance during the learning procedure of the ablated model.

The other ablation model is to replace the entire reinforcement learning component with soft relaxation as in

deepCLife which is an alternative for dealing with the non-differentiable component in a neural network. The

drawback of applying soft relaxation in our situation is possibly due to the dilemma of batch size selection during

training as mentioned above. As a result, this design corrupted the performance of SRPS (Figure 3).

SRPS outperforms comparatives approaches in real-world cohort adaptations of proteomic subtypes.

In this section, we evaluated all approaches in two different cohort adaptation scenarios with three hepatocellular

carcinoma (HCC) cohorts and a lung adenocarcinoma (LUAD) cohort to demonstrate the SOTA performance of

SRPS. Each cohort is provided with proteomic profiles of all samples and the time and status of clinical outcomes

including overall survival (OS) and recurrence-free survival (RFS).

Jiang et al.'s cohort[1] recruited 101 early stages (0-A) Chinese HCC patients according to Barcelona Clinic

Liver Cancer (BCLC) staging system[29]. According to the original paper of Jiang et al. cohort, all patients in this

cohort were classified into 3 subtypes with different proteomic features and prognosis as visualized in Figure S4,

which will be transferred to other target cohorts as the known subtype. Gao et al.'s cohort[2] involved 159 Chinese

patients with broader BCLC stages, additionally including stage B and stage C. Xing et al.'s cohort[30] included 152

Chinese patients with the same range of BCLC stages as Gao et al.'s cohort. Xu et al.'s cohort[5] recruited 103

Chinese patients with another type of cancer, i.e., LUAD. According to Figure S5, the proteomic profile matrices of

these cohorts exhibit large inter-cohort heterogeneity.

Transfer HCC subtypes to other HCC cohorts with broader cancer stages. The first experiment is to transfer the

proteomic subtyping of HCC patients from Jiang et al.'s cohort to Gao et al.'s cohort and Xing et al.'s cohort

respectively. **Figure 4**A and B show the testing results. Except RFH, all approaches share similar prediction

accuracy on the source cohort. Deep learning-based methods (DNN, DANN, semi-deepCLife and SRPS) have

comparatively higher ssGSEA similarities of the classified subtypes between source and target cohorts, indicating

that neural networks learn more generalizable features of each subtype. A similar trend remains for the Log-rank

score on OS. Pure supervised learning or domain adaptation techniques such as DNN and DANN do not perform
well in this metric mainly due to the reason that the RFS distributions of all subtypes in the source cohort are
originally not significantly different. Therefore, this attribution is naturally inherited by its prediction on the target
cohort. Semi-deepCLife was also designed to improve discrimination through exploiting two kinds of survival
information together. It performed comparatively to SRPS in C-index. In the end, SRPS exhibits powerful
discrimination ability in terms of both OS and RFS with comparable classification accuracy on source cohort and
ssGSEA similarity between two cohorts. Exemplary results of SRPS among 5 repeated tests on Gao et al.'s cohort
and Xing et al.'s cohort are visualized in Figure S6 and S7. It is worth noting that the clinically acceptable
prognosis discrimination should reach a log-rank score above $-log10(0.05) \approx 1.3$.

Transfer HCC subtypes to a LUAD cohort. Next, we attempted to transfer subtypes from Jiang et al.'s HCC cohort
to Xu et al.'s LUAD cohort (Figure 4C). Among all methods, SRPS again exhibits the highest prognostic
discrimination in OS and RFS, demonstrating its superiority in optimizing prognosis discrimination of subtypes.
However, we find that the ssGSEA similarities of all methods are lower than the similarities when transferring
between two HCC cohorts. It is reasonable since the onset of cancer at different organs can have drastically
heterogeneous biological processes. Thus, HCC patients and LUAD patients with consistent prognosis are unlikely
to share similar proteomic patterns between their tumor samples. This observation infers that although SRPS
enhances the probability of detecting biologically and prognostically consistent subtypes between two cohorts, it
compromises by reducing the biological consistency, when the original subtypes are unlikely to exist in the new
cohort naturally. Its discoveries obey the underlying biological facts. An exemplary result of SRPS among 5
repeated tests on Xu et al.'s cohort can be visualized in Figure S8.

PPIC is identified as a significant protein through model interpretation with subtype significance score.
The interpretability of models is of importance in biomedical research, where a common solution is to keep the
model as simple as possible. Therefore, the classifier utilized in SRPS for real-word proteomic experiments is a
single layer neural network with a parameter matrix shaped as $S \times D$ and is activated by a soft-max layer for
probabilistic outputs. Based on this simple model, we proposed a subtype significance metric named $\Delta weight$ to
indicate the contribution of each protein to classify patients into a specific subtype. It is worth noting that the scale
of the expression of each protein has been processed with z-score normalization so that the contribution of each
protein for subtyping does not depend on the range of its original expressions. The total number of $\Delta weight$
values equal to the number of values in the model parameter matrix. A detailed definition of $\Delta weight$ is provided
in Methods.
Based on the experimental results to transfer HCC subtypes from Jiang et al.'s cohort to Gao et al.'s cohort, we
investigated the weight matrix of all 25 classifier models of SRPS (5 random repeats $\times$ 5 folds) and focused on the

subtype S-III of HCC patients since it indicates the worst prognosis after surgery. The subtype significance score

averaged among all 25 models was used in the following analysis to alleviate the influence of random initialization.

Additionally, since the subtype significance score $\Delta weight$ is defined based on the model weights which vary

during the training procedure, we carry out stability experiments. Figure S9 informs that the rank of the top-10

proteins based on the average subtype significance score becomes stable quickly within the training phase. Besides,

the relationship between its ranking stability and the number of models required has been discussed in Figure S10.

SRPS classifies patients with prognosis-discriminative features. We first evaluated the correlation between the

subtype significance score of SRPS classifier model and prognosis discrimination of each protein in Gao et al.'s

cohort. The prognosis discrimination of each protein was measured by the coefficient of a univariate Cox

regression model and the correlation was estimated by the linear regression. Consequently, in terms of OS, the

$\Delta weight$ of SRPS model has a correlation (r=0.60) similar to that of DNN (r=0.55) (**Figure 5**A) mainly because

that DNN has already achieved good discrimination in OS (Figure 4A), albeit, SRPS shows much higher

correlation (r=0.55 vs r=0.32) in terms of RFS (Figure 5A), as it enhances the discrimination of RFS by a large

margin (Figure 4A). This result informs us that SRPS improves the prognostic discrimination of subtypes by

allocating higher weights on features that are more discriminative in prognosis during training than the method

without exploiting survival information.

SRPS encourages the discovery of proteins different from differential expression analysis. A similar and common

approach to identifying signature proteins for each subtype is Differential Expression Analysis (DEA) which

usually serves as a clue for biomarker discovery[1,2]. Hence, we calculated correlation between $\Delta weight$ and log2

fold change value of protein expression for S-III in each cohort where the latter is an essential metric for DEA

(Figure 5B). It exhibits a positive correlation and, more importantly, obvious discrepancy in proteins with peak

values, i.e., top 30 proteins with the highest subtype significance scores do not possess correspondingly pinnacle

log2 fold change values. This observation infers a potential ability of subtype significance scores to uncover

valuable proteins which might be ignored by classical DEA-based approaches.

PPIC identified by SRPS is an under-explored HCC-related protein and is discriminative in prognosis. We further

investigate the 30 top-ranked proteins about whether they or their corresponding genes have been formally reported

with an association with HCC in research publications (Figure 5C). As a result, 24 of 30 proteins were found with

literature evidence to support their relevance with HCC progress, interpreting that SRPS classifies patients by

exploiting biological meaningful features. Among the six under-explored HCC-related proteins, limited functional

evidence has been reported for **CORO7** (Coronin-7) and **WASHC3** (WASH complex subunit 3) in cancer types.

However, **PPIC** (Peptidyl-prolyl cis-trans isomerase), **TPPP3** (Tubulin polymerization-promoting protein family

member 3), **RHOG** (Rho-related GTP-binding protein RhoG), and **KLC1** (Kinesin light chain 1) have been shown
to play roles in cancer progression, such as cell proliferation and metastasis, in other cancer types (Table S2). These
findings suggest their potential involvement in HCC. More importantly, we found that PPIC protein, which
corresponds to the highest subtype significance score has received little attention in HCC-related research, thus
triggering our deeper investigation into that protein.

The survival analysis in Jiang et al.'s cohort and Gao et al.'s cohort for both OS and RFS by stratifying patients
according to the expression of PPIC shows its prognosis discrimination ability in these two clinical outcomes
(Figure 5D). The threshold was independently grid-searched in each case and the value resulting in the largest
significance of log-rank test was selected. As shown in results, PPIC is discriminative in prognosis and can
potentially be developed into a biomarker of HCC patients with poor survivals.

PPIC functions as a pro-cancer protein in HCC. Although PPIC was reported to be highly expressed in several
cancers, its role in HCC remains elusive. To determine the potential functions of PPIC in HCC, we knocked down
PPIC expression using two different siRNAs targeting PPIC in HCC cell lines. As shown in **Figure 6**A, the PPIC
mRNA expression was significantly reduced in cells treated with the siRNAs targeting PPIC respectively. Notably,
as shown in Figure 6B-C, PPIC knockdown profoundly inhibited cell proliferation and colony formation in two
HCC cell lines-Huh7 and MHCC-LM6, which suggests that PPIC promotes HCC progression. Similarly,
knockdown of PPIC also significantly inhibited cell colony formation in other two HCC cell lines-Hep3B and
MHCC-97H in Figure S11A-B. Besides, Figure S11C shows that cell migration was strongly inhibited by PPIC
knockdown in Huh7 cells. Thus, these results indicate that PPIC functions as a pro-cancer protein in HCC, which is
consistent with the results from SRPS, and the molecular mechanism behind it needs further investigation.

269 Discussion

Multicenter study is essential in clinical oncology research to eliminate the biological and environmental biases of
the sampled population. Therefore, to deliver the practical value of PDPM to clinical applications, expanding and
validating the discoveries from a single cohort to multiple ones becomes an inevitable request. However, since
proteins are the minimal functioning units of the human body system, proteome is a more real-time observation of
the disease progress compared to genome and transcriptome, therefore it exhibits large data heterogeneity between
cohorts.

We proposed the SRPS algorithm to adapt known proteomic subtypes from a labeled source cohort to the
unlabeled target cohort. Unlike existing batch effect removal or domain adaptation techniques which seek for
indistinguishable representations between batches/domains with the risk of ignoring essential biological difference,
SRPS unifies the classification features between cohorts by preserving the prognosis discrimination of subtypes
which is important for clinical applications. Through experiments on simulated and real-world data, we

demonstrated the effectiveness of guiding the subtyping with survival information through reinforcement learning.

Deep reinforcement learning has shown great success in optimizing a neural network with a self-defined

reward function by encouraging desired behaviors and penalizing undesired ones without explicit labels as in

gaming[31], robotics[32] and drug design[33]. It also provides a solution to estimate gradients of non-differentiable[34]

evaluations of the predictions, alongside soft approximation[25,34]/relaxation[35] as an alternative. By comparing SRPS

with semi-deepCLife or SRPS (soft), we have witnessed higher performance in prognosis discrimination of the

former option and, in general, this strategy can be applied to any objective due to the high degree-of-freedom in

designing the reward function. For instance, it is possible to reinforce the ssGSEA similarity of the subtypes

between two cohorts by incorporating it into the reward function.

Since survival information has been proved effective in guiding the learning process of subtyping,

sophisticated architectures of the neural network become unnecessary to achieve acceptable subtyping performance.

As a result, it enables the use of a single dense layer in the classifier which brings simplicity in model interpretation

and alleviates the problem of overfitting. Consequently, PPIC was discovered as a critical protein in identifying

HCC patients with poor prognosis.

Here, we demonstrate that PPIC is required for HCC cancer cell proliferation and colony formation, indicating

its pro-cancer functions. Though PPIC was reported to be involved in endoplasmic reticulum redox homeostasis

and hepatic stellate cell activation[36,37], its key molecular functions and direct substrates in HCC remain to be further

elucidated. Thus, our results showed that PPIC is a powerful prognostic marker for HCC and the molecular

revelation of its pro-cancer mechanism might contribute to HCC treatment.

Despite its promising results, SRPS has certain limitations. Currently, SRPS is restricted to transferring known

subtypes from a source cohort to target cohorts and does not have the capability to discover unified new subtypes

across multiple cohorts. In future work, we aim to address this limitation by integrating SRPS with unsupervised

clustering methods, enabling the discovery of novel subtypes from diverse datasets.

Additionally, while we validated the role of PPIC in this study, other subtype-significant proteins identified by

SRPS have yet to be experimentally examined. Future efforts will focus on validating these proteins through

functional experiments, which may further elucidate their biological relevance and clinical utility in cancer

subtyping.

Methods

Survival Reinforced Patient Stratification. As illustrated in Figure 1B, the training framework of SRPS consists

of a subtype classifier and a reward baseline estimator. The classifier predicts the subtyping probabilities of patients

given the proteomic profile matrix. For data with subtype labels in the source cohort, the predicted probability as

well as the provided ground truth is used to calculate a cross-entropy loss. By minimizing this objective, the

classifier can learn the principle proteomic pattern of each subtype and stratify patients according to it.

More specifically, given $x_i \in R^D$ to represent the D dimensional proteomic profile vector of sample $i \in I$

where I is the patient set, a prediction vector is calculated as:

317
$$p_i = f_{sm}(f_c(x_i)|\Theta). \tag{1}$$

318　Each element $p_i^{(s)}$ in p_i represents the probability of the patient i to be identified as the subtype $s \in$

319　$\{1, 2, ..., S\}$, supposing S different subtypes in total. $f_{sm}(\cdot)$ and $f_c(\cdot|\Theta)$ stand for the soft-max activation

320　function and the neural network classifier parameterized with Θ respectively. With the one-hot encoded label y_i

321　in source cohort, the cross-entropy loss is calculated as:

322
$$L_{CE} = -\sum_{s \in S} y_i^{(s)} \log\left(p_i^{(s)}\right). \tag{2}$$

323　　　　Meanwhile, the classifier adjusts its prediction with the guidance of prognostic information of each patient on

324　the target cohort through an on-policy reinforcement learning algorithm, REINFORCE[28]. It samples a subtype

325　prediction $\hat{y}_i$ of patient i from a multinomial distribution parameterized by the predicted subtype probability p_i

326　as:

327
$$\hat{y}_i \sim P_{multinomial}(s|p_i). \tag{3}$$

328　Such a random sampling strategy encourages the exploration of better classification boundaries and is only used for

329　training. The subtype prediction for inference is deterministic with an argmax operation given predicted

330　probabilities p. Then, for a specific subtype s we calculate the restricted mean survival time (RMST) τ_s. This

331　calculation is based on two aspects related to each patient within the population of subtype s: one is the lifetime t_i

332　of the patient, and the other is the observation of the patient's survival status, which we denote as d_i.

333
$$\tau_s = f_{RMST}(\{(t_i, d_i)|\hat{y}_i = s\}). \tag{4}$$

334　The detailed calculation of f_{RMST} is provided in latter sections. All RMST values formulate a reward r to assess

335　the prognosis discrimination of the predicted subtypes as:

336
$$r = f_{min}(\{\tau_a - \tau_b \,|a, b \in \{1, 2, ...S\}, a < b\}), \tag{5}$$

337　where f_{min} outputs the minimal value from a set and without the loss of generality, we use a smaller number to

338　annotate the subtype with a better prognosis which is known a priori from the source cohort. However, since such

339　behavior evaluation with rewards is usually noisy, a reward baseline is required for stabilization[27] which includes

340　an input-dependent component b_i and an input-independent component b_c as:

341
$$R = r - b_i - b_c, \tag{6}$$

342
$$b_i = f_b(x_i|\phi), \tag{7}$$

343　where f_b represents a neural network predictor with ϕ as parameters and both types of baseline components are

344　adjusted by minimizing the baseline loss:

345
$$L_{BL} = ||r - b_i - b_c||, \tag{8}$$

346　where $||\cdot||$ is the L2 norm. Afterwards, the predicted subtype probabilities, the sampled subtypes and the

347　baseline-stabilized rewards produce an approximation of the policy gradient[27,28] as:

348
$$\nabla_\theta J \approx \nabla_\theta \frac{1}{N} \sum_{i=1}^{N} \log\left(f_c(x_i|\theta)\right) R, \tag{9}$$

349   where N is the number of patients. It regulates the classifier with the aim of improving its prognostic

350   discrimination. The above objective can be implemented with a cross-entropy loss given the predicted probability

351   p and the sampled prediction $\hat{y}$ as:

352
$$L_{RE} = -\frac{1}{N}\sum_{i=1}^{N}\sum_{s\in S}\hat{y}_i^{(s)}\log\left(p_i^{(s)}\right)R. \tag{10}$$

353   The final loss function for training the classifier is:

354
$$L = \omega_1 L_{CE} + \omega_2 L_{RE} \tag{11}$$

where ω_1 and ω_2 are coefficients between 0 and 1. Note that above procedure describes the training phase of the

classifier and there is no need for survival information during inference phase.

The calculation of RMST is simple, but it requires the predicted subtyping results for all the patients in the

mini-batch, which is a discrete variable and is undifferentiable. Hence, we exploit the on-policy reinforcement

learning algorithm REINFORCE by taking [34] as a reference to approximate the true gradients and keep an

end-to-end training procedure. Furthermore, the reason for using an on-policy algorithm is that it is simpler for

implementation compared to an off-policy algorithm which needs more elaborate tuning on the replay buffer and

the exploration strategy.

Simulated dataset generation. 121 pairs of toy datasets were created to examine two basic assumptions about

SRPS. The original pair of datasets (top in Figure S1) involves a source and a target cohort with identical features

x_{origin} whose values ranges between $[0,1]$ and the feature dimension is 20. Normally distributed random noise

σ_{noise} was added to the features as batch effects between the source and target cohorts. The mean of the noise

vector was uniformly sampled from the interval of $[0,1]$ independently along each dimension and the standard

deviation was set to 0.2. The resulted feature vector is $x_{origin} + \alpha\sigma_{noise}$ where we gradually increase the noise

weight α from 0 to 4 with a step of 0.4, corresponding to the lowest batch effect scale 0 to the strongest scale 1

respectively as shown in Figure 2. The survival time of all patients was strictly divided according to the subtype

labels where S-I patients all survive longer than 30 months and S-II patients die before 30 months without any

censored value for simplicity. To decrease the relative survival correlation between the subtype and survival times

which leads to a weaker prognostic discrimination of subtypes we randomly swap the survival time of patients

between two subtypes. The swapping ratio ranges from 0 to 0.2 with a step of 0.02, corresponding to the strongest

relative correlation 1 and weakest relative correlation 0 respectively as shown in Figure 2.

The simulated datasets for benchmarking (Figure S2) are generated with the R package Splatter[38], with the

function splatSimulate. We generate two sets of datasets with/without batch effects. In each dataset we simulate

1000 total samples with 3 different subtypes which are divided into 2 batches. The batch effect between batches are

controlled with two parameters batch.facLoc and batch.facScale which are both set to 0.01 for no batch effects and

2 for large batch effects. The feature size of all samples is set to 1000. The survival data are generated with the R

package Simsurv[39], following the Weibull distribution with the coefficients as $(\lambda = 0.005, \gamma = 0.5)$. We carried

out two experiments to validate the reliability of the simulated data. Figure S12 demonstrates that the distributional

divergence between the simulated data and a real-world HCC cohort is as close as the divergence between two

real-world HCC cohorts. Besides, Figure S13 indicates that the difficulty of predicting patient prognosis, measured

with C-index by using a random survival forest model, between the simulated data and a real-world cohort is also

comparable.

Accuracy maps on the toy datasets. We generated 121 pairs of toy datasets to examine the influence of batch

effects between the source and target datasets, as well as the correlation between subtype labels and survival times

in the target cohort (termed survival correlation). Details of the dataset generation process are described in the

Simulated dataset generation section. The 121 pairs of datasets are a Cartesian product of 11 batch effect levels

and 11 survival correlation levels. Each cube in the accuracy maps in Figure 2 represents the result of experiments

conducted on a specific pair of source and target datasets, with batch effect and survival correlation levels indicated

by the axes of the sub-figures. The x-axis represents increasing batch effect levels, and the y-axis represents

increasing survival correlation levels.

For each experiment, the evaluation metric is prediction accuracy, which we define as:

$$Prediction\ Accuracy = \frac{Correct\ Predictions}{Samle\ Size}$$

where accuracy is calculated on 20% of the samples in the target cohort not used for model training. This definition

is consistently applied to all experiments involving synthesized datasets.

Three accuracy maps (Figure 2A-C) were constructed for different subtyping strategies:

1. **Figure 2A (Feature-based strategy):** A Deep Neural Network (DNN) trained on features in the source cohort

predicts two subtypes.

2. **Figure 2B (Survival-based strategy):** Patients in the target cohort are stratified by thresholding survival times

at 30 months. This strategy, while theoretical due to its reliance on unavailable survival data for at-risk patients,

serves as a reference for fully exploiting prognosis information.

3. **Figure 2C (SRPS):** Our proposed algorithm.

To further compare these strategies, three residual accuracy maps (Figure 2D-F) were generated via

element-wise subtraction between accuracy maps. For example, Figure 2D was created by subtracting the accuracy

of the survival-based strategy from that of SRPS across all 121 dataset pairs.

Real-world proteomic data preprocessing. The raw proteomic expression matrix of each cohort is preprocessed

before experiments.   Let the rows and columns of the matrix indicate samples and proteins respectively. The

preprocessing contains following steps: **1)** Each row of the profile matrix was normalized with the quantile

normalization; **2)** All the proteins expressed in less than 30% of the samples were filtered; **3)** All missing values

were imputed with zero; **4)** Each column was normalized with Z-score normalization; **5)** We use the intersection of

the proteins simultaneously identified in both source and target cohorts; **6)** The resulted protein sets in two

scenarios are then intersected with the signature protein sets suggested by the paper of source cohorts respectively.

Consequently, when transferring the subtypes from Jiang et al.'s cohort to other two HCC cohorts or to Xu et

al.'s LUAD cohort we used the signature proteins suggested from the literature[1] and the feature dimension of

proteomic profile matrices is 1097. (Table S1)

Restricted mean survival time (RMST). Given a series of paired survival times $T = T_1, T_2, ..., T_n$ and status

(dead or not) $D = \{D_1, D_2, ..., D_n\}$ of n patients, we can firstly estimate a Kaplan-Meier (KM) curve which

consists of successive survival probabilities S_t at each time within the time interval $t = \{0, t_1, t_2, ..., t_{max}\}$. At

$t = t_0$, we have $S_0 = 1$, and the consecutive probabilities can be extrapolated as follows:

$$S_{t+1} = S_t \times \left(1 - \frac{d_t}{n_t}\right) \tag{12}$$

where d_t counts the number of subjects died between $[t, t + 1]$ and n_t counts the number of subjects living at

the start. Note that subjects who are lost are regarded as censored and are not involved in n_t. The RMST is

calculated as the area under this KM curve within a restricted time interval, i.e. from 0 to 60 months in our

experiments.

Using the restricted mean survival time (RMST) is because of its simplicity and directionality. When

compared with other divergence metrics such as the Kullback-Leibler, the Maximum-Mean Discrepancy (MMD)

and the Kuiper test that only tell the distance between the survival distribution of two subtypes as mentioned in [25],

the difference between the RMST of two subtypes is simple to calculate and clearly indicates which one holds a

better prognosis. Therefore, it can largely boost the learning efficiency from the prognosis information.

Training settings of SRPS. The classifier of SRPS consists of only one linear layer with l1 regularization

(coefficient=ϕ) and dropout where drop rate is set to ρ_{su} for supervised learning and ρ_{rl} for reinforcement

learning. The output dimension equals the number of subtypes. The baseline estimator consists of 3 layers with n_h

neurons in each hidden layer with sigmoid function as activation except the output layer. The output dimension is 1.

Both models are optimized with Adam optimizers given learning rate α_{rl} and α_{bl} respectively. The models

are trained with the full batch for 10000 episodes with/without using early stop ($ES = true/false$) which save

the model with the highest $\Delta RMST$ on validation set.

Hyper-parameters are manually selected according to the performance on validation set within the possible

combinations of following settings: $n_h = \{10,100\}, \omega_1 = \{0.1, 0.01, 0.001\}, \omega_2 = 1, \phi = \{10^{-5}, 10^{-4}\}, \rho_{su} =$

$\{0, 0.3, 0.8\}, \rho_{rl} = \{0, 0.2\}, ES = \{true, false\}$. Given all possible combinations of hyper-parameters, we select the

best model with different criteria on simulated and real-world datasets respectively. For testing the model with

simulated data, we apply the validation accuracy as the selection criteria. When testing the model on real-word

datasets, we pick the model with the highest Log-rank score (OS) and a ssGSEA similarity score no less than 0.5 on

the validation set, since there is no subtyping label for the target dataset.

The model and training process was implemented with Python and Tensorflow library and was deployed on a

server equipped with an InteI XII Gold 6242R CPU and a Quadro GV100 GPU. Each run of training lasted about 2

minutes.

Single sample gene enrichment score analysis (ssGSEA) similarity. For each patient in the real-word proteomic

datasets, functional enrichment analysis[40]. was performed using the ssGSEA algorithm implemented in the R

package GSVA[41]. The quantile normalized protein expression matrix was imported to GSVA to calculate the

ssGSEA scores for each gene set with at least ten overlapping genes. The interested gene set was provided in the

literature[15]. After obtaining the enrichment scores of interested gene set of each patient, we calculated the average

enrichment score for each subtype and estimated the similarity between cohorts with the cosine similarity. The final

similarity score between the two cohorts is the average similarity of all subtypes.

Log-rank score and C-index. The log-rank score was defined as $-log_{10}(P)$ based on the P value of a log-rank

test[42], which indicates how likely all groups having the same lifetime distribution. A higher score means better

prognosis discrimination. Concordance index (C-index)[43] calculates the fraction of pairs of subjects for which the

model predicts the correct order of survival while also considering censoring. 0.5 indicates random predictions and

1.0 means perfect predictions. It was calculated by checking the concordance between the survival time and

probability difference between subtypes with the best and worst survivals, i.e., $p_i^{(1)} - p_i^{(3)}$ where p_i is the

predicted probability vector of patient i and its first and third dimensions represent the probability of being S-I

(best prognosis) and S-III (worst prognosis) respectively.

5-fold cross-validation. All benchmarking results (except for testing on toy datasets) are reported based on a 5-fold

cross-validation experiment repeated for 5 times with different random seeds. More concretely, for each repeat, we

set the random seed and evenly split the data into 5 folds. Then a loop starts by selecting 3 of the folds for training,

one for validation and the rest for testing. It finishes until all 5 folds have been used as the test fold respectively and

the testing results of all 5 folds are regarded as the final testing result of the current repeat.

Implementation of competitive algorithms. RF algorithm is an ensemble of tree predictors where all trees vote

for the most likely class prediction. We used the implementation from the python package sklearn[44] with the

function RandomForestClassifier where we set the max depth to 10 and trained it as a classification model under

the supervision of subtyping labels provided in the source cohort.

DNN is a neural network that consists of a hidden layer, a dropout layer and a prediction layer and was trained

purely in a supervised manner. It was implemented with Tensorflow library in python. The hidden dimension and

dropout rate were set to 20 and 0.8 respectively to avoid overfitting. The cross-entropy loss and Adam optimizer

were utilized. The learning rate was set to 0.01 and the model was trained for 2000 epochs.

Harmony is an algorithm designed to remove batch effects on single-cell data by projecting data from various

batches into a batch-invariant representation space through soft clustering[13]. Then, samples can be classified with

RF within this space without being affected by batch effects. We firstly did embeddings of the raw profile matrix

with PCA to obtain the low-dimensional representations (100 or 10 dimensions) of the data and then applied the

python implementation of Harmony algorithm from package harmony-py with its default parameter settings.

DANN is a counterpart solution in machine learning and computer vision area which contents with the domain

adaptation task. There are some more SOTA algorithms other than DANN for image domain adaptation[17,26,45],

howbeit, we found they could not lead to any improvement potentially due to the lack of effective neural network

structure in encoding omics data (Figure S2). The DANN was implemented with python tensorflow library. It

includes an encoder $z = f_{encode}(x)$, a task classifier $\hat{y} = f_{task}(z)$ and a domain classifier $\hat{d} = f_{domain}(z)$. On

the one hand the task classifier was trained to minimize the cross-entropy loss between the subtype predictions and

labels, on the other hand, the domain classified was optimized to correctly predict the domain of the sample, i.e. the

sample was drawn from the source or target cohorts. The critical trick was to insert a layer that can reverse the

gradients between the domain classifier and the encoder which encourages the encoder to learn domain-invariant

features to confuse the domain classifier. The number of layers in the encoder and classifiers were tuned with two

options (1 and 2). The hidden dimension of the encoder and classifiers was set to 20 and 10 respectively. The

learning rate was set to 0.01, and the dropout rate was tuned with two options (0 and 0.3).

DeepCLife[25] is the deep learning-based approach that solves an unsupervised clustering problem with survival

information. For fairness, its classifier is optimized by minimizing the original survival loss on target cohort

together with the supervised loss on source cohort, which we term as semi-deepCLife. We consider semi-deepCLife

to be the most relevant baseline method to SRPS. We reimplemented the tensorflow version according to the

original opensource code available at (https://github.com/PurdueMINDS/DeepLifetimeClustering) which is based

on the pytorch library. The parameters tuned for semi-deepCLife are learning rate= $\{0.01, 0.001\}$, l1

regularization= $\{10^{-5}, 10^{-4}\}$, dropout rate= $\{0.3, 0.8\}$ and weight of survival_loss= $\{0.01, 0.05\}$.

Ablated models of SRPS. The first ablated model is to remove the baseline predictions of rewards in SRPS. It

changes the Eq. 6 to $R = r$ and stops optimizing the baseline predictor. The second ablation is to replace the

reinforcement learning approach into a soft relaxation strategy as used in deepCLife. The main difference is that

instead of applying the Kuiper test p-value based loss function, we here calculate and maximize a soft version of

$\Delta RMST$ for optimization. More concretely, when calculating d_t and n_t in Eq. 12 for a specific subtype group,

the count of each subject is weighted by the probability of the subject belonging to this subtype. Such an operation

keeps the entire tensor graph differentiable and can be directly optimized through back-propagation algorithm.

Definition of subtype significance score $\Delta weight$. Given the parameter matrix of the classifier in SRPS as $\Theta \in R^{S \times D}$, the logits vector $l \in R^S$ based on an input profile vector $x \in R^D$ is formulated as $l = \Theta x$ and the predicted probability vector is:

$$p = \frac{\exp(l)}{\sum_s \exp(l^{(s)})}$$

where D and S are the profile dimension and the number of subtypes respectively and $l^{(s)}$ indicates the s^{th} element in the vector l. Unlike the random sampling based on predicted probabilities during training, the subtype prediction in the inference stage is deterministic with argmax operation as shown in Fig.1. In other words, for $a, b \in \{1, 2, \dots, S\}$ where $b \neq a$, the predicted subtype s will be a iff $p^{(a)} > p^{(b)} \Rightarrow l^{(a)} > l^{(b)} \Rightarrow \Theta^{(a)} x > \Theta^{(b)} x$ holds true for any possible b, where $\Theta^{(a)}$ represents the a^{th} row vector of Θ. Therefore, when we only focus on a specific feature $x^{(i)}, i \in \{1, 2, \dots, D\}$, we can approximately have:

$$P\big(s = a \big| x^{(i)}\big) \propto P\big(\Theta^{(a,i)} - \Theta^{(b,i)} > 0 \big| x^{(i)}\big)$$

where $b \in \{1, 2, \dots, S\}$ and $b \neq a$. $\Theta^{(a,i)}$ represents the element at a^{th} row and i^{th} column of Θ. The above equation informs us that the probability of predicting the given profile as subtype a when only considering a single protein expression $x^{(i)}$ is proportional to its corresponding weight $\Theta^{(a,i)}$ and inversely proportional to the weight of other subtypes. Accordingly, we give the following definition about $\Delta weight$:

$$\Delta weight^{(a,i)} = \Theta^{(a,i)} - \frac{\sum_{b \neq a} \Theta^{(b,i)}}{S - 1}.$$

Since this metric is defined based on the model weights and can possibly be affected by the random initialization of the model, we utilized the averaged value of multiple models to indicate significant proteins and the convergence of this approach during the training process was shown in Figure S9.

Cell culture and siRNA transfection assay. HCC cell lines-Huh7, Hep3B, MHCC-LM6 and MHCC-97H were cultured in Dulbecco's Modified Eagle Medium (DMEM) supplemented with 10% fetal bovine serum (FBS), 100 U/ml penicillin, and 100 mg/ml streptomycin, and the cells were incubated at 37□ with 5% CO_2. Cells were seeded in 6-well plates before transfection. When cell density approached 50%, cells were transfected with the indicated siRNAs twice at 24-hour interval using TurboFect Transfection Reagent (Thermo). Cells were collected for mRNA expression assays 48h after transfection. The siRNA sequences targeting *PPIC* are as follows:

si-PPIC#1: GCUCUAGCAACAGGAGAGA;

si-PPIC#2: CUCGAUCAUCAACAGUGGC.

mRNA expression assay. Total RNA was extracted using TRIzol Reagent (Invitrogen) according to the manufacturer's instructions, and the cDNA was obtained using HiScript® III All-in-one RT SuperMix Perfect for qPCR (Vazyme). The gene expression was measured by real-time PCR (qPCR) using Taq Pro Universal SYBR

qPCR Master Mix (Vazyme) with a Bio-Rad CFX96 instrument. Statistical graphs were generated using GraphPad

Prism 8.3.0 software. The qPCR primers used in this paper are as follows:

ACTIN-Forward: 5'-CACCATTGGCAATGAGCGGTTC-3';

ACTIN-Reverse: 5'-AGGTCTTTGCGGATGTCCACGT-3';

PPIC-Forward: 5'-CTGCTGCTACCTCTCGTGC-3';

PPIC-Reverse: 5'-GCCAATCACAATTCTGCCAACA-3'.

Cell viability and colony formation assays. For cell viability assay, after the indicated treatments, approximately

5×10^3 cells per well were seeded into 96-well plates. In the next five days, the cells were treated with CCK8 kit

(Aqlabtech) and the OD values (450 nm) were obtained using Spark® Microplate Reader (TECAN) per day. For

cell colony formation assay, after the indicated treatments, approximately 5×10^3 cells per well were seeded into

6-well plates. After 12 days, cells were fixed with methanol and then incubated with Crystal Violet Staining

Solution (Beyotime) for 1 h. Finally, the cells were washed with PBS three times and the resulting colony pictures

were taken by a camera. Statistical graphs were generated using GraphPad Prism 8.3.0 software.

Cell migration assay. After the indicated treatment, 1×10^5 cells were resuspended in 200 μL DMEM without FBS

and seeded onto the upper chamber of a transwell filter with 8-μm pores. The lower chamber contained 500 μL

DMEM with 20% FBS. 48h later, cells on the underside of the filter were fixed with methanol and then incubated

with Crystal Violet Staining Solution (Beyotime) for 1h. After washing, photos were taken by microscope equipped

with a digital camera. Statistical graphs were generated using GraphPad Prism 8.3.0 software.

Data availability

The code to generate synthetic datasets and the processed datasets of real-world HCC and LUAD cohorts are

available at https://github.com/PHOENIXcenter/SRPS. The raw proteomic profiles and clinical information can

also be downloaded from following pages: https://www.nature.com/articles/s41586-019-0987-8 for Jiang et al.'s

HCC cohort, https://www.cell.com/cell/fulltext/S0092-8674(19)31003-7 for Gao et al.'s HCC cohort,

https://www.cell.com/cell-reports-medicine/fulltext/S2666-3791(23)00509-8 for Xing et al.'s HCC cohort and

https://www.cell.com/cell/fulltext/S0092-8674(20)30676-0 for Xu et al.'s LUAD cohort.

Code availability

578 The full code in R and Python is available via GitHub at https://github.com/PHOENIXcenter/SRPS.

CRediT author statement

581 **Linhai Xie:** Conceptualization, Data curation, Formal analysis, Methodology, Software, Validation, Visualization,

Writing – original draft. **Pei Jiang**: Investigation, Methodology, Resources, Visualization, Writing – original draft.

Cheng Chang: Conceptualization, Formal analysis, Funding acquisition, Supervision, Writing – review & editing.

Competing interests

The authors have declared no competing interests.

Supplementary material

Supplementary material is available at *Genomics, Proteomics & Bioinformatics* online (xxxx).

Acknowledgements

This work was supported by the National Key Research and Development Program of China [2021YFA1301603 and 2020YFE0202200], the National Natural Science Foundation of China [32088101 and 82203601], and CAMS Innovation Fund for Medical Sciences (CIFMS) [2019-I2M-5-063].

ORCID

0000-0001-8593-2277 (Linhai Xie)

0000-0001-5013-5163 (Pei Jiang)

0000-0002-0361-2438 (Cheng Chang)

Reference

1. Jiang, Y. *et al.* Proteomics identifies new therapeutic targets of early-stage hepatocellular carcinoma. *Nature* **567**, 257–261 (2019).
2. Gao, Q. *et al.* Integrated Proteogenomic Characterization of HBV-Related Hepatocellular Carcinoma. *Cell* **179**, (2019).
3. Gillette, M. A. *et al.* Proteogenomic Characterization Reveals Therapeutic Vulnerabilities in Lung Adenocarcinoma. *Cell* **182**, 200-225.e35 (2020).
4. Krug, K. *et al.* Proteogenomic Landscape of Breast Cancer Tumorigenesis and Targeted Therapy. *Cell* **183**, (2020).
5. Xu, J. Y. *et al.* Integrative Proteomic Characterization of Human Lung Adenocarcinoma. *Cell* **182**, 245-261.e17 (2020).
6. Satpathy, S. *et al.* A proteogenomic portrait of lung squamous cell carcinoma. *Cell* **184**, (2021).
7. Van't Veer, L. J. *et al.* Gene expression profiling predicts clinical outcome of breast cancer. *Nature* **415**, (2002).
8. van de Vijver, M. J. *et al.* A Gene-Expression Signature as a Predictor of Survival in Breast Cancer. *N. Engl. J. Med.* **347**, (2002).
9. Buyse, M. *et al.* Validation and clinical utility of a 70-gene prognostic signature for women with node-negative breast cancer. *J. Natl. Cancer Inst.* **98**, (2006).
10. Cardoso, F. *et al.* 70-Gene Signature as an Aid to Treatment Decisions in Early-Stage Breast Cancer. *N. Engl. J. Med.* **375**, (2016).
11. Breiman, L. Random forests. *Mach. Learn.* **45**, (2001).
12. LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521**, 436–444 (2015).
13. Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data with Harmony. *Nat. Methods* **16**, (2019).
14. Tran, H. T. N. *et al.* A benchmark of batch-effect correction methods for single-cell RNA sequencing data. *Genome Biol.* **21**, (2020).

15. Nygaard, V., Rødland, E. A. & Hovig, E. Methods that remove batch effects while retaining group differences
may lead to exaggerated confidence in downstream analyses. *Biostatistics* **17**, (2016).
16. Ganin, Y. *et al.* Domain-adversarial training of neural networks. in *Advances in Computer Vision and Pattern*
Recognition (2017). doi:10.1007/978-3-319-58347-1_10.
17. Saito, K., Watanabe, K., Ushiku, Y. & Harada, T. Maximum Classifier Discrepancy for Unsupervised Domain
Adaptation. in *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern*
Recognition (2018). doi:10.1109/CVPR.2018.00392.
18. Des Combes, R. T., Zhao, H., Wang, Y. X. & Gordon, G. Domain adaptation with conditional distribution
matching and generalized label shift. in *Advances in Neural Information Processing Systems* vols 2020-Decem
(2020).
19. Kouw, W. M. & Loog, M. A Review of Domain Adaptation without Target Labels. *IEEE Transactions on*
Pattern Analysis and Machine Intelligence vol. 43 at https://doi.org/10.1109/TPAMI.2019.2945942 (2021).
20. Yan, L. *et al.* An interpretable mortality prediction model for COVID-19 patients. *Nat. Mach. Intell.* **2**, 283–288
(2020).
21. Elmarakeby, H. A. *et al.* Biologically informed deep neural network for prostate cancer discovery. *Nature* **598**,
(2021).
22. Ribeiro, M. T., Singh, S. & Guestrin, C. 'why should i trust you?' explaining the predictions of any classifier. in
NAACL-HLT 2016 - 2016 Conference of the North American Chapter of the Association for Computational
Linguistics: Human Language Technologies, Proceedings of the Demonstrations Session (2016).
doi:10.18653/v1/n16-3020.
23. Ancona, M., Ceolini, E., Öztireli, C. & Gross, M. Towards better understanding of gradient-based attribution
methods for deep neural networks. in *6th International Conference on Learning Representations, ICLR 2018 -*
Conference Track Proceedings (2018).
24. Lundberg, S. M. & Lee, S. I. A unified approach to interpreting model predictions. in *Advances in Neural*
Information Processing Systems vols 2017-December (2017).
25. Mouli, S. C., Teixeira, L., Neville, J. & Ribeiro, B. Deep Lifetime Clustering. *arXiv Prepr. arXiv1910.00547*
(2019).
26. Long, M., Cao, Z., Wang, J. & Jordan, M. I. Conditional adversarial domain adaptation. in *Advances in Neural*
Information Processing Systems vols 2018-Decem (2018).
27. Mnih, V., Heess, N., Graves, A. & Kavukcuoglu, K. Recurrent models of visual attention. in *Advances in*
Information Processing Systems vol. 3 (2014).
28. Williams, R. J. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Mach.*
Learn. **8**, (1992).
29. Llovet, J. M., Brú, C. & Bruix, J. Prognosis of hepatocellular carcinoma: The BCLC staging classification. *Semin.*
Liver Dis. **19**, (1999).
30. Xing, X. *et al.* Integrated omics landscape of hepatocellular carcinoma suggests proteomic subtypes for
precision therapy. *Cell reports. Med.* **4**, 101315 (2023).
31. Mnih, V. *et al.* Human-level control through deep reinforcement learning. *Nature* (2015)
doi:10.1038/nature14236.
32. Xie, L., Wang, S., Rosa, S., Markham, A. & Trigoni, N. Learning with training wheels: Speeding up training
with a simple controller for deep reinforcement learning. *Proc. - IEEE Int. Conf. Robot. Autom.* 6276–6283
(2018) doi:10.1109/ICRA.2018.8461203.
33. Popova, M., Isayev, O. & Tropsha, A. Deep reinforcement learning for de novo drug design. *Sci. Adv.* **4**, 1–15
(2018).
34. Xu, K. *et al.* Show, attend and tell: Neural image caption generation with visual attention. in *32nd International*
Conference on Machine Learning, ICML 2015 vol. 3 (2015).
35. Jang, E., Gu, S. & Poole, B. Categorical reparameterization with gumbel-softmax. in *5th International*
Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings (2017).
36. Stocki, P., Chapman, D. C., Beach, L. A. & Williams, D. B. Depletion of cyclophilins B and C Leads to
dysregulation of endoplasmic reticulum redox homeostasis. *J. Biol. Chem.* **289**, (2014).
37. Yang, X., Shu, B., Zhou, Y., Li, Z. & He, C. Ppic modulates CCl4-induced liver fibrosis and TGF-β-caused
mouse hepatic stellate cell activation and regulated by miR-137-3p. *Toxicol. Lett.* **350**, (2021).
38. Zappia, L., Phipson, B. & Oshlack, A. Splatter: Simulation of single-cell RNA sequencing data. *Genome Biol.* **18**,
(2017).
39. Brilleman, S. L., Wolfe, R., Moreno-Betancur, M. & Crowther, M. J. Simulating survival data using the simsurv
R package. *J. Stat. Softw.* **97**, (2021).
40. Reimand, J. *et al.* Pathway enrichment analysis and visualization of omics data using g:Profiler, GSEA,
Cytoscape and EnrichmentMap. *Nat. Protoc.* **14**, (2019).

41.   Hänzelmann, S., Castelo, R. & Guinney, J. GSVA: Gene set variation analysis for microarray and RNA-Seq data. *BMC Bioinformatics* **14**, (2013).
685
686   42.   Bewick, V., Cheek, L. & Ball, J. Statistics review 12: Survival analysis. *Critical Care* vol. 8 at https://doi.org/10.1186/cc2955 (2004).
687
688   43.   Harrell, F. E., Califf, R. M., Pryor, D. B., Lee, K. L. & Rosati, R. A. Evaluating the Yield of Medical Tests. *JAMA J. Am. Med. Assoc.* **247**, (1982).
689
690   44.   Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *J. Mach. Learn. Res.* **12**, (2011).
691   45.   Zhang, Y., Liu, T., Long, M. & Jordan, M. I. Bridging theory and algorithm for domain adaptation. in *36th International Conference on Machine Learning, ICML 2019* vols 2019-June (2019).
692

Figure legends

Figure 1 The innovation and the learning strategy of Survival Reinforced Patient Stratification (SRPS)

A. When transferring subtypes with known biological features and prognostic discrimination from a discovery

cohort to an extended cohort with batch effects, naïve methods face significant limitations. Supervised

classification often fails to preserve prognostic discrimination, while risk stratification can classify patients but

cannot transfer biological features. SRPS addresses these challenges by simultaneously learning from the subtype

labels of the discovery cohort and the survival data of the extended cohort. This dual approach enables SRPS to

preserve both the biological features and prognostic discrimination of the subtypes. **(b)** During training, SRPS

optimizes a classifier to predict patient subtypes based on molecular profiles using two complementary learning

paradigms. In the discovery cohort, supervised learning minimizes prediction errors relative to known subtype

labels. In the extended cohort, on-policy reinforcement learning maximizes prognostic discrimination between

subtypes by optimizing a policy gradient. $\ominus$ represents element-wise subtraction. In the inference phase, SRPS

assigns a predicted subtype to each patient using the trained classifier, as illustrated with the example of a predicted

liver cancer subtype ("S-I").

Figure 2 SRPS effectively improves classification accuracy by using prognosis information

Each subfigure displays an accuracy map on 121 simulated toy datasets with various levels of batch effects between

source and target cohort and the relative correlation between survival and subtypes (see Methods and

Supplementary). In each experiment, 20% samples from target cohort are used for testing. The upper row exhibits

the accuracy map of three different stratification strategies on the target cohort. **A.** A feature-based strategy is

applied by training a Deep Neural Network (DNN) to predict two subtypes according to features only in the source

cohort. **B.** A survival-based strategy directly stratifies patients by thresholding the survival times at 30 months in

the target cohort. Note that this strategy is impractical in real since the survival time is unavailable for a certain

patient who is still at risk, but here, it is only used as a theoretical reference when such prognosis information could

be fully exploited (or accurately predicted) for subtyping. **C.** SRPS uses features for prediction and is adjusted by

prognosis information in the target cohort during training phase. **D-F**. The bottom row exhibits the residual

accuracy maps between two strategies. The one-tailed Student's t-test was utilized to exam whether the values in

the whole area or the upper-right area are significantly above zeros. Acc means accuracy.

Figure 3 SRPS outperforms comparative approaches and ablated models in simulated datasets

All approaches were firstly benchmarked on two simulated datasets without any batch effect between them **(a-c)**. It

was then followed by the benchmarking on datasets with batch effects **(d-f)**. The metrics reported are the mean and

standard deviation values of classification accuracy and log-rank score from a 5-fold cross-validation test repeated

for 5 times. The competitive methods are random forests (RF), deep neural network (DNN) with supervised

learning, RF combined with Harmony (RFH) for batch effect removal, domain adversarial neural network (DANN)

for domain adaptation and semi-deepClife for survival guided approach while SRPS (soft) and SRPS (no base line)

are ablated models of SRPS.

Figure 4 SRPS outperforms comparatives approaches on real-world cohort data.

A. Subtypes discovered from Jiang et al.'s cohort were transferred to Gao et al.'s cohort. **B.** Subtypes discovered

from Jiang et al.'s cohort were transferred to Xing et al.'s cohort. **C.** Subtypes from Jiang et al.'s cohort were

transferred to Xu et al.'s LUAD cohort. Metrics include the accuracy in the source cohort, ssGSEA similarity of

subtypes between the source and target cohorts, log-rank score, and C-index for overall survival (OS) and

recurrence-free survival (RFS). Larger values represent better performance, as indicated by deeper colors in each

column. **D.** Summary of the four real-world cohorts, including cancer type, number of samples, cancer stage, and

clinical outcomes evaluated.

Figure 5 PPIC was identified as a significant protein through model interpretation with subtype significance

score

A. The correlation between the prognostic discrimination (the coefficient of a univariate COX model) and the

subtype significance score (Δweight) of each protein in the model (DNN and SRPS) in terms of OS and RFS. **B.**

The correlation between the subtype significance score of each protein in the model and the corresponding

log2(fold change) value on Jiang et al.'s cohort and Gao et al.'s cohort. Red points indicate proteins with top-ranked

significance scores. **C.** The mean and standard deviation of the significance score of the top-30 proteins and

whether they have been formally reported to be HCC-related in published literatures. **D.** The prognostic

discrimination power of PPIC in terms of OS and RFS on Jiang et al.'s cohort and Gao et al.'s cohort. The threshold

for dividing high and low expression groups in each subfigure is independently set to be the value with the highest

log-rank test significance.

Figure 6 PPIC promotes cell proliferation and colony formation in HCC cell lines

A. Relative mRNA expressions of *PPIC* after the indicated treatment. **B.** Cell proliferation curves determined by cell viability assay after the indicated treatment. **C.** Resulting cell colonies (left) and the related statistical graphs (right) after the indicated treatment. Data were presented as mean±SEM. *, $p<0.05$* (Two-tailed Student's t-test).

761   Figure 1

764   Figure 2

765
766

    Figure 3

770 Figure 4

Cohort	Num. of samples	Cancer type	Cancer stage	Clinical outcome
Jiang et al.[1]	101	HCC	BCLC 0/A	OS & RFS
Gao et al.[2]	159	HCC	BCLC 0/A/B/C	OS & RFS
Xing et al.[30]	152	HCC	BCLC 0/A/B/C	OS & RFS
Xu et al.[5]	103	LUAD	TNM stage I	OS & RFS

771
772

773   Figure 5

774
775

776   Figure 6

777