1 **SVCROWS: A User-Defined Tool for Interpreting Significant Structural Variants in Heterogeneous**
2 **Datasets**
3

4 **Authors:** Noah Brown*^, Charles Danis*, Vazira Ahmedjanova*, Jennifer L. Guler*^
5 **Affiliations:** *Department of Biology, University of Virginia. Charlottesville, VA 22903
6   ^Co-corresponding authors

Graphical Abstract. SVCROWS (Structural Variation Consensus with Reciprocal Overlap and Weighted Sizes) is a structural variant merger that leverages option-rich, size-weighted comparisons to better resolve complex inputs and separate out regions of meaningful biological differences.

8 **Abstract**

9
Genomic structural variants (SVs) are pervasive and can impose major phenotypic impacts.
However, it is difficult to appreciate the individual significance of SVs when they are
heterogeneously positioned across a genomic neighborhood. Further, ubiquitous variance in SV
calling accuracy complicates SV counting and downstream analysis. Tools exist to simplify SV
datasets but they are not suited for all applications. Here, we present a new SV merger,
SVCROWS: Structural Variation Consensus with Reciprocal Overlap and Weighted Sizes. This
option-rich merger summarizes SV regions using a size-weighted reciprocal overlap framework,
accounting for skewed impacts of variable-length SVs. User input directs stringency, enabling
various levels of resolution in complex genome regions that harbor a spectrum of SV sizes.
Further, by optimizing SVCROWS parameters, the user can tailor results to their study system.
When compared to other SV merging programs, SVCROWS maintained accuracy and conserved
rare genotypes from both simulated and real-world datasets. Visualization of merger output
was critical for identifying how some algorithms derived erroneous conclusions while SVCROWS

remained reliable, especially in complex regions. Overall, the novel SVCROWS algorithm
presents an improved framework for SV interpretation; its intuitive nature and generalizability
facilitates its application to virtually any workflow.

Introduction

Genomic structural variations (SVs) are large (>50 bp) duplications, deletions, inversions, insertions,
and/or translocations. SVs are both evolutionarily important for organisms and causative factors in many
human diseases(1–5). Their abundance in all life makes them prime targets of study. Recent advances in
sequencing technologies have improved detection of SVs, as well as the sequence accuracy and
breakpoint mapping of SV calls(6). Validation of these programs and protocols has become more
accessible using benchmarking datasets such as the *Genome in a Bottle* consortium(7), and the *1000*
Genomes Project consortium(8). However, newly developed tools and benchmarking programs largely
focus on single-sample SV detection (i.e. from bulk sequencing), abstaining from comparisons across
individuals in a population as is required for single-cell (SC) genomics.
39
As work determining the connection between rare genotypes and phenotypes becomes more common,
researchers must evaluate more data with increased precision. Overlapping yet distinct SV regions arise
either from biological variance or technical noise and make subsequent analysis more difficult.
Therefore, accurate SV merging to reduce complexity is a key step prior to SV interpretation which can
involve either checking for an expected genotype (i.e. validation) or detecting new genotypes (i.e.
discovery). Thus, the outcome of SV merging is an influential step in analysis pipelines. In the case of
both validation and discovery, merged SVs have greater statistical strength to support biological
conclusions(6, 9–12). Determining how to merge SVs is challenging because small shifts in position can
have major impacts on SV interpretation. SV merging must maintain a balance between removing
redundancy across a dataset by merging similar SVs and preserving heterogeneous and rare SVs.
50
The best way to address these merging challenges remains debated, but strides have been made by
several SV merging algorithms to reconcile this issue(10, 13–19). However, these existing approaches
have limitations. First, many rely on high-accuracy inputs and have only been validated in that context.
This is particularly an issue when sequencing depth is limited (e.g. for SC genomics), the reference
genome is low quality, or SVs sit in highly repetitive regions of the genome. Large population studies also
remain difficult to resolve despite high sequencing quality, because the increased SV heterogeneity leads
to overmerging(14, 18, 20). Another common limitation is incompatibility of mergers with different data
types, because many mergers are incorporated into larger analysis pipelines to increase effectiveness.
This places constraints on the input type or upstream SV caller, invalidating certain study designs.
Further, while SV mergers generally have options to control SV matching parameters, their direct impact
is not immediately transparent to the user without performing many iterations. Overall, under- or
overmerging of variable regions across many samples leads to a loss of information or generates
misleading information.
64

Here, we introduce a new SV merger, 'SVCROWS' (Structural Variation Consensus with Reciprocal
Overlap and Weighted Sizes), that seeks to overcome these limitations. SVCROWS merges SVs called by
upstream methods (or any genomic intervals of interest) into representative SV regions (SVRs), so that
technical variation is simplified while preserving rare alleles. This is accomplished through size-weighted
reciprocal overlap (RO) comparisons that adjust the stringency of merging in response to SV size. Here,
we demonstrate that size-weighted comparisons enable SVCROWS to achieve higher performance in
both simulated and real-world SV datasets, particularly in complex genomic regions. These results can be
further improved by parameter optimization and selection of an advantageous run mode. SVCROWS also
benefits from a focus on biologically oriented features and compatibility with both up- and downstream
steps of genomics protocols.
75

Materials and Methods

A framework of size-weighted comparisons to capture significant SVs
SVCROWS uses the principle of reciprocal overlap (RO) thresholds to determine whether to place SVs in
the same SVR (i.e. matching/merging SVs). While the RO-based approach is used in existing
applications(19, 21, 22), these rely on a single, fixed RO threshold value. This static method overlooks the
disparity in SV lengths and their potential biological impacts, creating a false equivalency between small
and large SVs. For instance, if we measure biological impact by the number of genes within an SV (**Fig.
1A-B**), a larger SV is more likely to have a greater effect (e.g. encompasses more genes and regulatory
regions) on the phenotype than a smaller SV (e.g. encompasses few genes or even a promoter region).
Specifically, as depicted in **Fig. 1A-B**, there are two obvious inconsistencies in treating different sized SVs
with the same stringency: 1) SV2 matches both large and small reference SVs, despite causing a 3X
increase in potential impact in the larger SV (i.e., involving 3 genes); 2) When either SV size lacks just one
gene compared to the reference (i.e. the same level of biological difference to the reference), the small
SV matches at a 55% RO (**Fig. 1A**, SV2) while the larger SV matches at 95% (**Fig. 1B**, SV1). Using this
reasoning, we posit that when a size-static matching parameter like RO is used, it is more likely to reflect
genotypes disproportionate to their impact. This is the basis for the size-weighted comparisons used by
SVCROWS.
93

Selecting parameters to dictate stringency using size-weighted comparisons
To address high variance in SV length and position, the user directs SVCROWS to increase or decrease the
requirements of the RO threshold and other factors involved in the decision to merge two SVs (i.e.
stringency) according to the SV size (**Fig. 1C**). Dynamic RO thresholding by SVCROWS involves 6 input
parameters to define the stringency based on analysis needs (**Fig. 1C,** colored boxes). First, SVCROWS
creates size categories to group SV-comparison stringencies by SV size. By default, these parameters are
determined by the first and third quartiles of SV length in the given dataset. These can be further refined
based on the minimum and maximum SV sizes the user considers relevant in their organism or study
interest. For example, in an analysis of CNVs, the 'small' category could be the average exon size while
the 'large' category could reflect the average size of CNVs reported in that genome (**Fig. 1C,** blue inputs 1
& 2). Second, users dictate bounds that allow SVCROWS to match breakpoints between input SVs (**Fig.
1C,** green inputs 3 & 4, **Fig. 1A**). Finally, users define RO thresholds at the boundaries of the size
categories (**Fig. 1C,** yellow inputs 5 & 6). Collectively, these input parameters set the SVCROWS algorithm
to respond to SV size (**Fig. 1C** red line). Detailed parameter definitions and functions are provided in the
Supplemental Methods.
109

SVR consensus generation

SVCROWS merges SVs and organizes data into a table of distinct SVRs according to the input parameters.
The algorithm processes SVRs in descending order of length (**Fig. 1D, top**). Therefore, the largest SV in
the region dictates boundaries, and the breakpoints reflect those provided by the upstream SV-caller.
When used as recommended, the stringency is higher for larger SVs than smaller SVs (**Fig 1D**); however
stringency can be assigned so that the opposite is true as well. SVCROWS quantifies matching SVs on the
number of RO and SV breakpoint (BP) matches at 5 and 3 ends of an SV (**Fig. 1D,** bottom).
117
118
119

Figure 1. The SVCROWS algorithm compares SVs with regard to size, and potential impact. A) A small (50,000bp) reference SV (light blue) encompassing 2 genes and, **B)** A large (250,000bp) reference SV (dark blue) encompassing 6 genes; being compared to 3 potential SVs (teal) at a static 50% Reciprocal Overlap threshold. Using each gene as a unit of biological impact; smaller SVs are more tolerant to changes in size when reflecting similarity to the original SV. **C)** Six inputs defined by the user weight the reciprocal overlap determination by size. x-axis: "Small" and "Large" SV category thresholds (variables 1&2). Left y-axis: The width (in base pairs) of BP-Matching region (see **Fig. S1,** variables 3&4 respectively). Right y-axis: The required level of RO-threshold (as a percentage) for SV matching (variables 3&4 respectively). These inputs generate the SVCROWS Calculation Trajectory (purple) which defines the dynamic RO stringencies. **D)** Logical workflow of SVCROWS merging function. A list of SVRs is produced, from a single input list. The number of matches is tabulated (bottom). 'Dup' = duplication, 'Del' = Deletion, '#RO' = Number of matching SVs, 'BP-Start/End' = matching breakpoints on the 3'/5' ends of the SVs. Options to augment the run mode are also available.

Optional inputs and functions

In addition to size-weighted merging ("Scavenge" mode), SVCROWS incorporates several features to construct and quantify SVRs. While some features mirror existing functionality, SVCROWS integrates these functions into a single platform and introduces novel functions (denoted with * below). Seven major optional features are outlined below, with detailed descriptions available in the **Supplemental Methods**:

i. *Automatic input parameter calculation: SVCROWS calculates six input parameters based on the first and third quartiles of input SV sizes. This allows SVCROWS to dynamically adjust to the specific characteristics of the dataset.

ii. *Breakpoints as a secondary SV matching factor: Users can opt to incorporate breakpoint matching to aid SV merging (**Fig. S1A**). When enabled, SVCROWS reduces the required RO threshold to its minimum value (user input 5) for SVs with matching breakpoints. This feature is useful for identifying matches in repetitive genomic regions where one breakpoint is consistent, but the opposite end is misaligned.

iii. *Use of 'Known' regions in input: A user can define input 'known' SVs, which reduces all requirements for matching in that region to only a single base pair (**Fig. S1B**). For example, by defining the region of *AMY1* in the human genome as a 'known' CNV(23), a user can collapse all variation in this genomic neighborhood.

iv. *Convenient annotation of all input SVs by sample: SVCROWS uses a custom input format that allows the program to individually track the outcome of all input SVs. This is especially convenient for workflows that require per-sample analyses.

v. Expansion of SVRs to maximum size: The user can employ this option to set SVR size based on the maximum and minimum matching breakpoint of all SVRs in a region (**Fig. S1C**). This functionality may be useful when downstream applications benefit from larger SVRs (e.g., gene ontology studies).

vi. Querying against a list of features: The user can alternatively use the "Hunt" function, which takes a secondary input - a 'feature list' - for comparison with an input list of SVs (or SVRs). For example, this functionality allows the user to compare a set of genes to SVRs determined from "Scavenge mode" using the size-weighted framework.

vii. Enumeration of other variables: As SVs match, the user can provide numeric information that 1) takes the number of reads originally used to call the SV and adds them together and 2) takes the quality score of each SV and averages them together.

SV merging for SV-Simulation, SC dataset, and HG002 Truth Set

In order to understand how different sequence-independent merging algorithms perform over diverse datasets, we compared SVCROWS to several SV mergers with a variety of algorithm types: Jasmine(17), Survivor(24), SVimmer(15), Truvari(18), and CNVRuler(19). We chose these five SV mergers because they are compatible with most upstream SV callers, and present different strengths and weaknesses in their composition. To normalize for these differences, we instructed each program to function with parameters as close to the default parameters of SVCROWS-Default as possible; using the 'default'

parameter assignment with breakpoint matching and RO expansion options enabled (**Fig. S1**). Default
SVCROWS parameters use the first and third quartiles of SV sizes to demarcate size boundaries, 10% of
respective lengths to set the size of breakpoint boundaries, and 40% and 70% as the small and large RO
thresholds. Unless otherwise indicated, SVCROWS is run in 'default' mode, which uses both the
breakpoint matching (function ii) and expand-RO (function v) features.

The precision of a typical CNV calling program ranges from a single basepair to no more than 500bp.
Because all mergers (excluding SVCROWS) include breakpoint distance to some extent in merging
decisions, we ran all mergers with a lenient 1000bp buffer region around either end of the SV; this is
larger than previously used in order to encourage SV comparison(15). See ***Supplemental Methods*** for
the precise command-line run for each program.

We manually compiled the SV input lists for SVCROWS and CNVRuler and organized them into TSV files
used for each run matching their individual formats (**Tables S2 & S3**). Jasmine, Survivor, and SVimmer
accept the raw VCF files from the SV caller. To normalize for any inconsistencies between output from
each caller, all alternative alleles were manually converted to either "<DUP>" or "<DEL>", and we
replaced the sample field with a ".". SVs were first consolidated for Truvari as recommended in their user
wiki BCFTools(25), which essentially concatenates all SVs together without merging. We noted this
concatenation step with BCFTools led to artifacts in complex regions in our dataset (see **Fig. S10B**) and
opted to use a different BCFTools command that merged purely redundant SVs (i.e. those with precisely
matching breakpoints) before further merging. This largely fixed the artifacts (See ***Supplemental***
Methods for more details). Truvari notably has the optional ability to use sequence information
contained within aligned reads, which may assist in refining some genotype calls. However, because
SVCROWS and other mergers cannot incorporate this information, and SVCROWS is intended to be
generalizable to any workflow, we used Truvari's otherwise robust merging algorithm without this
option.

SV-Simulation and analysis
To effectively test the capabilities of SVCROWS, we developed a custom script that simulates SVs as they
appear in datasets with many samples, such as SC datasets. Using this SV simulation, we generated a
simulated-Truth Set SV list and subsequently derived per-cell observed SVs that incorporate both
biological heterogeneity and technical noise that are propagated to simulated individuals ('cells'). The
command-line interface (CLI) accepts several inputs that control key dataset characteristics and is fully
described in the ***Supplemental Methods***. Briefly, we divide the simulated-Truth Set SVs into 'frequent'
events (prevalence >80% of cells; referred to as 'clonal' in the CLI) and 'infrequent' events (events with
frequencies drawn from a geometric distribution to mimic stochastic occurrence in one or a few cells;
referred to as 'subclonal' in the CLI). The simulator randomly determines the population frequencies of
common and rare SVs before constructing cells, ensuring that each simulated cell matches those
frequencies (e.g., if a feature occurs at 10% frequency in 100 total cells, the simulator assigns it to 10
randomly chosen cells). The simulator samples SV coordinates across a region of defined size (this study
used the length of HG38 chromosome 1) with log-uniformly distributed lengths, allowing overlaps. To
mimic genomic instability, the simulator generates high-complexity regions that guarantee multiple
simulated-Truth Set SVs overlap within a defined locus. Finally, to simulate real-world uncertainties in SV
calling, the simulator introduces positional and size fluctuations to per-cell SVs. A single variance
parameter controls the fluctuation magnitude: low values preserve true coordinates, whereas high
values allow large shifts (up to ~30% positional offset and 70% size distortion). Larger CNVs experience
proportionally greater absolute deviations (see **Fig. S2** for an example run of the simulation).

To analyze the SVR output of the simulation, we compiled the features divided among cells to match the
input format required by the merger tools (Jasmine, Truvari, and SVCROWS-Default). We then compared
the resulting outputs to the simulated-Truth Set using Bedtools intersect under three static reciprocal
overlap thresholds (50%, 80%, and 95%). We counted true positive (uniquely matched against the
simulated-Truth Set), false negatives (non-unique matches to the simulated-Truth Set), and false
positives (SVRs without matches to the simulated-Truth Set). We used these values to calculate the F1
score (see **Fig. 2A** and ***Supplemental Methods***).
223
SVCROWS parameter optimization using simulated data
To highlight the relationship between SVCROWS input parameters, we employed a 3-dimensional
analysis that allowed us to visualize the interplay between the three input axes (Size, RO, and BP) using
the F1 score. For each selected dataset, we generated an interactive 3D scatter plot using the plotly(26)
library in R. The x-, y-, and z-axes correspond to Size, RO, and BP parameter indices, respectively, while
color and size indicate F1 score. For each of the selected simulated SV runs where this 3D analysis was
performed, we produced a series of 5 levels of stringency based on the predetermined SVCROWS-
Default values (see ***Supplemental Methods*** and **Table S1** for full specification). Ultimately, this
visualization enables rapid identification of optimal parameter combinations where F1 scores are
maximized, thereby facilitating comparative evaluation of algorithmic performance across the full 5×5×5
parameter space.
235
Single Cell dataset acquisition and SV calling
We used pyega3 to download the single-cell ovarian cancer dataset, EGAD00001009455, with
permission of the European Genome Archive (EGA)(27). The authors note their compliance with best
practices detailed by the EGA. The dataset consists of 326 single cell (SC) whole genome sequences
derived from a solid ovarian cancer tumor from a single patient (termed SC dataset). Notably the patient
also had triple negative breast cancer. The full Galaxy-based pipeline can be found at
https://usegalaxy.eu/u/sillycrow/w/lumpy. Briefly, we used downloaded BAM files to generate files
containing only split and discordant reads as determined by previous sequence alignments. Then, all
three BAM files are used as input into the LUMPY SV caller. We chose LUMPY for this analysis due to its
high precision breakpoints and utility in single-cell datasets(28–30). We used default parameters except
for the expected read length (150 base pairs) and the minimum read mapping quality for inclusion (≥5).
For this analysis, we excluded BAM files with less than 1000 elements in either the split-read or
discordant-read files due to issues with LUMPY performance in low-read support samples(31, 32).
Additionally, we limited the SC analysis to only duplications and deletions with a length of <1Mb called
by LUMPY for simplicity. Prior analysis of this dataset detected high frequency SVs with variable
breakpoints, a common feature in cancers(33). Overall, 4771 total SVs were detected across the dataset
(**Tables S2 & S3**). For comparison of SVCROWS RO stringency in complex regions (see **Fig. 3C**), we tuned
SVCROWS to interpret differences in the human genome by using the average size of a human exon
(~1.3kb(34)) and the average size of a gene-plus-intergenic region (~38kb(35–37)) as small and large SV
sizes, respectively.
256
257
HG002 dataset processing and analysis
The HG002-Truth Set (HG002_SVs_Tier1_v0.6.tsv) is part of the *Genome in a Bottle* (GIAB) consortium, a
high confidence, multi-validation genome assembly(38–42). This dataset consists of 9641 individual SVs
(>50bp) confirmed by at least 3 independent SV calling programs, including SV calls from both long- and
short-read data. For this analysis, we used only Tier1 (GIAB certified highest confidence) SVs, including
representative SVs that allow assessment of merger efficacy in regions with multiple SV calls across the

same region. The HG002-Truth Set includes both deletions and insertions, but because not every merger
or SV caller can handle insertions without the inclusion of raw sequences, we only used deletions in this
analysis.
267
To test SV mergers, we used HG002 SV calls from 5 different programs as input: LUMPY(30), pbsv(43),
Sniffles(44), MrCaNaVaR(45), and MetaSV(46). We combined all calls into a single 'Aggregate List', many
of which are not part of the HG002-Truth Set (~90%), either because they are false positive calls, or they
did not reach the threshold to be called in the Truth Set (i.e. called by 3 programs, pass various quality
filters, etc.). Further, because the largest SV in the HG002-Truth Set was ~1Mb, we excluded SVs >2Mb
from the analysis. This represents the manual filtering step, which is part of most SV calling pipelines
(see **Fig. S9** for a diagram of the HG002 dataset processing). We first calculated Jaccard indices of the SV
mergers using the Bedtools-jaccard method on this cleaned Aggregate List, which considers both the
coverage and depth of represented regions to calculate differences in merging (see ***Supplemental***
Methods and **Table S4**).
278
Many of the SVs called in the cleaned Aggregate List are perfect (or near-perfect) matches the HG002-
Truth Set and were used as true positives in an effort to establish relative merger accuracy. To do this, we
filtered the Aggregate List and HG002-Truth Set to make a reference set containing only SVs common to
both. As such, we eliminated irrelevant false negatives and positives (i.e. those that are present in the
Aggregate List but not in the HG002-Truth Set, or vice-versa) to only those SVs that had any overlapping
bases ([Aggregate_List ⏃ HG002-Truth_Set] ≥ 1bp). The resulting pared-down reference set of SVs is
dubbed the 'On-Truth Set' and used to compare the filtered Aggregate List against. This filtering ensured
that only SVs present in both sources, hence theoretically recoverable by any merger, were evaluated as
potential true positives. (see **Fig. S9**). The filtered Aggregate List is then merged and then compared to
the On-Truth Set using F1 score in the same method as above (**Table S5**).
289
Because inclusion of an SV in the HG002-Truth Set depends on tight breakpoint concordance among
multiple callers, even small positional variances can cause otherwise correct calls to be excluded.
However, both accepted and rejected calls remain in the filtered Aggregate List. Therefore, this study
design leveraged the technical variance and noise in the calls made by the 5 callers to assess merger's
capabilities to reproduce the On-Truth Set purely computationally (as opposed to the original, labor-
intensive HG002-Truth Set construction). The recaptured similarity to the On-Truth Set was assessed
across different overlap thresholds to highlight how faithfully breakpoints were conserved after merging
the Aggregate List, we then overlapped the SVRs against the On-Truth Set to calculate true positives and
F1 score as above.
299
300
301
302
Results
Optimization of SVCROWS for outstanding performance under challenging input conditions
To benchmark the performance of our new size-weighted comparison framework, we evaluated
SVCROWS using different combinations of its optional decision-making functions (breakpoint matching
and expand-RO; **Fig. S1**) alongside two widely used SV mergers, Truvari(18) and Jasmine(17), in a
controlled SV-simulation environment. We used a custom script to generate SV input lists with precise
control over key characteristics, including event size, breakpoint variance ("discordancy"), local
complexity (multiple overlapping SVs), and the number of simulated cells (**Fig. S2**; see ***Supplemental***

Methods). These datasets were compared against a simulated-Truth Set to systematically evaluate
sensitivity and precision under increasingly challenging input conditions (**Fig. 2A–B**). Importantly, the
simulations reproduced expected patterns: F1 scores declined as input complexity increased, confirming
that the benchmarking system captured realistic SV-merging challenges (**Fig. 2C, F**).

Comparisons were affected by trade-offs between false positives and false negatives when assessing
similarity to the simulated-Truth Set (**Fig. 2A**). To address this, we measured merger performance using
three reciprocal-overlap (RO) thresholds - 50%, 80%, and 95% - which emphasize recall, balanced
accuracy, and precision, respectively. Across the four simulation scenarios (**Fig. 2**), SVCROWS
consistently outperformed competing tools, even under challenging inputs. Under increasing
discordancy, SVCROWS-Default retained higher precision than either Jasmine (F1 1.54× higher) or
Truvari (F1 1.49× higher) across comparisons. Although breakpoint shifts reduced overall F1 scores (**Fig.
2C–E**), SVCROWS maintained superior performance. With escalating sample sizes that increased
opportunities for merging errors, performance declined across all methods, yet SVCROWS-Default
maintained a distinct advantage, with mean F1 scores 1.84× and 1.39× higher than Jasmine and Truvari,
respectively (**Fig. 2F–H**).

In high-complexity regions containing many overlapping SVs, SVCROWS-Default produced far fewer false
positives and false negatives than either Jasmine or Truvari (2.20× and 1.40× fewer, respectively),
highlighting the utility of its size-weighted comparisons. This corresponded to a increase in F1 at the
95% overlap threshold - 2.06× and 1.86× higher than Jasmine and Truvari, respectively - in crowded
genomic contexts (**Fig. 2I, J**). Finally, in datasets with bimodal size distributions, where very large SVs co-
occurred with much smaller events, SVCROWS-Default showed a superior balance of recall and
precision, outperforming other methods across both liberal and stringent overlap thresholds despite its
reliance on size distribution to determine stringency (**Fig. 2K-L**).

The trade-off for SVCROWS' increased accuracy and precision is computational time. Because SVCROWS
must perform comparisons for each SV individually, small input lists execute almost instantly, whereas
increasingly larger datasets require proportionally more time than Truvari or Jasmine (**Fig. S3**).

Further optimization of SVCROWS input parameters substantially improved performance beyond the
SVCROWS-Default run mode. Systematic tuning of breakpoint, size, and overlap factors revealed strong
interactions among parameters, making multidimensional exploration essential (**Fig. S4**). Three-
dimensional visualizations of the parameter space showed that optimized settings produced F1 scores
exceeding the defaults at both 50% and 95% overlap thresholds (**Fig. 2D, G**). For example, under
discordant and high complexity conditions, parameter optimization elevated F1 scores well above those
achievable by Jasmine or Truvari at 95% RO, while simultaneously improving recall at 50% RO.

There were noticeable advantages among the distinct combinations of the four SVCROWS run modes.
For example, under high-discordancy inputs, the use of breakpoint matching was preferable to expand-
RO alone (**Fig. 2C**). Expand-RO by itself offered an advantage in almost all scenarios, while combining
both functions helped offset the biases of each.

Together, these results demonstrate that the size-weighted framework implemented in SVCROWS not
only performs robustly across diverse and challenging SV scenarios but also benefits from systematic
parameter optimization. The ability to tune parameters allows SVCROWS to achieve superior accuracy
and precision compared to existing tools, particularly under conditions where SV heterogeneity and
breakpoint uncertainty complicate merging.

Figure 2. Optimization of SVCROWS input parameters compared to other SV mergers on simulated datasets. A) Diagram illustrating how merger accuracy and precision are determined across three levels of stringency relative to the simulated-Truth Set. **B)** Key for mergers and options used for comparisons on simulated SV data (applies to subsequent figures). **C–L)** Comparison and optimization of F1 scores in four challenging simulations. Each merger or option set depicts three bars at varying levels of reciprocal-overlap stringency; each set of bars represents the same post-merge dataset. Error bars indicate the standard deviation of the F1 score. Each simulation tests one aspect of input variance while keeping others constant: **C–E)** Three levels of discordancy (fluctuations in start, end, and size of SVs). **F–H)** Three levels of sample number (100, 1000, 3000). **I–J)** High-complexity regions containing several overlapping SVs of various sizes and frequencies. **K–L)** A bimodal distribution of SV sizes in which very large SVs are interleaved with ~100× smaller SVs. **D, G)** Representative 3D visualizations of F1 scores from a single constituent SVCROWS-Default replicate (one of five replicates), showing systematic adjustment of the six input parameters required at 95% RO relative to the simulated-Truth Set. The **blue** dot represents the unoptimized F1 score at 95% RO, and the **red** dot represents the highest F1 score after parameter optimization (for all 3D plots, see **Fig. S4**). **E, H, J, L)** Representative graphical results of parameter optimization for the same replicate. The **blue** bar indicates the original F1 score, and the **red + blue** bar indicates the increase after optimization.

354   **SVCROWS allows control of SV merging in a complex single cell dataset**

355   While SVCROWS performs well compared to other merging programs in simulated data across all tested
356   scenarios (**Fig. 2**), it proves especially proficient at handling highly discordant and high complexity
357   regions (**Fig. 2C** and **2I**, respectively). However, simulated data cannot recapitulate all forms of natural
358   and technical variance found in real-world data. As such, we sought to further evaluate the performance
359   of SVCROWS using SVs called from complex regions in a SC cancer dataset.

360

361   We compared SVCROWS' size-weighted algorithm to the performance from 4 major types of SV mergers
362   including: distance-based algorithms (SVimmer(15) and Survivor(24)), a minimum spanning forest-based
363   algorithm (Jasmine(17)), a multifactored algorithm (Truvari(18)), a static RO algorithm (CNVRuler(19)), as
364   well as a pure redundancy removal algorithm (VCFTools(47)) denoted by color below (**Fig. 3A, B**). Across
365   the SC dataset, two regions stood out in complexity (>10x more SVs per 10kb than the background)
366   including one complex sub-centromeric region on chromosome 6 (**Fig.3**), and a second large intergenic
367   region on chromosome 10 (**Fig. S5, 6**). We focused our initial assessments on these regions to assess
368   merging patterns across programs.

369

370   In the chromosome 6 region, there were 143 unmerged SV calls, with only 43% harboring breakpoints
371   that exactly matched another SV (i.e. pure redundancy). Using only pure redundancy to define like-SVs is
372   inadequate to fully simplify the region; evidenced by the undermerging of the 'gain' SV present in the
373   majority of samples (**Fig. 3B**). After merging of pure redundancy, 82 SVs remained. When we visualized
374   how the merging algorithms perform, it was apparent that they prioritize different aspects of SVs for
375   merging (**Fig. 3A, S5, S6**). For example, Jasmine undermerged both small and large SVs across this region
376   (**Fig. 3A**, green). Overall, in contrast to its satisfactory performance on the highly discordant simulated
377   dataset (**Fig. 2C**), Jasmine failed to reduce complexity of this region compared to other programs,
378   perhaps due to the large range of SV sizes. Conversely, distance-based algorithms seemed prone to
379   overmerging where output had removed key differences (**Fig. 3A**, yellow). Truvari likely undermerged
380   smaller SVs, leaving overlapping SVs with as little difference as 90bp (9.5% of the total size) unmerged.
381   Further, by comparing SVCROWS to CNVRuler, we observed that the size-weighted RO led to substantial
382   changes in the outcome of large regions. These observations are largely consistent with the chromosome
383   10 region (**Fig. S5, 6**). In both cases CNVRuler output only appears similar to SVCROWS but overall makes
384   several repeatable errors in complex regions, that lower confidence in its consistency (highlighted in **Fig.**
385   **S7**).

386

387   Observations in these specific regions agree with those made when broadening the scope to the entire
388   SC dataset consisting of 4771 SVs (**Fig. S8, Table S3**). Specifically, we detected a wide range of resulting
389   SVR sizes (**Fig. S8A**) and total SVR numbers, that mirrored our observations from the complex region on
390   chromosome 6 (**Fig. S8B**). Merger choice also impacted summarized frequencies of losses and gains (**Fig.**
391   **S8C**). It is typical for studies to note the proportion of gains and losses, but depending on the merger
392   used, a researcher might either report similar numbers (**Fig. S8C,** Jasmine) or conclude there is a bias
393   towards deletions (**Fig. S8C,** SVimmer). As such, some biological conclusions may depend on merger
394   choice.

395

396   To demonstrate the impact of stringency on SVR discovery across complex regions (**Fig. 3C, C-F**), we
397   compared SVCROWS-Default to 2 other stringencies determined by biologically-relevant characteristics
398   (see *Materials and Methods*). At all three levels, SVCROWS maintained the major genotypes (the large
399   gain-SV and boxed loss-SV), preserving the same breakpoints called in the input dataset (**Fig. 3E**).
400   SVCROWS also conserved unique SVs (only appearing in a single sample across the dataset) indicating

avoidance of overmerging (**Fig. 3F**). Through this analysis, we demonstrate 3 different SVCROWS applications that could be employed by a user; all of which reduced the complexity in the region, while maintaining the major patterns of SV frequency.

Figure 3. Options to control stringency and SVR construction in SVCROWS allows for optimized merging in a complex region. A single cell (SC) dataset consisting of 326 cells was used to evaluate SVR generation by multiple mergers. **A)** Integrated Genome Viewer (IGV) frames showing the output from the 5 other mergers. **B)** IGV view of VCFTools as a non-merged negative control. **C-F)** SVCROWS applied to the dataset over optimized stringencies (strict, concise, or default, see *Supplemental Methods* for more details): **C)** IGV view of resulting SVRs in a representative 3.2kb centromeric region of chromosome 6. Dashed boxes indicate the most abundant 'loss' genotype detected in the dataset. **D-F)** Quantification of panel C. **D)** Total number SVRs in the region after merging. **E)** Total number of SVs matched to the SVR representing the abundant deletion present in ~14% of the population. **F)** Abundance of each of resulting SVRs across each merger. 'Unique' are those that only appeared once in the population, '<10%' represent SVRs rare but present in more than one sample, '≥10%' are common SVRs.

SVCROWS produces accurate and sensitive SVR calls compared to other SV mergers.

Using the SC dataset, we showed the utility of SVCROWS for handling complex regions with the goal of discovering SVs. However, without a single-cell (SC) Truth Set for comparison, validation of the merged results is not possible. To evaluate accuracy, we employed the HG002 benchmarking dataset(42) from the Genome in a Bottle (GIAB) consortium, which is considered the gold standard for high-accuracy SV benchmarking because of the extensive evidence used in its creation. After SVs were called using multiple SV callers and sequencing technologies, the HG002-Truth Set was compiled and merged largely through manual curation to determine the most accurate breakpoints. Thus, merging decisions could be validated or rejected based on factors beyond a simple algorithmic framework. Because such manual scrutiny is not feasible in most analyses, we sought to test how well computational mergers could recapitulate the HG002-Truth Set construction.

To accomplish this, we merged the outputs of 5 SV callers used in generating the HG002-Truth Set. Each caller contained false-positive and false-negative SV calls (**Fig. 2A**) in addition to true positives relative to the HG002-Truth Set. The datasets were combined, cleaned, and filtered into a single input, termed the 'Aggregate List,' for direct comparison of mergers. The incompleteness and inaccuracy inherent in these five datasets (despite their high quality) mimic the technical variance and error present in most real-world data. Correcting and summarizing the variance through accurate merging is therefore a critical step for downstream analyses. The post-merged Aggregate Lists were compared between mergers to assess overall similarity, and then back to a subset of the HG002-Truth Set containing only SVs also present in the Aggregate List. This subset - termed the 'On-Truth Set' - allowed assessment of merger accuracy without the confounding effect of unmerged, irrelevant SVs (**Fig. 4**; a diagram of data preparation steps is provided in **Fig. S9**).

The HG002-Truth Set has a relatively low density of SVs (only ~2.5 SVs per 100-kilobases), but includes regions of high complexity as well as those with sparse SVs (**Fig. S10**). Flexibility in handling both cases is a challenging task for mergers. To objectively measure SVR coverage regardless of the level of complexity, we first used Jaccard indices to compare SV merger similarity on a per-base level. Higher Jaccard values reflect more similarity between lists generated by two different tools. Because each SV merger had the same input data (i.e. the Aggregate List), even minor differences in the Jaccard index represent regional under- or overmerging. Post merging, it was evident that SVCROWS displayed higher than average similarity to the other mergers (SVCROWS = 0.91, study average = 0.86), the wide range (0.62 – 0.99) of indices observed is consistent with our previous results suggesting that merger choice has major impacts on resulting SVRs (**Fig. 4A, Table S4**). For example, Truvari was more dissimilar across all comparisons (index average = 0.70), and CNVRuler was relatively more similar to other mergers (index average = 0.81), but still less than the study average (0.86). Further, because CNVRuler and Truvari both reported far fewer total SVRs than the other mergers (**Fig. 4B**), one could reason that both programs simply overmerge SVs. However, the Jaccard index between Truvari and CNVRuler is the lowest of the analysis (0.62) indicating algorithm-specific differences independently increased the rate of merging by each algorithm. Meanwhile, the similar SVimmer and Survivor algorithms exhibited a high Jaccard index (0.997).

In totality, each SV merger produced between ~70,000-80,000 SVRs from the Aggregate List (**Fig. 4B**) with Jasmine and SVCROWS yielding the most SVRs. When we compared the size distribution of resulting SVRs, all SV mergers produced a nearly identical SV size range except for Jasmine (**Fig. 4D**). Further investigation revealed that Jasmine introduced SVR size alterations in the form of both truncations and extensions not present in the unmerged Aggregate List (**Fig. S10A**). Despite its dependence on size to

454 define performance, the SVCROWS algorithm reflected a size distribution like other SV mergers,
455 indicating a lack of size-related bias.
456
We then compared the merged SVRs to the On-Truth Set to assess merging accuracy using the same
method as above (**Fig. 1A**). Jasmine and SVCROWS had the highest F1 scores of any SV mergers (**Fig. 4D**).
In all 3 overlap stringencies, the number of true positive SVRs were ~30% higher for SVCROWS and
Jasmine compared to other programs while false positives were 20-40% lower on average. SVCROWS
and Jasmine had similar false positive rates (only 3% higher for SVCROWS, on average across all
stringencies). However, Jasmine consistently had false negative merges whereas SVCROWS produced
none (**Table S5**). A lack of false negatives reflected SVCROWS' tendency to avoid undermerging especially
when regions lack complexity (**Fig. 4D**) and therefore circumvents loss of statistical power in downstream
analysis.
466
Interestingly, in a reversal of the relative accuracy in the simulated datasets (**Fig. 2C, H**). Truvari's F1 score
was the lowest in this study, which agrees with its low Jaccard indices (**Fig. 4A**). When we directly
visualized Truvari's SVRs, we observed occasional merging artifacts in sparse regions that increase the
rate of false negatives (**Fig. S10B**, examples 1 & 2). Further, in complex SVRs, Truvari fails to preserve
genotypes from the Aggregate List (**Fig. S10B**, example 3). While SVCROWS also makes errors in the
examples given, they can be rationalized by the input parameters chosen, unlike Truvari and Jasmine
(**Fig. S10**). Combined, these inconsistencies led to both under- and overmerging by the Truvari algorithm.
Overall, using a high-quality dataset, SVCROWS strikes a balance between accuracy and sensitivity to
maintain the potential for rare genotype discovery with no indication of SV size-related biases.
476
477
478

Figure 4. Comparison of SVRs from 6 different SV mergers to the HG002-Truth Set. We generated an SV Aggregate List from the GIAB consortium's HG002 reference genome datasets consisting of calls from 5 different constituent SV callers. The Aggregate List was then merged using 5 different SV merging algorithm types (yellow; distance based (Survivor, SVimmer), green; minimum spanning forest based (Jasmine), blue; multifactored (Truvari), light purple; static RO (CNVRuler), dark purple; size weighted RO (SVCROWS), and gray; pure redundancy (VCFTools)), and then assessed for a variety of metrics. **A)** The Aggregate List was used as input to calculate differences in merging on a base-pair coverage level, and resultant Jaccard Indices for each merger are indicated (**Table S4**). **B)** Comparison of total SVR number after merging. **C)** Distribution of SVR sizes after merging. **D)** The resulting SVRs from above were then overlapped to a subset of the HG002-Truth Set ('On-Truth Set', see *Materials and Methods*) at 3 stringencies. Left) Accuracy of each merger as a rate of true positive calling. Right) Precision and Recall of merger performance represented by F1 scores using the following definitions: True positive SVRs uniquely overlapped to a single Truth Set SV. False negative SVRs exhibit non-unique matching or do not match to any Truth Set SV. False positives are those that had no overlaps to the HG002-Truth Set (**Table S5**).

479
480

Discussion

SV datasets experience variance from increasingly large datasets(48) or by using different SV-calling
applications on the same dataset(49). Resolving SV locations relies on accurate sequencing, precise
mapping, and suitable coverage across a genomic region of interest. Such standards are hard to achieve,
especially across repetitive regions like telomeric, centromeric, rDNA arrays(50, 51), or when using low-
input methods like SC sequencing(52, 53). Therefore, exacting comparative assessments of tools, like the
SV mergers used in this study, are required.

By comparing SVCROWS with several modern and widely used SV merging algorithms, we showed that
SVCROWS is as accurate as existing tools for validation (**Fig. 4**) while also being capable of maintaining
diversity during SV discovery in a multi-sample dataset (**Fig. 3**). Additionally, optional functions of
SVCROWS can be tuned to overcome unique challenges presented by datasets (**Fig. 2**) or provide
different resolutions of complex regions in the dataset. Ultimately, it is the user's choice as to whether it
is more important to remove or maintain variation in the final SVR dataset. Because of this choice and its
potential impact, no merger can be said to be objectively 'better'. Instead, we emphasize the importance
of options and balanced outcomes, which are the core principles of SVCROWS.

While some SV mergers are a part of more comprehensive pipelines, their merging function cannot be
used independently of the rest of the pipeline, and/or the merging function has only been validated with
defined upstream components(15–17). SVCROWS, on the other hand, is an accessible, standalone
merger that is applicable to large or small datasets for both SV validation and discovery. To our
knowledge, it is the only R-based SV merger, requiring minimal computational expertise. Further, the
text-based input format of SVCROWS is flexible enough to incorporate all data types and formats. Finally,
SVCROWS construction around RO as the main means of determining SV matching (i.e. no assignment of
arbitrary 'scores' or 'weights') provides a level of transparency as to what caused two SVs to match or
not. Given its flexibility the program also has appeal for more general applications of comparing sets of
any genomic intervals, not just SVs.

Overall, we demonstrated that there are disparities between SV merging algorithms. The choice of which
to use is up to the researcher, but we present three considerations based on direct comparisons of SV
merging performance on both simple and complex datasets (**Fig. 5**). The first consideration is that the
output of the program must reduce the complexity of the region (**Fig. 5**, 'Output'). In this analysis, all
mergers were able to reduce SV redundancy; however, most failed to strike a balance between under- or
overmerging especially when a range of SV sizes were found in the same genomic neighborhood (e.g.
Jasmine, Truvari, and Survivor, **Fig. 2C** and **4D**). We demonstrated above that this is less problematic for
SVCROWS (**Figs. 2K, 3E** and **S5F**). A second consideration is that the architecture of the algorithm needs
to be compatible with the study design (**Fig. 5**, 'Technical'). The user should recognize that not all
mergers work on all platforms, nor are they compatible with all upstream steps. A third consideration is
that the algorithm type determines how the input SVs contribute to the resulting SVR (**Fig. 5**, 'Algorithm
Type'). For example, Jasmine includes RO as an optional parameter but prioritizes size and start location
for merging decisions. Conversely, SVCROWS prioritizes RO and better reflects the relationship between
SV size and potential functionality of those SV.

SV Merger	Output				Technical			Algorithm Type
	Complexity reduction	Small/Large SV balance*	Minimal Over-merging	Minimal Under-merging	Size-Weighted Comparisons	Universal Input text Input**	Packaged with other genomics tools	
Survivor	✔	✘	✔	✘	✘	✘	✔	Distance based
SVimmer	✔✔	✔	✘	✔	✘	✘	✔	
Jasmine	✔	✔	✔	✘	✘	✘	✔	Minimum spanning forest based (size x start)
Truvari	✔	✘	✔	✘	✘	✘	✔	Distance, overlap, sequence similarity based
CNVRuler	✔✔	✔	✘	✔	✘	✔	✔	Static RO based
SVCROWS	✔✔	✔	✔	✔	✔	✔	✘	Size-weighted RO based
VCFTools	✘	✘	✘	✘	✘	✘	✔	Pure redundancy removal Based

Figure 5. Comparison of tools based on proposed considerations to make when choosing an SV merging algorithm. SV merging evaluation of different features of each program (left); Key for algorithm each type of program uses (right).

SVCROWS was recently employed for SV discovery on a highly variable low-input genomics dataset and
facilitated novel biological conclusions(54). Here, we also showed how merger choice can affect data
reporting under biological contexts (**Fig. S8, 3A, 4C**), but correct merging can also aid in supporting
causal relationships between genomic features. For example, a particular region on chromosome 16 in
the ovarian/breast cancer SC dataset contained many SVs (**Fig. S11**). Upon further investigation, this
region was part of a known super cis-regulatory elements (SCRE). SVs in SCREs can rapidly alter
expression patterns in ways that drive developmental changes, phenotypic diversity, and are associated
with worse cancer outcomes(55). According to the ENCODE database(56, 57), these SVs in the SC dataset
fell into regions responsible for both upregulating and downregulating 4 genes immediately
downstream(57). All 4 of these genes are implicated in ovarian and breast cancer in disparate capacities:
some are more highly transcribed in ovarian or breast cancers, while others are less transcribed (**Fig.**
S11)(58–61). Importantly, by preserving the variation across this region, SVCROWS helps convey that SVs
called within the SCRE experience populational heterogeneity and may contribute to oncogenicity
through diverse mechanisms, which in turn, can inform future experimental studies.

We do recognize that there are some limitations to SVCROWS implementation. While the SVCROWS'
input format is flexible, manual conversion from other formats may be necessary and add extra steps to
a pipeline. Fortunately, SVCROWS includes quick-conversion tools to go between SVCROWS-input, BED,
and VCF formats. Additionally, because SVCROWS makes more comparisons-per-SV to ensure accuracy,
its computational time is longer than that of similar programs (**Fig. S3**). While running SVCROWS in R is
more accessible, R-based software is notably slower than other languages. Further, the SVCROWS
algorithm does not include sequence information during merging decisions. Other tools like Truvari or
PanPop(16) can evaluate sequence identity at single base pair resolution in certain SVs (e.g. >50bp
insertions and deletions), which may be more beneficial for studies where variance is low across large
populations. However, these mergers are not compatible with all upstream calling tools required to

achieve that level of precision. Further, a granular analysis of their ability to resolve complex regions
(such as in **Fig. 3**) was not provided in those previous studies.
554
555 While these SV merging tools have been used to great effect in the past, SVCROWS promises
556 improvements to the field. This is especially true given the growing number of large, multi-sample
557 datasets that are harder to computationally refine accurately. Similarly, having tools like SVCROWS that
558 are capable of resolving uncommon mutations in complex genomic regions will be of continued
559 importance to researchers in need of high precision tools.
560
561
562

563 **Conflicts of Interest**
564 The authors report no conflicts of interest.
565
566 **Funding**
567 We acknowledge funding from NIH (**R01AI150856, to JLG**) and NSF-NRT award (**2021791**, to NJB).
568
569 **Data Availability**
570 SVCROWS can be downloaded as a Package or R-Markdown file at:
571 https://github.com/A-Crow-Nowhere/SVCROWS.git
572 The source code for SVCROWS can be accessed at https://doi.org/10.6084/m9.figshare.29099801.v1
573
574 Links to the GIAB project and EGA data files can be found in the *Supplemental Methods.*
575
576 **Contact**: jlg5fw@virginia.edu; njb8sg@virginia.edu
577

Author Contributions Statement

Noah Brown: Conceptualization, Data curation, Investigation, Formal analysis, Software, Validation,
Visualization, Writing-original draft, writing-review and editing

Charles Danis: Data curation, Formal analysis, Software

Vazira Ahmedjanova: Software

Jennifer Guler: Conceptualization, Funding acquisition, Methodology, Project administration, Resources,
writing-review and editing

Bibliography

1. Flint,J., Hill,A.V., Bowden,D.K., Oppenheimer,S.J., Sill,P.R., Serjeantson,S.W., Bana-Koiri,J., Bhatia,K., Alpers,M.P. and Boyce,A.J. (1986) High frequencies of alpha-thalassaemia are the result of natural selection by malaria. *Nature*, **321**, 744–750.

2. Gonzalez,E., Kulkarni,H., Bolivar,H., Mangano,A., Sanchez,R., Catano,G., Nibbs,R.J., Freedman,B.I., Quinones,M.P., Bamshad,M.J., *et al.* (2005) The influence of CCL3L1 gene-containing segmental duplications on HIV-1/AIDS susceptibility. *Science*, **307**, 1434–1440.

3. Lukácová,M., Barák,I. and Kazár,J. (2008) Role of structural variations of polysaccharide antigens in the pathogenicity of Gram-negative bacteria. *Clin. Microbiol. Infect. Off. Publ. Eur. Soc. Clin. Microbiol. Infect. Dis.*, **14**, 200–206.

4. Marshall,C.R., Noor,A., Vincent,J.B., Lionel,A.C., Feuk,L., Skaug,J., Shago,M., Moessner,R., Pinto,D., Ren,Y., *et al.* (2008) Structural Variation of Chromosomes in Autism Spectrum Disorder. *Am. J. Hum. Genet.*, **82**, 477-488.

5. Songsomboon,K., Brenton,Z., Heuser,J., Kresovich,S., Shakoor,N., Mockler,T. and Cooper,E.A. (2021) Genomic patterns of structural variation among diverse genotypes of Sorghum bicolor and a potential role for deletions in local adaptation. *G3 GenesGenomesGenetics*, **11**, jkab154.

6. Carvalho,C.M.B. and Lupski,J.R. (2016) Mechanisms underlying structural variant formation in genomic disorders. *Nat. Rev. Genet.*, **17**, 224–238.

7. Dwarshuis,N., Kalra,D., McDaniel,J., Sanio,P., Alvarez Jerez,P., Jadhav,B., Huang,W. (Eddy), Mondal,R., Busby,B., Olson,N.D., *et al.* (2024) The GIAB genomic stratifications resource for human reference genomes. *Nat. Commun.*, **15**, 9029.

8. Auton,A., Abecasis,G.R., Altshuler,D.M., Durbin,R.M., Abecasis,G.R., Bentley,D.R., Chakravarti,A., Clark,A.G., Donnelly,P., Eichler,E.E., *et al.* (2015) A global reference for human genetic variation. *Nature*, **526**, 68–74.

9. Tan,K.-T., Slevin,M.K., Meyerson,M. and Li,H. (2022) Identifying and correcting repeat-calling errors in nanopore sequencing of telomeres. *Genome Biol.*, **23**, 180.

10. Sedlazeck,F.J., Rescheneder,P., Smolka,M., Fang,H., Nattestad,M., von Haeseler,A. and Schatz,M.C. (2018) Accurate detection of complex structural variations using single-molecule sequencing. *Nat. Methods*, **15**, 461–468.

11. Zook,J.M., Chapman,B., Wang,J., Mittelman,D., Hofmann,O., Hide,W. and Salit,M. (2014)
Integrating human sequence data sets provides a resource of benchmark SNP and indel
genotype calls. *Nat. Biotechnol.*, **32**, 246–251.

12. Alonge,M., Wang,X., Benoit,M., Soyk,S., Pereira,L., Zhang,L., Suresh,H., Ramakrishnan,S.,
Maumus,F., Ciren,D., *et al.* (2020) Major Impacts of Widespread Structural Variation on
Gene Expression and Crop Improvement in Tomato. *Cell*, **182**, 145-161.e23.

13. Heller,D. and Vingron,M. (2021) SVIM-asm: structural variant detection from haploid and
diploid genome assemblies. *Bioinformatics*, **36**, 5519–5521.

14. Masood,D., Ren,L., Nguyen,C., Brundu,F.G., Zheng,L., Zhao,Y., Jaeger,E., Li,Y., Cha,S.W.,
Halpern,A., *et al.* (2024) Evaluation of somatic copy number variation detection by NGS
technologies and bioinformatics tools on a hyper-diploid cancer genome. *Genome Biol.*,
25, 163.

15. Eggertsson,H.P., Kristmundsdottir,S., Beyter,D., Jonsson,H., Skuladottir,A., Hardarson,M.T.,
Gudbjartsson,D.F., Stefansson,K., Halldorsson,B.V. and Melsted,P. (2019) GraphTyper2
enables population-scale genotyping of structural variation using pangenome graphs.
Nat. Commun., **10**, 5402.

16. Zheng,Z., Zhu,M., Zhang,J., Liu,X., Hou,L., Liu,W., Yuan,S., Luo,C., Yao,X., Liu,J., *et al.* (2024) A
sequence-aware merger of genomic structural variations at population scale. *Nat.*
Commun., **15**, 960.

17. Kirsche,M., Prabhu,G., Sherman,R., Ni,B., Battle,A., Aganezov,S. and Schatz,M.C. (2023)
Jasmine and Iris: Population-scale structural variant comparison and analysis. *Nat.*
Methods, **20**, 408–417.

18. English,A.C., Menon,V.K., Gibbs,R.A., Metcalf,G.A. and Sedlazeck,F.J. (2022) Truvari: refined
structural variant comparison preserves allelic diversity. *Genome Biol.*, **23**, 271.

19. Ji-Hong Kim, Hae-Jin Hu, Seon-Hee Yim, Joon Seol Bae, Seon-Young Kim, Yeun-Jun Chung,
(2012) CNVRuler: a copy number variation-based case–control association analysis tool |
Bioinformatics | Oxford Academic. *Bioinformatics*, **28**, 1790–1792.

20. Olson,N.D., Wagner,J., Dwarshuis,N., Miga,K.H., Sedlazeck,F.J., Salit,M. and Zook,J.M. (2023)
Variant calling and benchmarking in an era of complete human genome sequences. *Nat.*
Rev. Genet., **24**, 464–483.

21. Handsaker,R.E., Van Doren,V., Berman,J.R., Genovese,G., Kashin,S., Boettger,L.M. and
McCarroll,S.A. (2015) Large multiallelic copy number variations in humans. *Nat. Genet.*,
47, 296–303.

22. Handsaker,R.E., Korn,J.M., Nemesh,J. and McCarroll,S.A. (2011) Discovery and genotyping of
genome structural polymorphism by sequencing on a population scale. *Nat. Genet.*, **43**,
269–276.

23. Venkatapoorna,C.M.K., Ayine,P., Parra,E.P., Koenigs,T., Phillips,M., Babu,J.R., Sandey,M. and
Geetha,T. (2019) Association of Salivary Amylase (AMY1) Gene Copy Number with
Obesity in Alabama Elementary School Children. *Nutrients*, **11**, 1379.

24. Jeffares,D.C., Jolly,C., Hoti,M., Speed,D., Shaw,L., Rallis,C., Balloux,F., Dessimoz,C., Bähler,J.
and Sedlazeck,F.J. (2017) Transient structural variations have strong effects on
quantitative traits and reproductive isolation in fission yeast. *Nat. Commun.*, **8**, 14061.

25. Danecek,P., Bonfield,J.K., Liddle,J., Marshall,J., Ohan,V., Pollard,M.O., Whitwham,A.,
Keane,T., McCarthy,S.A., Davies,R.M., *et al.* (2021) Twelve years of SAMtools and
BCFtools. *GigaScience*, **10**, giab008.

26. Sievert,C. (2020) Interactive Web-Based Data Visualization with R, plotly, and shiny Chapman
and Hall/CRC.

27. Freeberg,M.A., Fromont,L.A., D'Altri,T., Romero,A.F., Ciges,J.I., Jene,A., Kerry,G., Moldes,M.,
Ariosa,R., Bahena,S., *et al.* (2021) The European Genome-phenome Archive in 2021.
Nucleic Acids Res., **50**, D980–D987.

28. Duan,D.-M., Cheng,C., Huang,Y.-S., Chung,A., Chen,P.-X., Chen,Y.-A., Hsu,J.S. and Chen,P.-L.
(2025) Comparisons of performances of structural variants detection algorithms in
solitary or combination strategy. *PLOS ONE*, **20**, e0314982.

29. Funnell,T., O'Flanagan,C.H., Williams,M.J., McPherson,A., McKinney,S., Kabeer,F., Lee,H.,
Salehi,S., Vázquez-García,I., Shi,H., *et al.* (2022) Single-cell genomic variation induced by
mutational processes in cancer. *Nature*, **612**, 106–115.

30. Layer,R.M., Chiang,C., Quinlan,A.R. and Hall,I.M. (2014) LUMPY: a probabilistic framework
for structural variant discovery. *Genome Biol.*, **15**, R84.

31. Mahmoud,M., Gobet,N., Cruz-Dávalos,D.I., Mounier,N., Dessimoz,C. and Sedlazeck,F.J.
(2019) Structural variant calling: the long and the short of it. *Genome Biol.*, **20**, 246.

32. Cameron,D.L., Di Stefano,L. and Papenfuss,A.T. (2019) Comprehensive evaluation and
characterisation of short read general-purpose structural variant calling software. *Nat.
Commun.*, **10**, 3240.

33. Jaber,D., Zhang,J. and Godley,L.A. Detecting likely germline variants during tumor-based
molecular profiling. *J. Clin. Invest.*, **135**, e190264.

34. *Human Molecular Genetics*. NLM Catalog. U.S. National Library of Medicine.
https://www.ncbi.nlm.nih.gov/nlmcatalog/101523906

35. Shabalina,S.A., Ogurtsov,A.Y., Kondrashov,V.A. and Kondrashov,A.S. (2001) Selective
constraint in intergenic regions of human and mouse genomes. *Trends Genet.*, **17**, 373–
376.

36. Kołomański,M., Szyda,J., Frąszczak,M. and Mielczarek,M. (2022) DNA sequence features
underlying large-scale duplications and deletions in human. *J. Appl. Genet.*, **63**, 527–533.

37. Rajic,Z.A., Jankovic,G.M., Vidovic,A., Milic,N.M., Skoric,D., Pavlovic,M. and Lazarevic,V.
(2005) Size of the protein-coding genome and rate of molecular evolution. *J. Hum.*
Genet., **50**, 217–229.

38. Rhie,A., Nurk,S., Cechova,M., Hoyt,S.J., Taylor,D.J., Altemose,N., Hook,P.W., Koren,S.,
Rautiainen,M., Alexandrov,I.A., *et al.* (2023) The complete sequence of a human Y
chromosome. *Nature*, **621**, 344–354.

39. Rautiainen,M., Nurk,S., Walenz,B.P., Logsdon,G.A., Porubsky,D., Rhie,A., Eichler,E.E.,
Phillippy,A.M. and Koren,S. (2023) Telomere-to-telomere assembly of diploid
chromosomes with Verkko. *Nat. Biotechnol.*, **41**, 1474–1482.

40. Wang,T., Antonacci-Fulton,L., Howe,K., Lawson,H.A., Lucas,J.K., Phillippy,A.M., Popejoy,A.B.,
Asri,M., Carson,C., Chaisson,M.J.P., *et al.* (2022) The Human Pangenome Project: a global
resource to map genomic diversity. *Nature*, **604**, 437–446.

41. Nurk,S., Koren,S., Rhie,A., Rautiainen,M., Bzikadze,A.V., Mikheenko,A., Vollger,M.R.,
Altemose,N., Uralsky,L., Gershman,A., *et al.* (2022) The complete sequence of a human
genome. *Science*, **376**, 44–53.

42. Zook,J.M., Hansen,N.F., Olson,N.D., Chapman,L., Mullikin,J.C., Xiao,C., Sherry,S., Koren,S.,
Phillippy,A.M., Boutros,P.C., *et al.* (2020) A robust benchmark for detection of germline
large deletions and insertions. *Nat. Biotechnol.*, **38**, 1347–1355.

43. Pacific Biosciences. *pbsv* [Computer software]. GitHub repository.
https://github.com/PacificBiosciences/pbsv (accessed 2025).

44. Smolka,M., Paulin,L.F., Grochowski,C.M., Horner,D.W., Mahmoud,M., Behera,S., Kalef-
Ezra,E., Gandhi,M., Hong,K., Pehlivan,D., *et al.* (2024) Detection of mosaic and
population-level structural variants with Sniffles2. *Nat. Biotechnol.*, **42**, 1571–1580.

45. Alkan,C., Kidd,J.M., Marques-Bonet,T., Aksay,G., Antonacci,F., Hormozdiari,F., Kitzman,J.O.,
Baker,C., Malig,M., Mutlu,O., *et al.* (2009) Personalized copy number and segmental
duplication maps using next-generation sequencing. *Nat. Genet.*, **41**, 1061–1067.

46. Mohiyuddin,M., Mu,J.C., Li,J., Bani Asadi,N., Gerstein,M.B., Abyzov,A., Wong,W.H. and
Lam,H.Y.K. (2015) MetaSV: an accurate and integrative structural-variant caller for next
generation sequencing. *Bioinformatics*, **31**, 2741–2744.

47. Danecek,P., Auton,A., Abecasis,G., Albers,C.A., Banks,E., DePristo,M.A., Handsaker,R.E.,
Lunter,G., Marth,G.T., Sherry,S.T., *et al.* (2011) The variant call format and VCFtools.
Bioinformatics, **27**, 2156–2158.

48. Conrad,D.F. and Hurles,M.E. (2007) The population genetics of structural variation. *Nat.*
Genet., **39**, S30–S36.

49. Joe,S., Park,J.-L., Kim,J., Kim,S., Park,J.-H., Yeo,M.-K., Lee,D., Yang,J.O. and Kim,S.-Y. (2024)
Comparison of structural variant callers for massive whole-genome sequence data. *BMC*
Genomics, **25**, 318.

50. Levy-Sakin,M., Pastor,S., Mostovoy,Y., Li,L., Leung,A.K.Y., McCaffrey,J., Young,E., Lam,E.T.,
Hastie,A.R., Wong,K.H.Y., *et al.* (2019) Genome maps across 26 human populations
reveal population-specific patterns of structural variation. *Nat. Commun.*, **10**, 1025.

51. Rothschild,D., Susanto,T.T., Sui,X., Spence,J.P., Rangan,R., Genuth,N.R., Sinnott-Armstrong,N.,
Wang,X., Pritchard,J.K. and Barna,M. (2024) Diversity of ribosomes at the level of rRNA
variation associated with human health and disease. *bioRxiv*,
10.1101/2023.01.30.526360.

52. Mallory,X.F., Edrisi,M., Navin,N. and Nakhleh,L. (2020) Methods for copy number aberration
detection from single-cell DNA-sequencing data. *Genome Biol.*, **21**, 1–22.

53. Ning,L., Liu,G., Li,G., Hou,Y., Tong,Y. and He,J. (2014) Current Challenges in the Bioinformatics
of Single Cell Genomics. *Front. Oncol.*, **4**, 7.

54. Brown,N., Luniewski,A., Yu,X., Warthan,M., Liu,S., Zulawinska,J., Ahmad,S., Congdon,M.,
Santos,W., Xiao,F., *et al. bioRxiv* (2024) Replication stress increases de novo CNVs across
the malaria parasite genome. 10.1101/2024.12.19.629492.

55. Wittkopp,P.J. and Kalay,G. (2012) Cis-regulatory elements: molecular mechanisms and
evolutionary processes underlying divergence. *Nat. Rev. Genet.*, **13**, 59–69.

56. Huang,H., Hu,J., Maryam,A., Huang,Q., Zhang,Y., Ramakrishnan,S., Li,J., Ma,H., Ma,V.W.S.,
Cheuk,W., *et al.* (2021) Defining super-enhancer landscape in triple-negative breast
cancer by multiomic profiling. *Nat. Commun.*, **12**, 2242.

57. Leistico,J.R., Saini,P., Futtner,C.R., Hejna,M., Omura,Y., Soni,P.N., Sandlesh,P., Milad,M.,
Wei,J.-J., Bulun,S., *et al.* (2021) Epigenomic tensor predicts disease subtypes and reveals
constrained tumor evolution. *Cell Rep.*, **34**, 108927.

58. Kozole,S.L. and Beningo,K.A. (2024) Myosin Light Chains in the Progression of Cancer. *Cells*,
13, 2081.

59. Liu,Y., Deng,H., Liang,L., Zhang,G., Xia,J., Ding,K., Tang,N. and Wang,K. (2020) Depletion of
VPS35 attenuates metastasis of hepatocellular carcinoma by restraining the Wnt/PCP
signaling pathway. *Genes Dis.*, **8**, 232–240.

60. Qi,G., Ma,H., Teng,K., Gai,P., Gong,Y., Chen,J., Luo,X. and Kong,B. (2025) SHCBP1 promotes
cisplatin resistance of ovarian cancer through AKT/mTOR/Autophagy pathway. *Apoptosis*
Int. J. Program. Cell Death, **30**, 83–98.

61. Lin,Y., Zhang,Y., Tuo,Z., Gao,L., Ding,D., Bi,L., Yu,D., Lv,Z., Wang,J. and Chen,X. (2023) ORC6, a
novel prognostic biomarker, correlates with T regulatory cell infiltration in prostate
adenocarcinoma: a pan-cancer analysis. *BMC Cancer*, **23**, 285.

773