BlueBerry: Closed-loop wireless optogenetic manipulation in freely moving animals

Ali Nourizonoz[1]*, Benoit Girard [1], Maëlle Guyoton[1], Gregorio Galiñanes [1], Raphael Thurnherr [1], Sebastien Pellat[1], Camilla Bellone[1], Daniel Huber[1]*

1 University of Geneva, Department of Basic Neurosciences, Geneva, Switzerland
* Corresponding authors

Abstract

Optogenetics is a powerful tool for neuroscientists, enabling manipulations of neuronal activity to explore their effects on behavior. Recent advances in wireless technology enabled the development of novel remotely controlled optogenetic devices, thereby promising to facilitate the study of more complex behaviors, including social interactions. Yet, studying such behaviors in real time and automated manner in large scale naturalistic settings or with multiple animals remains challenging. In addition, many published devices can only be reproduced in labs having specific engineering skills and fabrication facilities and are thus not accessible for the larger neuroscience community. Here we introduce BlueBerry, an open-source, multi-channel optogenetic device that can be assembled with off the shelf components. The lightweight (1.4 g) design and robust long-range communication makes Blueberry an ideal tool for behavior-triggered optogenetic studies with multiple animals interacting freely in a large-scale setting. We show how BlueBerry can be used to guide decision making during spatial navigation and demonstrate for the first time that social dynamics can be rapidly altered in groups of mice by triggering specific social behavior with closed-loop optogenetics.

Introduction

Understanding the link between brain and behavior requires detailed investigation of the related neural circuits (Krakauer et al. 2017). Although neural recordings play a crucial role to observe correlates with behaviors, manipulating brain circuits is essential to establish the causality of involved neural networks. To this end, neuroscientists have widely adopted optogenetic techniques for precise and controlled manipulation of neuronal activity in behaving animals (Boyden et al. 2005; Deisseroth 2011).

Traditionally, in freely moving settings, optogenetic stimulation has been carried out with tethered optical fibers to channel the light from its source to the brain (Adamantidis et al. 2007; Gradinaru et al. 2009; Tsai et al. 2009). The development of compact and power efficient computing devices have evolved optogenetic techniques toward wireless technology, allowing to study animal behavior with minimal physical constraints (Kim et al. 2013; Park et al. 2015; Montgomery et al. 2015; Jeong et al. 2015). Furthermore, wireless neuronal manipulations expanded the range of behavioral studies with freely moving animals, enabling the exploration of complex three-dimensional environments (S.-G. Park et al. 2018) and social settings (Yang et al. 2021; Li et al. 2022). For these situations the use of traditional tethered optical fiber setups would be challenging, as they restrict the animal's range of movement or can get tangled with the tethers of other animals or with structures found in a natural setting.

Approaches for developing wireless optogenetic devices have been mainly categorized in battery-free or battery powered designs. The primary benefit of using battery-free wireless optogenetics (Kim et al. 2013; Yang et al. 2021; Montgomery et al. 2015; Mickle et al. 2019; Shin et al. 2017) is their capability to operate for extended periods, making them ideal for experimental setups that require long experiment durations. However, the range of these devices are restricted to relatively small spaces as a magnetic induction coil system has to be installed around the experimental arena, therefore limiting their usage in large-scale or complex volumetric space (Shin et al. 2017). Moreover, battery-free designs often require chronic implantation of the entire device, impacting their usability and flexibility, as they cannot be easily reused on multiple animals and can be more invasive (Yang et al. 2021). Alternatively, battery-powered designs for wireless optogenetic have been developed in parallel for freely moving animals (Kathe et al. 2022; Li et al. 2022; Michoud et al. 2021). This approach can offer a scalable range, potentially extending to several meters and is not confined to two-dimensional

laboratory cage environments. Battery-powered designs only require the implantation of miniature light sources, as the rest can be disconnected. This can be convenient since it offers a large flexibility in designing minimally invasive light sources to be used in different brain regions.

Despite significant advancements in wireless optogenetics, many devices remains complex to reproduce as they are either lacking detailed documentation or are not publicly available (open-source) for the broader scientific community(Li et al. 2022; Jeong et al. 2015; Michoud et al. 2021; Kathe et al. 2022). Even in the case of open-source documentation some devices can be difficult to reproduce, requiring specialized equipment and conditions including clean room fabrication facilities that are not readily accessible to most neuroscience researchers (McCall et al. 2013; Yang et al. 2022). Finally, many devices are tailored for specific use cases or limited to specific experimental arenas (Mickle et al. 2019; Kathe et al. 2022; Michoud et al. 2021), therefore posing challenges on integrating them with existing behavioral frameworks. With the currently available wireless devices, triggering optogenetic stimulation based on the real time detection of specific social interactions between multiple animals would be challenging.

Here we introduce the BlueBerry (www.OptoBlueBerry.com), a novel battery-powered multichannel optogenetic system controlled and programmed remotely through standard Bluetooth Low Energy (BLE) communication protocol. The small and compact design, low cost and high flexibility of generating and controlling the stimulation patterns make BlueBerry ideal for optogenetic applications in freely-moving animals. To demonstrate BlueBerry's capabilities, we provide several examples of closed-loop behavior-triggered manipulations in complex large-scale environments, including guiding navigation through artificial sensory cues, and influencing social dynamics by interactively targeting individuals in a multi-animal setting. We believe that the ease of implementation of the BlueBerry device through its open-source documentation and modular integration into existing behavioral frameworks through a dedicated control unit (BlueHub), will lead to its widespread adoption in systems neuroscience research.

Results

Implementation of Blueberry wireless optogenetic system

To wirelessly deliver optogenetic stimulation to freely moving mice in large scale or multi-animal settings, we developed a battery-powered, compact (14 x 10.5 x 7 mm) and light (1.4 g) remote optogenetic system capable of controlling up to two independent channels (Fig. 1a). We named our device BlueBerry as it is the size and the weight of a blueberry and uses bluetooth for wireless communication. The BlueBerry includes a dedicated stand-alone bluetooth module communicating with a microcontroller through a custom designed printed circuit board (PCB, Fig. 1b and Supplementary Fig. 1 & 2) to deliver high-power pulses to both output channels with latencies below 30 ms for distances up to 3 m (Supplementary Fig. 6). Stimulation protocols such as pulse-width and frequency (independently for each stimulation channel) can be configured on-the-fly for each of the BlueBerry devices through a user-friendly Arduino-based control unit, the BlueHub (Fig. 1c & Supplementary Fig. 3). The BlueHub additionally includes up to four digital input channels that can be triggered by any external behavioral framework (rising edge of a 3-5 V signal), allowing each channel to activate an assigned BlueBerry unit, based on specified stimulation parameters (Fig. 1c). The BlueBerry is connected to an implanted LED light source. These implants (Fig. 1d) are capable of either targeting superficial cortical regions using miniature high-power LEDs (up to 60 mW) or deep-brain regions by coupling each LED with an optical fiber (7 to 9 mW at the output of a 400 um diameter fiber, Supplementary Fig. 5). Taken together, BlueBerry can be smoothly integrated into existing behavioral frameworks via the low-latency BlueHub control unit, enabling diverse applications for studying freely moving animals in real-time closed-loop experiments.

Figure 1. Description of BlueBerry wireless optogenetic system. a) Left) Left) Front and back side of the BlueBerry wireless optogenetic device with a blueberry fruit in the middle. Right) Image of a mouse carrying a BlueBerry device connected to the multichannel LED implant fixed on the skull. **b)** Exploded 3D view of the BlueBerry device illustrating all miniature electronic components. **c)** Simplified schematic of the control BlueHub control unit, the BlueBerry device and LED implants. Each BlueHub input channel (BNC1–4) can be assigned to a function that includes the BlueBerry (BlueBerry id) device to activate and the corresponding stimulation parameters (stimulation channel, frequency, pulse width and number of pulses). When a channel is triggered, the BlueHub sends a Bluetooth packet to the assigned BlueBerry device containing the specified stimulation protocol. On the BlueBerry side, Bluetooth packets are decoded inside the bluetooth module and communicated with the microcontroller where each output stimulation channel is configured in terms of frequency, pulse width and number of pulses. **d)** Multichannel implants targeting superficial cortical layers (top) through surface mount micro LEDs or deep brain regions through custom made fiber coupled LED (bottom).

Closed-loop manipulation of large-scale navigation

Artificial sensory cues delivered via optogenetic stimulation of sensory cortical regions, allow isolation of specific sensory pathways and precise control over the timing and intensity of stimulus, thereby enabling detailed investigations of sensory processing. Mice (N=6) expressing channelrhodopsin (ChR2) bilaterally in the sensory barrel field were implanted with flexible two-channel micro-LED implants (Fig. 2a, Supplementary Fig. 5), allowing to place each micro-LED on top of the targeted cortical areas (Fig. 2a&b). Inspired by an infinite virtual maze system for insects (Hassenstein and Reichardt 1956) we designed infinite Y-mazes of different sizes (1mx1m and 2.5 m x 2.5 m, Supplementary Fig. 7) consisting of arms containing a water port as reward at their center and connected through four intersections (Fig. 2c). In this paradigm, water-restricted mice arriving at any intersection triggered the activation of a directional optogenetic cue, by activating either the left or the right micro-LED (stimulating the contralateral sensory cortex, see Methods). Mice were trained to associate these artificial sensory cues with the rewarded direction and to indicate their decision by selecting the correct path leading to the rewarded port (Fig. 2d). Real-time location tracking and stimulation delivery were achieved using the EthoLoop system (Nourizonoz et al., 2020), which ensured precise closed-loop operation with minimal latency (see Methods). All mice expressing ChR2 (n=6, 3 mice per maze, see Methods) successfully associated sensory cortex stimulation with the correct direction after visiting each intersection, while control mice (not expressing ChR2) performed at chance level (n=5, 3 small maze and 2 in large maze, Fig. 2e, Supplementary Fig. 8).

Interestingly, we also observed a brief transient decrease in the speed of mice expressing ChR2 upon the delivery of the optogenetic stimulation to the sensory cortex (Supplementary Fig. 9). This motor effect was persistent from the first to the last training sessions and was absent in control mice (Supplementary Fig. 9). To determine if this effect was related to the optogenetic cortical activation or to the decision-making process, we used BlueBerry to provide visible visual cues instead of optogenetic stimulation (Methods and Supplementary Fig. 10). Mice could reliably use visual cues to navigate but showed no speed change, suggesting the slowdown during optogenetic trials is not linked to decision-making processing (Supplementary Fig. 9). A possible explanation for such fast and reproducible motor effects caused by stimulation of the sensory barrel field could be the activation of direct descending pathways affecting the motor centers (Matyas et al. 2010).

Taken together, these experiments demonstrate the ability of BlueBerry to be used to remotely shape decision making behavior of freely moving mice using optogenetic stimulation when navigating in large-scale environments.

Figure 2: Closed-loop control of large-scale navigation using the BlueBerry. a) Coronal section of mouse brain with bilateral ChR2 expression on the barrel sensory field and the LED implant setup. **b)** Top view of the arrangement of the two-channel LED implant on the skull before covering with dental acrylic. **c & d)** Detailed configuration of the infinit Y-maze along with an example highlighting the trial structure. Mice arriving at the intersection zones received optogenetic stimulation based on a randomly chosen path (contralateral barrel sensory field) that leads to the arm containing a rewarded port. High-power blue light flashes, matched in frequency to the optogenetic stimulation, were delivered at each intersection to mask any diffused light from the multi-channel LED on the animal's head, thereby preventing the mice from relying on visual cues. Reward is only delivered when mice choose the correct path and arrive in the corresponding reward zone. **e)** Performance of mice in first (no stimulation) versus the last session (4ms - 20Hz) to associate artificial sensory cues with the correct chosen path at every intersection in both small and large infinit Y-maze (N =6 ChR2 expressing mice, blue lines, 3 mice per maze; N=5 control mice not expressing ChR2, grey lines, 3 for small and 2 for large maze; two-way repeated measure ANOVA, main and interaction effect $P < 0.01$, pairwise two-sample t-test, Tukey post hoc test, ***$P < 0.001$).

Closed-loop shaping of social behavior in groups of mice

Studying social behaviors in mice requires an in-depth understanding of how they are shaped, developed and what factors contribute to altering their dynamics. Social hierarchies, established early and stable over time, serve as a prime example (Lindzey, Winston, and Manosevitz 1961; Wang et al. 2011; Fetcho et al. 2023). Characterized by dominance and submission relationships, they influence social interactions, often presented as asymmetric agonistic behaviors such as chasing and aggression (Wang et al. 2011; So et al. 2015). Here, we ask whether the manipulation of dopaminergic neurons in the ventral tegmental area (VTA-DA),

known for their role in social reinforcement learning (Solié et al. 2022), could also influence agonistic social behaviors.

We used BlueBerry to reinforce social interactions, which oppose the natural hierarchical dominance in groups of freely moving mice through optogenetic stimulation of VTA-DA neurons. Mice (N=9 males, housed in groups of 3 per cages) expressing channelrhodopsin (ChR2) in VTA-DA neurons were implanted with the fiber-coupled LED system (Supplementary Fig. 5), targeting the VTA (Fig. 3a, Methods). We first confirmed the functionality of the implant and virus expression via closed-loop reinforced place preference experiments, where all subjects showed a significant preference for zones associated with optogenetic stimulation (Fig. 3b&c).

We then investigated the social rank of each animal by performing the tube test (Lindzey, Winston, and Manosevitz 1961) across pairs of cagemates (Fig. 3d&e, Methods). Subsequently, mice from the same cage were monitored in a large 0.5 x 0.5m open field arena (Supplementary Fig. 11) for 2 hours per day, during which the total duration of social unilateral interactions were quantified in real-time (Fig. 3f, pre-stimulation baseline) by tracking their body parts with DeepLabCut-Live ((Kane et al. 2020), Methods) To investigate whether the established hierarchy could be challenged by selectively reinforcing certain social behaviors, we optogenetically stimulated VTA-DA neurons in lower-ranked mice whenever they initiated unilateral interaction (chasing) toward a higher-ranked animal. Specifically, for each cage, we attached two BlueBerry devices to the implants of the mice in ranks 2 and 3. These devices delivered VTA-DA stimulation when rank 2 chased rank 1, and when rank 3 chased rank 2 (Fig. 3g; Supplementary Fig. 12). This reinforcement protocol was conducted over eight consecutive days (2 hours per day) in the open-field arena, followed by a three-day observation period without stimulation (post-stimulation sessions) to assess any lasting effects on the social interactions.

During the reinforcement phase, all chasing behavior initiated by the lower rank mice including the ones not directly reinforced (rank 3 toward rank 1) significantly increased (Fig. 3h, N=9 mice, 3 interaction sets per cage, Supplementary Fig. 13). However, this effect was not sustained at post-stimulation sessions and did not impact the rank in the tube test followed after the reinforcement phase (Supplementary Fig. 13). Remarkably, while the closed-loop optogenetic stimulation independently reinforced only specific dyadic interactions, it influenced the entire group's dynamic, where all the cagemates at the same time formed a "moving train" led by the top-ranked animal in each cage (Fig. 3i).

These experiments demonstrate that VTA-DA stimulation can transiently override behaviors linked to natural social hierarchies, influencing group dynamics beyond the directly stimulated dyadic interactions. To our knowledge, this study is the first to implement real-time closed-loop optogenetic through wireless optogenetic stimulation in multiple interacting mice. This highlights the potential of BlueBerry for precise, behavior-specific reinforcement in freely moving groups, making it a powerful tool for investigating the neural basis of social behavior in multi-animal settings.

Figure 3: Closed-loop shaping of social behavior in groups of mice. **a)** (Top) Fiber-coupled LED setup for freely moving mice to optogenetically stimulate DA neurons expressing ChR2 in the VTA. (bottom) Representative histology of the optical fiber trace and virus expression in the VTA region. **b)** Representative trajectory of a mouse during place preference tasks (two chambers setting) where they received VTA optogenetic stimulation using the BlueBerry device upon entering a conditioned chamber. **c)** Performance of all mice in the real-time place preference task (N=9, Pairwise student t test, ***P<0.001) **d)** Schema of tube test applied to each cage (3 cagemates) to identify the dominance hierarchy. **e)** Color code for hierarchy within each cage after performing the tube test. **f)** Schema of real-time tracking and interaction detection. Simultaneous pose estimation of multiple freely moving mice is used to detect social interaction in real-time. Unilateral interaction is detected based on the angle (<110 degree) and distance (<5cm) of one mouse's nose to another's mouse tail. **g)** (Top) Expected baseline social interaction in a cage of three mice. (Middle) Second ranked and third ranked mice in the hierarchy receive optogenetic stimulation upon initiating unilateral interaction towards the first and second ranked mice, respectively. (Bottom) Timeline of the experiment including pre-stimulation, stimulation and post-stimulation sessions. **h)** Percentage of unilateral interactions (between pairs) initiated by the submissive of each pair across pre-stimulation, stimulation and post-stimulation sessions. The y-axis is scaled logarithmically (N=9 interaction, 3 interactions per cage, one-way repeated measure ANOVA, main effect ***P<0.001, Tukey post hoc test, ***P < 0.001, statistics performed on the log-scaled data). **i)** Train formation probability across pre-stimulation, stimulation and post-stimulation sessions. Each black line represents a cage. The y-axis is scaled logarithmically. The pie-chart represents the distribution of all possible trains (with the target train shown in orange) averaged across three cages during the optogenetic stimulation session. (Top) Image of multiple mice during an optogenetic stimulation session forming a moving train. The plotted dots on each mouse shows the location of their body parts (nose, body and tail) and the color indicates their natural hierarchy rank as shown in panel (e).

Discussion

We introduced a novel wireless optogenetic system able to efficiently manipulate neuronal activity in the brains of multiple freely moving mice and large scale settings including short latency for closed-loop behaviorally-triggered stimulations. The standard connector hardware provides flexibility in designing optogenetic stimulation implants across brain regions ranging from superficial cortical to deep subcortical structures. This flexibility removes any need for modification to the core device architecture, highlighting easy integration of BlueBerry devices into existing experimental frameworks. The compact and lightweight design, along with user-friendly and open-source documentation, makes the BlueBerry stand out among currently available wireless optogenetic tools (Kathe et al. 2022; Michoud et al. 2021; Li et al. 2022). Unlike systems requiring specialized manufacturing, BlueBerry can be assembled using commonly available parts and basic fabrication methods. This accessibility makes it an appealing candidate for widespread adoption, particularly in laboratories that lack high-end engineering infrastructure. Another unique strength of our system lies in the BlueHub (Supplementary Fig. 3), which enables simultaneous real-time programming of stimulation protocol and control of multiple BlueBerry devices. By providing a user-friendly graphical user interface (GUI), the BlueHub centralizes control over stimulus parameters and can flexibly integrate with a wide range of behavioral frameworks through TTL interfacing. Thus eliminating the need for coding expertise allowing closed-loop stimulation based on detected behavioral events via the BlueHub's digital inputs. As a result, BlueBerry can be readily deployed in existing experimental paradigms without the time consuming process of rewriting entire hardware-software pipelines. One of the current limitations of the BlueBerry device is the manual adjustment of LED powers through placing different resistors, which could be improved by using programmable voltage regulators. This would enhance the use of one BlueBerry unit for dynamic wavelengths of LEDs to manipulate brain activity with various opsins sensitive to different wavelengths.

With the battery-powered approach, BlueBerry also overcomes the spatial limitations often imposed by wireless power coils or other specialized power-delivery setups. It can be deployed in large-scale environments with minimal constraints, an advantage that expands the scope of naturalistic experimentation. To this end, we successfully demonstrated BlueBerry's ability to control navigation in a large-scale, infinite Y-maze via closed-loop stimulation of the primary somatosensory cortex, a distance range surpassing the majority of common behavioral studies

in the neuroscience community. Mice were able to integrate this artificial sensory stimulus and guide their navigation decisions. A potential application for such a scenario would be to study decision making across time and space (Harvey, Coen, and Tank 2012; Tseng et al. 2022), providing useful insights into underlying neural mechanisms.

Interestingly, we observed an abrupt and rapid motor response upon delivering the optogenetic stimulation to the primary sensory cortex in running mice (Supplementary Fig. 9). A phenomenon that was not reported by other studies employing artificial sensory cues, due to their experimental setup being restricted to head fixed design (Pancholi, Ryan, and Peron 2023), confined spaces (Karadimas et al. 2019) or applying the stimulation when animals are not engaged in an active motor behavior (Huber et al. 2008; Luis-Islas et al. 2022). By replacing optogenetic stimulation with natural sensory cues (visual), we excluded the possibility that this effect stems from underlying cognitive processes (Supplementary Fig. 10). Considering the rapid onset of this effect and the trajectory-time analysis (Supplementary Fig. 9) indicating decisions are made after animals start accelerating, it is plausible that the somatosensory cortex might directly influence this motor effect. Motor control by the sensory cortex has been reported previously and the descending pathway contributing to whisker retraction have been identified (Matyas et al. 2010). We can speculate that from an ethological perspective, the existence of this pathway might be explained by the natural behavior of mice of retracting their whiskers upon a sudden encountering an object.

Another important aspect of wireless optogenetics is its application in social settings, enabling targeted stimulation in multiple freely moving animals simultaneously. We demonstrated influence on group dynamics of animals by triggering interactions in closed-loop manner using multiple BlueBerry devices for optogenetic stimulation of the VTA-DA neurons. By simultaneously controlling two BlueBerry devices and monitoring social interactions in real-time, we effectively overexpressed social behaviors contradicting their natural hierarchical structure (Fig. 3h) sufficient to transiently shape overall group dynamics (Fig. 3i, moving train of mice). However, the reinforced behavior did not persist in the absence of optogenetic stimulation and did not affect the initial dominance hierarchy (Supplementary Fig. 13). This could possibly be explained by the experimental structure, where mice are stimulated for only 2 hours per day in a specific arena, different from their home cage, where no stimulation is applied. Therefore, we assume that the reinforcement was strongly associated with the environment, and upon returning to their home cage, the dominant mouse resumed its dominant behavior over the other

two cage mates. Future studies are needed to determine whether prolonged stimulation periods or alternative grouping strategies (mice from different cages) yield more durable modifications.

Taken together, our results highlight the effective integration of the BlueBerry system with various open source and commercial experimental frameworks (EthoLoop, DeepLabCut, and Ethovision) to investigate a broad range of behaviors, from sensory-guided navigation to social interactions. As neuroscience continues to embrace more naturalistic experimental designs, we anticipate that BlueBerry will address a critical need in the current set of wireless optogenetic tools and have broad use within the neuroscience community.

Acknowledgment

We express our gratitude to the members of the Huberlab for their support and discussions. We thank Mario Prsa and Alaister Loutit for their comments on the manuscript. We thank Lorena Jourdain for her technical support for VTA injections and Varta Microbattery for supplying the CP 1254 A4 coin batteries. This work was supported by the Swiss National Science Foundation (310030_184829 and 310030_215062).

Contributions

A.N. and D.H. conceptualized the BlueBerry system. A.N designed and constructed the BlueBerry hardware, BlueHub hardware and brain implants. A.N. wrote all software for BlueHub and BlueBerry. A.N. ran all the maze navigation experiments. A.N. carried out the surgeries for micro-LED implantation for sensory cortex stimulation. A.N and B.G. ran all the social behavior experiments. A.N analysed all the data. D.H. and C.B. oversaw data analysis. B.G. carried out all the VTA surgeries for social experiments. B.G wrote the software for real-time social behavior classification. B.G. and M.G. performed all histological verifications. G.G. provided expertise and guidance for virus expression and surgeries. R.T. and S.P. provided guidance and contributed to PCB design and hardware assembly. C.B. and D.H. supervised the social behavior experiments. A.N. and D.H. wrote the manuscript.

Material and methods

Hardware

BlueBerry

The BlueBerry optogenetic device consists of a bluetooth low energy module (RN4871) with integrated antenna and an 8-bit AVR microcontroller (ATTINY-85-QFN). A surface mounted red LED (QT BRIGHTEK, QBLP595-R) is connected to the microcontroller for monitoring bluetooth connectivity status. To increase the output current, a 2-channel mosfet is used between the microcontroller and the 2x2 male (Mill-Max, 852-10-020) connector for LED implants. Micro-switch (C&K, PCM12SMTR) is placed between (in series) a small lithium rechargeable coin battery (VARTA, CP1254-A3) to power the device through a low dropout voltage regulator (MAX8888EZK33+TCT-ND). To be able to charge the battery and upload the base program on each BlueBerry device (RN4871 and ATTINY-85 initial configuration) a 10 pin micro-connector (Hirose Electric, BM23PF0.8-10DP-0.35V) is used as an interface between the BlueBerry device and the BlueHub control unit (Supplementary Fig. 3). All the resistors and capacitors used for the design are in 0402 small package format. All the components except the battery are placed on top and bottom of a custom made printed circuit board (PCB, 10.5 x10.5 x 0.6 mm, Supplementary Fig. 1 & 2) using soldering paste (TS991AX35T4) and fixed in a reflow oven. The board size and design is restricted not to cover any area below the antenna of the bluetooth module. (Supplementary Fig. 2) In the end, both poles of the battery are manually soldered to positive and negative pads on the PCB. Connection and transmission of data to the Blueberry device is achieved either through the BlueHub (Supplementary Fig. 3), or directly through an Linux-based computer (see software section below) using a USB bluetooth dongle (ASUS).

Brain implants

For bilateral stimulation of the sensory barrel field, two high-power micro LEDs (Light Avenue, LA-UB20FP1) are placed at the ends of a custom designed flexible PCB (3.5mm long on each side, Supplementary Fig. 5). Female 2x2 connector (Mill-Max) is placed via 4 through holes at the center of the PCB for connecting to the BlueBerry. For VTA stimulation high power surface mount LED (2.5x3.5mm, TOP LED 2835 BL) is coupled with 10mm long fiber optic (Supplementary Fig. 5, 4.5 mm of fiber covered with shield, 400 µm diameter, FP400URT,

Thorlabs). The coupling of LED and optic fiber is achieved with miniature 3D printed parts attached via UV curable glue (Norland 61) to both fiber and LED (Supplementary Fig. 5).

BlueHub

The BlueHub control unit (Supplementary Fig. 3 & 4) uses an Arduino UNO R4 (with Wi-Fi/BLE connectivity) at its core, providing a link to BlueBerry devices and generating triggers based on four digital inputs connected to external BNC female connectors (Adam Tech, BNC RA PCB 50). The Arduino module drives a 2.42-inch screen (ZJY OLED ,128x64 pixels) for the GUI, allowing users to assign specific BlueBerry devices to each BNC channel and customize the stimulation parameters. A rotary encoder switch (Bourn Inc, PEC11R-4220F-S0024) enables menu navigation parameter adjustments. Momentary tactile switches (C&K, PTS645VM83-2 LFS) next to each BNC allow manual testing of the assigned functions. The BlueHub also contains three BlueBerry connection stations with female micro connectors (BM23PF0.8-10DS). Each of these connection stations are connected to a battery charging module (LTC4054LES5-4.2); two stations serve as charging-only stations, and the third station functions for both charging and uploading the base program (initial configuration) onto the BlueBerry device (the programming station). The programming station is connected to the Arduino for SPI-based programming of the BlueBerry's microcontroller and two non-inverting buffer units (74AHCT1G125GW,125) for RX/TX communication with the BlueBerry's Bluetooth module. For uploading the base program into the BlueBerry unit, the Wi-Fi/BLE Arduino UNO R4 of the BlueHub is replaced by a standard Arduino UNO to accommodate the required programming protocols.

Experimental setup

Infinite Y maze

To create an elevated infinite Y-maze, wood composites structures were cut in 7cm bins to form bridges between the intersections and reward zones (Supplementary Fig. 7). The intersections were made by cutting the same type of structure into equilateral triangles with side lengths of 28cm. Smaller equilateral triangles (7cm side length) were cut from each three corners of the intersection platforms to create a symmetric entry via each elongated bridge. For creating protection on the bridges and intersections, flexible black PVC at 4mm thickness were cut at 5 cm bins to create walls around both sides of bridges and the intersection platforms. The attachment of walls were done through custom made 3D printed clips. The entire maze was elevated 50cm using 12 pipes (Ostendorf Kunststoffe 110mm diameter) below every intersection platform, reward zones and turning points. Six holes (3 mm diameter) were drilled in the middle of every bridge to place reward ports. Liquid reward was delivered through solenoid valves (Lee Company, LHDA0531215H) connected to the output reward port using silicon tubes (TYGON, inside diameter 1.6mm). The digital output channels of a WiFi Arduino (Arduino MKR1010) were used to trigger an optocoupler-based circuit, which converted the Arduino's low-voltage signals into 12V to activate the solenoid valves for reward delivery. Four high power blue LEDs (Roithners, ELJ-465-627) were placed above each intersection platform (attached to ceiling) to create a mask light during optogenetic stimulation. Mask LEDs were controlled through a high power PNP transistor (BC328-16) each connected to digital ports of another WiFi Arduino (Arduino MKR1010). In order to have a strong reflection of the mask light for mice navigating in the maze, the intersection platforms and 20 cm of each entry bridge were fully covered with mat white tape (Dc-fix adhesive). In the end to avoid mice exiting the maze all the parts of the maze were covered with transparent plexiglass (Plexiglas ROHM, 4mm thickness).

For the small infinite maze setup (Supplementary Fig. 7), black PVC material was used on top of a white wooden platform (1m x 1m) to create six corridors intersecting at 4 different locations. The fixation of the corridors were done through custom 3d printed inserts nailed to the wooden platform at intersection locations. Middle of each corridor was drilled to place reward ports and the same system as the big maze was used for controlling the reward delivery. In the last stage a 1m x 1m plexiglass (Plexiglas ROHM, 4mm thickness) is placed on top of the maze.

In both small and large maze setups EtholLoop tracking system (www.etholoop.org, (Nourizonoz et al. 2020)) was used to track the location of freely moving mice. A retroreflective (2 x 9mm) tape was attached to the BlueBerry carried by the mouse for passive location tracking. All

wireless communication for the reward delivery system and mask light was done through a high speed wireless router (ASUS, AC 3100).

Multi-animal arena

The arena for shaping social dynamics experiments Supplementary Fig. 11) was built using five plexiglass (50 x 50cm, Plexiglas ROHM, 4mm thickness) placed at the surface and surrounding sides. The transparent arena was placed inside a custom made wooden box (0.8 x 0.8 x 0.9m) covered with soundproof foam on all six sides. The wooden box was illuminated at 25 Lux homogeneously via 100 white LEDs forming a ring around the box diffused by a sheet. A camera (Logitech c920 1080p HD) was fixed at the top having a 90 degree downward view to the center of the transparent arena.

Software

BlueBerry base program

The BlueBerry requires two separate programs for initial and one-time configuration; one for its Bluetooth module (RN4871) and one for its microcontroller (ATTINY-85). To upload these programs, the Arduino UNO Rev4 on the BlueHub is temporarily replaced with a standard Arduino UNO, and the BlueBerry is attached to the BlueHub's programming port (Supplementary Fig. 3). The upload process involves two steps. First, the Arduino UNO is placed into reset mode (via the dedicated programming mode switch on the BlueHub) so it can serve as a USB-to-UART bridge for the RN4871. Using ASCII command lines in an Ubuntu terminal, the RN4871 is programmed to adjust its connection parameters (e.g., latency and interval), indicate connection status, and communicate with the ATTINY-85 over the I²C protocol. Once the Bluetooth module is configured, the Arduino UNO is taken out of reset mode, and the Arduino IDE is used to program the ATTINY-85 via SPI. This microcontroller program decodes incoming 2-byte packets to determine which LED channel to activate and sets parameters for blinking frequency, pulse width, and the total number of pulses.

BlueHub programing and configuration

The BlueHub device is programmed via the Arduino IDE, which uploads both the control logic and the graphical user interface (GUI) onto the Arduino hardware at its core (Arduino UNO Rev4). The control logic is organized as a state machine that handles user input from the rotary encoder switch, push button presses, and the BNC input channels. An integrated OLED screen is driven over an I²C interface, enabling the GUI to display and manage all configuration options. Within this interface, the user assigns each BNC input channel to a specific BlueBerry device ID and defines the associated stimulation protocol (e.g., frequency, pulse width, and number of pulses). For example, a high-level digital signal on BNC 1 can be set to trigger a particular stimulation program on BlueBerry ID2. All settings are stored in the Arduino's EEPROM, preserving the assigned device IDs and stimulation parameters even when the BlueHub is powered off. Upon restarting, the BlueHub automatically recalls these saved configurations, therefore maintaining consistent settings across multiple sessions. Communication with BlueBerry devices is achieved using the Arduino BLE library.

Closed-loop control of navigation in Y-mazes

Tracking the position of freely moving animals was done using the EthoLoop 2D tracking software (on Ubuntu 20.04 environment) applied on undistorted images. The distance of animals to the center of each intersection was calculated in real-time to detect if they have entered any intersections through any of the three entrances (20cm threshold for large maze and 10cm for small maze). Upon entering an intersection, a bluetooth message for optogenetic stimulation is sent to the blueberry through Gattlib library (https://github.com/labapart/gattlib). The stimulation direction (left or right) is chosen randomly through C++ random generator. Simultaneously a UDP packet is sent to the WiFi Arduino of the mask light controlling unit that activates high power blue lights at the same frequency of optogenetic stimulation. Upon making the correct decision (exiting the chosen arm), the corresponding reward port will be activated through a WiFi UDP packet sent to the reward controlling unit. The reward message contains the solenoid valve number and duration of opening. A predefined matrix indicates which port is associated to each arm of all intersections. At the end of each session a configuration file is stored containing all information about the optogenetic stimulation protocol. The two-dimensional data along with time (in milliseconds), crossed intersection number, stimulation (left or right), reward delivery (correct or incorrect) and trial number was stored in a text file.

Closed-loop control of social behavior

We implemented our closed-loop stimulation for social behavior in MATLAB, which interfaced with a Python script via a memory-mapped file. This configuration created a shared memory space, allowing efficient data transfer and synchronization between the two environments. Each captured 500×500px image was transmitted to this shared memory location, where DeepLabCut-Live performed real-time body-part tracking (nose, body and tail) for each animal, identified by a unique shaving pattern (Supplementary Fig. 12). The MATLAB script continuously accessed the coordinates from the shared memory to compute distances and angles between each animal's nose and tail to detect unilateral social interactions. Once such an interaction was identified between desired pairs of mice and remained for 200ms, the MATLAB program triggered a PulsePal device to generate a high-level digital signal (5V), which was sustained until the detected unilateral interaction between the pair of mice ended. (https://github.com/sanworks/PulsePal/tree/master/MATLAB). This signal was connected to the BlueHub's digital inputs (BNC1 and BNC2), which had been configured to activate and deactivate the assigned BlueBerry devices according to predefined stimulation protocols (Supplementary Fig. 12). For two-chamber real-time place preference experiments, EthoVision software (Noldus) was similarly integrated with the BlueHub, enabling automated optogenetic stimulation via the BlueBerry device based on the animal's location in real time.

Animals

Surgeries for sensory barrel field stimulation

Cre-dependent channelrhodopsin mice (Ai32, RCL-ChR2(H134R)/EYFP) were anesthetized using 2% mix of isoflurane and oxygen and place under the stereotactic frame. They were administered with dexamethasone (Mephamesone, 20ul intramuscular), carprofen (Rimadyl, 2.5mg/1000gr, 50ul subcutaneous), buprenorphine (Temgesic, 0.1mg/1000g, 25ul intramuscular) and lidocaine (Rapidocain 10 mg/mL, 50 µL subcutaneous). At least 20 minutes later, a small incision was made in the scalp skin to gain access to the skull. Two separate Craniotomies were made bilaterally over the sensory barrel fields (1.5 mm posterior, 3.5mm lateral to bregma) and two viral injections (50nl each) of Cre virus (AAV5.CamKII0.4.Cre.SV40, dilution 1:50 with 2% fast green) were performed at depth of 300 um to target layer 2/3 cortex (this step was not performed for control animals). The flexible two channel implant was fixed on

top of the skull with cyanoacrylate glue so that the micro LEDs will be placed inside the craniotomies. Afterward the implant was secured and covered with black dental cement to avoid leakage of the LED lights.

Surgeries for VTA stimulation

DAT-iresCre mice (Slc6a3tm1.1(cre)Bkmn/J) were used. Mice aged 6–8 weeks were anesthetized using a mixture of oxygen (1 L/min) and 3% isoflurane (Baxter). Following anesthesia, the mice were placed in a stereotactic frame. The surgical area was prepared by shaving and disinfecting the skin, followed by local anesthesia with 40–50 µl of 0.5% lidocaine. Bilateral craniotomies were performed at precise stereotactic coordinates over the VTA (lateral ±0.5 mm, posterior −3.2 mm from Bregma, and depth −4.25 ± 0.05 mm). A viral solution containing rAAV5-Ef1a-DIO-hChR2(H134R)-eYFP (Addgene, titer ≥ 4.2 × 10^12 vg per ml) was injected bilaterally into the VTA, with a volume of 500 nl per side, using a glass micropipette. The virus was allowed to express for 3–4 weeks post-injection. Subsequent to the viral expression period, the mice were implanted with fiber-coupled LED implants targeting the VTA. For precise targeting, the fibers were implanted unilaterally (right side) using the coordinates: ML +0.5 mm, AP −3.2 mm, DV −4.20 mm from Bregma. The fibers were then secured to the skull with dental acrylic mixed with carbon powder. Injections and implantation sites were confirmed post hoc.

Histology

Mice were anesthetized with 3% isoflurane and euthanized with i.p. pentobarbital injection (Escornarkon, 150mg/kg). They were then transcardially perfused using a peristaltic pump (ISM829, Cole-Parmer) with 0.01 M PBS, pH 7.4 for 2 min, and then 4% paraformaldehyde (PFA) in phosphate sodium buffer (PBS; pH 7.4) for 3 min. The brains were post-fixed at 4°C in PFA 4% for 48h, washed 3x15min in PBS and then fully transferred into PBS. The brains were cut in slices of 60µm thickness for sensory barrel field and 50µm thickness for VTA with a vibratome (VT1000S, Leica). For sensory barrel field, the slices were incubated with slight agitation at room temperature with a Hoechst solution (dilution 1:1000, Invitrogen, #33342) during 5min for fluorescent nuclear counterstaining and washed again with PBS. For VTA, brain slices were washed three times with 0.1 M PBS, then pre-incubated in PBS-BSA-TX buffer (10% BSA, 0.3% Triton X-100, 0.1% NaN$_3$) for 60 minutes at room temperature in the dark. Slices were then incubated overnight at 4°C with primary antibodies diluted in PBS-BSA-TX (3%

BSA, 0.3% Triton X-100, 0.1% NaN$_3$). The next day, they were washed three times with PBS and incubated for 60 minutes at room temperature with secondary antibodies in PBS-Tween (0.25% Tween 20). The primary antibody used was rabbit polyclonal anti-tyrosine hydroxylase (1:500, Abcam, ab6211), and the secondary antibody was donkey anti-rabbit 555 (Alexa Fluor, 1:500). The sections were mounted on Superfrost microscope glass slides (Epredia) using mounting medium (Fluoromount, Southern Biotech), coverslipped with 24x50 mm coverslips (Menzel-Gläser) and kept in dark at 4°C until further imaging. All photomicrographs were taken using a Zeiss Axio Scan.Z1 (Zoom x10) for sensory barrel field and Zeiss LSM700/LSM800 confocal microscopes for VTA.

Ethics

All mouse experiments and surgeries were conducted in Geneva, Switzerland, and received approval from both the local ethics committee and the Geneva canton authorities. The mice were housed in the animal facility, maintained at a temperature of 21°C and a humidity level of 50%. In each cage, no more than five mice were accommodated.

Experimental procedure

Closed-loop control of navigation in Y mazes

Three weeks after the surgeries, animals' access to water was removed and limited to 1ml per day. For both small and large mazes, animals performed two baseline sessions with no optogenetic stimulations. Each session contained 200 trials and only one session per mouse was performed each day. A trial consisted of animals entering an intersection, receiving a stimulation (left or right sensory barrel field), choosing an exit path and finally arriving at the water port. When mice selected the correct exit at each intersection, a loud click noise was produced, using a solenoid striking a plastic surface located outside the maze. This serves as an early indicator of their decision's outcome and facilitates the learning process. In the initial sessions (the first 8 sessions), this auditory cue allowed mice to reconsider their choices (if they entered an incorrect arm, they could return to the intersection and make a different choice, triggering the click noise). After the 8th session, however, this sensory feedback was removed, preventing the animals from altering their decisions.

In the small maze animals underwent 7 sessions with optogenetic stimulations delivered at 20Hz. The pulse number and pulse width varied across the seven days starting from weak

stimulation 4 pulses of 1 ms and going up to 6 pulses of 5ms width and finally down to 4 pulses with 4 ms width (Supplementary Fig. 8). To characterize the effect of optogenetic stimulation on speed in more detail, animals in big maze underwent a total of 20 stimulation sessions with early sessions (first 7 stimulation sessions) including weak optogenetic stimulations (1 pulse with width of 1 and 2ms, Supplementary Fig. 8 & 9). After the 7th day the stimulation became stronger in terms of pulse number and pulse width and followed the exact same trajectory as the stimulation protocol used for the small maze (4 pulses of 4ms in the last day). All mice from the large maze experiment underwent 6 additional sessions where optogenetic stimulation was replaced with visual cues provided via two channel LED headstage (fabricated via 3D printer, 4 pulses of 4ms delivered at 20Hz, Supplementary Fig. 10). In both small and large mazes, animals were supplemented with additional water if they did not receive 1ml during the training session.

Shaping social dynamics

Three experimental cages, each housing three DAT-iresCre mice (Slc6a3tm1.1(cre)Bkmn/J) that had been cohabiting since birth were used. Three weeks post fiber-coupled LED implantation surgery, these mice were subjected to an optogenetic real-time place preference (rtPP) experiment, to validate the effectiveness of virus injection and the LED-fiber setup for optogenetic stimulation of dopaminergic neurons in the ventral tegmental area (VTA-DA). The rtPP experiment was conducted in a two-chamber setting. It began with a fixed 5-minute baseline session, during which the mice's chamber preference was determined. This was followed by a stimulation session lasting 15 minutes. The less preferred chamber, as identified during the baseline, was designated as the conditioned chamber for the stimulation sessions. Within this chamber, VTA-DA stimulation was provided as a continuous 20 Hz train of 5 ms pulses.

After the rtPP experiment, the dominance hierarchy within each cage was determined using a tube test. This involved releasing pairs of mice at opposite ends of a transparent plexiglass cylinder (30 cm long and 3 cm in diameter), with the trial finishing when one mouse exited the tube. The mouse remaining in the tube is considered the dominant of the pair. This test was repeated three times daily for each pair, resulting in a total of nine trials per cage per day, over three stable consecutive days. The mouse winning all tube tests over two other mice is considered as dominant of the cage (rank 1), mouse winning tube tests against only one animal

is considered as the middle in hierarchy (rank 2) and finally mouse losing all tube tests is considered as the submissive of the cage (rank 3). For identification during tracking, each mouse was shaved according to its hierarchical status; the submissive on the lower body, the middle near the neck, and the dominant remained unshaven (Supplementary Fig. 11 & 12). Initially, two baseline sessions (one session per day, 120 min) for each cage were performed where images of freely moving mice interacting with each other in the social arena were recorded. These images were used to train DeepLabCut model for real-time tracking purposes. Once the baseline was completed, each cage underwent eight sessions (8 days, 120min per day) where VTA-DA optogenetic stimulation was only delivered (continuous train of 5ms pulses at 20Hz) to the Rank 2 and Rank 3 mice only if engaging in a unilateral interaction toward the mouse one level above them in the dominance hierarchy (Rank 3 -> Rank 2 and Rank 2 -> Rank 1). Unilateral interaction was identified by monitoring the real-time positioning of the animal's body parts, including the nose and its angular relation to another mouse's tail. This type of interaction is confirmed when the nose-to-tail angle falls below 110 degrees, within a proximity of 5cm, and lasts at least 200 milliseconds. To evaluate the post effects of optogenetic stimulation, a tube test and three additional baseline sessions were conducted post-stimulation, enabling the observation of both changes in hierarchical status and social behavioral changes in the mice.

Post hoc data analysis

Navigation in Y-maze

All data analysis and statistics were performed in the R (Rstudio) environment. Data processing includes smoothening of the positional data (10ms window) and creating a separate log file containing all delivered stimulation and the related performance of the mouse for any given stimulation at every intersection. The first 20 trials were excluded for all animals as they exhibit exploratory behavior in the maze and performance was measured across the next 150 trials. Comparison between control and channelrhodopsin positive mice were made based on their performance on the second baseline session and the last stimulated session (7th session in small maze and 24th session in large maze). To extract the speed from position data, a 40 ms sliding window was applied on the two dimensional position data. Speed comparison across different trials (left, right and blank) were made by aligning all the speed profiles to the stimulation point (time zero). For normalization, all speed values were divided to the mean of speed during optogenetic stimulation.

Social behavior

All position data (nose, body and tail) were initially interpolated at 40 ms intervals in the MATLAB environment and further smoothed in the R programming environment. Afterward, the interactions between pairs of mice (unilateral) were assessed again on the processed data. All statistical analysis and plotting were performed in R.

References

Adamantidis, Antoine R., Feng Zhang, Alexander M. Aravanis, Karl Deisseroth, and Luis de Lecea. 2007. "Neural Substrates of Awakening Probed with Optogenetic Control of Hypocretin Neurons." *Nature* 450 (7168): 420–24.

Boyden, Edward S., Feng Zhang, Ernst Bamberg, Georg Nagel, and Karl Deisseroth. 2005. "Millisecond-Timescale, Genetically Targeted Optical Control of Neural Activity." *Nature Neuroscience* 8 (9): 1263–68.

Deisseroth, Karl. 2011. "Optogenetics." *Nature Methods* 8 (1): 26–29.

Fetcho, Robert N., Baila S. Hall, David J. Estrin, Alexander P. Walsh, Peter J. Schuette, Jesse Kaminsky, Ashna Singh, et al. 2023. "Regulation of Social Interaction in Mice by a Frontostriatal Circuit Modulated by Established Hierarchical Relationships." *Nature Communications* 14 (1): 2487.

Gradinaru, Viviana, Murtaza Mogri, Kimberly R. Thompson, Jaimie M. Henderson, and Karl Deisseroth. 2009. "Optical Deconstruction of Parkinsonian Neural Circuitry." *Science* 324 (5925): 354–59.

Harvey, Christopher D., Philip Coen, and David W. Tank. 2012. "Choice-Specific Sequences in Parietal Cortex during a Virtual-Navigation Decision Task." *Nature* 484 (7392): 62–68.

Hassenstein, B., and W. Reichardt. 1956. "Systemtheoretische Analyse Der Zeit-, Reihenfolgen- Und Vorzeichenauswertung Bei Der Bewegungsperzeption Des Rüsselkäfers Chlorophanus." *Zeitschrift Für Naturforschung B* 11 (9-10): 513–24.

Huber, Daniel, Leopoldo Petreanu, Nima Ghitani, Sachin Ranade, Tomás Hromádka, Zach Mainen, and Karel Svoboda. 2008. "Sparse Optical Microstimulation in Barrel Cortex Drives Learned Behaviour in Freely Moving Mice." *Nature* 451 (7174): 61–64.

Jeong, Jae-Woong, Jordan G. McCall, Gunchul Shin, Yihui Zhang, Ream Al-Hasani, Minku Kim, Shuo Li, et al. 2015. "Wireless Optofluidic Systems for Programmable In Vivo Pharmacology and Optogenetics." *Cell* 162 (3): 662–74.

Kane, Gary A., Gonçalo Lopes, Jonny L. Saunders, Alexander Mathis, and Mackenzie W. Mathis. 2020. "Real-Time, Low-Latency Closed-Loop Feedback Using Markerless Posture Tracking." *eLife* 9 (December). https://doi.org/10.7554/eLife.61909.

Karadimas, Spyridon K., Kajana Satkunendrarajah, Alex M. Laliberte, Dene Ringuette, Iliya Weisspapir, Lijun Li, Simon Gosgnach, and Michael G. Fehlings. 2019. "Sensory Cortical Control of Movement." *Nature Neuroscience* 23 (1): 75–84.

Kathe, Claudia, Frédéric Michoud, Philipp Schönle, Andreas Rowald, Noé Brun, Jimmy Ravier, Ivan Furfaro, et al. 2022. "Wireless Closed-Loop Optogenetics across the Entire Dorsoventral Spinal Cord in Mice." *Nature Biotechnology* 40 (2): 198–208.

Kim, Tae-Il, Jordan G. McCall, Yei Hwan Jung, Xian Huang, Edward R. Siuda, Yuhang Li, Jizhou Song, et al. 2013. "Injectable, Cellular-Scale Optoelectronics with Applications for Wireless Optogenetics." *Science* 340 (6129): 211–16.

Krakauer, John W., Asif A. Ghazanfar, Alex Gomez-Marin, Malcolm A. MacIver, and David Poeppel. 2017. "Neuroscience Needs Behavior: Correcting a Reductionist Bias." *Neuron* 93 (3): 480–90.

Li, Lizhu, Lihui Lu, Yuqi Ren, Guo Tang, Yu Zhao, Xue Cai, Zhao Shi, et al. 2022. "Colocalized, Bidirectional Optogenetic Modulations in Freely Behaving Mice with a Wireless Dual-Color Optoelectronic Probe." *Nature Communications* 13 (1): 839.

Lindzey, G., H. Winston, and M. Manosevitz. 1961. "Social Dominance in Inbred Mouse Strains." *Nature* 191 (July):474–76.

Luis-Islas, Jorge, Monica Luna, Benjamin Floran, and Ranier Gutierrez. 2022. "Optoception: Perception of Optogenetic Brain Perturbations." *eNeuro* 9 (3). https://doi.org/10.1523/ENEURO.0216-22.2022.

Matyas, Ferenc, Varun Sreenivasan, Fred Marbach, Catherine Wacongne, Boglarka Barsy, Celine Mateo, Rachel Aronoff, and Carl C. H. Petersen. 2010. "Motor Control by Sensory Cortex." *Science (New York, N.Y.)* 330 (6008): 1240–43.

McCall, Jordan G., Tae-Il Kim, Gunchul Shin, Xian Huang, Yei Hwan Jung, Ream Al-Hasani, Fiorenzo G. Omenetto, Michael R. Bruchas, and John A. Rogers. 2013. "Fabrication and Application of Flexible, Multimodal Light-Emitting Devices for Wireless Optogenetics." *Nature Protocols* 8 (12): 2413–28.

Michoud, Frédéric, Corey Seehus, Philipp Schönle, Noé Brun, Daniel Taub, Zihe Zhang, Aakanksha Jain, et al. 2021. "Epineural Optogenetic Activation of Nociceptors Initiates and Amplifies Inflammation."

Nature Biotechnology 39 (2): 179–85.

Mickle, Aaron D., Sang Min Won, Kyung Nim Noh, Jangyeol Yoon, Kathleen W. Meacham, Yeguang Xue, Lisa A. McIlvried, et al. 2019. "A Wireless Closed-Loop System for Optogenetic Peripheral Neuromodulation." *Nature* 565 (7739): 361–65.

Montgomery, Kate L., Alexander J. Yeh, John S. Ho, Vivien Tsao, Shrivats Mohan Iyer, Logan Grosenick, Emily A. Ferenczi, et al. 2015. "Wirelessly Powered, Fully Internal Optogenetics for Brain, Spinal and Peripheral Circuits in Mice." *Nature Methods* 12 (10): 969–74.

Nourizonoz, Ali, Robert Zimmermann, Chun Lum Andy Ho, Sebastien Pellat, Yannick Ormen, Clément Prévost-Solié, Gilles Reymond, et al. 2020. "EthoLoop: Automated Closed-Loop Neuroethology in Naturalistic Environments." *Nature Methods* 17 (10): 1052–59.

Pancholi, Ravi, Lauren Ryan, and Simon Peron. 2023. "Learning in a Sensory Cortical Microstimulation Task Is Associated with Elevated Representational Stability." *Nature Communications* 14 (1): 3860.

Park, Sung Il, Daniel S. Brenner, Gunchul Shin, Clinton D. Morgan, Bryan A. Copits, Ha Uk Chung, Melanie Y. Pullen, et al. 2015. "Soft, Stretchable, Fully Implantable Miniaturized Optoelectronic Systems for Wireless Optogenetics." *Nature Biotechnology* 33 (12): 1280–86.

Shin, Gunchul, Adrian M. Gomez, Ream Al-Hasani, Yu Ra Jeong, Jeonghyun Kim, Zhaoqian Xie, Anthony Banks, et al. 2017. "Flexible Near-Field Wireless Optoelectronics as Subdermal Implants for Broad Applications in Optogenetics." *Neuron* 93 (3): 509–21.e3.

Solié, Clément, Benoit Girard, Beatrice Righetti, Malika Tapparel, and Camilla Bellone. 2022. "VTA Dopamine Neuron Activity Encodes Social Interaction and Promotes Reinforcement Learning through Social Prediction Error." *Nature Neuroscience* 25 (1): 86–97.

So, Nina, Becca Franks, Sean Lim, and James P. Curley. 2015. "A Social Network Approach Reveals Associations between Mouse Social Dominance and Brain Gene Expression." *PloS One* 10 (7): e0134509.

Tsai, Hsing-Chen, Feng Zhang, Antoine Adamantidis, Garret D. Stuber, Antonello Bonci, Luis de Lecea, and Karl Deisseroth. 2009. "Phasic Firing in Dopaminergic Neurons Is Sufficient for Behavioral Conditioning." *Science* 324 (5930): 1080–84.

Tseng, Shih-Yi, Selmaan N. Chettih, Charlotte Arlt, Roberto Barroso-Luque, and Christopher D. Harvey. 2022. "Shared and Specialized Coding across Posterior Cortical Areas for Dynamic Navigation Decisions." *Neuron* 110 (15): 2484–2502.e16.

Wang, Fei, Jun Zhu, Hong Zhu, Qi Zhang, Zhanmin Lin, and Hailan Hu. 2011. "Bidirectional Control of Social Hierarchy by Synaptic Efficacy in Medial Prefrontal Cortex." *Science* 334 (6056): 693–97.

Yang, Yiyuan, Mingzheng Wu, Abraham Vázquez-Guardado, Amy J. Wegener, Jose G. Grajales-Reyes, Yujun Deng, Taoyi Wang, et al. 2021. "Wireless Multilateral Devices for Optogenetic Studies of Individual and Social Behaviors." *Nature Neuroscience* 24 (7): 1035–45.

Yang, Yiyuan, Mingzheng Wu, Amy J. Wegener, Abraham Vázquez-Guardado, Andrew I. Efimov, Ferrona Lie, Taoyi Wang, et al. 2022. "Preparation and Use of Wireless Reprogrammable Multilateral Optogenetic Devices for Behavioral Neuroscience." *Nature Protocols* 17 (4): 1073–96.