Parallel hierarchical encoding of linguistic representations in the human

auditory cortex and recurrent automatic speech recognition systems

Menoua Keshishian [1] [2,3], Gavin Mischler [1,2,3], Samuel Thomas [4], Brian Kingsbury [4],

Stephan Bickel [5,6], Ashesh D. Mehta [5,6] , Nima Mesgarani [2,3,*]

Abstract

Transforming continuous acoustic speech signals into discrete linguistic meaning is a remarkable
computational feat accomplished by both the human brain and modern artificial intelligence. A
key scientific question is whether these biological and artificial systems, despite their different
architectures, converge on similar strategies to solve this challenge. While ASR systems now
achieve human-level performance, research on their parallels with the brain has been limited by
biologically implausible, non-causal models and comparisons that stop at predicting brain activity
without detailing the alignment of the underlying representations. Furthermore, studies using
text-based models overlook the crucial acoustic stages of speech processing. Here, using high-
resolution intracranial recordings and a causal, recurrent ASR model, we bridge these gaps by
uncovering a striking correspondence between the brain's processing hierarchy and the model's
internal representations. Specifically, we demonstrate a deep alignment in their algorithmic
approach: neural activity in distinct cortical regions maps topographically to corresponding
model layers, and critically, the representational content at each stage follows a parallel
progression from acoustic to phonetic, lexical, and semantic information. This work thus moves
beyond demonstrating simple model-brain alignment to specifying the shared underlying
representations at each stage of processing, providing direct evidence that both systems
converge on a similar computational strategy for transforming sound into meaning.

[1] Equal contribution
[2] Department of Electrical Engineering, Columbia University, New York, NY, USA
[3] Zuckerman Institute, Columbia University, New York, NY, USA
[4] IBM Research, Yorktown Heights, NY, USA
[5] The Feinstein Institutes for Medical Research, Northwell Health, Manhasset, NY, USA
[6] Department of Neurosurgery, Zucker School of Medicine at Hofstra/Northwell, Hempstead, NY, USA
[*] Correspondence: nima@ee.columbia.edu

Main Text

Introduction

Understanding how the human brain processes and encodes linguistic information is a fundamental challenge in neuroscience and artificial intelligence. The human auditory cortex is capable of extracting meaning and structure from spoken language with remarkable efficiency. In parallel, automatic speech recognition (ASR) systems have achieved near-human accuracy in recognizing and transcribing speech (*1*). However, it remains unclear how closely the internal computation and representation of these ASR systems mirror those of the human brain, leaving a substantial gap in our understanding of speech processing in humans and machines. Are both systems converging toward similar strategies, or are they reaching different solutions independently as they optimize for performance?

Neuroimaging studies of speech processing in the brain have revealed an emergent encoding of linguistic hierarchies, progressing from primary to nonprimary areas of the auditory cortex (*2–4*). These studies show that the brain distributes, yet jointly encodes, various linguistic features, including phonemes, phonotactics, lexical-phonological, and lexical-semantic information. However, parallels between these hierarchical patterns in the brain and those found in ASR algorithms have not been directly established. Several studies have examined how end-to-end ASR systems represent linguistic information (*5*) and explored similarities between these systems and the brain (*6*). Additional research has also investigated the representational similarities between large language models (LLMs) and the brain (*7–11*). While these studies have provided valuable insights, they have some limitations. Many lacked the temporal precision necessary for speech processing, as they relied on functional MRI (fMRI) (*7, 10*) which is slow in capturing the neural dynamics. Moreover, by comparing the brain to text-based LLMs, these studies inherently overlooked the acoustic stages of speech processing even though the subjects listened to the stimuli (*7–11*). Other studies used models that were biologically implausible, such as transformers (*6–11*) or non-causal architectures (*6*). In addition, most studies did not explicitly analyze linguistic representation in the models (*7, 9–11*), or used only a narrow set of features (*6, 8*). Therefore, even though it has been shown that speech processing models and the brain

use increasingly similar representations as revealed by the predictability of neural responses

from these models, the precise nature of this convergent similarity remains unclear, replacing

one black box with another one without explaining the full picture of speech understanding (*12*).

This study addresses several gaps in the current understanding of speech processing in both

biological and artificial systems. First, we expand on previous studies by investigating a broad

range of linguistic features, providing a comprehensive analysis that includes phonetic, lexical,

semantic, and contextual representations. Second, we use a biologically plausible recurrent

neural network transducer (RNN-T) (*13*) model that processes speech in a causal and incremental

manner, aligning more closely with how the human brain processes speech in real time. By

incorporating high-resolution intracranial electroencephalography (iEEG) data from participants

listening to continuous speech, we establish a direct comparison between neural activations and

the internal states of the ASR model.

Through a detailed node-level analysis, we compare specific neural sites in the brain with

individual nodes in the ASR model to directly assess representational alignment. Additionally, a

layer-level analysis provides a more comprehensive view of the ASR model's internal hierarchical

representations, allowing us to examine how the structure of these representations parallels the

cortical encoding of speech in humans. We not only directly compare the brain with the model,

but we also explicitly test the linguistic features encoded within both the brain and model,

moving beyond simply mapping black-box representations onto neural responses. This dual

approach enables us to uncover both fine-grained and hierarchical similarities in how speech is

processed by biological and artificial systems, shedding light on shared mechanisms of linguistic

encoding while also revealing key divergences.

Results

We recorded intracranial electroencephalography (iEEG) data from fifteen human participants

implanted with subdural (electrocorticography; ECoG) and depth (stereotactic EEG; sEEG)

electrodes. The participants listened to 30 minutes of continuous speech spoken by four

speakers. To ensure that the subjects were engaged in the task, we paused the audio at random

intervals and asked the subjects to report the last sentence before the pause. All subjects were

attentive and could correctly repeat the speech utterances with 100% accuracy. We extracted

the envelope of the high-gamma frequency band (70-150 Hz), which has been shown to correlate

with neural firing in the proximity of the recording electrode (*14*, *15*), as the neural response

measure of the recorded signals.

We restricted our analyses to electrode sites in the auditory cortex (AC; $N = 335$) and the

inferior frontal gyrus (IFG; $N = 191$). Figure 1a shows the general location of the IFG and the

subregions of the auditory cortex on the FreeSurfer average brain (*16*). We further limited our

analysis to sites that were determined to be speech-responsive ($N = 291/526$, determined by

a t-test between responses during speech and in silence), including 62 ECoG electrodes and 229

sEEG electrodes. We labeled the neural sites in both hemispheres based on their anatomical

region to enable population tests: posteromedial Heschl's gyrus (pmHG; $N_L = 12/15$, $N_R =$

$16/19$), anterolateral Heschl's gyrus (alHG; $N_L = 34/36$, $N_R = 32/34$), planum temporale (PT;

$N_L = 9/12$, $N_R = 18/20$), middle superior temporal gyrus (mSTG; $N_L = 44/53$, $N_R = 17/18$),

posterior superior temporal gyrus (pSTG; $N_L = 27/32$, $N_R = 21/23$), anterior superior temporal

gyrus (aSTG; $N_L = 19/60$, $N_R = 0/13$), and inferior frontal gyrus (IFG; $N_L = 32/119$, $N_R =$

$10/72$). The electrode locations and their responsiveness are plotted in Figure 1b on the average

FreeSurfer brain, where the color indicates whether an electrode is speech-responsive.

Figure 1. Stages of speech processing in the brain based on ASR modelling. (a) General location of the inferior frontal gyrus (IFG) and subregions of the auditory cortex (AC). (b) Electrode locations within the regions of interest. Colours indicate whether an electrode showed significantly higher activation during speech stimuli compared to pre-trial silence. (c) The RNN-T model consists of a bottom-up Encoder (green) which processes the input spectrogram to produce acoustic representations (layers E1–E6), and a top-down Predictor (orange) which processes the label history to produce linguistic representations (layer P). A Joiner network combines these to predict output labels. To map model representations to neural activity, we fit a layer-wise Ridge regression model to predict the neural response at each electrode from the activations of each specific model layer. (d) Comparison of the cross-validated prediction score using the best ASR layer versus a baseline spectrogram predictor for all speech-responsive electrodes (N=291). (e) Electrodes are coloured according to the ASR model layer (E1–E6, P) that predicts their activity with the highest accuracy. (f) The normalized fraction of electrodes within each anatomical subregion that are best predicted by each layer of the ASR model. Each row is normalized by its maximum value to highlight

111   the subregion where a given layer is most strongly represented. Regions are sorted by their average

112   distance from pmHG.

Stages of speech processing in the brain based on ASR modeling

We use an RNN-Transducer (RNN-T) (*13*), a recurrent neural network trained to predict letters

(graphemes) from the speech spectrogram, to model the speech recognition process in the brain.

RNN-T models take spectro-temporal speech signals as input through a causal mechanism, and

have been widely used for speech recognition, including for recent state-of-the-art systems in

certain domains (*17–22*). Unlike transformer-based architectures, RNN-T models can be causal

and recurrent, making them an ideal candidate model to compare with the full hierarchy of

speech processing in the brain. The model consists of two branches: the encoder and the

predictor (Figure 1c. The encoder branch, consisting of 6 uni-directional LSTM layers (E1–E6), acts

as a bottom-up encoder by producing acoustic embeddings from the input speech spectrogram.

The predictor branch, consisting of 1 uni-directional LSTM layer (P), acts as an internal language

model in that it is conditioned on previous non-blank symbols produced by the model,

performing the role of top-down cortical feedback on language likelihood in real time. It stores

an internal representation of the prior predictions of the model that together with the encoder's

output are combined by a shallow joint network and used to make the next prediction. We

computed layer activations for all layers of these two branches in response to the same 30-

minute stimulus set that the human participants listened to.

To examine how the speech processing pathways of the brain and the model map to each other,

we find the best matching model layer for each electrode site. First, for each electrode-layer pair,

we fit a single-lag regression model that predicts the electrode activity from the layer activations

in response to the same stimuli (reduced to top 256 principal components). By using a single-lag

framework, we conceptualize each ASR layer as a candidate model for the computation occurring

at a given neural site. This approach treats the neural activity as a subspace of the layer's

representational space at a single point in time, which is consistent with the causal, step-by-step

processing of an RNN where each layer receives a single time-snapshot from the layer preceding

it. The model is defined as follows:

$$y = X_\delta \beta + c + \epsilon$$

where y is the $T \times 1$ response vector for an electrode site, X_δ is the $T \times H$ matrix of layer

activations shifted by a constant time lag δ, β is the $H \times 1$ vector of regression coefficients, c is

a constant bias term and ε is the regression error. We also define a baseline 256-dimensional

predictor which is obtained from a 128-dimensional log-Mel-spectrogram stacked on top of a 1-

sample delayed version of itself to capture local temporal spectral changes. For each electrode,

we also fit a single-lag linear regression model that predicts the neural activity from the baseline

predictor, allowing for a fixed time lag δ. Figure 1d shows the improvement of cross-validated

prediction scores for each electrode when predicting from the best-performing RNN-T layer

compared to the baseline spectrogram predictor. The RNN-T model significantly outperforms the

baseline spectrogram model (average correlation improvement = 0.053, $p \ll 1e-4$, paired t-

test).

To contextualize this performance, we compared the task-optimized RNN-T against two

alternative architectures: a Conformer-based ASR model (*23*) trained on the same speech

recognition task, and a CNN-based encoding model trained explicitly to predict the neural activity

(*24*, *25*). The Conformer ASR model was trained using a recent training recipe (*26*) on the same

training data as the RNN-T and achieved a word error rate of 6.9% on the stimuli used in this

study (compared to 4.9% by the RNN-T). We find that the RNN-T achieves very similar prediction

scores to the Conformer ASR model (Wilcoxon ranksum test, p>0.05). Additionally, despite never

being exposed to neural data during its training, the RNN-T achieves prediction scores on par

with the specialized CNN encoding model (Supplementary Fig. S1).

We next associate each electrode with the layer of the RNN-T model that predicts it with the

highest accuracy. The colors in Figure 1e indicate the corresponding layer of the model for each

neural site in the AC and IFG; and Figure 1f shows the normalized fraction of electrodes in each

brain region best predicted by each layer of the model (values indicate fraction of neural sites in

brain region, divided by the maximum fraction within layer/row). The model layers map to the

cortex such that as we move deeper in the model, in the cortex we move from the primary

auditory cortex (pmHG) laterally to PT and mSTG, and from there to pSTG, aSTG, and IFG. In

Figure 1f, the brain regions are sorted from nearest to farthest from primary auditory cortex. The

corresponding model depth (layer number) of an electrode is also correlated with various other

metrics associated with being downstream in speech processing – relative prediction

improvement from ASR over baseline (Spearman's $r = 0.582$, $p \ll 1 x 10^{-4}$), neural response

latency ($r = 0.373$, $p \ll 1 x 10^{-4}$), neural site's distance from the primary auditory cortex (center

of pmHG chosen as reference for primary AC; $r = 0.613$, $p \ll 1 x 10^{-4}$). Taken together, these

results confirm a robust linear alignment between the model's computational depth and the

brain's biological hierarchy, defined by both anatomical distance from the primary auditory

cortex and the temporal latency of neural responses

The brain results, however, show a difference in encoding between hemispheres, where neural

sites corresponding to deeper layers of the ASR model are predominantly found in the left

hemisphere. We can see this by a statistical comparison between the distribution of associated

model depth of electrodes (one-sided Wilcoxon rank-sum test, $U = 5.61$, $p = 1.0 \times 10^{-8}$, 177

speech-responsive sites in left and 114 in right). We also observe a difference by anatomical

region. Specifically, although the electrode coverage is not uniform across regions in both

hemispheres, a pattern emerges whereby lateralization increases as we move further away from

the primary AC – pmHG ($U = -0.139$, $p = 0.56$, 12 left, 16 right), aIHG ($U = -1.14$, $p = $

0.87, 34 left, 32 right), PT ($U = 1.90$, $p = 0.029$, 9 left, 18 right), mSTG ($U = 2.02$, $p = $

0.022, 44 left, 17 right), pSTG ($U = 2.11$ $p = 0.017$, 27 left, 21 right), aSTG (no speech-

responsive sites in the right hemisphere), IFG ($U = 2.27$, $p = 0.011$, 32 left, 10 right). These

results are in line with previous studies showing left-lateralization of higher-order regions in

linguistic processing (*27, 28*). Lower-level acoustic processing (according to ASR) is similar

between hemispheres, while higher-level processing is biased towards the left hemisphere.

Similar node-level linguistic encoding across the brain and ASR

We used a regression-based method with temporal receptive fields (TRFs) (*29*) to measure the degree of encoding of different levels of linguistic information in individual nodes of the ASR model and individual neural sites (Figure 2a). This method stands in contrast to the previous single-lag model, but in this case, a window of delays is more appropriate than a single-lag model for capturing the joint encoding of multiple features that may have varying latencies at a single neural site. In this method, we first predicted the neural activity of a site from a broad set of acoustic and linguistic features, including pitch, phonemes, phonotactics, lexical entropy and surprisal, word frequency, and semantic neighbourhood density (see Methods for definitions) (*30*). Next, we determined the contribution of each feature in predicting the response by replacing it with a control variable and interpret the drop in predictive power as the contribution of that feature to the prediction (*30*). We repeated the replacement process for each linguistic feature 100 times and measured the t-statistic between actual and control features to determine the significance of the feature.

Figure 2. Similar node-level linguistic encoding across the brain and ASR. (a) To measure which linguistic features are encoded in a given electrode site or ASR node, we fit a Ridge regression (TRF) model to predict the response to the stimulus from a set of time-aligned acoustic and linguistic features. This set includes pitch, phonemes, phonotactics, lexical entropy and surprisal, word frequency, and semantic neighbourhood density. The contribution of each feature was assessed by replacing it with a shuffled

control and measuring the resulting drop in prediction accuracy. (b) The normalized fraction of nodes in

each model layer (E1–E6, P) that significantly encode a given linguistic feature. (c) The normalized fraction

of electrodes in each anatomical region that significantly encode a given linguistic feature. The Spearman

correlation between the RNN-T linguistic feature map and the brain linguistic feature map is 0.473, p =

0.0016, where ** indicates p < 0.01. (d) The temporal order of linguistic feature encoding in both systems,

calculated as the average latency of the peak TRF weight for each feature. Error bars indicate 95%

confidence intervals (bootstrap, N=1000). The Pearson correlation between the average encoding

latencies of the brain and the RNN-T model is 0.93, p = 0.0027, where ** indicates p < 0.01.

Figure 2b shows the normalized fraction of nodes in each ASR layer that significantly encode each

linguistic feature group (fractions divided by maximum across feature/row). Figure 2c shows the

same, but for the normalized fraction of neural sites in each brain region. We find a significant

correlation between the feature representations over the 7 model layers and the 7 brain regions

(Spearman's $r = 0.473, p = 1.6 \times 10^{-3}$). To rigorously quantify the alignment of this hierarchical

progression, we calculated the center of mass (weighted mean depth) for each linguistic feature

within both systems. For the model, this metric defined the average layer (E1–P) where a feature

was most strongly encoded; for the brain, it defined the average anatomical region along the

ventral stream (pmHG to IFG). We found a strong, significant linear relationship between a

feature's computational depth and its biological depth (Spearman's r = 0.88, p = 0.033). This

result quantitatively confirms that despite their distinct architectures, both the ASR model and

the human brain prioritize the extraction of linguistic features in a highly correlated, parallel

order, progressing from acoustic to lexical to semantic representations. Supplementary figure S2

shows the average t-statistic without thresholding, normalized by the maximum of each row

(feature). We observed that the brain results show broader encoding of higher-level linguistic

features in the nonprimary auditory cortex (PT and STG) compared to the primary auditory cortex

(HG). This trend is also mirrored in the ASR model. These trends do not depend on the specific

choice of the threshold value, as we can see a similar result using average t-values of groups

instead of fractions.

Figure 2d shows the temporal order of the encoding of these linguistic features in the ASR model

and the brain. To measure the encoding latency for each feature, we first select the group of

nodes/electrodes that significantly encoded that feature. For each node/electrode, we compute

the latency of the peak absolute value of the TRF weight associated with that feature. We average

the latencies to obtain a single latency value for each feature. Finally, using bootstrapping, we

obtain 95% confidence intervals for the average latency of each feature. In line with prior findings

in the human brain (30), the results show a particular temporal order of emergence for the

different levels of linguistic information in both systems (Pearson correlation between average

latencies of features in the brain and the RNN-T ASR model, r = 0.93, p = 0.0027). To ensure that

this temporal order does not depend on the method of latency estimation, we also measure the

onset latency from the TRF weights and uncover a nearly identical hierarchical ordering of the

linguistic features in both the ASR model and brain (Supplementary Fig. S3).

Population-level linguistic encoding in the ASR

While the regression approach enabled us to compare the results between the two systems, it

cannot capture population-level representations. This is especially relevant in the case of the ASR

model, since we have full access to the entire neural population. To determine the patterns of

linguistic encoding in the model, we decoded each linguistic feature from the activations of the

model (Figure 3a). Because linguistic features are defined at different resolutions and linguistic

units have different lengths, we performed a unit-aligned analysis. For example, to predict

linguistic features that are defined at phoneme resolution—pitch, phoneme, bi-phone

probability, lexical entropy and surprisal—we extracted a layer's activations at time points

$\{p_i + \delta\}$, where $\{p_i\}$ were the time points corresponding to phoneme centers and δ was a

constant time lag. Similarly, for word resolution features—word frequency, semantic

neighborhood density, contextual embedding—we extracted activations at time points $\{w_i + \delta\}$,

where $\{w_i\}$ were the time points corresponding to word centers and δ was a constant time lag.

For predicting the categorical phoneme labels we fit linear Ridge classifiers, and for the rest of

the features, Ridge regressors (30). The best time lag (δ) and regularization parameter (λ) were

determined independently for each layer-feature pair by maximizing the 10-fold cross-validated

prediction scores.

a. Decoding linguistic features from RNN-T layer activations

b. Strength of linguistic representation across layers

c. Linguistic representation latency

Figure 3. Population-level linguistic encoding in the ASR. (a) To measure how strongly linguistic

features are encoded at the population level (layer embedding), we trained single-lag Ridge regressors

(for continuous features) or classifiers (for categorical features) to decode specific linguistic features

from the activations of each model layer (E1–E6, P). Activations were extracted at time points

corresponding to either phoneme centers (blue) or word centers (red), depending on the feature's

temporal resolution. (b) The min-max normalized prediction score for each linguistic feature across

model layers (normalized between the baseline spectrogram prediction score and the maximum score

across all layers). Yellow dots represent the peak layer for each feature. (c) The emergence of linguistic

representations in the model, plotted as the best predictive layer for each feature against its

corresponding optimal decoding latency. The Spearman correlation between layer depth and linguistic

representation latency is 0.98, $p = 3.4 x 10^{-5}$, where *** indicates p < 0.001).

We also decoded each linguistic feature from the 256-dimensional baseline predictor described

earlier. Figure 3b shows the prediction scores of predicting each feature from each layer of the

model, normalized per feature such that zero corresponds to the baseline prediction score and 1

corresponds to the best score across all layers of the model. We can see that as we move deeper

into the model, representations of higher-order linguistic information emerge. Based on these

scores, we can associate each linguistic feature with a layer of the model and find the best lag for

that layer-feature pair. As a result, we can describe the place of a linguistic feature in the speech

recognition process by its time lag and layer depth (Figure 3c). Each linguistic feature's best

predictive layer depth and the feature's representation peak latency are strongly correlated

(Spearman's $r = 0.98$, $p = 3.4 x 10^{-5}$). Together, these results show a pronounced emergent

linguistic representation in the model through time and space and with a specific order, enabling

a direct comparison with the results observed in the brain.

Effect of model training on linguistic representation

Finally, we explored the conditions in which such a linguistic representation can emerge in the

model. We tested two hypotheses: the emergent representation is training-dependent, and the

emergent representation is language-dependent. To test these, we decoded the same list of

English linguistic features from three different uni-directional RNN-T models: one trained on

English, one on French, and a randomly initialized model which underwent no training (Figure

4a). The results show a stark difference between the English and random models, where the

random model does not show a strong linguistic representation for any feature compared to the

baseline, especially for deeper layers. The French model shows a very similar representation of

pitch compared to the English model and a relatively strong representation of only pitch,

phonemes, and phonotactics compared to the random model.

Figure 4. Effect of model training on linguistic representation. (a) Linguistic decoding performance (as
in Figure 3) across three uni-directional RNN-T models: one trained on English, one trained on French
("Foreign"), and a randomly initialized model ("Random"). The Predictor branch (P) was excluded for
Foreign and Random models because their top-down representations cannot be aligned to the English
transcripts. Values are min-max normalized between the baseline (spectrogram) prediction score and
the maximum score across all layers of all models. (b) Pairwise centered kernel alignment (CKA)
similarity matrices comparing the layer activations of the English RNN-T model (y-axis) against the layer
activations of each of the three RNN-T models (x-axis): English, Foreign, and Random. The average CKA
similarity along the diagonal is displayed as the diagonal similarity for each model with the English
model.

We can also compare these models more directly by computing the similarities of their

representations of the same stimulus using centered kernel alignment (CKA) (*31*). We compared

the representations of each layer of all three models to the layers of the English model (Figure

4b). We observed that the English and French models share similar representations in their first

two layers to a large degree but steadily decrease in similarity over layers overall. In contrast, the

random model has weak similarity to the English model, even from early layers. To summarize

the similarity of each with the English RNN-T model, we computed the average CKA similarity

along the diagonal, finding that this diagonal similarity decreased from 1.0 in the ideal case

(English-vs-English) to 0.72 for the French model and 0.53 for the random model. Put together,

these results show that the emergent linguistic representation observed in the RNN-T is both

training-dependent and language-dependent.

Discussion

This study reveals a striking convergence in the computational strategies of the human brain and

artificial speech recognition systems. By employing a biologically constrained, causal RNN-

Transducer, we demonstrate that the model spontaneously develops a representational

hierarchy that mirrors the cortical ventral stream, not only in its spatiotemporal organization but,

critically, in the specific linguistic content encoded at each stage. Unlike prior works restricted to

text-based language models or non-causal architectures (*6–11*), our approach encompasses the

full trajectory of speech processing, from acoustic input to semantic understanding. This

establishes that the brain's hierarchical transformation of sound into meaning is likely an efficient

computational solution shared by both biological evolution and task-optimized artificial learning,

rather than an artifact of specific biological hardware.

Biological Plausibility and Emergent Hierarchy

Our claim of biological plausibility requires a careful distinction between a model's physical

implementation and its computational strategy. While our model diverges from neurobiology at

the implementational level, using backpropagation for learning (*32*, *33*) and possessing a

simplified feedback structure (*34*, *35*), it shows compelling parallels at the algorithmic level. The

model's input is a Mel spectrogram, a bio-inspired representation mimicking the cochlear output

(*36*, *37*). From this plausible starting point, the model's end-to-end training allows it to discover

its own processing hierarchy, unlike traditional multi-stage ASR systems where such stages were

pre-defined.

This hierarchical progression is consistent with patterns identified in prior studies using

other architectures (*38–41*), suggesting a robust phenomenon. However, it is important to

distinguish this approach from simpler encoding models like Spectro-Temporal Receptive Fields

(STRFs) (*29*, *42*). While STRFs offer a biologically realistic account of individual neural sites (*37*,

42, *43*), they are not designed to perform the overarching computational task of speech

recognition. By using a task-optimized RNN-T, we provide a computationally explicit hypothesis

for *why* these representations emerge: they are robust solutions for solving the sound-to-

meaning problem under causal constraints. Interestingly, we find that low-level acoustic features

like pitch strongly emerge in the initial layers (Figure 2b), creating a functional parallel to the

early auditory pathway before abstract linguistic processing begins.

Quantitative Alignment of Spatiotemporal Hierarchies

Our findings move beyond demonstrating a simple correlation between model layers and brain

regions. We show not only that model layers map topographically onto the cortical hierarchy,

but also that the representational content at each stage is analogous and follows a statistically

correlated trajectory (r=0.88) from acoustic to semantic processing. Furthermore, this

progression unfolds over a similar timescale (Figure 2d), with deeper model layers mapping to

cortical regions that are both anatomically downstream and temporally later in their neural

response.

This alignment suggests that the observed hierarchical transformation is a robust solution for

processing speech under realistic temporal constraints. While prior work has characterized

representational alignment through regression, our identification of specific linguistic features

across the hierarchy adds crucial depth. The fact that this distinct artificial system converges on

a representational hierarchy so similar to the brain's, both spatially (Figure 1e) and temporally

(Figure 2d), suggests they have arrived at a common, efficient computational strategy.

Mapping to the Cortical Ventral Stream

Our findings show a striking alignment between the ASR model's hierarchical layers and the

cortical ventral stream, the primary pathway for speech comprehension (*44–46*). This alignment

is quantitatively supported by the monotonic increase in both neural latency and anatomical

distance from the primary auditory cortex as a function of model depth. The progression from

early to deep model layers mapping from posterior to anterior temporal and inferior frontal

regions aligns well with the ventral stream's role in the sound-to-meaning transformation.

We also observed correlations between deeper model layers and regions of the dorsal stream

(*44–46*), though the interpretation is less direct given the dorsal stream's role in speech

production. This may reflect shared computations for complex sequential information (*47–50*) or

engagement of verbal working memory. Additionally, the Inferior Frontal Gyrus (IFG) most

strongly matched the later layers and the predictor branch of the ASR model. Given the IFG's

implicated role in unifying lexical and syntactic information (*47–49*, *51*, *52*), this match suggests

that the model's predictor branch functionally mirrors the brain's high-level integration

mechanisms. While the sentence repetition component of our task may have influenced

representations in IFG through its role in verbal working memory and cognitive control (*53–56*),

this confounding effect should be small since only a small fraction of sentences were repeated.

Overall, our findings indicate a functional congruence between the RNN-T ASR model and the

human brain's hierarchical linguistic representations (*44*, *57–59*), advancing prior work by

highlighting the specific regions and representational latencies at each stage of this hierarchy

which are common across both the human brain and the ASR model.

The Role of Training and Language Specificity

Our analysis of control models yielded new insights into how this hierarchy forms. We found that

in a French-trained model, acoustic features like pitch were strongly represented for English

stimuli, but higher-level linguistic representations were weak, and they were absent in an

untrained random model. This demonstrates that the high-level linguistic hierarchy is not an

inevitable byproduct of deep architectures and longer temporal integration (*60*) but is critically

dependent on language-specific training.

Our comparison of layer representations revealed that the French model diverged from the

English model quickly after the first two layers, pinpointing where language-specific encoding

begins. These results support recent findings that models trained on native languages better

predict neural responses (*6*) and offer a granular explanation: the divergence is driven by the

failure of non-native models to develop higher-order lexical and semantic features for the target

language.

Limitations and Future Directions

A key distinction is that the RNN-T processes speech in a non-lateralized fashion, whereas the

brain shows a strong left-hemisphere bias for higher-level linguistic tasks (*27*, *28*). Our single-

pathway model more closely approximates the computational style of the left hemisphere; the

weaker correspondence in the right hemisphere may reflect the model's inability to capture the

distinct, parallel processing strategies and speech comprehension capabilities of the right

hemisphere (*61–65*). Future biologically accurate models may require dual-pathway

architectures or multitask objectives (*38*) to capture these complex hemispheric dynamics.

Additionally, ASR models trained with a recognition loss tend to become speaker-independent,

likely removing speaker-specific information such as pitch in deeper layers (*66*, *67*). This matches

our finding that pitch encoding fades in later layers. Despite this, complex semantic

representations emerge from the relatively simple objective of predicting graphemes, a hallmark

of deep learning systems. Future work could systematically investigate how the choice of the

model's output unit (e.g., graphemes, phonemes, or words) modulates the specific nature and

strength of these emergent representations, but our results establish that the core brain-like

hierarchy is a robust outcome of the end-to-end learning process.

In conclusion, this study bridges neuroscience and artificial intelligence by revealing how both

systems process speech in hierarchical layers. Our findings not only advance our understanding

of the brain's mechanisms for linguistic encoding but also offer valuable guidance for the

development of more sophisticated and biologically informed ASR models. Moving forward,

integrating more brain-like features into artificial systems may unlock new possibilities for

understanding and enhancing human and machine communication.

Methods

Participants, neural data, task, and stimuli

Fifteen human patients (7 female, mean age: 36, range: 19-58) with drug-resistant epilepsy were studied. All patients were implanted with intracranial electroencephalography (iEEG) electrodes for epileptogenic foci localization. Twelve of the patients had stereoelectroencephalographic (sEEG) depth electrodes, while the other three had both depth electrodes and subdural grids and/or strips. All recordings were inspected by an epileptologist to ensure they were free of interictal spikes. The patients provided written, informed consent to participate in the research study prior to implantation, and the protocol was approved by the institutional review board at the Feinstein Institutes for Medical Research.

The subjects listened to approximately 30 minutes of stories spoken by voice actors. Occasional pauses in the story were added, resulting in 53 trial segments, and the subjects were asked to repeat the most recent sentence before the pause to ensure they were paying attention. All subjects were able to repeat the sentences without issue. iEEG signals were acquired at 3 kHz sampling rate, and the envelope of the high-gamma band (70-150 Hz) was extracted with the Hilbert transform (*68*). This signal was then z-scored and resampled to 100 Hz.

Electrode localization

Electrodes were localized using the iELVis toolbox (*69*). Prior to the iEEG recordings, each patient underwent a T1-weighted 1 mm isometric structural magnetic resonance imaging (MRI) scan on a 3 T scanner. After the electrode implantation, a computed tomography (CT) scan together with a T1-weighted MRI scan at 1.5 T were acquired. The post-implantation CT and MRI scans were co-registered to the preoperative MRI scan using FSL's BET and FLIRT algorithms (*70–72*). Afterwards, the artefacts of the contacts on the co-registered CT were identified manually in BioImageSuite (*73*). Volumetric information was obtained by processing and reconstructing the T1 scan using FreeSurfer v.6.0 (recon-all command) (*16*). For the anatomical analyses across

participants, we mapped the coordinates of the electrodes for each participant to the FreeSurfer

average brain (fsaverage), which is a template brain based on a combination of MRI scans of 40

real brains.

Electrode selection

Electrodes were projected onto the nearest cortical surface and assigned to a subregion

according to the Destrieux cortical atlas (*16*, *74*). We chose the Destrieux atlas due to its finer

granularity in the regions of interest. We selected all electrode sites within the auditory cortex

(AC; $N = 335$) —specifically, HG, which includes the PAC or core (*75*); the PT, which coincides

with the parabelt; and the STG—and the inferior frontal gyrus (IFG; $N = 191$). For increased

granularity during analysis, we further split the HG into posteromedial (pmHG) and anterolateral

(alHG) sections, as they have been shown to exhibit different properties (*76*). For the same reason

we also split the STG into three sections of anterior (aSTG), middle (mSTG), and posterior (pSTG).

The border between mSTG and pSTG was defined as the crossing of a virtual line extending from

the transverse temporal sulcus with the lateral surface of the STG (*76*, *77*). The border between

mSTG and aSTG was set such that they are roughly equal in size. Figure 1a shows the general

location of IFG and the subregions of the auditory cortex on the FreeSurfer average brain (*16*).

To determine whether an electrode site was speech-responsive, we first selected 53 pre-trial

silence segments ([-1 s, 0 s] relative to segment onset) and using a 200 ms wide non-overlapping

moving average window reduced it into 53×5 data points. We then selected 53 post-onset

speech segments ([0.4 s, 1.2 s] relative to segment onset) and using a similar moving average

window reduced it into 53×4 data points. We performed a two-sample t-test between the two

distributions for each electrode to obtain a p-value, and then performed a Benjamini-Hochberg

(false discovery rate) correction with an alpha of 0.05 to determine the speech-responsive

electrodes. This method was observed to be more robust compared to some alternatives when

viewing across the entire regions of interest which included electrodes inside and outside the

auditory cortex with different response latencies.

We limited our analysis to sites that were determined to be speech-responsive ($N = 291/526$).

We labeled the neural sites in both hemispheres based on their anatomical region to enable

population tests: posteromedial Heschl's gyrus (pmHG; $N_L = 12/15$, $N_R = 16/19$), anterolateral

Heschl's gyrus (alHG; $N_L = 34/36$, $N_R = 32/34$), planum temporale (PT; $N_L = 9/12$, $N_R =$

18/20), middle superior temporal gyrus (mSTG; $N_L = 44/53$, $N_R = 17/18$), posterior superior

temporal gyrus (pSTG; $N_L = 27/32$, $N_R = 21/23$), anterior superior temporal gyrus (aSTG; $N_L =$

19/60, $N_R = 0/13$), and inferior frontal gyrus (IFG; $N_L = 32/119$, $N_R = 10/72$). The electrode

locations and their responsiveness are plotted in Figure 1b on the average FreeSurfer brain,

where the color indicates whether an electrode is speech-responsive.

RNN-Transducer

To model the speech processing mechanism, we use an RNN-Transducer (RNN-T) (*13*), a

recurrent neural network trained to perform automatic speech recognition, i.e., predicting

graphemes from the speech spectrogram. The RNN-T is a general architecture, which can also

utilize self-attention and transformer layers, but our instantiation uses causal LSTM layers. The

model consists of two branches—the encoder and the predictor (Figure 1c). The encoder branch,

consisting of six uni-directional LSTM layers of 640 nodes each (E1–E6), acts as a bottom-up

encoder. It transforms the input speech spectrogram into a representation used to predict the

output labels. The predictor branch, consisting of a single uni-directional LSTM layer of 1024

nodes (P), acts as an internal language model. It stores an internal representation of the prior

predictions of the model that, together with the encoder's output, are used to make the next

prediction. A joint network merges the final encoder branch layer with the predictor branch's

embedding and predicts text characters to generate the speech transcription. The English

network outputs are projected to 42 logits, corresponding to 41 characters plus BLANK. Similarly,

for French, we use 72 output units. The model is trained with the RNN-T loss on the Switchboard

and Fisher datasets, which, put together, consist of about 2,000 hours of English phone

conversations. As presented in prior work (*78*), an additional 4-fold data augmentation was

applied to the input spectrograms to allow better generalization of the model, bringing the

duration of the unique training data to 10,000 hours. These augmentations included speed and

tempo perturbations which changed the rate of speech in the interval [0.9, 1.1] with or without

altering the pitch or timbre of the speaker, as well as spectrogram augmentation which masked

the spectrum of a training utterance with a random number of blocks of random size in both time

and frequency (*78*). Augmentation with an external language model as discussed in (*78*) was not

employed here. We computed layer activations for all layers of the model in response to the

same 30-minute stimulus set that the human participants listened to.

Time-aligning RNN-Transducer activations to neural data

The processed neural data is sampled at 100 Hz and has shape $T \times C$, where T is the number of

time steps and C is the number of electrode channels. The activations of the layers in the encoder

branch of the RNN-T models are sampled at 50 Hz and have the shape $\lfloor \frac{T}{2} \rfloor \times H_T$, where H_T is the

number of nodes in each hidden encoder layer. These activation matrices can be trivially aligned

with the neural data sampled through a resample with the integer factor 2. The activations of the

predictor branch, however, have shape $U \times H_P$, where U is the number of output graphemes

and H_P is the number of nodes in the hidden prediction layer. These activation matrices cannot

be directly aligned with the neural data since they are based on graphemes instead of time. To

make this alignment possible, we need to find the most likely "time warping" between output

grapheme indices ($1 \leq u \leq U$) and time ($1 \leq t \leq \lfloor \frac{T}{2} \rfloor$). We run the forward-backward algorithm

defined in section 2.4 of Graves (*13*) on the grapheme output probability lattice produced by the

model to obtain this "time warping" between the two sequences. We then use the $\alpha: t \rightarrow u$

alignment to stretch the activation matrix Z_P with shape $U \times H_P$ into a matrix Z_P' with shape

$\lfloor \frac{T}{2} \rfloor \times H_P$ where $Z_P'[t, :] = Z_P[\alpha(t), :]$. Since Z_P' has the same shape as encoder layer activations,

we can trivially align it to the neural data.

Linguistic features of speech

Pitch

As a measure of pitch, we computed the pitch contour (F0) of the speech signal using the
PyWORLD python package, which is a python wrapper for the WORLD vocoder (*79*). We then
averaged the value across the duration of each phoneme to obtain a phoneme-average pitch.

Phonemes

For phonetic features, we used the categorical (one-hot encoded) representation of ARPAbet
phonemes. We chose this because it allows classification in the layer-level analysis.

Phonotactic features

Phonotactics represent phoneme transition probabilities, so we used the biphone probability P_{ab}
for phoneme bigram ab:

554
$$P_{ab} = \frac{\text{freq}_{ab}}{\sum_{p \in S} \text{freq}_{ap}}$$

where S is the set of all ARPAbet phonemes. To compute the frequencies of each biphone, we
used the CMU dictionary (http://www.speech.cs.cmu.edu/cgi-bin/cmudict) to convert words to
phoneme sequences and counted the occurrence of each biphone using the SUBTLEX-US corpus,
which is an English word frequency dataset calculated from movie subtitles (*80*). Since biphone
frequencies were calculated from a word frequency dataset and without access to word
transition probability information, we counted the first phoneme transition of words separately
from non-first phonemes. For example, the biphones for the phrase "red hat" are the following:
/#r/, /re/, /ed/, /#h/ (not /dh/), /hæ/, and /æt/. The frequency of a phoneme bigram represents
the degree of exposure of an average native listener to the bigram and measures its probability
in natural speech. We purposefully chose a non-position-specific measure of phonotactics (as
opposed to the more common approach (*81*)) to maximally dissociate this effect from lexical
processes. This level represents the expectation and surprisal of the listener when hearing a new

phoneme, based on the immediate past. This prelexical phonotactics feature could indicate
predictive coding mechanisms that operate on the phonemic level (*82–85*).

Lexical-phonological features

To measure the lexical-phonological effect, we used lexical entropy and surprisal. These values
were calculated for each phoneme within a word from the previous phonemes in that word. The
surprisal caused by phoneme φ_i, $S(i)$, in word $w=\varphi_1...\varphi_K$ indicates the improbability of hearing
phoneme φ_i based on the previous $i-1$ phonemes that came before it in the word and is
calculated as follows:

576
$$S(i) = -\log_2 \frac{\text{freq}(\text{cohort}_i)}{\text{freq}(\text{cohort}_{i-1})}$$

577 where $\text{freq}(\text{cohort}_i)$ is the summed frequency of all words that start with the phoneme
578 sequence $\varphi_1...\varphi_i$. On the other hand, the lexical entropy, E(i), for phoneme φ_i, is the entropy
579 within all words that start with the phoneme sequence $\varphi_1...\varphi_i$ (the cohort) (*86*):

580
$$E(i) = -\sum_{\text{word} \in \{\text{cohort}_i\}} p(\text{word}) \log_2 p(\text{word})$$

where $p(\text{word})$ indicates the relative frequency of the word within the cohort. These two
parameters together encode the incremental lexical competition among all phonologically
consistent candidates as a word is being heard, weighted by their frequency. To compute lexical
surprisal for the word-initial phoneme, we assumed a transition from the entire lexicon, i.e., how
surprising it is to hear a word starting with phoneme p given the frequencies of all the words in
the lexicon.

Lexical-semantic features

To study the encoding of semantic information, we represented each word with its semantic
neighborhood density (SND) obtained from the English Lexicon Project (*87, 88*), which refers to
the relative distance between a word and its closest neighbors based on a global co-occurrence
model (*87, 88*). The neighborhood density can encode the degree of activation of semantically
related words in the lexicon upon hearing the target word.

Contextual embedding

We used the embedding obtained from the last hidden layer of a pre-trained GPT-2 XL model

obtained from Hugging Face (*89*). This 1.5B parameter version of GPT-2, a transformer-based

language model was pretrained using a causal language modeling (CLM) objective on English

language data. CLM is a training goal where the model predicts the next token in a sequence

given its preceding tokens, ensuring that the prediction for a position can only depend on known

outputs at previous positions.

To associate contextual embedding to words in the analysis data, we concatenated the

transcripts for all 53 trials, in the same order the participants heard them. Then, for each word,

we gave the model the last token of the target word and the 511 tokens preceding it (if available)

to obtain a contextual embedding for that word. The total 512 tokens are half the maximum

context window size of GPT-2 XL and correspond to about 3 minutes of context in the experiment

data.

Predicting neural responses from ASR activations

We predict the neural activity recorded at each electrode from each of the layers of the ASR

model (Figure 1c). We map ASR layers instead of ASR nodes to electrodes, because the high-

gamma envelope of an iEEG electrode represents a readout of the activity of neighboring neural

populations consisting of thousands of neurons rather than individual neurons.

To predict a neural response from a layer of the model, we fit a linear single-lag Ridge regressor

that predicts the electrode activity from the layer activations in response to the same stimuli.

Discounting a constant lag term δ, the output at time t is predicted only from the input at time

$t + \delta$. In other words, $y = A_i^{+\delta}\beta + \varepsilon$, where y is the $T \times 1$ neural response vector, $A_i^{+\delta}$ is the

$T \times H$ activation matrix for layer i of the ASR model with H nodes shifted by δ time steps across

its first dimension, β is the $H \times 1$ regression model that maps $A_i^{+\delta}$ to y, and ε is the regression

error.

We use the Ridge regressor from the python scikit-learn package to fit these models. The optimal
lag value (δ) and ridge regularization parameter (λ) are chosen independently for each electrode-
layer pair by maximizing the prediction score through 10-fold cross-validation. Here, and in all
regression models in this paper, nested cross-validation was used to fit models in an unbiased
way by performing finding the optimal lag and regularization parameters within only the training
set.

Predicting neural responses and ASR activations from linguistic features

We used a temporal receptive field (TRF) (*29*) framework to measure the extent to which
different linguistic features are encoded in the neural responses recorded from the brain and
activations extracted from the ASR nodes (Figure 2). We used a broad spectrum of acoustic and
linguistic features as predictors: spectrogram, acoustic edges, pitch (phoneme-average F0),
phonemes, phonotactics ($-\log P_{ab}$), word frequency, lexical-phonological (lexical entropy and
lexical surprisal), and lexical-semantics (semantic neighborhood density). The enormous
dimensionality of the contextual embedding feature prevented its use in this framework.

To produce a distribution of shuffled models for statistics, we replaced each linguistic feature
with a shuffled version, one at a time, 100 times. We measured a t-statistic of encoding using a
one-sample t-test to compute a t-value of the difference in scores between the true features and
the shuffled versions. A negative value for the t-statistic is possible if the shuffling produces a
random feature that happens to be better encoded in the neural response than the true stimuli
due to the small duration of the stimuli. So, following our previous work with the same data (*30*),
we used $t = 19$ as the threshold of significant encoding, since none of the negative t-values were
less than $t = -19$. This method was chosen over a non-parametric test of the shuffled score
improvements due to the computational limitations of estimating enough cross-validated models
to build a robust distribution with good resolution at low p-values. Special care was taken for
each type of feature to ensure that the shuffling did not alter the influence of lower-level features
in the hierarchy, as described below.

Pitch features

We grouped all the words within our 30-minute data based on their number of phonemes. Then

we shuffled the word-to-pitch sequence association map within each group.

Phonetic features

We took the CMU pronunciation dictionary (http://www.speech.cs.cmu.edu/cgi-bin/cmudict),

grouped words by their length measured in phonemes, and then shuffled the word-to-phoneme

mapping within each group. As a result, each word will have a consistent pronunciation at every

occurrence, but words that share phonemes will have independent pronunciations, e.g. /kæt/

and /bæt/ no longer share two of their three phonemes. We constrained the reassociation to

words of same length so that we kept the phoneme alignment information intact and because

words of the same length are more similar in frequency of occurrence (i.e. shorter words tend to

be more frequent). This is a rather strict control, since shuffling pronunciations with other actual

English words maintains the proper syllabic structure for English words.

Phonotactic features

To generate controls for phonotactic features, we shuffled the bigram-to-frequency associations

(i.e. the look-up table for bigram frequencies), which means that each bigram was associated

with the frequency of a randomly chosen bigram from the true distribution. This control scheme

maintained consistency across multiple occurrences of the same bigram. To counter the effect of

the separation caused by the first vs. non-first phoneme grouping, we perform the above

shuffling separately for first phones (ones starting with #) and non-first biphones, so that any first

vs. non-first effect will be maintained in the control, and thus discounted.

Word frequency

669 We grouped words based on their phoneme length and shuffled the word-to-frequency

670 associations within each group.

Lexical-phonological features

We grouped all cohorts based on the length of their shared phoneme sequence and shuffled the

cohort-to-frequency associations within each group. We used this constrained shuffling to keep

the effect of secondary information, such as the phoneme position in the word and word length,

unchanged. This control scheme also satisfies consistency, i.e. if two words share their first k

phonemes, the cohort information for their first k positions would be the same because the same

cohorts are mapped to the same information.

Lexical-semantic features

The control for the semantic condition was constructed by grouping words based on their

phoneme length and shuffling the word-to-SND associations within each group.

Predicting linguistic features from ASR activations

We predicted different linguistic features from each of the layers of the ASR model. Because

linguistic features are defined at different resolutions and linguistic units have different lengths,

we performed a unit-aligned analysis. For example, to predict linguistic features that are defined

at phoneme resolution—pitch, phoneme, biphone probability, lexical entropy and surprisal—we

extracted a layer's activations at time points $\{p_i + \delta\}$, where $\{p_i\}$ were the time points

corresponding to phoneme centers and δ was a constant time lag. This $N \times H$ activation matrix,

where N is the number of phonemes and H is the number of nodes, was multiplied by an $H \times D$

linear decoder to predict the D-dimensional linguistic feature. Similarly, for word resolution

features—word frequency, semantic neighborhood density, contextual embedding—we

extracted activations at time points $\{w_i + \delta\}$, where $\{w_i\}$ were the time times corresponding to

word centers and δ was a constant time lag.

For predicting the categorical phoneme labels we fit linear Ridge classifiers, and for the rest of

the features Ridge regressors. The best time lag (δ) and regularization parameter (λ) was

determined independently for each layer-feature pair by maximizing the 10-fold cross-validated

prediction scores.

Representation similarity of ASR model layers

We use two methods to compare representations of two ASR layers. The first is to compare their

linguistic decoding results. The second is to compare the representations directly with the

centered kernel alignment (CKA) method, which is used to measure the similarity between two
sets of high-dimensional vectors, especially representations learned by neural networks (*31*). For
this comparative analysis, we used three models: the baseline model trained on English data; a
"random" model that has the same architecture as the English model, but randomly initialized
and untrained; a "foreign" model that was trained on a French ASR task and was not exposed to
English.

Data availability

710 Although the iEEG recordings used in this study cannot be made publicly available due to
711 patient privacy restrictions, they can be requested from the author (N.M.).

Code availability

714 Code for preprocessing neural data, selecting responsive electrodes, and creating brain
715 plots is available in the naplib-python package (*90*). A reproducible capsule can be found on
716 CodeOcean (*91*). The software contains tutorial notebooks and guides for preprocessing
717 data as was done here.

Acknowledgements

720 This study was funded by the National Institute on Deafness and Other Communication
721 Disorders, (R01DC014279 to N.M.). S.B. was also supported by the National Institute on
722 Deafness and Other Communication Disorders, R01DC019979. The funders had no role in the
723 study design, data collection and analysis, decision to publish and manuscript preparation.

Author contributions

Conceptualization (M.K., N.M.); methodology (M.K., G.M., S.T., B.K., N.M.); data collection

(S.B., A.D.M.); data analysis (M.K., G.M., S.T., N.M.); writing – original draft (M.K., N.M.);

writing – revision (G.M., S.T., B.K., N.M.).

Competing interests
The authors declare no competing interests.

References

1. A. Stolcke, J. Droppo, Comparing Human and Machine Errors in Conversational Speech Transcription. arXiv arXiv:1708.08615 [Preprint] (2017). https://doi.org/10.48550/arXiv.1708.08615.
2. I. DeWitt, J. P. Rauschecker, Phoneme and word recognition in the auditory ventral stream. *Proc. Natl. Acad. Sci.* **109**, E505–E514 (2012).
3. C. J. Price, The anatomy of language: a review of 100 fMRI studies published in 2009. *Ann. N. Y. Acad. Sci.* **1191**, 62–88 (2010).
4. D. Poeppel, The neuroanatomic and neurophysiological infrastructure for speech and language. *Curr. Opin. Neurobiol.* **28**, 142–149 (2014).
5. Y. Belinkov, J. Glass, "Analyzing Hidden Representations in End-to-End Automatic Speech Recognition Systems" in *Advances in Neural Information Processing Systems* (Curran Associates, Inc., 2017; https://proceedings.neurips.cc/paper_files/paper/2017/hash/b069b3415151fa7217e870017374de7c-Abstract.html)vol. 30.
6. Y. Li, G. K. Anumanchipalli, A. Mohamed, P. Chen, L. H. Carney, J. Lu, J. Wu, E. F. Chang, Dissecting neural computations in the human auditory pathway using deep neural networks for speech. *Nat. Neurosci.* **26**, 2213–2225 (2023).
7. C. Caucheteux, A. Gramfort, J.-R. King, Evidence of a predictive coding hierarchy in the human brain listening to speech. *Nat. Hum. Behav.* **7**, 430–441 (2023).
8. C. Caucheteux, J.-R. King, Brains and algorithms partially converge in natural language processing. *Commun. Biol.* **5**, 134 (2022).
9. A. Goldstein, Z. Zada, E. Buchnik, M. Schain, A. Price, B. Aubrey, S. A. Nastase, A. Feder, D. Emanuel, A. Cohen, others, Shared computational principles for language processing in humans and deep language models. *Nat. Neurosci.* **25**, 369–380 (2022).

10. E. A. Hosseini, M. Schrimpf, Y. Zhang, S. Bowman, N. Zaslavsky, E. Fedorenko, Artificial
neural network language models align neurally and behaviorally with humans even
after a developmentally realistic amount of training. *BioRxiv*, 2022–10 (2022).
11. G. Mischler, Y. A. Li, S. Bickel, A. D. Mehta, N. Mesgarani, Contextual feature extraction
hierarchies converge in large language models and the brain. *Nat. Mach. Intell.*, 1–11
(2024).
12. N. Hadidi, E. Feghhi, B. H. Song, I. A. Blank, J. C. Kao, Illusions of Alignment Between
Large Language Models and Brains Emerge From Fragile Methods and Overlooked
Confounds. bioRxiv [Preprint] (2025). https://doi.org/10.1101/2025.03.09.642245.
13. A. Graves, Sequence Transduction with Recurrent Neural Networks. arXiv
arXiv:1211.3711 [Preprint] (2012). https://doi.org/10.48550/arXiv.1211.3711.
14. S. Ray, J. H. Maunsell, Different origins of gamma rhythm and high-gamma activity in
macaque visual cortex. *PLoS Biol.* **9**, e1000610 (2011).
15. M. Steinschneider, Y. I. Fishman, J. C. Arezzo, Spectrotemporal analysis of evoked and
induced electroencephalographic responses in primary auditory cortex (A1) of the
awake monkey. *Cereb. Cortex* **18**, 610–625 (2008).
16. B. Fischl, A. Van Der Kouwe, C. Destrieux, E. Halgren, F. Ségonne, D. H. Salat, E. Busa,
L. J. Seidman, J. Goldstein, D. Kennedy, others, Automatically parcellating the human
cerebral cortex. *Cereb. Cortex* **14**, 11–22 (2004).
17. Y. He, T. N. Sainath, R. Prabhavalkar, I. McGraw, R. Alvarez, D. Zhao, D. Rybach, A.
Kannan, Y. Wu, R. Pang, Q. Liang, D. Bhatia, Y. Shangguan, B. Li, G. Pundak, K. C. Sim,
T. Bagby, S. Chang, K. Rao, A. Gruenstein, "Streaming End-to-end Speech Recognition
for Mobile Devices" in *ICASSP 2019 - 2019 IEEE International Conference on Acoustics,
Speech and Signal Processing (ICASSP)* (2019;
https://ieeexplore.ieee.org/abstract/document/8682336), pp. 6381–6385.
18. K. Rao, H. Sak, R. Prabhavalkar, "Exploring architectures, data and units for streaming
end-to-end speech recognition with RNN-transducer" in *2017 IEEE Automatic Speech
Recognition and Understanding Workshop (ASRU)* (2017;
https://ieeexplore.ieee.org/abstract/document/8268935), pp. 193–199.
19. J. Li, R. Zhao, H. Hu, Y. Gong, "Improving RNN Transducer Modeling for End-to-End
Speech Recognition" in *2019 IEEE Automatic Speech Recognition and Understanding
Workshop (ASRU)* (2019; https://ieeexplore.ieee.org/abstract/document/9003906), pp.
114–121.
20. L. E. Shafey, H. Soltau, I. Shafran, Joint Speech Recognition and Speaker Diarization via
Sequence Transduction. arXiv arXiv:1907.05337 [Preprint] (2019).
https://doi.org/10.48550/arXiv.1907.05337.
21. M. Ghodsi, X. Liu, J. Apfel, R. Cabrera, E. Weinstein, "Rnn-Transducer with Stateless
Prediction Network" in *ICASSP 2020 - 2020 IEEE International Conference on
Acoustics, Speech and Signal Processing (ICASSP)* (2020;
https://ieeexplore.ieee.org/abstract/document/9054419), pp. 7049–7053.
22. A. Stooke, R. Prabhavalkar, K. C. Sim, P. M. Mengibar, Aligner-Encoders: Self-Attention
Transformers Can Be Self-Transducers. *Adv. Neural Inf. Process. Syst.* **37**, 100318–
100340 (2024).

23. A. Gulati, J. Qin, C.-C. Chiu, N. Parmar, Y. Zhang, J. Yu, W. Han, S. Wang, Z. Zhang, Y.
Wu, R. Pang, Conformer: Convolution-augmented Transformer for Speech Recognition.
arXiv arXiv:2005.08100 [Preprint] (2020). https://doi.org/10.48550/arXiv.2005.08100.
24. M. Keshishian, H. Akbari, B. Khalighinejad, J. L. Herrero, A. D. Mehta, N. Mesgarani,
Estimating and interpreting nonlinear receptive field of sensory neural responses with
deep neural network models. *eLife* **9**, e53445 (2020).
25. G. Mischler, M. Keshishian, S. Bickel, A. D. Mehta, N. Mesgarani, Deep neural networks
effectively model neural adaptation to changing background noise and suggest
nonlinear noise filtering methods in auditory cortex. *NeuroImage* **266**, 119819 (2023).
26. G. Saon, A. Dekel, A. Brooks, T. Nagano, A. Daniels, A. Satt, A. Mittal, B. Kingsbury, D.
Haws, E. Morais, G. Kurata, H. Aronowitz, I. Ibrahim, J. Kuo, K. Soule, L. Lastras, M.
Suzuki, R. Hoory, S. Thomas, S. Novitasari, T. Fukuda, V. Sunder, X. Cui, Z. Kons,
Granite-speech: open-source speech-aware LLMs with strong English ASR capabilities.
arXiv arXiv:2505.08699 [Preprint] (2025). https://doi.org/10.48550/arXiv.2505.08699.
27. C. McGettigan, S. Evans, S. Rosen, Z. K. Agnew, P. Shah, S. K. Scott, An Application of
Univariate and Multivariate Approaches in fMRI to Quantifying the Hemispheric
Lateralization of Acoustic and Linguistic Processes. *J. Cogn. Neurosci.* **24**, 636–652
(2012).
28. R. J. Zatorre, A. C. Evans, E. Meyer, A. Gjedde, Lateralization of Phonetic and Pitch
Discrimination in Speech Processing. *Science* **256**, 846–849 (1992).
29. M. J. Crosse, G. M. Di Liberto, A. Bednar, E. C. Lalor, The multivariate temporal
response function (mTRF) toolbox: a MATLAB toolbox for relating neural signals to
continuous stimuli. *Front. Hum. Neurosci.* **10**, 604 (2016).
30. M. Keshishian, S. Akkol, J. Herrero, S. Bickel, A. D. Mehta, N. Mesgarani, Joint,
distributed and hierarchically organized encoding of linguistic features in the human
auditory cortex. *Nat. Hum. Behav.* **7**, 740–753 (2023).
31. S. Kornblith, M. Norouzi, H. Lee, G. Hinton, "Similarity of neural network
representations revisited" in *International Conference on Machine Learning* (PMLR,
2019), pp. 3519–3529.
32. Is backpropagation biologically plausible? | IEEE Conference Publication | IEEE Xplore.
https://ieeexplore.ieee.org/abstract/document/118705.
33. A. Betti, M. Gori, G. Marra, Backpropagation and Biological Plausibility. arXiv
arXiv:1808.06934 [Preprint] (2018). https://doi.org/10.48550/arXiv.1808.06934.
34. C. D. Gilbert, M. Sigman, Brain States: Top-Down Influences in Sensory Processing.
Neuron **54**, 677–696 (2007).
35. K. Kveraga, A. S. Ghuman, M. Bar, Top-down predictions in the cognitive brain. *Brain*
Cogn. **65**, 145–168 (2007).
36. M. Rahman, B. D. B. Willmore, A. J. King, N. S. Harper, Simple transformations capture
auditory input to cortex. *Proc. Natl. Acad. Sci.* **117**, 28442–28451 (2020).
37. P. Gill, J. Zhang, S. M. N. Woolley, T. Fremouw, F. E. Theunissen, Sound representation
methods for spectro-temporal receptive field estimation. *J. Comput. Neurosci.* **21**, 5–
20 (2006).

38. G. Tuckute, J. Feather, D. Boebinger, J. H. McDermott, Many but not all deep neural
network audio models capture brain responses and exhibit correspondence between
model stages and brain regions. *Plos Biol*. **21**, e3002366 (2023).
39. T. Nagamine, N. Mesgarani, "Understanding the Representation and Computation of
Multilayer Perceptrons: A Case Study in Speech Recognition" in *Proceedings of the
34th International Conference on Machine Learning*, D. Precup, Y. W. Teh, Eds. (PMLR,
2017; https://proceedings.mlr.press/v70/nagamine17a.html)vol. 70 of *Proceedings of
Machine Learning Research*, pp. 2564–2573.
40. T. Nagamine, M. L. Seltzer, N. Mesgarani, "Exploring how deep neural networks form
phonemic categories." in *Interspeech* (2015), pp. 1912–1916.
41. Q. Raymondaud, M. Rouvier, R. Dufour, Probing the Information Encoded in Neural-
based Acoustic Models of Automatic Speech Recognition Systems. arXiv
arXiv:2402.19443 [Preprint] (2024). https://doi.org/10.48550/arXiv.2402.19443.
42. F. E. Theunissen, K. Sen, A. J. Doupe, Spectral-Temporal Receptive Fields of Nonlinear
Auditory Neurons Obtained Using Natural Sounds. *J. Neurosci*. **20**, 2315–2331 (2000).
43. Frédéric E Theunissen, Stephen V David, Nandini C Singh, Anne Hsu, William E Vinje,
Jack L Gallant, Estimating spatio-temporal receptive fields of auditory and visual
neurons from their responses to natural stimuli. *Netw. Comput. Neural Syst*. **12**, 289
(2001).
44. G. Hickok, D. Poeppel, The cortical organization of speech processing. *Nat. Rev.
Neurosci*. **8**, 393–402 (2007).
45. G. Hickok, D. Poeppel, Dorsal and ventral streams: a framework for understanding
aspects of the functional anatomy of language. *Cognition* **92**, 67–99 (2004).
46. A. D. Friederici, The cortical language circuit: from auditory perception to sentence
comprehension. *Trends Cogn. Sci*. **16**, 262–268 (2012).
47. C. Pallier, A.-D. Devauchelle, S. Dehaene, Cortical representation of the constituent
structure of sentences. *Proc. Natl. Acad. Sci*. **108**, 2522–2527 (2011).
48. E. Fedorenko, A. Nieto-Castañon, N. Kanwisher, Lexical and syntactic representations
in the brain: An fMRI investigation with multi-voxel pattern analyses. *Neuropsychologia*
50, 499–513 (2012).
49. S. G. Costafreda, C. H. Fu, L. Lee, B. Everitt, M. J. Brammer, A. S. David, A systematic
review and quantitative appraisal of fMRI studies of verbal fluency: role of the left
inferior frontal gyrus. *Hum. Brain Mapp*. **27**, 799–810 (2006).
50. J. P. Rauschecker, Ventral and dorsal streams in the evolution of speech and language.
Front. Evol. Neurosci. **4** (2012).
51. W. Matchin, C. Hammerly, E. Lau, The role of the IFG and pSTS in syntactic prediction:
Evidence from a parametric study of hierarchical structure in fMRI. *Cortex* **88**, 106–123
(2017).
52. P. Hagoort, On Broca, brain, and binding: a new framework. *Trends Cogn. Sci*. **9**, 416–
423 (2005).
53. W. Matchin, G. Hickok, The Cortical Organization of Syntax. *Cereb. Cortex* **30**, 1481–
1498 (2020).
54. C. Rogalsky, G. Hickok, The role of Broca's area in sentence comprehension. *J. Cogn.
Neurosci*. **23**, 1664–1680 (2011).

55. Broca's Area and Language Processing: Evidence for the Cognitive Control Connection
- Novick - 2010 - Language and Linguistics Compass - Wiley Online Library.
https://compass.onlinelibrary.wiley.com/doi/full/10.1111/j.1749-818X.2010.00244.x.
56. D. January, J. C. Trueswell, S. L. Thompson-Schill, Co-localization of stroop and
syntactic ambiguity resolution in Broca's area: implications for the neural basis of
sentence processing. *J. Cogn. Neurosci.* **21**, 2434–2444 (2009).
57. U. Hasson, E. Yang, I. Vallines, D. J. Heeger, N. Rubin, A hierarchy of temporal receptive
windows in human cortex. *J. Neurosci.* **28**, 2539–2550 (2008).
58. Y. Lerner, C. J. Honey, L. J. Silbert, U. Hasson, Topographic mapping of a hierarchy of
temporal receptive windows using a narrated story. *J. Neurosci.* **31**, 2906–2915 (2011).
59. N. Ding, L. Melloni, A. Yang, Y. Wang, W. Zhang, D. Poeppel, Characterizing neural
entrainment to hierarchical linguistic units using electroencephalography (EEG). *Front.*
Hum. Neurosci. **11**, 481 (2017).
60. M. Keshishian, S. Norman-Haignere, N. Mesgarani, "Understanding Adaptive,
Multiscale Temporal Integration In Deep Speech Recognition Systems" in *Advances in*
Neural Information Processing Systems (Curran Associates, Inc., 2021;
https://proceedings.neurips.cc/paper/2021/hash/ccce2fab7336b8bc8362d115dec2d
5a2-Abstract.html)vol. 34, pp. 24455–24467.
61. M. Dennis, H. A. Whitaker, "8 - Hemispheric Equipotentiality and Language
Acquisition" in *Language Development and Neurological Theory*, S. J. Segalowitz, F. A.
Gruber, Eds. (Academic Press, 1977;
https://www.sciencedirect.com/science/article/pii/B9780126356502500145), pp. 93–
106.
62. J. M. Millar, H. A. Whitaker, "CHAPTER 4 - The Right Hemisphere's Contribution to
Language: A Review of the Evidence from Brain-Damaged Subjects" in *Language*
Functions and Brain Organization, S. J. Segalowitz, Ed. (Academic Press, Boston, 1983;
https://www.sciencedirect.com/science/article/pii/B9780126356403500102), pp. 87–
113.
63. D. Poeppel, Pure word deafness and the bilateral processing of the speech code. *Cogn.*
Sci. **25**, 679–693 (2001).
64. D. Poeppel, The analysis of speech in different temporal integration windows: cerebral
lateralization as 'asymmetric sampling in time.' *Speech Commun.* **41**, 245–255 (2003).
65. C. Oderbolz, D. Poeppel, M. Meyer, Asymmetric Sampling in Time: Evidence and
perspectives. *Neurosci. Biobehav. Rev.* **171**, 106082 (2025).
66. C. Tang, L. S. Hamilton, E. F. Chang, Intonational speech prosody encoding in the
human auditory cortex. *Science* **357**, 797–801 (2017).
67. Y. Li, C. Tang, J. Lu, J. Wu, E. F. Chang, Human cortical encoding of pitch in tonal and
non-tonal languages. *Nat. Commun.* **12**, 1161 (2021).
68. E. Edwards, M. Soltani, W. Kim, S. S. Dalal, S. S. Nagarajan, M. S. Berger, R. T. Knight,
Comparison of time–frequency responses and the event-related potential to auditory
speech stimuli in human cortex. *J. Neurophysiol.* **102**, 377–386 (2009).
69. D. M. Groppe, S. Bickel, A. R. Dykstra, X. Wang, P. Mégevand, M. R. Mercier, F. A. Lado,
A. D. Mehta, C. J. Honey, iELVis: An open source MATLAB toolbox for localizing and
visualizing human intracranial electrode data. *J. Neurosci. Methods* **281**, 40–48 (2017).

70. M. Jenkinson, S. Smith, A global optimisation method for robust affine registration of brain images. *Med. Image Anal.* **5**, 143–156 (2001).

71. M. Jenkinson, P. Bannister, M. Brady, S. Smith, Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images. *NeuroImage* **17**, 825–841 (2002).

72. S. M. Smith, Fast robust automated brain extraction. *Hum. Brain Mapp.* **17**, 143–155 (2002).

73. X. Papademetris, M. P. Jackowski, N. Rajeevan, M. DiStasio, H. Okuda, R. T. Constable, L. H. Staib, BioImage Suite: An integrated medical image analysis suite: An update. *Insight J.* **2006**, 209 (2006).

74. C. Destrieux, B. Fischl, A. Dale, E. Halgren, Automatic parcellation of human cortical gyri and sulci using standard anatomical nomenclature. *NeuroImage* **53**, 1–15 (2010).

75. R. A. Sweet, K.-A. Dorph-Petersen, D. A. Lewis, Mapping auditory core, lateral belt, and parabelt cortices in the human superior temporal gyrus. *J. Comp. Neurol.* **491**, 270–289 (2005).

76. L. S. Hamilton, Y. Oganian, J. Hall, E. F. Chang, Parallel and distributed encoding of speech across human auditory cortex. *Cell* **184**, 4626-4639.e13 (2021).

77. M. Ozker, I. M. Schepers, J. F. Magnotti, D. Yoshor, M. S. Beauchamp, A Double Dissociation between Anterior and Posterior Superior Temporal Gyrus for Processing Audiovisual Speech Demonstrated by Electrocorticography. *J. Cogn. Neurosci.* **29**, 1044–1060 (2017).

78. G. Saon, Z. Tüske, D. Bolanos, B. Kingsbury, "Advancing RNN Transducer Technology for Speech Recognition" in *ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)* (2021; https://ieeexplore.ieee.org/abstract/document/9414716), pp. 5654–5658.

79. M. Masanori, K. Hideki, K. Haruhiro, Fast and reliable f0 estimation method based on the period extraction of vocal fold vibration of singing voice and speech. *J. Audio Eng. Soc.* (2009).

80. M. Brysbaert, B. New, Moving beyond Kučera and Francis: A critical evaluation of current word frequency norms and the introduction of a new and improved word frequency measure for American English. *Behav. Res. Methods* **41**, 977–990 (2009).

81. M. S. Vitevitch, P. A. Luce, Probabilistic Phonotactics and Neighborhood Activation in Spoken Word Recognition. *J. Mem. Lang.* **40**, 374–408 (1999).

82. C. Brodbeck, L. E. Hong, J. Z. Simon, Rapid Transformation from Auditory to Linguistic Representations of Continuous Speech. *Curr. Biol.* **28**, 3976-3983.e5 (2018).

83. S. Ylinen, M. Huuskonen, K. Mikkola, E. Saure, T. Sinkkonen, P. Paavilainen, Predictive coding of phonological rules in auditory cortex: A mismatch negativity study. *Brain Lang.* **162**, 72–80 (2016).

84. K. Friston, The free-energy principle: a rough guide to the brain? *Trends Cogn. Sci.* **13**, 293–301 (2009).

85. P. Gagnepain, R. N. Henson, M. H. Davis, Temporal Predictive Codes for Spoken Words in Auditory Cortex. *Curr. Biol.* **22**, 615–621 (2012).

86. M. K. Leonard, K. E. Bouchard, C. Tang, E. F. Chang, Dynamic Encoding of Speech Sequence Probability in Human Temporal Cortex. *J. Neurosci.* **35**, 7203–7214 (2015).

87. D. A. Balota, M. J. Yap, K. A. Hutchison, M. J. Cortese, B. Kessler, B. Loftis, J. H. Neely,
D. L. Nelson, G. B. Simpson, R. Treiman, The English Lexicon Project. *Behav. Res.*
Methods **39**, 445–459 (2007).

88. C. Shaoul, C. Westbury, Exploring lexical co-occurrence space using HiDEx. *Behav.*
Res. Methods **42**, 393–413 (2010).

89. A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever, others, Language models
are unsupervised multitask learners. *OpenAI Blog* **1**, 9 (2019).

90. G. Mischler, V. Raghavan, M. Keshishian, N. Mesgarani, naplib-python: Neural acoustic
data processing and analysis tools in python. *Softw. Impacts* **17**, 100541 (2023).

91. G. Mischler, V. Raghavan, M. Keshishian, N. Mesgarani, naplib-python: Neural Acoustic
Data Processing and Analysis Tools in Python, version 1.0 (2023);
https://doi.org/10.24433/CO.7346414.v1.