Robustness of high-throughput prediction of leaf
ecophysiological traits using near infra-red spectroscopy
and poro-fluorometry.

Eva Coindre[1,2], Romain Boulord[2], Laurine Chir[2], Virgilio Freitas[1,2], Maxime Ryckewaert[3],
Thomas Laisné[2], Virginie Bouckenooghe[4,5], Maëlle Lis[2], Llorenç Cabrera-Bosquet[2], Agnès
Doligez[1,5], Thierry Simonneau[2], Benoît Pallas[2], Aude Coupel-Ledru[2]*, Vincent Segura[1,5]*.

[1] UMR AGAP Institut, Univ Montpellier, CIRAD, INRAE, Institut Agro, F-34398 Montpellier,
France;
[2]LEPSE, Univ Montpellier, INRAE, Institut Agro, Montpellier, France;
[3]Inria, LIRMM, Univ Montpellier, CNRS, Montpellier, France;
[4]Institut français de la vigne et du vin, Pôle National Matériel Végétal, Le Grau du Roi 30240,
France
[5]Geno-Vigne®, IFV-INRAE-Institut Agro, F-34398, Montpellier, France;
(*Authors for correspondence: email aude.coupel-ledru@inrae.fr and vincent.segura@inrae.fr)

Abstract

Background: Water resource is a major limiting factor impacted by climate change that threatens
crop production and quality. Understanding the ecophysiological mechanisms involved in the
response to water deficit is crucial to select new varieties more drought tolerant. A major
bottleneck hampering such advances is the lack of methods for measuring ecophysiological traits
on large populations of individuals. We investigated the relevance of spectroscopy and poro-
fluorometry with related high-throughput measurement devices to predict leaf morphological and
ecophysiological traits using partial least square regression (PLSR) models. This work relies on
a grapevine diversity panel grown in pots under contrasted conditions, outdoors under well
watered conditions and in a greenhouse with three different soil water treatments. We took
advantage of these experimental designs to specifically assess the robustness of predictive
models.

Results: Some complementarity between measuring devices were found, with spectrometers
being able to predict leaf mass per area, water content and water quantity ($R^2>0.58$), while the
poro-fluorometer could predict net CO_2 assimilation ($R^2>0.72$), regardless of the water treatment.
The prediction of leaf mass per area appeared to be quite robust between outdoors and
greenhouse experiments. The prediction of water use efficiency was highly dependent on the
water treatment, with much better predictions under moderate ($R^2>0.73$) than severe water deficit.
We then used the high-throughput devices alone to measure the whole grapevine panel, by
applying calibration models to predict ecophysiological traits and estimated their broad sense
heritability. Leaf mass per area was also directly determined on the entire diversity panel and its

heritability was similar whether calculated on observed or predicted values. The highest computed
heritabilities for these traits reached values close to 0.5.

Conclusions: This study showed that spectrometers and poro-fluorometer could be reliable
nondestructive tools for the high-throughput phenotyping of ecophysiological traits on thousands
of plants, paving the way for studying the genetic determinism of such traits.

Keywords : High-throughput phenotyping, near-infrared spectroscopy (NIRS), fluorescence,
Partial least square regression (PLSR), leaf traits, diversity panel, soil water deficit, grapevine,
broad-sense heritability

44 Introduction

Over the last decades, climate change has become a global concern. The Mediterranean region

is particularly concerned, where prediction expects significant temperature rises and changes in

annual rainfall patterns [1,2]. In order to maintain crops in this context, there is a need to explore

new combinations of genetic and management choices depending on environmental conditions.

Identifying the best performing solutions further requires high throughput characterization of traits

related to plant functioning and their responses to the environment.

Gas exchange, leaf structure and specific leaf biochemical components are among the traits most

impacted by abiotic constraints such as soil water availability. The regulation of gas exchange at

the leaf level by stomatal closure/opening plays a key role in the whole plant response to water

stress. Indeed, a soil water deficit leads to a drop in water potential all along the plant that could

damage its water transfer capacity and result in organ or plant death [3]. To prevent such damage,

plants can quickly close their stomata, reducing transpiration (E) [4] and helping to maintain a

high leaf water content (WCf) [5]. However, this water saving strategy has a heavy cost for the

plant as it also decreases net photosynthesis (A_n) by decreasing CO_2 uptake [3], and in turn

biomass production. A trade-off between reducing E and maintaining A_n under water stress can

be sought by considering the water use efficiency, *i.e.* the biomass produced per unit of water

consumed. At the leaf level, it is measured with the instantaneous water use efficiency (WUE_{inst}),

calculated as the ratio between A_n and E, while the intrinsic water use efficiency (WUE_{intr}),

calculated as the ratio between A_n and the stomatal conductance for water vapor (g_{sw}), provides

an alternative estimate, less dependent on air vapor pressure deficit and closer to the genetic

determinisms than WUE_{inst} [6].

In grapevine, the species of interest in the present work, a large genotypic variability has already

been observed for A_n, g_{sw}, WUE_{intr}, leaf water potential (Ψ) [7–10]. However, this variability was

observed for a limited number of cultivars and/or in a limited number of growing conditions, usually

well-watered conditions. High-throughput assessment of these ecophysiological traits is limited

by the time required for measurements using leaf gas analyzers or pressure chambers. Studying

large populations with a wide range of genetic diversity under various conditions is crucial to

identify the best performing cultivars. It can also enable the identification of genetic regions

associated with these traits and their responses to contrasted environmental conditions [10,11].

A main challenge is thus to investigate the use of alternative high-throughput methods as proxies

to accurately predict traits of interest on large panels of genotypes under various water availability

treatments and under different growing conditions [12].

Fluorometer devices, measuring the quantum efficiency of photosystem II, electron transport rate,

and photochemical and non-photochemical quenching coefficients, have been proposed as a

low-cost and fast method to estimate A_n [13,14]. Chlorophyll fluorescence measurements were

also reported to evaluate the variability of photosynthetic performance among a population of

hybrids in barley [15]. Moreover, previous studies have calculated a semi-empirical index that

combines fluorescence parameters and leaf temperature, to estimate net photosynthesis in fruit

trees [16]. This indicator was then used to evaluate the photosynthesis activity of a core-collection

of apples in response to water deficit [17]. Near-infrared spectroscopy (NIRS) is another high-

throughput method commonly used to predict plant tissue composition [18–20]. Dedicated

chemometrics methods, such as Partial Least Square Regression (PLSR) [21], are used to

establish relationships between spectral absorbance or reflectance and reference measurements

obtained mostly by low-throughput methods. NIRS has been reported in plants to predict

numerous leaf compositional traits, including nitrogen [22] and carbon content, lignin, cellulose

[19], protein, starch, total non-structural carbohydrates [23] and sugars content [24,25]. NIRS has

also been implemented to predict various morphological and ecophysiological traits on multiple

species and on large populations of the same species. For instance, leaf mass per area (LMA),

which is widely used in plant ecology as an indicator of plant functioning, has been predicted by

NIRS on diverse species [24,26]. NIRS predictive models were also reported for LMA and A_n on

wheat and triticale germplasms [27] as well as on hybrids of maize [28]. LMA, A_n, WUE_{intr}, WUE_{inst},

Ψ and leaf water content were together predicted by NIRS on a diversity panel of maize [22] and

Ψ has also been predicted by NIRS on several cultivars of grapevine [29,30]. The relevance of

NIRS to predict water related traits was observed to be associated with light absorption by water

at wavelength bands centered around 1400 and 1900 nm [31,32]. However, the presence of water

can also reduce leaf reflectance, hindering the detection of other components. To minimize the

impact of water on spectra and consequently on the prediction accuracy of other traits, spectra

can be collected on dried leaves [33]. Alternatively, the water absorption effect can be reduced

using water-removed spectra [34] or by using an external parameter orthogonalisation [35].

Finally, not all spectrometers measure the same wavelength range. Therefore, the type of

spectrometer must be selected according to its application [36,37].

When studying ecophysiological traits, which vary according to experimental conditions, the

robustness of PLSR model predictions must be examined. On grapevine, predictive models with

NIRS data have been built on few cultivars subjected to different soil water treatments [29,30,38].

PLSR models were calibrated and validated with datasets containing samples from all water

treatments [29,38], without assessing the ability of the model calibrated on a given water

treatment to predict the values of plants subjected to another soil water treatment. If PLSR models

are robust across different aerial environmental conditions and soil water availabilities,

phenotyping time could be reduced in new experiments. Another issue with the PLSR model is

the risk of overfitting. To prevent this risk, the calibration model is usually built with a cross-

validation procedure. However, even in a cross-validation setting, the predictive ability of the

model could still depend on the calibration and validation sets that could be randomly or non-

randomly chosen [39].

In this study, we evaluated the ability and complementarity of NIRS and poro-fluorometry data to

predict leaf traits that are difficult to access at high-throughput. These two innovative approaches

were applied on a grapevine diversity panel [40], grown in pots both outdoors under non-limiting

water availability and in a greenhouse with varying intensities of soil water deficit. The robustness

of PLSR models was studied across experiments and water treatments. Heritabilities of traits

either directly measured or estimated from high-throughput data were compared to investigate

the ability of high-throughput phenotyping to assess the genotypic variability.

125 Material and methods

126 Plant material and experimental design

We used a subset of 241 cultivars from a panel of 279, previously designed to represent the

worldwide genetic diversity of *Vitis vinifera* [40]. We added 5 cultivars that are in the process of

being registered in the French catalog, resulting in 246 studied cultivars. Twenty own-rooted

plants were grown for each cultivar with ferti-irrigation from 2018 at the experimental vineyard of

l'Institut Agro Montpellier (France) in individual 3-liter pots containing a 30:70 (v/v) mixture of

loamy soil and organic compost [41]. In January 2020, the plants were transferred into larger,

individual 9-liter pots filled with the same substrate.

A first phenotyping season was conducted in July 2021, on the potted plants grown in the

experimental vineyard under non-limiting, drip-irrigated conditions ("Outdoor experiment"). Leaf

phenotyping was performed during seven mornings on two to three plants per cultivar. Six plants

out of the 20 available per cultivar were next retained to be part of a greenhouse experiment in

2022, where different watering treatments were set up ("Greenhouse experiment"). This second

experiment was conducted in the PhenoArch phenotyping platform [42] hosted at the M3P

(Montpellier Plant Phenotyping Platforms, https://eng-lepse.montpellier.hub.inrae.fr/platforms-

m3p/montpellier-plant-phenotyping-platforms-m3p), from May to August 2022. The whole panel

(246 cultivars) was subjected to three different water treatments: Well-Watered (WW), moderate

Water Deficit (WD1) and severe Water Deficit (WD2) maintained at different soil water content in

the pots, with two plants for each cultivar and each water treatment (1476 plants in total). These

treatments correspond to soil water potential equal to -0.03 MPa (well watered conditions, WW),

-0.11 Mpa (moderate water deficit, WD1) and -0.43 Mpa (severe water deficit, WD2) (protocol for

management of water treatment as in Coupel-Ledru et al., 2014 [10]). For each cultivar, the six

plants were grouped into two triplets (one triplet including one WW, one WD1 and one WD2 plant),

and cultivar triplets were randomized within the phenotyping platform. Leaf phenotyping was

conducted over 24 mornings in June and July 2022, once the water content in the pots had

stabilized at their target values. Environmental variables were monitored using 10 probes,

strategically distributed throughout the greenhouse.

Leaf phenotyping

For both experiments (outdoors and greenhouse), measurements were performed between 9:00

and 13:00 (UTC+2), maximizing environmental and traits variations to support the statistical

calibration process. Leaves were chosen as fully expanded and well exposed to sunlight. They

were usually located between the tenth and the fifteenth phytomer from the apex. Two kinds of

measurements were performed: high-throughput phenotyping on all six plants of the 246 cultivars

and low-throughput phenotyping, on a subset of randomly selected plants. Multiple devices were

used successively on the same leaf *in situ*, in a short time interval, for both high- and low-

throughput phenotyping. The first device used was a hand-held poro-fluorometer (Li600, Portable

Photosynthesis System LI-600, Licor, Lincoln, United States). It was used to measure the

transpiration rate, E (mmol m^{-2} s^{-1}), the stomatal conductance g_{sw} (mol m^{-2} s^{-1}), chlorophyll

fluorescence parameters and micro-climate variables i.e. leaf vapor pressure deficit, atmospheric

pressure and ambient light (Supplementary Table 1). Two measurements were taken at two

different points on the same leaf and were averaged to obtain a single value per leaf. The second

and third devices were micro-portable near infrared spectrometers: MicroNIR (MicroNIR™ Onsite-

W, VIAVI, Chandler, AZ, United States) and NeoSpectra (NeoSpectra™ Scanner, Si-Ware,

Miami, FL, United States). The MicroNIR covers a spectral range from 908 nm to 1676 nm with

125 wavelengths, resulting in a spectral sampling interval of 6.2 nm. The NeoSpectra covers a

spectral range from 1350 nm to 2500 nm with 257 wavelengths and a spectral sampling interval

of 16 nm. The wavelength interval between 1350 nm and 1676 nm was common between both

devices. For both devices, two spectra were collected per leaf on the lamina while avoiding the

principal veins. These two spectra were respectively collected on each side of the leaf (abaxial

and adaxial faces) and were then averaged to obtain a single spectrum per leaf. After these

measurements, a 3 cm diameter disk was sampled from the leaf. In the greenhouse experiment,

this disk was immediately weighed after sampling to obtain its fresh weight (FW, mg) with 0.1 mg

accuracy (Sartorius balance, QUINTIX224-1S, Göttingen, Germany). For both experiments, the

disk was oven-dried for one week at 60°C before being weighed to get its dry weight (DW, mg).

Leaf Mass per Area (LMA, mg cm^{-2}) was calculated as the ratio between DW and disk area (7.07

cm^2). For disks of leaves collected in the greenhouse experiment only, leaf water content (WC_f,

mg H_2O mg^{-1} fresh weight) was also calculated, as $\frac{FW - DW}{FW}$ and the water quantity (WQ, mg H_2O

per leaf disk) as $FW - DW$. The measurement of LMA, WCf, and WQ is traditionally considered a

low-throughput method due to the significant time and sample storage requirements. However,

in this study, these traits were measured on all plants in the greenhouse experiment. The high-

throughput leaf phenotyping was performed during 24 mornings on the greenhouse experiment.

After weighing, dried disks were stored at 20°C. They were later used again to collect NIRS

spectra using a laboratory spectrometer ASD (ASD LabSpec® 4, Analytical Spectral Devices,

Boulder, USA). The temperature was maintained at 20°C in the lab during measurements. Four

spectra were taken using a reflectance probe (4 mm diameter) at different points of the dried disk

before being averaged. The ASD covers a spectral range from 350 nm to 2500 nm with 2150

wavelengths and a sampling interval of 1 nm.

The low-throughput measurements presented in this paper were performed only in the

greenhouse experiment on a subset of 120 plants (34 cultivars) subjected to three water

treatments. They were performed during 4 mornings (June 14, 2022, July 6, 2022, July 21, 2022

and July 26, 2022). The measurements started as described above for the high-throughput

devices (i.e. Li600, MicroNir, NeoSpectra), and were followed by a measure with an InfraRed

Gas-exchange Analyzer (IRGA) equipped with a light-emitting diode light source (Li6800, Portable

Photosynthesis System, Licor, Lincoln, United States). This device allowed measuring net CO_2

assimilation (A_n, µmol m^{-2} s^{-1}), transpiration rate (E, mmol m^{-2} s^{-1}) and stomatal conductance (g_{sw},

mol m^{-2} s^{-1}). Intrinsic Water Use Efficiency (WUE_{intr}, µmol CO_2 mol^{-1} H_2O) and instantaneous

Water Use Efficiency (WUE_{inst}, µmol CO_2 mmol^{-1} H_2O) were further calculated as the ratio

between A_n and g_{sw} or A_n and E, respectively. The conditions in the leaf chamber during the

measurement were set to 400 µmol mol^{-1} CO_2, with actinic light adjusted to a value corresponding

to the ambient Photosynthetically Photon Flux Density (PPFD) measured simultaneously by the

Li600 device for each measured leaf. PPFD values thus ranged from 110 to 1150 µmol m^{-2} s^{-1}.

The leaf water potential (Ψ, MPa) was next measured using a pressure chamber (Scholander

pressure bomb, SoilMoisture Equipment Corp., Goleta, United States). Finally, leaf disks were

sampled and oven-dried to access LMA and collect spectra with the ASD device.

Preprocessing of spectral and fluorescence data

All data analyses were handled in R v4.3.0 [43]. Spectra from the ASD laboratory spectrometer were initially processed using the rmgap function (R/rchemo package) [44] to remove vertical gaps caused by differences between detectors. Wavelengths between 350 and 400 nm were removed and excluded from spectral analyses due to their noisy signals [45]. The spectra were then smoothed using R/loess, with the neighborhood size controlled by an α value of 0.03. In order to express spectra from all devices in reflectance and wavelength (nm), the MicroNIR absorbance (A) was converted into reflectance (R), as $R = \frac{1}{10^A}$, and the NeoSpectra wavenumber (v, cm^{-1}) was converted into wavelength (λ, nm), as $\lambda = \frac{10^7}{v}$. As the MicroNIR and NeoSpectra spectrometers have complementary ranges, with an overlap from 1350 nm to 1676 nm, a new, additional spectrum called MicroNIR_NeoSpectra was created for each leaf. Whole MicroNIR spectra from 950 nm to 1676 nm were retained due to their higher resolution than NeoSpectra spectra and combined with the 1676 nm - 2500 nm ranges measured with the NeoSpectra. The resulting gap at the junction of the two spectra was removed using R/rmgap from R/rchemo. All spectra (ASD, MicroNIR, NeoSpectra and MicroNIR_NeoSpectra) were then preprocessed using Standard Normal Variate (SNV) [46]. This was followed by a first-order derivative using the Savitzky-Golay filter (R/sgolayfilt from R/signal package, [47,48]). The polynomial order for the first-order derivative was set to 2, and the window sizes were set respectively to 11, 15, 15 and 41 for MicroNIR, NeoSpectra, MicroNIR_NeoSpectra and ASD, to account for their differences in resolution.

Twenty-one environmental, porometry and fluorescence measured variables were selected from the Li600 device raw measurements for further use as explicative variables in PLSR models (Supplementary Table 1).

Data modeling and cross-validation

Calibration models were constructed in order to relate high-throughput data from the

spectrometers and the poro-fluorometer Li600 to the traits of interest measured with conventional,

low-throughput devices or methods (IRGA, pressure chamber, disks weighing) using Partial Least

Square Regression (PLSR), as implemented in R/pls with the "kernelpls" method [49]. Calibration

was performed for the following traits: LMA, WC_f, WQ, A_n, Ψ, WUE_{intr} and WUE_{inst}, using data from

the greenhouse experiment. For the outdoors experiment, only LMA was considered as the other

traits were not measured. The number of leaves used to calibrate the model varied from 72 to

1437, depending on available data for the measured trait and the cross-validation settings (Table

1). Cross-validation was performed using either a 4-fold, 5-fold, or leave-one-out (LOO) method

[50]. Four- and 5-fold cross-validations were repeated 10 times (Table 1).

PLSR models were built with a maximum number of latent variables set at 20 for spectrometers

and 10 for the Li600. The optimal number of latent variables was determined by minimizing the

average Root Mean Squared Error (RMSE) over the 10 iterations of the 4- and 5-fold cross-

validations or directly the RMSE for the LOO cross-validation. Model quality was evaluated either

within the cross-validation or using validation (testing) sets (see section below for details on the

different calibration and validation sets tested) using both the R^2 computed as the squared

correlation between observed and predicted values, and the RMSE.

Table 1 Strategies to evaluate the robustness and the prediction quality of PLSR models.

	Dataset	LT or HT	Traits	Calibration					Cross-validation settings		Validation				Settings
				Nb of leaves				Total			Nb of leaves				
				WW	WD1	WD2	Outdoors	Total	Nb fold	Nb iter.	WW	WD1	WD2	Outdoors	Nb iter.
Devices complementarity	**A**	HT	LMA, WC$_f$, WQ	483	481	473	-	1437	5-fold	10	-	-	-	-	-
	B	LT	LMA, A$_n$, Ψ, WUE$_{intr}$, WUE$_{inst}$	37	36	36	-	109	5-fold	10	-	-	-	-	-
Robustness between experiments	**C**	HT	LMA	-	-	-	370	370	4-fold	10	100	100	100	100	15
	D	HT	LMA	124	123	123	-	370	4-fold	10	100	100	100	100	15
	E	HT	LMA	93	92	93	92	370	4-fold	10	100	100	100	100	15
Robustness between water treatments	**F**	HT	LMA, WC$_f$, WQ	370	-	-	-	370	4-fold	10	100	100	100	-	15
	G	HT	LMA, WC$_f$, WQ	-	370	-	-	370	4-fold	10	100	100	100	-	15
	H	HT	LMA, WC$_f$, WQ	-	-	370	-	370	4-fold	10	100	100	100	-	15
	I	HT	LMA, WC$_f$, WQ	124	123	123	-	370	4-fold	10	100	100	100	-	15
	J	LT	A$_n$, Ψ, WUE$_{intr}$, WUE$_{inst}$	24	24	24	-	72	LOO	10	10	10	10	-	100
Predictive models	**K**	LT	LMA, A$_n$, WUE$_{intr}$, WUE$_{inst}$	34	34	34	-	102	4-fold	1	-	-	-	-	1

252 Leaf mass per area (LMA), Water content (WC$_f$), Water quantity (WQ), Net CO$_2$ assimilation (A$_n$), Leaf water potential (Ψ), Intrinsic water use

253 efficiency (WUE$_{intr}$), Instantaneous water use efficiency (WUE$_{inst}$), High-throughput phenotyping (HT), Low-throughput phenotyping (LT), Number of

254 iterations (Nb Iter.), Leave-one out (LOO), Well-watered treatment (WW), Moderate water deficit treatment (WD1), Severe water deficit treatment

255 (WD2).

Devices complementarity

The first analyses aimed to compare the predictive performance of PLSR models across the

different devices for each trait, using only data from the greenhouse experiment. The calibration

set included the same number of leaves for each water treatment, consisting respectively of

approximately 480 leaves (dataset A in Table 1) or 36 leaves (dataset B in Table 1) for traits

measured at high-throughput (LMA, WC_f and WQ) or low-throughput (LMA, A_n, Ψ, WUE_{intr} and

WUE_{inst}), respectively. A 5-fold cross-validation was conducted based on cultivars rather than

individual leaves to avoid the confounding effect of cultivar prediction on the trait prediction. PLSR

models were compared based on their cross-validated R^2_{cv}, cross-validated normalized root

mean square error $NRMSE_{cv} = \frac{RMSE_{cv}}{\bar{x}}$ (with $\bar{x}$ the mean of the trait) and using a Student's t test, as

implemented in R/rstatix.

Robustness between experiments

LMA, was the trait used to assess the robustness of the PLSR models between experiments

(oudoors or in the greenhouse). Three calibration sets were used; each with a fixed size of 370

leaves (Table 1). The first calibration set (dataset C) included only outdoors leaves, the second

one (dataset D) included only greenhouse data, with approximately 123 leaves from each water

treatment and the last one (dataset E) included data from both outdoors and greenhouse

experiments.

The predictive ability of the PLSR models was assessed using validation sets, each including 100

leaves, selected to represent experiments and water treatments. The composition of the validation

set was determined through random sampling, which accounted for the proportion of plants

phenotyped each day in order to be representative of the entire phenotyping series. This sampling

was repeated 15 times, resulting in 15 distinct calibration and validation sets. PLSR models were

compared based on their R² and RMSE and a Tukey HSD post-hoc test, as implemented in
R/stats.

Robustness between water treatments

Data from the greenhouse experiment were used to assess the robustness of the PLSR models

between the different water treatments. For LMA, WC_f and WQ, which were phenotyped at high-

throughput, 4 calibration sets were tested, each including a fixed number of 370 leaves, randomly

selected independently of cultivar. A separate calibration set was created for each water treatment

(datasets F to H in Table 1) and an additional calibration set (dataset I) that included the three

water treatments in equal proportions of 123 leaves was also considered.

The predictive ability of the PLSR models was assessed using validation sets, each including 100

leaves per water treatment and accounting for the proportion of plants phenotyped each day in

order to be representative of the entire phenotyping series. This sampling was repeated 15 times,

resulting in 15 distinct calibration and validation sets.

For A_n, Ψ, WUE_{intr}, WUE_{inst}, which were phenotyped at low-throughput, the low number of leaves

did not allow us to build calibration sets per water treatment. Thus, calibration sets were created

including 24 leaves from each water treatment (dataset J in Table 1).

The predictive ability of the PLSR models was assessed using validation sets, each including 10

leaves per water treatment and accounting for the proportion of plants phenotyped each day in

order to be representative of the entire phenotyping series. This sampling was repeated 100

times, resulting in 100 distinct calibration and validation sets, in order to provide reliable estimates

and low risk of unrepresentative sampling. Significant differences between predictive abilities

were assessed with a Tukey HSD post-hoc test, as implemented in R/stats.

Calculation of WUE using predicted A

Intrinsic Water Use Efficiency (WUE_{intr_cal}) and instantaneous Water Use Efficiency (WUE_{inst_cal}) were calculated as the ratios between predicted A_n and the measured g_{sw} or E from the Li600 device, respectively. It was done for each validation set of the dataset J (Table 1). The prediction accuracy was obtained by comparing these calculated WUE_{intr_cal} and WUE_{inst_cal} with WUE_{intr} and WUE_{inst} obtained with the Li6800 measurements. Significance between predictive abilities were assessed with a Tukey HSD post-hoc test, as implemented in R/stats.

Heritability of predicted traits

To evaluate the usefulness of PLSR models we used them to predict phenotypic values across the whole panel. To this aim, a calibration set was built using leaves measured in the "low-throughput" sessions, resulting in 34 leaves per water treatment, and used to train PLSR models (dataset K in Table 1). The evaluation of these models was assessed through their cross-validated statistics R^2_{cv} and $RMSE_{cv}$. Accurate enough models ($R^2_{cv} >= 0.55$) were then applied to predict traits using high-throughput measurements.

The following mixed-linear model was applied to the resulting predicted values in order to decompose the phenotypic variation using R/lme4 [51]:

$Y_{ij} = \mu + G_i + \Sigma A_{ij} + \varepsilon_{ij}$, where Y_{ij} represented the vector of predicted values per water treatment, μ was the intercept, G_i was the random effect of the cultivar i, ΣA_{ij} was a sum of fixed effects of experimental covariates measured on the plant j from the cultivar i and ε_{ij} was the random residual effect. The fixed effects included date of measurement, time of measurement, time elapsed between the last irrigation of the plant and the measurement, duration between the entrance of the plant into the platform and the measurement, environmental conditions as the average of the 10 probes (temperature, PPFD, relative humidity, vapor pressure deficit), and plant density around each plant. For each trait within each water treatment a model selection was carried to

retain only the significant fixed effects (α = 0.05) using R/rutilstimflutre [52]. As WUE_{intr_cal} was not

symmetrically distributed, a square-root transformation was performed before the adjustment of

the mixed-linear model. Variance components in the selected model were then estimated and

used to estimate broad-sense heritability as: $H^2 = \dfrac{\sigma^2 G}{\sigma^2 G + (\frac{\sigma^2 E}{n})}$ with $\sigma^2 G$ the genotypic variance, $\sigma^2 E$ the

residual variance and n the mean number of repetitions (leaves) per cultivar within each water

treatment, typically around 2.

Results

Variability of leaf ecophysiological traits

The lowest coefficient of variation was observed for WC_f (<5%), regardless of the water treatment.

LMA and WQ showed intermediate coefficients of variation (between 15% and 22%), with

generally slight differences between water treatments and experiments (greenhouse *vs.*

outdoors) (Supplementary Table 2). LMA and WQ were positively correlated, with their correlation

coefficient increasing from 0.63 to 0.73 with the intensity of water deficit in the greenhouse

experiment (Supplementary Figure 1a, Supplementary Figure 1b and Supplementary Figure 1c).

LMA and WC_f were negatively correlated, regardless of the water treatment, with correlation

coefficient decreasing from -0.57 to -0.48 when water deficit increased. The correlation between

WC_f and WQ was lower but remained significant and positively different from zero, with values

close to 0.25 (Supplementary Figure 1a, Supplementary Figure 1b and Supplementary Figure

1c).

A_n, Ψ, WUE_{intr} and WUE_{inst} displayed more variability than LMA, WC_f and WQ (Supplementary

Figure 2), as underlined by higher coefficients of variation (Supplementary Table 2). A_n was the

trait whose coefficient of variation was the most affected by the water treatment, increasing as

the water deficit increased. Conversely, the coefficient of variation of WUE_{intr} decreased with

increasing water deficit. A_n was not significantly correlated with WUE_{intr} and WUE_{inst}, whatever the

water treatment (Supplementary Figure 1d, Supplementary Figure 1e and Supplementary Figure

1f). WUE_{intr} was strongly correlated with WUE_{inst} with values around 0.8 in all conditions

(Supplementary Figure 1d, Supplementary Figure 1e and Supplementary Figure 1f).

Devices complementarity for the prediction of leaf traits

Overall, spectra of the three spectrometers collected in the greenhouse experiment (Datasets A

and B in Table 1) were highly effective in predicting traits such as LMA, WC_f and WQ. The

coefficient of determination computed within the cross-validation procedure consistently

exceeded 0.67 (Fig 1a, Supplementary Figure 3a, Supplementary Figure 3b and Supplementary

Figure 3c) with almost no variability across the cross-validation repetitions. Nevertheless,

significant differences in R^2_{cv} were found between devices (Supplementary Table 3). The ASD

spectrometer on dry leaves yielded the most accurate models to predict LMA compared to micro-

portable spectrometers used *in situ* (Fig. 1, Supplementary Figure 4a). In contrast, the best

models for predicting WC_f and WQ were established with spectra from micro-portable

spectrometers collected *in situ* (MicroNIR, NeoSpectra and MicroNIR_NeoSpectra in Fig. 1a).

Although model performances were almost similar for these three modalities, slightly better

predictions were achieved by combining the wavelengths from MicroNIR and NeoSpectra (Fig.

1). The PLSR models built with the variables from the Li600 device were unable to predict LMA,

WC_f and WQ ($R^2_{cv} \leq 0.1$, Fig. 1a).

Regarding the prediction of A_n, Ψ, WUE_{intr} and WUE_{inst} with spectrometers, the R^2 values remained

low and not higher than 0.27 whatever the device considered (Fig. 1b). In contrast, the models

built with variables from the Li600 device for predicting A_n displayed an R^2_{cv} of 0.82 and an

$NRMSE_{cv}$ of 0.25 (Fig. 1b, Supplementary Figure 4b, Supplementary Figure 3d). The Li600 device

also seemed to capture relevant information for predicting WUE_{intr} and WUE_{inst}, with R^2_{cv} values

of 0.48 and 0.3, respectively (Fig. 1b, Supplementary Figure 3f and Supplementary Figure 3g).

Yet, it is noteworthy that the prediction accuracies of WUE_{inst} using either the Li600 or the

MicroNIR_NeoSpectra were not significantly different (Fig. 1b and Supplementary Table 3). Ψ

was poorly predicted, regardless of the device used, with an R^2_{cv} always below 0.24 (Fig. 1b and

Supplementary Figure 3e). The large variability in R^2_{cv} or $NRMSE_{cv}$ between the different cross-

validation sets was attributed to the small number of leaves included in each set (Fig. 1, dataset

B in Table 1).

To further investigate the effect of calibration set size on model accuracy, we compared PLSR

models built with low- (109 leaves) and high-throughput (1437 leaves) measurements of LMA. As

expected, models built within the low-throughput calibration set displayed significantly lower R^2_{cv}

than models built within the high-throughput calibration set (by 0.08 to 0.15) (Supplementary

Figure 5a). This might partly be due to a lower range of variation in the low-throughput calibration

set compared to the high-throughput calibration set (Supplementary Figure 1h). This point is

confirmed by the $RMSE_{cv}$ values which displayed low differences between low- and high-

throughput calibration sets with values always lower than 0.42 mg cm^{-2} (Supplementary Figure

5b).

Fig. 1 R^2_{cv} values computed in the cross validation procedure of leaf traits according to the device.

a High-throughput measured traits : leaf mass per area (LMA), Water content (WC_f) and Water quantity (WQ) (dataset A in Table 1). **b** Low-throughput measured traits : Net CO_2 assimilation (A_n), Leaf water potential (Ψ), Intrinsic water use efficiency (WUE_{intr}) and Instantaneous water use efficiency (WUE_{inst}) (dataset B in Table 1). Each point in the boxplot corresponds to the R^2_{cv} of one of the 10 iterations of the cross-validation (as detailed in Table 1).

Prediction robustness across experiments

The prediction accuracy for LMA (R^2) was significantly lower with the outdoors than the greenhouse validation set (Fig. 2). The median R^2 values of the 15 iterations ranged from 0.30 to 0.86 when models were evaluated with the outdoors validation set and from 0.78 to 0.90 when they were evaluated with the greenhouse validation set when all the devices were considered. The ASD device used on dried disks yielded the most robust models for predicting LMA, with a median R^2 values always exceeding 0.78, and RMSE values lower than 0.62 mg cm^{-2}, regardless of the calibration and validation sets (Fig. 2). Conversely the models built with micro-portable

spectrometers on fresh leaves, especially the MicroNIR, appeared to be impacted by the

environmental conditions in which they were calibrated and validated (Fig. 2). This was

particularly the case when models were calibrated with greenhouse data and validated on data

collected outdoors. For MicroNIR, NeoSpectra and MicroNIR_NeoSpectra devices, the

performance of models to predict LMA in outdoors conditions was similarly good whether

calibrated with outdoor or greenhouse_outdoor calibration sets with R^2 always exceeding 0.61

and RMSE always below 0.51 mg cm^{-2} (Fig. 2). Models calibrated with outdoors data remained

accurate to predict greenhouse data since R^2 was greater than 0.78 and RMSE lower than 0.8

mg cm^{-2}. However, the prediction of greenhouse data, using an outdoors calibration set

significantly reduced R^2 and RMSE values compared to greenhouse or greenhouse_outdoor

calibration sets (p-value ≤ 0.001). This might partly be due to a lower coefficient of variation for

LMA in outdoors (16.7) than in greenhouse (between 20.5 and 21.4) experiments (Supplementary

Table 2, Supplementary Figure 2h and Supplementary Figure 2i).

Fig. 2 Prediction quality of LMA depending on whether spectra were collected in outdoors or greenhouse experiments.

The top panel corresponds to the R^2 and the bottom panel corresponds to the RMSE (in mg cm^{-2}) of the prediction. Each point in the boxplot represents one of the 15 iterations of the validation (datasets C, D, E in Table 1). Different calibration sets are highlighted on the x-axis of each panel. Boxplots with the same letters within one facet are not significantly different ($p > 0.05$). exp. = experiment.

Prediction robustness between soil water treatments

PLSR models were compared between water treatments for LMA, WC_f and WQ as these 3 traits

were available on the entire diversity panel (datasets F to J in Table 1). Partitioning the validation

set according to the water treatment had more influence on model performance than partitioning

the calibration set (Supplementary Figure 6). We thus decided to focus our analysis on the

comparison of PLSR models calibrated with leaves from the 3 water treatments (Fig. 3).

In most cases, R^2 of predictive models was impacted by the water treatment (Fig. 3a) while RMSE

was not (Fig. 3b). For LMA, R^2 was significantly lower when predicting WD2 compared to WW

and WD1 validation sets (Fig. 3a). These differences in R^2 could be related to a decrease in the

range of variation with the increase in water deficit (Supplementary Figure 2a), since the

corresponding RMSE values did not significantly differ between water treatment (Fig. 3b).

Similarly for MicroNIR_NeoSpectra, WC_f was predicted with R^2 that significantly decreased from

0.86 to 0.75 with water deficit intensity, while RMSE did not significantly vary (Fig. 3a, Fig. 3b).

This influence of water treatment trait prediction was not observed for WQ, with R^2 values always

close to 0.8 with MicroNIR_NeoSpectra (Fig. 3a) and median RMSE values lower than 8.1 mg

H_2O, regardless of the water treatment considered for the validation sets (Fig. 3b). Spectra from

MicroNIR_NeoSpectra, taken *in situ*, provided a robust prediction of WQ across water treatment.

On the contrary, the ASD device, used on dried leaves, yielded a less accurate prediction of WQ

with median R^2 values ranging from 0.58 to 0.67 depending on the water treatment and RMSE

always higher than 9.3 mg H_2O.

Fig. 3 Prediction quality of PLSR models for LMA, WC$_f$ and WQ depending on the validation set. Models were calibrated using the WW+WD1+WD2 calibration set (dataset I in Table 1) and the MicroNIR_NeoSpectra and ASD devices. **a** corresponds to the R² and **b** corresponds to the RMSE in the validation set. Each point in the boxplot represents one of the 15 iterations of the validation (as detailed in Table 1). The blue dots and boxes correspond to the well-watered treatment (WW); orange dots and boxes to the moderate water deficit treatment (WD1); red dots and boxes to the severe water deficit treatment

(WD2); and pink dots and boxes to all WW, WD1 and WD2 treatments. LMA = leaf mass per area; WC_f =

water content; WQ = water quantity.

Because A_n, Ψ, WUE_{intr} and WUE_{inst} were phenotyped on a limited subset of leaves from the

diversity panel, PLSR models were only calibrated by gathering all water treatments, and they

were evaluated separately for each water treatment (dataset J in Table 1). The high variability of

models performance observed with the 100 resampling of validation sets within each water

treatment (Fig. 4) was likely a consequence of the small number of leaves in each validation set.

A_n was poorly predicted with spectrometers alone, with median R² values below 0.37 (Fig. 4a)

and median RMSE higher than 3.25 µmol m^{-2} s^{-1} for MicroNIR_NeoSpectra and ASD devices,

regardless of the water treatment considered for the validation (Fig. 4, Supplementary Figure 7).

In contrast, Li600 measurements resulted in a good prediction of A_n, without much influence of

water treatments, with median R² higher than 0.72 and median RMSE lower than 1.62 µmol m^{-2}

s^{-1} across all validation sets (Fig. 4). Neither the spectrometers nor the Li600 alone could reliably

predict Ψ, with median R² values consistently lower than 0.21, regardless of the water treatment

(Fig. 4a). The median RMSE consistently exceeded 0.33 MPa (Fig. 4b).

465
Fig. 4 Prediction quality of PLSR models for A_n and Ψ depending on the validation set.

Models were calibrated using the WW+WD1+WD2 calibration set (dataset J in Table 1) and the

MicroNIR_NeoSpectra, ASD and Li600 devices. **a** corresponds to the R^2 and **b** corresponds to the RMSE

in the validation set. Each point in the boxplot represents one of the 100 iterations of the validation (as

detailed in Table 1). The blue dots and boxes correspond to the well-watered treatment (WW); orange dots

and boxes to the moderate water deficit treatment (WD1); red dots and boxes to the severe water deficit

treatment (WD2); and pink dots and boxes to all WW, WD1 and WD2 treatments. A_n = Net CO_2 assimilation;

Ψ = Leaf water potential.

PLSR models built with Li600 measurements displayed a variable performance in predicting

WUE_{intr} and WUE_{inst} depending on the constitution of the validation set. The validation set that

included the three water treatments (WW+WD1+WD2) showed intermediate prediction quality

with median R^2 values of 0.52 and 0.46 for predicting WUE_{intr} and WUE_{inst}, respectively (Fig. 5a).

The prediction accuracy of PLSR models was significantly different from one water treatment to

another. It was maximal under WD1 water treatment for WUE_{intr} and WUE_{inst} with respectively,

median R^2 of 0.75 and 0.73, followed by intermediate performance under WW (median R^2 of 0.52

and 0.49 for WUE_{intr} and WUE_{inst}) and finally poor performance under WD2 (median R^2 of 0.1 and

0.25 for WUE_{intr} and WUE_{inst}) (Fig. 5). These results indicated that PLSR models built with the

Li600 device could be considered accurate enough to predict WUE_{intr} and WUE_{inst} for leaves

subjected to WD1 water treatment only. On the other hand, spectrometers performed poorly in

predicting WUE_{intr} (Supplementary Figure 8) while MicroNIR and MicroNIR_NeoSpectra provided

more relevant measurements to predict WUE_{inst} under WD1, with a median R^2 close to 0.53

(Supplementary Figure 8a).

Since WUE is the ratio between carbon gains (A_n) and water loss related data (g_{sw} or E), both

WUE_{intr} and WUE_{inst} could be either directly predicted, or calculated as WUE_{intr_cal} and WUE_{inst_cal}

using the prediction of A_n as and measured g_{sw} (or E) from the LI600 device.

We first compared values of g_{sw} (or E) directly measured with both devices (Li6800 or Li600). The

correlations for g_{sw} and E ranged from 0.93 to 0.97 and from 0.83 to 0.92, respectively, depending

on the water treatment (Supplementary Figure 9). Then, we assessed the interest of using

WUE_{intr_cal} and WUE_{inst_cal} instead of predicting directly WUE_{intr} and WUE_{inst}. The median R^2 of

WUE_{intr_cal} reached 0.77 for the WW validation set which was significantly higher than for the

prediction of WUE_{intr} for the same WW validation set (p-value < 0.001) (Fig. 5a). Prediction

performance for WUE_{intr_cal} was not significantly improved compared to WUE_{intr} prediction when

considering the other validation sets (WD1, WD2) (Fig. 5a and Fig. 5c). The use of calculated

values for both WUE resulted in considerable variation in RMSE values compared with direct

predictions for WD1 and WD2 water treatment (Fig. 5b and Fig. 5c).

Fig. 5 Prediction quality of PLSR models for WUE_{intr}, WUE_{inst}, WUE_{intr_cal}, WUE_{inst_cal} depending

on the validation set.

Models were calibrated with the WW+WD1+WD2 calibration set (dataset J in Table 1) with variables from

the Li600 device for intrinsic water use efficiency (WUE_{intr}) and instantaneous water use efficiency (WUE_{inst})

(as the ratio of Li6800 A_n and E or g_{sw} measurements) directly predicted or calculated (WUE_{intr_cal}

and WUE_{inst_cal}) as the ratio between (i) the prediction of the net CO_2 assimilation (A_n) and (ii) the Li600

measurements of the stomatal conductance (g_{sw}) and the transpiration rate (E) respectively. **a** corresponds

to the R^2, **b** corresponds to the RMSE expressed in µmol CO_2 mol^{-1} H_2O for WUE_{intr} and WUE_{intr_cal} and **c**

corresponds to the RMSE expressed in µmol CO_2 $mmol^{-1}$ H_2O for WUE_{inst} and WUE_{inst_cal}. Each point in the

boxplot corresponds to one of the 100 iterations of the validation (as detailed in Table 1). The blue dots and

boxes correspond to the well-watered treatment (WW); orange dots and boxes to the moderate water deficit

treatment (WD1); and red dots and boxes to the severe water deficit treatment (WD2).

Prediction of LMA, A_n, WUE_{intr} and WUE_{inst} using high-throughput measurements

The PLSR models that were retained to predict traits (LMA, A_n, WUE_{intr} and WUE_{inst}) were those

exhibiting a median R² higher than 0.55 in at least one validation set when they were built on low

throughput data (dataset K in Table 1). The prediction models for LMA used between 3 and 12

latent variables, had R^2_{cv} higher than 0.76 and $RMSE_{cv}$ lower than 0.4 mg cm^{-2}, irrespectively of

the water treatment. The cross-validated predicted values of LMA, regardless of the device used,

were highly correlated with the *in-situ* measurements, with a correlation coefficient higher than

0.76 (Supplementary Figure 10a). Ten latent variables were retained to predict A_n using the Li600

device (Table 2). The corresponding model displayed good performance for all water treatments

with R^2_{cv} and $RMSE_{cv}$ of 0.8 and 1.59 µmol m^{-2} s^{-1} respectively. WUE_{intr} and WUE_{inst} were predicted

with an R^2_{cv} of 0.47 and 0.44, across all water treatment. In agreement with previous results, R^2_{cv}

for WW and WD2 water treatments did not exceed 0.53 whereas the R^2_{cv} for WD1 was above

0.73 (Table 2, Supplementary Figure 10c and Supplementary Figure 10d). Therefore, models

built with Li600 data were used to predict WUE_{intr} and WUE_{inst} for leaves under WD1 treatment

only.

The heritability of measured LMA across the entire diversity panel ranged from 0.28 to 0.43

depending on the water treatment (Fig. 6a). The prediction of LMA using spectrometers provided

very similar heritability estimates ranging from 0.20 to 0.42. We also estimated genetic values

from LMA predictions which showed high correlations (r ≥ 0.9) with the genetic values estimated

with the observed phenotypes, whatever the water treatment considered (Fig. 6c). Predicted A_n,

WUE_{intr} and WUE_{inst} had heritability ranging from 0.16 to 0.5, depending on the water treatment

(Fig. 6b). WUE_{intr_cal} which was calculated with predicted A_n and measured g_{sw} was unable to

provide genetic information with an heritability lower than 0.1. For the WD1 water treatment,

WUE_{intr_cal} displayed a lower heritability than WUE_{intr} that was directly predicted with Li600

variables (Fig. 6b).

Table 2 PLSR criteria obtained for predictive models (dataset K in Table 1).

Trait	Device	LV	WW+WD1+WD2		WW		WD1		WD2	
			R^2_{cv}	$RMSE_{cv}$	R^2_{cv}	$RMSE_{cv}$	R^2_{cv}	$RMSE_{cv}$	R^2_{cv}	$RMSE_{cv}$
LMA	MicroNIR	12	0.78	0.38	0.83	0.40	0.82	0.33	0.58	0.42
LMA	NeoSpectra	3	0.76	0.40	0.84	0.41	0.74	0.40	0.66	0.38
LMA	MicroNIR_ NeoSpectra	4	0.82	0.34	0.88	0.35	0.86	0.30	0.64	0.39
LMA	ASD	8	0.83	0.34	0.84	0.38	0.80	0.36	0.80	0.27
A_n	Li600	10	0.80	1.59	0.74	1.63	0.74	1.57	0.69	1.56
WUE_{intr}	Li600	8	0.48	27.09	0.53	22.71	0.73	17.90	0.02	36.96
WUE_{inst}	Li600	7	0.44	1.53	0.46	1.25	0.74	1.01	0.17	2.11

PLSR models follows a cross-validation procedure using leaves directly measured with conventional

methods to predict Leaf mass per area (LMA), Net CO_2 assimilation (A_n), Intrinsic water use efficiency

(WUE_{intr}) and Instantaneous water use efficiency (WUE_{inst}) on the diversity panel.

LV corresponds to the optimal number of latent variables retained by the model. R^2_{cv} and $RMSE_{cv}$ are

calculated for all water treatment together (102 leaves) and for each water treatment separately (34 leaves):

Well-watered treatment (WW), Moderate water deficit treatment (WD1), Severe water deficit treatment

(WD2).

Fig. 6 Estimation of the heritability of observed and predicted leaf traits under different water treatments.

a Corresponds to the broad-sense heritability estimates for measured and predicted leaf mass per area (LMA) according to the spectrometer used as a predictor; **b** corresponds to the heritability estimates for predicted net CO_2 assimilation (Pred_A_n), predicted instantaneous water use efficiency (Pred_WUE$_{inst}$), predicted intrinsic water use efficiency (Pred_WUE$_{intr}$) and the square-root of the calculated intrinsic water use efficiency (WUE$_{intr\_cal}$); **c** corresponds to the distributions and correlations between genotypic values of measured LMA *versus* genotypic values of predicted LMA according to the spectrometer used as a predictor (MicroNIR_NeoSpectra or ASD). Blue bars represent the well-watered treatment (WW); yellow bars represent the moderate water-deficit treatment (WD1); red bars represent the severe water deficit treatment (WD2). NA indicates that the trait was not predicted (or calculated) under the corresponding water treatment. *** = p-value ≤ 0.001.

Discussion

In this study, we explored the performance of models built with high-throughput devices to predict

ecophysiological and morphological leaf traits across a large genetic diversity panel of *Vitis*

vinifera varieties. Using a combination of large datasets collected on thousands of grapevine

plants across different experiments and conditions, we were able to evaluate the robustness of

predictive models with respect to the experimental conditions. Based on an analytical framework

with dedicated and repeated calibration and validation data sets, we found that the prediction

accuracy within the validation set containing leaves of plants grown under severe water deficit

was generally lower than that for other water treatments. We also found that all devices (NIR

spectrometers or poro-fluorometer) were efficient in predicting at least one trait. Finally, we found

that the leaf traits predicted with NIRS and poro-fluorometry data captured a substantial part of

the genetic variation which paves the way towards their use in genetic studies.

High-throughput devices are complementary to predict a range of morphological and physiological traits

For too small datasets or too complex traits, repeated double cross-validation is more

efficient to obtain an accurate estimation of the prediction error compared to a simple cross-

validation [39]. In our analyses, we performed 100 resampling iterations for each cross-validated

calibration and validation sets for predicting A_n, Ψ, WUE_{intr} and WUE_{inst}. Previous studies most

often only made one iteration for cross-validating PLSR models [25]. In this study, we observed

that model R^2 was highly dependent on the iteration. Consequently, depending on the sampling

for unique datasets of calibration and validation, the models could have been biased.

Spectrometers resulted in better performances than Li600 for the prediction of LMA, WC_f and WQ

while the Li600 was more efficient for the prediction of A_n, WUE_{intr} and WUE_{inst}. The laboratory

spectrometer (ASD) was found as the most accurate to predict LMA. Absorption bands between

1670-1830 nm and 2000-2200 nm, covered by this device, were previously reported as relevant

for predicting leaf dry matter related traits like protein, lignin and cellulose contents [53–56]. The

difference of predictive performance between the laboratory spectrometer and the portable

spectrometers could also be due to the presence/absence of water in the corresponding leaf

samples as spectra from the ASD device were collected on dried leaves while spectra from

MicroNIR and NeoSpectra devices were collected *in situ*. It is known that the presence of water

in samples can dominate the signal, potentially reducing the detection of smaller peaks related to

other components such as nitrogen [33], protein, lignin and cellulose, which could be essential

for predicting LMA. LMA and WC_f were negatively correlated, likely because leaves with a low

LMA tend to have a high water content [57], but we observed that the devices yielding the best

PLSR models for predicting these traits differed. Water-related traits (WC_f and WQ) were better

predicted *in situ* using portable spectrometers while LMA was better predicted *ex situ* using a lab

spectrometer on dried leaves. Moreover, water-related traits were better predicted using the

combined wavelengths of MicroNIR and NeoSpectra than with either device alone. This is likely

because their combined spectral range includes the two main water absorption bands around

1400–1440 nm and 1900–1950 nm [29].

The poro-fluorometer device was found to provide good prediction of A_n. To our

knowledge, this is the first report of A_n prediction using rapid and simultaneous porometry and

fluorescence measurements. This aligns with previous studies showing that A_n correlates with

the fluorescence decline ratio under steady-state conditions with saturated light [58]. Additionally,

A_n was well predicted when combining the electron transport rate, also derived from leaf

fluorescence measurements, with the leaf-to-air temperature difference, used as a proxy for

stomatal closure [14,16,17]. In our study, spectrometers could not accurately predict A_n ,

conversely to other studies on maize [28]. At least 3 spectra from the same side of a leaf were

used in the maize experiment, while in our study, two spectra (one on each side) were taken from

the same spatial area of a given leaf. De Bei et al. [29] reported that decreasing the number of

spectra collected on a given leaf from 6 to 1 decreases the prediction accuracy. However,

increasing the number of spectra increases the phenotyping time which is not suitable for high-

throughput phenotyping.

We found that the Li600 device was able to predict WUE_{intr} and WUE_{inst} for plants under

a moderate water deficit. In contrast, spectral data generally failed to provide reliable predictions,

except for WUE_{inst}, which could be predicted using MicroNIR and the MicroNIR-NeoSpectra

combination under moderate water deficit. With a larger sample size, Cotrozzi et al. [28] reported

fairly good predictive performance of models built with NIRS data by performing 500 randomized

permutations for WUE_{intr} and WUE_{inst} on an external validation set of maize.

The leaf water potential is a physiological trait commonly used as an indicator of soil water

deficit intensity [3,29,59]. In our study, the leaf water potential was poorly predicted, regardless

of the device used. Experiments on maize have shown that the leaf water potential could be

predicted by NIRS with a R^2_{cv} of 0.63 on both greenhouse and field samples [28]. Field

experiments on grapevines have shown the interest of NIRS for the prediction of leaf water

potential on Syrah and Cabernet Sauvignon [29]. However, in these studies, stem water potential

was better predicted than leaf water potential perhaps because spectra, taken at a single spot on

the leaf, are not representative of the spatial variability in stomatal conductance [29,60]. Moreover,

in the case of a slow soil drying, the osmotic adjustment leads to a maintenance in water content

even when leaf water potential decreases [3] which could explain the good predictive ability of

water content compared to leaf water potential.

Recently, the PLSR method was extended to the combination of multiple methods and

sources of high-throughput data using deep learning [61] or multi-block techniques such as SO-

PLS or ROSA [62,63]. The prediction of amylose, starch and cellulose contents, using a SO-PLS

model with NIR and mid-infrared spectra, had a better R^2 and a smaller error compared to the

PLSR models based on a NIR and mid-infrared spectra separately [64]. The prediction of E using

NIRS data was shown to be improved by incorporating climatic data such as radiation,

temperature, relative humidity and wind speed [38]. It has also recently been shown that the

prediction of leaf water potential could be improved by combining leaf spectral reflectance and

leaf orientation parameters [65]. However, in a high-throughput phenotyping approach, some

complementary information such as leaf orientation, might be difficult to phenotype at a large

scale.

The robustness of PLSR models depends on the traits and the plant growing conditions

LMA has been widely used across species and locations to investigate the robustness of

predictive models when plants were subjected to different environmental conditions [26,66]. In

these studies, a considerable decrease in model accuracy was found when a trained PLSR model

was applied to a validation set containing other sites or experiments. Here, we consistently

highlighted a degradation of outdoors prediction using a greenhouse calibration set, similar to

recent reports on maize [28]. By contrast, a previous interspecific study using more than 700

species, reported that the prediction accuracy for LMA could reach a satisfying stable level with

a certain number of sites used in the calibration set [66].

Furthermore, here we aimed at deciphering the effect of the watering conditions on the

PLSR models prediction accuracy. The prediction of ecophysiological traits might indeed be

sensible to soil water availability. While most published studies pooled together data collected in

different growing conditions in their calibration and validation datasets [29,38], here we tested

both the effects of calibrating PLSR models per water treatment, and more importantly of

validating them under different water treatments. Our results highlighted that the composition of

the validation dataset is more influential than the calibration one. Validating PLSR models per

water treatment prevents an artificial inflation of R^2 value caused by the inclusion of multiple water

treatments which in turn increases the trait variance. This likely led to more accurate PLSR model

evaluations which highlighted changes in prediction accuracy for LMA, WC_f, WUE_{intr} and WUE_{inst}

depending on the water treatments. Such variation in R^2 is primarily due to the reduction in trait

variance as underlined by the smaller differences observed for RMSE across water treatments.

Yet, differences in RMSE remained and they could be attributed to a differential implication of

elementary processes across water treatments, some of them being more or less captured by

high-throughput measurements.

669 PLSR models allow capturing the genetic variability of leaf traits

High correlations between predicted and measured values do not necessarily imply an accurate

prediction of genetic variability for the traits, especially when the calibration set includes multiple

experimental conditions. In such cases, the model might have been trained to predict differences

between experimental treatments rather than between plant-related variation within a given

treatment.

Our results demonstrated that the broad sense heritability of predicted LMA was

comparable to that of measured LMA, underlying, at least for this trait, that predicted values were

as efficient as measured values for capturing the genetic variability within each water treatment.

Similar findings were reported for chlorophyll content, nitrogen content and specific leaf area,

predicted using hyperspectral reflectance data in maize grown under low and high nitrogen

conditions [67]. The heritability of predicted A_n, WUE_{intr} and WUE_{inst} was water treatment

dependent with a higher heritability for A_n and WUE_{intr} under moderate water deficit compared to

WUE_{inst} and other water treatments. One reason to explain these results could be that our study

was based on a single leaf per plant even though the choice of the leaf was homogeneous

between plants and chosen as well-exposed and fully expanded. Even so, we could not take into

account the intra-plant variability between well-exposed or shadowed leaves, their age or even

the plant architecture. Increasing the number of measurements is likely to increase trait heritability

[68], but this will also extend the phenotyping time, which may not be appropriate in a high-

throughput phenotyping strategy. To overcome this problem, other methodologies based on

contactless devices could be tested, such as hyper-spectral imaging [69]. Thermal imaging could

also be used to assess leaves and canopy temperature as proxies of water stress responses [70].

Architectural and functional traits have successfully been characterized using LiDAR,

multispectral and thermal imaging in a large core-collection of apple trees [17], highlighting a

strong genotypic effect on all traits, with high broad-sense heritability. A significant effect of the

water treatment was also detected on most of the traits. However, when traits exhibit high spatial

variability at fine scale, the accuracy of phenotyping using imaging sensors is related to the image

resolution. Airborne imaging may also be affected by background noise and atmospheric

scattering, which can alter the light absorption features of pigments [71]. Nevertheless, these

high-throughput methods are highly effective for phenotyping large numbers of plants and multiple

environments in a short time, thus reducing the error associated with the plant circadian cycle.

These phenotyping methods open prospects for further analyses of the genetic determinism of

ecophysiological traits as recently shown in apple trees [72].

Overall our results open promising avenues for further deploying genome-wide

association studies on traits predicted from high-throughput measurements.

704 Conclusion

Our findings demonstrate the strengths of high-throughput devices for predicting ecophysiological

traits not directly accessible at the same throughput in a diversity panel of grapevine under varying

experimental conditions. We have highlighted the importance of validating PLSR models for each

experimental condition and not being restricted to a single calibration/validation set. This

approach can be applied to other abiotic stresses, other populations or even other species. This

would require sharing high-throughput dataset collected on multiple species, growth conditions

and environments to increase predictive models robustness so that they can be applied more

easily to a wide range of study cases. High-throughput phenotyping strategies can be integrated

with imaging-based phenotyping or 3D modeling to improve the assessment of inter-plant

variability and further enhance our understanding of plant responses to environmental stresses

through genetic analyses.

Availability of data and materials

Ethics approval and consent to participate

722 Not applicable

Consent for publication

724 Not applicable

Competing interests

726 The authors declare that they have no competing interests.

Funding

728 This research was supported by the ANR (French Research Agency) through the G²WAS project

729 (ANR-19CE20-0024) and the #Digitag project (ANR-16-CONV-0004). PhenoArch platform is

730 funded by the project ANR-464 11-INBS-0012 (PHENOME-EMPHASIS). This work was publicly

731 funded through the Occitanie Region's program "Défi clé Vinid'Occ" run by the University of
732 Montpellier (PhD grant to EC within the project PlastiVigne).

Authors' contributions

Acknowledgments

We are grateful to the INRAE "Domaine de Vassal" Grape Germplasm Repository for collection
maintenance. We thank Freddy Gavanon and Mélyne Falcon for the plant management and the
preparation of the greenhouse experiment. We thank Gaëlle Rolland for her help in the leaf
phenotyping. We thank Martin Ecarnot and Frederic Compan for the access to the laboratory
spectrometer ASD. We thank the ETAP (LEPSE), M3P (LEPSE) and DAAV (AGAP Institut) team
members for providing help during the preparation and phenotyping of the grapevine panel. We
thank Laurent Torregrosa for administration of ANR G²WAS project and Dominique This and
Roberto Bacilieri for administration of Défi clé Vinid'Occ PlastiVigne.

References

1. Semia Cherif, Doblas-Miranda E, Lionello P, Borrego C, Giorgi F, Iglesias A, et al. First
Mediterranean Assessment Report - Chapter 2: Drivers of Change. Zenodo; 2020 Nov.

2. Van Leeuwen C, Sgubin G, Bois B, Ollat N, Swingedouw D, Zito S, et al. Climate change
impacts and adaptations of wine production. Nat Rev Earth Environ. 2024;5:258–75.

3. Simonneau T, Lebon E, Coupel-Ledru A, Marguerit E, Rossdeutsch L, Ollat N. Adapting plant
material to face water stress in vineyards: which physiological targets for an optimal control of
plant water status? OENO One. 2017;51:167.

4. Damour G, Simonneau T, Cochard H, Urban L. An overview of models of stomatal
conductance at the leaf level: Models of stomatal conductance. Plant, Cell & Environment.
2010;no-no.

5. Bhattacharya A. Effect of Soil Water Deficit on Growth and Development of Plants: A Review.
Soil Water Deficit and Physiological Issues in Plants. Singapore: Springer Singapore; 2021. p.
393–488.

6. Coupel-Ledru A. Plant Water-Use Efficiency. In: John Wiley & Sons, Ltd, editor. eLS. 1st ed.
Wiley; 2021. p. 1–8.

7. Bota BJ, Flexas J, Medrano H. Genetic variability of photosynthesis and water use in Balearic
grapevine cultivars. Annals of Applied Biology. 2001;138:353–61.

8. Tomás M, Medrano H, Escalona JM, Martorell S, Pou A, Ribas-Carbó M, et al. Variability of
water use efficiency in grapevines. Environmental and Experimental Botany. 2014;103:148–57.

9. Prieto JA, Lebon É, Ojeda H. Stomatal behavior of different grapevine cultivars in response to
soil water status and air water vapor pressure deficit. OENO One. 2010;44:9.

10. Coupel-Ledru A, Lebon É, Christophe A, Doligez A, Cabrera-Bosquet L, Péchier P, et al.
Genetic variation in a grapevine progeny (Vitis vinifera L. cvs Grenache×Syrah) reveals
inconsistencies between maintenance of daytime leaf water potential and response of
transpiration rate under drought. Journal of Experimental Botany. 2014;65:6205–18.

11. Trenti M, Lorenzi S, Bianchedi PL, Grossi D, Failla O, Grando MS, et al. Candidate genes
and SNPs associated with stomatal conductance under drought stress in Vitis. BMC Plant Biol.
2021;21:7.

12. Xiao Q, Bai X, Zhang C, He Y. Advanced high-throughput plant phenotyping techniques for
genome-wide association studies: A review. Journal of Advanced Research. 2022;35:215–30.

13. Murchie EH, Lawson T. Chlorophyll fluorescence analysis: a guide to good practice and
understanding some new applications. Journal of Experimental Botany. 2013;64:3983–98.

14. Han J, Chang CY, Gu L, Zhang Y, Meeker EW, Magney TS, et al. The physiological basis
for estimating photosynthesis from Chl *a* fluorescence. New Phytologist. 2022;234:1206–19.

15. Fernández-Calleja M, Monteagudo A, Casas AM, Boutin C, Pin PA, Morales F, et al. Rapid
On-Site Phenotyping via Field Fluorimeter Detects Differences in Photosynthetic Performance in
a Hybrid—Parent Barley Germplasm Set. Sensors. 2020;20:1486.

16. Losciale P, Manfrini L, Morandi B, Pierpaoli E, Zibordi M, Stellacci AM, et al. A multivariate
approach for assessing leaf photo-assimilation performance using the I_{PL} index. Physiologia
Plantarum. 2015;154:609–20.

17. Coupel-Ledru A, Pallas B, Delalande M, Boudon F, Carrié E, Martinez S, et al. Multi-scale
high-throughput phenotyping of apple architectural and functional traits in orchard reveals
genotypic variability under contrasted watering regimes. Hortic Res. 2019;6:52.

18. Foley WJ, McIlwee A, Lawler I, Aragones L, Woolnough AP, Berding N. Ecological
applications of near infrared reflectance spectroscopy - a tool for rapid, cost-effective prediction
of the composition of plant and animal tissues and aspects of animal performance. Oecologia.
1998;116:293–305.

19. Petisco C, García-Criado B, Mediavilla S, Vázquez De Aldana BR, Zabalgogeazcoa I,
García-Ciudad A. Near-infrared reflectance spectroscopy as a fast and non-destructive tool to
predict foliar organic constituents of several woody species. Anal Bioanal Chem.
2006;386:1823–33.

20. Cabrera-Bosquet L, Crossa J, Von Zitzewitz J, Serret MD, Luis Araus J. High-throughput
Phenotyping and Genomic Selection: The Frontiers of Crop Breeding Converge[F]. JIPB.
2012;54:312–20.

21. Wold S, Sjöström M, Eriksson L. PLS-regression: a basic tool of chemometrics.
Chemometrics and Intelligent Laboratory Systems. 2001;58:109–30.

22. Ge Y, Atefi A, Zhang H, Miao C, Ramamurthy RK, Sigmon B, et al. High-throughput analysis
of leaf physiological and chemical traits with VIS–NIR–SWIR spectroscopy: a case study with a
maize diversity panel. Plant Methods. 2019;15:66.

23. De Bei R, Fuentes S, Sullivan W, Edwards EJ, Tyerman S, Cozzolino D. Rapid
measurement of total non-structural carbohydrate concentration in grapevine trunk and leaf
tissues using near infrared spectroscopy. Computers and Electronics in Agriculture.
2017;136:176–83.

24. Ely KS, Burnett AC, Lieberman-Cribbin W, Serbin SP, Rogers A. Spectroscopy can predict
key leaf traits associated with source–sink balance and carbon–nitrogen status. Journal of
Experimental Botany. 2019;70:1789–99.

25. Van Wyngaard E, Blancquaert E, Nieuwoudt H, Aleixandre-Tudo JL. Infrared Spectroscopy
and Chemometric Applications for the Qualitative and Quantitative Investigation of Grapevine
Organs. Front Plant Sci. 2021;12:723247.

26. Serbin SP, Wu J, Ely KS, Kruger EL, Townsend PA, Meng R, et al. From the Arctic to the
tropics: multibiome prediction of leaf mass per area using leaf reflectance. New Phytologist.
2019;224:1557–68.

27. Silva-Perez V, Molero G, Serbin SP, Condon AG, Reynolds MP, Furbank RT, et al.
Hyperspectral reflectance as a tool to measure biochemical and physiological traits in wheat.
Journal of Experimental Botany. 2018;69:483–96.

28. Cotrozzi L, Peron R, Tuinstra MR, Mickelbart MV, Couture JJ. Spectral Phenotyping of
Physiological and Anatomical Leaf Traits Related with Maize Water Status. Plant Physiol.
2020;184:1363–77.

29. De Bei R, Cozzolino D, Sullivan W, Cynkar W, Fuentes S, Dambergs R, et al. Non-
destructive measurement of grapevine water potential using near infrared spectroscopy:
Measure of grapevine water potential using NIR. Australian Journal of Grape and Wine
Research. 2011;17:62–71.

30. Rapaport T, Hochberg U, Shoshany M, Karnieli A, Rachmilevitch S. Combining leaf
physiology, hyperspectral imaging and partial least squares-regression (PLS-R) for grapevine
water status assessment. ISPRS Journal of Photogrammetry and Remote Sensing.
2015;109:88–97.

31. Workman Jr. J, Weyer L. Practical Guide and Spectral Atlas for Interpretive Near-Infrared
Spectroscopy. 0 ed. CRC Press; 2012.

32. Das B, Sahoo RN, Pargal S, Krishna G, Verma R, Viswanathan C, et al. Evaluation of
different water absorption bands, indices and multivariate models for water-deficit stress
monitoring in rice using visible-near infrared spectroscopy. Spectrochimica Acta Part A:
Molecular and Biomolecular Spectroscopy. 2021;247:119104.

33. Masemola C, Cho MA. Estimating leaf nitrogen concentration from similarities in fresh and
dry leaf spectral bands using a model population analysis framework. International Journal of
Remote Sensing. 2019;40:6841–60.

34. Ramoelo A, Skidmore AK, Schlerf M, Mathieu R, Heitkönig IMA. Water-removed spectra
increase the retrieval accuracy when estimating savanna grass nitrogen and phosphorus
concentrations. ISPRS Journal of Photogrammetry and Remote Sensing. 2011;66:408–17.

35. Roger J-M, Chauchard F, Bellon-Maurel V. EPO–PLS external parameter orthogonalisation
of PLS application to temperature-independent measurement of sugar content of intact fruits.
Chemometrics and Intelligent Laboratory Systems. 2003;66:191–204.

36. Zhu C, Fu X, Zhang J, Qin K, Wu C. Review of portable near infrared spectrometers:
Current status and new techniques. Journal of Near Infrared Spectroscopy. 2022;30:51–66.

37. Barthès BG, Kouakoua E, Clairotte M, Lallemand J, Chapuis-Lardy L, Rabenarivo M, et al.
Performance comparison between a miniaturized and a conventional near infrared reflectance
(NIR) spectrometer for characterizing soil carbon and nitrogen. Geoderma. 2019;338:422–9.

38. Ryckewaert M, Héran D, Simonneau T, Abdelghafour F, Boulord R, Saurin N, et al.
Physiological variable predictions using VIS–NIR spectroscopy for water stress detection on
grapevine: Interest in combining climate data using multiblock method. Computers and
Electronics in Agriculture. 2022;197:106973.

39. Filzmoser P, Liebmann B, Varmuza K. Repeated double cross validation. Journal of
Chemometrics. 2009;23:160–71.

40. Nicolas SD, Péros J-P, Lacombe T, Launay A, Le Paslier M-C, Bérard A, et al. Genetic
diversity, linkage disequilibrium and power of a large grapevine (Vitis vinifera L) diversity panel
newly designed for association studies. BMC Plant Biol. 2016;16:74.

41. Coupel-Ledru A, Westgeest AJ, Albasha R, Millan M, Pallas B, Doligez A, et al. Clusters of
grapevine genes for a burning world. New Phytologist. 2024;nph.19540.

42. Cabrera-Bosquet L, Fournier C, Brichet N, Welcker C, Suard B, Tardieu F. High-throughput
estimation of incident light, light interception and radiation-use efficiency of thousands of plants
in a phenotyping platform. New Phytologist. 2016;212:269–81.

43. R Core Team. R: A Language and Environment for Statistical Computing [Internet]. Vienna,
Austria: R Foundation for Statistical Computing; 2023. Available from: https://www.R-project.org/

44. Brandolini-Bunlon M, Jaillais B, Roger J-M, Lesnoff M. rchemo: Dimension Reduction,
Regression and Discrimination for Chemometrics [Internet]. 2023 [cited 2024 Oct 9]. p. 0.1-3.
Available from: https://CRAN.R-project.org/package=rchemo

45. Ecarnot M, Compan F, Roumet P. Assessing leaf nitrogen content and leaf mass per unit
area of wheat in the field throughout plant cycle with a portable spectrometer. Field Crops
Research. 2013;140:44–50.

46. Barnes RJ, Dhanoa MS, Lister SJ. Standard Normal Variate Transformation and De-
Trending of Near-Infrared Diffuse Reflectance Spectra. Appl Spectrosc. 1989;43:772–7.

47. signal developers. signal: Signal processing [Internet]. 2023. Available from: https://r-forge.r-
project.org/projects/signal/

48. Savitzky Abraham, Golay MJE. Smoothing and Differentiation of Data by Simplified Least
Squares Procedures. Anal Chem. 1964;36:1627–39.

49. Liland KH, Mevik B-H, Wehrens R. pls: Partial Least Squares and Principal Component
Regression. 1999. p. 2.8-5.

50. Wong T-T. Performance evaluation of classification algorithms by k-fold and leave-one-out
cross validation. Pattern Recognition. 2015;48:2839–46.

51. Bates D, Mächler M, Bolker B, Walker S. Fitting Linear Mixed-Effects Models Using **lme4**. J
Stat Soft. 2015;67.

52. Flutre T, Chabrault. timflutre/rutilstimflutre: v0.170.0 [Internet]. Zenodo; 2019. Available
from: https://zenodo.org/record/3580267

53. Curran PJ. Remote sensing of foliar chemistry. Remote Sensing of Environment.
1989;30:271–8.

54. Kokaly RF. Investigating a Physical Basis for Spectroscopic Estimates of Leaf Nitrogen
Concentration. Remote Sensing of Environment. 2001;75:153–61.

55. Kawamura K, Watanabe N, Sakanoue S, Inoue Y. Estimating forage biomass and quality in
a mixed sown pasture based on partial least squares regression with waveband selection.
Grassland Science. 2008;54:131–45.

56. Cheng T, Rivard B, Sánchez-Azofeifa A. Spectroscopic determination of leaf water content
using continuous wavelet analysis. Remote Sensing of Environment. 2011;115:659–70.

57. Poorter H, Niinemets Ü, Poorter L, Wright IJ, Villar R. Causes and consequences of
variation in leaf mass per area (LMA): a meta-analysis. New Phytologist. 2009;182:565–88.

58. Lichtenthaler HK, Buschmann C, Knapp M. How to correctly determine the different
chlorophyll fluorescence parameters and the chlorophyll fluorescence decrease ratio R_{Fd} of
leaves with the PAM fluorometer. Photosynt. 2005;43:379–93.

59. Girona J, Mata M, Del Campo J, Arbonés A, Bartra E, Marsal J. The use of midday leaf
water potential for scheduling deficit irrigation in vineyards. Irrig Sci. 2006;24:115–27.

60. Albasha R, Fournier C, Pradal C, Chelle M, Prieto JA, Louarn G, et al. HydroShoot: a
functional-structural plant model for simulating hydraulic structure, gas and energy exchange
dynamics of complex plant canopies under water deficit—application to grapevine (*Vitis
vinifera*). in silico Plants. 2019;1:diz007.

61. Vaillant A, Beurier G, Cornet D, Rouan L, Vile D, Violle C, et al. NIRSpredict: a platform for
predicting plant traits from near infra-red spectroscopy. BMC Plant Biol. 2024;24:1100.

62. Naes T, Tomic O, Mevik B-H, Martens H. Path modelling by sequential PLS regression. J
Chemometrics. 2011;25:28–40.

63. Liland KH, Næs T, Indahl UG. ROSA—a fast extension of partial least squares regression
for multiblock data analysis. Journal of Chemometrics. 2016;30:651–62.

64. Kandpal LM, Mouazen AM, Masithoh RE, Mishra P, Lohumi S, Cho B-K, et al. Sequential
data-fusion of near-infrared and mid-infrared spectroscopy data for improved prediction of
quality traits in tuber flours. Infrared Physics & Technology. 2022;127:104371.

65. Kang C, Diverres G, Karkee M, Zhang Q, Keller M. Assessing grapevine water status
through fusion of hyperspectral imaging and 3D point clouds. Computers and Electronics in
Agriculture. 2024;226:109488.

66. Ji F, Li F, Hao D, Shiklomanov AN, Yang X, Townsend PA, et al. Unveiling the transferability
of PLSR models for leaf trait estimation: lessons from a comprehensive analysis with a novel
global dataset. New Phytologist. 2024;243:111–31.

67. Grzybowski M, Wijewardane NK, Atefi A, Ge Y, Schnable JC. Hyperspectral reflectance-
based phenotyping for quantitative genetics in crops: Progress and challenges. Plant
Communications. 2021;2:100209.

68. Jablonszky M, Garamszegi LZ. The effect of repeated measurements and within-individual
variance on the estimation of heritability: a simulation study. Behav Ecol Sociobiol. 2024;78:18.

69. Zhang H, Wang L, Jin X, Bian L, Ge Y. High-throughput phenotyping of plant leaf
morphological, physiological, and biochemical traits on multiple scales using optical sensing.
The Crop Journal. 2023;11:1303–18.

70. Wen T, Li J-H, Wang Q, Gao Y-Y, Hao G-F, Song B-A. Thermal imaging: The digital eye
facilitates high-throughput phenotyping traits of plant growth and stress responses. Science of
The Total Environment. 2023;899:165626.

71. Tattaris M, Reynolds MP, Chapman SC. A Direct Comparison of Remote Sensing
Approaches for High-Throughput Phenotyping in Plant Breeding. Front Plant Sci. 2016;7.

72. Coupel-Ledru A, Pallas B, Delalande M, Segura V, Guitton B, Muranty H, et al. Tree
architecture, light interception and water-use related traits are controlled by different genomic
regions in an apple tree core collection. New Phytologist. 2022;234:209–26.