# Large language models possess some ecological knowledge, but how much?

Filip Dorm[a,b], Joseph Millard[c], Drew Purves[d], Michael Harfoot[e], Oisin Mac Aodha[b]

[a]*School of Architecture, Civil and Environmental Engineering (ENAC), École Polytechnique Fédérale de Lausanne (EPFL), Switzerland*
[b]*School of Informatics, University of Edinburgh, United Kingdom*
[c]*Department of Zoology, University of Cambridge, United Kingdom*
[d]*Google DeepMind, United Kingdom*
[e]*Vizzuality, United Kingdom*

## Abstract

Large Language Models (LLMs) have shown remarkable capabilities in question answering across various domains, yet their effectiveness in ecological knowledge remains underexplored. Understanding their potential for ecological reasoning is crucial as AI tools become increasingly integrated into scientific workflows. Here, we assess the ecological knowledge of two LLMs, `Gemini 1.5 Pro` and `GPT-4o`, across a suite of ecologically focused tasks. These tasks evaluate an LLM's ability to predict species presence, generate range maps, list critically endangered species, classify threats, and estimate species traits. We introduce a new benchmark dataset to quantify LLM performance against expert-derived data. While the LLMs tested outperform naive baselines, achieving around 20 percentage points higher accuracy in species presence prediction, they reach only a third of the mean F1 score for range map generation and improve threat classification by just around 10 points over random guessing. These results highlight both the promise and challenges of applying LLMs in ecology. Our findings suggest that domain-specific fine-tuning is necessary to improve ecological reasoning in LLMs. By providing a repeatable evaluation framework, our benchmark dataset will facilitate future research in this area, helping to refine AI applications for ecological science.

*Keywords:* Benchmark, Ecological Question Answering, Evaluation, LLMs, Reasoning

## 1. Introduction

The biodiversity crisis is one of the defining challenges of our time, making data collation on biodiversity change increasingly important. With species loss accelerating at an unprecedented rate [1], ecologists are urgently working to address persistent gaps in our understanding of global biodiversity patterns [2]. Traditionally, biodiversity research has relied on manual curation and fragmented datasets, limiting both coverage and scalability. These persistent knowledge gaps and methodological limitations have prompted growing interest in new approaches to biodiversity data collection and analysis. In particular, recent efforts have focused on automating information extraction from the scientific literature, using tools like text mining to overcome the challenges of manual synthesis [3, 4].

Large Language Models (LLMs) have recently emerged as a powerful technology, demonstrating strong performance across a wide range of tasks, including coding, mathematics, and language understanding [5, 6, 7, 8]. These models, trained on massive corpora using significant computational resources, follow scaling laws that place the development of high-performing LLMs far beyond the reach of most ecological researchers. As a result, researchers in ecology are likely to turn to general-purpose, off-the-shelf models to support a wide range of tasks involving information extraction and synthesis. Despite growing enthusiasm, the baseline capabilities of LLMs in ecology use cases remain largely untested. While benchmarking studies have evaluated model performance in several fields [9], there has yet to be a systematic assessment of how these models perform on ecological knowledge and reasoning tasks.

One related domain where interest in LLM applications has grown rapidly is geospatial analysis [10, 11, 12, 13, 14, 15]. Particularly relevant to ecological applications is GPT4GEO [16], which includes evaluation tasks such as estimating the spatial distribution of species and bird migratory routes. In these spatial assessments, models tend to perform better when locations are described using place names, likely due to the alignment with the textual format of their training data [14]. More broadly, previous work has bridged geospatial analysis and ecology, with a focus on text retrieval for modeling the distribution of species [17, 18, 19]. These developments underscore growing interest in ecological applications of LLMs, not only for spatial reasoning, but increasingly for tasks like retrieving and synthesizing ecological evidence.

Ecological applications of LLMs are new, but developing quickly, particularly in retrieving and synthesizing text and data. Previous research demonstrates LLMs' ability to assist with tasks in ecology such as extracting information from scientific literature and coding [20, 21, 22, 23, 24, 25, 26]. To address challenges related to erroneous outputs, [27] explored methods for estimating uncertainty in LLM-generated results, helping to mitigate risks in ecological applications. LLMs have also shown promise in debunking sensational wildlife news stories [28] and assessing invasive species distributions based on news reports [29].

Here, we present a suite of species-centric evaluation tasks to assess LLMs' factual knowledge and reasoning across multiple areas of ecology. To test the baseline knowledge of state-of-the-art commercial LLMs, we evaluate two models, GPT-4o from OpenAI [30] and Gemini 1.5 Pro from Google [31], through a series of five experiments. These experiments assess the LLMs' ecological knowledge by quantifying their performance for predicting species presence (Section 2.3.1), range maps (Section 2.3.2), listing threatened species (Section 2.3.3), threats (Section 2.3.4), and traits (Section 2.3.5). This approach allows us to evaluate the factual accuracy and reasoning capabilities of LLMs in ecology in a repeatable manner, helping determine when their use is appropriate and where further adaptation may be needed.

Previous evaluation of LLMs for predicting trait-related quantities focuses primarily on extracting information from provided datasets and text [32, 33]. Trait estimation has also been explored using Vision-Language Models (VLMs), which enable reasoning over both images and text [34]. In contrast, we demonstrate that LLMs can estimate traits, without relying on additional data. For example, while previous research like [35] specializes in taxonomic entity recognition, our findings reveal that LLMs can perform similar tasks directly, eliminating the need for supplementary datasets.

## 2. Material and Methods

### 2.1. Models

Our experiments consist of querying two commercial LLMs, Gemini 1.5 Pro and GPT-4o, through their publicly accessible APIs. We select these two models as they are representative of the best commercial LLMs currently available. Both models are used in the period between August and October 2024. For both models, the temperature, a hyperparameter that controls

Figure 1: **Evaluation Overview.** We evaluate existing large language models (LLMs) on a set of five ecological question answering tasks. The tasks require the LLMs to answer questions related to identifying what species are present at a specified location, mapping their ranges, listing threatened species, assessing specific threat levels, and estimating species' traits.

the randomness of a model, is set to zero to ensure deterministic outputs, thereby enhancing the reproducibility of the results. However, the results may still vary when there are changes or updates to the underlying models themselves. We use following versions of the models: `gemini-1.5-pro-001` and `gpt-4o-2024-05-13`. Importantly, neither `Gemini 1.5 Pro` nor `GPT-4o` retains conversation history when utilizing their APIs [36, 37], which is advantageous for our purposes, as we do not want the model to learn from previous queries.

### 2.2. Datasets

**Spatial Distribution Data**. The species presence and range map tasks are based on expert-derived range maps of 2,418 species from the International Union for Conservation of Nature (IUCN) Red List [38]. This is the same filtered dataset used in existing work for evaluating species distribution models [39, 40]. In this dataset, species ranges are represented as hexagons of size 250 km$^2$, based on a H3 hexagon raster [41], each marked to indicate whether the species is present or absent.

**Threat Data.** For the threat classification task, we query the IUCN's API [42] to extract the Red List status of species, countries they reside in, and threats they face.

**Trait Data.** For tasks related to predicting numerical traits for species, we utilize two primary data sources. For bird traits, we use AVONET [43], and for mammals, we use COMBINE [44]. Both datasets encompass a wide range of species and contain average measurements of morphological traits.

## 2.3. Evaluation Tasks

We design a set of five evaluation tasks to test the ecological information recall of LLMs (Figure 1). These diverse tasks allow us to test an LLM's knowledge of the geographical distribution of species, their ability to assess threats, and understand species' size and morphology.

### 2.3.1. Task 1: Species Presence

```
                        Task 1 Prompt
Can you tell me if the <common_name> (<scientific_name>) can be found at the
following locations:<[Location 1, ... Location 10]>. Please respond with a score
for each location between 0 and 1, where 1 indicates that you think the species
is very likely to be present there. Provide your answer as a Python list
containing only the likelihood scores.
```

Figure 2: **Prompt template for Task 1: Species Presence**.

Here we focus on identifying species presence or absence across ten specific locations, aiming to evaluate LLMs' understanding of species' geographical distributions. We select 100 species using a stratified random sampling approach to ensure equal representation across four taxonomic groups: 25 amphibians, 25 reptiles, 25 mammals, and 25 birds. The full list of selected species is available at https://github.com/filipgdorm/eco-llm/blob/main/SPECIES.md.

Each species is paired with ten geographic locations: five where the species is present and five where it is absent. These locations are sampled from IUCN expert-derived range maps. Locations are defined using the centroid coordinates of equal-area hexagonal grid cells, each covering approximately 253 km².

To test the impact of spatial proximity on model performance, two of the five absence locations are intentionally selected to be geographically close to the species' known range. These difficult absences are drawn from smaller grid cells (253 km²) that fall within larger regional cells of about 12,393 km², which neighbor but do not overlap the known range. This approach ensures that the absence points are near the range boundary while remaining outside it.

We repeated the experiment using country names instead of geographic coordinates (Task 1b). Here, "presences" are defined as countries where the species is known to occur, and "absences" are countries where the species

does not occur. The number of presence countries for each species varies, from a minimum of one (for species that inhabit only a single country) to a maximum of five. Absence countries are chosen from neighboring countries where the species is not found. If there are not enough neighboring countries to provide ten absences, random countries are selected as absences. The same prompt structure is used, but instead of specific locations, the countries are listed (see prompt in Figure 2).

A response is deemed valid if it contains identifiable opening and closing brackets of a Python list, with the content in between being loadable without errors. Evaluation metrics are computed from the valid and parseable responses. As baselines, we include randomly guessing probabilities (i.e., selecting a random number between 0 and 1), always predicting presence (i.e., 1), and always predicting absence (i.e., 0).

To test whether LLM performance on species presence prediction is influenced by model type, taxonomic group, or continent of occurrence, we fit two linear regressions with accuracy as the dependent variable, and LLM type, taxonomic group, and continent presence indicators as predictors. We did this for both Tasks 1a and 1b i.e., coordinates and countries. The continent variables are a set of five binary indicators, each representing whether the species occurs or not in Africa, the Americas, Asia, Europe, or Oceania. Species can occur on multiple continents simultaneously, so these are not mutually exclusive categories. Categorical variables are encoded using treatment coding, with GPT as the reference level for LLM type and Amphibia as the reference level for group name. The models are fit using ordinary least squares regression with the `ols` function using the `statsmodels` Python package [45], and the diagnostic tests are presented in Table C.5 and Table C.6.

### 2.3.2. Task 2: Range Maps

---
**Task 2 Prompt**

My goal is to create a GEOJSON describing the geographical distribution of the *<common_name>* (*<scientific_name>*). I am looking for a correctly formatted, parsable GEOJSON file. Please provide a complete GEOJSON that I can then render and nothing else.

---

Figure 3: **Prompt template for Task 2: Range Maps**.

Here we ask the LLMs to generate range maps for the same 100 species as

in Task 1. Assessing LLMs' geographic awareness through their range map accuracy provides insights into their ability to handle ecological spatial data.

We ask the model to return a GEOJSON string (Figure 3), as this format has a plain text, nested structure that can be easily parsed and converted into a plottable dataframe for visualization. The F1 score, measuring how well the GEOJSON-generated range maps match the expert-derived range maps, is computed from this comparison. The F1 score measures how well a model balances precision (the proportion of correctly predicted presences among all predicted presences) and recall (the proportion of correctly predicted presences among all actual presences). Refer to the Appendix B for more details on the F1 score evaluation metric. The GEOJSON is extracted by locating the curly braces {} in the response. The enclosed string is then parsed as a GEOJSON object through Python's JSON parsing library.

In addition, we also compare our results to a recent deep learning-based species distribution model, SINR [39]. SINR (Spatial Implicit Neural Representations) is a deep learning-based model designed to estimate the distribution of a species from sparse presence-only observations, leveraging large-scale crowdsourced observation data during training. We utilize a coordinate-only version of the SINR model with the $\mathcal{L}_{\text{AN-full}}$ loss function, capped at 1,000 training samples per species and without incorporating any environmental covariates. Predictions are made using either a fixed threshold of 0.1 or a threshold estimated through the LPT-R (Lowest Presence Threshold - Robust) approach as outlined in [40]. The LPT-R method identifies optimal thresholds for binarizing species distribution predictions using only presence data, improving robustness to outliers and offering more accurate range map binarization when only species presence data are available. The mean F1 scores of the range maps produced by SINR and the two binarization methods are also computed, making them directly comparable to the LLMs.

The influence of model type, taxonomic group, or continent of occurrence on the F1 score is assessed through linear regression. As in Task 1, the predictors used are LLM type (with levels GPT and Gemini), group name (with levels Amphibia, Aves, Mammalia, and Reptilia), and continent indicators (Africa, the Americas, Asia, Europe, and Oceania). The dependent variable in this case is the F1 score of the range map. The models are fit using ordinary least squares regression with the `ols` function from the `statsmodels` Python package, and the diagnostic tests are presented in Table C.7.

### 2.3.3. Task 3: List Threatened Species in a Region

```
                              Task 3 Prompt
List the birds that are classified as Critically Endangered on the IUCN Red List
and are found in <country>.

Instructions:
- Provide the species names using their common names only.
- Format your response as a Python list, like this: [Species name 1, Species name
2, ...].
- Ensure that there are no duplicate species names in your list.
```

Figure 4: **Prompt template for Task 3: Threatened Species**.

Here we evaluate the LLMs' ability to comprehensively list species that meet specific conservation criteria, specifically focusing on species assessed as critically endangered (CR) by the IUCN within a given geographic region (Figure 4). We focused on critically endangered species, since this allows us to quantify the LLMs' effectiveness as a tool for researchers and conservationists in identifying species that may be at risk in a given area. The experiment is intentionally designed to incorporate a geographic element to test how well the two LLMs can synthesize information across domains of ecological knowledge (species, threat status, and location). This approach aligns with real-world conservation use cases, where the geographic scope in assessing conservation status is often constrained to specific regions, such as evaluating the conservation status of species within protected areas, national parks, or even entire countries. The CR category includes species that the IUCN has assessed as having a very high risk of extinction and is limited to those formally assessed, excluding species that may also be at risk but have not yet undergone evaluation. We choose to limit the task to a specific threat class and to bird species to ensure that the LLMs can generate a complete and well-formatted response, as longer answers tend to lose coherence or are truncated.

The task is grounded in political boundaries, meaning that species are assigned to countries based on jurisdictional classifications in the underlying dataset. For instance, both Congo and Lithuania report no critically endangered bird species according to IUCN records, while regions such as Greenland may appear to have no species at all, likely due to their inclusion under Denmark's jurisdiction. Indonesia has the highest number of CR birds with 30 unique species in that class. Countries without available species data

or those not recognized as independent entities by our plotting tool are shown in gray in Figure 9 and are excluded from the summary statistics in Table 3.

### *2.3.4.* Task 4: Threat Assessment

```
                            Task 4 Prompt
Complete the threat assessment by making assessments for scope and severity for
the <common_name> (<scientific_name>).

Here are the scoring instructions from the IUCN: <scope_severity_instructions>

The threat description from IUCN is
<threats_description>.
Specifically, focus on the threat identified as <code> <title>. Additional details
about the threat code: \n{threat_code_description}

Scope options are:
- Whole (>90%)
- Majority (50-90%)
- Minority (<50%)

Severity options are:
- Very Rapid Declines
- Rapid Declines
- Slow, Significant Declines
- Causing/Could cause fluctuations
- Negligible declines
- No decline

Provide your answer as a flat Python list, containing only two elements like this:
[scope option, severity option]. Do not provide any additional context or
information.
```

Figure 5: **Prompt template for Task 4: Threat Assessment**.

Here, we evaluate the LLMs' ability to perform threat assessments, specifically to reason about the scope and severity of threats faced by species. Using species with known threat classifications, we assess whether the model can replicate these labels when given a textual description of the threat.

Biodiversity is undergoing rapid change due to multiple interacting threats. Understanding the magnitude and extent of these threats is essential for effective conservation and mitigation efforts. The IUCN Red List provides a standardized framework for assessing such threats, including structured classifications that indicate their "scope" (the proportion of the population affected) and "severity" (the expected rate of population decline). While threat descriptions are often available for assessed species, explicit scope and severity classifications are frequently omitted.

Scope refers to the proportion of the population affected by a given threat. In the IUCN Red List API, scope is represented using categorical labels corresponding to the percentage ranges "Whole (>90%)", "Majority (50-90%)", and "Minority (<50%)" [46]. Severity is concerned with the acuteness of the threat, or the overall declines caused by it, and can take on the categories "Very Rapid Declines", "Rapid Declines", "Slow, Significant Declines", "Causing/Could Cause Fluctuations", "Negligible Declines", or "No Decline" [46].

The species selected for this evaluation collectively span all combinations of severity and scope categories defined by the IUCN, resulting in 100 unique severity–scope pairs. To assess a models' ability to reason about these categories, we present them with threat classes used by the IUCN (e.g., hunting, threat code 5.1.1) along with species names and ask them to predict the corresponding scope and severity classifications. We select the threat-species pairs independently of species names, meaning a single species may appear multiple times, each instance associated with a different threat with associated severity and scope classification.

For each species, we provide a description of the threat in the prompt, along with an explanation of the associated threat code, including its definitions and examples when available (Figure 5). Additionally, descriptions of what severity and scope entail are also included. The threat code descriptions are sourced from the IUCN Threat Classification documentation [47].

We implement a cost-sensitive performance metric where we account for the severity of misclassifications by awarding partial credit when predicted labels are close to the true labels. For example, predicting "Majority (50–90%)" instead of "Whole (>90%)" in scope classification is considered a smaller error than predicting "Minority (<50%)." We also define a scoring scheme for both scope and severity tasks. For scope, labels ("Minority," "Majority," and "Whole") are mapped to scores (1, 2, and 3). Exact matches score 1.0; adjacent categories score 0.5; distant categories score 0. For severity, six categories are ordered from "No Decline" (1) to "Very Rapid Declines" (6). Matches score 1.0; near matches score 0.75; intermediate 0.5; distant 0.25; and opposites 0.

*2.3.5.* **Task 5: Trait Identification**

```
Task 5 Prompt

Could you please provide an estimate of the <trait> (measured in <unit>) for the
species <common_name> (<scientific_name>)? Output your numerical estimate and
nothing else.
```

Figure 6: **Prompt template for Task 5: Trait Identification**.

Here we assess LLMs' knowledge of traits of different species (Figure 6). We use the AVONET bird [43] and COMBINE mammal [44] trait datasets. From AVONET, we extract the beak, wing, tail length, and mass for 100 randomly sampled bird species. From COMBINE, we select the adult body length, gestation length, max longevity, and adult mass for 100 randomly sampled mammal species. Neither of the datasets make any distinction between females and males for the traits used, which has an impact on the expected values for some traits. However, given that most species in the sample do not exhibit significant sexual dimorphism, this is not expected to significantly affect the predictive ability of the model.

We ask the models for a numeric answer and specify what unit we want the estimate in, which can both be found in the AVONET and COMBINE datasets (Figure 6). We ask the models to only provide the number, but are lenient to responses that include the unit, e.g., "50 mm". Wherever units are included in the response, we extract only the numeric substring.

## 3. Results

*3.1.* **Task 1: Species Presence**

Both `GPT-4o` and `Gemini 1.5 Pro` outperform the random baseline in the presence-absence predictions, particularly when locations are provided as countries rather than precise coordinates (Table 1). While `GPT-4o` shows slightly higher mean accuracy (Table 1, Figure 7), the difference between models is modest. Notably, `Gemini 1.5 Pro` generates more invalid outputs, often due to unparseable formats or because the model refuses to provide an estimate accompanied by a disclaimer. Both models exhibit large standard deviations for their reported accuracies.

Figure 7: **Species Presence**. Visualization of selected species spanning all taxonomic groups and IUCN threat categories. Circles show presence locations, crosses show nearby challenging absences. Color indicates predicted presence probability, green is high and close to 1, red is low and close to 0. Dark gray indicates the IUCN range map. A perfect model predicts green for circles and red for crosses.

Table 1: **Species Presence**. We present mean accuracy (with scores binarized at 0.5) and mean average precision (MAP) for 100 species, along with the count of unparseable model responses.

| Method | Task 1a - Locations | | Task 1b - Countries | |
| --- | --- | --- | --- | --- |
| | Mean Acc. | #Invalid R. | Mean Acc. | #Invalid R. |
| `Gemini 1.5 Pro` | $70.8 \pm 15.7\%$ | 14 | $84.9 \pm 16.1\%$ | 2 |
| `GPT-4o` | $\mathbf{78.0}\pm 11.9\%$ | 0 | $\mathbf{87.6}\pm 13.7\%$ | 1 |
| Random Baseline | $51.6 \pm 14.7\%$ | - | $51.3 \pm 12.3\%$ | - |
| Always Absent Baseline | $50.0 \pm 0.0\%$ | - | $68.3 \pm 16.8\%$ | - |
| Always Present Baseline | $50.0 \pm 0.0\%$ | - | $31.7 \pm 16.8\%$ | - |

When locations are provided as countries (Task 1b), species from Africa ($p < 0.001$), Asia ($p = 0.003$), and Europe ($p < 0.001$) exhibit substantially lower predicted accuracies than those from Oceania or the Americas (Figure C.11, Table C.6). These geographic patterns are absent in Task 1a, where only Europe ($p = 0.028$) showed a significant difference and accuracy does not deviate meaningfully across other continents (Figure C.11, Table C.5). Accuracy differences across taxonomic groups were minimal in both tasks, with no consistent trend. Model predictions did not vary by LLM type, consistent with the non-significant coefficients in our regression results.

*3.2.* **Task 2: Range Maps**

While both `GPT-4o` and `Gemini 1.5 Pro` can generate species range maps that overlap with expert-defined ranges, their outputs do not yet match the accuracy of deep learning-based species distribution models (SDMs) (Table 2). For 77 out of 100 species (`GPT-4o`) and 68 out of 100 species (`Gemini 1.5 Pro`), the predicted ranges intersect the expert-defined ranges, indicating that the models are focusing on the correct geographic regions. `Gemini 1.5 Pro` achieves a higher mean F1 score (24.7% vs. 20.9% for `GPT-4o`) (Table 2), but it also produces more invalid range maps (26 vs. 15). Both models exhibit high variability across species, with standard deviations above 20%.

Qualitative inspection reveals important differences, e.g., `Gemini 1.5 Pro` tends to generate range maps at a finer spatial resolution, while `GPT-4o` often returns coarse, square-like predictions. Among the ten example species shown in Figure 8, only `Gemini 1.5 Pro` achieves F1 scores above 60% for three species (Eastern Grey Kangaroo, Alpine Newt, and Wood Thrush), while `GPT-4o` reaches this level for only one (Eastern Grey Kangaroo). However, even these best cases still exhibit low spatial resolution. A typical

Table 2: **Range Maps**. Here we report the mean F1 score of the range maps generated by different LLMs compared with the expert-derived maps. In addition, we also compare to a recent deep learning-based species distribution model SINR [39] (specifically using a coordinate only SINR model with the $\mathcal{L}_{\text{AN-full}}$ loss, capped at 1000 training samples per species and without environmental covariates) using either a fixed threshold of 0.1 or a threshold estimated using the LPT-R approach from [40].

| Method | Mean F1 Score | # Invalid R. |
|---|---|---|
| Gemini 1.5 Pro | $24.7 \pm 22.1\%$ | 26 |
| GPT-4o | $20.9 \pm 21.9\%$ | 15 |
| SINR (threshold 0.1) | $54.9 \pm 22.8\%$ | - |
| SINR (threshold LPT-R) | $\mathbf{60.7 \pm 17.9\%}$ | - |

failure mode for both models involves generating excessively long lists of co-ordinates that exceed response limits or become incoherent, as seen in the Snow Leopard example (Figure 8), where GPT-4o fails to generate a range map.

Attempts to prompt the models for higher-resolution maps by requesting approximately 50 border coordinates lead to lower accuracy and more parsing errors, such as missing commas and malformed coordinates. In contrast, asking for outputs in GeoJSON format results in more consistent and well-structured predictions.

Species in the group *Aves* exhibit higher predicted mean F1 scores than other groups ($p = 0.024$). While species occurring in Asia and Africa show a lower mean F1 in Figure C.12, these differences are not statistically significant after accounting for other factors in the regression model ($p = 0.438$) and ($p = 0.513$) respectively (Table C.7)). Similarly, no significant difference in performance is observed between GPT-4o and Gemini 1.5 Pro ($p = 0.941$).

Figure 8: **Task 2: Range Maps**. Here we display range maps for a subset of species generated by `Gemini 1.5 Pro` (red) and `GPT-4o` (blue) as well as the expert-derived range maps from IUCN (dark gray) we use for evaluation.

### *3.3.* **Task 3: List Threatened Species in Region**

Both models exhibit low mean precision, recall and F1 with high standard deviations, indicating they miss a significant number of species and that the performance varies a lot between countries (Table 3). This difficulty stems from the models' limitations when handling longer responses. In our case, the average response length is 2.3 species, with a maximum of 19 species identified across all countries. In countries like Indonesia, where up to 30 species need to be listed, this poses a particular challenge for both LLMs.

The models demonstrate high recall and F1 scores in several countries with few critically endangered (CR) species (Figure 9). Accurately predicting just a few CR species in these nations leads to high scores. Many countries in southern Africa fall into this category. However, this performance is not uniformly high across all countries with low CR species counts and in many cases, such as Europe, F1 and recall are low. This inconsistency may arise because, when there are only a small number of correct species to predict, the model must be highly precise, making it challenging to generate outputs that align closely with the "ground truth". The models are able to achieve high

Figure 9: **Task 3: Threatened Species**. (Lower left) The number of critically endangered (CR) bird species across different countries, with darker red shades representing higher numbers. Grey indicates regions where data is unavailable. (Middle) The recall and F1 of `Gemini 1.5 Pro` when asked to list CR birds in different countries, with darker blue and purple shades representing higher recall and F1 respectively. (Right) The recall and F1 of `GPT-4o`.

Table 3: **Threatened Species**. The mean precision, recall, and F1 computed across countries for `Gemini 1.5 Pro` and `GPT-4o`. Geographic regions and countries without any known CR birds are not included in these scores.

| Model | Mean Precision | Mean Recall | Mean F1 |
|---|---|---|---|
| Gemini 1.5 Pro | $25.5 \pm 35.7\%$ | $18.0 \pm 28.4\%$ | $19.1 \pm 26.9\%$ |
| GPT-4o | **31.6**$\pm$**39.3%** | **20.1**$\pm$**28.2%** | **22.1**$\pm$**27.7%** |

F1 and recall in Brazil, India, and Vietnam, even though they are countries with a higher number of CR bird species.

### 3.4. Task 4: Threat Assessment

Neither model performs much better than a random guessing baseline when assessing threats (Table 4). For the random guessing baseline, one scope and severity option is randomly selected for each threat assessment. For scope classification, `GPT-4o` outperforms `Gemini 1.5 Pro` with an accuracy of 48.5% compared to `Gemini 1.5 Pro`'s 47.5%. In severity classification, `Gemini 1.5 Pro` shows a small advantage, with higher accuracy (28.3%) and cost-sensitive accuracy (71.7%) compared to `GPT-4o`, but both

Table 4: **Threat Classification**. Accuracy (Acc.) and cost-sensitive accuracy (CS Acc.) for the scope and severity classification predictions made by `Gemini 1.5 Pro` and `GPT-4o`.

| Model | Scope | | Severity | |
|---|---|---|---|---|
| | Acc. | CS Acc. | Acc. | CS Acc. |
| Gemini 1.5 Pro | 47.5% | 65.2% | **28.3%** | **71.7%** |
| GPT-4o | **48.5%** | **66.7%** | 22.2% | 68.7% |
| Random Baseline | 35.3% | 57.1% | 16.2% | 51.8% |

barely outperform the random baseline. Although the cost-sensitive accuracy indicates that the models often misclassify into adjacent categories, the results suggest that relying solely on zero-shot capabilities based on threat descriptions is insufficient.

The models' performance, which is only about ten percentage points higher than the random baseline, suggests that LLMs do not yet reliably perform this task. However, the cost-sensitive accuracy, which is higher for both models than the random baseline, indicates that when the models are incorrect, they tend to be closer to the correct answer than random guessing, though not substantially better. Both models tend to underestimate the scope by choosing "Minority" and tend to predict one of the medium severity options (Figure C.14).

### 3.5. Task 5: Trait Identification

`GPT-4o` consistently outperforms `Gemini 1.5 Pro` across both birds and mammals when predicting traits (Figure 10). For bird traits, `GPT-4o` achieves higher $R^2$ values and lower Normalized Mean Absolute Error (NMAE) across all four traits, indicating more accurate predictions (Figure 10). Both models show lower performance for beak length, but `Gemini 1.5 Pro` additionally has low performance for the wing length predictions. Notably, an extreme overestimate for Turkey Vulture (*Cathartes aura*), with a prediction 1000 mm too large, results in a negative $R^2$ score for wing length in `Gemini 1.5 Pro`.

For mammals, `GPT-4o` similarly outperforms `Gemini 1.5 Pro` across all four traits. Both models have the lowest metrics for max longevity prediction, with `GPT-4o` achieving an $R^2$ close to zero and `Gemini 1.5 Pro` yielding a negative $R^2$.

In terms of output validity, `GPT-4o` also demonstrates greater reliability: we observed zero invalid responses out of 400 queries, compared to nine for

Figure 10: **Trait Identification**. Comparison of predictions between `Gemini 1.5 Pro` and `GPT-4o` for four bird traits: beak length, wing length, tail length, and mass, as well as four mammals traits: adult body length, gestation length, max longevity, and adult mass. Each panel shows a scatter plot of target values versus predictions with a reference line indicating a perfect prediction. NMAE (Normalized Mean Absolute Error) and $R^2$ scores are reported for both models.

`Gemini 1.5 Pro`. Failures in `Gemini 1.5 Pro` were due to inclusion of extra details, returning value ranges rather than single estimates, or null responses. Finally, while both models tend to make similar errors for mammal traits, they diverge in their erroneous predictions for bird traits, suggesting potential

differences in model behavior across taxonomic groups (Figure C.13).

## 4. Discussion

Large language models (LLMs) show promise for addressing ecological questions but their capabilities in this domain remain largely unexplored. In this study, we evaluate two leading LLMs, `GPT-4o` and `Gemini 1.5 Pro`, across five tasks related to species traits, threat statuses, and distributions. Our aim is to test how well these models perform retrieval and reasoning tasks across a range of ecological concepts. We find that while the models often perform above simple baselines, their reliability and utility vary substantially across task type, taxonomic group, and geography. This highlights both the current potential of LLMs in ecology and the need for more targeted model development.

Model performance shows substantial variability across ecological tasks, reflecting how well each task aligns with the types of data likely encountered during LLM training. Among the tasks, the models have higher reported metrics for the presence–absence prediction, especially when species presence is assessed at the country level (Task 1b). In contrast, performance is lower for trait prediction tasks (Task 5) and further declines for range map generation (Task 2), which require precise numerical estimates and spatially coherent outputs. The inconsistency between presence–absence predictions and range map outputs highlights a lack of fine-scale geographic coherence and understanding in both models. For these two first geographic tasks, no statistically significant difference is observed between `GPT-4o` and `Gemini 1.5 Pro`. The reliability of LLMs in solving a task depends more on the structure of the task than on the model type, particularly because LLMs are pre-trained on text corpora that are likelier to contain country names and trait descriptions rather than geospatial data such as shapefiles or fine-scale distribution information.

The performance of LLMs in predicting species traits shows patterns that suggest a mix of memorization and inference. For example, when estimating traits like beak length, the models often produce values that cluster around a narrow range across species, forming horizontal bands in scatter plots. In contrast, predictions for traits such as wing length show greater variability and closer alignment with expert data. These differences may reflect cases where the model has been trained on sufficient data to memorize the pattern (e.g., for wing length), as compared to cases where the model needs to infer

the value (e.g., beak length). Traits such as beak length and wing length are governed by known allometric relationships, which the model could leverage. These patterns raise important questions about whether LLMs are capable of reasoning from ecological principles or simply reproducing associations present in their training data. While the focus of this study remains on text-based LLMs, recent advances in multi-modal models, which combine text and visual inputs, offer new possibilities. For example, such models could potentially estimate traits for individual specimens directly from photographs [48, 49].

Biases in training data present a core challenge for the application of LLMs in ecology. We observe that tasks involving classification of threats, such as scope and severity (Task 4), are especially difficult for the models, which often predict these incorrectly. This may be due to the relative rarity and complexity of such information in publicly available data. Even for human experts, such classifications are nuanced and context dependent. This underscores the need for domain-specific training or post-processing strategies that incorporate ecological expertise and structured data to support more reliable outputs.

The application of LLMs in ecology introduces ethical and environmental concerns [50]. These include the risk of amplifying existing data biases, generating plausible but false information, and misusing sensitive knowledge such as indigenous ecological practices. Furthermore, training and deploying large models consume significant computational resources and energy [51]. When tools such as databases or web searches suffice, LLMs may represent an unnecessarily costly solution. Therefore, it is essential to evaluate their utility against their environmental footprint.

Improving the ecological utility of LLMs will require a combination of domain-specific fine-tuning, expanded training data, and careful evaluation. This could include incorporating structured biodiversity data, expert assessments, and spatial information into training pipelines. As in this work, it is important that evaluation is performed across a range of diverse tasks to ensure that models do not simply overfit to only one or two focal tasks. Tasks such as the estimation of range maps could benefit from hybrid approaches that combine statistical models with LLMs. Moreover, future LLM development should be informed by the known limitations and biases in biodiversity data, particularly in underrepresented regions and taxa.

Future evaluations should also explore how prompt structure and in context learning affect performance. While our evaluation focuses on retrieval-

style questions, more complex tasks requiring ecological reasoning remain largely untested. Predicting the outcomes of ecosystem interventions or inferring missing data from phylogenetic and spatial relationships are examples of reasoning tasks that LLMs could help address. However, evaluating such capabilities requires future benchmarks that are both ecologically meaningful and computationally reproducible.

## 5. Conclusions

We have presented an initial evaluation of LLMs in the ecological domain, which highlights both their current abilities, limitations, and points to their potential in the future. The commercial models evaluated show promise for tasks that involve recalling information, such as species presence predictions and trait estimation. However, their performance drops significantly in more complex tasks, such as generating accurate range maps or producing detailed threat classifications.

While these models could assist in accelerating certain conservation-related tasks and make ecological information more accessible, their limitations suggest that they are not yet ready for direct application in biodiversity decision making. Nonetheless, our new evaluation dataset represents a valuable resource that can be used to stimulate and facilitate future research, enabling advancements in the evaluation and application of LLMs to ecological and conservation challenges. Models that are more ecologically useful are likely to improve over time as techniques and training datasets evolve. However, it is important that we direct development towards ethically sound practices. Given the urgency of the biodiversity crisis, the benchmarking tasks introduced here can catalyze efficient and focused development of tools to help accelerate better conservation decision making.

## 6. Data availability

Code and data for reproducing our experiments is available at: https://github.com/filipgdorm/eco-llm.

## 7. Author contributions: CRediT

**FD**: Conceptualization, Methodology, Software, Validation, Formal Analysis, Investigation, Data Curation, Writing - Original Draft, Visualization.

**JM**: Conceptualization, Methodology, Writing - Review & Editing. **DP**: Conceptualization, Methodology, Writing - Review & Editing. **MH**: Conceptualization, Methodology, Writing - Review & Editing. **OMA**: Conceptualization, Methodology, Resources, Writing - Review & Editing, Supervision, Project administration, Funding acquisition.

## 8. Funding Information

FD and OMA were supported by a Royal Society Research Grant. JM was funded by the Leverhulme Trust and the Isaac Newton Trust on an Early Career Fellowship.

# References

[1] A. D. Barnosky, N. Matzke, S. Tomiya, G. O. Wogan, B. Swartz, T. B. Quental, C. Marshall, J. L. McGuire, E. L. Lindsey, K. C. Maguire, et al., Has the Earth's sixth mass extinction already arrived?, Nature (2011). 2

[2] J. Hortal, F. de Bello, J. A. F. Diniz-Filho, T. M. Lewinsohn, J. M. Lobo, R. J. Ladle, Seven shortfalls that beset large-scale knowledge of biodiversity, Annual review of ecology, evolution, and systematics (2015). 2

[3] R. Cornford, J. Millard, M. González-Suárez, R. Freeman, T. F. Johnson, Automated synthesis of biodiversity knowledge requires better tools and standardised research output, Ecography 2022 (3) (2022) e06068. 2

[4] J. W. Millard, R. Freeman, T. Newbold, Text-analysis reveals taxonomic and geographic disparities in animal pollination literature, Ecography 43 (1) (2020) 44–59. 2

[5] R. A. Poldrack, T. Lu, G. Beguš, AI-assisted coding: Experiments with GPT-4, arXiv:2304.13187 (2023). 2

[6] S. Frieder, L. Pinchetti, R.-R. Griffiths, T. Salvatori, T. Lukasiewicz, P. Petersen, J. Berner, Mathematical capabilities of chatgpt, NeurIPS Datasets and Benchmarks (2023). 2

[7] I. Mirzadeh, K. Alizadeh, H. Shahrokhi, O. Tuzel, S. Bengio, M. Farajtabar, GSM-Symbolic: Understanding the Limitations of Mathematical Reasoning in Large Language Models, arXiv:2410.05229 (2024). 2

[8] K. K. Chang, M. Cramer, S. Soni, D. Bamman, Speak, memory: An archaeology of books known to chatgpt/gpt-4, arXiv:2305.00118 (2023). 2

[9] G. Team, R. Anil, S. Borgeaud, J.-B. Alayrac, J. Yu, R. Soricut, J. Schalkwyk, A. M. Dai, A. Hauth, K. Millican, et al., Gemini: a family of highly capable multimodal models, arXiv:2312.11805 (2023). 2

[10] Y. Zhang, Z. Wang, Z. He, J. Li, G. Mai, J. Lin, C. Wei, W. Yu, BB-GeoGPT: A Framework for Learning a Large Language Model for Geographic Information Science, Information Processing and Management (2024). 2

[11] J. Roberts, T. Lüddecke, R. Sheikh, K. Han, S. Albanie, Charting new territories: Exploring the geographic and geospatial capabilities of multimodal llms, in: CVPR, 2024. 2

[12] R. Tao, J. Xu, Mapping with chatgpt, ISPRS International Journal of Geo-Information (2023). 2

[13] C. Deng, T. Zhang, Z. He, Q. Chen, Y. Shi, Y. Xu, L. Fu, W. Zhang, X. Wang, C. Zhou, et al., K2: A foundation language model for geoscience knowledge understanding and utilization, in: International Conference on Web Search and Data Mining, 2024. 2

[14] R. Manvi, S. Khanna, G. Mai, M. Burke, D. Lobell, S. Ermon, Geollm: Extracting geospatial knowledge from large language models, arXiv:2310.06213 (2023). 2

[15] R. Manvi, S. Khanna, M. Burke, D. Lobell, S. Ermon, Large language models are geographically biased, arXiv:2402.02680 (2024). 2

[16] J. Roberts, T. Lüddecke, S. Das, K. Han, S. Albanie, GPT4GEO: How a Language Model Sees the World's Geography, in: NeurIPS 2023 Foundation Models for Decision Making Workshop, 2024. 2

[17] S. Sastry, X. Xing, A. Dhakal, S. Khanal, A. Ahmad, N. Jacobs, LD-SDM: Language-Driven Hierarchical Species Distribution Modeling, arXiv:2312.08334 (2023). 2

[18] M. Hamilton, C. Lange, E. Cole, A. Shepard, S. Heinrich, O. Mac Aodha, G. Van Horn, S. Maji, Combining Observational Data and Language for Species Range Estimation, in: NeurIPS, 2024. 2

[19] M. J. Elliott, J. A. Fortes, Toward Reliable Biodiversity Information Extraction From Large Language Models, in: International Conference on e-Science, 2024. 2

[20] H. Doi, T. Osawa, N. Tsutsumida, The role of large pre-trained models in ecology and biodiversity conservation: Opportunities and Challenges, Authorea Preprints (2024). 3

[21] A. V. Gougherty, H. L. Clipp, Testing the reliability of an AI-based large language model to extract ecological information from the scientific literature, npj Biodiversity (2024). 3

[22] N. Cooper, A. T. Clark, N. Lecomte, H. Qiao, A. M. Ellison, Harnessing large language models for coding, teaching and inclusion to empower research in ecology and evolution, Methods in Ecology and Evolution (2024). 3

[23] M. J. Farrell, N. Le Guillarme, L. Brierley, B. Hunter, D. Scheepens, A. Willoughby, A. Yates, N. Mideo, The changing landscape of text mining: a review of approaches for ecology and evolution, Proceedings of the Royal Society B: Biological Sciences (2024). 3

[24] J. Atuhurra, S. C. Dujohn, H. Kamigaito, H. Shindo, T. Watanabe, Distilling Named Entity Recognition Models for Endangered Species from Large Language Models, arXiv:2403.15430 (2024). 3

[25] D. Scheepens, J. Millard, M. Farrell, T. Newbold, Large language models help facilitate the automated synthesis of information on potential pest controllers, Methods in Ecology and Evolution (2024). 3

[26] F. Keck, H. Broadbent, F. Altermatt, Extracting massive ecological data on state and interactions of species using large language models, bioRxiv (2025). 3

[27] M. Mora-Cross, S. Calderon-Ramirez, Uncertainty Estimation in Large Language Models to Support Biodiversity Conservation, in: Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, 2024. 3

[28] A. Santangeli, S. Mammola, V. Nanni, S. A. Lambertucci, Large language models debunk fake and sensational wildlife news, Integrative Conservation (2024). 3

[29] A. Castro, J. Pinto, L. Reino, P. Pipek, C. Capinha, Large language models overcome the challenges of unstructured text data in ecology, bioRxiv (2024). 3

[30] OpenAI, ChatGPT, https://chatgpt.com/, Accessed: 2024-10-15. 3

[31] Google DeepMind, Gemini, https://deepmind.google/technologies/gemini/, Accessed: 2024-10-15. 3

[32] V. Domazetoski, Enhancing Ecological Knowledge Discovery Using Large Language Models, MSc Thesis (2024). 3

[33] D. Marcos, R. van de Vlasakker, I. N. Athanasiadis, P. Bonnet, H. Goeau, A. Joly, W. D. Kissling, C. Leblanc, A. S. van Proosdij, K. P. Panousis, Fully automatic extraction of morphological traits from the Web: utopia or reality?, arXiv:2409.17179 (2024). 3

[34] M. Maruf, A. Daw, K. S. Mehrab, H. B. Manogaran, A. Neog, M. Sawhney, M. Khurana, J. P. Balhoff, Y. Bakis, B. Altintas, et al., VLM4Bio: A Benchmark Dataset to Evaluate Pretrained Vision-Language Models for Trait Discovery from Biological Images, arXiv:2408.16176 (2024). 3

[35] N. Le Guillarme, W. Thuiller, TaxoNERD: deep neural models for the recognition of taxonomic entities in the ecological and evolutionary literature, Methods in Ecology and Evolution (2022). 3

[36] Google DeepMind, Gemini API Documentation, https://cloud.google.com/vertex-ai/generative-ai/docs/model-reference/inference, Accessed: 2024-10-15 (2024). 4

[37] OpenAI, GPT-4 API Documentation, https://platform.openai.com/docs/overview, Accessed: 2024-10-15. 4

[38] IUCN, The IUCN Red List of Threatened Species, version 2024-1 (2024). URL https://www.iucnredlist.org 4

[39] E. Cole, G. Van Horn, C. Lange, A. Shepard, P. Leary, P. Perona, S. Loarie, O. Mac Aodha, Spatial implicit neural representations for global-scale species mapping, in: ICML, 2023. 4, 7, 14

[40] F. Dorm, C. Lange, S. Loarie, O. Mac Aodha, Generating Binary Species Range Maps, in: Computer Vision for Ecology Workshop at ECCV, 2024. 4, 7, 14

[41] Uber Technologies, Inc., H3: A Hexagonal Hierarchical Spatial Index, https://h3geo.org, Accessed: 2024-10-15. 4

[42] IUCN, IUCN Red List - API, https://apiv3.iucnredlist.org/api/v3/docs, Accessed: 2024-10-01. 4

[43] J. A. Tobias, C. Sheard, A. L. Pigot, A. J. Devenish, J. Yang, F. Sayol, M. H. Neate-Clegg, N. Alioravainen, T. L. Weeks, R. A. Barber, et al., AVONET: morphological, ecological and geographical data for all birds, Ecology Letters (2022). 4, 11

[44] Soria, Carmen D. and Pacifici, Michela and Di Marco, Moreno and Stephen, Sarah M. and Rondinini, Carlo, Combine: a coalesced mammal database of intrinsic and extrinsic traits, Ecology (2021). 4, 11

[45] S. Seabold, J. Perktold, statsmodels: Econometric and statistical modeling with python, in: 9th Python in Science Conference, 2010. 6

[46] IUCN, Threats Classification Scheme (Version 3.3), https://www.iucnredlist.org/resources/threat-classification-scheme, Accessed: 2024-10-15 (2024). 10

[47] IUCN, IUCN - CMP Unified Classification of Direct Threats, https://nc.iucnredlist.org/redlist/content/attachment_files/Dec_2022_Guidance_Threats_Classification_Scheme.pdf, Accessed: 2024-10-15 (2022). 10

[48] Z. Fabian, Z. Miao, C. Li, Y. Zhang, Z. Liu, A. Hernández, A. Montes-Rojas, R. Escucha, L. Siabatto, A. Link, et al., Multimodal foundation models for zero-shot animal species recognition in camera trap images, arXiv:2311.01064 (2023). 20

[49] Z. Miao, Y. Zhang, Z. Fabian, A. H. Celis, S. Beery, C. Li, Z. Liu, A. Gupta, M. Nasir, W. Li, et al., New frontiers in AI for biodiversity research and conservation with multimodal language models, EcoEvoRxiv (2024). 20

[50] K.-J. Tokayev, Ethical implications of large language models a multi-dimensional exploration of societal, economic, and technical concerns, International Journal of Social Analytics (2023). 20

[51] S. Samsi, D. Zhao, J. McDonald, B. Li, A. Michaleas, M. Jones, W. Bergeron, J. Kepner, D. Tiwari, V. Gadepally, From words to watts: Benchmarking the energy costs of large language model inference, in: High Performance Extreme Computing Conference, 2023. 20

## Appendix A. Datasets

The full list of species utilized for the tasks is available in the `SPECIES.md` file within the code repository.

## Appendix B. Evaluation Metrics

**F1 Score.** The F1 score is computed in the overlap of cells between the LLM generated range map, and the expert range map.

$$F_1 = 2 \cdot \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} = \frac{\text{TP}}{\text{TP} + \frac{1}{2}(\text{FP} + \text{FN})}, \tag{B.1}$$

where TP denotes True Positives, FP False Positives, and FN False Negatives.

## Appendix C. Additional Visualizations

Figure C.11: Predicted accuracy of species presence assessments for Task 1, grouped by language model (left), taxonomic class (middle), and species' continental presence (right).

| | coef | std err | t | P> |t| | [0.025 | 0.975] |
|---|---|---|---|---|---|---|
| Intercept | 0.7025 | 0.041 | 17.038 | 0.000 | 0.621 | 0.784 |
| LLM_type[T.Gemini] | 2.22e-16 | 0.021 | 1.04e-14 | 1.000 | -0.042 | 0.042 |
| class_name[T.Aves] | -0.0350 | 0.031 | -1.129 | 0.261 | -0.096 | 0.026 |
| class_name[T.Mammalia] | 0.0047 | 0.031 | 0.153 | 0.878 | -0.056 | 0.065 |
| class_name[T.Reptilia] | 0.0506 | 0.030 | 1.658 | 0.099 | -0.010 | 0.111 |
| Africa[T.True] | 0.0064 | 0.040 | 0.161 | 0.873 | -0.072 | 0.085 |
| Americas[T.True] | 0.0331 | 0.037 | 0.898 | 0.371 | -0.040 | 0.106 |
| Asia[T.True] | 0.0059 | 0.036 | 0.162 | 0.872 | -0.066 | 0.078 |
| Europe[T.True] | -0.0711 | 0.032 | -2.208 | 0.028 | -0.135 | -0.008 |
| Oceania[T.True] | -0.0132 | 0.040 | -0.328 | 0.743 | -0.092 | 0.066 |

| | | | | |
|---|---|---|---|---|
| R-squared: | 0.078 | Omnibus: | 3.704 | Durbin-Watson: 1.048 |
| Adj. R-squared: | 0.035 | Prob(Omnibus): | 0.157 | Jarque-Bera (JB): 3.775 |
| F-statistic: | 1.796 | Skew: | -0.322 | Prob(JB): 0.151 |
| Prob (F-statistic): | 0.0714 | Kurtosis: | 2.802 | Cond. No. 9.47 |
| Log-Likelihood: | 100.41 | | | |
| AIC: | -180.8 | | | |
| BIC: | -147.8 | | | |

Table C.5: OLS Regression Results for Task 1a produced by the statsmodels package in Python.

| | coef | std err | t | P> |t| | [0.025 | 0.975] |
|---|---|---|---|---|---|---|
| Intercept | 0.9595 | 0.038 | 25.378 | 0.000 | 0.885 | 1.034 |
| LLM_type[T.Gemini] | -2.22e-16 | 0.019 | -1.14e-14 | 1.000 | -0.038 | 0.038 |
| class_name[T.Aves] | -0.0081 | 0.028 | -0.285 | 0.776 | -0.064 | 0.048 |
| class_name[T.Mammalia] | -0.0245 | 0.028 | -0.873 | 0.384 | -0.080 | 0.031 |
| class_name[T.Reptilia] | -0.0304 | 0.028 | -1.087 | 0.278 | -0.086 | 0.025 |
| Africa[T.True] | -0.1863 | 0.037 | -5.077 | 0.000 | -0.259 | -0.114 |
| Americas[T.True] | -0.0487 | 0.034 | -1.442 | 0.151 | -0.115 | 0.018 |
| Asia[T.True] | -0.1008 | 0.033 | -3.016 | 0.003 | -0.167 | -0.035 |
| Europe[T.True] | -0.1292 | 0.030 | -4.373 | 0.000 | -0.187 | -0.071 |
| Oceania[T.True] | 0.0158 | 0.037 | 0.429 | 0.668 | -0.057 | 0.088 |

| | | | | |
|---|---|---|---|---|
| R-squared: | 0.293 | Omnibus: | 32.917 | Durbin-Watson: 0.897 |
| Adj. R-squared: | 0.259 | Prob(Omnibus): | 0.000 | Jarque-Bera (JB): 50.732 |
| F-statistic: | 8.730 | Skew: | -0.914 | Prob(JB): 9.63e-12 |
| Prob (F-statistic): | 6.08e-11 | Kurtosis: | 4.657 | Cond. No. 9.47 |
| Log-Likelihood: | 117.74 | | | |
| AIC: | -215.5 | | | |
| BIC: | -182.5 | | | |

Table C.6: OLS Regression Results for Task 1b produced by the statsmodels package in Python.

Figure C.12: Predicted F1 of range maps for Task 2, grouped by language model (left), taxonomic class (middle), and species' continental presence (right).

| | coef | std err | t | P> |t| | [0.025 | 0.975] |
|---|---|---|---|---|---|---|
| Intercept | 0.1799 | 0.068 | 2.646 | 0.009 | 0.046 | 0.314 |
| LLM_type[T.Gemini] | 0.0025 | 0.034 | 0.074 | 0.941 | -0.065 | 0.070 |
| class_name[T.Aves] | 0.1120 | 0.049 | 2.278 | 0.024 | 0.015 | 0.209 |
| class_name[T.Mammalia] | 0.0616 | 0.050 | 1.242 | 0.216 | -0.036 | 0.160 |
| class_name[T.Reptilia] | -0.0436 | 0.047 | -0.923 | 0.357 | -0.137 | 0.050 |
| Africa | -0.0464 | 0.071 | -0.656 | 0.513 | -0.186 | 0.093 |
| Americas | 0.0534 | 0.062 | 0.862 | 0.390 | -0.069 | 0.176 |
| Asia | -0.0494 | 0.064 | -0.777 | 0.438 | -0.175 | 0.076 |
| Europe | 0.0274 | 0.051 | 0.538 | 0.592 | -0.073 | 0.128 |
| Oceania | 0.0811 | 0.064 | 1.268 | 0.207 | -0.045 | 0.207 |

| | | | | |
|---|---|---|---|---|
| R-squared: | 0.120 | Omnibus: | 14.339 | Durbin-Watson: 1.253 |
| Adj. R-squared: | 0.067 | Prob(Omnibus): | 0.001 | Jarque-Bera (JB): 10.418 |
| F-statistic: | 2.256 | Skew: | 0.510 | Prob(JB): 0.00547 |
| Prob (F-statistic): | 0.0215 | Kurtosis: | 2.270 | Cond. No. 10.2 |
| Log-Likelihood: | 25.216 | | | |
| AIC: | -30.43 | | | |
| BIC: | 0.2577 | | | |

Table C.7: OLS Regression Results for Task 2 produced by the statsmodels package in Python.

Figure C.13: **Task 5: Trait Identification**. Scatter plot comparing species-level errors made by GPT (x-axis) and Gemini (y-axis) in Task 5. Each point represents a species, with its coordinates indicating the average error made by each model. Points along the diagonal line (y = x) reflect species for which both models perform similarly, while deviations indicate species where one model outperforms the other. This visualization helps identify whether the models struggle with the same species or exhibit complementary strengths.

Figure C.14: **Task 4 Threat Assessment**. The confusion matrices for Gemini and GPT for the scope and severity threat assessments.